

# FCC PART 18

## MEASUREMENT AND TEST REPORT

For

**Inno light(Shanghai) Int.Co.,Ltd**

No.90 QingAn Road, QingPu Zhen Shanghai China

**FCC ID: SBZINNOS10014**

July 19, 2004

<b>This Report Concerns:</b> <input checked="" type="checkbox"/> Original Report	<b>Equipment Type:</b> Compact type fluorescent lamp with self-ballast
<b>Test Engineer:</b> Sam Lin	
<b>Report Number</b> RSH04062903	
<b>Test Date:</b> July 15, 2004	
<b>Reviewed By:</b> Chris Zheng	
<b>Prepared By:</b> Bay Area Compliance Lab Corp. ShenZhen Suite C, 41-D Electronics Science & Technology Building, No. 2070 Shennanzhong Rd ShenZhen, Guandong 518031, P.R. China Tel: 86-755- 83296449 Fax: 86-755- 83273756	

**Note:** The test report is specially limited to the above company and the product model only. It may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the US Government.

**TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>3</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	3
OBJECTIVE .....	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY .....	3
TEST FACILITY .....	3
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>4</b>
JUSTIFICATION .....	4
EQUIPMENT MODIFICATIONS .....	4
CONFIGURATION OF TEST SYSTEM .....	4
TEST SETUP BLOCK DIAGRAM.....	4
<b>CONDUCTED EMISSION.....</b>	<b>5</b>
MEASUREMENT UNCERTAINTY.....	5
EUT SETUP.....	5
SPECTRUM ANALYZER SETUP .....	6
TEST EQUIPMENT LIST AND DETAILS.....	6
TEST PROCEDURE .....	6
TEST DATA .....	6
PLOT(S) OF TEST DATA.....	7

## GENERAL INFORMATION

---

### Product Description for Equipment Under Test (EUT)

The *Inno light(Shanghai) Int.Co.,Ltd*'s model *INNO-S10-014L* or the "EUT" as referred to in this report is a *Compact type fluorescent lamp with self-ballast* which measures approximately 12.0cm L x 5.0cm W x 5.0cm H, rated input voltage: AC 120 V/60Hz.

\* The test data gathered are from production sample, serial number: 040653, provided by the manufacturer.

### Objective

The following test report is prepared on behalf of *Inno light(Shanghai) Int.Co.,Ltd* in accordance with Part 2, Subpart J, and Part 18, Subparts A, B, and C of the Federal Communication Commissions rules and regulations.

The objective is to determine compliance with FCC rules.

### Related Submittal(s)/Grant(s)

No Related Submittals.

### Test Methodology

All measurements contained in this report were conducted with MP-5, FCC Methods of Measurements of Radio Noise Emissions from ISM Equipment, February 1986. All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 Meters.

### Test Facility

Test site at Bay Area Compliance Laboratory Corporation has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2001 and FCC MP-5.

The Federal Communications Commission and Voluntary Control Council for Interference has the reports on file and is listed under FCC file 31040/SIT 1300F2 and VCCI Registration No.: C-1298 and R-1234. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION


### Justification

The EUT was tested under the normal operating conditions stated in the instructions by the manufacturer

### Equipment Modifications


The EUT samples provided were reported by the manufacturer to be unmodified production samples

### Configuration of Test System



EUT

### Test Setup Block Diagram




## CONDUCTED EMISSION

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at BACL is  $\pm 2.4$  dB.

### EUT Setup



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with MP-5 measurement procedure. The specification used was the FCC Part 18 limits.

The EUT was connected to a 120 VAC/ 60Hz power source.

## Spectrum Analyzer Setup

The spectrum analyzer was set to investigate the spectrum from 450 KHz to 30MHz.

During the conducted emission test, the spectrum analyzer was set with the following configurations:

<b>Frequency Range</b>	<b>RBW</b>	<b>Video B/W</b>
450KHz - 30MHz	10KHz	10KHz

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
COM Power	LISN	LI-200	12208	2003-10-30	2004-10-29
COM Power	LISN	LI-200	12005	2003-10-30	2004-10-29
R/S	Spectrum Analyzer	FSEM	849720/019	2003-10-30	2004-10-29
FLUKE	True RMS Multimeter	187	78540402	2004-3-23	2005-3-22

\* **Statement of Traceability:** **BACL Corp.** attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

## Test Procedure

During the conducted emission test, the EUT power cord was connected to the outlet of the LISN.

Maximizing procedure were performed on the six (6) highest emissions of the EUT.

All data was recorded in the peak detection mode.

## Test Data

Date of Test :	July 15, 2004	Temperature :	25°C
EUT :	Compact type fluorescent lamp with self-ballast	Humidity :	70%
M/N :	INNO-S10-014L	Operating Mode :	On
S/N :	040653	Test Engineer:	Sam Lin


LINE CONDUCTED EMISSIONS				FCC PART 18	
Frequency MHz	Amplitude dB $\mu$ V	Detector QP/AV/Peak	Phase Line/Neutral	Limit dB $\mu$ V	Margin dB
0.450	41.98	QP	Line	48.00	-6.02
0.453	41.78	QP	Neutral	48.00	-6.22
0.470	41.20	QP	Line	48.00	-6.80
0.481	40.81	QP	Neutral	48.00	-7.19
0.541	40.68	QP	Neutral	48.00	-7.32
0.530	40.39	QP	Line	48.00	-7.61

Test Result: Pass

## Plot(s) of Test Data


Plot(s) of Test Data is presented hereinafter as reference.

Line:



IYIEN → S10 -0.4 dB

Neutral:



IYIEN → C10 -0.1 dB