Model No.:

MA5G14DP 5GHz 14dBi Dual-Polarization CPE Antenna Module (Prelimitary)

MA5G14DP is a 14 dBi Dual Polarization Outdoor/Indoor Directional Antenna module amplifies your Outdoor WiF-N AP/Birdge wireless signal in a concentrated direction. The directional design of antenna module with 2 RF connector that creates the Vertical and Horizontal transmit/reciving at same time . MA5G14DP may amplified wireless-N (MIMO) signal that extend the coverage of a wireless local area network .

Features

■ High gain: 14.84 dBi

■ Frequency: 5.150 – 5.825GHz

Support Dual Polarization (Vertical and Horizontal)

■ Two RF Connector

■ For Wireless-n (MIMO) Application

■ Increase your Wireless Network Strength

Target Customer

- Outdoor / Indoor Wireless System Integrator
- Outdoor / Indoor Surveillance IP Camera System Provider
- Outdoor /Indoor Industrial Automation System Integrator
- Outdoor /Indoor Wireless Control System Integrator

Application

- Outdoor / Indoor long range Point to Point
- Outdoor / Indoor long range CPE / Client Bridge
- Outdoor / Indoor long range Wireless IP Video Surveillance
- Outdoor/ Indoor long range Wireless Automation and Control


Specifications			
Antenna Type	Indoor/Outdoor Patch Directional Antenna		
Gain	14.8 dBi @ 5.470 - 5.825GHz (H-Plan)		
	13.53 dBi @ 5.470 – 5.825GHz (E-Plan)		
	12.6 dBi @ 5.150-5.825GHz(H-Plan)		
	11 dBi @5.150-5.825GHz(E-Plan)		
Frequency Range	5.150 ~ 5.825GHz		
Network Specification	IEEE 802.11a, IEEE802.11n Wireless 5 GHz Network		
V.S.W.R	< 2		
Beam Width-H Plane	35°		
Beam Width-E Plane	20°		
Polarization	Vertical (Linear)		
Input Impedance	50 Ohms		
RF Cable Connector	IPEX Connector with 13.5 cm RGB RF Cable		
Operation Temperature	-20°C - + 70°C		
Storage Temperature	-30°C - +85°C		
Humidity	95% maximum (non-condensing)		

Package Content			
High-Gain Wireless Antenna Module with 2 * RF Cable	1 Set		
with IPEX Connector			
Quick Installation Guide	1 pc		

Antenna test: Polarization 1



7f8 ln120 neihu rd sec1 taipei, taiwan r.o.c. tel:+886-2-26594900 fax:+886-2-26594833 http://www.audix.com



Center Frequency: 4900 MHz Trace: V-Plan

:site

Site


V-Plan :Avg:2.63dBi,Max:356.0deg 11.08dBi,Min:175.0deg -19.15dBi

EUT model :IN5G14P-A(middle)

Temp./Humid.:25/65 Operator :Brian



7f8 lnl 20 neihu rd secl taipei, taiwan roc. tel:+886-2-26594900 fax:+886-2-26594833 http://www.audix.com




Site:site

∀-Plan :Avg:2.65dBi,Max:6.0deg 11.08dBi,Min:196.0deg -18.79dBi

EUT model :IN5G14P-A(middle)



File: C:/Documents and Settings\sky_wang\Desktop\a1\Project\泰鉅秦鉅20091103\Antenna Data: 638



Azimuth (deg)

Center Frequency: 5100 MHz Trace: V-Plan

Site :site


V-Plan :Avg:2.99dBi,Max:359.0deg 11.32dBi,Min:130.0deg -16.43dBi

EUT model :IN5G14P-A(middle)

Temp./Humid.:25/65 Operator :Brian



7f8 ln120 neihu rd sec1 taipei, taiwan r.o.c. tel:+886-2-26594900 fax:+886-2-26594833 http://www.audix.com




Azimuth (deg)

Site :site

:Avg:4.03dBi,Max:5.0deg 12.44dBi,Min:162.0deg -18.68dBi V-Plan

EUT model :IN5G14P-A(middle)





Center Frequency: 5300 MHz Trace: V-Plan

Site :site

:Avg:3.65dBi,Max:356.0deg 12.24dBi,Min:178.0deg -19.71dBi V-Plan


EUT model :IN5G14P-A(middle)

Temp./Humid.:25/65 **Operator** :Brian



7f8 ln120 neihu rd sec1 taipei, taiwan r.o.c. tel:+886-2-26594900 fax:+886-2-26594833 http://www.audix.com

Data: 641 File: C:Documents and Settings\sky_wang\Desktop\a1\Project\秦鉅秦鉅20091103\Antenna



Center Frequency: 5400 MHz Trace: V-Plan : site


Azimuth (deg)

Site

V-Plan :Avg:3.91dBi,Max:6.0deg 12.61dBi,Min:198.0deg -17.62dBi

:IN5G14P-A(middle) EUT model

File: C:/Documents and Settings\sky_wang\Desktop\a1\Project\秦鉅秦鉅20091103\Antenna



Site :site


V-Plan :Avg:4.91dBi,Max:357.0deg 13.71dBi,Min:132.0deg -16.77dBi


EUT model :IN5G14P-A(middle)

Temp./Humid.:25/65 Operator 0 :Brian



7f8 ln120 neihu rd sec1 taipei, taiwan r.o.c. tel:+886-2-26594900 fax:+886-2-26594833 http://www.audix.com





Center Frequency: 5600 MHz Trace: V-Plan


180 Azimuth (deg)

Site

V-Plan :Avg:5.73dBi,Max:6.0deg 14.67dBi,Min:168.0deg -16.99dBi

EUT model :IN5G14P-A(middle)

File: C:/Documents and Settings\sky_wang\Desktop\a1\Project\秦鉅\秦鉅20091103\Antenna



Center Frequency: 5700 MHz Trace: V-Plan

:site


Site


:Avg:5.93dBi,Max:358.0deg 14.84dBi,Min:209.0deg -15.43dBi V-Plan

:IN5G14P-A(middle) EUT model

Temp./Humid.:25/65 Operator (:Brian

7f8 lnl 20 neihu rd secl taipei, taiwan r.o.c. tel:+886-2-26594900 fax:+886-2-26594833 http://www.audix.com






Center Frequency: 5800 MHz Trace: V-Plan

Azimuth (deg)

Site :site

V-Plan :Avg:5.51dBi,Max:6.0deg 14.38dBi,Min:163.0deg -11.52dBi

EUT model :IN5G14P-A(middle)




Polarization 2



:Brian

Operator


7f8 ln120 neihu rd sec taipei, taiwan r.o.c. tel:+886-2-26594900 fax:+886-2-26594833 http://www.audix.com



V-Plan :Avg:1.23dBi,Max:342.0deg 6.63dBi,Min:132.0deg -17.10dBi

EUT model : IN5G14P-A(onder)

File: C:Documents and Settings\sky_wang\Desktop\a1\Project\秦鉅秦鉅20091103\Antenna



Center Frequency: 5000 MHz Trace: V-Plan

Azimuth (deg)

Site :site


:Avg:1.44dBi,Max:18.0deg 7.75dBi,Min:191.0deg -17.69dBi V-Plan


EUT model :IN5G14P-A(onder)

Temp./Humid.:25/65 Operator :Brian



7f8 lnl 20 neihu rd secl taipei, taiwan r.o.c. tel:+886-2-26594900 fax:+886-2-26594833 http://www.audix.com






Center Frequency: 5100 MHz Trace: V-Plan

:Avg:1.28dBi,Max:349.0deg 8.07dBi,Min:166.0deg -16.82dBi

EUT model :IN5G14P-A(onder)

Temp./Humid.:25/65 Operator :Brian

Site V-Plan



Center Frequency: 5200 MHz Trace: V-Plan

Azimuth (deg)


Site :site

V-Plan :Avg:1.29dBi,Max:8.0deg 9.14dBi,Min:158.0deg -16.04dBi

EUT model :IN5G14P-A(onder)

Temp./Humid.:25/65 Operator :Brian


7f8 ln120 neihu rd sec1 taipei, taiwan r.o.c. tel:+886-2-26594900 fax:+886-2-26594833 http://www.audix.com



Site

:Avg:0.99dBi,Max:358.0deg 9.90dBi,Min:125.0deg -15.41dBi V-Plan

:IN5G14P-A(onder) EUT model



Center Frequency: 5400 MHz Trace: V-Plan

Site :site


:Avg:1.03dBi,Max:0.0deg 10.59dBi,Min:237.0deg -15.39dBi V-Plan

:IN5G14P-A(onder) EUT model

Temp./Humid.:25/65 Operator :Brian



7f8 lnl 20 neihu rd secl taipei, taiwan r.o.c. tel:+886-2-26594900 fax:+886-2-26594833 http://www.audix.com




Center Frequency: 5500 MHz Trace: V-Plan

:site Site

V-Plan :Avg:2.23dBi,Max:0.0deg 12.18dBi,Min:24.0deg -13.75dBi

EUT model :IN5G14P-A(onder)

File: C:Documents and Settings\sky_wang\Desktop\a1\Project\秦鉅\秦鉅20091103\Antenna



Center Frequency: 5600 MHz Trace: V-Plan


Site :site

V-Plan :Avg:3.28dBi,Max:0.0deg 13.40dBi,Min:140.0deg -18.06dBi

EUT model :IN5G14P-A(onder)

Temp./Humid.:25/65 Operator

7f8 lnl 20 neihu rd secl taipei, taiwan r.o.c. tel:+886-2-26594900 fax:+886-2-26594833 http://www.audix.com



Center Frequency: 5700 MHz Trace: V-Plan


Site :site

V-Plan :Avg:3.60dBi,Max:2.0deg 13.53dBi,Min:124.0deg -17.04dBi

EUT model :IN5G14P-A(onder)

Temp./Humid.:25/65 Operator

File: C::Documents and Settings\sky_wang\Desktop\a1\Project\秦鉅\秦鉅20091103\Antenna Data: 656



:Avg:3.14dBi,Max:359.0deg 12.43dBi,Min:128.0deg -12.33dBi

Center Frequency: 5800 MHz Trace: V-Plan


:site

EUT model :IN5G14P-A(onder)

Temp./Humid.:25/65 Operator :Brian

Site ∀-Plan

> 7f8 lnl 20 neiku rd secl taipei, taiwan r.o.c. tel:+686-2-26594900 fax:+886-2-26594833 http://www.audix.com



:site Site

:Avg:2.45dBi,Max:4.0deg 10.96dBi,Min:240.0deg -10.75dBi V-Plan

EUT model : IN5G14P-A(onder)