



RF EXPOSURE REPORT

Applicant	:	BYD Auto Industry Company Limited
Address of Applicant	:	No.3001, 3007, HengPing Road, Pingshan, Shenzhen, Guangdong, P.R. China
Manufacturer	:	BYD Auto Industry Company Limited
Address of Manufacturer	:	No.3001, 3007, HengPing Road, Pingshan, Shenzhen, Guangdong, P.R. China
Equipment under Test	:	In-vehicle Multimedia Host
Model No.	:	MTCJ06-A03
FCC ID	:	SD4- MTCJ06-A03
Test Standard(s)	:	KDB447498 D01 General RF Exposure Guidance v06
Report No.	:	DDT-RE24122405-5E05
Issue Date	:	2025/03/08
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

Table of Contents

1. General Test Information.....5

1.1. Description of EUT5

1.2. Accessories of EUT5

1.3. Test laboratory6

2. RF Exposure evaluation for FCC.....7

2.1. Assessment procedure.....7

2.2. Assess result.....8

Test Report Declare

Applicant	:	BYD Auto Industry Company Limited
Address of Applicant	:	No.3001, 3007, HengPing Road, Pingshan, Shenzhen, Guangdong, P.R. China
Equipment under Test	:	In-vehicle Multimedia Host
Model No.	:	MTCJ06-A03
Manufacturer	:	BYD Auto Industry Company Limited
Address of Manufacturer	:	No.3001, 3007, HengPing Road, Pingshan, Shenzhen, Guangdong, P.R. China

Test Standard Used:

KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE24122405-5E05		
Date of Receipt:	2025/01/03	Date of Test:	2025/01/03 - 2025/03/07

Created: Jacky Huang	Reviewed: Ella Gong	Approved: Damon Hu
		
2025/03/17	2025/03/17	2025/03/17

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Version	Revision Content	Issue Date	Approved
---	Initial issue	2025/03/17	

1. General Test Information

1.1. Description of EUT

EUT Name	: In-vehicle Multimedia Host
Model Number	: MTCJ06-A03
EUT Function Description	: Please reference user manual of this device
Power Supply	: DC 12V
Radio Technology	: IEEE 802.11b/g/a/n/ac/ax
Operation frequency	: 2402 MHz-2480MHz 2412MHz-2472MHz 5180 MHz to 5825 MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax: OFDM, OFDMA (1024QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Type	: External PCB antenna
Max Antenna Gain (dBi)	: Bluetooth: 3.16 2.4G WIFI antenna 1: 3.16 5G WIFI antenna 1: U-NII-1: 5180 MHz to 5240 MHz: 1.63 U-NII-2A: 5260 MHz to 5320 MHz: 1.17 U-NII-2C: 5500 MHz to 5720 MHz: 1.83 U-NII-3: 5745 MHz to 5825 MHz: 1.89 2.4G WIFI antenna 2: 3.16 5G WIFI antenna 2: U-NII-1: 5180 MHz to 5240 MHz: 1.63 U-NII-2A: 5260 MHz to 5320 MHz: 1.17 U-NII-2C: 5500 MHz to 5720 MHz: 1.83 U-NII-3: 5745 MHz to 5825 MHz: 1.89

Note: This product does not support beamforming, TPC and MIMO. The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual.

1.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
Connecting cable	N/A	N/A	length: 2.0m, unshielded
Bluetooth/WIFI antenna	N/A	N/A	length: 1.80m, shielded
FM/AM antenna	N/A	N/A	length: 3.15m, shielded
GNSS antenna	N/A	N/A	length: 2.0m, shielded

1.3. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20240, G-20118

2. RF Exposure evaluation for FCC

2.1. Assessment procedure

Requirement:

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time $ E ^2$, $ H ^2$ or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100000			1.0	30

Note: f= frequency in MHz; *Plane-wave equivalent power density

Calculation method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d}$$

$$\text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2 m, as well as the gain of the used antenna, the RF power density can be obtained.

2.2. Assess result

Mode	Output power (dBm)	tune up power (dBm)	tune up power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm ²)	MPE Limit (mW/cm ²)
BR/EDR	11.90	13.00	19.95	3.16	2.07	0.008	1
BLE	2.82	4.00	2.51	3.16	2.07	0.001	1
2.4 G WIFI	13.91	14.00	25.12	3.16	2.07	0.010	1
5G WIFI band1	15.20	16.00	39.81	1.63	1.46	0.012	1
5G WIFI band2	14.64	16.00	39.81	1.17	1.31	0.010	1
5G WIFI band3	15.11	16.00	39.81	1.83	1.52	0.012	1
5G WIFI band4	16.24	17.00	50.12	1.89	1.55	0.015	1

Note 1: The estimation distance is 20 cm

Note 2: The EUT cannot support simultaneous emission.

Conclusion: MPE evaluation required since transmitter power is below FCC threshold

-----End Report-----