

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-23

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT1 AX80 TX 5530MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G 5G\166

Memo:

Sample Number:S24122405-001 Power Setting:8

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5427.144	46.02	33.05	5.46	-29.60	54.93	74.00	19.07	PK	Vertical
2	5460.000	41.26	33.00	5.48	-29.60	50.14	68.20	18.06	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5427.144	38.48	33.05	5.46	47.39	54.0	6.61	AV	Vertical	
2	5460.000	38.83	33.00	5.48	47.71	54.0	6.29	AV	Vertical	

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-23

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT1 AX80 TX 5610MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G 5G\167

Memo:

Sample Number:S24122405-001 Power Setting:8

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.000	41.78	33.75	5.66	-29.60	51.59	68.20	16.61	PK	Horizontal
2	5734.250	45.17	33.81	5.66	-29.60	55.04	68.20	13.16	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-23

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT1 AX80 TX 5610MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G 5G\168

Memo:

Sample Number:S24122405-001 Power Setting:8

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.000	42.08	33.75	5.66	-29.60	51.89	68.20	16.31	PK	Vertical
2	5731.300	44.96	33.79	5.66	-29.60	54.81	68.20	13.39	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-23

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT2 AX80 TX 5610MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G 5G\169

Memo:

Sample Number:S24122405-001 Power Setting:8

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.000	41.76	33.75	5.66	-29.60	51.57	68.20	16.63	PK	Horizontal
2	5737.650	44.41	33.83	5.67	-29.60	54.31	68.20	13.89	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-23

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT2 AX80 TX 5610MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G 5G\170

Memo:

Sample Number:S24122405-001 Power Setting:8

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.000	41.63	33.75	5.66	-29.60	51.44	68.20	16.76	PK	Vertical
2	5727.825	45.73	33.77	5.66	-29.60	55.56	68.20	12.64	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-20

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT1 RU0 AX20 TX 5180MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G RU\5

Memo:

Sample Number:S24122405-001 Power Setting:9

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5142.680	44.35	33.40	5.27	-29.60	53.42	74.00	20.58	PK	Horizontal
2	5150.000	42.04	33.40	5.28	-29.60	51.12	68.20	17.08	PK	Horizontal

Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5142.680	38.27	33.40	5.27	47.34	54.0	6.66	AV	Horizontal	
2	5150.000	38.67	33.40	5.28	47.75	54.0	6.25	AV	Horizontal	

- Note:
- 1. Level = Reading + Cable loss + Antenna Factor + AMP
 - 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 - 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-20

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT1 RU0 AX20 TX 5180MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G RU\6

Memo:

Sample Number:S24122405-001 Power Setting:9

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5142.960	44.68	33.40	5.27	-29.60	53.75	74.00	20.25	PK	Vertical
2	5150.000	40.83	33.40	5.28	-29.60	49.91	68.20	18.29	PK	Vertical

Data List									
NO .	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5142.960	38.67	33.40	5.27	47.74	54.0	6.26	AV	Vertical
2	5150.000	38.37	33.40	5.28	47.45	54.0	6.55	AV	Vertical

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-20

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT2 RU0 AX20 TX 5180MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G RU\7

Memo:

Sample Number:S24122405-001 Power Setting:9

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5135.310	44.39	33.40	5.27	-29.60	53.46	74.00	20.54	PK	Horizontal
2	5150.000	41.86	33.40	5.28	-29.60	50.94	68.20	17.26	PK	Horizontal

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5135.310	38.48	33.40	5.27	47.55	54.0	6.45	AV	Horizontal	
2	5150.000	38.59	33.40	5.28	47.67	54.0	6.33	AV	Horizontal	

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-20

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT2 RU0 AX20 TX 5180MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G RU\8

Memo:

Sample Number:S24122405-001 Power Setting:9

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5126.770	45.08	33.40	5.26	-29.60	54.14	74.00	19.86	PK	Vertical
2	5150.000	42.86	33.40	5.28	-29.60	51.94	68.20	16.26	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5126.770	38.29	33.40	5.26	47.35	54.0	6.65	AV	Vertical	
2	5150.000	38.47	33.40	5.28	47.55	54.0	6.45	AV	Vertical	

- Note:
- 1. Level = Reading + Cable loss + Antenna Factor + AMP
 - 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 - 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:2025-01-20

Tested By:Zhong Nan

EUT:In-vehicle Multimedia Host

Model Number:MTCJ06-A03

Test Mode:ANT1 RU8 AX20 TX 5320MHz Mode

Power Supply:DC 12V


Condition:Temp:23°C;Humi:59.5%

Test Site:DDT 3# Chamber

File Path:d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G RU\9

Memo:Sample Number:S24122405-001 Power Setting:9

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	41.19	33.10	5.41	-29.60	50.10	68.20	18.10	PK	Horizontal
2	5365.440	44.62	33.10	5.42	-29.60	53.54	74.00	20.46	PK	Horizontal

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5350.000	38.29	33.10	5.41	47.20	54.0	6.80	AV	Horizontal	
2	5365.440	38.74	33.10	5.42	47.66	54.0	6.34	AV	Horizontal	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-20

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT1 RU8 AX20 TX 5320MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G RU\10

Memo:

Sample Number:S24122405-001 Power Setting:9

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	42.03	33.10	5.41	-29.60	50.94	68.20	17.26	PK	Vertical
2	5353.500	44.87	33.10	5.41	-29.60	53.78	74.00	20.22	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5350.000	38.67	33.10	5.41	47.58	54.0	6.42	AV	Vertical	
2	5353.500	38.29	33.10	5.41	47.20	54.0	6.80	AV	Vertical	

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-20

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT2 RU8 AX20 TX 5320MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G RU\11

Memo:

Sample Number:S24122405-001 Power Setting:9

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	41.91	33.10	5.41	-29.60	50.82	68.20	17.38	PK	Horizontal
2	5360.160	44.60	33.10	5.42	-29.60	53.52	74.00	20.48	PK	Horizontal

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5350.000	38.91	33.10	5.41	47.82	54.0	6.18	AV	Horizontal	
2	5360.160	38.35	33.10	5.42	47.27	54.0	6.73	AV	Horizontal	

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-01-20 Tested By: Zhong Nan
EUT: In-vehicle Multimedia Host Model Number: MTCJ06-A03
Test Mode: ANT2 RU8 AX20 TX 5320MHz Mode Power Supply: DC 12V
Condition: Temp:23°C;Humi:59.5% Test Site: DDT 3# Chamber
File Path: d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G RU\12
Memo: Sample Number:S24122405-001 Power Setting:9

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	41.70	33.10	5.41	-29.60	50.61	68.20	17.59	PK	Vertical
2	5360.630	44.81	33.10	5.42	-29.60	53.73	74.00	20.27	PK	Vertical

Data List									
NO .	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	38.29	33.10	5.41	47.20	54.0	6.80	AV	Vertical
2	5360.630	38.11	33.10	5.42	47.03	54.0	6.97	AV	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-20

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT2 RU0 AX20 TX 5500MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G RU\13

Memo:

Sample Number:S24122405-001 Power Setting:9

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5423.036	44.26	33.05	5.46	-29.60	53.17	74.00	20.83	PK	Horizontal
2	5460.000	42.07	33.00	5.48	-29.60	50.95	68.20	17.25	PK	Horizontal

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5423.036	38.28	33.05	5.46	47.19	54.0	6.81	AV	Horizontal	
2	5460.000	38.59	33.00	5.48	47.47	54.0	6.53	AV	Horizontal	

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-20

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT2 RU0 AX20 TX 5500MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G RU\14

Memo:

Sample Number:S24122405-001 Power Setting:9

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5420.813	44.41	33.06	5.46	-29.60	53.33	74.00	20.67	PK	Vertical
2	5460.000	41.77	33.00	5.48	-29.60	50.65	68.20	17.55	PK	Vertical

Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5420.813	38.51	33.06	5.46	47.43	54.0	6.57	AV	Vertical	
2	5460.000	38.36	33.00	5.48	47.24	54.0	6.76	AV	Vertical	

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-20

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT1 RU0 AX20 TX 5500MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G RU\15

Memo:

Sample Number:S24122405-001 Power Setting:9

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5439.455	44.50	33.02	5.47	-29.60	53.39	74.00	20.61	PK	Horizontal
2	5460.000	41.12	33.00	5.48	-29.60	50.00	68.20	18.20	PK	Horizontal

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5439.455	38.71	33.02	5.47	47.60	54.0	6.40	AV	Horizontal	
2	5460.000	38.65	33.00	5.48	47.53	54.0	6.47	AV	Horizontal	

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-01-20 Tested By: Zhong Nan
EUT: In-vehicle Multimedia Host Model Number: MTCJ06-A03
Test Mode: ANT1 RU0 AX20 TX 5500MHz Mode Power Supply: DC 12V
Condition: Temp:23°C;Humi:59.5% Test Site: DDT 3# Chamber
File Path: d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G RU\16
Memo: Sample Number:S24122405-001 Power Setting:9

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5447.554	44.41	33.00	5.48	-29.60	53.29	74.00	20.71	PK	Vertical
2	5460.000	42.44	33.00	5.48	-29.60	51.32	68.20	16.88	PK	Vertical


Data List									
NO .	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5447.554	38.49	33.00	5.48	47.37	54.0	6.63	AV	Vertical
2	5460.000	38.26	33.00	5.48	47.14	54.0	6.86	AV	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-01-20 Tested By: Zhong Nan
EUT: In-vehicle Multimedia Host Model Number: MTCJ06-A03
Test Mode: ANT1 RU8 AX20 TX 5700MHz Mode Power Supply: DC 12V
Condition: Temp:23°C;Humi:59.5% Test Site: DDT 3# Chamber
File Path: d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G RU\17
Memo: Sample Number:S24122405-001 Power Setting:9

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.000	42.54	33.75	5.66	-29.60	52.35	68.20	15.85	PK	Horizontal
2	5740.753	44.11	33.84	5.67	-29.60	54.02	68.20	14.18	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-20

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT1 RU8 AX20 TX 5700MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G RU\18

Memo:

Sample Number:S24122405-001 Power Setting:9

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.000	41.21	33.75	5.66	-29.60	51.02	68.20	17.18	PK	Vertical
2	5733.487	44.03	33.80	5.66	-29.60	53.89	68.20	14.31	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-20

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT2 RU8 AX20 TX 5700MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G RU\19

Memo:

Sample Number:S24122405-001 Power Setting:9

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.000	41.26	33.75	5.66	-29.60	51.07	68.20	17.13	PK	Horizontal
2	5732.605	43.93	33.80	5.66	-29.60	53.79	68.20	14.41	PK	Horizontal

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-01-20 Tested By: Zhong Nan
EUT: In-vehicle Multimedia Host Model Number: MTCJ06-A03
Test Mode: ANT2 RU8 AX20 TX 5700MHz Mode Power Supply: DC 12V
Condition: Temp:23°C;Humi:59.5% Test Site: DDT 3# Chamber
File Path: d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G RU\20
Memo: Sample Number:S24122405-001 Power Setting:9

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.000	41.01	33.75	5.66	-29.60	50.82	68.20	17.38	PK	Vertical
2	5738.716	43.87	33.83	5.67	-29.60	53.77	68.20	14.43	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-24

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT1 11A TX 5720MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\1

Memo:

Sample Number:S24122405-001 Power Setting:13

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5462.780	44.23	33.00	5.49	-29.60	53.12	68.20	15.08	PK	Horizontal
2	5470.000	42.09	33.00	5.49	-29.60	50.98	68.20	17.22	PK	Horizontal
3	5850.000	42.39	34.00	5.74	-29.60	52.53	68.20	15.67	PK	Horizontal
4	5876.735	44.84	34.05	5.76	-29.60	55.05	68.20	13.15	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:2025-01-24

Tested By:Zhong Nan

EUT:In-vehicle Multimedia Host

Model Number:MTCJ06-A03

Test Mode:ANT1 11A TX 5720MHz Mode

Power Supply:DC 12V


Condition:Temp:23°C;Humi:59.5%

Test Site:DDT 3# Chamber

File Path:d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\2

Memo:Sample Number:S24122405-001 Power Setting:13

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5465.615	44.32	33.00	5.49	-29.60	53.21	68.20	14.99	PK	Vertical
2	5470.000	42.26	33.00	5.49	-29.60	51.15	68.20	17.05	PK	Vertical
3	5850.000	43.28	34.00	5.74	-29.60	53.42	68.20	14.78	PK	Vertical
4	5868.275	44.80	34.04	5.75	-29.60	54.99	68.20	13.21	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:2025-01-24

Tested By:Zhong Nan

EUT:In-vehicle Multimedia Host

Model Number:MTCJ06-A03

Test Mode:ANT2 11A TX 5720MHz Mode

Power Supply:DC 12V


Condition:Temp:23°C;Humi:59.5%

Test Site:DDT 3# Chamber

File Path:d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\3

Memo:Sample Number:S24122405-001 Power Setting:13

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5466.920	45.60	33.00	5.49	-29.60	54.49	68.20	13.71	PK	Horizontal
2	5470.000	41.87	33.00	5.49	-29.60	50.76	68.20	17.44	PK	Horizontal
3	5850.000	41.28	34.00	5.74	-29.60	51.42	68.20	16.78	PK	Horizontal
4	5868.140	44.71	34.04	5.75	-29.60	54.90	68.20	13.30	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:2025-01-24

Tested By:Zhong Nan

EUT:In-vehicle Multimedia Host

Model Number:MTCJ06-A03

Test Mode:ANT2 11A TX 5720MHz Mode

Power Supply:DC 12V


Condition:Temp:23°C;Humi:59.5%

Test Site:DDT 3# Chamber

File Path:d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\4

Memo:Sample Number:S24122405-001 Power Setting:13

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5455.175	45.10	33.00	5.48	-29.60	53.98	74.00	20.02	PK	Vertical
2	5470.000	44.27	33.00	5.49	-29.60	53.16	68.20	15.04	PK	Vertical
3	5850.000	41.63	34.00	5.74	-29.60	51.77	68.20	16.43	PK	Vertical
4	5876.150	44.78	34.05	5.76	-29.60	54.99	68.20	13.21	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-24

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT2 N20 TX 5720MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\5

Memo:

Sample Number:S24122405-001 Power Setting:10

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5454.860	44.49	33.00	5.48	-29.60	53.37	74.00	20.63	PK	Horizontal
2	5470.000	41.27	33.00	5.49	-29.60	50.16	68.20	18.04	PK	Horizontal
3	5850.000	42.52	34.00	5.74	-29.60	52.66	68.20	15.54	PK	Horizontal
4	5858.825	45.13	34.02	5.75	-29.60	55.30	68.20	12.90	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-24

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT2 N20 TX 5720MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\6

Memo:

Sample Number:S24122405-001 Power Setting:10

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5465.120	44.50	33.00	5.49	-29.60	53.39	68.20	14.81	PK	Vertical
2	5470.000	42.12	33.00	5.49	-29.60	51.01	68.20	17.19	PK	Vertical
3	5850.000	43.08	34.00	5.74	-29.60	53.22	68.20	14.98	PK	Vertical
4	5853.110	44.58	34.01	5.74	-29.60	54.73	68.20	13.47	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:2025-01-24

Tested By:Zhong Nan

EUT:In-vehicle Multimedia Host

Model Number:MTCJ06-A03

Test Mode:ANT1 N20 TX 5720MHz Mode

Power Supply:DC 12V


Condition:Temp:23°C;Humi:59.5%

Test Site:DDT 3# Chamber

File Path:d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\7

Memo:Sample Number:S24122405-001 Power Setting:10

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5457.785	45.67	33.00	5.48	-29.60	54.55	74.00	19.45	PK	Horizontal
2	5470.000	42.68	33.00	5.49	-29.60	51.57	68.20	16.63	PK	Horizontal
3	5850.000	42.69	34.00	5.74	-29.60	52.83	68.20	15.37	PK	Horizontal
4	5876.960	44.21	34.05	5.76	-29.60	54.42	68.20	13.78	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-24

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT1 N20 TX 5720MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\8

Memo:

Sample Number:S24122405-001 Power Setting:10

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5457.740	45.83	33.00	5.48	-29.60	54.71	74.00	19.29	PK	Vertical
2	5470.000	41.76	33.00	5.49	-29.60	50.65	68.20	17.55	PK	Vertical
3	5850.000	42.60	34.00	5.74	-29.60	52.74	68.20	15.46	PK	Vertical
4	5864.405	45.82	34.03	5.75	-29.60	56.00	68.20	12.20	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-24

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT1 N40 TX 5710MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\9

Memo:

Sample Number:S24122405-001 Power Setting:10

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5450.675	45.51	33.00	5.48	-29.60	54.39	74.00	19.61	PK	Horizontal
2	5470.000	43.66	33.00	5.49	-29.60	52.55	68.20	15.65	PK	Horizontal
3	5850.000	42.56	34.00	5.74	-29.60	52.70	68.20	15.50	PK	Horizontal
4	5865.125	44.75	34.03	5.75	-29.60	54.93	68.20	13.27	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-24

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT1 N40 TX 5710MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\10

Memo:

Sample Number:S24122405-001 Power Setting:10

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5461.115	45.07	33.00	5.48	-29.60	53.95	68.20	14.25	PK	Vertical
2	5470.000	41.37	33.00	5.49	-29.60	50.26	68.20	17.94	PK	Vertical
3	5850.000	42.45	34.00	5.74	-29.60	52.59	68.20	15.61	PK	Vertical
4	5873.900	45.00	34.05	5.76	-29.60	55.21	68.20	12.99	PK	Vertical

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-01-24 Tested By: Zhong Nan
EUT: In-vehicle Multimedia Host Model Number: MTCJ06-A03
Test Mode: ANT2 N40 TX 5710MHz Mode Power Supply: DC 12V
Condition: Temp:23°C;Humi:59.5% Test Site: DDT 3# Chamber
File Path: d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\11
Memo: Sample Number:S24122405-001 Power Setting:10

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5456.165	44.51	33.00	5.48	-29.60	53.39	74.00	20.61	PK	Horizontal
2	5470.000	42.76	33.00	5.49	-29.60	51.65	68.20	16.55	PK	Horizontal
3	5850.000	43.38	34.00	5.74	-29.60	53.52	68.20	14.68	PK	Horizontal
4	5869.625	45.48	34.04	5.75	-29.60	55.67	68.20	12.53	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-24

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT2 N40 TX 5710MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\12

Memo:

Sample Number:S24122405-001 Power Setting:10

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5466.605	44.79	33.00	5.49	-29.60	53.68	68.20	14.52	PK	Vertical
2	5470.000	42.26	33.00	5.49	-29.60	51.15	68.20	17.05	PK	Vertical
3	5850.000	43.03	34.00	5.74	-29.60	53.17	68.20	15.03	PK	Vertical
4	5879.570	45.50	34.06	5.76	-29.60	55.72	68.20	12.48	PK	Vertical

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-24

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT1 AC20 TX 5720MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\13

Memo:

Sample Number:S24122405-001 Power Setting:12

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5461.610	44.50	33.00	5.48	-29.60	53.38	68.20	14.82	PK	Horizontal
2	5470.000	41.66	33.00	5.49	-29.60	50.55	68.20	17.65	PK	Horizontal
3	5850.000	41.94	34.00	5.74	-29.60	52.08	68.20	16.12	PK	Horizontal
4	5883.215	44.39	34.07	5.76	-29.60	54.62	68.20	13.58	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-24

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT1 AC20 TX 5720MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\14

Memo:

Sample Number:S24122405-001 Power Setting:12

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5461.475	44.67	33.00	5.48	-29.60	53.55	68.20	14.65	PK	Vertical
2	5470.000	42.25	33.00	5.49	-29.60	51.14	68.20	17.06	PK	Vertical
3	5850.000	43.28	34.00	5.74	-29.60	53.42	68.20	14.78	PK	Vertical
4	5882.090	45.22	34.06	5.76	-29.60	55.44	68.20	12.76	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-01-24 Tested By: Zhong Nan
EUT: In-vehicle Multimedia Host Model Number: MTCJ06-A03
Test Mode: ANT2 AC20 TX 5720MHz Mode Power Supply: DC 12V
Condition: Temp:23°C;Humi:59.5% Test Site: DDT 3# Chamber
File Path: d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\15
Memo: Sample Number:S24122405-001 Power Setting:12

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5454.230	45.21	33.00	5.48	-29.60	54.09	74.00	19.91	PK	Horizontal
2	5470.000	41.43	33.00	5.49	-29.60	50.32	68.20	17.88	PK	Horizontal
3	5850.000	41.14	34.00	5.74	-29.60	51.28	68.20	16.92	PK	Horizontal
4	5867.825	45.43	34.04	5.75	-29.60	55.62	68.20	12.58	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-24

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT2 AC20 TX 5720MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\16

Memo:

Sample Number:S24122405-001 Power Setting:12

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5455.355	44.92	33.00	5.48	-29.60	53.80	74.00	20.20	PK	Vertical
2	5470.000	43.19	33.00	5.49	-29.60	52.08	68.20	16.12	PK	Vertical
3	5850.000	41.37	34.00	5.74	-29.60	51.51	68.20	16.69	PK	Vertical
4	5892.575	45.25	34.09	5.77	-29.60	55.51	68.20	12.69	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-24

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT2 AC40 TX 5710MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\17

Memo:

Sample Number:S24122405-001 Power Setting:12

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5462.915	44.63	33.00	5.49	-29.60	53.52	68.20	14.68	PK	Horizontal
2	5470.000	42.04	33.00	5.49	-29.60	50.93	68.20	17.27	PK	Horizontal
3	5850.000	41.27	34.00	5.74	-29.60	51.41	68.20	16.79	PK	Horizontal
4	5879.795	44.76	34.06	5.76	-29.60	54.98	68.20	13.22	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-24

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT2 AC40 TX 5710MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\18

Memo:

Sample Number:S24122405-001 Power Setting:12

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5462.375	44.29	33.00	5.49	-29.60	53.18	68.20	15.02	PK	Vertical
2	5470.000	42.57	33.00	5.49	-29.60	51.46	68.20	16.74	PK	Vertical
3	5850.000	41.31	34.00	5.74	-29.60	51.45	68.20	16.75	PK	Vertical
4	5889.245	44.43	34.08	5.77	-29.60	54.68	68.20	13.52	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-01-24 Tested By: Zhong Nan
EUT: In-vehicle Multimedia Host Model Number: MTCJ06-A03
Test Mode: ANT1 AC40 TX 5710MHz Mode Power Supply: DC 12V
Condition: Temp:23°C;Humi:59.5% Test Site: DDT 3# Chamber
File Path: d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\19
Memo: Sample Number:S24122405-001 Power Setting:12

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5463.950	44.36	33.00	5.49	-29.60	53.25	68.20	14.95	PK	Horizontal
2	5470.000	43.07	33.00	5.49	-29.60	51.96	68.20	16.24	PK	Horizontal
3	5850.000	42.08	34.00	5.74	-29.60	52.22	68.20	15.98	PK	Horizontal
4	5883.350	44.58	34.07	5.76	-29.60	54.81	68.20	13.39	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-24

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT1 AC40 TX 5710MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\20

Memo:

Sample Number:S24122405-001 Power Setting:12

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5464.310	44.73	33.00	5.49	-29.60	53.62	68.20	14.58	PK	Vertical
2	5470.000	42.53	33.00	5.49	-29.60	51.42	68.20	16.78	PK	Vertical
3	5850.000	42.36	34.00	5.74	-29.60	52.50	68.20	15.70	PK	Vertical
4	5880.605	44.78	34.06	5.76	-29.60	55.00	68.20	13.20	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-24

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT1 AC80 TX 5690MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\21

Memo:

Sample Number:S24122405-001 Power Setting:12

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5452.205	44.27	33.00	5.48	-29.60	53.15	74.00	20.85	PK	Horizontal
2	5470.000	42.37	33.00	5.49	-29.60	51.26	68.20	16.94	PK	Horizontal
3	5850.000	41.29	34.00	5.74	-29.60	51.43	68.20	16.77	PK	Horizontal
4	5869.850	45.34	34.04	5.75	-29.60	55.53	68.20	12.67	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-01-24 Tested By: Zhong Nan
EUT: In-vehicle Multimedia Host Model Number: MTCJ06-A03
Test Mode: ANT1 AC80 TX 5690MHz Mode Power Supply: DC 12V
Condition: Temp:23°C;Humi:59.5% Test Site: DDT 3# Chamber
File Path: d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\22
Memo: Sample Number:S24122405-001 Power Setting:12

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5458.910	45.39	33.00	5.48	-29.60	54.27	74.00	19.73	PK	Vertical
2	5470.000	42.12	33.00	5.49	-29.60	51.01	68.20	17.19	PK	Vertical
3	5850.000	42.58	34.00	5.74	-29.60	52.72	68.20	15.48	PK	Vertical
4	5896.400	44.29	34.09	5.77	-29.60	54.55	68.20	13.65	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:2025-01-24

Tested By:Zhong Nan

EUT:In-vehicle Multimedia Host

Model Number:MTCJ06-A03

Test Mode:ANT2 AC80 TX 5690MHz Mode

Power Supply:DC 12V


Condition:Temp:23°C;Humi:59.5%

Test Site:DDT 3# Chamber

File Path:d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\23

Memo:Sample Number:S24122405-001 Power Setting:12

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5455.670	44.17	33.00	5.48	-29.60	53.05	74.00	20.95	PK	Horizontal
2	5470.000	41.45	33.00	5.49	-29.60	50.34	68.20	17.86	PK	Horizontal
3	5850.000	40.77	34.00	5.74	-29.60	50.91	68.20	17.29	PK	Horizontal
4	5892.710	44.80	34.09	5.77	-29.60	55.06	68.20	13.14	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-24

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT2 AC80 TX 5690MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\24

Memo:

Sample Number:S24122405-001 Power Setting:12

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5450.765	43.89	33.00	5.48	-29.60	52.77	74.00	21.23	PK	Vertical
2	5470.000	41.65	33.00	5.49	-29.60	50.54	68.20	17.66	PK	Vertical
3	5850.000	42.53	34.00	5.74	-29.60	52.67	68.20	15.53	PK	Vertical
4	5892.035	44.87	34.08	5.77	-29.60	55.12	68.20	13.08	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-24

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT2 AX20 TX 5720MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\25

Memo:

Sample Number:S24122405-001 Power Setting:12

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5456.255	44.95	33.00	5.48	-29.60	53.83	74.00	20.17	PK	Horizontal
2	5470.000	43.20	33.00	5.49	-29.60	52.09	68.20	16.11	PK	Horizontal
3	5850.000	42.62	34.00	5.74	-29.60	52.76	68.20	15.44	PK	Horizontal
4	5875.115	44.05	34.05	5.76	-29.60	54.26	68.20	13.94	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-01-24

Tested By:

Zhong Nan

EUT:

In-vehicle Multimedia Host

Model Number:

MTCJ06-A03

Test Mode:

ANT2 AX20 TX 5720MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23°C;Humi:59.5%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\26

Memo:

Sample Number:S24122405-001 Power Setting:12

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5465.795	45.04	33.00	5.49	-29.60	53.93	68.20	14.27	PK	Vertical
2	5470.000	42.93	33.00	5.49	-29.60	51.82	68.20	16.38	PK	Vertical
3	5850.000	42.11	34.00	5.74	-29.60	52.25	68.20	15.95	PK	Vertical
4	5886.500	44.18	34.07	5.77	-29.60	54.42	68.20	13.78	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-01-24 Tested By: Zhong Nan
EUT: In-vehicle Multimedia Host Model Number: MTCJ06-A03
Test Mode: ANT1 AX20 TX 5720MHz Mode Power Supply: DC 12V
Condition: Temp:23°C;Humi:59.5% Test Site: DDT 3# Chamber
File Path: d:\ts\2024 report data\Q24122405-5E\FCC ABOVE1G KUAYUE\27
Memo: Sample Number:S24122405-001 Power Setting:12

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5460.485	44.32	33.00	5.48	-29.60	53.20	68.20	15.00	PK	Horizontal
2	5470.000	40.99	33.00	5.49	-29.60	49.88	68.20	18.32	PK	Horizontal
3	5850.000	41.32	34.00	5.74	-29.60	51.46	68.20	16.74	PK	Horizontal
4	5883.350	45.31	34.07	5.76	-29.60	55.54	68.20	12.66	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.