

Test of Sensus U905458B  
To: FCC 47 CFR Part(s) 24, 90, 101  
Test Report Serial No.: SNUS06-U1 Rev A





Test of Sensus U905458B

To FCC 47 CFR Part(s) 24, 90, 101  
RSS-134 & RSS-119

Test Report Serial No.: SNUS06-U1 Rev A

This report supersedes: None

**Manufacturer:** Sensus Metering Systems  
8609 Six Forks Road, 3rd Floor  
Raleigh, North Carolina 27615  
USA

**Product Function:** Remote Telemetry Module

**Copy No:** pdf      **Issue Date:** 17th December 2010

**This Test Report is Issued Under the Authority of:**

**MiCOM Labs, Inc.**  
440 Boulder Court, Suite 200  
Pleasanton, CA 94566 USA  
Phone: +1 (925) 462-0304  
Fax: +1 (925) 462-0306  
[www.micomlabs.com](http://www.micomlabs.com)



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 3 of 83

---

This page has been left intentionally blank

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

## TABLE OF CONTENTS

<b>ACCREDITATION, LISTINGS &amp; RECOGNITION .....</b>	<b>5</b>
TESTING ACCREDITATION .....	5
RECOGNITION .....	6
PRODUCT CERTIFICATION .....	7
<b>1. TEST RESULT CERTIFICATE .....</b>	<b>9</b>
<b>2. REFERENCES AND MEASUREMENT UNCERTAINTY .....</b>	<b>10</b>
2.1. Normative References .....	10
2.2. Test and Uncertainty Procedures .....	10
<b>3. PRODUCT DETAILS AND TEST CONFIGURATIONS .....</b>	<b>11</b>
3.1. Technical Details .....	11
3.2. Scope of Test Program .....	12
3.3. Equipment Model(s) and Serial Number(s) .....	12
3.4. Antenna Details .....	12
3.5. Cabling and I/O Ports .....	13
3.6. Test Configurations .....	13
3.7. Equipment Modifications .....	15
3.8. Deviations from the Test Standard .....	15
3.9. Subcontracted Testing or Third Party Data .....	15
<b>4. TEST SUMMARY .....</b>	<b>16</b>
<b>5. TEST RESULTS .....</b>	<b>18</b>
5.1. Device Characteristics .....	18
5.1.1. <i>Output Power</i> .....	18
5.1.2. <i>Occupied Bandwidth and Spectrum Mask</i> .....	21
5.1.3. <i>Frequency Stability; Temperature Variations, and Voltage Variations</i> ..	42
5.1.4. <i>Spurious Emissions from Antenna Terminals</i> .....	47
5.1.5. <i>Maximum Permissible Exposure</i> .....	60
5.1.6. <i>Radiated Spurious Emissions</i> .....	61
5.1.7. <i>AC Wireline Conducted Emissions (0.15 – 30 MHz)</i> .....	72
<b>6. TEST SET-UP PHOTOGRAPHS .....</b>	<b>76</b>
6.1. General Measurement Test Set-Up .....	76
6.2. General Measurement – Environmental Chamber .....	77
6.3. Radiated Emissions below 1 GHz (1) .....	78
6.4. Radiated Emissions Module Test Configuration .....	79
6.5. Radiated Digital Emissions above 1 GHz .....	80
6.6. AC Wireline Emissions .....	81
<b>7. TEST EQUIPMENT DETAILS .....</b>	<b>82</b>

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

## ACCREDITATION, LISTINGS & RECOGNITION

### TESTING ACCREDITATION

MiCOM Labs, Inc. is an accredited Electrical testing laboratory per the international standard EN ISO/IEC 17025. The company is accredited by the American Association for Laboratory Accreditation (A2LA) [www.a2la.org](http://www.a2la.org) test laboratory number 2381.01. MiCOM Labs test schedule is available at the following URL; <http://www.a2la.org/scopepdf/2381-01.pdf>



The American Association for Laboratory Accreditation

### *Accredited Laboratory*

A2LA has accredited

#### **MICOM LABS**

*Pleasanton, CA*

for technical competence in the field of

*Electrical Testing*

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 *General Requirements for the Competence of Testing and Calibration Laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-LAF Communiqué dated 8 January 2009).

Presented this 14<sup>th</sup> day of April 2010.



President & CEO  
For the Accreditation Council  
Certificate Number 2381.01  
Valid to November 30, 2011



*For the tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.*

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 6 of 83

## RECOGNITION

MiCOM Labs, Inc has widely recognized Electrical testing capabilities. Our international recognition includes Conformity Assessment Body designation by APEC MRA\*\* countries. Our test reports are widely accepted for global type approvals.

Country	Recognition Body	Status	Phase	Identification No.
USA	Federal Communications Commission (FCC)	TCB	-	Listing #: 102167
Canada	Industry Canada (IC)	FCB	APEC MRA 2	Listing #: 4143A
Japan	VCCI	-	-	No. 2959
Europe	European Union	NB	N/A	US0159
Australia	Australian Communications and Media Authority (ACMA)	CAB	APEC MRA 1	
Hong Kong	Office of the Telecommunication Authority (OFTA)	CAB	APEC MRA 1	
Korea	Ministry of Information and Communication Radio Research Laboratory (RRL)	CAB	APEC MRA 1	
Singapore	Infocomm Development Authority (IDA)	CAB	APEC MRA 1	
Taiwan	National Communications Commission (NCC) Bureau of Standards, Metrology and Inspection (BSMI)	CAB	APEC MRA 1	
Vietnam	Ministry of Communication (MIC)	CAB	APEC MRA 1	

\*\*APEC MRA – Asia Pacific Economic Community Mutual Recognition Agreement.

Is a recognition agreement under which test lab is accredited to regulatory standards of the APEC member countries.

Phase I - recognition for product testing

Phase II – recognition for both product testing and certification

N/A – Not Applicable

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 7 of 83

## **PRODUCT CERTIFICATION**

MiCOM Labs, Inc. is an accredited Product Certification Body per the international standard EN ISO/IEC Guide 65. The company is accredited by the American Association for Laboratory Accreditation (A2LA) [www.a2la.org](http://www.a2la.org) test laboratory number 2381.02. MiCOM Labs test schedule is available at the following URL; <http://www.a2la.org/scopepdf/2381-02.pdf>



World Class Accreditation

## ***Accredited Product Certification Body***

A2LA has accredited

**MICOM LABS**

*Pleasanton, CA*

for technical competence as a

**Product Certification Body**

This product certification body is accredited in accordance with the recognized International Standard ISO/IEC Guide 65:1996 *General requirements for bodies operating product certification systems*. This accreditation demonstrates technical competence for a defined scope and the operation of a quality management system for a Telecommunications Certification Body (TCB) meeting FCC (U.S.), and IC (Canada) requirements.

Presented this 24<sup>th</sup> day of June 2010.



  
Peter Myer  
President & CEO  
For the Accreditation Council  
Certificate Number 2381.02  
Valid to November 30, 2011

*For the product certification schemes to which this accreditation applies, please refer to the organization's Product Certification Scope of Accreditation.*

## **United States of America – Telecommunication Certification Body**

TCB Identifier – US0159

## **Industry Canada – Certification Body**

CAB Identifier – US0159

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 8 of 83

---

## DOCUMENT HISTORY

Document History		
Revision	Date	Comments
Draft		
A	9 <sup>th</sup> December 2010	Initial Release

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 9 of 83

## 1. TEST RESULT CERTIFICATE

Manufacturer:	Sensus Metering Systems 8609 Six Forks Road, 3rd Floor Raleigh, North Carolina 27615 USA	Tested By:	MiCOM Labs, Inc. 440 Boulder Court Suite 200 Pleasanton California, 94566, USA
EUT:	900 MHz Remote Telemetry Module	Telephone:	+1 925 462 0304
Model:	U905458B	Fax:	+1 925 462 0306
S/N:	23495		
Test Date(s):	25th to 27th May 2010	Website:	<a href="http://www.micomlabs.com">www.micomlabs.com</a>

STANDARD(S)	TEST RESULTS
FCC 47 CFR Part(s) 24, 90, 101	EQUIPMENT COMPLIES


MiCOM Labs, Inc. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.

### Notes:

1. This document reports conditions under which testing was conducted and the results of testing performed.
2. Details of test methods used have been recorded and kept on file by the laboratory.
3. Test results apply only to the item(s) tested.

Approved & Released for MiCOM Labs, Inc. by:

  
Graeme Grieve  
Quality Manager MiCOM Labs,

  
Gordon Hurst  
President & CEO MiCOM Labs, Inc.



TEST CERTIFICATE #2381.01

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

## 2. REFERENCES AND MEASUREMENT UNCERTAINTY

### 2.1. Normative References

Ref.	Publication	Year	Title
(i)	FCC 47 CFR Part 24	2009	Code of Federal Regulations
(ii)	FCC 47 CFR Part 90	2009	Code of Federal Regulations
(iii)	FCC 47 CFR Part 101	2009	Code of Federal Regulations
(iv)	ANSI C63.4	2003	American National Standards for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
(v)	CISPR 22/ EN 55022	1997 1998	Limits and Methods of Measurements of Radio Disturbance Characteristics of Information Technology Equipment
(vi)	M 3003	Edition 1 Dec. 1997	Expression of Uncertainty and Confidence in Measurements
(vii)	LAB34	Edition 1 Aug 2002	The expression of uncertainty in EMC Testing
(viii)	ETSI TR 100 028	2001	Parts 1 and 2 Electromagnetic compatibility and Radio Spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics
(xv)	A2LA	14 <sup>th</sup> September 2005	Reference to A2LA Accreditation Status – A2LA Advertising Policy
(x)	FCC (OET)	15 <sup>th</sup> April 2010	Compliance Management Guidance for Wireless Broadband Services Operating in the 3650-3700 MHz Band

### 2.2. Test and Uncertainty Procedures

Conducted and radiated emission measurements were conducted in accordance with American National Standards Institute ANSI C63.4, listed in the Normative References section of this report.

Measurement uncertainty figures are calculated in accordance with ETSI TR 100 028 Parts 1 and 2.

Measurement uncertainties stated are based on a standard uncertainty multiplied by a coverage factor  $k = 2$ , providing a level of confidence of approximately 95 % in accordance with UKAS document M 3003 listed in the Normative References section of this report.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### **3. PRODUCT DETAILS AND TEST CONFIGURATIONS**

#### **3.1. Technical Details**

<b>Details</b>	<b>Description</b>
Purpose:	Test of the Sensus U905458B to FCC 47 CFR Part(s) 24, 90, 101 regulations.
Applicant:	Sensus Metering Systems 8609 Six Forks Road, 3rd Floor Raleigh, North Carolina 27615 USA
Manufacturer:	As Applicant
Laboratory performing the tests:	MiCOM Labs, Inc. 440 Boulder Court, Suite 200 Pleasanton, California 94566 USA
Test report reference number:	SNUS06-U1 Rev A
Date EUT received:	25 <sup>th</sup> May 2010
Dates of test (from - to):	25th to 27th May 2010
Standard(s) applied:	FCC 47 CFR Part(s) 24, 90, 101
No of Units Tested:	3
Type of Equipment:	900 MHz Transceiver (Licensed Bands)
Model:	U905458B
Location for use:	Outdoor use only
Equipment Classification:	Mobile Applications
Declared Frequency Range(s):	Transmit: 896.0375 – 959.9250 MHz Receiver: 896.0375 – 959.9250 MHz
Type of Modulation:	C & I, DD Extend, mPass, Normal
Operational Bandwidth:	25 kHz
Declared Maximum Output Power:	+30 dBm
Transmit/Receive Operation:	Time Division Duplex (TDD)
Software Revision:	6.5.0
Hardware Release:	Rev X3
Antenna Type:	Phantom external 3 dBi
ITU Emission Designator:	6.25 KHz: 6K01F2D 12.5 KHz: 12K3F1D
Rated Input Voltage and Current:	Module Voltage: 5 Vdc ±5%
Operating Temperature Range:	-33°C to +50°C
Clock/Oscillator(s):	32.768 KHz, 6.5 MHz, 12.8 MHz
Frequency Stability:	N/A
Equipment Dimensions:	3.25" x 1.6" x 0.5"
Weight:	<1 lbs
Primary function of equipment:	Remote Telemetry Module

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 3.2. Scope of Test Program

The scope of the test program was to test the Sensus U905458B for compliance against the following standards:-

FCC 47 CFR Part 24, Subpart D requirements

FCC 47 CFR Part 90, Subpart I requirements.

FCC 47 CFR Part 101, Subpart C requirements.

### Modular Approval

The test program addressed the Sensus U905458B product for limited modular approval.

### Applicable Variants

This report contains data with respect to a four modulations;

- C & I
- DD Extend
- mPass
- Normal

### 3.3. Equipment Model(s) and Serial Number(s)

EUT/Support	Manufacturer	Equipment Description (Including Brand Name)	Model No.	Serial No.
EUT	Sensus	FlexNet 900 MHz radio transceiver	U905458B	23495
EUT	Sensus	900 MHz Remote Telemetry	DNP-RTMII-MA-FLX-900	--
Support	Mean Well	Universal AC/DC Switching Adapter Input:100-240Vac 50/60 Hz Output: 11-13 Vdc, 1.63-1.38A	GS18A12-P1J	R091138785
Support	Dell Laptop	Computer	--	--

### 3.4. Antenna Details

Antenna Type	Gain (dBi)	Manufacturer	Model No.	Serial No.
External	3.0	Phantom	N/A	N/A

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 3.5. Cabling and I/O Ports

Number and type of I/O ports

Type of I/O Port	Description	Screened	Length
RS232-DB9	Communicate with IED	y	< 1 Meter
RS232-DB9	Unused	y	< 1 Meter
RS232	comm. with IED, custom wiring	n	< 1 Meter
USB Full Speed	Configure unit at the factory	y	< 1 Meter
12Vdc Power Input		n	6'

### 3.6. Test Configurations

Test Matrix V's Variants

Parameter	Operational Mode	Test Conditions	Bandwidths (KHz)
Output power	Modulated - C & I, DD Extend, mPass, Normal	Ambient, 12Vdc	12.5
Occupied BW			
Spectrum Mask			
Frequency Stability	Single Tone (CW)	-33°C to +50°C + voltage variation	N/A
Conducted Spurious Emissions	BPSK	Ambient, 12Vdc	12.5
Radiated Spurious Emissions	Single Tone (CW)	Ambient, 12Vdc	12.5
AC Wireline Emissions	Normal	Ambient, 12Vdc	12.5

### Test Frequencies

For testing in accordance with 47 CFR 2.1046-2, 1057, FCC OET recommends the following is used to select test frequencies for licensed devices;

Frequency Range of Device	Number of Selected Frequencies	Location in Range of Operation
1 MHz or less	1	Middle
1 to 10 MHz	2	1 near top and 1 near bottom
10 to 100 MHz	3	1 near top, 1 near middle, 1 near bottom

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 14 of 83

## Test Frequency Selection

The following is the list of frequency bands associated by rule part.


Rule Part	Frequency Range (MHz)
24D	901.0-902.0
24D	930.0-931.0
24D	940.0-941.0
90	896.0375 – 901.0
90	935.0-940.0
101	928.85-929.0
101	932.0-932.5
101	941.0-941.5
101	959.85-960.0

Rule Part	Frequency Range (MHz)	Selected Test Frequency (MHz)
90	896.0375 – 901.0	896.0375
24D	901.0-902.0	901.9875
101	928.85-929.0	925.9250
24D	930.0-931.0	930.5000
101	932.0-932.5	932.2500
90	935.0-940.0	935.0125
101	941.0-941.5	941.4875
101	959.85-960.0	959.9250

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

## Test Set-Up

Test software was available to exercise the Access Point and the equipment was tested using the following test configuration.



## General Test Set-Up

### 3.7. Equipment Modifications

The following modifications were required to bring the equipment into compliance:

1. Modulation Issue

When the equipment was initially delivered only a single modulation could be selected. Updated unit arrived 5<sup>th</sup> November 2010 to complete modulation V's Spectrum mask.

### 3.8. Deviations from the Test Standard

The following deviations from the test standard were required in order to complete the test program:

1. NONE

### 3.9. Subcontracted Testing or Third Party Data

1. NONE

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

## 4. TEST SUMMARY

### List of Measurements

The following table represents the list of measurements required under the **FCC CFR47 Part 24, 90, and 101**.

### IC RSS-134, RSS-119 & RSS Gen

Section(s)	Test Items	Description	Condition	Result	Test Report Section
<b>2.1046</b>	Output Power	Modulated Output Power	Conducted	Complies	5.1.1
<b>24.133 a(1),a(2) 90.210 (j) 101.111 a(6) RSS-134 6.3 (i), (ii) RSS-119 5.8.8</b>	Occupied Bandwidth & Spectrum Mask	Bandwidth and spectrum mask	Conducted	Complies	5.1.2
<b>2.1055, 24.135, 90.213, 101.107 RSS-134 (7), RSS-119 (5.3)</b>	Frequency Stability	Includes temperature and voltage variations	Conducted	Complies	5.1.3
<b>24.133 a(1),a(2) 90.210 (j) 101.111 a(6) RSS-134 6.3 (i), (ii) RSS-119 5.8.8</b>	Conducted Spurious Emissions	Emissions from Antenna Port	Conducted	Complies	5.1.4
<b>FCC, Part 1 Subpart §1.1310</b>	Maximum Permissible Exposure	Exposure to radio frequency energy levels	Calculated	Complies	5.1.5
<b>24.133 a(1),a(2) 90.210 (j) 101.111 a(6) ANSI/TIA-603 RSS-134 6.3 (i), (ii) RSS-119 5.8.8</b>	Radiated Spurious Emissions	Spurious emissions	Radiated	Complies	5.1.6
<b>15.207 7.2.2</b>	AC Wireline Conducted	Emissions 150 kHz–30 MHz	Conducted	Complies	5.1.7

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 17 of 83

---

**Note 1:** Test results reported in this document relate only to the items tested

**Note 2:** The required tests demonstrated compliance as per client declaration of test configuration, monitoring methodology and associated pass/fail criteria

**Note 3:** Section 3.7 'Equipment Modifications' highlight the equipment modifications that were required to bring the product into compliance with the above matrix

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 18 of 83

---

## **5. TEST RESULTS**

### **5.1. Device Characteristics**

#### **5.1.1. Output Power**

**FCC 47 CFR Part 24 Subpart 24.133 a(1), a(2)**

**FCC 47 CFR Part 90 Subpart 90.210 (j)**

**FCC 47 CFR Part 101 Subpart 101.111 a(6)**

#### **Test Procedure**

The transmitter output was connected to an average power meter and the Output Power was measured on a modulated carrier under all operational modes.

Output Power was measured under ambient conditions, nominal voltage for all modulations and rule parts for the applicable frequency channels.

#### **Test Set-up is shown in Section 3.6 Test Configuration**

Ambient conditions.

Temperature: **17 to 23 °C**      Relative humidity: **31 to 57 %**      Pressure: **999 to 1012 mbar**

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 19 of 83

#### Part 24 Measurement Results

Output Power (dBm)				
Center Frequency (MHz)	C & I	DD Extend	mPass	Normal
901.9875	+29.63	+29.68	+29.73	+29.84
930.5000	+29.03	+29.02	+29.07	+29.07

#### Part 90 Measurement Results

Output Power (dBm)				
Center Frequency (MHz)	C & I	DD Extend	mPass	Normal
896.0375	+29.67	+29.73	+29.73	+29.73
935.0125	+28.84	+29.01	+29.00	+29.02

#### Part 101 Measurement Results

Output Power (dBm)				
Center Frequency (MHz)	C & I	DD Extend	mPass	Normal
928.9250	+29.04	+29.15	+29.16	+29.15
932.2500	+28.97	+29.08	+29.10	+29.19
941.4875	+28.45	+28.43	+28.40	+28.47
959.9250	+27.00	+27.01	+27.06	+27.03

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 20 of 83

---

### Laboratory Measurement Uncertainty for Power Measurement

Measurement uncertainty	±1.33 dB
-------------------------	----------

### Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-03 'Measurement of RF Output Power'	0070, 0116, 0158, 0193, 0252, 0313, 0314.

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### **5.1.2. Occupied Bandwidth and Spectrum Mask**

**FCC 47 CFR Part 24 Subpart 24.133 a(1), a(2)**

**FCC 47 CFR Part 90 Subpart 90.210 (j)**

**FCC 47 CFR Part 101 Subpart 101.111 a(6)**

**RSS-134 6.3 (i), (ii)**

**RSS-119 5.8.8**

#### **Test Procedure**

The transmitter output was connected to a spectrum analyzer and the Occupied Bandwidth was measured with a modulated carrier.

Occupied Bandwidth was measured under ambient conditions, nominal voltage for all modulations and rule parts on low, mid and high channels. The spectrum analyzer RBW and VBW was set for 300 Hz which was based on the bandwidth of the output spectrum.

To position the mask relative to the output spectrum the EUT was initially set to transmit a CW (single) tone at the frequency of interest. The mask was then lined up with the peak of the CW tone. The EUT then was then set to modulate each modulation of interest and measurements reported.

Spectrum mask parameters were generated using the attenuation characteristics which were found in each rule part as highlighted for 12.5 kHz. The spectrum analyzer pass/fail criteria was used to determine compliance which is clearly marked on each plot provided. The automatic bandwidth function within the analyzer was used to determine 99% bandwidth.

#### **Test Set-up is shown in Section 3.6 Test Configuration**

Ambient conditions.

Temperature: **17 to 23 °C**      Relative humidity: **31 to 57 %**      Pressure: **999 to 1012 mbar**



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 22 of 83



## PART 24 RESULTS

### Part 24.133 Measurement Results – Occupied Bandwidth + Plots



99% Bandwidth (kHz)				
Center Frequency (MHz)	C & I	DD Extend	mPass	Normal
901.9875	5.711	12.325	6.012	10.822
930.5000	5.711	12.024	5.711	10.822

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



### Part 24.133 Measurement Results





This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 27 of 83



## PART 90 RESULTS

### Part 90.210 j Measurement Results – Occupied Bandwidth + Plots



99% Bandwidth (kHz)				
Center Frequency (MHz)	C & I	DD Extend	mPass	Normal
896.0375	5.711	12.024	6.012	10.822
935.0125	5.711	12.024	5.711	11.122

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



### Part 90.210 j Measurement Results





This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 32 of 83

## PART 101 RESULTS


### Part 101.111 a(6) Measurement Results – Occupied Bandwidth + Plots

Center Frequency (MHz)	99% Bandwidth (kHz)			
	C & I	DD Extend	mPass	Normal
928.9250	5.711	12.024	6.012	11.122
932.2500	5.711	12.024	5.711	11.122
941.4875	5.711	12.325	5.711	10.822
959.9250	5.711	12.325	5.711	11.122


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

**Part 101.111 a(6) Measurement Results**



**Channel 928.925 MHz C&I Modulation – Spectrum Mask, 99% Occupied Bandwidth**





**Channel 928.925 MHz DD Extend – Spectrum Mask, 99% Occupied Bandwidth**





This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 40 of 83

#### Channel 959.925 MHz mPass – Spectrum Mask & 99% Occupied Bandwidth



Channel 959.925 MHz Normal – Spectrum Mask & 99% Occupied Bandwidth



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 41 of 83

---

#### **Laboratory Measurement Uncertainty for Power Measurements**

Measurement uncertainty	±1.33 dB
-------------------------	----------

#### **Traceability**

Method	Test Equipment Used
Measurements were made per work instruction WI-03 'Measurement of RF Spectrum Mask'	0070, 0116, 0158, 0193, 0252, 0313, 0314.

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### **5.1.3. Frequency Stability; Temperature Variations, and Voltage Variations**

**FCC 47 CFR Sections 2.1055, 24.135, 90.213, 101.107**

**IC RSS-134 (7), RSS-119 (5.3)**

#### **Test Procedure**

The EUT was placed inside an environmental chamber. The transmitter output was connected to a spectrum analyzer and the frequency stability was measured using a unmodulated (CW) single tone. A thermocouple was used to monitor chamber temperature. The EUT was attached to a variable power supply providing the primary supply voltage.

Frequency stability was measured through the extremes of temperature and voltage on the mid channel of each frequency band. Before measurements were taken at each temperature the equipment waited until thermal balance was obtained.

At +20°C the primary voltage was varied  $\pm 15\%$  and measurements were taken at each voltage level.

#### **Test Set-up is shown in Section 3.6 Test Configuration**

Ambient conditions.

Temperature: 17 to 23 °C      Relative humidity: 31 to 57 %      Pressure: 999 to 1012 mbar

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

TABLE OF RESULTS Frequency Stability – Channel Measured 896.0125 MHz

EUT Classification: Mobile Applications

Voltage	Temperature (°C)	Center Frequency (MHz)	Delta (Hz)	ppm
12 Vdc	-33	896012309.22	-190.78	-0.21
	-30	896012340.51	-159.49	-0.18
	-20	896012512.71	12.71	0.01
	-10	896012539.09	39.09	0.04
	+0	896012517.11	17.11	0.02
	+10	896012494.60	-5.40	-0.01
	+20	896012514.34	14.34	0.02
10.2 Vdc	+20	896012507.55	7.55	0.01
13.8 Vdc	+20	896012471.76	-28.24	-0.03
12 Vdc	+30	896012554.81	54.81	0.06
	+40	896012536.17	36.17	0.04
	+50	896012516.63	16.63	0.02
Maximum Frequency Drift with respect to the nominal frequency		-190.78 Hz / +54.81 Hz -0.21 ppm / +0.06 ppm		

**Limits**

**§ 90.213 (a) Frequency stability**

(a) Unless noted elsewhere, transmitters used in the services governed by this part must have a minimum frequency stability as specified in the following table.

MINIMUM FREQUENCY STABILITY [Parts per million (ppm)]

Frequency Range (MHz)	Fixed and Base Stations (ppm)	Mobile Stations (ppm)	
		Over 2 watts output power	2 watts or less output power
896 - 901	±0.1	±1.5	±1.5
935 - 940	±0.1	±1.5	±1.5

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

TABLE OF RESULTS Frequency Stability – Channel Measured 930.1125 MHz

Voltage	Temperature (°C)	Center Frequency (MHz)	Delta (Hz)	ppm
12 Vdc	-33	930112275.64	-224.36	-0.24
	-30	930112336.74	-163.26	-0.18
	-20	930112580.17	80.17	0.09
	-10	930112568.11	68.11	0.07
	+0	930112545.07	45.07	0.05
	+10	930112482.98	-17.02	-0.02
	+20	930112513.02	13.02	0.01
10.2 Vdc	+20	930112519.03	19.03	0.02
13.8 Vdc	+20	930112521.03	21.03	0.02
12 Vdc	+30	930112587.13	87.13	0.09
	+40	930112569.11	69.11	0.07
	+50	930112530.05	30.05	0.03
Maximum Frequency Drift with respect to the nominal frequency		-224.36 Hz / +87.13 Hz -0.24 ppm / +0.09 ppm		

**Limits**

**§ 24.135 Frequency stability**

- (a) The frequency stability of the transmitter shall be maintained within  $\pm$  0.0001 percent ( $\pm 1$  ppm) of the center frequency over a temperature variation of 30° Celsius to +50° Celsius at normal supply voltage, and over a variation in the primary supply voltage of 85 percent to 115 percent of the rated supply voltage at a temperature of 20° Celsius.
- (b) For battery operated equipment, the equipment tests shall be performed using a new battery without any further requirement to vary supply voltage.
- (c) It is acceptable for a transmitter to meet this frequency stability requirement over a narrower temperature range provided the transmitter ceases to function before it exceeds these frequency stability limits.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 45 of 83

TABLE OF RESULTS Frequency Stability – Channel Measured 959.93125 MHz

Voltage	Temperature (°C)	Center Frequency (MHz)	Delta (Hz)	ppm	%
12 Vdc	-33	959930668.22	-581.78	-0.61	-0.0000606
	-30	959931050.47	-199.53	-0.21	-0.0000208
	-20	959931398.56	148.56	0.15	0.0000155
	-10	959931277.59	27.59	0.03	0.0000029
	+0	959931286.81	36.81	0.04	0.0000038
	+10	959931232.80	-17.20	-0.02	-0.0000018
	+20	959931332.11	82.11	0.09	0.0000086
10.2 Vdc	+20	959931235.73	-14.27	-0.01	-0.0000015
13.8 Vdc	+20	959931276.67	26.67	0.03	0.0000028
12 Vdc	+30	959931285.35	35.35	0.04	0.0000037
	+40	959931349.04	99.04	0.10	0.0000103
	+50	959931253.82	3.82	0.00	0.0000004
Maximum Frequency Drift with respect to the nominal frequency		-581.78 Hz / +148.56 Hz -0.61 ppm / +0.15 ppm			

#### § 101.107 Frequency tolerance.

(a) The carrier frequency of each transmitter authorized in these services must be maintained within the following percentage of the reference frequency except as otherwise provided in paragraph (b) of this section or in the applicable subpart of this part (unless otherwise specified in the instrument of station authorization the reference frequency will be deemed to be the assigned frequency):

#### Frequency Tolerance (percent)

Frequency Range (MHz)	Frequency Tolerance (%)
928 - 929.5	0.0005
932 - 932.5	0.00015
932.5 - 935	0.00025
941 - 941.5	0.00015
941.5 TO 944	0.00025

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 46 of 83

---

### Laboratory Uncertainty for Frequency Measurements

Measurement uncertainty (dB)	±0.86ppm
------------------------------	----------

### Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-02 'Frequency Measurement'	0075, 0156, 0193, 0252, 0313, 0314

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

#### **5.1.4. Spurious Emissions from Antenna Terminals**

**FCC 47 CFR Part 24 Subpart 24.133 a(1), a(2)**

**FCC 47 CFR Part 90 Subpart 90.210 (j)**

**FCC 47 CFR Part 101 Subpart 101.111 a(6)**

**IC RSS-134 6.3 (i), (ii)**

**IC RSS-119 5.8.6**

#### **Test Procedure**

The transmitter output was connected to a spectrum analyzer and the Spurious Emissions were measured using an un-modulated carrier.

Spurious Emissions were measured under ambient conditions, nominal voltage for all rule parts on low and high channels for the particular frequency band.

The limit line was calculated from the attenuation characteristics found within each rule part.

#### **Test Set-up is shown in Section 3.6 Test Configuration**

Ambient conditions.

Temperature: **17 to 23 °C**      Relative humidity: **31 to 57 %**      Pressure: **999 to 1012 mbar**

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 48 of 83


## PART 24 RESULTS

### Part 24.133 Measurement Results


Channel Centre Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Maximum Emission Observed (dBm)	Limit (dBm)	Margin (dB)
901.9875	30	1,000	-38.20	-13.0	-25.20
	1,000	10,000	-24.84		-11.84
930.5000	30	1,000	-37.60	-13.0	-24.60
	1,000	10,000	-24.46		-11.46

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Channel 901.9875 MHz-Conducted Spurious Emissions from Antenna Port 0.03–1 GHz**



**Channel 901.9875 MHz-Conducted Spurious Emissions from Antenna Port 1– 10 GHz**



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 51 of 83

---

## PART 90 RESULTS


### Part 90.210 j Measurement Results – Conducted Spurious Emissions

Channel Centre Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Maximum Emission Observed (dBm)	Limit (dBm)	Margin (dB)
896.0375	30	1,000	-36.80	-20	-16.80
	1,000	10,000	-25.19		-5.19
935.0125	30	1,000	-37.30	-20	-17.30
	1,000	10,000	-24.30		-4.30


---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

**Channel 896.0375 MHz-Conducted Spurious Emissions from Antenna Port 0.03–1 GHz**




**Channel 896.0375 MHz-Conducted Spurious Emissions from Antenna Port 1– 10 GHz**




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

**Channel 935.0125 MHz-Conducted Spurious Emissions from Antenna Port 0.03–1 GHz**



**Channel 935.0125 MHz-Conducted Spurious Emissions from Antenna Port 1-10 GHz**



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 54 of 83

## PART 101 RESULTS



### Part 101.111 a(6) Measurement Results – Conducted Spurious Emissions

Channel Centre Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Maximum Emission Observed (dBm)	Limit (dBm)	Margin (dB)
928.9250	30	1,000	-37.40	-13.0	-24.40
	1,000	10,000	-24.33		-11.33
932.2500	30	1,000	-37.60	-13.0	-24.60
	1,000	10,000	-24.53		-11.53
941.4875	30	1,000	-37.90	-13.0	-24.90
	1,000	10,000	-24.09		-11.09
959.9250	30	1,000	-38.10	-13.0	-25.10
	1,000	10,000	-25.18		-12.18

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Channel 941.4875 MHz-Conducted Spurious Emissions from Antenna Port 0.03–1 GHz**



**Channel 941.4875 MHz-Conducted Spurious Emissions from Antenna Port 1-10 GHz**



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 59 of 83

---

### Laboratory Measurement Uncertainty for Power Measurement

Measurement uncertainty	±1.33 dB
-------------------------	----------

### Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-03 'Measurement of RF Output Power'	0070, 0116, 0158, 0193, 0252, 0313, 0314.

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### **5.1.5. Maximum Permissible Exposure**

#### **FCC, Part 1 Subpart §1.1310**

##### **Calculations for Maximum Permissible Exposure Levels**

$$\text{Power Density} = P_d \text{ (mW/cm}^2\text{)} = \text{EIRP}/(4\pi d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

$$\text{Numeric Gain} = 10 ^ {(G \text{ (dBi)})/10}$$

The calculated separation distance is for worst case i.e. highest power level.

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is f/1500 (where f = 896 MHz) = 0.6 mW/cm<sup>2</sup>

Freq. Band (GHz)	Antenna Gain (dBi)	Numeric Gain (numeric)	Max Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 0.6 mW/cm <sup>2</sup> Limit(cm)	Minimum Separation Distance (cm)
900	3.0	2.00	+29.84	963.9	16	20

\*Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if the calculations indicate the MPE distance to be lower.

#### **Specification**

##### **Maximum Permissible Exposure Limits**

**§1.1310** Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency levels in excess of the Commission's guidelines. See §1.1307 (b)(1) of this chapter.

Limit = 0.6 mW / cm<sup>2</sup> from 1.310 Table 1

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

#### **Laboratory Measurement Uncertainty for Power Measurements**

Measurement uncertainty	±1.33dB
-------------------------	---------

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### **5.1.6. Radiated Spurious Emissions**

#### **5.1.6.1. Transmitter Radiated Emissions above 1 GHz**

**FCC 47 CFR Part 24 Subpart 24.133 a(1), a(2)**

**FCC 47 CFR Part 90 Subpart 90.210 (j)**

**FCC 47 CFR Part 101 Subpart 101.111 a(6)**

**ANSI/TIA-603**

**IC RSS-134 6.3 (i), (ii)**

**IC RSS-119 5.8.6**

#### **Test Procedure**

Test was performed on a CW (continuous) carrier at the maximum allowed output power at the appropriate center frequency. Substitution was performed on any emissions observed within 6 dB of the limit.

The measurement equipment was set to measure in peak hold mode. The emissions were measured in the anechoic chamber at a 3-meter distance on every azimuth in both horizontal and vertical polarities. The emissions are recorded and maximized as a function of azimuth by rotation through 360° with a spectrum analyzer in peak hold mode.

The highest emissions relative to the limit were then further evaluated using substitution methodology.

#### ***Substitution Methodology***

Upon completion of the above for all emission frequencies found:

- a) Replace the EUT with a signal generator connected to a substitution antenna
- b) To provide a better impedance match for the signal generator place a 3dB attenuator on the antenna port
- c) Depending on the standard frequencies below 1GHz may require the use of the dipole antenna
  - for the frequency of interest set the length of the dipole antenna per the manufacturers setting
- d) For each emission noted set the antenna to the appropriate polarization and tune the signal generator to match the frequency of interest
- e) Where required raise / lower the measurement antenna, if necessary, to maximize the emission.
- f) Adjust the input signal to the substitute antenna until a known related level to that detected from the EUT is obtained at the receiver or spectrum analyzer.
- g) Correct the above level for the substitution antenna gain and any path loss present to find the radiated spurious emission at this frequency.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 62 of 83

---

EUT emission = Sig. gen output power – cable loss + transmitting antenna gain (dBi)

dBi =  $10 \log (\text{antenna numeric gain})$ , dBi is with respect to an isotropic radiating antenna

Sample calculation

Sig. Gen output power = -21.2dBm

Cable loss = 4.25dB

Antenna numeric gain = 7.3

EUT spurious emission power level =  $-21.2 - 4.25 + 10 \log (7.3)$

EUT spurious emission = -16.8dBm

Record the frequency of emission, power level and measurement bandwidth.


#### Limit

The worst case limit for all applicable CFR Parts were applied during radiated testing.

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

<b>Test Freq.</b>	896.0375 MHz	<b>Engineer</b>	CSB
<b>Variant</b>	CW - Max Power	<b>Temp (°C)</b>	22.5
<b>Freq. Range</b>	1000 MHz - 10000 MHz	<b>Rel. Hum. (%)</b>	40
<b>Power Setting</b>	Maximum Power	<b>Press. (mBars)</b>	1004
<b>Antenna</b>	External	<b>Duty Cycle (%)</b>	CW Signal
<b>Test Notes 1</b>			
<b>Test Notes 2</b>			




#### Formally measured emission peaks

Frequency MHz	Raw dBm	Loss	Level dBm	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBm	Margin dB	Pass /Fail	Comments
1792.099	-31.1	10.7	-20.4	SUB	V	98	0	-20.0	-0.4	Pass	
2688.133	-42.7	13.2	-29.4	SUB	V	98	0	-20.0	-9.4	Pass	
3584.167	-56.7	15.7	-41.0	SUB	V	98	0	-20	-21.0	Pass	
Legend:	TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission										

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

<b>Test Freq.</b>	930.5 MHz	<b>Engineer</b>	CSB
<b>Variant</b>	CW - Max Power	<b>Temp (°C)</b>	22.5
<b>Freq. Range</b>	1000 MHz - 10000 MHz	<b>Rel. Hum. (%)</b>	40
<b>Power Setting</b>	Maximum Power	<b>Press. (mBars)</b>	1004
<b>Antenna</b>	External	<b>Duty Cycle (%)</b>	CW Signal
<b>Test Notes 1</b>			
<b>Test Notes 2</b>			



#### Formally measured emission peaks

Frequency MHz	Raw dBm	Loss	Level dBm	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBm	Margin dB	Pass /Fail	Comments
1860.986	-43.8	10.8	-33.0	SUB	H	98	360	-20.0	-13.0	Pass	
2791.515	-42.8	13.4	-29.4	SUB	V	98	360	-20.0	-9.4	Pass	
Legend:	TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission										

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

<b>Test Freq.</b>	959.925 MHz	<b>Engineer</b>	CSB
<b>Variant</b>	CW - Max Power	<b>Temp (°C)</b>	22.5
<b>Freq. Range</b>	1000 MHz - 10000 MHz	<b>Rel. Hum. (%)</b>	40
<b>Power Setting</b>	Maximum Power	<b>Press. (mBars)</b>	1004
<b>Antenna</b>	External	<b>Duty Cycle (%)</b>	CW Signal
<b>Test Notes 1</b>			
<b>Test Notes 2</b>			



#### Formally measured emission peaks

Frequency MHz	Raw dBm	Loss	Level dBm	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBm	Margin dB	Pass /Fail	Comments
1919.790	-47.2	11.1	-36.1	SUB	H	98	0	-20.0	-16.1	Pass	
4799.579	-50.3	18.2	-32.0	SUB	V	100	0	-20.0	-12.0	Pass	
8639.379	-58.2	27.9	-30.3	SUB	V	100	0	-20	-10.3	Pass	
9963.928	-65.0	33.7	-31.3	SUB	V	100	0	-20	-11.3	Pass	
Legend:	TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission										

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 66 of 83

---

### Laboratory Measurement Uncertainty for Radiated Emissions

Measurement uncertainty	+5.6/ -4.5 dB
-------------------------	---------------

### Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-03 'Measurement of Radiated Emissions'	0088, 0104, 0158, 0134, 0310, 0312, Dipole.

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 5.1.6.2. Transmitter Radiated Spurious Emissions (30M-1 GHz)


**FCC, Part 15 Subpart C §15.205/ §15.209**  
**Industry Canada RSS-111 §4.4**

**RSS Gen 6**

#### Test Procedure

Preliminary radiated emissions were measured in the anechoic chamber at a 10-meter distance on every azimuth in both horizontal and vertical polarity. The emissions are recorded with a spectrum analyzer in peak hold mode. Emissions closest to the limits are measured in the quasi-peak mode with the tuned receiver using a bandwidth of 120 kHz. Only the highest emissions relative to the limit are listed. The anechoic chamber test set-up is identified in Section 6 Test Set-Up Photographs.

#### Test Measurement Set up



#### Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. In this test facility, the Antenna Factor, Cable Loss, and Amplifier Gains are loaded into the Rohde & Schwarz Receiver and the corrected field strength can be read directly on the receiver.

$$FS = R + AF + CORR$$

where:

FS = Field Strength

R = Measured Receiver Input Amplitude

AF = Antenna Factor

CORR = Correction Factor = CL - AG + NFL

CL = Cable Loss

AG = Amplifier Gain



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 68 of 83

---

For example:

Given a Receiver input reading of 51.5dB $\mu$ V; Antenna Factor of 8.5dB; Cable Loss of 1.3dB; Falloff Factor of 0dB, an Amplifier Gain of 26dB and Notch Filter Loss of 1dB. The Field Strength of the measured emission is:

$$FS = 51.5 + 8.5 + 1.3 - 26.0 + 1 = 36.3\text{dB}\mu\text{V/m}$$

Conversion between dB $\mu$ V/m (or dB $\mu$ V) and  $\mu$ V/m (or  $\mu$ V) are done as:

$$\text{Level (dB}\mu\text{V/m)} = 20 * \text{Log}(\text{level } (\mu\text{V/m}))$$

$$40 \text{ dB}\mu\text{V/m} = 100\mu\text{V/m}$$


$$48 \text{ dB}\mu\text{V/m} = 250\mu\text{V/m}$$

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

## Measurement Results for Spurious Emissions (30 MHz – 1 GHz)

Test Freq.	N/A	Engineer	CSB
Variant	Digital Emissions	Temp (°C)	24
Freq. Range	30 MHz - 1000 MHz	Rel. Hum. (%)	34
Power Setting	12V DC; AC Power Adaptor	Press. (mBars)	1005
Antenna	External		
Test Notes 1			
Test Notes 2			




### Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
33.030	45.8	3.4	-11.8	37.4	Quasi Peak	V	98	91	40	-2.6	Pass	DIG
76.132	42.3	3.9	-23.0	23.3	Quasi Peak	V	156	82	40	-16.8	Pass	DIG
215.982	57.3	4.8	-19.7	42.4	Quasi Peak	V	98	355	43.5	-1.1	Pass	DIG
287.765	39.4	5.2	-17.3	27.3	Peak [Scan]	V	156	82	46	-18.7	Pass	DIG
323.401	45.5	5.3	-16.2	34.7	Peak [Scan]	H	156	82	46	-11.4	Pass	DIG
504.568	35.8	6.0	-12.8	29.1	Peak [Scan]	V	156	82	46	-16.9	Pass	DIG
Legend: DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency												
NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### Measurement Results for Spurious Emissions (1GHz – 10GHz)

<b>Test Freq.</b>	N/A	<b>Engineer</b>	CSB
<b>Variant</b>	Digital Emissions	<b>Temp (°C)</b>	24
<b>Freq. Range</b>	1000 MHz - 6000 MHz	<b>Rel. Hum. (%)</b>	33
<b>Power Setting</b>	12V DC; AC Power Adaptor	<b>Press. (mBars)</b>	1000
<b>Antenna</b>	External		
<b>Test Notes 1</b>	Red Trace is Average Detector; Blue Trace is Peak detector (max for Horizontal and Vertical polarities)		
<b>Test Notes 2</b>			



### Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
No emissions were observed.												
Legend: DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

## Specification

### Limits

**§15.205 (a)** Except as shown in paragraph (d) of 15.205 (a), only spurious emissions are permitted in any of the frequency bands listed.

**§15.205 (a)** Except as shown in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

**§15.209 (a)** Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table.

### §15.209 (a) Limit Matrix

Frequency(MHz)	Field Strength ( $\mu$ V/m)	Field Strength (dB $\mu$ V/m)	Measurement Distance (meters)
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

### Laboratory Measurement Uncertainty for Radiated Emissions

Measurement uncertainty	+5.6/ -4.5 dB
-------------------------	---------------

### Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-03 'Measurement of Radiated Emissions'	0088, 0158, 0134, 0304, 0311, 0315, 0310, 0312

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


### **5.1.7. AC Wireline Conducted Emissions (0.15 – 30 MHz)**

**FCC, Part 15 Subpart C §15.207**  
**Industry Canada RSS-Gen §7.2.2**

#### **Test Procedure**

The EUT is configured in accordance with ANSI C63.4. The conducted emissions are measured in a shielded room with a spectrum analyzer in peak hold in the first instance. Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation. The highest emissions relative to the limit are listed.

#### **Test Measurement Set up**




Measurement set up for AC Wireline Conducted Emissions Test

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### Measurement Results for AC Wireline Conducted Emissions (150 kHz – 30 MHz)

Test Freq.	N/A	Engineer	CSB
Variant	AC Line Emissions	Temp (°C)	24
Freq. Range	0.150 MHz - 30 MHz	Rel. Hum.(%)	35
Power Setting	120V AC; 60Hz	Press. (mBars)	1004
Antenna	External		
Test Notes 1			
Test Notes 2			




#### Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	Factors dB	Level dBuV	Measurement Type	Line	Limit dBuV	Margin dB	Pass /Fail	Comments
0.197	24.4	9.9	0.1	34.4	Average	Live	53.74	-19.4	Pass	
0.197	34.4	9.9	0.1	44.4	Quasi Peak	Live	63.74	-19.4	Pass	
0.346	40.5	9.9	0.1	50.5	Quasi Peak	Neutral	59.06	-8.6	Pass	
0.346	29.4	9.9	0.1	39.4	Average	Neutral	49.06	-9.7	Pass	
0.393	42.1	9.9	0.1	52.0	Quasi Peak	Neutral	58	-6.0	Pass	
0.393	30.4	9.9	0.1	40.4	Average	Neutral	48	-7.6	Pass	
0.443	22.7	9.9	0.1	32.7	Average	Neutral	47.01	-14.3	Pass	
0.443	36.7	9.9	0.1	46.7	Quasi Peak	Neutral	57.01	-10.3	Pass	
0.555	34.3	9.9	0.1	44.3	Quasi Peak	Neutral	56	-11.7	Pass	
0.555	21.4	9.9	0.1	31.5	Average	Neutral	46	-14.6	Pass	
1.169	37.1	9.9	0.1	47.2	Quasi Peak	Neutral	56	-8.8	Pass	
1.169	22.3	9.9	0.1	32.3	Average	Neutral	46	-13.7	Pass	
Legend:		DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency								
		NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band								

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

<b>Test Freq.</b>	N/A	CSB
<b>Variant</b>	Telecom Line	24
<b>Freq. Range</b>	0.150 MHz - 30 MHz	35
<b>Power Setting</b>	120V AC; 60Hz	1004
<b>Antenna</b>	External	
<b>Test Notes 1</b>	Red Trace is Average Detector; Blue Trace is Peak detector	
<b>Test Notes 2</b>		



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 75 of 83

## Specification

### Limit

**§15.207 (a)** Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu\Omega$  line impedance stabilization network (LISN), see §15.207 (a) matrix below. Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.

### §15.207 (a) Limit Matrix

The lower limit applies at the boundary between frequency ranges

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency

### Laboratory Measurement Uncertainty for Conducted Emissions

Measurement uncertainty	$\pm 2.64$ dB
-------------------------	---------------


### Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-EMC-01 'Measurement of Conducted Emissions'	0158, 0184, 0193, 0190, 0293, 0307

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

## **6. TEST SET-UP PHOTOGRAPHS**

### **6.1. General Measurement Test Set-Up**



---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


## 6.2. General Measurement – Environmental Chamber



---


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6.3. Radiated Emissions below 1 GHz (1)



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


#### 6.4. Radiated Emissions Module Test Configuration



---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

## 6.5. Radiated Digital Emissions above 1 GHz



---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

## 6.6. AC Wireline Emissions



---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Sensus U905458B  
**To:** FCC 47 CFR Part(s) 24, 90, 101  
**Serial #:** SNUS06-U1 Rev A  
**Issue Date:** 17<sup>th</sup> December 2010  
**Page:** 82 of 83

## 7. TEST EQUIPMENT DETAILS

Asset #	Instrument	Manufacturer	Part #	Serial #
0088	Spectrum Analyzer	Hewlett Packard	8564E	3410A00141
0134	Amplifier	Com Power	PA 122	181910
0158	Barometer /Thermometer	Control Co.	4196	E2846
0193	EMI Receiver	Rhode & Schwartz	ESI 7	838496/007
0287	EMI Receiver	Rhode & Schwartz	ESIB 40	100201
0252	SMA Cable	Megaphase	Sucoflex 104	None
0310	2m SMA Cable	Micro-Coax	UFA210A-0-0787-3G03G0	209089-001
0312	3m SMA Cable	Micro-Coax	UFA210A-1-1181-3G0300	209092-001
0313	Coupler	Hewlett Packard	86205A	3140A01285
0314	30dB N-Type Attenuator	ARRA	N9444-30	1623
0070	Power Meter	Hewlett Packard	437B	3125U11552
0116	Power Sensor	Hewlett Packard	8485A	3318A19694
0117	Power Sensor	Hewlett Packard	8487D	3318A00371
0184	Pulse Limiter	Rhode & Schwartz	ESH3Z2	357.8810.52
0190	LISN	Rhode & Schwartz	ESH3Z5	836679/006
0293	BNC Cable	Megaphase	1689 1GVT4	15F50B001
0307	BNC Cable	Megaphase	1689 1GVT4	15F50B002
0335	1-18GHz Horn Antenna	ETS- Lindgren	3117	00066580
0104	1-18GHz Horn Antenna	EMCO	3115	9205-3882
0337	Amplifier	MiCOM Labs	--	--
0338	Antenna	Sunol Sciences	JB-3	A052907

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



440 Boulder Court, Suite 200  
Pleasanton, CA 94566, USA  
Tel: 1.925.462.0304  
Fax: 1.925.462.0306  
[www.micomlabs.com](http://www.micomlabs.com)