

SENSUS METERING SYSTEMS INC. RF EXPOSURE REPORT

SCOPE OF WORK

RF EXPOSURE CALCULATIONS – KV2C RADIO MODULE

REPORT NUMBER

106182196ATL-001

ISSUE DATE

05 June 2025

REVISION DATE

[N/A]

PAGES

8



DOCUMENT CONTROL NUMBER

Non-Specific Radio Report Shell Rev. December 2017

© 2017 INTERTEK

RF EXPOSURE REPORT

Report Number: 106182196ATL-009

Project Number: G106182196

Report Issue Date: 05 June 2025

Model / HVIN: FLEXKV2C

FCC ID: SDBFLEXKV2C

IC: 2220A-FLEXKV2C

Standards: FCC Title 47 CFR Parts 1.1307, 2.1091
RSS-102, Issue 6

Test Location

Intertek
1950 Evergreen Blvd., Suite 100
Duluth, GA 30096 USA
FCC Designation: US1046
CAB Designator: US0128

Client

Sensus Metering Systems Inc.
639 Davis Drive
Morrisville, NC 27560 USA

Report prepared by:



Jeremy Pickens / Senior Staff Engineer

Report reviewed by:



Brian Lackey / EMC Staff Engineer

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Table of Contents

1	<i>Introduction and Conclusion</i>	4
2	<i>Evaluation Summary</i>	4
3	<i>Client Information</i>	5
4	<i>Description of Equipment Under Test and Variant Models</i>	5
5	<i>FCC Routine Evaluation Exemption Criteria.....</i>	6
6	<i>ISED Routine Evaluation Exemption Criteria.....</i>	7
7	<i>Revision History.....</i>	8

1 Introduction and Conclusion

RF Exposure calculations were performed on the product constructed as described in Section 4. Information provided by the client including maximum output power, antenna gain(s), and minimum separation distance(s) was used to determine if the product under evaluation was exempt from routine evaluation. Any change in these stated values may invalidate these results. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted.

Based on the results of our investigation, we have concluded the product under evaluation is exempt from routine evaluation for each of the standard(s) indicated. The results obtained in this test report pertain only to the item(s) evaluated. Intertek does not make any claims of compliance for samples or variants which were not evaluated.

2 Evaluation Summary

Section	Test full name	Result
5	Routine Evaluation Exemption Criteria (FCC Title 47 CFR Part 1.1307, 2.1091)	Exempt
6	ISED Routine Evaluation Exemption Criteria (RSS-102 Issue 6)	Exempt

3 Client Information

This evaluation was performed at the request of:

Client: Sensus Metering Systems Inc.
639 Davis Drive
Morrisville, NC 27560 USA

Contact: James Francisco

Email: James.francisco@xylem.com

4 Description of Equipment Under Test and Variant Models

Manufacturer: Sensus Metering Systems Inc.
639 Davis Drive
Morrisville, NC 27560 USA

Equipment Under Test			
Description	Manufacturer	Model Number (HVIN)	Serial Number
Transceiver Module	Sensus Metering Systems Inc.	FLEXKV2C	083 ¹ 057 ²

- 1) Antenna port conducted measurements
- 2) Radiated spurious emissions measurements

Receive Date:	27 May 2025
Received Condition:	Good
Type:	Production

Description of Equipment Under Test

This transceiver module is a standard FlexNet protocol with FEM controlled output capable of 1W nominal conducted output power. The modular design enables Sensus partner with Aclara to locate the transceiver in several standard S form meters retailed to Utilities.

Certification Purpose

Class II Permissive Change: Sensus is updating the PCBA with a new Skyworks Front End Module (FEM), P/N: CC1120.

Equipment Under Test Power Configuration

Rated Voltage	Rated Current	Rated Frequency	Number of Phases
20Vdc	450mA	NA	NA

Radio/Receiver Characteristics

Frequency Range	901-960MHz
Modulation Type(s)	7-FSK, 13-FSK, 2-GFSK, 4-GFSK, 2-SFSK, 4-SFSK, 8-SFSK
Maximum Rated Output Power (Conducted):	30 +/- 1dBm
MIMO Information (# of Transmit and Receive antenna ports)	1 (SISO)
Equipment Type	Full Module
Antenna Type and Gain	Integral (-0.47dBi)
Device Category	Mobile
Environment	General Population/Uncontrolled Exposure

5 FCC Routine Evaluation Exemption Criteria

FCC Title 47 CFR Part 1.1307(3)(i)

For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

- (A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);
- (B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

5.1 Calculations

Channel (MHz)	Measured Conducted Power (dBm)	Max Tune Up Power		Antenna Gain		Separation Distance (m)	Result (mW/cm ²)	Limit (mW/cm ²)
		(dBm)	(W)	(dBi)	Numeric			
901.5	30.47	31	1.259	-0.47	0.897	0.2	0.2247	0.601
928.925	30.13	31	1.259	-0.47	0.897	0.2	0.2247	0.619
930.5	30.01	31	1.259	-0.47	0.897	0.2	0.2247	0.620
932.25	30.06	31	1.259	-0.47	0.897	0.2	0.2247	0.622
940.0125	29.92	31	1.259	-0.47	0.897	0.2	0.2247	0.627
941.4875	29.93	31	1.259	-0.47	0.897	0.2	0.2247	0.628
952.5	29.73	31	1.259	-0.47	0.897	0.2	0.2247	0.635
959.925	29.48	31	1.259	-0.47	0.897	0.2	0.2247	0.640

6 ISED Routine Evaluation Exemption Criteria

RSS-102 Issue 6 § 5.3.2: RF Exposure limits

The electric and magnetic field strength reference levels, power density reference levels, and associated reference period for devices employed by the general public (uncontrolled environment) and controlled-use devices (controlled environment) are specified in table 7 and table 8. Note that the power density limits specified in these tables apply to whole body exposure conditions.

Table 7: RF field strength and power density limits for devices used by the general public (uncontrolled environment)

Frequency range (MHz)	Electric field (V _{RMS} /m)	Magnetic field (A _{RMS} /m)	Power density (W/m ²)	Reference period (minutes)
10-20	27.46	0.0728	2	6
20-48	$58.07 / f^{0.25}$	$0.1540 / f^{0.25}$	$8.944 / f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	$3.142 f^{0.3417}$	$0.008335 f^{0.3417}$	$0.02619 f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	$616000 / f^{1.2}$
150000-300000	$0.158 f^{0.5}$	$4.21 \times 10^{-4} f^{0.5}$	$6.67 \times 10^{-5} f$	$616000 / f^{1.2}$

6.1 Calculations

Channel (MHz)	Measured Conducted Power (dBm)	Max Tune Up Power		Antenna Gain		Separation Distance (m)	Result (W/m ²)	Limit (W/m ²)
		(dBm)	(W)	(dBi)	Numeric			
901.5	30.47	31	1.259	-0.47	0.897	0.2	2.247	2.739
928.925	30.13	31	1.259	-0.47	0.897	0.2	2.247	2.795
930.5	30.01	31	1.259	-0.47	0.897	0.2	2.247	2.799
932.25	30.06	31	1.259	-0.47	0.897	0.2	2.247	2.802
940.0125	29.92	31	1.259	-0.47	0.897	0.2	2.247	2.818
941.4875	29.93	31	1.259	-0.47	0.897	0.2	2.247	2.821
952.5	29.73	31	1.259	-0.47	0.897	0.2	2.247	2.844
959.925	29.48	31	1.259	-0.47	0.897	0.2	2.247	2.859

7 Revision History

Revision Level	Date	Report Number	Prepared By	Reviewed By	Notes
0	05 June 2025	106182196ATL-009	JOP	BZ	Original Issue