



Excellence in Compliance Testing

---

## **Certification Exhibit**

**FCC ID: SDBVGBM4600  
IC: 2220A-VGBM4600**

**FCC Rule Part: CFR 47 Part 24 Subpart D, Part 101 Subpart C  
IC Radio Standards Specification: RSS 119, RSS 134**

**ACS Project Number: 11-2106**

Manufacturer: Sensus Metering Systems, Inc.  
Model: M4600

## **RF Exposure**

**General Information:**

Applicant: Sensus Metering Systems, Inc.  
 ACS Project: 11-2106  
 Device Category: Mobile  
 Environment: General Population/Uncontrolled Exposure

**Technical Information:**

Antenna Type: ASPG918 Elevated Feedpoint Antenna  
 Antenna Gain: 5.15 dBi  
 Maximum Transmitter Conducted Power: 34.58 dBm  
 Maximum System EIRP: 39.73 dBm, 9397.23 mW  
 Exposure Conditions: Greater than 35 centimeters

**MPE Calculation**

The Power Density (mW/cm<sup>2</sup>) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

MPE Calculator for Mobile Equipment							
Limits for General Population/Uncontrolled Exposure*							
Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm2)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm^2)
930.5	34.58	0.62	2870.78	5.15	3.273	35	0.610
940.0125	34.45	0.63	2786.12	5.15	3.273	35	0.592
928.925	34.54	0.62	2844.46	5.15	3.273	35	0.605
932.25	34.54	0.62	2844.46	5.15	3.273	35	0.605
941.4875	34.43	0.63	2773.32	5.15	3.273	35	0.590

**Installation Guidelines**

The installation manual should contain text similar to the following advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

**RF Exposure**

In accordance with FCC requirements of human exposure to radio frequency fields, the radiating element shall be installed such that a minimum separation distance of 35 centimeters will be maintained.

**Conclusion**

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.