

FCC RF EXPOSURE REPORT

FCC ID: SEP-CORE

Project No. : 1503C019
Equipment : Wireless Speaker System
Model : Core
Applicant : MASS FIDELITY
Address : 326 Adeliade Street West suite 400 Toronto ON
M5V 1R3 Canada

According: : FCC Guidelines for Human Exposure IEEE C95.1

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.
TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	PIFA	N/A	2.12

TEST RESULTS

EUT :	Wireless Speaker System	Model Name :	Core
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX Mode_1Mbps		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.12	1.6293	3.13	2.0559	0.00066673	1	Complies
2.12	1.6293	3.76	2.3768	0.00077082	1	Complies
2.12	1.6293	3.24	2.1086	0.00068383	1	Complies

Note: the calculated distance is 20 cm.