

Analysis Report

Report No.: 22100319HKG-001

The Equipment Under Test (EUT), is a portable 27MHz Transmitter for a RC Racer. The sample supplied operated on a single channel, 27.145MHz.

The EUT is powered by 2 x 1.5V AA batteries. After switching on the EUT, the car will be moved forward or backward based on the switches pressed in the controller.

Antenna Type: External, Dedicated Whip Antenna

Antenna Gain: 0dBi

Nominal rated field strength: 55.0dBμV/m at 3m

Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 58.0dBμV/m at 3m in frequency 27.145MHz, thus;

The worst case of SAR Exclusion Threshold Level for 27.145MHz when the minimum test separation distance is < 50mm:
= $[474 * (1 + \log_{10}(f(\text{MHz})))]/2$
= 371.2mW

According to the KDB 412172 D01:

$EIRP = [(FS * D)^2 * 1000 / 30]$

Calculated Field Strength for 371.2mW is 120.9dBuV/m @3m

Since maximum field strength plus production tolerance <= 120.9dBuV/m @3m and antenna gain is >= 0.0dBi, it is concluded that maximum Conducted Power and Field Strength are well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.