

700/800/900/1850 MHz

700/800/900/1850 MHz COILS/WHIPS

Model	Type	Frequency (MHz)	Gain (dBd/dBi)	Max Height (In)	Power Rating (Watts)	Whip Color	Cable Assembly	Conn
LM800	5/8 over 1/2 λ	806-866	3.5/5.6	14.5	200	Stainless	Order Separately	N/A
LM825	5/8 over 1/2 λ	824-896	3.5/5.6	14.5	200	Stainless	Order Separately	N/A
LM900	5/8 over 1/2 λ	890-960	3.5/5.6	14.5	200	Stainless	Order Separately	N/A
NMOQW700	1/4 λ	740-806	0/2	3	200	Stainless	Order Separately	N/A
NMOQW800	1/4 λ	806-896	0/2	3	200	Stainless	Order Separately	N/A
NMOQW900	1/4 λ	890-970	0/2	3	200	Stainless	Order Separately	N/A
NMQSPEC800B	1/4 λ	806-896	0/2	4	200	Black	Order Separately	N/A
NMQSPEC900B	1/4 λ	890-970	0/2	4	200	Black	Order Separately	N/A
NMQ700B	1/4 λ	740-806	0/2	4.5	200	Black	Order Separately	N/A
NMQ800B	1/4 λ	806-896	0/2	4.5	200	Black	Order Separately	N/A
NMQ900B	1/4 λ	890-960	0/2	4.5	200	Black	Order Separately	N/A
NMOSPEC800	5/8 over 1/4 λ	806-866	3.3/5.4	13.5	200	Stainless	Order Separately	N/A
NMOSPEC825	5/8 over 1/4 λ	824-896	3.3/5.4	13.5	200	Stainless	Order Separately	N/A
NMOSPEC900	5/8 over 1/4 λ	890-960	3.3/5.4	13.5	200	Stainless	Order Separately	N/A
NMO3HD800B	5/8 over 1/4 λ	806-866	3.3/5.4	13.75	200	Black	Order Separately	N/A
NMO3HD825B	5/8 over 1/4 λ	824-896	3.3/5.4	13.75	200	Black	Order Separately	N/A
NMO3HD800B	5/8 over 1/4 λ	890-960	3.3/5.4	13.75	200	Black	Order Separately	N/A
NMO3E700B	5/8 over 1/4 λ	740-806	3.3/5.4	13.5	200	Black	Order Separately	N/A
NMO3E800B	5/8 over 1/4 λ	806-866	3.3/5.4	13.5	200	Black	Order Separately	N/A
NMO3E825B	5/8 over 1/4 λ	824-896	3.3/5.4	13.5	200	Black	Order Separately	N/A
NMO3E900B	5/8 over 1/4 λ	890-960	3.3/5.4	13.5	200	Black	Order Separately	N/A
NMO700	5/8 over 1/2 λ	740-806	3.5/5.6	12.75	200	Stainless	Order Separately	N/A
NMO800	5/8 over 1/2 λ	806-866	3.5/5.6	12.75	200	Stainless	Order Separately	N/A
NMO825	5/8 over 1/2 λ	824-896	3.5/5.6	12.75	200	Stainless	Order Separately	N/A
NMO900	5/8 over 1/2 λ	890-960	3.5/5.6	12.75	200	Stainless	Order Separately	N/A
NMO800B	5/8 over 1/2 λ	806-866	3.5/5.6	12.75	200	Black	Order Separately	N/A
NMO825B	5/8 over 1/2 λ	824-896	3.5/5.6	12.75	200	Black	Order Separately	N/A
NMO900B	5/8 over 1/2 λ	890-960	3.5/5.6	12.75	200	Black	Order Separately	N/A
NMO5T800B	5/8 over 5/8 over 1/4 λ	806-866	5/7.2	18	200	Black	Order Separately	N/A
NMO5T825B	5/8 over 5/8 over 1/4 λ	824-896	5/7.2	18	200	Black	Order Separately	N/A
NMO5T900B	5/8 over 5/8 over 1/4 λ	890-960	5/7.2	18	200	Black	Order Separately	N/A
NMO5E825B	5/8 over 5/8 over 1/4 λ	824-896	5/7.2	19	200	Black	Order Separately	N/A
NMO5E900B	5/8 over 5/8 over 1/4 λ	890-960	5/7.2	19	200	Black	Order Separately	N/A
Q800	1/4 λ	806-866	0/2	3.5	200	Stainless	Order Separately	N/A
Q900	1/4 λ	890-960	0/2	3.5	200	Stainless	Order Separately	N/A



The most commonly used cable assembly/mount is the NMOKHFUD (27 MHz to 6 GHz) with 17' of UD (RG-58/U Dual Shield).

www.pulseelectronics.com/products/antennas

NOTE: Antennas are not to scale