

Techcorp Ltd.

Application
For
Certification

RF Wireless Controller (Receiver Module)

(FCC ID: SGFJS109HR1)

04073842
TL/ Sandy Lee
October 21, 2004

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report shall not be reproduced except in full without prior authorization from Intertek Testing Services Hong Kong Limited.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

Intertek Testing Services Hong Kong Ltd.

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.

Tel: (852) 2173 8888 Fax: (852) 2371 0521 Website: www.hk.intertek-etlsemko.com

INTERTEK TESTING SERVICES

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	Summary of Tests
<i>EXHIBIT 2:</i>	General Description
<i>EXHIBIT 3:</i>	System Test Configuration
<i>EXHIBIT 4:</i>	Measurement Results
<i>EXHIBIT 5:</i>	Equipment Photographs
<i>EXHIBIT 6:</i>	Product Labelling
<i>EXHIBIT 7:</i>	Technical Specifications
<i>EXHIBIT 8:</i>	Instruction Manual

INTERTEK TESTING SERVICES

MEASUREMENT/TECHNICAL REPORT

Techcorp Ltd. - MODEL: JOYTECH JS109HR1

FCC ID: SGFJS109HR1

October 21, 2004

This report concerns (check one) Original Grant ☒ Class II Change _____

Equipment Type: DSS, Part 15 Spread Spectrum Transmitter

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes _____ No ☒

If yes, defer until : _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued
on that date.

Transition Rules Request per 15.37? Yes _____ No ☒

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [12-08-03
Edition] provision.

Report prepared by:

Tommy Leung
Intertek Testing Services
2/F., Garment Centre,
576 Castle Peak Road,
Kowloon, Hong Kong.
Phone: 852-2173-8538
Fax: 852-2371-0521

INTERTEK TESTING SERVICES

Table of Contents

1.0	<u>Summary of test results</u>	2
2.0	<u>General Description</u>	4
2.1	Product Description	4
2.2	Related Submittal(s) Grants	5
2.3	Test Methodology	5
2.4	Test Facility	5
3.0	<u>System Test Configuration</u>	7
3.1	Justification	7
3.2	EUT Exercising Software	7
3.3	Support Equipment List and Description	8
3.4	Equipment Modification	9
4.0	<u>Measurement Results</u>	11
4.1	Maximum Conducted Output Power at Antenna Terminals	11
4.2	Minimum 6dB RF Bandwidth	12
4.3	Maximum Power Density	13
4.4	Out of Band Conducted Emissions	14
4.5	Out of Band Radiated Emissions	15
4.6	Transmitter Radiated Emissions in Restricted Bands	15
4.7	Field Strength Calculation	16
4.8	Radiated Emission Configuration Photograph	17
4.9	Radiated Emission Data	18
4.10	AC Line Conducted Emission	20
4.11	Line Conducted Configuration Photograph	21
4.12	Line Conducted Emission Configuration Data	22
4.13	Radiated Emission from Digital Section of Transceiver	23
4.14	Transmitter Duty Cycle Calculation and Measurements	25
5.0	<u>Equipment Photographs</u>	27
6.0	<u>Product Labelling</u>	29
7.0	<u>Technical Specifications</u>	31
8.0	<u>Instruction Manual</u>	33

INTERTEK TESTING SERVICES

List of attached file

Exhibit type	File Description	filename
Test Report	Test Report	report.pdf
Operation Description	Technical Description	descri.pdf
Test Setup Photo	Radiated Emission	radiated photos.doc
Test Report	6 dB Bandwidth Plot	b6dB.pdf
Test Report	Maximum Power Density Plot	bpowden.pdf
Test Report	Out Band Antenna Conducted Emission Plot	bobantcon.pdf
Test Report	Duty Cycle Calculation and Measurement	bdcc.pdf
Test Setup Photo	Conducted Emission	conducted photos.doc
Test Report	Conducted Emission Test Result	conduct.pdf
External Photo	External Photo	external photos.doc
Internal Photo	Internal Photo	internal photos.doc
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf

INTERTEK TESTING SERVICES

EXHIBIT 1

SUMMARY OF TEST RESULTS

INTERTEK TESTING SERVICES

1.0 Summary of Test

Techcorp Ltd. - MODEL: JOYTECH JS109HR1
FCC ID: SGFJS109HR1

TEST	REFERENCE	RESULTS
Max. Output power	15.247(b)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(d)	Pass
Out of Band Antenna Conducted Emission	15.247(c)	Pass
Radiated Emission in Restricted Bands	15.247(c)	Pass
AC Conducted Emission	15.207	Pass
Radiated Emission from Digital Part	15.109	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses a permanently attached antenna, which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

INTERTEK TESTING SERVICES

EXHIBIT 2

GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

2.0 General Description

2.1 Product Description

The Equipment Under Test (EUT) is a 2.4GHz Direct Sequence Spread Spectrum Transmitter operating at 2440.560MHz. It is a base unit which is part of the RF wireless controller system for PS2 and is connected to PS2 when use. It works with the hand-held unit (so called controller unit) to perform wireless keypad function when the ID setting of both units is the same.

During normal use, hand-held unit transmits "key data" to it so as to establish connection and send control commands. In return, it will transmit "ACK data" to the hand-held unit to confirm the connection. Upon received the control signal, it transfers the signal to PS2 and the game activities will be according to the key commands. Besides, it may transmit "motor data" to the handheld unit. The motor inside the hand-held unit will run and the hand-held unit will vibrate.

Antenna type: Internal, Integral

The circuit description is saved with filename: descri.pdf

INTERTEK TESTING SERVICES

2.2 Related Submittal(s) Grants

This is an application for Certification of a DSS-Part 15 Spread Spectrum Transmitter. The receiver portion associated with this transmitter is exempted from technical requirement of this Part.

The handheld unit associated with this EUT has FCC ID: SGFJS109HT1 and will be filed at the same time.

2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2001). All measurements were performed in Open Area Test Sites. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

2.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC.

INTERTEK TESTING SERVICES

EXHIBIT 3

SYSTEM TEST CONFIGURATION

INTERTEK TESTING SERVICES

3.0 System Test Configuration

3.1 Justification

For emission testing, the equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). During testing, all cables were manipulated to produce worst case emissions. It was connected to PS2. To set the EUT for continuous transmission, 500kbit/s signal, which was generated from the functional generator, was fed into the data pin of the RF module.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Detector function is in peak mode. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1MHz or greater for frequencies above 1000MHz.

Radiated emission measurement was performed from the lowest radio frequency signal generated in the device which is greater than 9kHz to 25GHz.

3.2 EUT Exercising Software

There was no special software to exercise the device. Once powered up, the unit transmits the typical signal. For simplicity of testing, the unit was set to transmit continuously.

INTERTEK TESTING SERVICES

3.3 Support Equipment List and Description

The FCC ID's for all equipment, plus descriptions of all cables used in the tested system (included inserted cards, which have grants) are:

HARDWARE:

The unit was operated with host unit and peripheral. Their description are listed below.

- (1) PS2
- (2) TV receiver
- (3) PS2 keypad

CABLES:

- (1) Signal Cable with BNC connector and crocodile clips (1.0m, unshielded)
- (2) TV Cable with AV connectors and PS2 connector (1.4m, unshielded)

OTHERS:

- (1) Functional generator

INTERTEK TESTING SERVICES

3.4 Equipment Modification


Any modifications installed previous to testing by Techcorp Ltd. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by ETL Division, Intertek Testing Services Hong Kong Ltd.

All the items listed under section 3.0 of this report are confirmed by:

Confirmed by:

*Tommy Leung
Supervisor
Intertek Testing Services Hong Kong Ltd.
Agent for Techcorp Ltd.*



Signature

October 21, 2004 Date

INTERTEK TESTING SERVICES

EXHIBIT 4

MEASUREMENT RESULTS

INTERTEK TESTING SERVICES

Applicant: Techcorp Ltd.
Model: JOYTECH JS109HR1

Date of Test: September 14, 2004

4.0 Measurement Results

4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b) :

- ☒ The antenna port of the EUT was connected to the input of a power meter. Power was read directly and cable loss correction was added to the reading to obtain power at the EUT antenna terminals.
- ☐ The antenna port of the EUT was connected to the input of a spectrum analyzer. The analyzer was set for RBW >6dB bandwidth and power was read directly in dBm. External attenuation and cable loss were compensated for using the OFFSET function of the analyzer.

For antennas with gains of 6 dBi or less, maximum allowed transmitter output is 1 watt (+30 dBm).

For antennas with gains greater than 6 dBi, transmitter output level must be decreased by an amount equal to (GAIN - 6) dBm.

Max. Antenna Gain = -20.6 dBi			
Frequency (MHz)	Output in dBm	Limit in dBm	Margin in dB
2440.560	4.5	30	-25.5
	Output in mWatt	Limit in mW	Margin mW
	2.8	1000	-997.2

Cable loss : 0.5 dB External Attenuation : 0 dB

Cable loss, external attenuation: ☐ included in OFFSET function
☒ added to power meter raw reading

For RF safety, the RF safety information is included in the instruction manual and is saved with filename: manual.pdf.

INTERTEK TESTING SERVICES

Applicant: Techcorp Ltd.
Model: JOYTECH JS109HR1

Date of Test: September 14, 2004

4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a)(2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Frequency (MHz)	6 dB Bandwidth (MHz)
2440.560	12.08

Refer to the following plots for 6 dB bandwidth data:

Plot B2: 6 dB RF Bandwidth

Limit: at least 500kHz

For electronic filing, the above plots are saved with filename: b6dB.pdf.

INTERTEK TESTING SERVICES

Applicant: Techcorp Ltd.
Model: JOYTECH JS109HR1

Date of Test: September 14, 2004

4.3 Maximum Power Density Reading, FCC Rule 15.247(d) :

The spectrum analyzer RES BW was set to 3 kHz. The START and STOP frequencies were set to the band edges of the maximum output passband. If there is no clear maximum amplitude in any given portion of the band, it may be necessary to make measurements at a number of bands defined by several START and STOP frequency pairs. The specification calls for a 1 second interval at each 3 kHz bandwidth; total SWEEP TIME is calculated as follows:

$$\text{SWEEP TIME (SEC)} = (\text{Fstop, kHz} - \text{Fstart, kHz}) / 3 \text{ kHz}$$

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Frequency (MHz)	Power Density (dBm)
2440.560	-15.39

Frequency Span = 2.4 MHz

Sweep Time = Frequency Span / 3 kHz = 800 seconds

Cable Loss: 0.5 dB

Limit: 8 dBm

Refer to the following plots for power density data :

Plot B3: Power density

For electronic filing, the above plots are saved with filename: bpowden.pdf.

INTERTEK TESTING SERVICES

Applicant: Techcorp Ltd.
Model: JOYTECH JS109HR1

Date of Test: September 14, 2004

4.4 Out of Band Conducted Emissions, FCC Rule 15.247(c):

In any 100 kHz bandwidth outside the EUT passband, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20dB below that of the maximum in-band 100 kHz emission, or else shall meet the general limits for radiated emissions at frequencies outside the passband, whichever results in lower attenuation.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the following plots for out of band conducted emissions data:

Plot B4a.1 - B4a.3: Modulation Products Emissions
Plot B4d.1 - B4d.2: Out of Band Emissions

The plots showed the 2nd harmonic and modulation products at the band edges of 2400 MHz and 2483.5 MHz. In addition, all spurious emission and up to the tenth harmonic was measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

For the electronic filing, the above plots are saved with filename: bobantcon.pdf.

INTERTEK TESTING SERVICES

Applicant: Techcorp Ltd.
Model: JOYTECH JS109HR1

Date of Test: September 14, 2004

4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 26dB below carrier), FCC Rule 15.247(c):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

- ☐ Not required
- ☒ See attached data sheet

4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b), (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

INTERTEK TESTING SERVICES

4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in dB μ V/m

RA = Receiver Amplitude (including preamplifier) in dB μ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$AV = -10 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

4.8 Radiated Emission Configuration Photograph

Worst Case Radiated Emission
at
976.228 MHz

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.doc.


INTERTEK TESTING SERVICES

4.9 Radiated Emission Data

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Judgement: Passed by 9.9 dB

TEST PERSONNEL:



Tester Signature

Ben W. K. Ho, Compliance Engineer
Typed/Printed Name

October 21, 2004
Date

INTERTEK TESTING SERVICES

Applicant: Techcorp Ltd.
Model: JOYTECH JS109HR1

Date of Test: September 14, 2004

Table 1

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Factor (-dB)	Peak at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	976.228	19.1	16	33.0	36.1	0.0	36.1	46.0	-9.9
V	1464.342	45.2	34	26.1	37.3	0.0	37.3	74.0	-36.7
V	3904.912	39.1	34	33.3	38.4	0.0	38.4	74.0	-35.6
V	4393.026	53.0	34	34.8	53.8	0.0	53.8	74.0	-20.2
V	4881.140	38.2	34	34.9	39.1	0.0	39.1	74.0	-34.9
V	7321.710	35.1	34	37.9	39.0	0.0	39.0	74.0	-35.0

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Factor (-dB)	Average at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	976.228	19.1	16	33.0	36.1	28.6	7.5	46.0	-38.5
V	1464.342	45.2	34	26.1	37.3	28.6	8.7	54.0	-45.3
V	3904.912	39.1	34	33.3	38.4	28.6	9.8	54.0	-44.2
V	4393.026	53.0	34	34.8	53.8	28.6	25.2	54.0	-28.8
V	4881.140	38.2	34	34.9	39.1	28.6	10.5	54.0	-43.5
V	7321.710	35.1	34	37.9	39.0	28.6	10.4	54.0	-43.6

NOTES: 1. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

2. Negative value in the margin column shows emission below limit.

3. Horn antenna was used for the emissions over 1000MHz.

Test Engineer: Ben W. K. Ho

INTERTEK TESTING SERVICES

Applicant: Techcorp Ltd.
Model: JOYTECH JS109HR1

Date of Test: September 14, 2004

4.10 AC Line Conducted Emission, FCC Rule 15.207:

☐ Not required; battery operation only

☒ Test data attached

INTERTEK TESTING SERVICES

4.11 Line Conducted Configuration Photograph

Worst Case Line-Conducted Emission
at
0.175 MHz

For electronic filing, the worst case line conducted configuration photographs are saved with filename: conducted photos.doc.

INTERTEK TESTING SERVICES


4.12 Line Conducted Emission Data

The data on the following pages list the significant emission frequencies, the limit, and the margin of compliance.

Judgement : Passed by 7.9 dB margin

For electronic filing, the worst case line conducted emission data are saved with filename: conduct.pdf

TEST PERSONNEL:



Tester Signature

Ben W. K. Ho, Compliance Engineer
Typed/Printed Name

October 21, 2004
Date

INTERTEK TESTING SERVICES

Applicant: Techcorp Ltd.
Model: JOYTECH JS109HR1

Date of Test: September 14, 2004

4.13 Radiated Emissions from Digital Section of Transceiver (Transmitter), FCC Ref:
15.109

☐ Not required - No digital part

☒ Test results are attached

INTERTEK TESTING SERVICES

Applicant: Techcorp Ltd.
Model: JOYTECH JS109HR1

Date of Test: September 14, 2004

Table 2

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	30.000	30.0	16	10.0	24.0	40.0	-16.0
V	36.001	30.6	16	10.0	24.6	40.0	-15.4
V	42.000	31.3	16	10.0	25.3	40.0	-14.7
V	48.000	31.0	16	11.0	26.0	40.0	-14.0
V	54.000	31.4	16	11.0	26.4	40.0	-13.6

- NOTES:
1. Quasi-peak detector is used for the emission below or equal to 1000MHz.
 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna and average detector are used for the emission over 1000MHz.

Test Engineer: Ben W. K. Ho

INTERTEK TESTING SERVICES

Applicant: Techcorp Ltd.
Model: JOYTECH JS109HR1

Date of Test: September 14, 2004

4.14 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The transmitter ON time was determined from the resultant time-amplitude display:

Duty cycle = Maximum ON time / duration
= 0.644ms / 17ms

Duty Cycle correction, dB = $20 \cdot \log(\text{Duty Cycle})$
= $20 \cdot \log(0.037)$
= -28.6 dB

	See attached spectrum analyzer chart (s) for transmitter timing Plot B5a.1-B5a.3
X	See transmitter timing diagram provided by manufacturer
	Not applicable, duty cycle was not used.

For electronic filing, the above plots are saved with filename: bdcc.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 5

EQUIPMENT PHOTOGRAPHS

INTERTEK TESTING SERVICES

5.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.doc & internal photos.doc.

INTERTEK TESTING SERVICES

EXHIBIT 6

PRODUCT LABELLING

INTERTEK TESTING SERVICES

6.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 7

TECHNICAL SPECIFICATIONS

INTERTEK TESTING SERVICES

7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

EXHIBIT 8
INSTRUCTION MANUAL

INTERTEK TESTING SERVICES

8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.