





## RF Exposure Evaluation Declaration

Applicant : SHENZHEN TENA ELECTRONIC CO., LTD.  
Product : Multi-Screen Interactive Device  
Model No. : S311A  
FCC ID : SGRS311A0001  
Standards : FCC Oet65 Supplement C June 2001  
Test Date : September 30, 2013 ~ November 01, 2013

Reviewed By :   
( Engineer: Sunny Sun )  
Approved By :   
( Manager: Marlin Chen )

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

## Revision History

| Report No.   | Version | Description    | Issue Date |
|--------------|---------|----------------|------------|
| 1309RSU00502 | Rev. 01 | Initial report | 2013-11-04 |
|              |         |                |            |

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range (MHz)                                     | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Average Time (Minutes) |
|-----------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| (A) Limits for Occupational/ Control Exposures            |                               |                               |                                     |                        |
| 300-1500                                                  | --                            | --                            | F/300                               | 6                      |
| 1500-100,000                                              | --                            | --                            | 5                                   | 6                      |
| (B) Limits for General Population/ Uncontrolled Exposures |                               |                               |                                     |                        |
| 300-1500                                                  | --                            | --                            | F/1500                              | 6                      |
| 1500-100,000                                              | --                            | --                            | 1                                   | 30                     |

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

## 1.3. Test Result of RF Exposure Evaluation

|           |                                 |
|-----------|---------------------------------|
| Product   | Multi-Screen Interactive Device |
| Test Item | RF Exposure Evaluation          |

Antenna Gain: The maximum Gain measured in fully anechoic chamber is -2.0dBi for 2.4GHz in logarithm scale.

### Output Power into Antenna:

| Test Mode          | Frequency Band (MHz) | Maximum output power to antenna (mW) | Limit of Power Density S(mW/cm <sup>2</sup> ) |
|--------------------|----------------------|--------------------------------------|-----------------------------------------------|
| 802.11b/g/n(20MHz) | 2412~2462            | 8.26                                 | 10                                            |
| 802.11n(40MHz)     | 2422~2452            | 9.04                                 | 10                                            |

Per FCC KDB 447498 D01v05r01, the SAR exclusion threshold for distances<50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Wi-Fi and the antenna to use separation distance, Wi-Fi SAR was not required;

$$[(9.04\text{mW}/5) * \sqrt{2.437}] = 2.82 < 3.0.$$

Note: When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

\_\_\_\_\_ The End \_\_\_\_\_