

RF TEST REPORT



Report No.: 14070694-FCC-R1

Supersede Report No.: N/A

Applicant	Chongqing JINOUE Science and Technology Development Co.,Ltd.	
Product Name	JO Bluetooth Low Energy Module(BLE)	
Model No.	JO-BLE02	
Test Standard	FCC Part 15.247: 2014, ANSI C63.10: 2013; IC RSS-210: Issue 8, December 2010; IC RSS-Gen: Issue 4, November 2014; ANSI C63.10: 2013	
Test Date	December 19 to December 23, 2014	
Issue Date	December 24, 2014	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification	☒	
Equipment did not comply with the specification	☐	
		
Wiky Jam Test Engineer	Alex Liu Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	14070694-FCC-R1
Page	3 of 36

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	7
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	8
6.1 ANTENNA REQUIREMENT	8
6.2 DTS (6 DB) CHANNEL BANDWIDTH	9
6.3 MAXIMUM OUTPUT POWER	11
6.4 POWER SPECTRAL DENSITY	13
6.5 BAND-EDGE & UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS.....	15
6.6 AC POWER LINE CONDUCTED EMISSIONS	18
6.7 RADIATED SPURIOUS EMISSIONS	22
6.8 RADIATED SPURIOUS EMISSIONS & RESTRICTED BANDS (RX).....	26
ANNEX A. TEST INSTRUMENT.....	29
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	30
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	32
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	35
ANNEX E. DECLARATION OF SIMILARITY	36

1. Report Revision History

Report No.	Report Version	Description	Issue Date
14070694-FCC-R1	NONE	Original	December 24, 2014

2. Customer information

Applicant Name	Chongqing JINOUE Science and Technology Development Co.,Ltd.
Applicant Add	Huaxuan Road 108#, Hi-Tech Development Zone, Chongqing, 400041, P.R.China
Manufacturer	Chongqing JINOUE Science and Technology Development Co.,Ltd.
Manufacturer Add	Huaxuan Road 108#, Hi-Tech Development Zone, Chongqing, 400041, P.R.China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Labview of SIEMIC version 2.0

4. Equipment under Test (EUT) Information

Description of EUT: JO Bluetooth Low Energy Module(BLE)

Main Model: JO-BLE02

Serial Model: N/A

Date EUT received: December 18, 2014

Test Date(s): December 19 to December 23, 2014

Equipment Category : DTS

Antenna Gain: BLE: 0.5 dBi

Type of Modulation: BLE: GFSK

RF Operating Frequency (ies): BLE: 2402-2480 MHz

Max. Power: BLE: 0.429 dBm

Number of Channels: BLE: 40CH

Port: Power Port

Trade Name :



GPRS/EGPRS Multi-slot class N/A

FCC ID: SI8JO-BLE02

IC ID: 12627A-JOBLE02

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	IC Rules	Description of Test	Result
§15.203	-	Antenna Requirement	Compliance
§15.247 (a)(2)	RSS-210 [A8.2] RSS-Gen	DTS (6 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	RSS-210 [A8.4]	Conducted Maximum Output Power	Compliance
§15.247(e)	RSS-210 [A8.2]	Power Spectral Density	Compliance
§15.247(d)	RSS-210 [A8.5]	Band-Edge & Unwanted Emissions into Non-Restricted Frequency Bands	Compliance
§15.207 (a)	RSS-Gen	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	RSS-210 [A8.5]	Radiated Spurious Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance
-	RSS-Gen	Radiated Spurious Emissions & Restricted Bands(Rx)	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one antenna:


A Chip antenna for BLE, the gain is 0.5 dBi.

The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 DTS (6 dB) Channel Bandwidth

Temperature	20°C
Relative Humidity	59%
Atmospheric Pressure	1011mbar
Test date :	December 23, 2014
Tested By :	Wiky Jam

Spec	Item	Requirement	Applicable
§ 15.247(a)(2) RSS-210[A8.2] RSS-Gen[4.6.1]	a)	6dB BW≥ 500kHz;	☒
	b)	99% BW: For FCC reference only; required by IC.	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	558074 D01 DTS MEAS Guidance v03r02, 8.1 DTS bandwidth <u>6dB Emission bandwidth measurement procedure</u> - Set RBW = 100 kHz. - Set the video bandwidth (VBW) ≥ 3 ´ RBW. - Detector = Peak. - Trace mode = max hold. - Sweep = auto couple. - Allow the trace to stabilize. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Measurement result

Test Data

CH	Freq (MHz)	6dB Bandwidth (kHz)	Occupied Bandwidth (MHz)	Limit (MHz)	Result
Low	2402	687.879	1.1206	≥ 0.5	Pass
Mid	2440	716.033	1.0947	≥ 0.5	Pass
High	2480	719.077	1.0877	≥ 0.5	Pass

Test Plots




6.3 Maximum Output Power

Temperature	20°C
Relative Humidity	59%
Atmospheric Pressure	1011mbar
Test date :	December 23, 2014
Tested By :	Wiky Jam

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (2), RSS210 (A8.4)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	☐
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	☐
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	☐
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	☐
	e)	FHSS in 902-928MHz with ≥ 25 & <50 channels: ≤ 0.25 Watt	☐
	f)	DSSS in 902-928MHz, 2400-2483.5MHz, 5725-5850MHz: ≤ 1 Watt	☒

Test Setup	 Spectrum Analyzer EUT
Test Procedure	558074 D01 DTS MEAS Guidance v03r02, 9.1.2 Integrated band power method Maximum output power measurement procedure - Set the RBW $\geq$ DTS bandwidth. - Set VBW $\geq 3 \times$ RBW. - Set span $\geq 3 \times$ RBW - Sweep time = auto couple. - Detector = peak. - Trace mode = max hold. - Allow trace to fully stabilize. - Use peak marker function to determine the peak amplitude level.
Remark	

Result	☒ Pass	☐ Fail
--------	--	-------------------------------

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Output Power measurement result

Test Data


Type	CH	Freq (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	Low	2402	0.429	30	Pass
	Mid	2440	-0.313	30	Pass
	High	2480	-0.795	30	Pass

Test Plots



6.4 Power Spectral Density

Temperature	20°C
Relative Humidity	59%
Atmospheric Pressure	1011mbar
Test date :	December 23, 2014
Tested By :	Wiky Jam

Spec	Item	Requirement	Applicable
§15.247(e) RSS-210 [A8.2]	a)	The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	558074 D01 DTS MEAS Guidance v03r02, 10.2 power spectral density method power spectral density measurement procedure - a) Set analyzer center frequency to DTS channel center frequency. - b) Set the span to 1.5 times the DTS bandwidth. - c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. - d) Set the VBW $\geq 3 \times \text{RBW}$. - e) Detector = peak. - f) Sweep time = auto couple. - g) Trace mode = max hold. - h) Allow trace to fully stabilize. - i) Use the peak marker function to determine the maximum amplitude level within the RBW. - j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Power Spectral Density measurement result

Test Data

Type	CH	Freq (MHz)	PSD (dBm)	Limit (dBm)	Result
PSD	Low	2402	-7.796	8	Pass
	Mid	2440	-9.055	8	Pass
	High	2480	-10.240	8	Pass


Test Plots



6.5 Band-Edge & Unwanted Emissions into Non-Restricted Frequency Bands

Temperature	20°C
Relative Humidity	60%
Atmospheric Pressure	1010mbar
Test date :	December 22, 2014
Tested By :	Wiky Jam

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d) RSS-210 [A8.5]	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	☒
Test Setup			
Test Procedure	Radiated Method Only 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.		


Test Report No.	14070694-FCC-R1
Page	16 of 36

	- 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	☒ Pass ☐ Fail


Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A

Test Plots

Band Edge measurement result




Date: 22.DEC.2014 10:17:13




Date: 22.DEC.2014 10:07:22

Band Edge, Left Side (Average))

Band Edge, Left Side (Peak)



Date: 22.DEC.2014 10:24:02



Date: 22.DEC.2014 10:21:46

Band Edge, Right Side (Average


Band Edge, Right Side (Peak)

6.6 AC Power Line Conducted Emissions

Temperature	18°C
Relative Humidity	63%
Atmospheric Pressure	1007mbar
Test date :	December 19, 2014
Tested By :	Wiky Jam

Requirement(s):

Spec	Item	Requirement	Applicable		
47CFR§15.207, RSS-Gen (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	☒		
		Frequency ranges (MHz)		Limit (dBµV)	
				QP	Average
		0.15 ~ 0.5		66 – 56	56 – 46
		0.5 ~ 5		56	46
5 ~ 30	60	50			

Test Setup	 Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.
------------	---

Procedure	- The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. - The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. - The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss
-----------	---


Test Report No.	14070694-FCC-R1
Page	19 of 36

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Transmitting Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

Frequency (MHz)	Quasi Peak (dBμV)	Limit (dBμV)	Margin (dB)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Factors (dB)
3.02	36.99	56.00	-19.01	28.66	46.00	-17.34	10.63
3.74	34.32	56.00	-21.68	24.94	46.00	-21.06	10.76
3.98	34.81	56.00	-21.19	27.17	46.00	-18.83	10.81
0.86	34.97	56.00	-21.03	27.05	46.00	-18.95	10.37
1.38	35.30	56.00	-20.70	27.81	46.00	-18.19	10.33
3.50	33.73	56.00	-22.27	21.86	46.00	-24.14	10.71

Test Mode: Transmitting Mode



Test Data

Phase Neutral Plot at 120Vac, 60Hz


Frequency (MHz)	Quasi Peak (dBμV)	Limit (dBμV)	Margin (dB)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Factors (dB)
3.02	40.61	56.00	-15.39	29.43	46.00	-16.57	10.63
3.98	35.16	56.00	-20.84	26.48	46.00	-19.52	10.81
2.78	37.68	56.00	-18.32	27.71	46.00	-18.29	10.58
3.74	37.81	56.00	-18.19	26.40	46.00	-19.60	10.76
3.50	35.96	56.00	-20.04	26.07	46.00	-19.93	10.71
1.00	33.60	56.00	-22.40	20.87	46.00	-25.13	10.29

6.7 Radiated Spurious Emissions

Temperature	18°C
Relative Humidity	63%
Atmospheric Pressure	1007mbar
Test date :	December 19, 2014
Tested By :	Wiky Jam

Requirement(s):

Spec	Item	Requirement	Applicable										
47CFR§15.247(d), RSS210 [A8.5]	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges <table><tr><th>Frequency range (MHz)</th><th>Field Strength (µV/m)</th></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table>	Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	☒
	Frequency range (MHz)	Field Strength (µV/m)											
	30 – 88	100											
	88 – 216	150											
216 960	200												
Above 960	500												
b)	For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required ☒ 20 dB down ☐ 30 dB down	☒											
c)	or restricted band, emission must also comply with the radiated emission limits specified in 15.209	☒											

Test Setup	
Procedure	- The EUT was switched on and allowed to warm up to its normal operating condition. - The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: - Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. - The EUT was then rotated to the direction that gave the maximum emission. - Finally, the antenna height was adjusted to the height that gave the maximum emission. - The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz. - The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	Different RF configuration has been evaluated but not much difference was found. The data presented here is the worst case data with EUT under 802.11n – HT20-2437MHz mode.
Result	☒ Pass ☐ Fail


Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Transmitting Mode

(Below 1GHz)

Peak Detector 
Quasi Peak Limit 



Test Data

Vertical & Horizontal Polarity Plot @3m

Frequency (MHz)	Quasi Peak (dBμV/m)	Azimuth	Polarity (H/V)	Height (cm)	Factors (dB)	Limit (dBμV/m)	Margin (dB)
831.01	38.94	34.00	V	141.00	3.89	46.00	-7.06
815.39	30.24	121.00	H	355.00	3.69	46.00	-15.76
816.91	36.60	95.00	H	100.00	3.71	46.00	-9.40
39.51	23.75	312.00	V	102.00	-7.14	40.00	-16.25
790.26	30.69	109.00	H	231.00	3.19	46.00	-15.31
840.99	32.09	110.00	H	101.00	4.01	46.00	-13.91

Test Mode:	Transmitting Mode
------------	-------------------

(Above 1GHz)

Note: Other modes were verified, only the result of worst case basic rate mode was presented.

Low Channel (2402 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre- Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4804	33.77	AV	V	33.83	4.87	24	48.47	54	-5.53
4804	34.09	AV	H	33.83	4.87	24	48.79	54	-5.21
4804	42.02	PK	V	33.83	4.87	24	56.72	74	-17.28
4804	41.87	PK	H	33.83	4.87	24	56.57	74	-17.43

Middle Channel (2440 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre- Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4880	34.92	AV	V	33.86	4.87	24	49.65	54	-4.35
4880	33.27	AV	H	33.86	4.87	24	48	54	-6.0
4880	41.84	PK	V	33.86	4.87	24	56.57	74	-17.43
4880	42.37	PK	H	33.86	4.87	24	57.1	74	-16.90

High Channel (2480 MHz)


Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre- Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4960	33.56	AV	V	33.9	4.87	24	48.33	54	-5.67
4960	34.72	AV	H	33.9	4.87	24	49.49	54	-4.51
4960	42.04	PK	V	33.9	4.87	24	56.81	74	-17.19
4960	41.93	PK	H	33.9	4.87	24	56.7	74	-17.30

6.8 Radiated Spurious Emissions & Restricted Bands (Rx)

Temperature	20°C
Relative Humidity	60%
Atmospheric Pressure	1010mbar
Test date :	December 22, 2014
Tested By :	Wiky Jam

Requirement(s):

Spec	Item	Requirement	Applicable
47CFR§ 15.247(d), RSS210 [A8.5]	a)	If the receiver is super-regenerative, stabilize it by coupling to it an unmodulated carrier on the receiver frequency (antenna conducted measurement) or by transmitting an unmodulated carrier on the receiver frequency from an antenna in the proximity of the receiver (radiated measurement). Taking care not to overload the receiver, vary the amplitude and frequency of the stabilizing signal to obtain the highest level of the spurious emissions from the receiver. For either method, the search for spurious emissions shall be from the lowest frequency internally generated or used in the receiver (e.g. local oscillator, intermediate or carrier frequency), or 30 MHz, whichever is higher, to at least 3 times the highest tuneable or local oscillator frequency, whichever is higher, without exceeding 40 GHz. For emissions below 1000 MHz, measurements shall be performed using a CISPR quasi-peak detector and the related measurement bandwidth. As an alternative to CISPR quasi-peak measurement, compliance with the emission limit can be demonstrated using measuring equipment employing a peak detector function properly adjusted for factors such as pulse desensitization as required, with an equal or greater measurement bandwidth relative to the	


		applicable CISPR quasi-peak bandwidth. Above 1000 MHz, measurements shall be performed using an average detector with a minimum resolution bandwidth of 1 MHz.	
Test Setup			
Procedure	The receiver shall be operated in the normal receive mode near the mid-point of the band in which the receiver is designed to operate. Radiated emission measurements are to be performed on a test site registered with Industry Canada. As an alternative, the conducted measurement method may be used when the antenna is detachable. In such a case, the receiver spurious signal may be measured at the antenna port. Radiated Emissions Measurement Uncertainty All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 1GHz & 1GHz above (3m & 10m) is +/-6dB.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Transmitting Mode

(Below 1GHz)



Test Data

Vertical & Horizontal Polarity Plot @3m


Frequency (MHz)	Quasi Peak (dBuV/m)	Azimuth	Polarity (H/V)	Height (cm)	Factors (dB)	Limit (dBuV/m)	Margin (dB)
830.95	32.65	62.00	V	270.00	3.88	46.00	-13.35
815.87	37.13	95.00	H	118.00	3.69	46.00	-8.87
815.39	34.78	116.00	H	100.00	3.69	46.00	-11.22
791.47	27.25	172.00	H	347.00	3.23	46.00	-18.75
232.42	35.25	109.00	H	133.00	-7.65	46.00	-10.75
838.20	33.74	110.00	H	193.00	3.98	46.00	-12.26

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/18/2014	09/17/2015	☒
Line Impedance	LI-125A	191106	09/26/2014	09/25/2015	☒
Line Impedance	LI-125A	191107	09/26/2014	09/25/2015	☒
LISN	ISN T800	34373	09/26/2014	09/25/2015	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/25/2014	09/24/2015	☒
Transient Limiter	LIT-153	531118	09/02/2014	09/01/2015	☒
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/18/2014	09/17/2015	☒
Power Splitter	1#	1#	09/02/2014	09/01/2015	☒
DC Power Supply	E3640A	MY40004013	09/18/2014	09/17/2015	☒
Radiated Emissions					
EMI test receiver	ESL6	100262	09/18/2014	09/17/2015	☒
Positioning Controller	UC3000	MF780208282	11/20/2014	11/19/2015	☒
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/02/2014	09/01/2015	☒
Microwave Preamplifier (0.5 ~ 18GHz)	PAM-118	443008	09/02/2014	09/01/2015	☒
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/22/2014	09/21/2015	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/25/2014	09/24/2015	☒
Universal Radio Communication Tester	CMU200	121393	09/26/2014	09/25/2015	☒

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT Photo




Annex B.ii. Photograph: Test Setup Photo




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above 1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions



Test Report No.	14070694-FCC-R1
Page	34 of 36

Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Manufacturer	Equipment Description	Model	Calibration Date	Calibration Due Date
Lenovo	Lenovo Laptop	E40& 0579A52	N/A	N/A

Test Report No.	14070694-FCC-R1
Page	35 of 36

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment

Test Report No.	14070694-FCC-R1
Page	36 of 36

Annex E. DECLARATION OF SIMILARITY

N/A