



FCC RF Exposure Evaluation

1. Product Information

FCC ID : SI9ELITE10QH
EUT : TABLET
Test Model : ELITE10QH
Power Supply : Input: 5.0V==2500mA
For AC Adapter Input: 100-240V~, 50/60Hz, 0.68A Max
For AC Adapter Output: 5.0V==2500mA
DC 3.8V by Rechargeable Li-ion Battery, 5000mAh
Hardware Version : D607P-v1
Software Version : /

Bluetooth

Frequency Range : 2402MHz-2480MHz
Bluetooth Channel Number : 79 Channels for Bluetooth V4.1(DSS)
40 channels for Bluetooth V4.1(DTS)
Bluetooth Channel Spacing : 1MHz for Bluetooth V4.1(DSS)
2MHz for Bluetooth V4.1(DTS)
Bluetooth Modulation Type : GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V4.1(DSS)
GFSK for Bluetooth V4.1 (DTS)
Bluetooth Version : V4.1
Antenna Description : PIFA Antenna, 1.61dBi (max.)

2.4G WLAN

Frequency Range : 2412MHz-2462MHz
Channel Number : 11 Channels for 20MHz bandwidth(2412~2462MHz)
7 Channels for 40MHz bandwidth(2422~2452MHz)
Channel Spacing : 5MHz
Modulation Type : IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK)
IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK)
IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description : PIFA Antenna, 1.61dBi (max.)

5.2G WLAN

Frequency Range : 5180MHz-5240MHz
Channel Number : 4 channels for 20MHz bandwidth(5180MHz-5240MHz)
2 channels for 40MHz bandwidth(5190MHz~5230MHz)
1 channels for 80MHz bandwidth(5210MHz)
Modulation Type : IEEE 802.11a/n/ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description : PIFA Antenna, 1.06dBi (max.)

5.8G WLAN



Frequency Range	: 5745MHz-5825MHz
Channel Number	: 5 channels for 20MHz bandwidth(5745MHz-5825MHz) 2 channels for 40MHz bandwidth(5755MHz~5795MHz) 1 channels for 80MHz bandwidth(5775MHz)
Modulation Type	: IEEE 802.11a/n/ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: PIFA Antenna, 1.13dBi (max.)
Exposure category	: General population/uncontrolled environment
EUT Type	: Production Unit
Device Type	: Portable Device



2. Evaluation method and Limit

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: “Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.²² The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc.”
[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] · [√f (GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.

When one of the following test exclusion conditions is satisfied for all combinations of simultaneous transmission configurations, further equipment approval is not required to incorporate transmitter modules in host devices that operate in the mixed mobile and portable host platform exposure conditions. The grantee is responsible for documenting this according to Class I permissive change requirements. Antennas that qualify for standalone SAR test exclusion must apply the estimated standalone SAR to determine simultaneous transmission test exclusion.

- a) The $[\sum \text{ (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance) / 1.6 W/kg}] + [\sum \text{ of MPE ratios}]$ is ≤ 1.0 .
- b) The SAR to peak location separation ratios of all simultaneously transmitting antenna pairs operating in portable device exposure conditions are all ≤ 0.04 , and the $[\sum \text{ of MPE ratios}]$ is ≤ 1.0 .

3. Refer Evaluation Method

[ANSI C95.1–1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1093](#): Radiofrequency radiation exposure evaluation: portable devices



4. Conducted Power Results

[BT Max Conducted Power]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	5.31
	39	2441	5.57
	78	2480	3.93
$\pi/4$ DQPSK	0	2402	4.58
	39	2441	4.93
	78	2480	3.28
8DPSK	0	2402	4.59
	19	2440	4.87
	39	2480	3.29

[BLE Max Conducted Power]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
BT LE	0	2402	-3.32
	19	2440	-3.23
	39	2480	-4.52

[2.4GWIFI Max Conducted Power]

Mode	Channel	Meas.Level [dBm]	Limit [dBm]	Verdict
11B	2412	8.77	30	PASS
	2437	8.78	30	PASS
	2462	8.48	30	PASS
11G	2412	8.49	30	PASS
	2437	8.72	30	PASS
	2462	8.03	30	PASS
11N20SISO	2412	8.44	30	PASS
	2437	8.82	30	PASS
	2462	8.19	30	PASS
11N40SISO	2422	8.47	30	PASS
	2437	8.68	30	PASS
	2452	8.39	30	PASS



[5.2GWIFI Max Conducted Power]

Test Mode	Channel	Frequency (MHz)	AVG Conducted Power (dBm)	Duty Cycle Factor(d B)	Report Conducted Power(dBm)	Limit (dBm)	Verdict
11A	36	5180	7.57	0	7.57	24	Pass
	40	5200	7.71	0	7.71		Pass
	48	5240	7.75	0	8.37		Pass
11N20 SISO	36	5180	7.11	0	7.11	24	Pass
	40	5200	7.39	0	7.39		Pass
	48	5240	7.61	0	7.61		Pass
11N40 SISO	38	5190	7.54	0	7.54	24	Pass
	46	5230	7.49	0	7.49		Pass
11AC20 SISO	36	5180	7.79	0	7.79	24	Pass
	40	5200	7.25	0	7.25		Pass
	48	5240	7.98	0	7.98		Pass
11AC40 SISO	38	5190	6.50	0	6.50	24	Pass
	46	5230	7.51	0	7.51		Pass
11AC80 SISO	42	5210	7.63	0	7.63	24	Pass



[5.8WIFI Max Conducted Power]

Test Mode	Channel	Frequency (MHz)	AVG Conducted Power (dBm)	Duty Cycle Factor(dB)	Report Conducted Power(dBm)	Limit (dBm)	Verdict
11A	149	5745	6.99	0	6.99	30	Pass
	157	5785	6.83	0	6.83		Pass
	165	5825	6.56	0	6.56		Pass
11N20 SISO	149	5745	6.25	0	6.25	30	Pass
	157	5785	6.44	0	6.44		Pass
	165	5825	6.22	0	6.22		Pass
11N40 SISO	151	5755	6.48	0	6.48	30	Pass
	159	5795	6.77	0	6.77		Pass
11AC20 SISO	149	5745	6.88	0	6.88	30	Pass
	157	5785	6.74	0	6.74		Pass
	165	5825	6.49	0	6.49		Pass
11AC40 SISO	151	5755	6.57	0	6.57	30	Pass
	159	5795	6.96	0	6.96		Pass
11AC80 SISO	155	5775	6.51	0	6.51	30	Pass

5. Manufacturing Tolerance

BT			
GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	5.0	5.0	3.0
Tolerance \pm (dB)	1.0	1.0	1.0
π/4DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	4.0	4.0	3.0
Tolerance \pm (dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	4.0	4.0	3.0
Tolerance \pm (dB)	1.0	1.0	1.0



BLE

BT LE (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	-3.0	-3.0	-4.0
Tolerance \pm (dB)	1.0	1.0	1.0

2.4GWIFI

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	8.0	8.0	8.0
Tolerance \pm (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	8.0	8.0	8.0
Tolerance \pm (dB)	1.0	1.0	1.0
11N20SISO (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	8.0	8.0	8.0
Tolerance \pm (dB)	1.0	1.0	1.0
11N40SISO (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	8.0	8.0	8.0
Tolerance \pm (dB)	1.0	1.0	1.0



5.2GWIFI

11A (Peak)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	7.0	7.0	7.0
Tolerance \pm (dB)	1.0	1.0	1.0
11N20 SISO (Peak)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	7.0	7.0	7.0
Tolerance \pm (dB)	1.0	1.0	1.0
11N40 SISO (Peak)			
Channel	Channel 38		Channel 46
Target (dBm)	7.0		7.0
Tolerance \pm (dB)	1.0		1.0
11AC20 SISO (Peak)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	7.0	7.0	7.0
Tolerance \pm (dB)	1.0	1.0	1.0
11AC40 SISO (Peak)			
Channel	Channe38		Channel 46
Target (dBm)	6.0		7.0
Tolerance \pm (dB)	1.0		1.0
11AC80 SISO (Peak)			
Channel	Channel 42		
Target (dBm)	7.0		
Tolerance \pm (dB)	1.0		



5.8GWIFI

11A (Peak)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	6.0	6.0	6.0
Tolerance \pm (dB)	1.0	1.0	1.0
11N20 SISO (Peak)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	6.0	6.0	6.0
Tolerance \pm (dB)	1.0	1.0	1.0
11N40 SISO (Peak)			
Channel	Channel 151		Channel 159
Target (dBm)	6.0		6.0
Tolerance \pm (dB)	1.0		1.0
11AC20 SISO (Peak)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	6.0	6.0	6.0
Tolerance \pm (dB)	1.0	1.0	1.0
11AC40 SISO (Peak)			
Channel	Channe151		Channel 159
Target (dBm)	6.0		6.0
Tolerance \pm (dB)	1.0		1.0
11AC80 SISO (Peak)			
Channel	Channel 155		
Target (dBm)	6.0		
Tolerance \pm (dB)	1.0		



6. Evaluation Results

6.1 Standalone Evaluation

BT

Band/Mode	f (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
			dBm	mW		
GFSK	2.441	5	6.0	3.9811	1.2440<3.0	Yes
$\pi/4$ DQPSK	2.441	5	5.0	3.1623	0.9881<3.0	Yes
8DPSK	2.441	5	5.0	3.1623	0.9881<3.0	Yes

BLE

Band/Mode	f (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
			dBm	mW		
BLE	GFSK	2.440	5	-2.0	0.6310	0.1971<3.0

2.4GWIFI

Band/Mode	f (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
			dBm	mW		
IEEE 802.11b	2.437	5	9.0	7.9433	2.4800<3.0	Yes
IEEE 802.11g	2.437	5	9.0	7.9433	2.4800<3.0	Yes
IEEE 802.11n HT20	2.437	5	9.0	7.9433	2.4800<3.0	Yes
IEEE 802.11n HT40	2.437	5	9.0	7.9433	2.4800<3.0	Yes

5.2GWIFI

Band/Mode	f (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
			dBm	mW		
11A	5.240	5	8.0	6.3096	2.8887<3.0	Yes
11N20 SISO	5.240	5	8.0	6.3096	2.8887<3.0	Yes
11N40 SISO	5.190	5	8.0	6.3096	2.8748<3.0	Yes
11AC20 SISO	5.240	5	8.0	6.3096	2.8887<3.0	Yes
11AC40 SISO	5.230	5	8.0	6.3096	2.8859<3.0	Yes
11AC80 SISO	5.210	5	8.0	6.3096	2.8804<3.0	Yes

5.8GWIFI

Band/Mode	f (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
			dBm	mW		
11A	5.745	5	7.0	5.0119	2.4026<3.0	Yes
11N20 SISO	5.745	5	7.0	5.0119	2.4026<3.0	Yes
11N40 SISO	5.795	5	7.0	5.0119	2.4130<3.0	Yes
11AC20 SISO	5.745	5	7.0	5.0119	2.4026<3.0	Yes
11AC40 SISO	5.795	5	7.0	5.0119	2.4130<3.0	Yes
11AC80 SISO	5.775	5	7.0	5.0119	2.4088<3.0	Yes



6.2 Simultaneous Transmission for SAR Exclusion

Not Applicable

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

.....THE END OF REPORT.....