

1-4F, Huafeng Science Park, Xin'an Sixth Road, 82th District,
Bao'an, Shenzhen, China.
Telephone: +86-755-29451282,
Fax: +86-755-22639141

Report No.: EBO1508096-E262
Page: 1 of 25

FCC REPORT

Applicant: VISUAL LAND INC.

Address of Applicant: 17785 Center Court Dr. Suite 670, Cerritos, CA 90703

Equipment Under Test (EUT)

Product Name: 8INCH TABLET

Trade Mark: VISUAL LAND

Model No.: ME-8QI

FCC ID: SI9PRESTIGE8QI

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249:2014

Date of sample receipt: September 01, 2015

Date of Test: September 02, 2015 To September 22, 2015

Date of report issued: September 23, 2015

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Kevin Yu
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the EBO product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of EBO International Electrical Approvals or testing done by EBO International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by EBO International Electrical Approvals in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

2 Version

Version No.	Date	Description
00	September 23, 2015	Original

Prepared By:



Date:

September 23, 2015

Project Engineer

Check By:



Date:

September 23, 2015

Reviewer

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.ebotek.cn> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.ebotek.cn>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST MODE	7
5.4 DESCRIPTION OF SUPPORT UNITS	7
5.5 TEST FACILITY.....	7
5.6 TEST LOCATION	7
5.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	7
6 TEST INSTRUMENTS LIST.....	8
7 TEST RESULTS AND MEASUREMENT DATA.....	10
7.1 ANTENNA REQUIREMENT:.....	10
7.2 CONDUCTED EMISSIONS	11
7.3 RADIATED EMISSION METHOD	14
7.3.1 Field Strength of The Fundamental Signal	16
7.3.2 Spurious emissions.....	17
7.3.3 Bandedge emissions.....	21
7.4 20dB OCCUPY BANDWIDTH.....	23
8 TEST SETUP PHOTO	25
9 EUT CONSTRUCTIONAL DETAILS	25

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Pass: The EUT complies with the essential requirements in the standard.

All test are according to ANSI C63.4:2014 and ANSI C63.10:2013

5 General Information

5.1 Client Information

Applicant:	VISUAL LAND INC.
Address of Applicant:	17785 Center Court Dr. Suite 670, Cerritos, CA 90703
Manufacturer/Factory:	VISUAL LAND INC.
Address of Manufacturer/Factory:	17785 Center Court Dr. Suite 670, Cerritos, CA 90703

5.2 General Description of EUT

Product Name:	8INCH TABLET
Trade Mark:	VISUAL LAND
Model No.:	ME-8QI
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	40
Channel separation:	2MHz
Modulation type:	GFSK
Antenna Type:	Integral Antenna
Antenna gain:	0.4dBi (declare by Applicant)
Power supply:	DC 5V, 2100mA Or DC 3.7V, 3500mAh Li-ion Battery Adapter: Model:SW-050210 Input:100-240V~,50/60Hz,0.68A Max Output:5Vdc, 2100mA

Channel list							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	11	2422MHz	21	2442MHz	31	2462MHz
2	2404MHz	12	2424MHz	22	2444MHz	32	2464MHz
...
9	2418MHz	19	2438MHz	29	2458MHz	39	2478MHz
10	2420MHz	20	2440MHz	30	2460MHz	40	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2440MHz
The Highest channel	2480MHz

5.3 Test mode

Transmitting mode	Keep the Bluetooth in continuously transmitting mode
<i>Remark: 1. During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

5.4 Description of Support Units

None.

5.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 28, 2013.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, June 26, 2013.

5.6 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District, Shenzhen, China

5.7 Other Information Requested by the Customer

None.

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Mar. 29 2014	Mar. 28 2016
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	Spectrum Analyzer	Agilent	E4440A	GTS533	July 08 2015	July 07 2016
4	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	July 08 2015	July 07 2016
5	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	July 08 2015	July 07 2016
6	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	July 08 2015	July 07 2016
7	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 27 2015	Mar. 26 2016
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial Cable	GTS	N/A	GTS213	Mar. 27 2015	Mar. 26 2016
10	Coaxial Cable	GTS	N/A	GTS211	Mar. 27 2015	Mar. 26 2016
11	Coaxial Cable	GTS	N/A	GTS210	Mar. 27 2015	Mar. 26 2016
12	Coaxial Cable	GTS	N/A	GTS212	Mar. 27 2015	Mar. 26 2016
13	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	July 08 2015	July 07 2016
14	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	July 08 2015	July 07 2016
15	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	July 08 2015	July 07 2016
16	Band filter	Amindeon	82346	GTS219	Mar. 27 2015	Mar. 26 2016
17	Power Meter	Anritsu	ML2495A	GTS540	July 08 2015	July 07 2016
18	Power Sensor	Anritsu	MA2411B	GTS541	July 08 2015	July 07 2016

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.0(L)x3.0(W)x3.0(H)	GTS264	July 08 2015	July 07 2016
2	EMI Test Receiver	Rohde & Schwarz	ESCS30	GTS223	July 08 2015	July 07 2016
3	10dB Pulse Limita	Rohde & Schwarz	N/A	GTS224	July 08 2015	July 07 2016
4	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	July 08 2015	July 07 2016
5	LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	GTS226	July 08 2015	July 07 2016
6	Coaxial Cable	GTS	N/A	GTS227	July 08 2015	July 07 2016
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory	Cal.Date	Cal.Due date

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.ebtek.cn> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.ebtek.cn>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

				No.	(mm-dd-yy)	(mm-dd-yy)
1	Barometer	ChangChun	DYM3	GTS257	July 08 2015	July 07 2016


This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.ebotek.cn> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.ebotek.cn>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

7 Test results and Measurement Data

7.1 Antenna requirement:

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	
<i>The antenna is Integral antenna, the best case gain of the antenna is 0.4dBi</i>	


7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207																
Test Method:	ANSI C63.10:2013																
Test Frequency Range:	150KHz to 30MHz																
Class / Severity:	Class B																
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto																
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>			Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
5-30	60	50															
	* Decreases with the logarithm of the frequency.																
Test setup:	 <p><i>Remark:</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>																
Test procedure:	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4:2013 on conducted measurement. 																
Test Instruments:	Refer to section 6.0 for details																
Test mode:	Refer to section 5.3 for details																
Test results:	Pass																

Measurement data:


This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.ebtek.cn> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.ebtek.cn>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

Test mode:	Bluetooth mode	LINE
------------	----------------	------



Condition	FCC PART15 CLASSB QP LISN-2013 LINE							
	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	
	MHz	dBuV		dB	dBuV	dBuV	dB	Remark
1	0.307	37.73	0.11	0.10	37.94	60.06	-22.12	QP
2	0.307	27.49	0.11	0.10	27.70	50.06	-22.36	Average
3	0.521	44.42	0.12	0.11	44.65	56.00	-11.35	QP
4	0.521	35.05	0.12	0.11	35.28	46.00	-10.72	Average
5	1.141	42.07	0.13	0.13	42.33	56.00	-13.67	QP
6	1.141	30.54	0.13	0.13	30.80	46.00	-15.20	Average
7	2.133	40.85	0.12	0.15	41.12	56.00	-14.88	QP
8	2.133	30.07	0.12	0.15	30.34	46.00	-15.66	Average
9	10.342	40.79	0.30	0.19	41.28	60.00	-18.72	QP
10	10.342	29.31	0.30	0.19	29.80	50.00	-20.20	Average
11	16.398	45.13	0.39	0.22	45.74	60.00	-14.26	QP
12	16.398	30.51	0.39	0.22	31.12	50.00	-18.88	Average

Test mode:	Bluetooth mode		NEUTRAL
------------	----------------	--	---------




Condition : FCC_PART15 CLASSB QP LISN-2013 NEUTRAL
 Read LISN Cable Limit Over
 Freq Level Factor Loss Level Line Limit Remark

	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.322	41.31	0.06	0.10	41.47	59.66	-18.19	QP
2	0.322	27.88	0.06	0.10	28.04	49.66	-21.62	Average
3	0.541	47.07	0.07	0.11	47.25	56.00	-8.75	QP
4	0.541	32.39	0.07	0.11	32.57	46.00	-13.43	Average
5	1.094	40.30	0.08	0.13	40.51	56.00	-15.49	QP
6	1.094	26.09	0.08	0.13	26.30	46.00	-19.70	Average
7	1.552	39.84	0.09	0.14	40.07	56.00	-15.93	QP
8	1.552	23.92	0.09	0.14	24.15	46.00	-21.85	Average
9	2.554	37.74	0.10	0.15	37.99	56.00	-18.01	QP
10	2.554	23.57	0.10	0.15	23.82	46.00	-22.18	Average
11	11.080	36.92	0.29	0.20	37.41	60.00	-22.59	QP
12	11.080	20.38	0.29	0.20	20.87	50.00	-29.13	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7.3 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209								
Test Method:	ANSI C63.10:2013								
Test Frequency Range:	30MHz to 25GHz								
Test site:	Measurement Distance: 3m								
Receiver setup:	Frequency	Detector	RBW	VBW	Remark				
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value				
	Above 1GHz	Peak	1MHz	3MHz	Peak Value				
Limit: (Field strength of the fundamental signal)		Peak	1MHz	10Hz	Average Value				
Frequency	Limit (dBuV/m @3m)		Remark						
2400MHz-2483.5MHz	94.00		Average Value						
	Limit: (Spurious Emissions)		114.00		Peak Value				
For fundamental test, the RBW and VBW were set to 3MHz and 10MHz. Peak detector for peak value, Average detector for average value									
Frequency	Limit (dBuV/m @3m)		Remark						
30MHz-88MHz	40.00		Quasi-peak Value						
88MHz-216MHz	43.50		Quasi-peak Value						
216MHz-960MHz	46.00		Quasi-peak Value						
Limit: (band edge)	960MHz-1GHz	54.00		Quasi-peak Value					
	Above 1GHz	54.00		Average Value					
		74.00		Peak Value					
Test setup:	Below 1GHz								
									
	Above 1GHz								

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.ebotek.cn> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.ebotek.cn>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 7. The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test worst case mode is recorded in the report.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Measurement data:

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.ebotek.cn> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.ebotek.cn>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

7.3.1 Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	91.65	27.58	5.39	30.18	94.44	114.00	-19.56	Vertical
2402.00	88.98	27.58	5.39	30.18	91.77	114.00	-22.23	Horizontal
2440.00	90.46	27.55	5.43	30.06	93.38	114.00	-20.62	Vertical
2440.00	87.63	27.55	5.43	30.06	90.55	114.00	-23.45	Horizontal
2480.00	89.71	27.52	5.47	29.93	92.77	114.00	-21.23	Vertical
2480.00	87.16	27.52	5.47	29.93	90.22	114.00	-23.78	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	80.04	27.58	5.39	30.18	82.83	94.00	-11.17	Vertical
2402.00	77.44	27.58	5.39	30.18	80.23	94.00	-13.77	Horizontal
2440.00	78.86	27.55	5.43	30.06	81.78	94.00	-12.22	Vertical
2440.00	76.13	27.55	5.43	30.06	79.05	94.00	-14.95	Horizontal
2480.00	77.69	27.52	5.47	29.93	80.75	94.00	-13.25	Vertical
2480.00	75.05	27.52	5.47	29.93	78.11	94.00	-15.89	Horizontal

7.3.2 Spurious emissions

■ Below 1GHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
35.13	36.04	14.35	0.61	30.07	20.93	40.00	-19.07	Vertical
52.76	36.41	15.12	0.80	29.98	22.35	40.00	-17.65	Vertical
87.73	40.33	13.18	1.09	29.76	24.84	40.00	-15.16	Vertical
134.56	43.67	10.56	1.47	29.49	26.21	43.50	-17.29	Vertical
178.76	42.03	11.62	1.73	29.28	26.10	43.50	-17.40	Vertical
234.99	39.01	13.83	2.05	29.52	25.37	46.00	-20.63	Vertical
62.00	31.98	13.90	0.88	29.91	16.85	40.00	-23.15	Horizontal
129.02	38.34	11.12	1.43	29.52	21.37	43.50	-22.13	Horizontal
172.60	44.46	11.16	1.70	29.31	28.01	43.50	-15.49	Horizontal
222.95	45.32	13.30	1.98	29.41	31.19	46.00	-14.81	Horizontal
318.82	38.07	15.33	2.46	29.89	25.97	46.00	-20.03	Horizontal
668.14	30.96	20.69	3.97	29.23	26.39	46.00	-19.61	Horizontal

■ Above 1GHz

Test channel:	Lowest
---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	36.09	31.78	8.60	32.09	44.38	74.00	-29.62	Vertical
7206.00	38.22	36.15	11.65	32.00	54.02	74.00	-19.98	Vertical
9608.00	36.30	37.95	14.14	31.62	56.77	74.00	-17.23	Vertical
12010.00	28.68	39.08	15.03	35.51	47.28	74.00	-26.72	Vertical
14412.00	*					74.00		Vertical
4804.00	36.36	31.78	8.60	32.09	44.65	74.00	-29.35	Horizontal
7206.00	42.56	36.15	11.65	32.00	58.36	74.00	-15.64	Horizontal
9608.00	30.74	37.95	14.14	31.62	51.21	74.00	-22.79	Horizontal
12010.00	29.04	39.08	15.03	35.51	47.64	74.00	-26.36	Horizontal
14412.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	26.65	31.78	8.60	32.09	34.94	54.00	-19.06	Vertical
7206.00	28.44	36.15	11.65	32.00	44.24	54.00	-9.76	Vertical
9608.00	26.49	37.95	14.14	31.62	46.96	54.00	-7.04	Vertical
12010.00	18.79	39.08	15.03	35.51	37.39	54.00	-16.61	Vertical
14412.00	*					54.00		Vertical
4804.00	26.79	31.78	8.60	32.09	35.08	54.00	-18.92	Horizontal
7206.00	32.54	36.15	11.65	32.00	48.34	54.00	-5.66	Horizontal
9608.00	21.55	37.95	14.14	31.62	42.02	54.00	-11.98	Horizontal
12010.00	18.30	39.08	15.03	35.51	36.90	54.00	-17.10	Horizontal
14412.00	*					54.00		Horizontal

Remark:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “**”, means this data is the too weak instrument of signal is unable to test.

Test channel:	Middle
---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	38.24	31.85	8.66	32.12	46.63	74.00	-27.37	Vertical
7320.00	36.87	36.37	11.72	31.89	53.07	74.00	-20.93	Vertical
9760.00	31.74	38.35	14.25	31.59	52.75	74.00	-21.25	Vertical
12200.00	29.42	38.92	15.14	35.65	47.83	74.00	-26.17	Vertical
14652.00	*					74.00		Vertical
4880.00	36.59	31.85	8.66	32.12	44.98	74.00	-29.02	Horizontal
7320.00	41.25	36.37	11.72	31.89	57.45	74.00	-16.55	Horizontal
9760.00	30.59	38.35	14.25	31.59	51.60	74.00	-22.40	Horizontal
12200.00	28.30	38.92	15.14	35.65	46.71	74.00	-27.29	Horizontal
14652.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	27.93	31.85	8.66	32.12	36.32	54.00	-17.68	Vertical
7320.00	31.72	36.37	11.72	31.89	47.92	54.00	-6.08	Vertical
9760.00	20.82	38.35	14.25	31.59	41.83	54.00	-12.17	Vertical
12200.00	18.89	38.92	15.14	35.65	37.30	54.00	-16.70	Vertical
14652.00	*					54.00		Vertical
4880.00	28.21	31.85	8.66	32.12	36.60	54.00	-17.40	Horizontal
7320.00	27.00	36.37	11.72	31.89	43.20	54.00	-10.80	Horizontal
9760.00	22.16	38.35	14.25	31.59	43.17	54.00	-10.83	Horizontal
12200.00	19.43	38.92	15.14	35.65	37.84	54.00	-16.16	Horizontal
14652.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. **, means this data is the too weak instrument of signal is unable to test.

Test channel:	Highest							
---------------	---------	--	--	--	--	--	--	--

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	35.00	31.93	8.73	32.16	43.50	74.00	-30.50	Vertical
7440.00	33.91	36.59	11.79	31.78	50.51	74.00	-23.49	Vertical
9920.00	33.12	38.81	14.38	31.88	54.43	74.00	-19.57	Vertical
12400.00	28.68	38.76	15.27	35.27	47.44	74.00	-26.56	Vertical
14880.00	*					74.00		Vertical
4960.00	33.94	31.93	8.73	32.16	42.44	74.00	-31.56	Horizontal
7440.00	39.31	36.59	11.79	31.78	55.91	74.00	-18.09	Horizontal
9920.00	28.96	38.81	14.38	31.88	50.27	74.00	-23.73	Horizontal
12400.00	29.69	38.76	15.27	35.27	48.45	74.00	-25.55	Horizontal
14880.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	25.07	31.93	8.73	32.16	33.57	54.00	-20.43	Vertical
7440.00	24.59	36.59	11.79	31.78	41.19	54.00	-12.81	Vertical
9920.00	23.75	38.81	14.38	31.88	45.06	54.00	-8.94	Vertical
12400.00	19.22	38.76	15.27	35.27	37.98	54.00	-16.02	Vertical
14880.00	*					54.00		Vertical
4960.00	23.79	31.93	8.73	32.16	32.29	54.00	-21.71	Horizontal
7440.00	29.38	36.59	11.79	31.78	45.98	54.00	-8.02	Horizontal
9920.00	19.55	38.81	14.38	31.88	40.86	54.00	-13.14	Horizontal
12400.00	19.61	38.76	15.27	35.27	38.37	54.00	-15.63	Horizontal
14880.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. **, means this data is the too weak instrument of signal is unable to test.

7.3.3 Bandedge emissions*All of the restriction bands were tested, and only the data of worst case was exhibited.*

Test channel:	Lowest							
---------------	--------	--	--	--	--	--	--	--

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	46.15	27.91	5.30	30.37	48.99	74.00	-25.02	Vertical
2390.00	45.75	27.59	5.38	30.18	48.54	74.00	-25.46	Vertical
2400.00	50.26	27.58	5.39	30.18	53.05	74.00	-20.95	Vertical
2310.00	46.16	27.91	5.30	30.37	49.00	74.00	-25.00	Horizontal
2390.00	46.20	27.59	5.38	30.18	48.99	74.00	-25.01	Horizontal
2400.00	47.44	27.58	5.39	30.18	50.23	74.00	-23.78	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	35.73	27.91	5.30	30.37	38.57	54.00	-15.43	Vertical
2390.00	35.39	27.59	5.38	30.18	38.18	54.00	-15.82	Vertical
2400.00	37.41	27.58	5.39	30.18	40.20	54.00	-13.80	Vertical
2310.00	35.72	27.91	5.30	30.37	38.56	54.00	-15.44	Horizontal
2390.00	35.47	27.59	5.38	30.18	38.26	54.00	-15.74	Horizontal
2400.00	36.13	27.58	5.39	30.18	38.92	54.00	-15.08	Horizontal

Test channel:	Highest							
---------------	---------	--	--	--	--	--	--	--

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	47.11	27.53	5.47	29.93	50.18	74.00	-23.82	Vertical
2500.00	45.10	27.55	5.49	29.93	48.21	74.00	-25.79	Vertical
2483.50	44.77	27.53	5.47	29.93	47.84	74.00	-26.16	Horizontal
2500.00	45.31	27.55	5.49	29.93	48.42	74.00	-25.58	Horizontal

Average value:


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	34.93	27.53	5.47	29.93	38.00	54.00	-16.00	Vertical
2500.00	33.87	27.55	5.49	29.93	36.98	54.00	-17.02	Vertical
2483.50	35.19	27.53	5.47	29.93	38.26	54.00	-15.74	Horizontal
2500.00	33.79	27.55	5.49	29.93	36.90	54.00	-17.10	Horizontal

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.ebotek.cn> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.ebotek.cn>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

7.4 20dB Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10:2013
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass


Measurement Data

Test channel	20dB bandwidth(MHz)	Result
Lowest	1.201	Pass
Middle	1.200	Pass
Highest	1.208	Pass


Test plot as follows:



Lowest channel



Middle channel



Highest channel

8 Test Setup Photo

Refer to test setup photos.

9 EUT Constructional Details

Refer to EUT external and internal photos.

-----End-----