



210-3 Yungduck-Ri, Kihung-Eup, Yongin-Si, Kyungki-Do, South Korea 449-908

TEL : (82)31-206-4693 FAX : (82)31-206-3051

<http://www.kesilab.com>

[webmaster@kesilab.com](mailto:webmaster@kesilab.com)

<http://www.koreaemc.co.kr>

[webmaster@koreaemc.co.kr](mailto:webmaster@koreaemc.co.kr)

## **CERTIFICATE OF COMPLIANCE**

### **(CLASS B)**

**CERTIFICATION OF COMPLIANCE** is hereby issued to the named Applicant and is **VALID ONLY** for the equipment identified below:

**Date of Tested : Sep. 06. 2004**

**Applicant's Name : MBN Partners Co., Ltd.**

**Applicant's Address : 2Na-406 Sihwa Industrial Complex 1268-5 Jeongwang-Dong,  
Siheung-City, Kyunggi-Do, Korea**

**Manufacturer's Name : MBN Partners Co., Ltd.**

**Manufacturer's Address : 2Na-406 Sihwa Industrial Complex 1268-5 Jeongwang-Dong,  
Siheung-City, Kyunggi-Do, Korea**

**Declares that the product**

**Product Description : USB DRIVE**

**Brand Name : MBN Partners**

**Model Number : SPEEDMBN-ONE**

**(Memory size is 16 MB, 32 MB, 64 MB, 128 MB, 256 MB, 512 MB and 1 GB)**

**FCC ID : SIA-SPEEDMBN**

Conforms to FCC Rules and Regulations Part 15 Subpart B requirements.

This product herewith complies with the requirements of the FCC Rules and Regulations as listed below:

Part 15.107: Conducted Emissions.

Part 15.109: Radiated Spurious Emissions.

TESTED and CERTIFIED by:

### **KOREA EMC LABORATORY**

210-3 Yungduck-Ri, Kihung-Eup,  
Yongin-Si, Kyungki-Do,  
South, Korea

**Date : Sep. 07. 2004**

**Report No : KEL04-F08064**

**Authorized Signature :**

**M. S. CHO / President**

## TABLE OF CONTENTS

| <b>DESCRIPTION</b>                                     | <b>Page</b> |
|--|-------------|
| 0. VERIFICATION OF COMPLIANCE                          | 3           |
| 1. GENERAL INFORMATION                                 |             |
| 1.1 Product Description                                | 4           |
| 1.2 Related Submittal(s)/Grant(s)                      | 4           |
| 1.3 Tested System Details                              | 4           |
| 1.4 System Configuration                               | 4           |
| 1.5 General Setup of the test Shield room              | 5           |
| 1.6 Test Facility                                      | 5           |
| 2. Measurement Procedure                               |             |
| 2.1 System test configuration                          | 6           |
| 2.1.1 Video mode Justification                         | 6           |
| 2.1.2 EUT Exercise S/W                                 | 6           |
| 2.2 Special Accessories                                | 6           |
| 2.3 Equipment Modification                             | 6           |
| 2.4 Connected Cable                                    | 6           |
| 2.5 System Configuration Diagram                       | 6           |
| 2.6 Preliminary testing                                | 7           |
| 2.7 Shielded Enclosure                                 | 7           |
| 2.8 Data Reporting Format                              | 7           |
| 2.9 Operating Condition                                | 7           |
| 2.10 Conditioning of the EUT                           | 7           |
| 2.11 Power Line Conducted Emissions                    | 8           |
| 2.12 Open field Radiated Emissions Tests               | 8           |
| 3. Measurement Data                                    |             |
| 3.1 Conducted Emission Data                            | 9           |
| 3.2 Conducted Emission Graph                           | 10-11       |
| 3.3 Radiated Emission Data                             | 12          |
| 3.4 Summary  | 13          |
| 4. Labeling Requirement                                | 14          |
| Appendix   |             |
| - A : Test set-up Photographs (Conducted and Radiated) |             |
| - B : External Photographs of E.U.T                    |             |
| - C : Internal Photographs of E.U.T                    |             |
| - D : FCC ID label location information and sample     |             |
| - E : Block Diagram                                    |             |
| - F : User's Manual                                    |             |

## 0 . VERIFICATION OF COMPLIANCE

Equipment Under Test : USB DRIVE

Model Number : SPEEDMBN-ONE  
(Memory size is 16MB, 32MB, 64MB, 128MB, 256MB, 512MB and 1GB)

Serial Number : Prototype

Manufacturer : MBN Partners Co., Ltd.  
2Na-406 Sihwa Industrial Complex 1268-5 Jeongwang-Dong,  
Siheung-City, Kyunggi-Do, Korea

Type of Test : FCC CLASS B

Report Number : KEL04-F08064

Date Tested : Sep. 06. 2004

Tested By : S.J.KIM

The results show that the sample equipment tested as described in this reports is in compliance with the CLASS B conducted and radiated emission limits of FCC Rules Part 15, Subpart B.

## 1. GENERAL INFORMATION

### 1.1 PRODUCT DESCRIPTION

The SPEEDMBN-ONE is a USBDRIVE made by MBN Partners Co., Ltd. in Korea. Refer to the user's manual for more information.

| ITEM      | SPECIFICATION                      |
|-----------|------------------------------------|
| I/O Port  | USB                                |
| Dimension | 6.0 x 2.1 x 1.0 cm                 |
| Speed     | Read : 9 MB/sec<br>Write: 7 MB/sec |

<Model Differences>

The difference(s) compared to the EUT is as follow:

| Model        | Memory size   | Model Differences                                 |
|--------------|---|---|
| SPEEDMBN-ONE | 1 GB<br>512 MB<br>256 MB<br>128 MB<br>64 MB<br>32 MB<br>16 MB | Only type designation by a memory size of the EUT |

### 1.2 Related Submittal(s)/Grant(s)

N/A

### 1.3 Tested System Details

| Type         | Model Name    | FCC ID       | Serial NO              | Manufacturer                 |
|--------------|---------------|--------------|------------------------|------------------------------|
| USB DRIVE    | SPEEDMBN-ONE  | SIA-SPEEDMBN | Prototype              | MBN Partners Co., Ltd.       |
| Desk Book    | TGIC-NP2400PA | DoC          | 9146TZ101032100124K000 | SAMBO                        |
| Adapter      | ADP-150BB B   | Verification | VBT0321010509          | Delta Electronics Inc.       |
| Monitor      | TGIC-LC1710P  | DoC          | FHUJ350009181          | Proview Technology Co., Ltd. |
| Adapter      | DTA-SXGA03    | Verification | AFS03000409            | D-TECH                       |
| Printer      | 2225C+        | DSI6XU2225   | 3119S96116             | HP                           |
| Adapter      | PW118         | Verification | KA1202F52              | AULT INC.                    |
| Mouse        | M-S48a        | JNZ201213    | LZA94853128            | LOGITECH                     |
| USB Mouse    | M-BJ558       | DoC          | HCA40500459            | LOGITECH                     |
| Serial Mouse | M-CE15-9F     | DZLMCE15     | LT292R00285            | LOGITECH                     |

### 1.4 System Configuration

| Type     | Model Name  | Serial NO | Manufacturer           | Remark |
|----------|-------------|-----------|------------------------|--------|
| MAIN B/D | SPEEDMBN-ON | NONE      | MBN Partners Co., Ltd. | Korea  |

## 1.5 General Set-up of the Test Shielded Room

The EUT was set up in accordance with the suggested configuration given in FCC measurement Procedure ANSI C63.4 2000. The measurement are performed in the shielded room which dimension is 3.0\*7.0\*2.5(m). The EUT was placed on a non conductive table which is 1.0\*1.5(m), 80 cm above an earthed ground plane and is kept at least 1m from any other earthed ground plane except the rear of table top being removed 40 cm from a vertical conducting plane.

Power to the EUT was provided through the LISN(NSLK8128, SCHWARZBECK) which has the Impedance vs Frequency Characteristic in accordance with the conducted setup photographs in Appendix-A Impedance Characteristic of LISN. Peripheral equipment required to provide a functional system(support equipment) for EUT testing was powered through another LISN(ESH3-Z5, Rohde & Schwarz).

Power to the LISN was filtered to eliminate ambient signal interference. A coaxial type connector which provides a 50 Ohm terminating impedance was provided for the test instrument. The excess length of the power cord was wrapped in the two non metallic pegs attached to the top of the LISN. The two pegs are 9 cm high, approximately 2.0 cm in diameter and that are spaced 6 cm on the center apart.

## 1.6 Test Facility

Location: Korea EMC Laboratory

210-3 Yungduck-Ri, Kihung-Eup,  
Yongin-Si, Kyungki-Do,  
South, Korea

Site : - 3/10m Open Fielded Radiated  
- Indoor Line Conducted Room(Shielded)

The Open Field Radiated and Indoor Line Conducted sites are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4 2000. Korea EMC Lab. was refiled in FCC in Dec. 19. 2003.

### INSTRUMENTATION

| Description          | Model     | Manufacturer    | Serial No  | Due Cal.   |
|----------------------|-----------|-----------------|------------|------------|
| TEST RECEIVER        | ESVS10    | Rohde & Schwarz | 825120/006 | 2004.10.11 |
| TEST RECEIVER        | ESCS30    | Rohde & Schwarz | 100054     | 2004.11.11 |
| SPECTRUM ANALYZER    | 8566B     | Hewlett-Packard | 2421A00473 | -          |
| BI-LOG               | VULB9160  | SCHWARZBECK     | 3121       | 2004.12.02 |
| LISN(for EUT)        | NSLK 8128 | SCHWARZBECK     | 8128144    | 2004.11.11 |
| AMPLIFIER            | 87405A    | Hewlett-Packard | 2944A06481 | 2005.07.18 |
| LISN(for Peripheral) | ESH3-Z5   | Rohde & Schwarz | 860685/005 | 2004.11.24 |
| PLOTTOR              | 7550A     | Hewlett-Packard | 2407A00471 | -          |
| Attenuator           | 8491A     | Hewlett-Packard | 30907      | -          |

The calibration of the measuring instruments, including any accessories that may effect such calibration, are checked frequently to assure their accuracy. Adjustments are made and correction factors are applied in accordance with instruments contained in the manual for the measuring instrument.

## 2. MEASUREMENT PROCEDURES

### 2.1 System Test Configuration

#### 2.1.1 Video mode Justification

N/A

#### 2.1.2 EUT Exercise Software

Measure executing Copy&Delete repeatedly in WindowsXP after connect USB DRIVE to Desk Book.

### 2.2 Special Accessories


### 2.3 Equipment Modifications

No equipment modifications were performed during testing.

### 2.4 Connected cable

| Beginning device |          | Last device  |          | Standard of cable |                |
|------------------|----------|--------------|----------|-------------------|----------------|
| Type             | I/O Port | Type         | I/O Port | length (m)        | shielding      |
| Desk Book        | USB      | USB DRIVE    |          | -                 | Shielded       |
| "                | USB      | USB Mouse    |          | 1.5               | Shielded       |
| "                | Serial   | Serial Mouse |          | 1.5               | Shielded       |
| "                | Mouse    | Mouse        |          | 1.5               | Shielded       |
| "                | VGA      | Monitor      |          | 1.5               | Shielded(Core) |
| "                | Parallel | Printer      |          | 1.5               | Shielded(Core) |
| "                | Power    | Adapter      |          | 1.5               | Shielded(Core) |
| "                | MIC      | MIC          |          | 1.5               |                |
| Monitor          | Power    | Adapter      |          | 1.5               | Shielded(Core) |
| "                | Audio in | Desk Book    | Line out | 1.5               |                |
| Printer          | Power    | Adapter      |          | 1.5               |                |

### 2.5 System Configuration Diagram



## 2.6 PRELIMINARY TESTING

It is often valuable to performing preliminary radiated measurements at a closer distance than specified for compliance to determine the emission characteristics of the EUT. At close-in distance, it is easier to determine the spectrum signature of EUT, and if applicable, the EUT configuration that emanate the maximum level of emissions. The data may not be precisely correlatable results.

## 2.7 SHIELDED ENCLOSURE

To search the Radiated frequency outline of an EUT a shielded screen room may be used. If the shielded room is used for radiated data, the data page will state that the EUT was in a shielded enclosure. All data collected in a screen room for radiated emissions is for frequency outline only. If an EUT is placed in screen room for Line Conducted Data, the data page will show that a screen room was used and data frequencies and levels will be correct and used for test data.

## 2.8 DATA REPORTING FORMAT

The measurement results expressed in accordance with C63.4 and specified limits where applicable are presented in tabular or graphical form, or alternatively as recorder charts or photographs of a spectrum analyzer display, showing the level vs. frequency.

## 2.9 OPERATING CONDITIONS

The EUT was operated at the specified load conditions(mechanical and/or electrical)for which it was designed.

## 2.10 CONDITIONING OF THE EUT

The EUT was operated for a sufficient period of time to approximate normal operating conditions.

## 2.11 Power line Conducted Emissions

The EUT is set up in accordance with the suggested configuration given in FCC Measurement Procedure ANSI C63.4 2000. The measurements are performed in a 3m x 6m x 2.5m shielded room. A wooden table which height is 80 cm is located at the center of the shielded room; desktop EUTs are placed on top of this table. The rear of the EUT and table are placed 40 cm apart from the shielded room wall. All items on the table (or test-table) were placed at least 10 cm apart each other. Excess EUT power cord is folded back and forth to form a 30 cm by 40 cm bundle. Interconnecting cables which hang closer than 40 cm to the ground plane are folded back and forth to form a 30 cm by 40 cm long bundle, hanging approximately in the middle between the ground plane and table. The EUT power cord was plugged into a LISN 80 cm away, while all other devices were plugged into a second LISN, also 80 cm away.

The highest emissions were also analyzed in detail by operating the spectrum analyzer in fixed tuned mode to determine the precise amplitude of the emissions. On the other hand, the interconnecting cables were moved around the table to maximize the emissions, and the position of the peripheral devices were interchanged to check whether there is any changes in emissions.

NOTE : The resolution bandwidth and video bandwidth of test receiver is 10 kHz for Quasi-peak detection (QP) at frequency below 30 MHz. Q.P value A.V limit when do over by A.V mode conversion after measure .

## 2.12 Open field Radiated Emissions Tests

The EUT and support equipment are set up on the turntable in an open field site. Desktop EUTs are set up on a wooden stand (test-table), 80 cm above the ground plane. All items on the table were placed at least 10 cm apart each other. Interconnecting cables which hang closer than 40 cm to the ground plane are folded back and forth to form a 30 cm by 40 cm long bundle, hanging approximately between the ground plane and table. The highest emissions were also analyzed, in detail, with the tuned aerial to search the precise amplitude of the emissions. On the other hand, the interconnecting cables were moved around the table and if the highest amplitudes is observed, the EUT is rotated in the horizontal plane while changing the antenna polarization to the vertical plane to maximize the field strength. Once the maximum field strength is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings. The position of the peripheral devices are interchanged to check for any changes in emissions. In rare instances, the maximum field strength may occur with the antenna polarized between vertical and horizontal.

NOTE : The resolution bandwidth and video bandwidth of test receiver is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz

### 3. Measurement Data

#### 3.1 CONDUCTED EMISSION DATA

TEST : USBDRIVE ; SPEEDMBN-ONE(Memory size is 16MB,32MB,64MB,128MB,256MB,512MB and 1GB)

DATE : Sep. 06. 2004


| Freq.<br>(MHz) | EUT<br>State     | Polarity<br>(H/N) | Level (Q.P/A.V)<br>dB(uV) | LIMIT (Q.P/A.V)<br>dB(uV) | Margin for(Q.P/A.V)<br>dB(uV) |
|----------------|------------------|-------------------|---------------------------|---------------------------|-------------------------------|
| 0.151          |                  | L2                | 52.2                      | 66.0                      | 13.8                          |
| 0.198          |                  | L2                | 51.4                      | 64.6                      | 13.2                          |
| 0.243          |                  | L2                | 48.2                      | 63.3                      | 15.1                          |
| 0.276          |                  | L2                | 51.5                      | 62.4                      | 10.9                          |
| 0.316          |                  | L2                | 45.6                      | 61.3                      | 15.7                          |
| 0.487          |                  | L2                | 43.2                      | 56.4                      | 13.2                          |
|                | Refer<br>to Note |                   |                           |                           |                               |
| 0.623          |                  | L2                | 48.2/39.0                 | 56.0/46.0                 | 7.8/7.0                       |
| 0.984          |                  | L2                | 39.4                      | 56.0                      | 16.6                          |
| 1.592          |                  | L2                | 45.2                      | 56.0                      | 10.8                          |
| 2.211          |                  | L1                | 42.6                      | 56.0                      | 13.4                          |
| 3.258          |                  | L2                | 41.4                      | 56.0                      | 14.6                          |
| 4.083          |                  | L1                | 40.5                      | 56.0                      | 15.5                          |
|                |                  |                   |                           |                           |                               |
| 6.293          |                  | L2                | 38.0                      | 60.0                      | 22.0                          |
| 8.087          |                  | L2                | 42.4                      | 60.0                      | 17.6                          |
| 10.008         |                  | L2                | 39.4                      | 60.0                      | 20.6                          |
| 18.089         |                  | L1                | 34.6                      | 60.0                      | 25.4                          |
| 20.014         |                  | L1                | 40.0                      | 60.0                      | 20.0                          |
| 21.084         |                  | L1                | 33.8                      | 60.0                      | 26.2                          |

Notes: The test is implemented in a shielded room in accordance with ANSI C63.4

L1 : HOT LINE , L2 : NEUTRAL LINE

Test Engineer.

Reviewed by.




### 3.2 Conducted Emission Graph

#### Korea EMC Laboratory Conducted Emission

Comment: L1  
PK: RED AV: BLUE

Scan Settings (1 Range)  
Frequencies | Receiver Settings  
Start Stop Step IF BW Detector M-Time Atten Presamp  
150K 30M 0.2% 9K PK+AV 20ms 10dBLN Off




Red : PK, Blue : AV  
LINE EMISSION GRAPH(L1)

Korea EMC Laboratory  
Conducted Emission

Comment: L2  
PK: RED AV: BLUE

Scan Settings (1 Range)  
Frequencies | Receiver Settings  
Start Stop Step IF BW Detector H-Time Atten Preamp  
150K 30M 0.2K 8K PK+AV 20ms 10dBLN OFF




Red : PK, Blue : AV  
LINE EMISSION GRAPH(L2)

### 3.2 RADIATED EMISSION DATA

**TEST : USB DRIVE : SPEEDMBN-ONE (Memory size is 16 MB, 32 MB, 64 MB, 128 MB, 256 MB, 512 MB and 1 GB)**

DATE : Sep. 06. 2004



Notes: The test is performed in a distance of 3m. Af : Antenna factor, Cl : Cable loss

The test is performed in accordance with ANSI C63.4

## Test Engineer.

Reviewed by.

Korea EMC Laboratory

### 3.3 SUMMARY

Company : MBN Partners Co., Ltd.  
Equipment Under Test : USB DRIVE  
Model Number : SPEEDMBN-ONE  
(Memory size is 16 MB, 32 MB, 64 MB, 128 MB, 256 MB, 512 MB and 1 GB)  
Type of Test : FCC CLASS B      Serial Number: Prototype  
Passed/Failed: PASSED

The Equipment Under Test(EUT) was configured and operated in a manner which tends to maximize its emission characteristics in a typical application. Power and signal distribution, ground, interconnecting cabling, and physical placement of equipment were simulating the typical application and usage in so far as practicable.

**LINE CONDUCTED TEST:** An unshielded power cord was used to connect the EUT to a LISN Box which supplied 120 VAC/60 Hz power. The EUT was tested according to C63.4 test specifications. Line conductance scanned from 150 kHz to 30 MHz range on both Line 1(hot side) and Line 2(neutral side). ***The highest emission was observed at 0.623 MHz on Line 2 with a margin of 7.8 dB(uV) from the limit.*** All line conductance emissions were within the FCC CLASS B requirements for compliance.

**RADIATED TEST:** The EUT was placed on a three meter open field test site according to C63.4 test specifications. Preliminary scans ranged from 30 MHz to 1 GHz in both vertical and horizontal polarizations in all possible modes of operation. The highest six point of emission levels were recorded as data each ranges of limit. ***The highest emission was observed at 608.138 MHz(Horizontal) with margin of 4.1 dB from the limit.*** All radiated emissions were within the FCC CLASS B requirements for compliance.

## 4. LABELING REQUIREMENT

Section 15.19 of the Code of Federal Regulation

1) A CLASS B computing device subject to certification by the Commission shall be identified pursuant to par. 2.925 et Seq of this chapter. In addition, the label shall include the following statement:

This device complies with Part 15 of the FCC Rules.  
Operation is subject to the following two conditions:  
(1) This Device may not cause harmful interference, and  
(2) This device must accept any interference received,  
including interference that may cause undesired  
operation.

Where a device is constructed in two or more sections connected by wires and marketed together, the statement specified in this Section is required to be affixed only to the main control unit.

The users manual or instruction manual for the EUT shall contain the following statement or equivalent.

Caution: Changes or Modifications not expressly approved by the party responsible for compliance could void the users authority to operate the equipment.

If the EUT requires accessories such as special shielded cables and/or connectors to enable compliance with emission limits, the instruction manual for the EUT shall include appropriate instructions on the first page of the text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

For a CLASS B digital device or peripheral, the instructions furnished the user shall include the following or similar statement placed in a prominent location in the text of the manual.

Note: This equipment has been tested and found to comply with the limits for a CLASS B digital device, pursuant to Part 15 of FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.