



A D T

RF EXPOSURE REPORT

REPORT NO.: SA131220C10

MODEL NO.: XR600

FCC ID: SK6-XR630

RECEIVED: Dec. 12, 2013

TESTED: Dec. 24, 2013 ~ Mar. 06, 2014

ISSUED: Mar. 10, 2014

APPLICANT: Xirrus, INC.

ADDRESS: 2101 Corporate Center Driver Thousand Oaks,
California 91320

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,
New Taipei City, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim
product certification, approval, or endorsement by any
government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



A D T

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION	4
2. RF EXPOSURE.....	5
2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	5
2.2 MPE CALCULATION FORMULA	5
2.3 CLASSIFICATION	5
2.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA131220C10	Original release.	Mar. 10, 2014



A D T

1. CERTIFICATION

PRODUCT: 802.11ac 3x3 AP

MODEL: XR600

BRAND: Xirrus

APPLICANT: Xirrus, INC.

TESTED: Dec. 24, 2013 ~ Mar. 06, 2014

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC Part 2 (Section 2.1091)

FCC OET Bulletin 65, Supplement C (01-01)

IEEE C95.1

The above equipment (model: XR600) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Maggie Wu , **DATE :** Mar. 10, 2014
Maggie Wu / Specialist

APPROVED BY : Ken Liu , **DATE :** Mar. 10, 2014
Ken Liu / Senior Manager



A D T

2. RF EXPOSURE

2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE CALCULATION FORMULA

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 24cm away from the body of the user. So, this device is classified as **Mobile Device**.



A D T

2.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

TEST MODE A (Radio 1)

FREQUENCY BAND (MHz)	MODE	MAX POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412 ~ 2462	802.11b	25.15	8.85	24	0.347	1
	802.11g	26.41	8.85	24	0.464	1
	802.11n (20MHz)	26.37	4.08	24	0.153	1
	802.11n (40MHz)	24.58	4.08	24	0.101	1
5180 ~ 5240	802.11a	11.49	10.74	24	0.023	1
	802.11n (20MHz)	16.55	5.97	24	0.025	1
	802.11n (40MHz)	16.83	5.97	24	0.026	1
	802.11ac (VHT80)	15.50	10.74	24	0.058	1
5745 ~ 5825	802.11a	24.50	10.74	24	0.462	1
	802.11n (20MHz)	24.47	5.97	24	0.153	1
	802.11n (40MHz)	24.52	5.97	24	0.155	1
	802.11ac (VHT80)	23.49	10.74	24	0.366	1

2.4GHz Band:

1. 802.11b/g: Directional gain = $4.08\text{dBi} + 10\log(3) = 8.85\text{dBi}$
2. 802.11n (20MHz), 802.11n (40MHz): IEEE 802.11n, MCS = 16-23, NSS = 3,
Directional gain = $4.08\text{dBi} + 10\log(3/3) = 4.08\text{dBi}$

5GHz Band:

1. 802.11a, 802.11ac (VHT80): Directional gain = $5.97\text{dBi} + 10\log(3) = 10.74\text{dBi}$
2. 802.11n (20MHz), 802.11n (40MHz): IEEE 802.11n, MCS = 16-23, NSS = 3,
Directional gain = $5.97\text{dBi} + 10\log(3/3) = 5.97\text{dBi}$

TEST MODE B (Radio 2)

FREQUENCY BAND (MHz)	MODE	MAX POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412 ~ 2462	802.11b	24.98	8.85	24	0.334	1
	802.11g	25.75	8.85	24	0.398	1
	802.11n (20MHz)	25.68	4.08	24	0.131	1
	802.11n (40MHz)	24.93	4.08	24	0.110	1
5180 ~ 5240	802.11a	11.66	10.74	24	0.024	1
	802.11n (20MHz)	16.54	5.97	24	0.025	1
	802.11n (40MHz)	15.96	5.97	24	0.022	1
	802.11ac (VHT80)	15.44	10.74	24	0.057	1
5745 ~ 5825	802.11a	24.62	10.74	24	0.475	1
	802.11n (20MHz)	24.43	5.97	24	0.151	1
	802.11n (40MHz)	24.48	5.97	24	0.153	1
	802.11ac (VHT80)	23.64	10.74	24	0.379	1

2.4GHz Band:

1. 802.11b/g: Directional gain = $4.08\text{dBi} + 10\log(3) = 8.85\text{dBi}$
2. 802.11n (20MHz), 802.11n (40MHz): IEEE 802.11n, MCS = 16-23, NSS = 3,
Directional gain = $4.08\text{dBi} + 10\log(3/3) = 4.08\text{dBi}$

5GHz Band:

1. 802.11a, 802.11ac (VHT80): Directional gain = $5.97\text{dBi} + 10\log(3) = 10.74\text{dBi}$
2. 802.11n (20MHz), 802.11n (40MHz): IEEE 802.11n, MCS = 16-23, NSS = 3,
Directional gain = $5.97\text{dBi} + 10\log(3/3) = 5.97\text{dBi}$



CONCLUSION:

The formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

The EUT is collocated two dual band RF modules (Radio 1, Radio 2), which cannot co-transmit in the same band.

1. WLAN 2.4GHz (Radio 1) + WLAN 5GHz (Radio 2) = 0.464 + 0.475 = 0.939
2. WLAN 5GHz (Radio 1) + WLAN 2.4GHz (Radio 2) = 0.462 + 0.398 = 0.860

---END---