

## **Certification Test Report**

**FCC ID: SK9AMI-3  
IC: 864G-AMI3**

**FCC Rule Part: 15.247  
IC Radio Standards Specification: RSS-210**

**ACS Report Number: 11-0232.W04.11.A**

Manufacturer: Itron Electricity Metering, Inc.  
Model(s): CN2SO, CN2SOD, C2SOD, and C2SO

Test Begin Date: June 23, 2011  
Test End Date: June 24, 2011

Report Issue Date: July 27, 2011



FOR THE SCOPE OF ACCREDITATION UNDER LAB Code 200612-0

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

A handwritten signature in black ink, appearing to read "Kirby Munroe".

Reviewed by:  
**Kirby Munroe**  
**Director, Wireless Certifications**  
**ACS, Inc.**

This test report shall not be reproduced except in full. This report may be reproduced in part with prior written consent of ACS, Inc. The results contained in this report are representative of the sample(s) submitted for evaluation.

**This report contains 13 pages**

## TABLE OF CONTENTS

<b>1</b>	<b>GENERAL .....</b>	<b>3</b>
1.1	PURPOSE.....	3
1.2	PRODUCT DESCRIPTION .....	3
1.3	TEST METHODOLOGY AND CONSIDERATIONS .....	4
<b>2</b>	<b>TEST FACILITIES.....</b>	<b>5</b>
2.1	LOCATION .....	5
2.2	LABORATORY ACCREDITATIONS/RECOGNITIONS/CERTIFICATIONS .....	5
2.3	RADIATED EMISSIONS TEST SITE DESCRIPTION .....	6
2.3.1	<i>Semi-Anechoic Chamber Test Site.....</i>	6
2.3.2	<i>Open Area Tests Site (OATS) .....</i>	7
<b>3</b>	<b>APPLICABLE STANDARD REFERENCES.....</b>	<b>8</b>
<b>4</b>	<b>LIST OF TEST EQUIPMENT.....</b>	<b>8</b>
<b>5</b>	<b>SUPPORT EQUIPMENT.....</b>	<b>9</b>
<b>6</b>	<b>EQUIPMENT UNDER TEST SETUP BLOCK DIAGRAM .....</b>	<b>9</b>
<b>7</b>	<b>SUMMARY OF TESTS.....</b>	<b>10</b>
7.1	ANTENNA REQUIREMENT – FCC: SECTION 15.203 .....	10
7.2	RADIATED SPURIOUS EMISSIONS (RESTRICTED BANDS) - FCC SEC. 15.205 IC: RSS-210 2.5 .....	10
7.2.1	<i>Measurement Procedure.....</i>	10
7.2.2	<i>Measurement Results .....</i>	10
7.2.3	<i>Sample Calculation: .....</i>	12
<b>8</b>	<b>CONCLUSION .....</b>	<b>12</b>

## 1 GENERAL

### 1.1 Purpose

The purpose of this report is to demonstrate compliance with Part 15 Subpart C of the FCC's Code of Federal Regulations and Industry Canada's Radio Standards Specification RSS-210 for a class II permissive change.

The purpose of this class II permissive change is to add new antenna types to the 900 MHz LAN frequency hopping spread spectrum radio.

### 1.2 Product description

The AMI3 OpenWay CENTRON meter is a solid-state meter used for measuring electrical energy consumption. The OpenWay CENTRON meter incorporates a two-piece design combining a base metrology with a variety of OpenWay registers or options. The metrology portion of the meter contains all measurement circuitry and calibration information, while the personality modules contain the register functionality and communication mediums. The register board contains (1) 900 MHz LAN frequency hopping spread spectrum radio and (1) 2.4 GHz direct sequence spread spectrum Zigbee radio. This report addresses the 900 MHz LAN radio only.

Modulation	Frequency Range (MHz)	Number of Channels	Channel Separation (kHz)	Data Rates Supported (kbps)
FSK	902.25 - 927.75	52	500	19.2
FSK	902.25 - 927.75	52	500	152.3

Manufacturer Information:

Itron Electricity Metering, Inc.  
313 North Highway 11  
West Union, SC 29696

Test Sample Serial Number(s): NA

Antenna Information:

Larson LP800 Low Profile Radome Antenna  
Frequency: 806 - 960 MHz  
VSWR: 2.0:1 or less  
Gain: 2.14 dBi

Comtelco A158192B Stub Antenna  
Frequency: 700 - 960 MHz  
VSWR: 2.0:1 or less  
Gain: 2.0 dBi

PCTEL, Inc. ASPG918 Elevated Feed Point Whip Antenna  
Frequency: 890 - 960 MHz  
VSWR: 2.0:1 or less  
Gain: 3.0 dBi

Test Sample Condition: The test samples were provided in good working order with no visible defects.

---

### 1.3 Test Methodology and Considerations

The antennas included in this filing are connected to the meter via an adhesive patch antenna. The intention of the patch antenna is to couple to the integral meter antenna over-the-air. The coupled signal is then to be routed, via coax, to the antennas described in this filing.

Only model C2SO was evaluated as it represents worst case. All available data rates were evaluated with worst case data provided in this report.

## 2 TEST FACILITIES

### 2.1 Location

The radiated and conducted emissions test sites are located at the following address:

Advanced Compliance Solutions  
5015 B.U. Bowman Drive  
Buford, GA 30518  
Phone: (770) 831-8048  
Fax: (770) 831-8598

### 2.2 Laboratory Accreditations/Recognitions/Certifications

ACS is accredited to ISO/IEC 17025 by the National Institute of Standards and Technology under their National Voluntary Laboratory Accreditation Program (NVLAP), Lab Code 200612-0. Unless otherwise specified, all tests methods described within this report are covered under the ISO/IEC 17025 scope of accreditation.

The Semi-Anechoic Chamber Test Site, Open Area Test Site (OATS) and Conducted Emissions Site have been fully described, submitted to, and accepted by the FCC, Industry Canada and the Japanese Voluntary Control Council for Interference by information technology equipment.

FCC Registration Number: 511277

Industry Canada Lab Code: IC 4175A-1

VCCI Member Number: 1831

- VCCI OATS Registration Number R-1526
- VCCI Conducted Emissions Site Registration Number: C-1608

## 2.3 Radiated Emissions Test Site Description

### 2.3.1 Semi-Anechoic Chamber Test Site

The Semi-Anechoic Chamber Test Site consists of a 20' x 30' x 18' shielded enclosure. The chamber is lined with Toyo Ferrite Grid Absorber, model number FFG-1000. The ferrite tile grid is 101 x 101 x 19mm thick and weighs approximately 550 grams. These tiles are mounted on steel panels and installed directly on the inner walls of the chamber.

The turntable is 150cm in diameter and is located 160cm from the back wall of the chamber. The chamber is grounded via 1 - 8' copper ground rod, installed at the center of the back wall, it is bound to the ground plane using 3/4" stainless steel braided cable.

The turntable is all steel, flush mounted table installed in an all steel frame. The table is remotely operated from inside the control room located 25' from the range. The turntable is electrically bonded to the surrounding ground plane via steel fingers installed on the edge of the turn table. The steel fingers make constant contact with the ground plane during operation.

Behind the turntable is a 3' x 6' x 4' deep shielded pit used for support equipment if necessary. The pit is equipped with 1 - 4" PVC chases from the turntable to the pit that allow for cabling to the EUT if necessary. The underside of the turntable can be accessed from the pit so cables can be supplied to the EUT from the pit.

A diagram of the Semi-Anechoic Chamber Test Site is shown in Figure 2.3-1 below:




Figure 2.3-1: Semi-Anechoic Chamber Test Site

### 2.3.2 Open Area Tests Site (OATS)

The open area test site consists of a 40' x 66' concrete pad covered with a perforated electro-plated galvanized sheet metal. The perforations in the sheet metal are 1/8" holes that are staggered every 3/16". The individual sheets are placed to overlap each other by 1/4" and are riveted together to provide a continuous seam. Rivets are spaced every 3" in a 3 x 20 meter perimeter around the antenna mast and EUT area. Rivets in the remaining area are spaced as necessary to properly secure the ground plane and maintain the electrical continuity.

The entire ground plane extends 12' beyond the turntable edge and 16' beyond the antenna mast when set to a 10 meter measurement distance. The ground plane is grounded via 4 - 8' copper ground rods, each installed at a corner of the ground plane and bound to the ground plane using 3/4" stainless steel braided cable.

The turntable is an all aluminum 10' flush mounted table installed in an all aluminum frame. The table is remotely operated from inside the control room located 40' from the range. The turntable is electrically bonded to the surrounding ground plane via steel fingers installed on the edge of the turn table. The steel fingers make constant contact with the ground plane during operation.

Adjacent to the turntable is a 7' x 7' square and 4' deep concrete pit used for support equipment if necessary. The pit is equipped with 5 - 4" PVC chases from the pit to the control room that allow for cabling to the EUT if necessary. The underside of the turntable can be accessed from the pit so cables can be supplied to the EUT from the pit. The pit is covered with 2 sheets of 1/4" diamond style re-enforced steel sheets. The sheets are painted to match the perforated steel ground plane; however the underside edges have been masked off to maintain the electrical continuity of the ground plane. All reflecting objects are located outside of the ellipse defined in ANSI C63.4.

A diagram of the Open Area Test Site is shown in Figure 2.3-2 below:




Figure 2.3-2: Open Area Test Site

### 3 APPLICABLE STANDARD REFERENCES

The following standards were used:

- ❖ ANSI C63.4-2003: Method of Measurements of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the 9KHz to 40GHz
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 2, Subpart J: Equipment Authorization Procedures, 2010
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 15, Subpart C: Radio Frequency Devices, Intentional Radiators, 2010
- ❖ Industry Canada Radio Standards Specification: RSS-210 - Low-power License-exempt Radiocommunication Devices (All Frequency Bands):Category I Equipment, Issue 8, Dec 2010
- ❖ Industry Canada Radio Standards Specification: RSS-GEN – General Requirements and Information for the Certification of Radiocommunication Equipment, Issue 3, Dec 2010.

### 4 LIST OF TEST EQUIPMENT

The calibration interval of test equipment is annually or the manufacturer's recommendations. Where the calibration interval deviates from the annual cycle based on the instrument manufacturer's recommendations, it shall be stated below.

**Table 4-1: Test Equipment**


AssetID	Manufacturer	Model #	Equipment Type	Serial #	Last Calibration Date	Calibration Due Date
1	Rohde & Schwarz	ESMI - Display	Spectrum Analyzers	833771/007	9/23/2010	9/23/2012
2	Rohde & Schwarz	ESMI-Receiver	Spectrum Analyzers	839587/003	9/23/2010	9/23/2012
25	Chase	CBL6111	Antennas	1043	9/13/2010	9/13/2012
30	Spectrum Technologies	DRH-0118	Antennas	970102	4/27/2011	4/27/2013
73	Agilent	8447D	Amplifiers	2727A05624	3/21/2011	3/21/2012
291	Florida RF Cables	SMRE-200W-12.0-SMRE	Cables	None	12/7/2010	12/7/2011
292	Florida RF Cables	SMR-290AW-480.0-SMR	Cables	None	4/11/2011	4/11/2012
337	Microwave Circuits	H1G513G1	Filters	282706	7/11/2011	7/11/2012
338	Hewlett Packard	8449B	Amplifiers	3008A01111	3/24/2011	3/24/2012
422	Florida RF	SMS-200AW-72.0-SMR	Cables	805	12/29/2010	12/29/2011

## 5 SUPPORT EQUIPMENT

Table 5-1: Support Equipment

Item	Equipment Type	Manufacturer	Model Number	Serial Number
1	Electric Meter (EUT)	Itron Electricity Metering, Inc.	C2SO	57 479 229

## 6 EQUIPMENT UNDER TEST SETUP BLOCK DIAGRAM



## 7 SUMMARY OF TESTS

Along with the tabular data shown below, plots were taken of all signals deemed important enough to document.

### 7.1 Antenna Requirement – FCC: Section 15.203

The low profile radome, stub, and whip antennas are connected to the host device via an adhesive coupling patch antenna. Professional installation is utilized.

### 7.2 Radiated Spurious Emissions (Restricted Bands) - FCC Sec. 15.205 IC: RSS-210 2.5

#### 7.2.1 Measurement Procedure

Radiated emissions tests were made over the frequency range of 30MHz to 10GHz, 10 times the highest fundamental frequency.

The EUT was rotated through 360° and the receive antenna height was varied from 1m to 4m so that the maximum radiated emissions level would be detected. For frequencies below 1000MHz, quasi-peak measurements were made using a resolution bandwidth RBW of 120 kHz and a video bandwidth VBW of 300 kHz. For frequencies above 1000MHz, peak and average measurements were made with RBW and VBW of 1 MHz and 3 MHz respectively.

Each emission found to be in a restricted band as defined by section 15.205 was compared to the radiated emission limits as defined in section 15.209.

All available data rates were evaluated with worst case data provided.

#### 7.2.2 Measurement Results

Table 7.2.2-1: Radiated Spurious Emissions Tabulated Data – 902.5 MHz – Low Profile Radome

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
2706.75	51.13	44.86	H	-3.79	47.34	41.07	74.0	54.0	26.7	12.9
2706.75	49.60	42.03	V	-3.79	45.81	38.24	74.0	54.0	28.2	15.8
3609	51.52	44.19	H	-0.55	50.97	43.64	74.0	54.0	23.0	10.4
3609	50.11	41.76	V	-0.55	49.56	41.21	74.0	54.0	24.4	12.8
4511.25	53.25	48.05	H	1.35	54.60	49.40	74.0	54.0	19.4	4.6
4511.25	52.74	46.63	V	1.35	54.09	47.98	74.0	54.0	19.9	6.0
8120.25	49.18	40.31	H	7.79	56.97	48.10	74.0	54.0	17.0	5.9
8120.25	50.27	42.52	V	7.79	58.06	50.31	74.0	54.0	15.9	3.7

Table 7.2.2-2: Radiated Spurious Emissions Tabulated Data – 914.75 MHz – Low Profile Radome

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
2744.25	50.39	43.08	H	-3.67	46.72	39.41	74.0	54.0	27.3	14.6
4573.75	50.14	41.22	H	1.49	51.63	42.71	74.0	54.0	22.4	11.3
4573.75	49.51	39.47	V	1.49	51.00	40.96	74.0	54.0	23.0	13.0

**Table 7.2.2-3: Radiated Spurious Emissions Tabulated Data – 927.75 MHz – Low Profile Radome**

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
All measurements below the noise floor.										

**Table 7.2.2-4: Radiated Spurious Emissions Tabulated Data – 902.5 MHz – Stub Antenna**

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
2706.75	51.46	45.39	H	-3.79	47.67	41.60	74.0	54.0	26.3	12.4
2706.75	49.47	41.93	V	-3.79	45.68	38.14	74.0	54.0	28.3	15.9
3609	51.11	43.41	H	-0.55	50.56	42.86	74.0	54.0	23.4	11.1
3609	50.21	42.03	V	-0.55	49.66	41.48	74.0	54.0	24.3	12.5
4511.25	54.27	49.40	H	1.35	55.62	50.75	74.0	54.0	18.4	3.3
4511.25	53.61	48.48	V	1.35	54.96	49.83	74.0	54.0	19.0	4.2
8120.25	50.02	41.63	H	7.79	57.81	49.42	74.0	54.0	16.2	4.6
8120.25	48.10	40.49	V	7.79	55.89	48.28	74.0	54.0	18.1	5.7

**Table 7.2.2-5: Radiated Spurious Emissions Tabulated Data – 914.75 MHz – Stub Antenna**

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
2744.25	51.13	44.85	H	-3.67	47.46	41.18	74.0	54.0	26.5	12.8
2744.25	48.32	40.18	V	-3.67	44.65	36.51	74.0	54.0	29.3	17.5
3659	49.31	40.92	H	-0.33	48.98	40.59	74.0	54.0	25.0	13.4
3659	48.26	38.12	V	-0.33	47.93	37.79	74.0	54.0	26.1	16.2
4573.75	51.80	44.47	H	1.49	53.29	45.96	74.0	54.0	20.7	8.0
4573.75	51.30	44.24	V	1.49	52.79	45.73	74.0	54.0	21.2	8.3
8232.75	51.03	42.75	H	7.98	59.01	50.73	74.0	54.0	15.0	3.3
8232.75	49.02	40.38	V	7.98	57.00	48.36	74.0	54.0	17.0	5.6

**Table 7.2.2-6: Radiated Spurious Emissions Tabulated Data – 927.75 MHz – Stub Antenna**

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
All measurements below the noise floor.										

**Table 7.2.2-7: Radiated Spurious Emissions Tabulated Data – 902.5 MHz – Whip Antenna**

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
2706.75	51.26	45.87	H	-3.79	47.47	42.08	74.0	54.0	26.5	11.9
2706.75	49.18	41.60	V	-3.79	45.39	37.81	74.0	54.0	28.6	16.2
3609	51.14	43.58	H	-0.55	50.59	43.03	74.0	54.0	23.4	11.0
3609	50.09	42.09	V	-0.55	49.54	41.54	74.0	54.0	24.5	12.5
4511.25	53.07	47.72	H	1.35	54.42	49.07	74.0	54.0	19.6	4.9
4511.25	52.24	46.22	V	1.35	53.59	47.57	74.0	54.0	20.4	6.4
8120.25	50.07	41.17	H	7.79	57.86	48.96	74.0	54.0	16.1	5.0
8120.25	49.35	41.53	V	7.79	57.14	49.32	74.0	54.0	16.9	4.7

**Table 7.2.2-8: Radiated Spurious Emissions Tabulated Data – 914.75 MHz – Whip Antenna**

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
2744.25	50.36	43.41	H	-3.67	46.69	39.74	74.0	54.0	27.3	14.3
2744.25	48.01	37.79	V	-3.67	44.34	34.12	74.0	54.0	29.7	19.9
3659	49.03	39.32	H	-0.33	48.70	38.99	74.0	54.0	25.3	15.0
3659	48.14	37.46	V	-0.33	47.81	37.13	74.0	54.0	26.2	16.9
4573.75	51.24	43.76	H	1.49	52.73	45.25	74.0	54.0	21.3	8.8
4573.75	50.21	42.67	V	1.49	51.70	44.16	74.0	54.0	22.3	9.8
8232.75	49.17	40.49	H	7.98	57.15	48.47	74.0	54.0	16.9	5.5
8232.75	49.25	40.28	V	7.98	57.23	48.26	74.0	54.0	16.8	5.7

**Table 7.2.2-9: Radiated Spurious Emissions Tabulated Data – 927.75 MHz – Whip Antenna**

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
All measurements below the noise floor.										

### 7.2.3 Sample Calculation:

$$R_C = R_U + CF_T$$

Where:

$CF_T$  = Total Correction Factor (AF+CA+AG)-DC (Average Measurements Only)

$R_U$  = Uncorrected Reading

$R_C$  = Corrected Level

AF = Antenna Factor

CA = Cable Attenuation

AG = Amplifier Gain

DC = Duty Cycle Correction Factor

#### Example Calculation: Peak

Corrected Level:  $51.13 - 3.79 = 47.34$  dBuV/m

Margin:  $74$  dBuV/m –  $47.34$  dBuV/m =  $26.7$  dB

#### Example Calculation: Average

Corrected Level:  $44.86 - 3.79 - 0 = 41.07$  dBuV

Margin:  $54$  dBuV –  $41.07$  dBuV =  $12.9$  dB

## 8 CONCLUSION

In the opinion of ACS, Inc. the CN2SO, CN2SOD, C2SOD, and C2SO, manufactured by Itron Electricity Metering, Inc. meets the requirements of FCC Part 15 subpart C and Industry Canada's Radio Standards Specification RSS-210 for the additional antennas.

**END REPORT**