



Excellence in Compliance Testing

## Certification Test Report

**Frequency Hopping Spread Spectrum Transmitter**

### Test Report

**FCC ID: SK9AMI-3  
IC: 864G-AMI3**

**FCC Rule Part: 15.247  
IC Radio Standards Specification: RSS-210**

**ACS Report Number 08-0028-900-DSS**

**Manufacturer: Itron Electricity Metering, Inc.  
Model(s): C2SOD**

**Test Begin Date: January 31, 2008  
Test End Date: March 17, 2008**

**Report Issue Date: April 7, 2008**



FOR THE SCOPE OF ACCREDITATION UNDER LAB Code 200612-0

This report is not be used to claim certification, approval, or endorsement by NVLAP, NIST or any government agency.

**Prepared by:** \_\_\_\_\_  
J. Kirby Munroe  
Manager Wireless Certifications  
ACS, Inc.

**Reviewed by:** \_\_\_\_\_  
R. Sam Wismer  
Engineering Manager  
ACS, Inc.

This test report shall not be reproduced except in full. This report may be reproduced in part with prior written consent of ACS, Inc. The results contained in this report are representative of the sample(s) submitted for evaluation.

**This report contains 23 pages**

# Table of Contents

---

<b>1.0 General</b>	3
1.1 Purpose	3
1.2 Product Description	3
1.2.1 General	3
1.2.2 Intended Use	3
1.3 Test Methodology and Considerations	3
<b>2.0 Test Facilities</b>	4
2.1 Location	4
2.2 Laboratory Accreditations/Recognitions/Certifications	4
2.3 Radiated Emissions Test Site Description	5
2.3.1 Semi-Anechoic Chamber Test Site	5
2.3.2 Open Area Tests Site (OATS)	6
2.4 Conducted Emissions Test Site Description	7
<b>3.0 Applicable Standards and References</b>	7
<b>4.0 List of Test Equipment</b>	8
<b>5.0 Support Equipment</b>	9
<b>6.0 EUT Setup Block Diagram</b>	9
<b>7.0 Summary of Tests</b>	10
7.1 Antenna Requirement	10
7.2 Power Line Conducted Emissions	10
7.2.1 Test Methodology	10
7.2.2 Test Results	10
7.3 Radiated Emissions - Unintentional Radiation	11
7.3.1 Test Methodology	11
7.3.2 Test Results	11
7.4 Peak Output Power	12
7.4.1 Test Methodology	12
7.4.2 Test Results	12
7.5 Channel Usage	14
7.5.1 Carrier Frequency Separation	14
7.5.1.1 Test Methodology	14
7.5.1.2 Test Results	14
7.5.2 Number of Hopping Channels	15
7.5.3 Channel Dwell Time	16
7.5.3.1 Test Methodology	16
7.5.3.2 Test Results	16
7.5.4 20dB Bandwidth	17
7.5.4.1 Test Methodology	17
7.5.4.2 Test Results	17
7.6 Band-edge Compliance and Spurious Emissions	19
7.6.1 Band-edge Compliance of RF Conducted Emissions	19
7.6.1.1 Test Methodology	19
7.6.1.2 Test Results	19
7.6.2 RF Conducted Spurious Emissions	20
7.6.2.1 Test Methodology	20
7.6.2.2 Test Results	20
7.6.3 Radiated Spurious Emissions – Intentional Radiation (Restricted Bands)	23
7.6.3.1 Test Methodology	23
7.6.3.2 Duty Cycle Correction	23
7.6.3.3 Test Results	23
7.6.3.4 Sample Calculations	23
<b>8.0 CONCLUSION</b>	23

## Additional Exhibits Included In Filing

<b>Internal Photographs</b>	<b>Installation/Users Guide</b>
<b>External Photographs</b>	<b>Theory of Operation</b>
<b>Test Setup Photographs</b>	<b>BOM (Parts List)</b>
<b>Product Labeling</b>	<b>System Block Diagram</b>
<b>RF Exposure – MPE Calculations</b>	<b>Schematics</b>

## 1.0 GENERAL

### 1.1 Purpose

The purpose of this report is to demonstrate compliance with Part 15 Subpart C of the FCC's Code of Federal Regulations and Industry Canada's Radio Standards Specification RSS-210.

### 1.2 Product Description

#### 1.2.1 General

The OpenWay CENTRON meter is a solid-state meter used for measuring electrical energy consumption. The OpenWay CENTRON meter incorporates a two-piece design combining a base metrology with a variety of OpenWay registers or options. The metrology portion of the meter contains all measurement circuitry and calibration information, while the personality modules contain the register functionality and communication mediums.

The register board contains (1) 900 MHz LAN frequency hopping spread spectrum radio and (1) 2.4 GHz direct sequence spread spectrum Zigbee radio. These transmitters can operate simultaneously and inter-modulation data is presented in Section 7.6.3.

Manufacturer Information:

Itron Electricity Metering, Inc.  
313 North Highway 11  
West Union, SC 29696

Test Sample Condition: The test samples were provided in good working order with no visible defects.

Detailed photographs of the EUT are filed separately with this filing.

#### 1.2.2 Intended Use

The OpenWay CENTRON meter is a solid-state meter used for measuring electrical energy consumption.

### 1.3 Test Methodology and Considerations

The C2SOD operates at multiple voltages from the AC mains. All input voltages were evaluated and in some instances only the worst case data presented in this report.

This device is considered a composite device by definition. The 900 MHz LAN radio and the 2.4 GHz Zigbee radio operate under CFR 47 Part 15.247 and IC RSS-210. This report addresses the 900 MHz radio only and a separate report, 08-0028-2400-DTS, will be issued for the 2.4 GHz Zigbee radio.

## 2.0 TEST FACILITIES

### 2.1 Location

The radiated and conducted emissions test sites are located at the following address:

Advanced Compliance Solutions  
5015 B.U. Bowman Drive  
Buford, GA 30518  
Phone: (770) 831-8048  
Fax: (770) 831-8598

### 2.2 Laboratory Accreditations/Recognitions/Certifications

The Semi-Anechoic Chamber Test Site, Open Area Test Site (OATS) and Conducted Emissions Site have been fully described, submitted to, and accepted by the FCC, Industry Canada and the Japanese Voluntary Control Council for Interference by information technology equipment. In addition, ACS is compliant to ISO 17025 as certified by the National Institute of Standards and Technology under their National Voluntary Laboratory Accreditation Program. The following certification numbers have been issued in recognition of these accreditations and certifications:

FCC Registration Number: 894540

Industry Canada Lab Code: IC 4175

VCCI Member Number: 1831

- VCCI OATS Registration Number R-1526
- VCCI Conducted Emissions Site Registration Number: C-1608

NVLAP Lab Code: 200612-0

## 2.3 Radiated Emissions Test Site Description

### 2.3.1 Semi-Anechoic Chamber Test Site

The Semi-Anechoic Chamber Test Site consists of a 20' x 30' x 18' shielded enclosure. The chamber is lined with Toyo Ferrite Grid Absorber, model number FFG-1000. The ferrite tile grid is 101 x 101 x 19mm thick and weighs approximately 550 grams. These tiles are mounted on steel panels and installed directly on the inner walls of the chamber.

The turntable is 150cm in diameter and is located 160cm from the back wall of the chamber. The chamber is grounded via 1 - 8' copper ground rod, installed at the center of the back wall, it is bound to the ground plane using 3/4" stainless steel braided cable.

The turntable is all steel, flush mounted table installed in an all steel frame. The table is remotely operated from inside the control room located 25' from the range. The turntable is electrically bonded to the surrounding ground plane via steel fingers installed on the edge of the turn table. The steel fingers make constant contact with the ground plane during operation.

Behind the turntable is a 3' x 6' x 4' deep shielded pit used for support equipment if necessary. The pit is equipped with 1 - 4" PVC chases from the turntable to the pit that allow for cabling to the EUT if necessary. The underside of the turntable can be accessed from the pit so cables can be supplied to the EUT from the pit.

A diagram of the Semi-Anechoic Chamber Test Site is shown in Figure 2.3-1 below:




Figure 2.3-1: Semi-Anechoic Chamber Test Site

### 2.3.2 Open Area Tests Site (OATS)

The open area test site consists of a 40' x 66' concrete pad covered with a perforated electro-plated galvanized sheet metal. The perforations in the sheet metal are 1/8" holes that are staggered every 3/16". The individual sheets are placed to overlap each other by 1/4" and are riveted together to provide a continuous seam. Rivets are spaced every 3" in a 3 x 20 meter perimeter around the antenna mast and EUT area. Rivets in the remaining area are spaced as necessary to properly secure the ground plane and maintain the electrical continuity.

The entire ground plane extends 12' beyond the turntable edge and 16' beyond the antenna mast when set to a 10 meter measurement distance. The ground plane is grounded via 4 - 8' copper ground rods, each installed at a corner of the ground plane and bound to the ground plane using 3/4" stainless steel braided cable.

The turntable is an all aluminum 10' flush mounted table installed in an all aluminum frame. The table is remotely operated from inside the control room located 40' from the range. The turntable is electrically bonded to the surrounding ground plane via steel fingers installed on the edge of the turn table. The steel fingers make constant contact with the ground plane during operation.

Adjacent to the turntable is a 7' x 7' square and 4' deep concrete pit used for support equipment if necessary. The pit is equipped with 5 - 4" PVC chases from the pit to the control room that allow for cabling to the EUT if necessary. The underside of the turntable can be accessed from the pit so cables can be supplied to the EUT from the pit. The pit is covered with 2 sheets of 1/4" diamond style re-enforced steel sheets. The sheets are painted to match the perforated steel ground plane; however the underside edges have been masked off to maintain the electrical continuity of the ground plane. All reflecting objects are located outside of the ellipse defined in ANSI C63.4.

A diagram of the Open Area Test Site is shown in Figure 2.3-2 below:




Figure 2.3-2: Open Area Test Site

## 2.4 Conducted Emissions Test Site Description

The AC mains conducted EMI site is located in the main EMC lab. It consists of an 8' x 8' solid aluminum horizontal group reference plane (GRP) bonded every 3" to an 8' X 8' vertical ground plane.

The site is of sufficient size to test table top and floor standing equipment in accordance with section 6.1.4 of ANSI C63.4.

A diagram of the room is shown below in figure 4.1.3-1:




Figure 2.4-1: AC Mains Conducted EMI Site

## 3.0 APPLICABLE STANDARD REFERENCES

The following standards were used:

- ❖ ANSI C63.4-2003: Method of Measurements of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the 9KHz to 40GHz
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 2, Subpart J: Equipment Authorization Procedures, 2006
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 15, Subpart C: Radio Frequency Devices, Intentional Radiators, 2006
- ❖ FCC OET Bulletin 65 Appendix C - Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, 2001
- ❖ FCC Public Notice DA 00-705 - Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems, March 30, 2000
- ❖ Industry Canada Radio Standards Specification: RSS-210 - Low-power License-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, Issue 7 June 2007

**4.0 LIST OF TEST EQUIPMENT**

All test equipment used for regulatory testing is calibrated yearly or according to manufacturer's specifications.

**Table 4-1: Test Equipment**

Equipment Calibration Information					
ACS#	Mfg.	Eq. type	Model	S/N	Cal. Due
331	Microwave Circuits	Filter	H1G513G1	31417	8/27/08
22	Agilent	Amplifier	8449B	3008A00526	10/25/08
30	Spectrum Technologies	Antenna	DRH-0118	970102	5/10/08
291	Florida RF Cables	Cable	SMRE-200W-12.0-SMRE	none	11/21/08
292	Florida RF Cables	Cable	SMR-290AW-480.0-SMR	none	11/21/08
422	Florida RF Cables	Cables	SMS-200AW-72.0-SMR	0805	2/25/09
1	Rohde & Schwarz	Spectrum Analyzer	ESMI - Display	833771/007	10/26/08
2	Rohde & Schwarz	Spectrum Analyzer	ESMI - Receiver	839587/003	10/26/08
282	Rohde & Schwarz	Spectrum Analyzer	FSP40	1000033	11/9/08
152	EMCO	LISN	3835/2	9111-1905	3/26/09
16	ACS	Cable	Cable	16	5/21/08
168	Hewlett Packard	Attenuator	11947A	44829	2/18/09
73	Agilent	Amplifier	8447D	2727A05624	12/19/08
167	ACS	Cable Set	Chamber EMI Set	167	1/4/09
25	Chase	Antenna	CBL6111	1043	6/6/08
211	Eagle	Filter	C7RFM3NFM	HLC-700	1/4/09
213	TEC	Amplifier	PA 102	44927	12/19/08
N/A	Agilent	Spectrum Analyzer	E7405A	MY45104194	4/1/09
193	ACS	Cable	OATS Cable Set	0193	1/4/09
41	Electro Metrics	Antenna	BIA-25	2925	5/29/08
277	Emco	Antenna	93146	9904-5199	6/18/08

## 5.0 SUPPORT EQUIPMENT

Table 5-1: Support Equipment

Manufacturer	Equipment Type	Model Number	Serial Number	FCC ID
<b>EUT Was Self Supporting</b>				

## 6.0 EQUIPMENT UNDER TEST SETUP BLOCK DIAGRAM




Figure 6-1: EUT Test Setup

\*See Test Setup photographs for additional detail.

## 7.0 SUMMARY OF TESTS

Along with the tabular data shown below, plots were taken of all signals deemed important enough to document.

### 7.1 Antenna Requirement

The C2SOD utilizes an embedded quarter wave slot antenna with an estimated gain of 0dBi.

### 7.2 Power Line Conducted Emissions

#### 7.2.1 Test Methodology

ANSI C63.4 sections 6 and 7 were the guiding documents for this evaluation. Conducted emissions were performed from 150kHz to 30MHz with the spectrum analyzer's resolution bandwidth set to 9kHz and the video bandwidth set to 30kHz. The calculation for the conducted emissions is as follows:

**Corrected Reading = Analyzer Reading + LISN Loss + Cable Loss**

**Margin = Applicable Limit - Corrected Reading**

#### 7.2.2 Test Results

Results of the test are shown below in and Table 7.2-1 and Table 7.2-2.

**Table 7.2-1: Conducted EMI Results 120V**

Frequency (MHz)	Uncorrected Reading (dBuV)		Total Correction Factor (dB)	Corrected Level (dBuV)		Limit (dBuV)		Margin (dB)	
	Quasi-Peak	Average		Quasi-Peak	Average	Quasi-Peak	Average	Quasi-Peak	Average
Line 1									
0.382	7.63	1.76	9.80	17.43	11.56	58.24	48.24	40.8	36.7
4.22	27.44	22.32	9.80	37.24	32.12	56.00	46.00	18.8	13.9
12.58	20.09	18.87	10.01	30.10	28.88	60.00	50.00	29.9	21.1
20.97	24.65	24.03	10.12	34.77	34.15	60.00	50.00	25.2	15.9
28.49	12.23	5.55	10.20	22.43	15.75	60.00	50.00	37.6	34.3
29.4	21.62	19.75	10.30	31.92	30.05	60.00	50.00	28.1	20.0
Line 2									
0.382	7.92	1.72	9.80	17.72	11.52	58.24	48.24	40.5	36.7
4.22	28.04	23.15	9.80	37.84	32.95	56.00	46.00	18.2	13.1
9.98	8.13	4.05	9.92	18.05	13.97	60.00	50.00	42.0	36.0
12.52	21.24	20.1	10.01	31.25	30.11	60.00	50.00	28.8	19.9
20.97	25.84	25.3	10.12	35.96	35.42	60.00	50.00	24.0	14.6
29.33	22.75	21.66	10.30	33.05	31.96	60.00	50.00	27.0	18.0

**Table 7.2-2: Conducted EMI Results 240V**

Frequency (MHz)	Uncorrected Reading (dBuV)		Total Correction Factor (dB)	Corrected Level (dBuV)		Limit (dBuV)		Margin (dB)	
	Quasi-Peak	Average		Quasi-Peak	Average	Quasi-Peak	Average	Quasi-Peak	Average
Line 1									
0.15	10.27	2.93	9.80	20.07	12.73	66.00	56.00	45.9	43.3
0.315	8.54	1.95	9.80	18.34	11.75	59.84	49.84	41.5	38.1
0.514	7.71	1.58	9.80	17.51	11.38	56.00	46.00	38.5	34.6
1.57	7.18	0.98	9.80	16.98	10.78	56.00	46.00	39.0	35.2
4.19	27.45	23.16	9.80	37.25	32.96	56.00	46.00	18.8	13.0
12.28	20.41	19.02	10.01	30.42	29.03	60.00	50.00	29.6	21.0
Line 2									
0.15	10.82	2.65	9.80	20.62	12.45	66.00	56.00	45.4	43.6
0.249	8.59	2.11	9.80	18.39	11.91	61.79	51.79	43.4	39.9
0.315	8.52	2.02	9.80	18.32	11.82	59.84	49.84	41.5	38.0
4.19	28.19	24.07	9.80	37.99	33.87	56.00	46.00	18.0	12.1
12.58	21.32	19.99	10.01	31.33	30.00	60.00	50.00	28.7	20.0
20.97	25.42	24.83	10.12	35.54	34.95	60.00	50.00	24.5	15.1

### 7.3 Radiated Emissions - Unintentional Radiation

#### 7.3.1 Test Methodology

Radiated emissions tests were performed over the frequency range of 30MHz to 10GHz. Measurements of the radiated field strength were made at a distance of 3m from the boundary of the equipment under test (EUT) and the receiving antenna. The antenna height was varied from 1m to 4m so that the maximum radiated emissions level would be detected. Radiated measurements above 30MHz and below 1GHz were made with the Spectrum Analyzer's resolution bandwidth set to 120 KHz using a Quasi-peak detector. Above 1GHz, average measurements are taken with the RBW and VBW were set to 1MHz and 10 Hz respectively.

#### 7.3.2 Test Results

Results of the test are given in Table 7.3-1 below:

**Table 7.3-1: Radiated Emissions Tabulated Data**

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
113.14	-----	28.22	V	-8.46	-----	19.76	-----	43.5	-----	23.74
113.471	-----	27.96	H	-9.36	-----	18.60	-----	43.5	-----	24.90
146	-----	27.62	V	-10.36	-----	17.26	-----	43.5	-----	26.24
285.211	-----	47.12	H	-9.24	-----	37.88	-----	46.0	-----	8.12
293.6	-----	47.17	H	-8.96	-----	38.21	-----	46.0	-----	7.79
297.795	-----	48.92	H	-8.79	-----	40.13	-----	46.0	-----	5.87
306.881	-----	42.27	H	-7.60	-----	34.67	-----	46.0	-----	11.33
322.961	-----	49.43	H	-8.02	-----	41.41	-----	46.0	-----	4.59
331.345	-----	44.34	H	-8.29	-----	36.05	-----	46.0	-----	9.95
360.709	-----	44.75	H	-7.69	-----	37.06	-----	46.0	-----	8.94
984.871	-----	21.62	H	3.95	-----	25.57	-----	54.0	-----	28.43

\* Note: All emissions above 984.871 MHz were attenuated below the permissible limit.

## 7.4 Peak Output Power

### 7.4.1 Test Methodology (Conducted Method)

The 20dB bandwidth of the EUT was within the resolution bandwidth of spectrum analyzer, therefore the power measurement was made using the spectrum analyzer method. The RF output port of the EUT was directly connected to the input of the spectrum analyzer. The resolution and video bandwidth were set to > 20 dB bandwidth of the emission measured. The device employs  $\geq 50$  channels therefore the power is limited to 1 Watt.

### 7.4.2 Test Results

Results are shown below in table 7.4-1 and the worst case was plotted and shown in figure 7.4-1 to 7.4-3 below:

Table 7.4-1: RF Output Power

Frequency [MHz]	Level [dBm]
902.25	21.74
915.00	21.40
927.75	20.95




Figure 7.4-1: Output power – Low Channel




Figure 7.4-2: Output power – Mid Channel




Figure 7.4-3: Output power – High Channel

## 7.5 Channel Usage Requirements

### 7.5.1 Carrier Frequency Separation

### 7.5.1.1 Test Methodology

The RF output port of the EUT was directly connected to the input of the spectrum analyzer. The span of the spectrum analyzer was set wide enough to capture two adjacent peaks and the RBW and VBW were set to  $\geq 1\%$  of the span.

### 7.5.1.2 Test Results

The maximum 20dB bandwidth of the hopping channel was measured to be 155kHz (See figure 7.5.4-1 to 7.5.4-3 below). The adjacent channel separation was measured to be 500kHz. Results are shown in figure 7.5.1-1 below:




Figure 7.5.1-1: Carrier Frequency Separation

### 7.5.2 Number of Hopping Channels

The 20dB bandwidth of the device is less than 250 kHz. The device employs  $\geq 50$  hopping channels as required. Results are shown in Figure 7.5.2-1 below:




Figure 7.5.2-1: Number of Hopping Channels

### 7.5.3 Channel Dwell Time

#### 7.5.3.1 Test Methodology

The RF output port of the EUT was directly connected to the input of the spectrum analyzer. The hopping channel is centered on the analyzer and the span set to 0 Hz. The RBW was set to 1 MHz and the VBW to 3 MHz. Sweep time was set to 200 ms to capture the burst duration of the emission. The marker – delta function of the analyzer was employed to measure the burst duration.

#### 7.5.3.2 Test Results

The duration of the RF transmission is 123.1 ms. There is a minimum 7.8 second rest period in which the device hops to another channel according to the pseudorandom frequency table before transmitting another 123.1ms burst. Therefore the average time of occupancy on any channel in a 20 second period is 369ms. A single transmission is shown in figure 7.5.3-1 below:




Figure 7.5.3-1: Channel Dwell Time

### 7.5.4 20dB Bandwidth

#### 7.5.4.1 Test Methodology

The RF output port of the EUT was directly connected to the input of the spectrum analyzer. The spectrum analyzer span was set to 2 to 3 times the estimated 20 dB bandwidth of the emission. The RBW was to  $\geq 1\%$  of the estimated 20 dB bandwidth. The trace was set to max hold with a peak detector active. The Delta function of the analyzer was utilized to determine the 20 dB bandwidth of the emission. The span and RBW were examined and re-adjusted if necessary to meet the requirements of 2 to 3 times the 20 bandwidth for the span and  $\geq 1\%$  of the 20 dB bandwidth for the RBW.

#### 7.5.4.2 Test Results

The maximum 20dB bandwidth was found to be approximately 155kHz. Results are shown below in Table 7.5.4-1 and Figures 7.5.4-1 through 7.5.4-3.

Table 7.5.4-1

Frequency (MHz)	20dB Bandwidth (kHz)
902.25	155
915.00	154
927.75	148



Figure 7.5.4-1: 20dB Bandwidth Low Channel



Figure 7.5.4-2: 20dB Bandwidth Mid Channel




Figure 7.5.4-3: 20dB Bandwidth High Channel

## 7.6 Band-Edge Compliance and Spurious Emissions

### 7.6.1 Band-Edge Compliance of RF Conducted Emissions

#### 7.6.1.1 Test Methodology

The RF output port of the EUT was directly connected to the input of the spectrum analyzer. The EUT was investigated at the lowest and highest channel available to determine band-edge compliance. For each measurement the spectrum analyzer's RBW was set to 30 kHz, which is  $\geq 1\%$  of the span, and the VBW was set to 100 kHz.

#### 7.6.1.2 Test Results

In a 100 kHz bandwidth at the lower and upper band-edge, the radio frequency power that was produced by the EUT is at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of desired power. Band-edge compliance is displayed in Figures 7.6.1-1 and 7.6.2-2.




Figure 7.6.1-1: Lower Band-edge




Figure 7.6.1-2: Upper Band-edge

## 7.6.2 RF Conducted Spurious Emissions

### 7.6.2.1 Test Methodology

The RF output port of the EUT was directly connected to the input of the spectrum analyzer. The EUT was investigated for conducted spurious emissions from 30MHz to 10GHz, 10 times the highest fundamental frequency. Measurements were made at the low, center and high channels of the EUT. For each measurement, the spectrum analyzer's RBW was set to 100kHz. A peak detector function was used with the trace set to max hold.

### 7.6.2.1 Test Results

All emission found were greater than 20dB down from the fundamental carrier. The RF conducted spurious emissions were measured in the band of 30MHz to 10GHz. Results are shown below in Figure 7.6.2-1 through 7.6.2-6.




Figure 7.6.2-1 RF Conducted Spurious Emissions – Low Channel




Figure 7.6.2-2 RF Conducted Spurious Emissions – Low Channel




Figure 7.6.2-3 RF Conducted Spurious Emissions – Mid Channel




Figure 7.6.2-4 RF Conducted Spurious Emissions – Mid Channel




Figure 7.6.2-5 RF Conducted Spurious Emissions – High Channel




Figure 7.6.2-6 RF Conducted Spurious Emissions – High Channel

### 7.6.3 Radiated Spurious Emissions – Intentional Radiation (Restricted Bands)

#### 7.6.3.1 Test Methodology

Radiated emissions tests were made over the frequency range of 30MHz to 10GHz, 10 times the highest fundamental frequency.

The EUT was rotated through 360° and the receive antenna height was varied from 1m to 4m so that the maximum radiated emissions level would be detected. For frequencies below 1000MHz, quasi-peak measurements were made using a resolution bandwidth (RBW) of 120 kHz and a video bandwidth (VBW) of 300 kHz. For frequencies above 1000MHz, average measurements were made using an RBW of 1 MHz and a VBW of 10 Hz and peak measurements were made with RBW of 1 MHz and a VBW of 1 MHz.

The EUT was caused to generate a continuous carrier signal on the hopping channel.

Inter-modulation data was measured and all emissions were found to be below the permissible level.

#### 7.6.3.3 Test Results

\* The magnitude of all emissions not reported were below the noise floor of the measurement system and below the permissible limit.

## 8.0 CONCLUSION

In the opinion of ACS, Inc. the C2SOD, manufactured by Itron Electricity Metering, Inc. meets the requirements of FCC Part 15 subpart C and Industry Canada's Radio Standards Specification RSS-210.

**END REPORT**