



Certification Exhibit

FCC ID: SL6MINIMINI

FCC Rule Part: 47 CFR Part 2.1093

TÜV SÜD Project Number: 72155614

**Manufacturer: HID Global Bluvision Inc
Model: MiniMini**

RF Exposure

TÜV SÜD America
5610 West Sligh Ave., Suite 100
Tampa, FL 33634

Phone: 813-284-2715
www.tuv-sud-america.com

General Information:

Applicant: HID Global Bluvision Inc
Environment: General Population/Uncontrolled Exposure
Exposure Conditions: Portable

Technical Information:

Minimum Test Separation Distance: 5 mm
Highest Operating Frequency: 2480 MHz
Antenna Type: PCB Embedded Antenna
Antenna Gain: 0 dBi
Maximum Transmitter Conducted Power: -0.19 dBm, 0.96 mW
Maximum Transmitter EIRP: -0.19 dBm, 0.96 mW

Justification for SAR Test Exclusion:**Standalone SAR Test Exclusion:**

Per KDB 447498 D01 General RF Exposure Guidance v05r02, the standalone 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \left[\sqrt{f(\text{GHz})} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

$$= (0.96 / 5) \cdot (\sqrt{2.48}) = 0.3$$

0.3 < 3.0

Standalone SAR test exclusion is applied.