

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan  
District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
Email: ee.shenzhen@sgs.com

Report No.: SZEM140200063502  
Page: 1 of 57

## FCC REPORT

**Application No:**

SZEM1402000635RF

**Applicant:**

Shenzhen Baojia Battery Technology Co., Ltd

**Manufacturer:**

Shenzhen Baojia Battery Technology Co., Ltd

**Factory:**

Shenzhen Baojia Battery Technology Co., Ltd

**Product Name:**

MIPOW M3

**Model No.(EUT):**

BTX500

**Trade mark:**

MIPOW

**FCC ID:**

SL7BTX500

**Standards:**

47 CFR Part 15, Subpart C (2013)

**Date of Receipt:**

2014-02-27

**Date of Test:**

2014-03-06 to 2014-03-12

**Date of Issue:**

2014-04-01

**Test Result:**

**PASS \***

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang  
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

## 2 Test Summary

Test Item	Test Requirement	Test method	Result
<b>Antenna Requirement</b>	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2009	PASS
<b>AC Power Line Conducted Emission</b>	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2009	PASS
<b>Conducted Peak Output Power</b>	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	KDB558074 D01 v03r01	PASS
<b>6dB Occupied Bandwidth</b>	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	KDB558074 D01 v03r01	PASS
<b>Power Spectral Density</b>	47 CFR Part 15, Subpart C Section 15.247 (e)	KDB558074 D01 v03r01	PASS
<b>Band-edge for RF Conducted Emissions</b>	47 CFR Part 15, Subpart C Section 15.247(d)	KDB558074 D01 v03r01	PASS
<b>RF Conducted Spurious Emissions</b>	47 CFR Part 15, Subpart C Section 15.247(d)	KDB558074 D01 v03r01	PASS
<b>Radiated Spurious Emissions</b>	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS
<b>Restricted bands around fundamental frequency (Radiated Emission)</b>	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS

### 3 Contents

	Page
1 COVER PAGE .....	1
2 TEST SUMMARY .....	2
3 CONTENTS .....	3
4 GENERAL INFORMATION .....	4
4.1 CLIENT INFORMATION .....	4
4.2 GENERAL DESCRIPTION OF EUT .....	4
4.3 TEST ENVIRONMENT .....	6
4.4 DESCRIPTION OF SUPPORT UNITS .....	6
4.5 TEST LOCATION .....	6
4.6 TEST FACILITY .....	7
4.7 DEVIATION FROM STANDARDS .....	8
4.8 ABNORMALITIES FROM STANDARD CONDITIONS .....	8
4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....	8
5 EQUIPMENT LIST .....	9
6 TEST RESULTS AND MEASUREMENT DATA .....	13
6.1 ANTENNA REQUIREMENT .....	13
6.2 CONDUCTED EMISSIONS .....	14
6.3 CONDUCTED PEAK OUTPUT POWER .....	18
6.4 6dB OCCUPY BANDWIDTH .....	21
6.5 POWER SPECTRAL DENSITY .....	24
6.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS .....	27
6.7 SPURIOUS RF CONDUCTED EMISSIONS .....	29
6.8 RADIATED SPURIOUS EMISSION .....	39
6.8.1 Spurious Emissions .....	39
6.9 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY .....	46
7 PHOTOGRAPHS - EUT TEST SETUP .....	56
7.1 CONDUCTED EMISSION .....	56
7.2 RADIATED EMISSION .....	56
7.3 RADIATED SPURIOUS EMISSION .....	57
8 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS .....	57

## 4 General Information

### 4.1 Client Information

Applicant:	Shenzhen Baojia Battery Technology Co., Ltd
Address of Applicant:	Block A, yonghe Road, Tongfuyu Industrial Zone, Heping, Fuyong, Baoan Shenzhen, China
Manufacturer:	Shenzhen Baojia Battery Technology Co., Ltd
Address of Manufacturer:	Block A, yonghe Road, Tongfuyu Industrial Zone, Heping, Fuyong, Baoan Shenzhen, China
Factory:	Shenzhen Baojia Battery Technology Co., Ltd
Address of Factory:	Block A, yonghe Road, Tongfuyu Industrial Zone, Heping, Fuyong, Baoan Shenzhen, China

### 4.2 General Description of EUT

Name:	MIPOW M3	
Model No.:	BTX500	
Trade Mark:	MIPOW	
Operation Frequency:	2402MHz~2480MHz	
Bluetooth Version:	V4.0 (with BLE mode)	
Modulation Type:	GFSK	
Number of Channel:	40	
EUT Function:	DAVINCI 500	
Sample Type:	Portable production	
Test Power Grade:	-1 (manufacturer declare )	
Test Software of EUT:	Bluetest3 (manufacturer declare )	
Antenna Type	Integral	
Antenna Gain	2.114dBi	
Power Supply:	AC adapter	Supply by SGS
	USB charge: DC 5V Rechargeable Battery: -BJ303040 +3H153I29	
Test Voltage:	AC 120V 60Hz	
Retractable Audio Cable:	100cm (Unshielded)	
USB Cable:	100cm (Shielded)	
Detachable Audio Cable:	120cm (Unshielded)	



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	11	2422MHz	21	2442MHz	31	2462MHz
2	2404MHz	12	2424MHz	22	2444MHz	32	2464MHz
3	2406MHz	13	2426MHz	23	2446MHz	33	2466MHz
4	2408MHz	14	2428MHz	24	2448MHz	34	2468MHz
5	2410MHz	15	2430MHz	25	2450MHz	35	2470MHz
6	2412MHz	16	2432MHz	26	2452MHz	36	2472MHz
7	2414MHz	17	2434MHz	27	2454MHz	37	2474MHz
8	2416MHz	18	2436MHz	28	2456MHz	38	2476MHz
9	2418MHz	19	2438MHz	29	2458MHz	39	2478MHz
10	2420MHz	20	2440MHz	30	2460MHz	40	2480MHz

**Note:**

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2440MHz
The Highest channel	2480MHz

### 4.3 Test Environment

Operating Environment:	
Temperature:	25.0 °C
Humidity:	55 % RH
Atmospheric Pressure:	1015 mbar

### 4.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.
Adapter	Supply by SGS	Output: 5V == 1A

### 4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory,  
198 Kezhu Road, Scientech Park, Guangzhou Economic & Technology Development District,  
Guangzhou, China 510663  
Tel: +86 20 82155555 Fax: +86 20 82075059

## 4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

- **FCC (Registration No.: 282399)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

- **Industry Canada (Registration No.: 4620B-1)**

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

- **VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IECEE 01:2006-10 and Rules of procedure IECEE 02:2006-10, and the relevant IECEE CB-Scheme Operational documents.

#### 4.7 Deviation from Standards

None.

#### 4.8 Abnormalities from Standard Conditions

None.

#### 4.9 Other Information Requested by the Customer

None.

## 5 Equipment List

Conducted Emission						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date	Calibration Interval
					(YYYY-MM-DD)	
EMC0306	Shielding Room	Zhong Yu	8 x 3 x 3.8 m <sup>3</sup>	N/A	N/A	N/A
EMC0118	Two-line v-netwok	R&S	ENV216	100359	2015-03-03	1Y
EMC0102	LISN	SCHAFFNER CHASE	MN2050D/1	1421	2014-08-31	1Y
EMC2046	Artificial Mains Network (LISN)	AFJ Instruments	LT32C	S.N.32031120150	2015-03-03	1Y
EMC0506	EMI Test Receiver	Rohde & Schwarz	ESCS30	100085	2015-03-03	1Y
EMC0107	Coaxial Cable	SGS	2m	N/A	2014-07-25	2Y
EMC0106	Voltage Probe	SGS	N/A	N/A	N/A	1Y
EMC0120	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	20550	2014-08-31	1Y
EMC0121	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	20549	2014-08-31	1Y
EMC0122	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	20548	2014-08-31	1Y
EMC2047	CDN	Elektronik-Feinmechanik	L-801:AF2	2793	2014-11-11	3Y
EMC2048	CDN	Elektronik-Feinmechanik	L-801:M2/M3	2738	2014-11-11	3Y
EMC2062	6dB Attenuator	HP	8491A	24487	2015-01-04	1Y
EMC167	Conical metal housing	SGS-EMC	N/A	N/A	2016-02-16	2Y

RE in Chamber						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date	Calibration Interval
					(YYYY-MM-DD)	
EMC0525	Compact Semi-Anechoic Chamber	ChangZhou ZhongYu	N/A	N/A	2014-08-30	2Y
EMC0522	EMI Test Receiver	Rohde & Schwarz	ESIB26	100283	2014-05-06	1Y
EMC0056	EMI Test Receiver	Rohde & Schwarz	ESCI	100236	2015-03-03	1Y
EMC0528	RI High frequency Cable	SGS	20 m	N/A	2014-05-09	1Y
EMC2025	Trilog Broadband Antenna 30-3000MHz	SCHWARZBECK MESS-ELEKTRONIK	VULB 9163	9163-450	2016-08-31	3Y
EMC0524	Bi-log Type Antenna	Schaffner -Chase	CBL6112B	2966	2016-08-31	3Y
EMC0519	Bilog Type Antenna	Schaffner -Chase	CBL6143	5070	2014-06-02	2Y
EMC2026	Horn Antenna 1-18GHz	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	9120D-841	2016-08-31	3Y
EMC0518	Horn Antenna	Rohde & Schwarz	HF906	100096	2014-07-01	2Y
EMC0521	1-26.5 GHz Pre-Amplifier	Agilent	8449B	3008A01649	2015-03-03	1Y
EMC2065	Amplifier	HP	8447F	N/A	2014-08-31	1Y
EMC2063	1-26GHz Pre Amplifier	Compliance Direction System Inc.	PAP-1G26-48	6279.628	2014-07-29	1Y
EMC0075	310N Amplifier	Sonama	310N	272683	2015-03-03	1Y
EMC0523	Active Loop Antenna	EMCO	6502	42963	2014-04-07	2Y
EMC2041	Broad-Band Horn Antenna (14)15-26.5(40)GHz	SCHWARZBECK MESS-ELEKTRONI	BBHA 9170	9170-375	2014-06-01	3Y
EMC2069	2.4GHz filter	Micro-Tronics	BRM 50702	149	2014-06-05	1Y
EMC0530	10m Semi-Anechoic Chamber	ETS	N/A	N/A	2014-04-27	2Y
EMC2041	Broad-Band Horn Antenna(14)15-26.5(40)GHz	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9170	9170-375	2014-06-11	3Y



RF connected test						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date	Calibration Interval
					(YYYY-MM-DD)	
EMC0039	Temperature Chamber	GZ GongWen Co.Ltd.	GDJW-100	118	2014-08-31	1Y
EMC2022	DC Power Supply	KIKUSUI ELECTRONICS CORP.	PAN60-20A	HH000269	2014-05-06	1Y
EMC0007	DMM	Fluke	73	70671122	2014-09-13	1Y
EMC0006	DMM	Fluke	73	70681569	2014-09-13	1Y
EMC0525	Compact Semi-Anechoic Chamber	ChangZhou ZhongYu	N/A	N/A	N/A	N/A
EMC0530	10m Semi- Anechoic Chamber	ETS	N/A	N/A	2014-04-27	2Y
EMC0502	Biconical Antenna (Rx)	Rohde & Schwarz	HK116	100032	2014-08-30	2Y
EMC0503	Biconical Antenna (Tx)	Rohde & Schwarz	HK116	100033	2014-07-01	2Y
EMC0504	Log-Perd. Dipole Antenna (Rx)	Rohde & Schwarz	HL223	100039	2014-08-30	2Y
EMC0518	Horn Antenna (Rx)	Rohde & Schwarz	HF906	100096	2014-07-01	2Y
EMC0519	Bilog Type Antenna	Schaffner Chase	CBL6143	5070	2014-06-02	2Y
EMC0521	1-26.5GHz Pre Amplifier	Agilent	8449B	3008A01649	2015-03-03	1Y
EMC2063	1-26GHz Pre Amplifier	Compliance Direction System Inc.	PAP-1G26-48	6279.628	2014-07-29	1Y
EMC0075	9KHz-1GHz Pre Amplifier	SONOMA INSTRUMENT Co.	310N	272683	2015-03-03	1Y
EMC0507	Antenna Mask (Tx)	HD-GmbH	AS620M	620/408	N/A	N/A
EMC0508	Antenna Mask (Rx)	HD-GmbH	MA240	240/619	N/A	N/A
EMC0509	Turntable	HD-GmbH	DT430	N/A	N/A	N/A
EMC0510	Turntable & Antenna Mask Controller	HD-GmbH	HD100	N/A	N/A	N/A
EMC0512	EMI Test Software	Rohde & Schwarz	ES-K1	N/A	N/A	N/A
EMC0522	EMI Test Receiver	Rohde & Schwarz	ESIB26	100283	2014-05-06	1Y
EMC0516	Signal Generator	Rohde & Schwarz	SMR20	100416	2014-05-06	1Y
EMC0032	Radio Communication Monitor	Rohde & Schwarz	CMS54	100137	2014-08-31	1Y
EMC0904	Power Meter	Rohde & Schwarz	NRVS	825770/074	2015-03-03	1Y


EMC0071	URV5-Z2 Insert. Unit	Rohde & Schwarz	URV5-Z2	100309	2015-03-03	1Y
EMC0906	Dual Directional Coupler	Werlatone Inc.	C1795	6634	2014-08-31	1Y
EMC2012	Power-Electronics Measurement System	Tektronix	TDS 744A	N/A	2015-03-03	1Y
EMC0523	Active Loop Antenna	EMCO	6502	42963	2014-04-07	2Y
EMC0069	Signal Analyzer (20Hz ~ 26.5Ghz)	R&S	FSIQ26	100312	2015-03-03	1Y
EMC2041	Broad-Band Horn Antenna(14)15-26.5(40)GHz	SCHWARZBECK MESS-ELEKTRONI	BBHA 9170	9170-375	2014-06-01	3Y
EMC0078	Temperature, & Humidity	Shanghai Meteorological Instrument factory Co., Ltd.	ZJ1-2B	709131	2014-09-13	1Y

**Note: The calibration interval is one year, all the instruments are valid.**

## 6 Test results and Measurement Data

### 6.1 Antenna Requirement


<b>Standard requirement:</b>	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
15.247(b) (4) requirement:	The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
<b>EUT Antenna:</b>	The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.114dBi.



## 6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2009		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)		Limit (dBuV)
			Quasi-peak
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
Test Procedure:	5-30	60	50
	* Decreases with the logarithm of the frequency.		
	<ol style="list-style-type: none"><li>1) The mains terminal disturbance voltage test was conducted in a shielded room.</li><li>2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a <math>50\Omega/50\mu\text{H} + 5\Omega</math> linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</li><li>3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,</li><li>4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.</li><li>5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2009 on conducted measurement.</li></ol>		




Test Setup:	
Test Mode:	AC charge + Transmitting mode
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

**Measurement Data**

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live line:




Site : Shielding Room  
Condition : 47 CFR PART 15 B QP GZ LISN EMC0118 2014 LINE  
Job No. : 0635RF  
Mode : AC charge + TX

Freq	Cable	LISN	Read	Limit	Over	Remark
	MHz	dB	dB	dBuV	dBuV	
1	0.53498	0.07	9.70	22.12	31.89	56.00 -24.11 QP
2	0.53498	0.07	9.70	12.38	22.15	46.00 -23.85 Average
3	0.85729	0.05	9.70	3.72	13.47	46.00 -32.53 Average
4	0.85729	0.05	9.70	13.63	23.38	56.00 -32.62 QP
5	1.082	0.05	9.70	16.42	26.17	56.00 -29.83 QP
6	1.082	0.05	9.70	6.70	16.45	46.00 -29.55 Average
7	3.009	0.15	9.70	15.81	25.66	56.00 -30.34 QP
8	3.009	0.15	9.70	5.70	15.56	46.00 -30.44 Average
9	5.653	0.18	9.74	9.64	19.56	50.00 -30.44 Average
10	5.653	0.18	9.74	19.62	29.53	60.00 -30.47 QP
11	7.486	0.17	9.80	20.19	30.16	60.00 -29.84 QP
12	7.486	0.17	9.80	10.41	20.38	50.00 -29.62 Average

Neutral line:

Data: 76

Level (dBuV)




Site : Shielding Room  
 Condition : 47 CFR PART 15 B QP GZ LISN EMC0118 2014 NEUTRAL  
 Job No. : 0635RF  
 Mode : AC charge + TX

Freq	Cable	LISN	Read	Limit	Over	
	MHz	dB	dB	dBuV	dBuV	dB
1 0	0.52654	0.07	9.66	28.93	38.67	56.00 -17.33 QP
2	0.52654	0.07	9.66	18.69	28.42	46.00 -17.58 Average
3	0.68626	0.06	9.67	22.68	32.41	56.00 -23.59 QP
4	0.68626	0.06	9.67	12.45	22.18	46.00 -23.82 Average
5	2.297	0.08	9.69	22.37	32.15	56.00 -23.85 QP
6	2.297	0.08	9.69	12.31	22.09	46.00 -23.91 Average
7	4.549	0.17	9.71	23.67	33.55	56.00 -22.45 QP
8	4.549	0.17	9.71	12.36	22.24	46.00 -23.76 Average
9	5.961	0.18	9.72	24.45	34.35	60.00 -25.65 QP
10	5.961	0.18	9.72	14.88	24.78	50.00 -25.22 Average
11	8.235	0.19	9.78	26.84	36.81	60.00 -23.19 QP
12	8.235	0.19	9.78	16.68	26.65	50.00 -23.35 Average

**Notes:**

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.

### 6.3 Conducted Peak Output Power


Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)
Test Method:	KDB558074 D01 v03r01
Test Setup:	 <p><b>Spectrum Analyzer</b> E.U.T Non-Conducted Table Ground Reference Plane</p> <p><i>Remark:</i> <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p>
Limit:	30dBm
Test Mode:	Non-hopping transmitting with GFSK modulation
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

#### Measurement Data


GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-2.17	30.00	Pass
Middle	1.34	30.00	Pass
Highest	1.12	30.00	Pass

**Test plot as follows:**


Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------



Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------



## 6.4 6dB Occupy Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	KDB558074 D01 v03r01
Test Setup:	
Limit:	$\geq 500$ kHz
Test Mode:	Non-hopping transmitting with GFSK modulation
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

### Measurement Data


Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	0.701923076923	$\geq 500$	Pass
Middle	0.701923076923	$\geq 500$	Pass
Highest	0.701923076923	$\geq 500$	Pass

**Test plot as follows:**


Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------



Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------



## 6.5 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	KDB558074 D01 v03r01
Test Setup:	
Limit:	≤8.00dBm
Test Mode:	Non-hopping transmitting with GFSK modulation
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass


### Measurement Data

GFSK mode			
Test channel	Power Spectral Density (dBm)	Limit (dBm)	Result
Lowest	-2.74	≤8.00	Pass
Middle	0.78	≤8.00	Pass
Highest	0.57	≤8.00	Pass




**Test plot as follows:**


Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------



Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------




## 6.6 Band-edge for RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	KDB558074 D01 v03r01
Test Setup:	 <p>Diagram illustrating the test setup for RF Conducted Emissions. A Spectrum Analyzer is connected to the E.U.T (Equipment Under Test) via a cable. The E.U.T is placed on a Non-Conducted Table. The entire setup is positioned above a Ground Reference Plane.</p> <p>Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</p>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Non-hopping transmitting with GFSK modulation
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

**Test plot as follows:**


Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------



Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------







## 6.7 Spurious RF Conducted Emissions



Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	KDB558074 D01 v03r01
Test Setup:	
Remark:	Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Non-hopping transmitting with GFSK modulation
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

**Test plot as follows:**



Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------













Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------











Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------






**Remark:**

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report.

## 6.8 Radiated Spurious Emission

6.8.1 Spurious Emissions					
Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2009				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					
Test Setup:					




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1 GHz

## Test Procedure:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel (2402MHz), the middle channel (2440MHz), the Highest channel (2480MHz)
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which is worse

	case i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting with GFSK modulation Transmitting mode, AC charge +Transmitting mode
Final Test Mode:	Pretest the EUT at Transmitting mode and AC charge +Transmitting mode, found the AC charge +Transmitting mode which it is worse case. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

Radiated Emission below 1GHz		
30MHz~1GHz (QP)		
Test mode:	AC charge +Transmitting mode	Vertical




Condition: 47 CFR PART 15B 3m GZ VULB 9163 3M 2010 VERTICAL

Job No. : 0635RF

Mode : AC charge+TX

Freq	Cable		Antenna	Preamp	Read	Limit	Over
	Loss	Factor	Factor	Level	Level		
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	47.33	0.98	13.41	31.60	45.39	28.18	40.00 -11.82
2	70.09	1.23	8.65	31.60	47.10	25.38	40.00 -14.62
3	131.30	1.62	8.82	31.51	44.43	23.36	43.50 -20.14
4	211.53	1.95	10.93	31.30	50.80	32.38	43.50 -11.12
5	261.06	2.20	12.09	31.30	43.24	26.23	46.00 -19.77
6	345.60	2.54	14.20	31.19	40.39	25.94	46.00 -20.06

Test mode:	AC charge +Transmitting mode	Horizontal
------------	------------------------------	------------



Condition: 47 CFR PART 15B 3m GZ VULB 9163 3M 2010 HORIZONTAL

Job No. : 0635RF

Mode : AC charge+TX

Freq	Cable		Antenna	Preamp	Read	Limit	Over
	Loss	Factor	Factor	Level	Level		
1	85.00	1.31	10.31	31.60	39.48	19.50	40.00 -20.50
2	176.27	1.81	9.42	31.33	38.46	18.36	43.50 -25.14
3	266.61	2.22	12.26	31.30	46.16	29.34	46.00 -16.66
4	338.40	2.51	14.05	31.21	43.50	28.85	46.00 -17.15
5	492.47	3.07	16.39	31.20	39.15	27.41	46.00 -18.59
6	965.54	4.22	21.52	30.52	31.50	26.72	54.00 -27.28

Transmitter Emission above 1GHz									
Test mode:		GFSK		Test channel:		Lowest		Remark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
2987.923	7.91	28.47	45.10	51.02	42.30	74	-31.70	Vertical	
3863.900	10.52	29.67	44.82	48.86	44.23	74	-29.77	Vertical	
4804.000	11.11	31.53	45.16	49.80	47.28	74	-26.72	Vertical	
7206.000	12.90	36.47	45.44	44.90	48.83	74	-25.17	Vertical	
9608.000	15.16	38.08	45.87	42.93	50.30	74	-23.70	Vertical	
12086.330	17.26	39.33	47.06	43.25	52.78	74	-21.22	Vertical	
3018.502	7.96	28.51	45.10	50.73	42.10	74	-31.90	Horizontal	
3943.392	10.85	29.80	44.81	48.30	44.14	74	-29.86	Horizontal	
4804.000	11.11	31.53	45.16	50.45	47.93	74	-26.07	Horizontal	
7206.000	12.90	36.47	45.44	45.06	48.99	74	-25.01	Horizontal	
9608.000	15.16	38.08	45.87	43.47	50.84	74	-23.16	Horizontal	
12055.600	17.21	39.32	47.06	43.20	52.67	74	-21.33	Horizontal	

Test mode:		GFSK		Test channel:		Middle		Remark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3026.195	7.98	28.53	45.09	51.43	42.85	74	-31.15	Vertical	
3893.520	10.62	29.72	44.81	47.56	43.09	74	-30.91	Vertical	
4880.000	11.24	31.57	45.18	52.22	49.85	74	-24.15	Vertical	
7320.000	13.28	36.50	45.54	44.16	48.40	74	-25.60	Vertical	
9760.000	15.05	38.46	45.88	42.59	50.22	74	-23.78	Vertical	
12272.340	17.51	39.35	47.07	43.11	52.90	74	-21.10	Vertical	
3018.502	7.96	28.51	45.10	50.71	42.08	74	-31.92	Horizontal	
3943.392	10.85	29.80	44.81	47.59	43.43	74	-30.57	Horizontal	
4880.000	11.24	31.57	45.18	49.08	46.71	74	-27.29	Horizontal	
7320.000	13.28	36.50	45.54	44.92	49.16	74	-24.84	Horizontal	
9760.000	15.05	38.46	45.88	43.22	50.85	74	-23.15	Horizontal	
12086.330	17.26	39.33	47.06	43.20	52.73	74	-21.27	Horizontal	



Test mode:		GFSK		Test channel:		Highest		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization		
2995.538	7.92	28.47	45.10	52.20	43.49	74	-30.51	Vertical		
3903.444	10.66	29.75	44.81	48.90	44.50	74	-29.50	Vertical		
4960.000	11.39	31.70	45.19	48.56	46.46	74	-27.54	Vertical		
7440.000	13.60	36.60	45.68	44.41	48.93	74	-25.07	Vertical		
9920.000	14.92	38.65	45.89	43.37	51.05	74	-22.95	Vertical		
11812.580	16.69	39.51	47.04	43.76	52.92	74	-21.08	Vertical		
3018.502	7.96	28.51	45.10	51.05	42.42	74	-31.58	Horizontal		
3933.367	10.80	29.79	44.81	48.14	43.92	74	-30.08	Horizontal		
4960.000	11.39	31.70	45.19	51.73	49.63	74	-24.37	Horizontal		
7440.000	13.60	36.60	45.68	45.17	49.69	74	-24.31	Horizontal		
9920.000	14.92	38.65	45.89	43.59	51.27	74	-22.73	Horizontal		
12055.600	17.21	39.32	47.06	42.98	52.45	74	-21.55	Horizontal		

**Remark:**

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported .
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

## 6.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10 2009		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			




Figure 1. 30MHz to 1GHz





Figure 2. Above 1 GHz

Test Procedure:	<ol style="list-style-type: none"> <li>The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel</li> </ol>
-----------------	---

	<ul style="list-style-type: none"><li>g. Test the EUT in the lowest channel , the Highest channel</li><li>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case.</li><li>i. Repeat above procedures until all frequencies measured was complete.</li></ul>
Exploratory Test Mode:	Non-hopping transmitting with GFSK modulation. Transmitting mode, AC charge +Transmitting mode
Final Test Mode:	Pretest the EUT at Transmitting mode and AC charge +Transmitting mode, found the AC charge +Transmitting mode which it is worse case Only the worst case is recorded in the report.
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

**Test plot as follows:**

Worse case mode:	GFSK	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	------	---------------	--------	---------	------	----------

**Data: 63****Level (dBuV/m)**

Condition : FCC PART15(&gt;1G) PK 3m VERTICAL

Job No. : 0635RF


Mode : 2402 BLE

Freq	Cable Loss	Antenna Factor	Preamp Factor	Read Level		Limit Line	Over Limit
				dB	dBuV		
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.000	6.55	27.63	44.97	53.15	42.37	74.00 -31.63
2	2402.245	6.56	27.58	44.98	101.16	90.33	74.00 16.33

Worse case mode:	GFSK	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	------	---------------	--------	---------	------	------------

Data: 2

Level (dBuV/m)




Condition : FCC PART15(&gt;1G) PK 3m HORIZONTAL

Job No. : 0635RF

Mode : 2402 BLE

	Freq	Cable	Antenna	Preamp	Read	Limit	Over	
		Loss	Factor	Factor	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.000	6.55	27.63	44.97	54.20	43.41	74.00	-30.59
2 X	2402.245	6.56	27.58	44.98	101.27	90.43	74.00	16.43

Worse case mode:	GFSK	Test channel:	Lowest	Remark:	Average	Vertical
------------------	------	---------------	--------	---------	---------	----------

**Data: 64**  
Level (dBuV/m)


Condition : FCC PART15(&gt;1G) AV 3m VERTICAL

Job No. : 0635RF

Mode : 2402 BLE

	Freq	Cable	Antenna	Preamp	Read	Limit	Over	
		Loss	Factor	Factor	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.000	6.55	27.63	44.97	40.34	29.56	54.00	-24.44
2	2402.150	6.56	27.58	44.98	81.75	70.91	54.00	16.91

Worse case mode:	GFSK	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	------	---------------	--------	---------	---------	------------

**Data: 1**  
Level (dBuV/m)

Condition : FCC PART15(&gt;1G) AV 3m HORIZONTAL

Job No. : 0635RF


Mode : 2402 BLE

	Freq	Cable	Antenna	Preamp	Read	Limit	Over	
		Loss	Factor	Factor	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.000	6.55	27.63	44.97	42.30	31.52	54.00	-22.48
2	2402.150	6.56	27.58	44.98	81.52	70.68	54.00	16.68

Worse case mode:	GFSK	Test channel:	Highest	Remark:	Peak	Vertical
------------------	------	---------------	---------	---------	------	----------

**Data: 5**

Level (dBuV/m)




Condition : FCC PART15(&gt;1G) PK 3m VERTICAL

Job No. : 0635RF

Mode : 2480 BLE

		Cable	Antenna	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 X	2479.750	6.98	27.56	45.02	100.92	90.44	74.00	16.44
2	2483.500	6.99	27.55	45.02	62.31	51.84	74.00	-22.16

Worse case mode:	GFSK	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	------	---------------	---------	---------	------	------------

**Data: 3**


Condition : FCC PART15(&gt;1G) PK 3m HORIZONTAL

Job No. : 0635RF

Mode : 2480 BLE

		Cable	Antenna	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	0	2479.675	6.98	27.56	45.02	102.40	91.92	74.00	17.92
2		2483.500	6.99	27.55	45.02	63.74	53.27	74.00	-20.73

Worse case mode:	GFSK	Test channel:	Highest	Remark:	Average	Vertical
------------------	------	---------------	---------	---------	---------	----------

**Data: 6**  
**Level (dBuV/m)**

Condition : FCC PART15(&gt;1G) AV 3m VERTICAL


Job No. : 0635RF

Mode : 2480 BLE

	Freq	Cable Loss	Antenna Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m		dB	dBuV	dBuV/m	dBuV/m	dB
1	2479.875	6.98	27.56	45.02	81.89	71.41	54.00	54.00	17.41
2	2483.500	6.99	27.55	45.02	56.42	45.95	54.00	54.00	-8.05



Worse case mode:	GFSK	Test channel:	Highest	Remark:	Average	Horizontal
------------------	------	---------------	---------	---------	---------	------------

**Data: 4****Level (dBuV/m)**

Condition : FCC PART15(&gt;1G) AV 3m HORIZONTAL

Job No. : 0635RF

Mode : 2480 BLE

	Freq	Cable	Antenna	Preamp	Read	Limit	Line	Over
		Loss	Factor	Factor	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2479.975	6.98	27.56	45.02	82.49	72.01	54.00	18.01
2	2483.500	6.99	27.55	45.02	56.88	46.41	54.00	-7.59

**Note:**


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor


## 7 Photographs - EUT Test Setup

Test model No.: BTX500


### 7.1 Conducted Emission



### 7.2 Radiated Emission



### 7.3 Radiated Spurious Emission



## 8 Photographs - EUT Constructional Details

**Test model No.: BTX500**

Refer to Report No. SZEM140200063501 for EUT external and internal photos.