

FCC Test Report

Report No.: RF150527C04

FCC ID: SLY-WX1X33

Test Model: WX-1

Series Model: WX-1-B

Received Date: May 27, 2015

Test Date: Jun. 12 ~ Jun. 24, 2015

Issued Date: Jun. 29, 2015

Applicant: Packedge Device and Software Inc.

Address: 3847 Breakwater Ave., Hayward, California, United States, 94545

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Description of Test Modes	8
3.2.1 Test Mode Applicability and Tested Channel Detail	9
3.3 Duty Cycle of Test Signal	11
3.4 Description of Support Units	12
3.4.1 Configuration of System under Test	13
3.5 General Description of Applied Standards	14
4 Test Types and Results	15
4.1 Radiated Emission and Bandedge Measurement	15
4.1.1 Limits of Radiated Emission and Bandedge Measurement	15
4.1.2 Test Instruments	16
4.1.3 Test Procedures	17
4.1.4 Deviation from Test Standard	17
4.1.5 Test Set Up	18
4.1.6 EUT Operating Conditions	18
4.1.7 Test Results	19
4.2 Conducted Emission Measurement	33
4.2.1 Limits of Conducted Emission Measurement	33
4.2.2 Test Instruments	33
4.2.3 Test Procedures	34
4.2.4 Deviation from Test Standard	34
4.2.5 Test Setup	34
4.2.6 EUT Operating Conditions	34
4.2.7 Test Results	35
4.3 6dB Bandwidth Measurement	39
4.3.1 Limits of 6dB Bandwidth Measurement	39
4.3.2 Test Setup	39
4.3.3 Test Instruments	39
4.3.4 Test Procedure	39
4.3.5 Deviation from Test Standard	39
4.3.6 EUT Operating Conditions	39
4.3.7 Test Result	40
4.4 Conducted Output Power Measurement	42
4.4.1 Limits of Conducted Output Power Measurement	42
4.4.2 Test Setup	42
4.4.3 Test Instruments	42
4.4.4 Test Procedures	42
4.4.5 Deviation from Test Standard	42
4.4.6 EUT Operating Conditions	42
4.4.7 Test Results	43
4.5 Power Spectral Density Measurement	44
4.5.1 Limits of Power Spectral Density Measurement	44
4.5.2 Test Setup	44
4.5.3 Test Instruments	44
4.5.4 Test Procedure	44
4.5.5 Deviation from Test Standard	44
4.5.6 EUT Operating Condition	44

4.5.7 Test Results	45
4.6 Conducted Out of Band Emission Measurement.....	48
4.6.1 Limits of Conducted Out of Band Emission Measurement	48
4.6.2 Test Setup.....	48
4.6.3 Test Instruments	48
4.6.4 Test Procedure	48
4.6.5 Deviation from Test Standard	48
4.6.6 EUT Operating Condition	48
4.6.7 Test Results	48
5 Pictures of Test Arrangements.....	61
Appendix – Information on the Testing Laboratories	62



A D T

Release Control Record

Issue No.	Description	Date Issued
RF150527C04	Original release.	Jun. 29, 2015

1 Certificate of Conformity

Product: 802.11a/b/g/n/ac wireless AP

Brand: PAKEDGE

Test Model: WX-1

Series Model: WX-1-B

Sample Status: Engineering sample

Applicant: Pakedge Device and Software Inc.

Test Date: Jun. 12 ~ Jun. 24, 2015

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :


Pettie Chen / Senior Specialist

Date:

Jun. 29, 2015

Approved by :


Ken Liu / Senior Manager

Date:

Jun. 29, 2015

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (SECTION 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -2.75dB at 0.15000MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -1.0dB at 2288.00, 2390.00MHz.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is IPEX not a standard connector.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.44 dB
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	3.86 dB
	200MHz ~1000MHz	3.87 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.29 dB
	18GHz ~ 40GHz	2.29 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	802.11a/b/g/n/ac wireless AP
Brand	PAKEDGE
Test Model	WX-1
Series Model	WX-1-B
Model Difference	marketing purpose
Status of EUT	Engineering sample
Power Supply Rating	12Vdc from adapter 48Vdc from PoE
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: 11.0/ 5.5/ 2.0/ 1.0Mbps 802.11g: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11n: up to 450.0Mbps
Operating Frequency	2412 ~ 2462MHz
Number of Channel	11 for 802.11b, 802.11g, 802.11n (HT20) 7 for 802.11n (HT40)
Output Power	498.350mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	Adapter
Data Cable Supplied	NA

Note:

1. All models are listed as below.

Brand	Model	Difference
PAKEDGE	WX-1	All models are electrically identical, different model names are for marketing purpose.
	WX-1-B	

2. The EUT incorporates a MIMO function. Physically, the EUT provides 3 completed transmitters and 3 receivers.

Modulation Mode	TX Function
802.11b	3TX
802.11g	3TX
802.11n (HT20)	3TX
802.11n (HT40)	3TX

3. The EUT consumes power from the following adapter & PoE.

Adapter	
Brand	Powertron Electronics Corp.
Model	PA1024-2HUB PA1024-120HUB200
Input Power	100-240Vac~50-60Hz, 0.6A
Output Power	12Vdc / 2.0A 24W Max
Power Line	1.5m power cable with 1 core attached on adapter

PoE (Support unit only)	
Model	NPE-5818
Rating	48Vdc, 1.25A

Adapter of PoE (Support unit only)	
Brand	Powertron Electronics Corp.
Model	PA1040-480IB080
Input Power	100-240Vac, 50-60Hz 1.5A
Output Power	48Vdc, 0.8A, 38.4W Max

4. The following antennas were provided to the EUT.

Type	Gain(dBi)		Connector
	2.4GHz Band	5GHz Band	
PCB	Ant. 1: 5.16dBi	Ant. 4: 5.18dBi	IPEX
	Ant. 2: 4.59dBi	Ant. 5: 4.93dBi	
	Ant. 3: 4.17dBi	Ant. 6: 4.26dBi	

5. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

Channel	Frequency	Channel	Frequency
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40):

Channel	Frequency	Channel	Frequency
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
A	√	√	√	√	Power from adapter
B	-	√	√	-	Power from PoE

Where **RE≥1G**: Radiated Emission above 1GHz & Bandedge Measurement
RE<1G: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission
APCM: Antenna Port Conducted Measurement

Note: 1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.
2. "-" means no effect.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	7.2
A	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	15.0

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A, B	802.11n (HT20)	1 to 11	6	OFDM	BPSK	7.2

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A, B	802.11n (HT20)	1 to 11	6	OFDM	BPSK	7.2

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	7.2
A	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	15.0

Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	21deg. C, 64%RH	120Vac, 60Hz	Jones Chang
RE<1G	21deg. C, 66%RH	120Vac, 60Hz 48Vdc	Jones Chang
PLC	20deg. C, 70%RH	120Vac, 60Hz 48Vdc	Jones Chang
APCM	25deg. C, 60%RH	120Vac, 60Hz	Frank Liu

3.3 Duty Cycle of Test Signal

Duty cycle of test signal is $\geq 98\%$, duty factor is not required.


802.11b: Duty cycle = $12.162/12.237 = 0.994$

Duty cycle of test signal is $< 98\%$, duty factor shall be considered.

802.11g: Duty cycle = $2.024/2.083 = 0.972$, Duty factor = $10 * \log(1/0.972) = 0.12$

802.11n (HT20): Duty cycle = $1.887/1.946 = 0.97$, Duty factor = $10 * \log(1/0.97) = 0.13$

802.11n (HT40): Duty cycle = $0.926/0.973 = 0.952$, Duty factor = $10 * \log(1/0.952) = 0.22$



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Notebook	DELL	D531	CN-0XM006-4864 3-81U-2610	QDS-BRCM1020	-
B.	PoE	NA	NPE-5818	NA	NA	Supplied by the manufacturer
C.	Adapter of PoE	Powertron Electronics Corp.	PA1040-480IB080	NA	NA	Supplied by the manufacturer

Note:


1. All power cords of the above support units are non-shielded (1.8m).
2. Item A~C acted as communication partners to transfer data.

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	LAN cable	1	10	N	0	Cat5e
2.	LAN cable	1	1.8	N	0	Cat5e
3.	DC cable	1	1.5	N	1	Attached on adapter


Note: The core(s) is(are) originally attached to the cable(s).

3.4.1 Configuration of System under Test

<Adapter Mode>



<PoE Mode>



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
558074 D01 DTS Meas Guidance v03r02
662911 D01 Multiple Transmitter Output v02r01
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

NOTE: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 30dB under any condition of modulation.

4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESIB7	100187	Apr. 10, 2015	Apr. 09, 2016
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100041	Aug. 29, 2014	Aug. 28, 2015
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Feb. 05, 2015	Feb. 04, 2016
HORN Antenna SCHWARZBECK	9120D	209	Feb. 09, 2015	Feb. 08, 2016
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Feb. 09, 2015	Feb. 08, 2016
Preamplifier Agilent	8447D	2944A10738	Oct.18, 2014	Oct. 17, 2015
Preamplifier Agilent	8449B	3008A01964	Aug. 22, 2014	Aug. 21, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	214378/4	Aug. 22, 2014	Aug. 21, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 106	12738/6 +309224/4	Aug. 22, 2014	Aug. 21, 2015
Software BV ADT	ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA	NA
Antenna Tower Controller BV ADT	AT100	AT93021702	NA	NA
Turn Table BV ADT	TT100	TT93021702	NA	NA
Turn Table Controller BV ADT	SC100	SC93021702	NA	NA
High Speed Peak Power Meter	ML2495A	0824011	Jul. 26, 2014	Jul. 25, 2015
Power Sensor	MA2411B	0738171	Jul. 26, 2014	Jul. 25, 2015

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 3.

3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.

4. The FCC Site Registration No. is 988962.

5. The IC Site Registration No. is IC 7450F-3.

4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Set Up

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Prepared notebook to act as communication partner and placed it outside of testing area.
- The communication partner connected with EUT via a RJ45 cable and ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- The communication partner sent data to EUT by command "PING".

4.1.7 Test Results

Above 1GHz Data :

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2220.00	52.0 PK	74.0	-22.0	1.37 H	8	52.90	-0.90
2	2220.00	43.5 AV	54.0	-10.5	1.37 H	8	44.40	-0.90
3	2370.00	61.6 PK	74.0	-12.4	1.71 H	0	29.10	32.50
4	2370.00	50.7 AV	54.0	-3.3	1.71 H	0	18.20	32.50
5	*2412.00	115.3 PK			1.52 H	356	82.70	32.60
6	*2412.00	111.7 AV			1.52 H	356	79.10	32.60
7	4824.00	48.9 PK	74.0	-25.1	1.40 H	192	43.00	5.90
8	4824.00	36.9 AV	54.0	-17.1	1.40 H	192	31.00	5.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	58.8 PK	74.0	-15.2	1.16 V	13	58.20	0.60
2	2288.00	52.1 AV	54.0	-1.9	1.16 V	13	51.50	0.60
3	2370.00	62.7 PK	74.0	-11.3	1.40 V	328	30.20	32.50
4	2370.00	51.6 AV	54.0	-2.4	1.40 V	328	19.10	32.50
5	*2412.00	119.5 PK			1.20 V	327	86.90	32.60
6	*2412.00	116.0 AV			1.20 V	327	83.40	32.60
7	4824.00	48.8 PK	74.0	-25.2	1.80 V	14	42.90	5.90
8	4824.00	38.4 AV	54.0	-15.6	1.80 V	14	32.50	5.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2200.00	51.0 PK	74.0	-23.0	1.20 H	19	52.30	-1.30
2	2200.00	42.6 AV	54.0	-11.4	1.20 H	19	43.90	-1.30
3	2390.00	58.9 PK	74.0	-15.1	1.51 H	349	26.40	32.50
4	2390.00	48.1 AV	54.0	-5.9	1.51 H	349	15.60	32.50
5	*2437.00	112.7 PK			1.49 H	355	80.00	32.70
6	*2437.00	108.9 AV			1.49 H	355	76.20	32.70
7	4874.00	49.1 PK	74.0	-24.9	1.38 H	212	43.20	5.90
8	4874.00	36.8 AV	54.0	-17.2	1.38 H	212	30.90	5.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	59.4 PK	74.0	-14.6	1.16 V	14	58.80	0.60
2	2288.00	53.0 AV	54.0	-1.0	1.16 V	14	52.40	0.60
3	2390.00	62.4 PK	74.0	-11.6	1.21 V	346	29.90	32.50
4	2390.00	50.0 AV	54.0	-4.0	1.21 V	346	17.50	32.50
5	*2437.00	118.3 PK			1.21 V	346	85.60	32.70
6	*2437.00	114.8 AV			1.21 V	346	82.10	32.70
7	4871.00	50.1 PK	74.0	-23.9	1.46 V	350	44.20	5.90
8	4871.00	37.3 AV	54.0	-16.7	1.46 V	350	31.40	5.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2200.00	52.4 PK	74.0	-21.6	1.36 H	0	53.70	-1.30
2	2200.00	41.3 AV	54.0	-12.7	1.36 H	0	42.60	-1.30
3	*2462.00	114.0 PK			1.35 H	20	81.40	32.60
4	*2462.00	110.1 AV			1.35 H	20	77.50	32.60
5	2483.50	59.9 PK	74.0	-14.1	1.35 H	20	27.20	32.70
6	2483.50	49.1 AV	54.0	-4.9	1.35 H	20	16.40	32.70
7	4874.00	49.4 PK	74.0	-24.6	1.37 H	188	43.50	5.90
8	4874.00	36.6 AV	54.0	-17.4	1.37 H	188	30.70	5.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	57.8 PK	74.0	-16.2	1.16 V	13	57.20	0.60
2	2288.00	52.1 AV	54.0	-1.9	1.16 V	13	51.50	0.60
3	*2462.00	117.7 PK			1.18 V	331	85.10	32.60
4	*2462.00	114.1 AV			1.18 V	331	81.50	32.60
5	2483.50	62.6 PK	74.0	-11.4	1.60 V	341	29.90	32.70
6	2483.50	50.3 AV	54.0	-3.7	1.60 V	341	17.60	32.70
7	4924.00	50.4 PK	74.0	-23.6	1.70 V	19	44.40	6.00
8	4924.00	37.5 AV	54.0	-16.5	1.70 V	19	31.50	6.00

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2200.00	54.3 PK	74.0	-19.7	1.38 H	13	55.60	-1.30
2	2200.00	43.5 AV	54.0	-10.5	1.38 H	13	44.80	-1.30
3	2390.00	62.5 PK	74.0	-11.5	1.39 H	355	30.00	32.50
4	2390.00	50.8 AV	54.0	-3.2	1.39 H	355	18.30	32.50
5	*2412.00	111.2 PK			1.39 H	355	78.60	32.60
6	*2412.00	101.7 AV			1.39 H	355	69.10	32.60
7	4824.00	48.8 PK	74.0	-25.2	1.51 H	125	42.90	5.90
8	4824.00	35.6 AV	54.0	-18.4	1.51 H	125	29.70	5.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	58.2 PK	74.0	-15.8	1.70 V	11	57.60	0.60
2	2288.00	51.8 AV	54.0	-2.2	1.70 V	11	51.20	0.60
3	2390.00	69.3 PK	74.0	-4.7	1.52 V	328	36.80	32.50
4	2390.00	53.0 AV	54.0	-1.0	1.52 V	328	20.50	32.50
5	*2412.00	116.2 PK			1.52 V	328	83.60	32.60
6	*2412.00	106.7 AV			1.52 V	328	74.10	32.60
7	4824.00	49.5 PK	74.0	-24.5	1.68 V	1	43.60	5.90
8	4824.00	36.2 AV	54.0	-17.8	1.68 V	1	30.30	5.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2230.00	53.1 PK	74.0	-20.9	1.50 H	355	53.70	-0.60
2	2230.00	43.9 AV	54.0	-10.1	1.50 H	355	44.50	-0.60
3	2390.00	62.8 PK	74.0	-11.2	1.40 H	340	30.30	32.50
4	2390.00	49.4 AV	54.0	-4.6	1.40 H	340	16.90	32.50
5	*2437.00	116.6 PK			1.40 H	341	83.90	32.70
6	*2437.00	106.7 AV			1.40 H	341	74.00	32.70
7	2483.50	62.6 PK	74.0	-11.4	1.40 H	351	29.90	32.70
8	2483.50	49.2 AV	54.0	-4.8	1.40 H	351	16.50	32.70
9	4874.00	48.3 PK	74.0	-25.7	1.60 H	23	42.40	5.90
10	4874.00	35.4 AV	54.0	-18.6	1.60 H	23	29.50	5.90
11	7311.00	72.7 PK	74.0	-1.3	1.67 H	267	61.00	11.70
12	7311.00	43.2 AV	54.0	-10.8	1.67 H	267	31.50	11.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	57.1 PK	74.0	-16.9	1.67 V	7	56.50	0.60
2	2288.00	51.2 AV	54.0	-2.8	1.67 V	7	50.60	0.60
3	2390.00	70.1 PK	74.0	-3.9	1.51 V	1	37.60	32.50
4	2390.00	52.4 AV	54.0	-1.6	1.51 V	1	19.90	32.50
5	*2437.00	120.5 PK			1.66 V	345	87.80	32.70
6	*2437.00	111.1 AV			1.66 V	345	78.40	32.70
7	2483.50	68.5 PK	74.0	-5.5	1.63 V	346	35.80	32.70
8	2483.50	52.3 AV	54.0	-1.7	1.63 V	346	19.60	32.70
9	4874.00	49.7 PK	74.0	-24.3	1.67 V	357	43.80	5.90
10	4874.00	36.6 AV	54.0	-17.4	1.67 V	357	30.70	5.90
11	7311.00	72.3 PK	74.0	-1.7	1.67 V	81	60.60	11.70
12	7311.00	46.2 AV	54.0	-7.8	1.67 V	81	34.50	11.70

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	111.4 PK			1.47 H	6	78.80	32.60
2	*2462.00	101.3 AV			1.47 H	6	68.70	32.60
3	2483.50	66.6 PK	74.0	-7.4	1.47 H	10	33.90	32.70
4	2483.50	50.2 AV	54.0	-3.8	1.47 H	10	17.50	32.70
5	4924.00	48.5 PK	74.0	-25.5	1.34 H	136	42.50	6.00
6	4924.00	35.6 AV	54.0	-18.4	1.34 H	136	29.60	6.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	116.1 PK			1.82 V	339	83.50	32.60
2	*2462.00	106.6 AV			1.82 V	339	74.00	32.60
3	2483.50	71.3 PK	74.0	-2.7	1.75 V	350	38.60	32.70
4	2483.50	52.2 AV	54.0	-1.8	1.75 V	350	19.50	32.70
5	4924.00	49.3 PK	74.0	-24.7	1.70 V	11	43.30	6.00
6	4924.00	36.1 AV	54.0	-17.9	1.70 V	11	30.10	6.00

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (HT20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2240.00	51.5 PK	74.0	-22.5	1.52 H	359	52.00	-0.50
2	2240.00	42.3 AV	54.0	-11.7	1.52 H	359	42.80	-0.50
3	2390.00	61.1 PK	74.0	-12.9	1.65 H	4	28.60	32.50
4	2390.00	48.5 AV	54.0	-5.5	1.65 H	4	16.00	32.50
5	*2412.00	110.2 PK			1.67 H	4	77.60	32.60
6	*2412.00	100.5 AV			1.67 H	4	67.90	32.60
7	4824.00	48.8 PK	74.0	-25.2	1.49 H	11	42.90	5.90
8	4824.00	35.6 AV	54.0	-18.4	1.49 H	11	29.70	5.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	54.6 PK	74.0	-19.4	1.70 V	315	54.00	0.60
2	2288.00	48.7 AV	54.0	-5.3	1.70 V	315	48.10	0.60
3	2390.00	68.6 PK	74.0	-5.4	1.54 V	333	36.10	32.50
4	2390.00	52.1 AV	54.0	-1.9	1.54 V	333	19.60	32.50
5	*2412.00	115.4 PK			1.67 V	345	82.80	32.60
6	*2412.00	105.4 AV			1.67 V	345	72.80	32.60
7	4824.00	49.2 PK	74.0	-24.8	1.68 V	352	43.30	5.90
8	4824.00	36.1 AV	54.0	-17.9	1.68 V	352	30.20	5.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2250.00	54.7 PK	74.0	-19.3	1.58 H	348	54.90	-0.20
2	2250.00	45.5 AV	54.0	-8.5	1.58 H	348	45.70	-0.20
3	2390.00	64.3 PK	74.0	-9.7	1.53 H	343	31.80	32.50
4	2390.00	49.3 AV	54.0	-4.7	1.53 H	343	16.80	32.50
5	*2437.00	114.4 PK			1.53 H	343	81.70	32.70
6	*2437.00	105.2 AV			1.53 H	343	72.50	32.70
7	2483.50	60.2 PK	74.0	-13.8	1.53 H	350	27.50	32.70
8	2483.50	48.2 AV	54.0	-5.8	1.53 H	350	15.50	32.70
9	4874.00	49.4 PK	74.0	-24.6	1.62 H	330	43.50	5.90
10	4874.00	36.6 AV	54.0	-17.4	1.62 H	330	30.70	5.90
11	7311.00	72.1 PK	74.0	-1.9	1.66 H	264	60.40	11.70
12	7311.00	42.1 AV	54.0	-11.9	1.66 H	264	30.40	11.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	52.7 PK	74.0	-21.3	1.70 V	325	52.10	0.60
2	2288.00	46.6 AV	54.0	-7.4	1.70 V	325	46.00	0.60
3	2390.00	70.6 PK	74.0	-3.4	1.52 V	341	38.10	32.50
4	2390.00	51.6 AV	54.0	-2.4	1.52 V	341	19.10	32.50
5	*2437.00	120.6 PK			1.50 V	338	87.90	32.70
6	*2437.00	111.2 AV			1.50 V	338	78.50	32.70
7	2483.50	72.3 PK	74.0	-1.7	1.47 V	338	39.60	32.70
8	2483.50	51.7 AV	54.0	-2.3	1.47 V	338	19.00	32.70
9	4874.00	48.4 PK	74.0	-25.6	1.60 V	354	42.50	5.90
10	4874.00	35.2 AV	54.0	-18.8	1.60 V	354	29.30	5.90
11	7311.00	67.6 PK	74.0	-6.4	1.69 V	254	55.90	11.70
12	7311.00	41.4 AV	54.0	-12.6	1.69 V	254	29.70	11.70

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2240.00	53.3 PK	74.0	-20.7	1.52 H	352	53.80	-0.50
2	2240.00	44.3 AV	54.0	-9.7	1.52 H	352	44.80	-0.50
3	*2462.00	111.0 PK			1.79 H	1	78.40	32.60
4	*2462.00	101.3 AV			1.79 H	1	68.70	32.60
5	2483.50	67.5 PK	74.0	-6.5	1.79 H	359	34.80	32.70
6	2483.50	50.7 AV	54.0	-3.3	1.79 H	359	18.00	32.70
7	4924.00	48.5 PK	74.0	-25.5	1.45 H	299	42.50	6.00
8	4924.00	35.5 AV	54.0	-18.5	1.45 H	299	29.50	6.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	55.5 PK	74.0	-18.5	1.79 V	305	54.90	0.60
2	2288.00	49.7 AV	54.0	-4.3	1.79 V	305	49.10	0.60
3	*2462.00	115.3 PK			1.79 V	338	82.70	32.60
4	*2462.00	105.8 AV			1.79 V	338	73.20	32.60
5	2483.50	70.0 PK	74.0	-4.0	1.75 V	351	37.30	32.70
6	2483.50	52.6 AV	54.0	-1.4	1.75 V	351	19.90	32.70
7	4924.00	49.0 PK	74.0	-25.0	1.71 V	22	43.00	6.00
8	4924.00	36.0 AV	54.0	-18.0	1.71 V	22	30.00	6.00

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (HT40)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	65.8 PK	74.0	-8.2	1.69 H	11	33.30	32.50
2	2390.00	49.9 AV	54.0	-4.1	1.69 H	11	17.40	32.50
3	*2422.00	104.5 PK			1.83 H	170	71.90	32.60
4	*2422.00	95.0 AV			1.83 H	170	62.40	32.60
5	4844.00	48.3 PK	74.0	-25.7	1.54 H	265	42.40	5.90
6	4844.00	35.0 AV	54.0	-19.0	1.54 H	265	29.10	5.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.0 PK	74.0	-5.0	1.51 V	348	36.50	32.50
2	2390.00	52.4 AV	54.0	-1.6	1.51 V	348	19.90	32.50
3	*2422.00	109.1 PK			1.48 V	342	76.50	32.60
4	*2422.00	100.0 AV			1.48 V	342	67.40	32.60
5	4844.00	48.6 PK	74.0	-25.4	1.44 V	245	42.70	5.90
6	4844.00	35.7 AV	54.0	-18.3	1.44 V	245	29.80	5.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	54.0 PK	74.0	-20.0	1.33 H	356	53.40	0.60
2	2288.00	43.6 AV	54.0	-10.4	1.33 H	356	43.00	0.60
3	2390.00	59.4 PK	74.0	-14.6	1.70 H	339	26.90	32.50
4	2390.00	48.3 AV	54.0	-5.7	1.70 H	339	15.80	32.50
5	*2437.00	107.4 PK			1.85 H	342	74.70	32.70
6	*2437.00	97.5 AV			1.85 H	342	64.80	32.70
7	2483.50	58.6 PK	74.0	-15.4	1.77 H	333	25.90	32.70
8	2483.50	47.7 AV	54.0	-6.3	1.77 H	333	15.00	32.70
9	4874.00	48.8 PK	74.0	-25.2	1.21 H	222	42.90	5.90
10	4874.00	35.7 AV	54.0	-18.3	1.21 H	222	29.80	5.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	58.1 PK	74.0	-15.9	1.14 V	14	57.50	0.60
2	2288.00	52.6 AV	54.0	-1.4	1.14 V	14	52.00	0.60
3	2390.00	66.6 PK	74.0	-7.4	1.51 V	350	34.10	32.50
4	2390.00	52.0 AV	54.0	-2.0	1.51 V	350	19.50	32.50
5	*2437.00	112.3 PK			1.74 V	14	79.60	32.70
6	*2437.00	102.3 AV			1.74 V	14	69.60	32.70
7	2483.50	66.2 PK	74.0	-7.8	1.44 V	16	33.50	32.70
8	2483.50	50.7 AV	54.0	-3.3	1.44 V	16	18.00	32.70
9	4874.00	49.4 PK	74.0	-24.6	1.49 V	0	43.50	5.90
10	4874.00	36.7 AV	54.0	-17.3	1.49 V	0	30.80	5.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	105.1 PK			1.64 H	4	72.40	32.70
2	*2452.00	95.1 AV			1.64 H	4	62.40	32.70
3	2483.50	65.2 PK	74.0	-8.8	1.62 H	348	32.50	32.70
4	2483.50	48.5 AV	54.0	-5.5	1.62 H	348	15.80	32.70
5	4904.00	48.4 PK	74.0	-25.6	1.65 H	252	42.60	5.80
6	4904.00	35.0 AV	54.0	-19.0	1.65 H	252	29.20	5.80
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	108.0 PK			1.48 V	349	75.30	32.70
2	*2452.00	98.8 AV			1.48 V	349	66.10	32.70
3	2483.50	69.5 PK	74.0	-4.5	1.62 V	347	36.80	32.70
4	2483.50	52.6 AV	54.0	-1.4	1.62 V	347	19.90	32.70
5	4904.00	49.0 PK	74.0	-25.0	1.55 V	352	43.20	5.80
6	4904.00	36.1 AV	54.0	-17.9	1.55 V	352	30.30	5.80

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

Below 1GHz Data:

Test Mode A

802.11n (HT20)

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	57.12	30.8 QP	40.0	-9.2	2.00 H	358	45.40	-14.60
2	140.72	36.8 QP	43.5	-6.7	2.00 H	109	51.60	-14.80
3	206.83	33.8 QP	43.5	-9.7	1.50 H	135	50.70	-16.90
4	500.42	33.0 QP	46.0	-13.0	1.50 H	42	41.40	-8.40
5	624.85	40.7 QP	46.0	-5.3	1.01 H	172	46.30	-5.60
6	875.67	37.6 QP	46.0	-8.4	2.00 H	272	38.70	-1.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	218.50	32.4 QP	46.0	-13.6	1.49 V	16	48.80	-16.40
2	374.04	28.5 QP	46.0	-17.5	1.49 V	177	39.50	-11.00
3	418.76	31.2 QP	46.0	-14.8	1.00 V	287	41.40	-10.20
4	500.42	30.5 QP	46.0	-15.5	1.00 V	302	38.90	-8.40
5	624.85	34.7 QP	46.0	-11.3	1.00 V	12	40.30	-5.60
6	875.67	41.2 QP	46.0	-4.8	1.49 V	163	42.30	-1.10

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

Test Mode B

802.11n (HT20)

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	57.12	30.7 QP	40.0	-9.3	1.99 H	82	45.30	-14.60
2	134.89	35.2 QP	43.5	-8.3	1.99 H	120	50.40	-15.20
3	208.77	28.8 QP	43.5	-14.7	1.00 H	130	45.70	-16.90
4	500.42	34.3 QP	46.0	-11.7	1.49 H	30	42.70	-8.40
5	624.85	42.8 QP	46.0	-3.2	1.00 H	13	48.40	-5.60
6	875.67	39.9 QP	46.0	-6.1	1.49 H	340	41.00	-1.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	49.34	32.6 QP	40.0	-7.4	1.01 V	2	47.00	-14.40
2	131.00	30.9 QP	43.5	-12.6	1.01 V	207	46.40	-15.50
3	169.89	30.9 QP	43.5	-12.6	1.01 V	175	45.10	-14.20
4	201.00	30.8 QP	43.5	-12.7	1.01 V	16	47.60	-16.80
5	624.85	37.9 QP	46.0	-8.1	2.00 V	108	43.50	-5.60
6	875.67	40.2 QP	46.0	-5.8	1.50 V	176	41.30	-1.10

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration	Due Date Of Calibration
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Apr. 27, 2015	Apr. 26, 2016
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 26, 2014	Dec. 25, 2015
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Dec. 30, 2014	Dec. 29, 2015
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100312	Jul. 10, 2014	Jul. 09, 2015
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 2.

3. The VCCI Site Registration No. is C-2047.

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.

4.2.7 Test Results

Test Mode A


802.11n (HT20)

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	0.19	63.06	45.24	63.25	45.43	66.00	56.00	-2.75	-10.57
2	0.16562	0.20	59.17	42.72	59.37	42.92	65.18	55.18	-5.81	-12.26
3	0.18125	0.20	56.79	41.93	56.99	42.13	64.43	54.43	-7.44	-12.30
4	0.23203	0.20	50.07	37.05	50.27	37.25	62.38	52.38	-12.11	-15.13
5	0.53281	0.22	42.75	36.25	42.97	36.47	56.00	46.00	-13.03	-9.53
6	12.26953	0.54	36.03	31.53	36.57	32.07	60.00	50.00	-23.43	-17.93

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15781	0.21	60.88	46.81	61.09	47.02	65.58	55.58	-4.49	-8.56
2	0.16953	0.21	57.71	42.31	57.92	42.52	64.98	54.98	-7.06	-12.46
3	0.19687	0.22	55.08	41.46	55.30	41.68	63.74	53.74	-8.44	-12.06
4	0.23203	0.22	51.01	37.86	51.23	38.08	62.38	52.38	-11.14	-14.29
5	0.52500	0.26	43.79	36.88	44.05	37.14	56.00	46.00	-11.95	-8.86
6	10.57422	0.59	42.42	36.71	43.01	37.30	60.00	50.00	-16.99	-12.70

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Test Mode B 802.11n (HT20)

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16953	0.20	39.02	30.74	39.22	30.94	64.98	54.98	-25.77	-24.05
2	0.21632	0.20	32.26	24.25	32.46	24.45	62.96	52.96	-30.50	-28.51
3	0.27500	0.20	28.04	27.58	28.24	27.78	60.97	50.97	-32.73	-23.19
4	0.47117	0.21	31.73	25.77	31.94	25.98	56.49	46.49	-24.55	-20.51
5	3.03906	0.40	32.12	30.43	32.52	30.83	56.00	46.00	-23.48	-15.17
6	14.63787	0.58	31.14	30.55	31.72	31.13	60.00	50.00	-28.28	-18.87

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16562	0.21	36.30	23.30	36.51	23.51	65.18	55.18	-28.67	-31.67
2	0.27500	0.23	27.88	27.56	28.11	27.79	60.97	50.97	-32.85	-23.17
3	0.50547	0.26	32.20	23.01	32.46	23.27	56.00	46.00	-23.54	-22.73
4	1.02734	0.31	29.18	17.47	29.49	17.78	56.00	46.00	-26.51	-28.22
5	4.69531	0.47	32.15	31.26	32.62	31.73	56.00	46.00	-23.38	-14.27
6	7.73299	0.53	29.73	27.30	30.26	27.83	60.00	50.00	-29.74	-22.17

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)			Minimum Limit (MHz)	Pass / Fail
		CHAIN 0	CHAIN 1	CHAIN 2		
1	2412	7.09	7.07	7.10	0.5	PASS
6	2437	7.11	7.10	7.11	0.5	PASS
11	2462	7.09	7.06	7.08	0.5	PASS

802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)			Minimum Limit (MHz)	Pass / Fail
		CHAIN 0	CHAIN 1	CHAIN 2		
1	2412	16.41	16.38	16.40	0.5	PASS
6	2437	16.39	16.39	16.38	0.5	PASS
11	2462	16.39	16.41	16.40	0.5	PASS

802.11n (HT20)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)			Minimum Limit (MHz)	Pass / Fail
		CHAIN 0	CHAIN 1	CHAIN 2		
1	2412	17.64	17.60	17.63	0.5	PASS
6	2437	17.60	17.60	17.56	0.5	PASS
11	2462	17.62	17.62	17.61	0.5	PASS


802.11n (HT40)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)			Minimum Limit (MHz)	Pass / Fail
		CHAIN 0	CHAIN 1	CHAIN 2		
3	2422	36.18	36.22	36.42	0.5	PASS
6	2437	36.22	36.36	36.39	0.5	PASS
9	2452	36.37	36.41	36.40	0.5	PASS


Spectrum Plot of Worst Value

802.11b

802.11g




A D T




A D T

802.11n (HT20)

802.11n (HT40)



A D T



A D T

4.4 Conducted Output Power Measurement

4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

An average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor. Record the power level.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

4.4.7 Test Results

FOR AVERAGE POWER

802.11b

Chan.	Chan. Freq. (MHz)	Average Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
1	2412	20.73	20.12	20.60	335.921	25.26	30	Pass
6	2437	19.84	19.32	19.92	280.065	24.47	30	Pass
11	2462	20.29	19.82	20.99	328.448	25.16	30	Pass

802.11g

Chan.	Chan. Freq. (MHz)	Average Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
1	2412	17.39	16.45	16.84	147.291	21.68	30	Pass
6	2437	22.32	21.84	22.43	498.350	26.98	30	Pass
11	2462	17.58	17.11	18.08	172.953	22.38	30	Pass

802.11n (HT20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
1	2412	15.55	14.81	15.02	97.930	19.91	30	Pass
6	2437	21.53	21.46	21.91	437.431	26.41	30	Pass
11	2462	16.68	16.39	16.87	138.751	21.42	30	Pass

802.11n (HT40)


Chan.	Chan. Freq. (MHz)	Average Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
3	2422	13.07	12.27	13.01	57.142	17.57	30	Pass
6	2437	16.68	16.14	16.83	135.869	21.33	30	Pass
9	2452	13.51	12.94	14.01	67.295	18.28	30	Pass

4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

For AVG. power (duty cycle $\geq 98\%$)

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq 3 \times \text{RBW}$.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- Sweep time = auto couple.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.

For AVG. power (duty cycle $< 98\%$)

- Measure the duty cycle (x).
- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq 3 \times \text{RBW}$.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- Sweep time = auto couple.
- Do not use sweep triggering. Allow sweep to "free run".
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- Add $10 \log (1/x)$, where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as Item 4.3.6

4.5.7 Test Results

802.11b

TX chain	Channel	Freq. (MHz)	PSD (dBm)	10 log (N=3) dB	Total PSD (dBm)	Limit (dBm)	Pass /Fail
0	1	2412	-6.27	4.77	-1.50	4.58	Pass
	6	2437	-6.95	4.77	-2.18	4.58	Pass
	11	2462	-6.85	4.77	-2.08	4.58	Pass
1	1	2412	-6.36	4.77	-1.59	4.58	Pass
	6	2437	-7.77	4.77	-3.00	4.58	Pass
	11	2462	-6.28	4.77	-1.51	4.58	Pass
2	1	2412	-6.46	4.77	-1.69	4.58	Pass
	6	2437	-6.90	4.77	-2.13	4.58	Pass
	11	2462	-5.88	4.77	-1.11	4.58	Pass

NOTE:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/3] = 9.42 \text{ dBi}$, so the power density limit shall be reduced to $8-(9.42-6) = 4.58 \text{ dBm}$.

802.11g

TX chain	Channel	Freq. (MHz)	PSD (dBm)	10 log (N=3) dB	Duty Factor	Total PSD with Duty Factor (dBm)	Limit (dBm)	Pass /Fail
0	1	2412	-9.49	4.77	0.12	-4.60	4.58	Pass
	6	2437	-8.31	4.77	0.12	-3.42	4.58	Pass
	11	2462	-7.38	4.77	0.12	-2.49	4.58	Pass
1	1	2412	-14.11	4.77	0.12	-9.22	4.58	Pass
	6	2437	-8.49	4.77	0.12	-3.60	4.58	Pass
	11	2462	-14.09	4.77	0.12	-9.20	4.58	Pass
2	1	2412	-13.26	4.77	0.12	-8.37	4.58	Pass
	6	2437	-8.18	4.77	0.12	-3.29	4.58	Pass
	11	2462	-12.24	4.77	0.12	-7.35	4.58	Pass

NOTE:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/3] = 9.42 \text{ dBi}$, so the power density limit shall be reduced to $8-(9.42-6) = 4.58 \text{ dBm}$.

802.11n (HT20)

TX chain	Channel	Freq. (MHz)	PSD (dBm)	10 log (N=3) dB	Duty Factor	Total PSD with Duty Factor (dBm)	Limit (dBm)	Pass /Fail
0	1	2412	-15.04	4.77	0.13	-10.14	4.58	Pass
	6	2437	-9.23	4.77	0.13	-4.33	4.58	Pass
	11	2462	-14.55	4.77	0.13	-9.65	4.58	Pass
1	1	2412	-16.09	4.77	0.13	-11.19	4.58	Pass
	6	2437	-9.02	4.77	0.13	-4.12	4.58	Pass
	11	2462	-14.33	4.77	0.13	-9.43	4.58	Pass
2	1	2412	-15.74	4.77	0.13	-10.84	4.58	Pass
	6	2437	-8.73	4.77	0.13	-3.83	4.58	Pass
	11	2462	-9.37	4.77	0.13	-4.47	4.58	Pass

NOTE:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/3] = 9.42 \text{ dBi}$, so the power density limit shall be reduced to $8-(9.42-6) = 4.58 \text{ dBm}$.

802.11n (HT40)

TX chain	Channel	Freq. (MHz)	PSD (dBm)	10 log (N=3) dB	Duty Factor	Total PSD with Duty Factor (dBm)	Limit (dBm)	Pass /Fail
0	3	2422	-19.75	4.77	0.22	-14.76	4.58	Pass
	6	2437	-13.61	4.77	0.22	-8.62	4.58	Pass
	9	2452	-19.73	4.77	0.22	-14.74	4.58	Pass
1	3	2422	-21.20	4.77	0.22	-16.21	4.58	Pass
	6	2437	-13.57	4.77	0.22	-8.58	4.58	Pass
	9	2452	-20.06	4.77	0.22	-15.07	4.58	Pass
2	3	2422	-20.54	4.77	0.22	-15.55	4.58	Pass
	6	2437	-16.52	4.77	0.22	-11.53	4.58	Pass
	9	2452	-18.98	4.77	0.22	-13.99	4.58	Pass



NOTE:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/3] = 9.42 \text{ dBi}$, so the power density limit shall be reduced to $8-(9.42-6) = 4.58 \text{ dBm}$.

Spectrum Plot of Worst Value



802.11b

802.11g



802.11n (HT20)

802.11n (HT40)




4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition


Same as Item 4.3.6

4.6.7 Test Results


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.

802.11b CHAIN 0


CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





CHAIN 1



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





CHAIN 2



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11g CHAIN 0



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





CHAIN 1



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





CHAIN 2



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11n (HT20) CHAIN 0



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





CHAIN 1



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





CHAIN 2



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11n (HT40) CHAIN 0



CH 3




CH 6




CH 9



CH 3 Band edge





CH 9 Band edge





CHAIN 1



CH 3




CH 6




CH 9



CH 3 Band edge





CH 9 Band edge





CHAIN 2



CH 3




CH 6




CH 9



CH 3 Band edge



CH 9 Band edge



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---