

Certification Test Report

FCC ID: SM6-MINODE-WATER4

IC: 9235A-MINODE4

FCC Rule Part: 15.247
IC Radio Standards Specification: RSS-210

ACS Report Number: 15-0006.W06.2B

Manufacturer: Mueller Systems, LLC

Model: MiNODE-WATER4

Test Begin Date: January 19, 2015

Test End Date: January 30, 2015

Report Issue Date: March 6, 2015



FOR THE SCOPE OF ACCREDITATION UNDER LAB Code 200612-0

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

A handwritten signature in black ink, appearing to read "Kirby Munroe", is placed over a horizontal line.

Reviewed by:

Kirby Munroe
Director, Wireless Certifications
ACS, Inc.

This test report shall not be reproduced except in full. This report may be reproduced in part with prior written consent of ACS, Inc. The results contained in this report are representative of the sample(s) submitted for evaluation.

This report contains 21 pages

TABLE OF CONTENTS

1	GENERAL	3
1.1	PURPOSE.....	3
1.2	PRODUCT DESCRIPTION.....	3
1.3	TEST METHODOLOGY AND CONSIDERATIONS	4
2	TEST FACILITIES.....	5
2.1	LOCATION	5
2.2	LABORATORY ACCREDITATIONS/RECOGNITIONS/CERTIFICATIONS	5
2.3	RADIATED EMISSIONS TEST SITE DESCRIPTION	6
2.3.1	<i>Semi-Anechoic Chamber Test Site.....</i>	6
2.3.2	<i>Open Area Tests Site (OATS)</i>	7
2.4	CONDUCTED EMISSIONS TEST SITE DESCRIPTION	8
3	APPLICABLE STANDARD REFERENCES.....	8
4	LIST OF TEST EQUIPMENT.....	9
5	SUPPORT EQUIPMENT	10
6	EQUIPMENT UNDER TEST SETUP BLOCK DIAGRAM	10
7	SUMMARY OF TESTS.....	11
7.1	ANTENNA REQUIREMENT – FCC 15.203	11
7.2	POWER LINE CONDUCTED EMISSIONS – FCC 15.207, IC: RSS-GEN 8.8	11
7.2.1	<i>Measurement Procedure.....</i>	11
7.3	6dB / 99% BANDWIDTH – FCC 15.247(A)(2), IC: RSS-210 A8.2(A)	12
7.3.1	<i>Measurement Procedure.....</i>	12
7.3.2	<i>Measurement Results</i>	12
7.4	FUNDAMENTAL EMISSION OUTPUT POWER – FCC 15.247(B)(3), IC: RSS-210 A8.4(4)	14
7.4.1	<i>Measurement Procedure.....</i>	14
7.4.2	<i>Measurement Results</i>	14
7.5	EMISSION LEVELS – FCC 15.247(D), 15.205, 15.209; IC RSS-210 2.2/A8.5, RSS-GEN 8.9.....	15
7.5.1	<i>Emissions into Non-restricted Frequency Bands.....</i>	15
7.5.1.1	<i>Measurement Procedure.....</i>	15
7.5.1.2	<i>Measurement Results</i>	15
7.5.2	<i>Emissions into Restricted Frequency Bands.....</i>	17
7.5.2.1	<i>Measurement Procedure.....</i>	17
7.5.2.2	<i>Measurement Results</i>	17
7.5.2.3	<i>Sample Calculation:</i>	19
7.6	MAXIMUM POWER SPECTRAL DENSITY IN THE FUNDAMENTAL EMISSION – FCC 15.247(E) IC: RSS-210 A8.2(B)	20
7.6.1	<i>Measurement Procedure.....</i>	20
7.6.2	<i>Measurement Results</i>	20
8	CONCLUSION	21

1 GENERAL

1.1 Purpose

The purpose of this report is to demonstrate compliance with Part 15 Subpart C of the FCC's Code of Federal Regulations and Industry Canada's Radio Standards Specification RSS-210 Certification for modular approval.

1.2 Product Description

The Mueller Systems MiNODE-WATER4 is an ISM band 902 to 928 MHz transceiver module with a maximum output power of +30dBm used in a data collection system connected to a device such as a standard water meter register.

Technical Information:

The 2 modes of operation are detailed as follows. Only mode 2 is addressed in this report.

Mode of Operation	Frequency Range (MHz)	Number of Channels	Channel Separation (kHz)	Data Rates Supported (kbps)	Modulation
1	912.310059 - 927.012451	50	300	4557.3bps and 2604.2bps	FHSS, DSSS
2	903.649963 - 915.725525	24	525	10416.7bps	DTS, DSSS

Antenna Type / Gain: $\frac{1}{4}$ Monopole / 0dBi (Antenna 1)

$\frac{1}{4}$ Helical / -1dBi (Antenna 2)

Operating Voltage: 3.6Vdc

Manufacturer Information:

Mueller Systems, LLC
1200 Abernathy Road, NE

Suite 1200
Atlanta, GA 30328

EUT Serial Numbers: 4000665 NT:14; 4000664 NT:14

Test Sample Condition: The test samples were provided in good working order with no visible defects.

1.3 Test Methodology and Considerations

All modes of operation, including all available data rates, were evaluated. The data presented in this report represents the worst case where applicable.

For radiated emissions three orientations of the EUT were evaluated to determine worst case. The worst case orientation was determined to be the Z orientation.

The EUT is designed for battery operation only therefore AC power line conducted emissions is not applicable.

Multiple antenna types are available for use with the EUT. The highest gain of each antenna type was evaluated for compliance.

Software power setting during test: DCOM4 Release 4.0.8+FCCL

2 TEST FACILITIES

2.1 Location

The radiated and conducted emissions test sites are located at the following address:

Advanced Compliance Solutions
5015 B.U. Bowman Drive
Buford, GA 30518
Phone: (770) 831-8048
Fax: (770) 831-8598

2.2 Laboratory Accreditations/Recognitions/Certifications

ACS is accredited to ISO/IEC 17025 by the National Institute of Standards and Technology under their National Voluntary Laboratory Accreditation Program (NVLAP), Lab Code 200612-0. Unless otherwise specified, all tests methods described within this report are covered under the ISO/IEC 17025 scope of accreditation.

The Semi-Anechoic Chamber Test Site, Open Area Test Site (OATS) and Conducted Emissions Site have been fully described, submitted to, and accepted by the FCC, Industry Canada and the Japanese Voluntary Control Council for Interference by information technology equipment.

FCC Registration Number: 511277

Industry Canada Lab Code: IC 4175A

VCCI Member Number: 1831

- VCCI OATS Registration Number R-1526
- VCCI Conducted Emissions Site Registration Number: C-1608

2.3 Radiated Emissions Test Site Description

2.3.1 Semi-Anechoic Chamber Test Site

The Semi-Anechoic Chamber Test Site consists of a 20' x 30' x 18' shielded enclosure. The chamber is lined with Toyo Ferrite Grid Absorber, model number FFG-1000. The ferrite tile grid is 101 x 101 x 19mm thick and weighs approximately 550 grams. These tiles are mounted on steel panels and installed directly on the inner walls of the chamber.

The turntable is 150cm in diameter and is located 160cm from the back wall of the chamber. The chamber is grounded via 1 - 8' copper ground rod, installed at the center of the back wall, it is bound to the ground plane using 3/4" stainless steel braided cable.

The turntable is all steel, flush mounted table installed in an all steel frame. The table is remotely operated from inside the control room located 25' from the range. The turntable is electrically bonded to the surrounding ground plane via steel fingers installed on the edge of the turn table. The steel fingers make constant contact with the ground plane during operation.

Behind the turntable is a 3' x 6' x 4' deep shielded pit used for support equipment if necessary. The pit is equipped with 1 - 4" PVC chases from the turntable to the pit that allow for cabling to the EUT if necessary. The underside of the turntable can be accessed from the pit so cables can be supplied to the EUT from the pit.

A diagram of the Semi-Anechoic Chamber Test Site is shown in Figure 2.3-1 below:




Figure 2.3-1: Semi-Anechoic Chamber Test Site

2.3.2 Open Area Tests Site (OATS)

The open area test site consists of a 40' x 66' concrete pad covered with a perforated electro-plated galvanized sheet metal. The perforations in the sheet metal are 1/8" holes that are staggered every 3/16". The individual sheets are placed to overlap each other by 1/4" and are riveted together to provide a continuous seam. Rivets are spaced every 3" in a 3 x 20 meter perimeter around the antenna mast and EUT area. Rivets in the remaining area are spaced as necessary to properly secure the ground plane and maintain the electrical continuity.

The entire ground plane extends 12' beyond the turntable edge and 16' beyond the antenna mast when set to a 10 meter measurement distance. The ground plane is grounded via 4 - 8' copper ground rods, each installed at a corner of the ground plane and bound to the ground plane using 3/4" stainless steel braided cable.

The turntable is an all aluminum 10' flush mounted table installed in an all aluminum frame. The table is remotely operated from inside the control room located 40' from the range. The turntable is electrically bonded to the surrounding ground plane via steel fingers installed on the edge of the turn table. The steel fingers make constant contact with the ground plane during operation.

Adjacent to the turntable is a 7' x 7' square and 4' deep concrete pit used for support equipment if necessary. The pit is equipped with 5 - 4" PVC chases from the pit to the control room that allow for cabling to the EUT if necessary. The underside of the turntable can be accessed from the pit so cables can be supplied to the EUT from the pit. The pit is covered with 2 sheets of 1/4" diamond style re-enforced steel sheets. The sheets are painted to match the perforated steel ground plane; however the underside edges have been masked off to maintain the electrical continuity of the ground plane. All reflecting objects are located outside of the ellipse defined in ANSI C63.4.

A diagram of the Open Area Test Site is shown in Figure 2.3-2 below:




Figure 2.3-2: Open Area Test Site

2.4 Conducted Emissions Test Site Description

The AC mains conducted EMI site is located in the main EMC lab. It consists of an 8' x 8' solid aluminum horizontal ground reference plane (GRP) bonded every 3" to an 8' X 8' vertical ground plane.

The site is of sufficient size to test table top and floor standing equipment in accordance with section 6.1.4 of ANSI C63.4.

A diagram of the room is shown below in figure 4.1.3-1:




Figure 2.4-1: AC Mains Conducted EMI Site

3 APPLICABLE STANDARD REFERENCES

The following standards were used:

- ❖ ANSI C63.10-2013: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 2, Subpart J: Equipment Authorization Procedures, 2014
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 15, Subpart C: Radio Frequency Devices, Intentional Radiators, 2014
- ❖ FCC KDB 558074 D01 DTS Meas Guidance v03r02 - Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247, June 5, 2014
- ❖ Industry Canada Radio Standards Specification: RSS-210 - Low-power License-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, Issue 8, Dec 2010
- ❖ Industry Canada Radio Standards Specification: RSS-GEN - General Requirements for Compliance of Radio Apparatus, Issue 4, Nov 2014.

4 LIST OF TEST EQUIPMENT

The calibration interval of test equipment is annually or the manufacturer's recommendations. Where the calibration interval deviates from the annual cycle based on the instrument manufacturer's recommendations, it shall be stated below.

Table 4-1: Test Equipment

AssetID	Manufacturer	Model #	Equipment Type	Serial #	Last Calibration Date	Calibration Due Date
1	Rohde & Schwarz	ESMI - Display	Spectrum Analyzers	833771/007	7/11/2014	7/11/2015
2	Rohde & Schwarz	ESMI-Receiver	Spectrum Analyzers	839587/003	7/11/2014	7/11/2015
30	Spectrum Technologies	DRH-0118	Antennas	970102	4/23/2013	4/23/2015
40	EMCO	3104	Antennas	3211	2/14/2013	2/14/2015
73	Agilent	8447D	Amplifiers	2727A05624	7/15/2014	7/15/2015
167	ACS	Chamber EMI Cable Set	Cable Set	167	10/28/2014	10/28/2015
267	Agilent	N1911A	Meters	MY45100129	7/30/2013	7/30/2015
268	Agilent	N1921A	Sensors	MY45240184	7/30/2013	7/30/2015
292	Florida RF Cables	SMR-290AW-480.0-SMR	Cables	None	3/17/2014	3/17/2015
331	Microwave Circuits	H1G513G1	Filters	31417	6/2/2014	6/2/2015
338	Hewlett Packard	8449B	Amplifiers	3008A01111	7/30/2013	7/30/2015
340	Aeroflex/Weinschel	AS-20	Attenuators	7136	7/14/2014	7/14/2015
412	Electro Metrics	LPA-25	Antennas	1241	7/24/2014	7/24/2016
422	Florida RF	SMS-200AW-72.0-SMR	Cables	805	11/5/2014	11/5/2015
616	Florida RF Cables	SMRE-200W-12.0-SMRE	Cables	N/A	9/10/2014	9/10/2015
622	Rohde & Schwarz	FSV40	Analyzers	101338	7/12/2014	7/12/2015

5 SUPPORT EQUIPMENT

Table 5-1: Support Equipment

Item	Equipment Type	Manufacturer	Model/Part Number	Serial Number
1	DC Power Supply	Agilent	6286A	2109A-06095

6 EQUIPMENT UNDER TEST SETUP BLOCK DIAGRAM




Figure 6-1: Test Setup Block Diagram

7 SUMMARY OF TESTS

Along with the tabular data shown below, plots were taken of all signals deemed important enough to document.

7.1 Antenna Requirement – FCC 15.203

The antennas used are a $\frac{1}{4}$ Monopole with 0dBi gain and a $\frac{1}{4}$ Helical with -1dBi gain. These antennas are either detachable utilizing unique coupling to the EUT or soldered directly to the module, therefore satisfying the requirements of Section 15.203.

7.2 Power Line Conducted Emissions – FCC 15.207, IC: RSS-Gen 8.8

7.2.1 Measurement Procedure

The EUT is battery operated therefore power line conducted emissions is not applicable.

7.3 6dB / 99% Bandwidth – FCC 15.247(a)(2), IC: RSS-210 A8.2(a)

7.3.1 Measurement Procedure

The 6dB bandwidth was measured in accordance with the FCC KDB 558074 D01 DTS Meas Guidance v03r02. The Resolution Bandwidth (RBW) of the spectrum analyzer was set to 100 kHz. The Video Bandwidth (VBW) was set to \geq 3 times the RBW. The trace was set to max hold with a peak detector active. The marker-delta function of the spectrum analyzer was utilized to determine the 6 dB bandwidth of the emission.

The occupied bandwidth measurement function of the spectrum analyzer was used to measure the 99% bandwidth. The span of the analyzer was set to capture all products of the modulation process, including the emission sidebands. The resolution bandwidth was set to 1% to 5% of the occupied bandwidth. The video bandwidth was set to 3 times the resolution bandwidth. A peak detector was used.

7.3.2 Measurement Results

Table 7.3.2-1: 6dB / 99% Bandwidth

Frequency [MHz]	6dB Bandwidth [kHz]	99% Bandwidth [kHz]
903.649963	835.17	664.58
909.950256	830.84	661.51
915.725525	833.57	665.64




Figure 7.3.2-1: 6dB Bandwidth Plot – LCH




Figure 7.3.2-2: 6dB Bandwidth Plot – MCH




Figure 7.3.2-3: 6dB Bandwidth Plot – HCH




Figure 7.3.2-4: 99% Bandwidth Plot – LCH




Figure 7.3.2-5: 99% Bandwidth Plot – MCH




Figure 7.3.2-6: 99% Bandwidth Plot – HCH

7.4 Fundamental Emission Output Power – FCC 15.247(b)(3), IC: RSS-210 A8.4(4)**7.4.1 Measurement Procedure**

The maximum peak conducted output power was measured in accordance with FCC KDB 558074 D01 DTS Meas Guidance v03r02 utilizing the AVGPM average power meter method. The RF output of the equipment under test was directly connected to the input of the power meter applying suitable attenuation.

7.4.2 Measurement Results**Table 7.4.2-1: Maximum Peak Conducted Output Power**

Frequency [MHz]	Level [dBm]
903.649963	28.19
909.950256	28.47
915.625525	28.69

7.5 Emission Levels – FCC 15.247(d), 15.205, 15.209; IC RSS-210 2.2/A8.5, RSS-Gen 8.9

7.5.1 Emissions into Non-restricted Frequency Bands

7.5.1.1 Measurement Procedure

The unwanted emissions into non-restricted bands were measured conducted in accordance with FCC KDB 558074 D01 DTS Meas Guidance v03r02. The RF output of the equipment under test was directly connected to the input of the spectrum analyzer applying suitable attenuation. The Resolution Bandwidth (RBW) of the spectrum analyzer was set to 100 kHz. The Video Bandwidth (VBW) was set to \geq 300 kHz. Span was set to 1.5 times the DTS bandwidth. The trace was set to max hold with a peak detector active. The resulting spectrum analyzer peak level was used to determine the reference level with respect to the 30 dBc limit. The spectrum span was then adjusted for the measurement of spurious emissions from 30MHz to 10GHz, 10 times the highest fundamental frequency.

Band-edge compliance was determined using the conducted marker-delta method in which the radio frequency power that is produced by the EUT is at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of desired power.

7.5.1.2 Measurement Results




Figure 7.5.1.2-1: 30 MHz – 1.0 GHz – LCH




Figure 7.5.1.2-2: 1.0 GHz – 10 GHz – LCH




Figure 7.5.1.2-3: 30 MHz – 1.0 GHz – MCH




Figure 7.5.1.2-4: 1.0 GHz – 10 GHz – MCH




Figure 7.5.1.2-5: 30 MHz – 1.0 GHz – HCH




Figure 7.5.1.2-6: 1.0 GHz – 10 GHz – HCH




Figure 7.5.1.2-7: Lower Band-edge - LCH




Figure 7.5.1.2-8: Upper Band-edge - HCH

7.5.2 Emissions into Restricted Frequency Bands

7.5.2.1 Measurement Procedure

The unwanted emissions into restricted bands were measured radiated over the frequency range of 30MHz to 10GHz, 10 times the highest fundamental frequency.

The EUT was rotated through 360° and the receive antenna height was varied from 1m to 4m so that the maximum radiated emissions level would be detected. For frequencies below 1000MHz, quasi-peak measurements were made using a resolution bandwidth RBW of 120 kHz and a video bandwidth VBW of 300 kHz. For frequencies above 1000MHz, peak and average measurements were made with RBW and VBW of 1 MHz and 3 MHz respectively.

Each emission found to be in a restricted band as defined by section 15.205, including any emission at the operational band-edge, was compared to the radiated emission limits as defined in section 15.209.

7.5.2.2 Measurement Results

Table 7.5.2.2-1: Radiated Spurious Emissions Tabulated Data – Antenna 1

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
Low Channel										
2710.949889	49.49	39.55	H	-4.66	44.83	34.89	74.0	54.0	29.2	19.1
2710.949889	52.67	46.57	V	-4.66	48.01	41.91	74.0	54.0	26.0	12.1
3614.599852	50.27	38.33	H	-1.37	48.90	36.96	74.0	54.0	25.1	17.0
3614.599852	48.46	37.57	V	-1.37	47.09	36.20	74.0	54.0	26.9	17.8
4518.249815	49.64	38.13	H	0.68	50.32	38.81	74.0	54.0	23.7	15.2
4518.249815	48.15	36.25	V	0.68	48.83	36.93	74.0	54.0	25.2	17.1
Middle Channel										
2729.850768	50.91	41.81	H	-4.58	46.33	37.23	74.0	54.0	27.7	16.8
2729.850768	48.52	39.53	V	-4.58	43.94	34.95	74.0	54.0	30.1	19.1
3639.801024	49.58	38.56	H	-1.28	48.30	37.28	74.0	54.0	25.7	16.7
3639.801024	48.77	37.19	V	-1.28	47.49	35.91	74.0	54.0	26.5	18.1
4549.75128	50.18	38.49	H	0.75	50.93	39.24	74.0	54.0	23.1	14.8
4549.75128	47.28	36.07	V	0.75	48.03	36.82	74.0	54.0	26.0	17.2
7279.602048	46.14	33.71	H	7.62	53.76	41.33	74.0	54.0	20.2	12.7
7279.602048	45.94	33.79	V	7.62	53.56	41.41	74.0	54.0	20.4	12.6
High Channel										
2747.176575	51.36	43.89	H	-4.51	46.85	39.38	74.0	54.0	27.2	14.6
2747.176575	48.56	38.05	V	-4.51	44.05	33.54	74.0	54.0	30.0	20.5
3662.9021	49.51	37.37	H	-1.20	48.31	36.17	74.0	54.0	25.7	17.8
3662.9021	47.71	36.28	V	-1.20	46.51	35.08	74.0	54.0	27.5	18.9
4578.627625	50.21	38.92	H	0.81	51.02	39.73	74.0	54.0	23.0	14.3
4578.627625	48.59	36.93	V	0.81	49.40	37.74	74.0	54.0	24.6	16.3
7325.8042	46.37	33.97	H	7.69	54.06	41.66	74.0	54.0	19.9	12.3
7325.8042	46.51	34.02	V	7.69	54.20	41.71	74.0	54.0	19.8	12.3

Table 7.5.2.2-2: Radiated Spurious Emissions Tabulated Data – Antenna 2

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
Low Channel										
977.77		44.54	H	1.12	-----	45.66	-----	54.0	-----	8.3
977.77		38.82	V	1.12	-----	39.94	-----	54.0	-----	14.1
2710.949889	49.10	39.81	H	-4.66	44.44	35.15	74.0	54.0	29.6	18.8
2710.949889	49.84	41.36	V	-4.66	45.18	36.70	74.0	54.0	28.8	17.3
3614.599852	49.30	39.22	H	-1.37	47.93	37.85	74.0	54.0	26.1	16.1
3614.599852	51.46	42.02	V	-1.37	50.09	40.65	74.0	54.0	23.9	13.3
4518.249815	48.71	37.67	H	0.68	49.39	38.35	74.0	54.0	24.6	15.6
4518.249815	47.42	36.40	V	0.68	48.10	37.08	74.0	54.0	25.9	16.9
5421.899778	45.44	33.71	H	3.43	48.87	37.14	74.0	54.0	25.1	16.9
Middle Channel										
982.78		45.25	H	1.18	-----	46.43	-----	54.0	-----	7.6
982.78		38.90	V	1.18	-----	40.08	-----	54.0	-----	13.9
2729.850768	51.03	43.67	H	-4.58	46.45	39.09	74.0	54.0	27.6	14.9
2729.850768	51.13	43.62	V	-4.58	46.55	39.04	74.0	54.0	27.5	15.0
3639.801024	50.27	40.70	H	-1.28	48.99	39.42	74.0	54.0	25.0	14.6
3639.801024	50.93	41.56	V	-1.28	49.65	40.28	74.0	54.0	24.3	13.7
4549.75128	49.61	38.64	H	0.75	50.36	39.39	74.0	54.0	23.6	14.6
4549.75128	49.07	38.03	V	0.75	49.82	38.78	74.0	54.0	24.2	15.2
7279.602048	45.60	33.84	H	7.62	53.22	41.46	74.0	54.0	20.8	12.5
7279.602048	47.37	35.01	V	7.62	54.99	42.63	74.0	54.0	19.0	11.4
High Channel										
987.6		48.70	H	1.33	-----	50.03	-----	54.0	-----	4.0
987.6		42.28	V	1.33	-----	43.61	-----	54.0	-----	10.4
2747.176575	53.83	47.17	H	-4.51	49.32	42.66	74.0	54.0	24.7	11.3
2747.176575	54.71	48.85	V	-4.51	50.20	44.34	74.0	54.0	23.8	9.7
3662.9021	50.29	40.97	H	-1.20	49.09	39.77	74.0	54.0	24.9	14.2
3662.9021	51.21	41.58	V	-1.20	50.01	40.38	74.0	54.0	24.0	13.6
4578.627625	49.18	38.51	H	0.81	49.99	39.32	74.0	54.0	24.0	14.7
4578.627625	48.77	37.19	V	0.81	49.58	38.00	74.0	54.0	24.4	16.0
7325.8042	46.97	34.78	H	7.69	54.66	42.47	74.0	54.0	19.3	11.5
7325.8042	47.04	34.91	V	7.69	54.73	42.60	74.0	54.0	19.3	11.4

7.5.2.3 Sample Calculation:

$$R_C = R_U + CF_T$$

Where:

CF_T = Total Correction Factor (AF+CA+AG)-DC (Average Measurements Only)

R_U = Uncorrected Reading

R_C = Corrected Level

AF = Antenna Factor

CA = Cable Attenuation

AG = Amplifier Gain

DC = Duty Cycle Correction Factor

Example Calculation: Peak (Antenna 1)

Corrected Level: $49.49 - 4.66 = 44.83$ dBuV/m

Margin: 74.0 dBuV/m – 44.83 dBuV/m = 29.2 dB

Example Calculation: Average (Antenna 1)

Corrected Level: $39.55 - 4.66 - 0 = 34.89$ dBuV

Margin: 54.0 dBuV – 34.89 dBuV = 19.1 dB

7.6 Maximum Power Spectral Density in the Fundamental Emission – FCC 15.247(e) IC: RSS-210 A8.2(b)

7.6.1 Measurement Procedure

The power spectral density was measured in accordance with the FCC KDB 558074 D01 DTS Meas Guidance v03r02 utilizing the AVGPSD-1 (trace averaging with EUT transmitting at full power throughout each sweep) method. The RF output of the equipment under test was directly connected to the input of the spectrum analyzer applying suitable attenuation. The Resolution Bandwidth (RBW) of the spectrum analyzer was set to 3 kHz. The Video Bandwidth (VBW) was set to 10 kHz. Span was set to 1.5 times the occupied bandwidth. Trace averaging was employed over a minimum of 100 sweeps with a RMS detector active.

7.6.2 Measurement Results

Table 7.6.2-1: Peak Power Spectral Density

Frequency (MHz)	PSD Level (dBm)
903.649963	7.81
909.950256	7.96
915.725525	7.80




Figure 7.6.2-1: PSD Plot – LCH




Figure 7.6.2-2: PSD Plot – MCH




Figure 7.6.2-3: PSD Plot – HCH

8 CONCLUSION

In the opinion of ACS, Inc. the MiNODE-WATER4, provided by Mueller Systems, LLC meets the requirements of FCC Part 15 subpart C and Industry Canada's Radio Standards Specification RSS-210.

END REPORT