

RADIO TEST REPORT

FCC ID: SMC-H70

Product: JMGO Smart Projector

Trade Mark: N/A

Model No.: N7

Serial Model: N7S, N7C, N7 PRO

Report No.: SER180428004001E

Issue Date: 25 Jun. 2018

Prepared for

SHENZHEN HOLATEK CO.,LTD.

Rm.1001,Unit 4,Bld.B,Kexing Science Park,Keyuan Road, Nshan
District, Shenzhen,China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community,
Xixiang Street Bao'an District, Shenzhen 518126 P.R. China

Tel.: +86-755-6115 6588

Fax.: +86-755-6115 6599

Website:<http://www.ntek.org.cn>

TABLE OF CONTENTS

1	TEST RESULT CERTIFICATION	3
2	SUMMARY OF TEST RESULTS.....	4
3	FACILITIES AND ACCREDITATIONS	5
3.1	FACILITIES.....	5
3.2	LABORATORY ACCREDITATIONS AND LISTINGS	5
3.3	MEASUREMENT UNCERTAINTY	5
4	GENERAL DESCRIPTION OF EUT	6
5	DESCRIPTION OF TEST MODES	8
6	SETUP OF EQUIPMENT UNDER TEST	9
6.1	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM.....	9
6.2	SUPPORT EQUIPMENT.....	10
6.3	EQUIPMENTS LIST FOR ALL TEST ITEMS.....	11
7	TEST REQUIREMENTS.....	13
7.1	CONDUCTED EMISSIONS TEST	13
7.2	RADIATED SPURIOUS EMISSION	22
7.3	NUMBER OF HOPPING CHANNEL.....	35
7.4	HOPPING CHANNEL SEPARATION MEASUREMENT	37
7.5	AVERAGE TIME OF OCCUPANCY (DWELL TIME)	43
7.6	20DB BANDWIDTH TEST	50
7.7	PEAK OUTPUT POWER.....	56
7.8	CONDUCTED BAND EDGE MEASUREMENT.....	62
7.9	SPURIOUS RF CONDUCTED EMISSION.....	69
7.10	ANTENNA APPLICATION	76

1 TEST RESULT CERTIFICATION

Applicant's name	SHENZHEN HOLATEK CO.,LTD.
Address	Rm.1001,Unit 4,Bld.B,Kexing Science Park,Keyuan Road, Noshan District, Shenzhen,China
Manufacturer's Name	SHENZHEN HOLATEK CO.,LTD.
Address	Rm.1001,Unit 4,Bld.B,Kexing Science Park,Keyuan Road, Noshan District, Shenzhen,China
Product description	
Product name	JMGO Smart Projector
Model and/or type reference	N7
Serial Model	N7S, N7C, N7 PRO

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C KDB 174176 D01 Line Conducted FAQ v01r01 ANSI C63.10-2013	Complied

This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : 28 Apr. 2018 ~25 Jun. 2018

Testing Engineer : Loren · Luo
(Loren Luo)

Technical Manager : Jason Chen
(Jason Chen)

Authorized Signatory : Sam · Chen
(Sam Chen)

2 SUMMARY OF TEST RESULTS**FCC Part15 (15.247), Subpart C**

Standard Section	Test Item	Verdict	Remark
15.207	Conducted Emission	PASS	
15.209 (a) 15.205 (a)	Radiated Spurious Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

Remark:

1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.

3 FACILITIES AND ACCREDITATIONS

3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab.

: The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)
The Certificate Registration Number is L5516.

IC-Registration

The Certificate Registration Number is 9270A-1.

FCC- Accredited

Test Firm Registration Number: 463705.

Designation Number: CN1184

A2LA-Lab.

The Certificate Registration Number is 4298.01

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories.

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

: Shenzhen NTEK Testing Technology Co., Ltd.

: 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.80\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(30MHz~1GHz)	$\pm 2.64\text{dB}$
5	All emissions, radiated(1GHz~6GHz)	$\pm 2.40\text{dB}$
6	All emissions, radiated(>6GHz)	$\pm 2.52\text{dB}$
7	Temperature	$\pm 0.5^\circ\text{C}$
8	Humidity	$\pm 2\%$

4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification	
Equipment	JMGO Smart Projector
Trade Mark	N/A
FCC ID	SMC-H70
Model No.	N7
Serial Model	N7S, N7C, N7 PRO
Model Difference	Different types of sales channels with different requirements, the circuit and RF module are the same.
Operating Frequency	2402MHz~2480MHz
Modulation	GFSK, π/4-DQPSK, 8-DPSK
Bluetooth Version	BT V4.0(EDR+BLE)
Number of Channels	79 Channels
Antenna Type	Antenna A (Module1): FPCB Antenna Antenna B (Module2): FPCB Antenna
Antenna Gain	Antenna A:3 dBi Antenna B:3 dBi
Power supply	<input checked="" type="checkbox"/> DC supply: DC 19V from Adapter.
	<input checked="" type="checkbox"/> Adapter supply: Model:GQ150-1900780-E1 Input: 100-240V~50/60Hz 2.0A Max Output: 19V---7.8A
HW Version	H53S_MB_VerC_170808
SW Version	N/A

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.

Revision History

5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for GFSK modulation; 2Mbps for $\pi/4$ -DQPSK modulation; 3Mbps for 8-DPSK modulation) were used for all test.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

Carrier Frequency and Channel list:

Channel	Frequency(MHz)
0	2402
1	2403
...	...
39	2441
40	2442
...	...
77	2479
78	2480

Note: $f_c = 2402\text{MHz} + k \times 1\text{MHz}$ $k=0$ to 78

The following summary table is showing all test modes to demonstrate in compliance with the standard.

For AC Conducted Emission

Final Test Mode	Description
Mode 1	normal link mode

Note: AC power line Conducted Emission was tested under maximum output power.

For Radiated Test Cases

Final Test Mode	Description
Mode 1	normal link mode
Mode 2	CH00(2402MHz)
Mode 3	CH39(2441MHz)
Mode 4	CH78(2480MHz)

Note: For radiated test cases, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.

For Conducted Test Cases

Final Test Mode	Description
Mode 2	CH00(2402MHz)
Mode 3	CH39(2441MHz)
Mode 4	CH78(2480MHz)
Mode 5	Hopping mode


Note: The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.

1. AC power line Conducted Emission was tested under maximum output power.


6 SETUP OF EQUIPMENT UNDER TEST

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM

For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: 1. The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.
2. The EUT has two modules, which distinguish between "module1" and "module2", all modules have been tested, the data were record in this report.

6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	JMGO Smart Projector	N/A	N7	N/A	EUT
E-2	Adapter	N/A	GQ150-1900780-E1	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	Power Cable	NO	NO	1.2m
C-2	RF Cable	NO	NO	0.5m

Notes:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".

6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2017.06.06	2018.06.05	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2017.10.26	2018.10.25	1 year
3	EMI Test Receiver	Agilent	N9038A	MY53227146	2017.06.06	2018.06.05	1 year
4	Test Receiver	R&S	ESPI	101318	2017.06.06	2018.06.05	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2018.04.08	2019.04.07	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2017.06.06	2018.06.05	1 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2018.04.08	2019.04.07	1 year
8	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2017.07.06	2018.07.05	1 year
9	Amplifier	EMC	EMC051835 SE	980246	2017.08.09	2018.08.08	1 year
10	Amplifier	MITEQ	TTA1840-35-HG	177156	2017.06.06	2018.06.05	1 year
11	Loop Antenna	ARA	PLA-1030/B	1029	2017.06.06	2018.06.05	1 year
12	Power Meter	DARE	RPR3006W	15100041SN 084	2017.08.07	2018.08.06	1 year
13	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2017.04.21	2020.04.20	3 year
14	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2017.04.21	2020.04.20	3 year
15	High Test Cable(1G-40GHz)	N/A	R-03	N/A	2017.04.21	2020.04.20	3 year
16	High Test Cable(1G-40GHz)	N/A	R-04	N/A	2017.04.21	2020.04.20	3 year
17	Filter	TRILTHIC	2400MHz	29	2018.03.29	2019.03.28	1 year
18	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2018.06.05	2019.06.04	1 year
2	LISN	R&S	ENV216	101313	2018.04.18	2019.04.19	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2018.06.05	2019.06.04	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2018.06.05	2019.06.04	1 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2017.04.21	2020.04.20	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2017.04.21	2020.04.20	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2017.04.21	2020.04.20	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable which is scheduled for calibration every 3 years.

7 TEST REQUIREMENTS

7.1 CONDUCTED EMISSIONS TEST

7.1.1 Applicable Standard


According to FCC Part 15.207(a) and KDB 174176 D01 Line Conducted FAQ v01r01

7.1.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
 2. The lower limit shall apply at the transition frequencies
 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

7.1.3 Test Configuration



7.1.4 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

7.1.5 Test Results

Pass

7.1.6 Test Results


EUT:	JMGO Smart Projector	Model Name :	N7
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 19V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Module1:

Frequency (MHz)	Reading Level (dB μ V)	Correct Factor (dB)	Measure-ment (dB μ V)	Limits (dB μ V)	Margin (dB)	Remark
0.1700	35.93	9.82	45.75	54.96	-9.21	AVG
0.1739	50.44	9.82	60.26	64.77	-4.51	QP
0.1940	50.04	9.82	59.86	63.86	-4.00	QP
0.1940	36.71	9.82	46.53	53.86	-7.33	AVG
0.2548	36.82	9.82	46.64	51.60	-4.96	AVG
0.2580	47.49	9.82	57.31	61.49	-4.18	QP
0.3499	42.16	9.82	51.98	58.96	-6.98	QP
0.3539	31.21	9.83	41.04	48.87	-7.83	AVG
0.4179	35.19	9.83	45.02	57.49	-12.47	QP
0.4219	28.10	9.83	37.93	47.41	-9.48	AVG
3.4940	33.10	10.05	43.15	56.00	-12.85	QP
3.5419	19.62	10.05	29.67	46.00	-16.33	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT:	JMGO Smart Projector	Model Name :	N7
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	DC 19V from Adapter AC 120V/60Hz	Test Mode:	Mode 1


Module1:

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB μ V)	(dB)	(dB μ V)	(dB μ V)	(dB)	
0.1539	51.01	9.92	60.93	65.78	-4.85	QP
0.1539	39.13	9.92	49.05	55.78	-6.73	AVG
0.2540	47.20	9.92	57.12	61.62	-4.50	QP
0.2540	35.74	9.92	45.66	51.62	-5.96	AVG
0.3459	39.96	9.92	49.88	59.06	-9.18	QP
0.3539	28.61	9.93	38.54	48.87	-10.33	AVG
0.4219	36.45	9.93	46.38	57.41	-11.03	QP
0.4219	29.83	9.93	39.76	47.41	-7.65	AVG
0.4580	35.39	9.93	45.32	56.73	-11.41	QP
0.4580	23.72	9.93	33.65	46.73	-13.08	AVG
4.2419	19.30	9.95	29.25	46.00	-16.75	AVG
4.4179	31.21	9.96	41.17	56.00	-14.83	QP

Remark:

1. All readings are Quasi-Peak and Average values.

2. Factor = Insertion Loss + Cable Loss.




EUT:	JMGO Smart Projector	Model Name :	N7
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 19V from Adapter AC 240V/60Hz	Test Mode:	Mode 1

Module1:

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB μ V)	(dB)	(dB μ V)	(dB μ V)	(dB)	
0.1580	51.53	9.82	61.35	65.56	-4.21	QP
0.1580	38.12	9.82	47.94	55.56	-7.62	AVG
0.2540	46.49	9.82	56.31	61.62	-5.31	QP
0.2540	36.30	9.82	46.12	51.62	-5.50	AVG
0.3457	42.16	9.82	51.98	59.06	-7.08	QP
0.3497	29.84	9.82	39.66	48.97	-9.31	AVG
0.7217	38.15	9.84	47.99	56.00	-8.01	QP
0.7419	21.88	9.84	31.72	46.00	-14.28	AVG
3.4700	21.20	10.05	31.25	46.00	-14.75	AVG
3.4940	36.78	10.05	46.83	56.00	-9.17	QP
4.2499	35.45	10.05	45.50	56.00	-10.50	QP
4.3539	20.67	10.06	30.73	46.00	-15.27	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT:	JMGO Smart Projector	Model Name :	N7
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	DC 19V from Adapter AC 240V/60Hz	Test Mode:	Mode 1


Module1:

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB μ V)	(dB)	(dB μ V)	(dB μ V)	(dB)	
0.1564	51.80	9.92	61.72	65.65	-3.93	QP
0.1564	37.22	9.92	47.14	55.65	-8.51	AVG
0.1737	50.88	9.92	60.80	64.78	-3.98	QP
0.1737	36.60	9.92	46.52	54.78	-8.26	AVG
0.2540	47.20	9.92	57.12	61.62	-4.50	QP
0.2540	37.29	9.92	47.21	51.62	-4.41	AVG
0.4218	27.51	9.93	37.44	47.41	-9.97	AVG
0.4339	37.36	9.93	47.29	57.18	-9.89	QP
0.7217	29.07	9.93	39.00	56.00	-17.00	QP
0.7378	11.29	9.93	21.22	46.00	-24.78	AVG
2.9739	16.11	9.95	26.06	46.00	-19.94	AVG
2.9860	32.59	9.95	42.54	56.00	-13.46	QP

Remark:

1. All readings are Quasi-Peak and Average values.

2. Factor = Insertion Loss + Cable Loss.




EUT:	JMGO Smart Projector	Model Name :	N7
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 19V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Module2:

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB μ V)	(dB)	(dB μ V)	(dB μ V)	(dB)	
0.1555	50.93	9.82	60.75	65.70	-4.95	QP
0.1580	37.67	9.82	47.49	55.56	-8.07	AVG
0.2038	43.73	9.82	53.55	63.45	-9.90	QP
0.2099	34.73	9.82	44.55	53.21	-8.66	AVG
0.2459	47.65	9.82	57.47	61.89	-4.42	QP
0.2540	37.10	9.82	46.92	51.62	-4.70	AVG
0.2819	43.80	9.82	53.62	60.76	-7.14	QP
0.2819	33.49	9.82	43.31	50.76	-7.45	AVG
0.4259	38.18	9.83	48.01	57.33	-9.32	QP
0.4259	31.27	9.83	41.10	47.33	-6.23	AVG
0.4540	23.62	9.83	33.45	46.80	-13.35	AVG
0.4580	37.76	9.83	47.59	56.73	-9.14	QP

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	JMGO Smart Projector	Model Name :	N7
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	DC 19V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Module2:

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB μ V)	(dB)	(dB μ V)	(dB μ V)	(dB)	
0.1500	40.85	9.92	50.77	55.99	-5.22	AVG
0.1539	51.33	9.92	61.25	65.78	-4.53	QP
0.2459	47.86	9.92	57.78	61.89	-4.11	QP
0.2519	37.07	9.92	46.99	51.69	-4.70	AVG
0.3539	42.86	9.93	52.79	58.87	-6.08	QP
0.3539	29.93	9.93	39.86	48.87	-9.01	AVG
0.4259	37.67	9.93	47.60	57.33	-9.73	QP
0.4259	29.53	9.93	39.46	47.33	-7.87	AVG
0.5738	17.69	9.93	27.62	46.00	-18.38	AVG
0.5819	31.04	9.93	40.97	56.00	-15.03	QP
3.7219	29.83	9.95	39.78	56.00	-16.22	QP
3.7219	18.16	9.95	28.11	46.00	-17.89	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT:	JMGO Smart Projector	Model Name :	N7
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 19V from Adapter AC 240V/60Hz	Test Mode:	Mode 1


Module2:

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB μ V)	(dB)	(dB μ V)	(dB μ V)	(dB)	
0.1739	50.30	9.82	60.12	64.77	-4.65	QP
0.1739	38.70	9.82	48.52	54.77	-6.25	AVG
0.2459	47.41	9.82	57.23	61.89	-4.66	QP
0.2500	37.65	9.82	47.47	51.75	-4.28	AVG
0.3659	32.22	9.83	42.05	48.59	-6.54	AVG
0.3699	42.69	9.83	52.52	58.50	-5.98	QP
0.4179	40.93	9.83	50.76	57.49	-6.73	QP
0.4259	29.23	9.83	39.06	47.33	-8.27	AVG
0.7139	37.17	9.83	47.00	56.00	-9.00	QP
0.7378	20.41	9.84	30.25	46.00	-15.75	AVG
1.9659	33.56	9.84	43.40	56.00	-12.60	QP
1.9699	19.88	9.84	29.72	46.00	-16.28	AVG

Remark:

1. All readings are Quasi-Peak and Average values.

2. Factor = Insertion Loss + Cable Loss.



EUT:	JMGO Smart Projector	Model Name :	N7
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	DC 19V from Adapter AC 240V/60Hz	Test Mode:	Mode 1


Module2:

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB μ V)	(dB)	(dB μ V)	(dB μ V)	(dB)	
0.1700	50.71	9.92	60.63	64.96	-4.33	QP
0.1700	39.25	9.92	49.17	54.96	-5.79	AVG
0.2500	37.53	9.92	47.45	51.75	-4.30	AVG
0.2580	47.16	9.92	57.08	61.49	-4.41	QP
0.3539	41.25	9.93	51.18	58.87	-7.69	QP
0.3539	30.36	9.93	40.29	48.87	-8.58	AVG
0.7219	32.14	9.93	42.07	56.00	-13.93	QP
0.7339	15.57	9.93	25.50	46.00	-20.50	AVG
2.0739	34.31	9.94	44.25	56.00	-11.75	QP
2.0939	19.71	9.94	29.65	46.00	-16.35	AVG
4.9618	32.63	9.96	42.59	56.00	-13.41	QP
5.0618	17.14	9.96	27.10	50.00	-22.90	AVG

Remark:

1. All readings are Quasi-Peak and Average values.

2. Factor = Insertion Loss + Cable Loss.



7.2 RADIATED SPURIOUS EMISSION

7.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and ANSI C63.10-2013

7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μ V/m)	Field Strength (dB μ V/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (μ V/m)	300
0.490~1.705	2400/F(KHz)	20 log (μ V/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dB μ V/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dB μ V/m=20 log (μ V/m)


2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. Distance extrapolation factor =40log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dB μ V) + distance extrapolation factor.

7.2.3 Measuring Instruments


The Measuring equipment is listed in the section 6.3 of this test report.

7.2.4 Test Configuration


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [\text{kHz}]/\text{narrower RBW} [\text{kHz}])$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

7.2.6 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	JMGO Smart Projector	Model No.:	N7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Loren Luo

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $20 \log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission below 1GHz (30MHz to 1GHz)

All the modulation modes have been tested, and the worst result was report as below:


EUT:	JMGO Smart Projector	Model Name :	N7
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010hPa	Test Mode:	Mode 1
Test Voltage :	DC 19V from Adapter AC 120V/60Hz		

Module1:

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	33.7986	15.45	19.47	34.92	40.00	-5.08	QP
V	37.0248	18.18	17.96	36.14	40.00	-3.86	QP
V	55.2207	23.54	12.23	35.77	40.00	-4.23	QP
V	185.7880	21.45	12.70	34.15	43.50	-9.35	QP
V	614.2142	15.64	19.86	35.50	46.00	-10.50	QP
V	896.9963	12.70	24.51	37.21	46.00	-8.79	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit




Module1:

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	30.7454	8.90	20.89	29.79	40.00	-10.21	QP
H	57.3922	20.33	11.83	32.16	40.00	-7.84	QP
H	75.9770	15.90	11.56	27.46	40.00	-12.54	QP
H	198.5877	23.67	13.75	37.42	43.50	-6.08	QP
H	627.2738	17.73	20.11	37.84	46.00	-8.16	QP
H	900.1471	14.74	24.52	39.26	46.00	-6.74	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit

72.0 dBuV/m




Module2:

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	30.7454	14.35	20.89	35.24	40.00	-4.76	QP
V	42.7496	21.07	15.08	36.15	40.00	-3.85	QP
V	58.8185	24.29	11.60	35.89	40.00	-4.11	QP
V	198.5877	16.06	13.75	29.81	43.50	-13.69	QP
V	612.0642	16.03	19.79	35.82	46.00	-10.18	QP
V	900.1471	13.40	24.52	37.92	46.00	-8.08	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit




Module2:

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	58.8185	20.46	11.60	32.06	40.00	-7.94	QP
H	197.8925	22.91	13.75	36.66	43.50	-6.84	QP
H	287.9904	20.87	14.05	34.92	46.00	-11.08	QP
H	455.9057	21.77	16.34	38.11	46.00	-7.89	QP
H	631.6884	15.88	20.05	35.93	46.00	-10.07	QP
H	900.1471	14.90	24.52	39.42	46.00	-6.58	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



■ Spurious Emission Above 1GHz (1GHz to 25GHz)

EUT:	JMGO Smart Projector	Model No.:	N7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Loren Luo

All the modulation modes have been tested, and the worst result was report as below:

Module1:

Frequency (MHz)	Read Level (dB μ V)	Cable loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Remark	Comment
Low Channel (2402 MHz)(8-DPSK)--Above 1G									
4803.312	62.24	5.21	35.59	44.30	58.74	74.00	-15.26	Pk	Vertical
4803.312	40.73	5.21	35.59	44.30	37.23	54.00	-16.77	AV	Vertical
7206.353	62.16	6.48	36.27	44.60	60.31	74.00	-13.69	Pk	Vertical
7206.353	40.66	6.48	36.27	44.60	38.81	54.00	-15.19	AV	Vertical
4803.076	59.65	5.21	35.55	44.30	56.11	74.00	-17.89	Pk	Horizontal
4803.076	41.85	5.21	35.55	44.30	38.31	54.00	-15.69	AV	Horizontal
7206.284	61.12	6.48	36.27	44.52	59.35	74.00	-14.65	Pk	Horizontal
7206.284	40.94	6.48	36.27	44.52	39.17	54.00	-14.83	AV	Horizontal
Mid Channel (2441 MHz)(8-DPSK)--Above 1G									
4882.278	60.55	5.21	35.66	44.20	57.22	74.00	-16.78	Pk	Vertical
4882.278	42.51	5.21	35.66	44.20	39.18	54.00	-14.82	AV	Vertical
7323.740	60.68	7.10	36.50	44.43	59.85	74.00	-14.15	Pk	Vertical
7323.740	39.60	7.10	36.50	44.43	38.77	54.00	-15.23	AV	Vertical
4881.726	59.89	5.21	35.66	44.20	56.56	74.00	-17.44	Pk	Horizontal
4881.726	41.03	5.21	35.66	44.20	37.70	54.00	-16.30	AV	Horizontal
7322.737	62.05	7.10	36.50	44.43	61.22	74.00	-12.78	Pk	Horizontal
7322.737	39.76	7.10	36.50	44.43	38.93	54.00	-15.07	AV	Horizontal
High Channel (2480 MHz)(8-DPSK)-- Above 1G									
4960.918	59.62	5.21	35.52	44.21	56.14	74.00	-17.86	Pk	Vertical
4960.918	42.91	5.21	35.52	44.21	39.43	54.00	-14.57	AV	Vertical
7440.214	60.48	7.10	36.53	44.60	59.51	74.00	-14.49	Pk	Vertical
7440.214	40.64	7.10	36.53	44.60	39.67	54.00	-14.33	AV	Vertical
4960.500	62.22	5.21	35.52	44.21	58.74	74.00	-15.26	Pk	Horizontal
4960.500	42.21	5.21	35.52	44.21	38.73	54.00	-15.27	AV	Horizontal
7440.607	62.33	7.10	36.53	44.60	61.36	74.00	-12.64	Pk	Horizontal
7440.607	42.08	7.10	36.53	44.60	41.11	54.00	-12.89	AV	Horizontal

All the modulation modes have been tested, and the worst result was report as below:

Module2:

Frequency (MHz)	Read Level (dB μ V)	Cable loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Remark		Comment
								Low Channel (2402 MHz)(8-DPSK)--Above 1G	Mid Channel (2441 MHz)(8-DPSK)--Above 1G	
4804.330	60.12	5.21	35.59	44.30	56.62	74.00	-17.38	Pk	Vertical	
4804.330	41.13	5.21	35.59	44.30	37.63	54.00	-16.37	AV	Vertical	
7206.433	62.00	6.48	36.27	44.60	60.15	74.00	-13.85	Pk	Vertical	
7206.433	41.22	6.48	36.27	44.60	39.37	54.00	-14.63	AV	Vertical	
4803.460	61.50	5.21	35.55	44.30	57.96	74.00	-16.04	Pk	Horizontal	
4803.460	41.34	5.21	35.55	44.30	37.80	54.00	-16.20	AV	Horizontal	
7206.270	60.50	6.48	36.27	44.52	58.73	74.00	-15.27	Pk	Horizontal	
7206.270	40.84	6.48	36.27	44.52	39.07	54.00	-14.93	AV	Horizontal	
Mid Channel (2441 MHz)(8-DPSK)--Above 1G										
4881.144	61.83	5.21	35.66	44.20	58.50	74.00	-15.50	Pk	Vertical	
4881.144	40.41	5.21	35.66	44.20	37.08	54.00	-16.92	AV	Vertical	
7323.804	62.07	7.10	36.50	44.43	61.24	74.00	-12.76	Pk	Vertical	
7323.804	41.00	7.10	36.50	44.43	40.17	54.00	-13.83	AV	Vertical	
4882.311	60.50	5.21	35.66	44.20	57.17	74.00	-16.83	Pk	Horizontal	
4882.311	42.69	5.21	35.66	44.20	39.36	54.00	-14.64	AV	Horizontal	
7323.318	61.68	7.10	36.50	44.43	60.85	74.00	-13.15	Pk	Horizontal	
7323.318	39.79	7.10	36.50	44.43	38.96	54.00	-15.04	AV	Horizontal	
High Channel (2480 MHz)(8-DPSK)-- Above 1G										
4960.975	61.08	5.21	35.52	44.21	57.60	74.00	-16.40	Pk	Vertical	
4960.975	40.11	5.21	35.52	44.21	36.63	54.00	-17.37	AV	Vertical	
7439.622	60.02	7.10	36.53	44.60	59.05	74.00	-14.95	Pk	Vertical	
7439.622	41.20	7.10	36.53	44.60	40.23	54.00	-13.77	AV	Vertical	
4960.117	61.99	5.21	35.52	44.21	58.51	74.00	-15.49	Pk	Horizontal	
4960.117	40.40	5.21	35.52	44.21	36.92	54.00	-17.08	AV	Horizontal	
7440.658	61.92	7.10	36.53	44.60	60.95	74.00	-13.05	Pk	Horizontal	
7440.658	41.76	7.10	36.53	44.60	40.79	54.00	-13.21	AV	Horizontal	

Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).

(2) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor

(3)All other emissions more than 20dB below the limit.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

EUT:	JMGO Smart Projector	Model No.:	N7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4	Test By:	Loren Luo

All the modulation modes have been tested, and the worst result was report as below:

Module1:

Frequency (MHz)	Meter Reading (dB μ V)	Cable Loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type	Comment
3Mbps (8-DPSK)-hopping									
2310.00	61.02	2.97	27.80	43.80	47.99	74	-26.01	Pk	Horizontal
2310.00	40.06	2.97	27.80	43.80	27.03	54	-26.97	AV	Horizontal
2310.00	62.10	2.97	27.80	43.80	49.07	74	-24.93	Pk	Vertical
2310.00	40.30	2.97	27.80	43.80	27.27	54	-26.73	AV	Vertical
2390.00	59.54	3.14	27.21	43.80	46.09	74	-27.91	Pk	Vertical
2390.00	42.14	3.14	27.21	43.80	28.69	54	-25.31	AV	Vertical
2390.00	60.87	3.14	27.21	43.80	47.42	74	-26.58	Pk	Horizontal
2390.00	42.77	3.14	27.21	43.80	29.32	54	-24.68	AV	Horizontal
2483.50	62.43	3.58	27.70	44.00	49.71	74	-24.29	Pk	Vertical
2483.50	40.55	3.58	27.70	44.00	27.83	54	-26.17	AV	Vertical
2483.50	60.56	3.58	27.70	44.00	47.84	74	-26.16	Pk	Horizontal
2483.50	40.75	3.58	27.70	44.00	28.03	54	-25.97	AV	Horizontal
3Mbps (8-DPSK)- Non-hopping									
2310.00	60.59	2.97	27.80	43.80	47.56	74	-26.44	Pk	Horizontal
2310.00	40.90	2.97	27.80	43.80	27.87	54	-26.13	AV	Horizontal
2310.00	59.57	2.97	27.80	43.80	46.54	74	-27.46	Pk	Vertical
2310.00	39.77	2.97	27.80	43.80	26.74	54	-27.26	AV	Vertical
2390.00	62.39	3.14	27.21	43.80	48.94	74	-25.06	Pk	Vertical
2390.00	42.16	3.14	27.21	43.80	28.71	54	-25.29	AV	Vertical
2390.00	62.06	3.14	27.21	43.80	48.61	74	-25.39	Pk	Horizontal
2390.00	42.76	3.14	27.21	43.80	29.31	54	-24.69	AV	Horizontal
2483.50	60.46	3.58	27.70	44.00	47.74	74	-26.26	Pk	Vertical
2483.50	42.63	3.58	27.70	44.00	29.91	54	-24.09	AV	Vertical
2483.50	60.06	3.58	27.70	44.00	47.34	74	-26.66	Pk	Horizontal
2483.50	42.07	3.58	27.70	44.00	29.35	54	-24.65	AV	Horizontal

All the modulation modes have been tested, and the worst result was report as below:

Module2:

Frequency (MHz)	Meter Reading (dB μ V)	Cable Loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type	Comment
3Mbps (8-DPSK)-hopping									
2310.00	61.64	2.97	27.80	43.80	48.61	74	-25.39	Pk	Horizontal
2310.00	40.93	2.97	27.80	43.80	27.90	54	-26.10	AV	Horizontal
2310.00	62.03	2.97	27.80	43.80	49.00	74	-25.00	Pk	Vertical
2310.00	42.25	2.97	27.80	43.80	29.22	54	-24.78	AV	Vertical
2390.00	60.49	3.14	27.21	43.80	47.04	74	-26.96	Pk	Vertical
2390.00	39.65	3.14	27.21	43.80	26.20	54	-27.80	AV	Vertical
2390.00	61.17	3.14	27.21	43.80	47.72	74	-26.28	Pk	Horizontal
2390.00	40.24	3.14	27.21	43.80	26.79	54	-27.21	AV	Horizontal
2483.50	60.55	3.58	27.70	44.00	47.83	74	-26.17	Pk	Vertical
2483.50	40.88	3.58	27.70	44.00	28.16	54	-25.84	AV	Vertical
2483.50	59.55	3.58	27.70	44.00	46.83	74	-27.17	Pk	Horizontal
2483.50	42.86	3.58	27.70	44.00	30.14	54	-23.86	AV	Horizontal
3Mbps (8-DPSK)- Non-hopping									
2310.00	60.79	2.97	27.80	43.80	47.76	74	-26.24	Pk	Horizontal
2310.00	41.95	2.97	27.80	43.80	28.92	54	-25.08	AV	Horizontal
2310.00	59.64	2.97	27.80	43.80	46.61	74	-27.39	Pk	Vertical
2310.00	39.90	2.97	27.80	43.80	26.87	54	-27.13	AV	Vertical
2390.00	62.47	3.14	27.21	43.80	49.02	74	-24.98	Pk	Vertical
2390.00	40.03	3.14	27.21	43.80	26.58	54	-27.42	AV	Vertical
2390.00	60.49	3.14	27.21	43.80	47.04	74	-26.96	Pk	Horizontal
2390.00	42.43	3.14	27.21	43.80	28.98	54	-25.02	AV	Horizontal
2483.50	60.24	3.58	27.70	44.00	47.52	74	-26.48	Pk	Vertical
2483.50	40.66	3.58	27.70	44.00	27.94	54	-26.06	AV	Vertical
2483.50	59.65	3.58	27.70	44.00	46.93	74	-27.07	Pk	Horizontal
2483.50	41.05	3.58	27.70	44.00	28.33	54	-25.67	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

■ Spurious Emission in Restricted Band 3260MMHz-18000MHz

EUT:	JMGO Smart Projector	Model No.:	N7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4	Test By:	Loren Luo

All the modulation modes have been tested, and the worst result was report as below:

Module1:

Frequency (MHz)	Reading Level (dB μ V)	Cable Loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type	Comment
3260	61.64	4.04	29.57	44.70	50.55	74	-23.45	Pk	Vertical
3260	50.89	4.04	29.57	44.70	39.80	54	-14.20	AV	Vertical
3260	62.03	4.04	29.57	44.70	50.94	74	-23.06	Pk	Horizontal
3260	51.65	4.04	29.57	44.70	40.56	54	-13.44	AV	Horizontal
3332	59.62	4.26	29.87	44.40	49.35	74	-24.65	Pk	Vertical
3332	50.64	4.26	29.87	44.40	40.37	54	-13.63	AV	Vertical
3332	61.94	4.26	29.87	44.40	51.67	74	-22.33	Pk	Horizontal
3332	51.04	4.26	29.87	44.40	40.77	54	-13.23	AV	Horizontal
17797	40.19	10.99	43.95	43.50	51.63	74	-22.37	Pk	Vertical
17797	29.99	10.99	43.95	43.50	41.43	54	-12.57	AV	Vertical
17788	40.73	11.81	43.69	44.60	51.63	74	-22.37	Pk	Horizontal
17788	30.20	11.81	43.69	44.60	41.10	54	-12.90	AV	Horizontal

Module2:

Frequency (MHz)	Reading Level (dB μ V)	Cable Loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type	Comment
3260	60.74	4.04	29.57	44.70	49.65	74	-24.35	Pk	Vertical
3260	49.65	4.04	29.57	44.70	38.56	54	-15.44	AV	Vertical
3260	62.08	4.04	29.57	44.70	50.99	74	-23.01	Pk	Horizontal
3260	50.54	4.04	29.57	44.70	39.45	54	-14.55	AV	Horizontal
3332	60.12	4.26	29.87	44.40	49.85	74	-24.15	Pk	Vertical
3332	48.58	4.26	29.87	44.40	38.31	54	-15.69	AV	Vertical
3332	60.07	4.26	29.87	44.40	49.80	74	-24.20	Pk	Horizontal
3332	51.52	4.26	29.87	44.40	41.25	54	-12.75	AV	Horizontal
17797	41.96	10.99	43.95	43.50	53.40	74	-20.60	Pk	Vertical
17797	30.11	10.99	43.95	43.50	41.55	54	-12.45	AV	Vertical
17788	39.68	11.81	43.69	44.60	50.58	74	-23.42	Pk	Horizontal
17788	29.94	11.81	43.69	44.60	40.84	54	-13.16	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

7.3 NUMBER OF HOPPING CHANNEL

7.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (iii) and ANSI C63.10-2013

7.3.2 Conformance Limit

Frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

7.3.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.3

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW : To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.3.6 Test Results

EUT:	JMGO Smart Projector	Model No.:	N7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode 5(1Mbps)	Test By:	Loren Luo


Module1

Number of Hopping (Channel)	Adaptive Frequency hopping (Channel)	limit	Verdict
79	20	≥ 15	Pass


Module2

Number of Hopping (Channel)	Adaptive Frequency hopping (Channel)	limit	Verdict
79	20	≥ 15	Pass

Number of Hopping Channel Plot (Module1)



Number of Hopping Channel Plot (Module2)



7.4 HOPPING CHANNEL SEPARATION MEASUREMENT

7.4.1 Applicable Standard

According to FCC Part 15.247(a)(1) and ANSI C63.10-2013

7.4.2 Conformance Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

7.4.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.2

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Measurement Bandwidth or Channel Separation

RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.4.6 Test Results

EUT:	JMGO Smart Projector	Model No.:	N7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Loren Luo

Module1:


Modulation Mode	Channel Number	Channel Frequency (MHz)	Measured Channel Separation (MHz)	Limit (kHz)		Verdict
GFSK	0	2402	0.996	>694.000	2/3 of 20dB BW	PASS
	39	2441	1.004	>693.333	2/3 of 20dB BW	PASS
	78	2480	1.000	>692.667	2/3 of 20dB BW	PASS
$\pi/4$ -DQPSK	0	2402	1.004	>911.333	2/3 of 20dB BW	PASS
	39	2441	1.000	>910.000	2/3 of 20dB BW	PASS
	78	2480	1.004	>914.000	2/3 of 20dB BW	PASS
8-DPSK	0	2402	0.996	>870.000	2/3 of 20dB BW	PASS
	39	2441	0.996	>870.000	2/3 of 20dB BW	PASS
	78	2480	1.004	>872.667	2/3 of 20dB BW	PASS

Module2:


Modulation Mode	Channel Number	Channel Frequency (MHz)	Measured Channel Separation (MHz)	Limit (kHz)		Verdict
GFSK	0	2402	1.000	>694.000	2/3 of 20dB BW	PASS
	39	2441	1.000	>694.000	2/3 of 20dB BW	PASS
	78	2480	1.004	>693.333	2/3 of 20dB BW	PASS
$\pi/4$ -DQPSK	0	2402	1.000	>910.667	2/3 of 20dB BW	PASS
	39	2441	1.004	>910.667	2/3 of 20dB BW	PASS
	78	2480	1.000	>913.333	2/3 of 20dB BW	PASS
8-DPSK	0	2402	1.000	>870.000	2/3 of 20dB BW	PASS
	39	2441	1.000	>869.333	2/3 of 20dB BW	PASS
	78	2480	1.000	>874.000	2/3 of 20dB BW	PASS

Test Plot (Module1)


(1Mbps) Channel Separation plot on channel 00-01




(2Mbps) Channel Separation plot on channel 00-01




(1Mbps) Channel Separation plot on channel 39-40




(2Mbps) Channel Separation plot on channel 39-40



(1Mbps) Channel Separation plot on channel 77-78




(2Mbps) Channel Separation plot on channel 77-78




Test Plot (Module1)


(3Mbps) Channel Separation plot on channel 00-01



(3Mbps) Channel Separation plot on channel 39-40




(3Mbps) Channel Separation plot on channel 77-78




Test Plot (Module2)


(1Mbps) Channel Separation plot on channel 00-01




(2Mbps) Channel Separation plot on channel 00-01




(1Mbps) Channel Separation plot on channel 39-40




(2Mbps) Channel Separation plot on channel 39-40



(1Mbps) Channel Separation plot on channel 77-78




(2Mbps) Channel Separation plot on channel 77-78




Test Plot (Module2)


(3Mbps) Channel Separation plot on channel 00-01



(3Mbps) Channel Separation plot on channel 39-40



(3Mbps) Channel Separation plot on channel 77-78



7.5 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

7.5.1 Applicable Standard

According to FCC Part 15.247(a)(1)(iii) and ANSI C63.10-2013

7.5.2 Conformance Limit

The average time of occupancy on any channel shall not be greater than 0.4s within a period of 0.4s multiplied by the number of hopping channels employed.

7.5.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.5.4 Test Setup

Please refer to Section 6.1 of this test report.

7.5.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.4

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW \geq 1MHz

VBW \geq RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

Measure the maximum time duration of one single pulse.

Set the EUT for DH5, DH3 and DH1 packet transmitting.

Measure the maximum time duration of one single pulse.

7.5.6 Test Results

EUT:	JMGO Smart Projector	Model No.:	N7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Loren Luo

Module1:

Modulation Mode	Channel Number	Packet type	Mode	Hops Over Occupancy Time	Pulse width	dwell time (ms)	Limit	Verdict
				(ms)	(ms)		(ms)	
GFSK	39	DH1	Normal	320	0.453	144.96	<400	PASS
	39		AFH	160	0.453	72.48	<400	PASS
	39	DH3	Normal	160	1.707	273.12	<400	PASS
	39		AFH	80	1.707	136.56	<400	PASS
	39	DH5	Normal	106.67	2.947	314.36	<400	PASS
	39		AFH	53.33	2.947	157.16	<400	PASS
π/4-DQPSK	39	2DH1	Normal	320	0.453	144.96	<400	PASS
	39		AFH	160	0.453	72.48	<400	PASS
	39	2DH3	Normal	160	1.693	270.88	<400	PASS
	39		AFH	80	1.693	135.44	<400	PASS
	39	2DH5	Normal	106.67	2.960	315.74	<400	PASS
	39		AFH	53.33	2.960	157.86	<400	PASS
8DPSK	39	3DH1	Normal	320	0.453	144.96	<400	PASS
	39		AFH	160	0.453	72.48	<400	PASS
	39	3DH3	Normal	160	1.720	275.20	<400	PASS
	39		AFH	80	1.720	137.60	<400	PASS
	39	3DH5	Normal	106.67	2.947	314.36	<400	PASS
	39		AFH	53.33	2.947	157.16	<400	PASS

Module2:

Modulation Mode	Channel Number	Packet type	Mode	Hops Over Occupancy Time	Pulse width (ms)	dwell time (ms)	Limit (ms)	Verdict
				(ms)				
GFSK	39	DH1	Normal	320	0.453	144.96	<400	PASS
	39		AFH	160	0.453	72.48	<400	PASS
	39	DH3	Normal	160	1.720	275.20	<400	PASS
	39		AFH	80	1.720	137.60	<400	PASS
	39	DH5	Normal	106.67	2.973	317.13	<400	PASS
	39		AFH	53.33	2.973	158.55	<400	PASS
π/4-DQPSK	39	2DH1	Normal	320	0.466	149.12	<400	PASS
	39		AFH	160	0.466	74.56	<400	PASS
	39	2DH3	Normal	160	1.720	275.20	<400	PASS
	39		AFH	80	1.720	137.60	<400	PASS
	39	2DH5	Normal	106.67	2.960	315.74	<400	PASS
	39		AFH	53.33	2.960	157.86	<400	PASS
8DPSK	39	3DH1	Normal	320	0.453	144.96	<400	PASS
	39		AFH	160	0.453	72.48	<400	PASS
	39	3DH3	Normal	160	1.707	273.12	<400	PASS
	39		AFH	80	1.707	136.56	<400	PASS
	39	3DH5	Normal	106.67	2.947	314.36	<400	PASS
	39		AFH	53.33	2.947	157.16	<400	PASS

Note:

A Period Time = (channel number)*0.4

DH1 Dwell time: Reading * (1600/2)*31.6/(channel number)

DH3 Dwell time: Reading * (1600/4)*31.6/(channel number)


DH5 Dwell time: Reading * (1600/6)*31.6/(channel number)

For Example:


1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels. With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels. With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s), Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

Test Plot (Module1)


Package Transfer Time Plot CH39-DH1




Package Transfer Time Plot CH39-2DH1




Package Transfer Time Plot CH39-DH3




Package Transfer Time Plot CH39-2DH3



Package Transfer Time Plot CH39-DH5




Package Transfer Time Plot CH39-2DH5




Test Plot (Module1)


Package Transfer Time Plot CH39-3DH1



Package Transfer Time Plot CH39-3DH3




Package Transfer Time Plot CH39-3DH5




Test Plot (Module2)


Package Transfer Time Plot CH39-DH1




Package Transfer Time Plot CH39-2DH1




Package Transfer Time Plot CH39-DH3




Package Transfer Time Plot CH39-2DH3



Package Transfer Time Plot CH39-DH5




Package Transfer Time Plot CH39-2DH5




Test Plot (Module2)


Package Transfer Time Plot CH39-3DH1



Package Transfer Time Plot CH39-3DH3



Package Transfer Time Plot CH39-3DH5



7.6 20DB BANDWIDTH TEST

7.6.1 Applicable Standard

According to FCC Part 15.247(a)(1) and ANSI C63.10-2013

7.6.2 Conformance Limit

No limit requirement.

7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

7.6.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 6.9.2

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW \geq 1% of the 20 dB bandwidth

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.6.6 Test Results

EUT:	JMGO Smart Projector	Model No.:	N7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Loren Luo

Module1:

Test Channel	Frequency (MHz)	Measured Bandwidth (KHz)	Limit	Verdict
			(kHz)	
1Mbps				
0	2402	1041	N/A	PASS
39	2441	1040	N/A	PASS
78	2480	1039	N/A	PASS
2Mbps				
0	2402	1367	N/A	PASS
39	2441	1365	N/A	PASS
78	2480	1371	N/A	PASS
3Mbps				
0	2402	1305	N/A	PASS
39	2441	1305	N/A	PASS
78	2480	1309	N/A	PASS

Module2:

Test Channel	Frequency (MHz)	Measured Bandwidth (KHz)	Limit	Verdict
			(kHz)	
1Mbps				
0	2402	1041	N/A	PASS
39	2441	1041	N/A	PASS
78	2480	1040	N/A	PASS
2Mbps				
0	2402	1366	N/A	PASS
39	2441	1366	N/A	PASS
78	2480	1370	N/A	PASS
3Mbps				
0	2402	1305	N/A	PASS
39	2441	1304	N/A	PASS
78	2480	1311	N/A	PASS

Note: N/A (Not Applicable)

Test Plot (Module1)


20dB Bandwidth plot on channel 00 (1Mbps)




20dB Bandwidth plot on channel 00 (2Mbps)



20dB Bandwidth plot on channel 39 (1Mbps)




20dB Bandwidth plot on channel 39 (2Mbps)



20dB Bandwidth plot on channel 78 (1Mbps)




20dB Bandwidth plot on channel 78 (2Mbps)




Test Plot (Module1)


20dB Bandwidth plot on channel 00 (3Mbps)



20dB Bandwidth plot on channel 39 (3Mbps)



20dB Bandwidth plot on channel 78 (3Mbps)




Test Plot (Module2)


20dB Bandwidth plot on channel 00 (1Mbps)




20dB Bandwidth plot on channel 00 (2Mbps)




20dB Bandwidth plot on channel 39 (1Mbps)




20dB Bandwidth plot on channel 39 (2Mbps)



20dB Bandwidth plot on channel 78 (1Mbps)



20dB Bandwidth plot on channel 78 (2Mbps)




Test Plot (Module2)


20dB Bandwidth plot on channel 00 (3Mbps)



20dB Bandwidth plot on channel 39 (3Mbps)



20dB Bandwidth plot on channel 78 (3Mbps)



7.7 PEAK OUTPUT POWER

7.7.1 Applicable Standard

According to FCC Part 15.247(b)(1) and ANSI C63.10-2013

7.7.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.

7.7.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.7.4 Test Setup

Please refer to Section 6.1 of this test report.

7.7.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.5.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW \geq the 20 dB bandwidth of the emission being measured

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.7.6 Test Results

EUT:	JMGO Smart Projector	Model No.:	N7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Loren Luo

Module1:


Test Channel	Frequency (MHz)	Power Setting	Peak Output Power	LIMIT (dBm)	Verdict
			(dBm)		
1Mbps					
0	2402	Default	1.56	20.97	PASS
39	2441	Default	1.71	20.97	PASS
78	2480	Default	0.96	20.97	PASS
2Mbps					
0	2402	Default	2.76	20.97	PASS
39	2441	Default	2.93	20.97	PASS
78	2480	Default	2.15	20.97	PASS
3Mbps					
0	2402	Default	2.94	20.97	PASS
39	2441	Default	3.18	20.97	PASS
78	2480	Default	2.45	20.97	PASS

Module2:


Test Channel	Frequency (MHz)	Power Setting	Peak Output Power	LIMIT (dBm)	Verdict
			(dBm)		
1Mbps					
0	2402	Default	1.58	20.97	PASS
39	2441	Default	1.67	20.97	PASS
78	2480	Default	0.97	20.97	PASS
2Mbps					
0	2402	Default	2.85	20.97	PASS
39	2441	Default	2.91	20.97	PASS
78	2480	Default	2.21	20.97	PASS
3Mbps					
0	2402	Default	2.96	20.97	PASS
39	2441	Default	3.16	20.97	PASS
78	2480	Default	2.39	20.97	PASS

Test Plot (Module1)


Peak output Power plot on channel 00 (1Mbps)




Peak output Power plot on channel 00 (2Mbps)




Peak output Power plot on channel 39 (1Mbps)




Peak output Power plot on channel 39 (2Mbps)



Peak output Power plot on channel 78 (1Mbps)




Peak output Power plot on channel 78 (2Mbps)




Test Plot (Module1)


Peak output Power plot on channel 00 (3Mbps)



Peak output Power plot on channel 39 (3Mbps)




Peak output Power plot on channel 78 (3Mbps)




Test Plot (Module2)


Peak output Power plot on channel 00 (1Mbps)




Peak output Power plot on channel 00 (2Mbps)




Peak output Power plot on channel 39 (1Mbps)




Peak output Power plot on channel 39 (2Mbps)



Peak output Power plot on channel 78 (1Mbps)




Peak output Power plot on channel 78 (2Mbps)




Test Plot (Module2)


Peak output Power plot on channel 00 (3Mbps)



Peak output Power plot on channel 39 (3Mbps)



Peak output Power plot on channel 78 (3Mbps)



7.8 CONDUCTED BAND EDGE MEASUREMENT

7.8.1 Applicable Standard

According to FCC Part 15.247(d) and ANSI C63.10-2013

7.8.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.8.4 Test Setup

Please refer to Section 6.1 of this test report.

7.8.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.6.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = 100KHz

VBW = 300KHz

Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.


Repeat above procedures until all measured frequencies were complete.

7.8.6 Test Results

EUT:	JMGO Smart Projector	Model No.:	N7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2 /Mode4/ Mode 5	Test By:	Loren Luo


Test Plot (Module1)

GFSK: Band Edge-Low Channel




Copyright 2000-2008 Agilent Technologies

GFSK: Band Edge-High Channel




Copyright 2000-2008 Agilent Technologies

GFSK: Band Edge-Low Channel (Hopping Mode)



Copyright 2000-2008 Agilent Technologies


GFSK: Band Edge-High Channel (Hopping Mode)



Copyright 2000-2008 Agilent Technologies


Test Plot (Module1)

π /4-DQPSK: Band Edge-Low Channel



Copyright 2000-2008 Agilent Technologies


π /4-DQPSK: Band Edge-High Channel



Copyright 2000-2008 Agilent Technologies

π /4-DQPSK: Band Edge-Low Channel


(Hopping Mode)




Copyright 2000-2008 Agilent Technologies

π /4-DQPSK: Band Edge-High Channel


(Hopping Mode)




Copyright 2000-2008 Agilent Technologies

Test Plot (Module1)**8-DPSK: Band Edge-Low Channel**


Copyright 2000-2008 Agilent Technologies

8-DPSK: Band Edge-High Channel

Copyright 2000-2008 Agilent Technologies

8-DPSK: Band Edge-Low Channel (Hopping Mode)


Copyright 2000-2008 Agilent Technologies

8-DPSK: Band Edge-High Channel (Hopping Mode)

Copyright 2000-2008 Agilent Technologies


Test Plot (Module2)

GFSK: Band Edge-Low Channel




Copyright 2000-2008 Agilent Technologies

GFSK: Band Edge-High Channel




Copyright 2000-2008 Agilent Technologies

GFSK: Band Edge-Low Channel (Hopping Mode)



Copyright 2000-2008 Agilent Technologies


GFSK: Band Edge-High Channel (Hopping Mode)



Copyright 2000-2008 Agilent Technologies


Test Plot (Module2)

π /4-DQPSK: Band Edge-Low Channel



Copyright 2000-2008 Agilent Technologies


π /4-DQPSK: Band Edge-High Channel



Copyright 2000-2008 Agilent Technologies

π /4-DQPSK: Band Edge-Low Channel


(Hopping Mode)



Copyright 2000-2008 Agilent Technologies

π /4-DQPSK: Band Edge-High Channel


(Hopping Mode)



Copyright 2000-2008 Agilent Technologies


Test Plot (Module2)

8-DPSK: Band Edge-Low Channel




Copyright 2000-2008 Agilent Technologies

8-DPSK: Band Edge-High Channel




Copyright 2000-2008 Agilent Technologies

8-DPSK: Band Edge-Low Channel
(Hopping Mode)

Copyright 2000-2008 Agilent Technologies

8-DPSK: Band Edge-High Channel (Hopping Mode)



Copyright 2000-2008 Agilent Technologies

7.9 SPURIOUS RF CONDUCTED EMISSION

7.9.1 Applicable Standard

According to FCC Part 15.247(d) and ANSI C63.10-2013.

7.9.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.9.4 Test Setup

Please refer to Section 6.1 of this test report.

7.9.5 Test Procedure

Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Then the limit shall be attenuated by at least 20 dB relative to the maximum amplitude level in 100 kHz.


7.9.6 Test Results

Remark: The measurement frequency range is from 9KHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.


The worst mode is 8-DPSK mode, and the report only show the worst mode data.

Test Plot (Module1)


8-DPSK on channel 00




8-DPSK on channel 00





8-DPSK on channel 00



8-DPSK on channel 00




Test Plot (Module1)



Test Plot (Module1)


8-DPSK on channel 78




8-DPSK on channel 78



8-DPSK on channel 78




8-DPSK on channel 78




Test Plot (Module2)


8-DPSK on channel 00




8-DPSK on channel 00



8-DPSK on channel 00




8-DPSK on channel 00



Test Plot (Module2)


8-DPSK on channel 39




8-DPSK on channel 39





8-DPSK on channel 39



8-DPSK on channel 39



Test Plot (Module2)



7.10 ANTENNA APPLICATION**7.10.1 Antenna Requirement**

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.10.2 Result

The EUT antenna is permanent attached FPCB antenna(Gain:3 dBi). It comply with the standard requirement.

END OF REPORT