



BEC INCORPORATED

SAR REPORT

TEST STANDARDS:
FCC Part 15 Subpart C Intentional Radiator
KDB 447498 D01

**Woodstream Corporation Model V400M LoRa Radio Module
With Models V450 and V460 Connected Control Rodent Traps (DTS)**

**FCC ID: SNA-V400M
ISED ID: 9458A-V400M**

REPORT BEC-1908-04

CUSTOMER:
Woodstream Corporation
69 North Locust Street
Lititz, PA 17543

PREPARED BY: 
Paul Banker, Test Engineer

REVIEWED and APPROVED BY: 
Steve Fanella, Quality Manager


The results described in this report relate only to the item(s) tested. This document shall not be reproduced except in full without prior written permission of BEC Incorporated





TABLE OF CONTENTS

Notice To Customer	3
Revision History	3
1.0 Administrative Information.....	4
1.1 General Information Table	4
2.0 SAR Test Exclusion Parameters and Justification	5
3.0 SAR Test Exclusion Calculation.....	6



Notice To Customer

This report and any recommendations it contains represent the result of BEC's testing and assessment on behalf of your company. Testing has been conducted according to accepted engineering standards and practices. This report reflects testing and assessment of product samples provided by your company and may not reflect the characteristics of other samples, especially those produced at different times. Therefore this report and its findings and recommendations, if implemented, should not be construed as an assurance or implied warranty for the continuing electromagnetic compatibility (EMC) of the product. **BEC shall not be liable for incidental or consequential damages, even if advised of the possibility thereof.**

BEC will not disseminate this report to other parties without your express permission. You may reproduce this report in its entirety including this notice and the entireties of any supplemental test reports on the same product (e.g. reports on additional testing following modification). However 'you may not reproduce portions of the report (except for the entirety of the summary section) or quote from it for any purpose without specific prior written permission from BEC'.

Revision History

Revision #	Description of Changes	Date of Changes	Date Released
0	Test Report Initial Release	N/A	11/26/2018
1	Re-calculation of RF Exposure Exclusion using KDB447498 D01	12/05/2018	12/05/2018



1.0 Administrative Information

1.1 General Information Table

Project Number	BEC-1908
Manufacturer	Woodstream Corporation
Chassis Model Numbers	Connected Control Rodent Traps V450 (Small) and V460 (Large)
Chassis Model Serial Numbers	None
LoRa Radio Module Model Number	V400M
LoRa Radio Module Type	Modified with SMA connector on transmitter output port
LoRa Radio Module Serial #s	None
LoRa Radio Module Sample Numbers	1908-06
FCC ID	SNA-V400M
Radio Chip Manufacturer	Semtech Corporation
Radio Chip Model Number	SX1272
Frequency of Operation	902 – 915 MHz
FCC Classification	DTS
Date Samples Received	10/18/2018
Condition Samples Received	Suitable for test
Sample Type	Production unit
EUT Description	Connected Control Rodent Traps with LoRa Radio Communication
Applicable FCC Rules	47 CFR Part 2.1093, KDB 447498 D01



2.0 SAR Test Exclusion Parameters and Justification

From KDB 447498 D01:

4.3. General SAR test exclusion guidance

4.3.1. Standalone SAR test exclusion considerations

The Maximum Antenna Power used for the RF Exposure Threshold calculation is the highest measured output power shown in the following table. The table comes from the FCC Part 15C test report for this product.

Channel	LoRa Modulation Spread Factor	Frequency (MHz)	Measured Level (dBm)(Avg)	Cable # 814 Loss (dB)	Total		Limit		Margin	
					dBm	Watts	dBm	Watts	dBm	Watts
0	7	903.0	21.65	0.33	21.98	0.158	30.00	1.000	-8.02	-0.842
4		909.4	21.65	0.34	21.99	0.158	30.00	1.000	-8.01	-0.842
7		914.2	21.46	0.35	21.81	0.152	30.00	1.000	-8.19	-0.848
0	12	903.0	24.73	0.33	25.06	0.321	30.00	1.000	-4.94	-0.679
4		909.4	24.34	0.34	24.68	0.294	30.00	1.000	-5.32	-0.706
7		914.2	24.27	0.35	24.62	0.290	30.00	1.000	-5.38	-0.710

The separation distance used in the calculation is 20 centimeters. This distance is derived from the usage of the product. The rodent trap would normally be placed on the floor of a dwelling where rodents travel. People will not dwell within 20 cm of the device except to perform maintenance. The device would be powered off during maintenance because of shocking hazard.



3.0 SAR Test Exclusion Calculation

The table in Appendix B, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≥ 50 mm does not include the frequency or separation distance. Therefore, the following calculation, from paragraph 4.3.1 (b), was used to determine the SAR Test Exclusion Threshold:

$$\{[\text{Power allowed at numeric threshold for } 50 \text{ mm in step a})] + [(\text{test separation distance} - 50 \text{ mm}) \times (f(\text{MHz}) / 150)]\} \text{ mW}$$

Channel	LoRa Modulation Spread Factor	1 g SAR numeric threshold	Separation Distance (mm)	Frequency (MHz)	SAR Test Exclusion Threshold (mW)	EUT Power Output (mW)	Margin (mW)	
		(mw)						
0	7	3	200	903.0	906.0	157.8	-748.2	
4				909.4	912.4	158.1	-754.3	
7				914.2	917.2	151.7	-765.5	
0		12		903.0	906.0	320.6	-585.4	
4				909.4	912.4	293.8	-618.6	
7				914.2	917.2	289.7	-627.5	

Channel	LoRa Modulation Spread Factor	10 g SAR numeric threshold	Separation Distance (mm)	Frequency (MHz)	SAR Test Exclusion Threshold (mW)	EUT Power Output (mW)	Margin (mW)	
		(mw)						
0	7	8	200	903.0	911.0	157.8	-753.2	
4				909.4	917.4	158.1	-759.3	
7				914.2	922.2	151.7	-770.5	
0		12		903.0	911.0	320.6	-590.4	
4				909.4	917.4	293.8	-623.6	
7				914.2	922.2	289.7	-632.5	

Results: The Woodstream Model V400M, using DTS transmission, complies with SAR Test Exclusion Thresholds shown in the tables. Therefore, SAR evaluation is not required.