

6. Safety Human exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT:**Passed**

Test standard : FCC KDB Publication 447498 D01 v06
FCC CFR 47 Part 2 Subpart J Section 2.1091
ISED RSS-102 issue 5, 2.5.2

Separation distance is more than 20 cm, thus mobile device exposure limits can be applied.

FCC Maximum Exposure:

Mode	Frequency (MHz)	Antenna Gain (dBi)	Antenna Gain (numeric)	Maximum Output Power (dBm)	Output Power (mW)	Power Density (S)(mW/cm ²)	Test Result
Thread	2480	3.02	2.0045	8.09	6.4417	0.002570	Pass

Limit FCC: 1500-100,000 MHz 1.0 mW/cm²

ISED:**Exemption Limits for Routine Evaluation – RF Exposure Evaluation**

At or above 300MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W, where f is in MHz;

f= 2480MHz

$1.31 \times 10^{-2} \times 2480^{0.6834} = 2.74W$

After evaluation the 2480MHz e.i.r.p 11.11dBm calculated result is closer to its limit.

11.11dBm = 0.01291W, it is well below the limit of Exemption Limits for Routine Evaluation, so RF exposure assessment meets its standards.