

FCC RF Exposure Exemption report
for

Eve Energy Outlet

Model No.: 20ECN4101 B

FCC ID: SNE-DOUS-002

of

Applicant: Eve Systems LLC

Address: 100 Pine St., Suite 1250, San Francisco CA 94111 USA

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634



Report No.: W6M22504-24369-EE

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wts@wts-lab.com



TABLE OF CONTENTS

1	GENERAL INFORMATION	2
1.1	NOTES	2
1.2	TESTING LABORATORY	3
1.3	APPLICATION DETAILS	3
1.4	GENERAL INFORMATION OF TEST ITEM	4
1.5	DUTY CYCLE AND FACTOR	5
1.6	TEST STANDARDS	8
2	TEST CONFIGURATION	9
2.1	TEST ENVIRONMENT	9
2.2	MEASUREMENT UNCERTAINTY	9
2.3	TEST EQUIPMENT LIST	9
3	EQUIVALENT ISOTROPIC RADIATED POWER (EIRP).....	10
3.1	EXEMPTION LIMITS FOR ROUTINE EVALUATION	10



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22504-24369-EE

FCC ID: SNE-DOUS-002

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

Laboratory disclaimer-

1. The test results of this test report relate exclusively to the item tested as specified in 1.5.
2. The test report may only be reproduced or published in full.
3. Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.
4. Antenna gain is provided by applicant and laboratory issue relevant data and results.

Tester:

May 29, 2025

Ken Kang

Date

WTS-Lab.

Name

Signature

Technical responsibility for area of testing:

May 29, 2025

Kevin Wang

Date

WTS

Name

Signature



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22504-24369-EE

FCC ID: SNE-DOUS-002

1.2 Testing laboratory

1.2.1 Location

10m OATS

No.5-1, Lishui, Shuang Sing Village, Wanli Dist.,
New Taipei City 207, Taiwan (R.O.C.)

3 meter semi-anechoic chamber/Conducted Emission

No. 99, Sec. 1, Balian Rd., Xizhi Dist.,
New Taipei City 221032, Taiwan (R.O.C.)

Worldwide Testing Services (Taiwan) Co., Ltd.

6F., No. 58, Ln. 188, Ruiguang Rd., Neihu Dist.,

Taipei City 114, Taiwan (R.O.C.)

Tel: 886-2-6606-8877

1.2.2 Details of accreditation status

Accredited testing laboratory

FCC filed test laboratory Reg. No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634

Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :

Name: ./.

Accredited no.: ./.

Street: ./.

Town: ./.

Country: ./.

1.3 Application details

Approval holder

Name: Eve Systems LLC

Street: 100 Pine St., Suite 1250, San Francisco

Town: CA 94111

Country: USA

Manufacturer: (if applicable)

Name: Dexatek Technology Ltd.

Street: 16F., No.81, Sec. 1, Xintai 5th Rd., Xizhi Dist.,

Town: New Taipei City 221,

Country: Taiwan (R.O.C.)



Registration number: W6M22504-24369-EE

FCC ID: SNE-DOUS-002

Date of receipt of test item^(1st):

May 08, 2025

Date of test^(1st):

from May 09, 2025 to May 16, 2025

1.4 General information of Test item

Type of test item: Eve Energy Outlet

Model no.: 20ECN4101 B

Multi-listing model no.: ./.

Brand name: Eve

Power supply: 100-110V a.c./60Hz, 15A

Type of antenna: PIFA antenna

Antenna gain: 0.31 dBi

Technical data

Mode	Channel	Conducted Power (dBm)
BLE 1M	Ch 0 : 2402 MHz	4.54
	Ch 19 : 2440 MHz	4.42
	Ch 39 : 2480 MHz	3.83

Mode	Channel	Conducted Power (dBm)
BLE 2M	Ch 0 : 2402 MHz	4.61
	Ch 19 : 2440 MHz	4.45
	Ch 39 : 2480 MHz	3.87

Mode	Channel	Conducted Power (dBm)
THREAD	Ch 11 : 2405 MHz	7.28
	Ch 18 : 2440 MHz	7.09
	Ch 26 : 2480 MHz	6.64

Operation modes: Duplex

Modulation type: GFSK

Sample no.: #01

Special statement: ./.

Classification:

Fixed Device	☐
Mobile Device (Human Body distance > 20cm)	☒
Portable Device (Human Body distance < 20cm)	☐



Registration number: W6M22504-24369-EE

FCC ID: SNE-DOUS-002


1.5 Duty cycle and factor

BLE

Mode	T _{on} (ms)	T _{on} +T _{off} (ms)	Duty cycle (%)	1/T - VBW (kHz)
BLE 1M	0.40465	0.62901	64.33%	2.47
BLE 2M	0.22436	0.63301	35.44%	4.46

THREAD

Mode	T _{on} (ms)	T _{on} +T _{off} (ms)	Duty cycle (%)	1/T - VBW (kHz)
THREAD	0.865384615	1.013622	85.38%	1.16




Registration number: W6M22504-24369-EE

FCC ID: SNE-DOUS-002

Duty cycle plot


BLE

1M




DUTY T BLE 1M

Date: 8.MAY.2025 10:05:43



DUTY TON BLE 1M


Date: 8.MAY.2025 10:05:28



Registration number: W6M22504-24369-EE


FCC ID: SNE-DOUS-002

2M




DUTY T BLE 2M

Date: 8.MAY.2025 10:04:42



DUTY TON BLE 2M


Date: 8.MAY.2025 10:04:59



Registration number: W6M22504-24369-EE


FCC ID: SNE-DOUS-002

THREAD



DUTY T THREAD

Date: 8.MAY.2025 10:37:46



DUTY TON THREAD

Date: 8.MAY.2025 10:37:30

1.7 Test standards

FCC KDB Publication

447498 D01 General RF Exposure Guidance v06



Registration number: W6M22504-24369-EE

FCC ID: SNE-DOUS-002

2 Test configuration

2.1 Test environment

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Extreme conditions parameters: ./.

2.2 Measurement uncertainty

Test item Name	Uncertainty
Estimation Result of Uncertainty of Conducted Output Power Measurement (Peak Output Power (transmitter))	Expanded Uncertainty : 1.63 dB

The decision rule is: Measurement uncertainty is not included in the calculation of test results.

2.3 Test Equipment List

Max Output Power

No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2025/2/14	2026/2/13
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2025/3/5	2026/3/4
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2025/2/14	2026/2/13
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S_Cable 9)	279067	HUBER+SUHNER	2025/2/14	2026/2/13



Registration number: W6M22504-24369-EE

FCC ID: SNE-DOUS-002

3 Equivalent Isotropic Radiated Power (EIRP)

3.1 Exemption Limits for Routine Evaluation

according to 47 CFR FCC Part 2 Subpart J, section 2.1091

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20 cm normally can be maintained between the user and the device.

MPE Calculation Method

(A) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6

(B) Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz

*Plane-wave equivalent power density



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22504-24369-EE

FCC ID: SNE-DOUS-002

E = Electric field (V/m) P = output power (W) G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{3770 \times d^2}$$

mW/cm².

Established separation distance is 20 cm.

BLE

Operating frequency band: 2402-2480 MHz

THREAD

Operating frequency band: 2405-2480 MHz

Mode	Channel/Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Power density (mW/cm ²)	Limit (mW/cm ²)
BLE 1M	Ch 0 : 2402 MHz	4.54	0.31	0.0006	1
	Ch 19 : 2440 MHz	4.42	0.31	--	--
	Ch 39 : 2480 MHz	3.83	0.31	--	--
BLE 2M	Ch 0 : 2402 MHz	4.61	0.31	0.0006	1
	Ch 19 : 2440 MHz	4.45	0.31	--	--
	Ch 39 : 2480 MHz	3.87	0.31	--	--

Mode	Channel/Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Power density (mW/cm ²)	Limit (mW/cm ²)
THREAD	Ch 11 : 2405 MHz	7.28	0.31	0.0011	1
	Ch 18 : 2440 MHz	7.09	0.31	--	--
	Ch 26 : 2480 MHz	6.64	0.31	--	--