Prüfbericht-Nr.: *Test report no.:*	CN222PVA (P15C-BLE) 001	**Auftrags-Nr.:** *Order no.:*	238524417	Seite 1 von 27 *Page 1 of 27*
Kunden-Referenz-Nr.: *Client reference no.:*	N/A	**Auftragsdatum:** *Order date:*	2022-01-12	
Auftraggeber: *Client:*	Eve Systems LLC 100 Pine St., Suite 1250, San Francisco CA 94111 USA			
Prüfgegenstand: *Test item:*	Eve Flare			
Bezeichnung / Typ-Nr.: *Identification / Type no.:*	20EBV9901			
Auftrags-Inhalt: *Order content:*	FCC Part 15C Test report (BLE)			
Prüfgrundlage: *Test specification:*	FCC 47CFR Part 15: Subpart C Section 15.247			
Wareneingangsdatum: *Date of sample receipt:*	2022-01-06			
Prüfmuster-Nr.: *Test sample no:*	A003195940-039 A003195940-019			
Prüfzeitraum: *Testing period:*	2022-01-18 - 2022-02-14			
Ort der Prüfung: *Place of testing:*	EMC/RF Taipei Testing Site			
Prüflaboratorium: *Testing laboratory:*	Taipei Testing Laboratories			
Prüfergebnis*: *Test result*:*	Pass			

überprüft von: *compiled by:*	Ryan Chen	**genehmigt von:** authorized by:	Brenda Chen
Datum: *Date:* 2022-02-23		**Ausstellungsdatum:** *Issue date:* 2022-02-23	
Stellung / *Position:*	Senior Project Manager	**Stellung** / *Position:*	Senior Project Manager

Sonstiges / *Other:*

Zustand des Prüfgegenstandes bei Anlieferung: Prüfmuster vollständig und unbeschädigt
Condition of the test item at delivery: *Test item complete and undamaged*

* Legende:	1 = sehr gut	2 = gut	3 = befriedigend	4 = ausreichend	5 = mangelhaft
	P(ass) = entspricht o.g. Prüfgrundlage(n)		F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
** Legend:*	*1 = very good*	*2 = good*	*3 = satisfactory*	*4 = sufficient*	*5 = poor*
	P(ass) = passed a.m. test specification(s)		*F(ail) = failed a.m. test specification(s)*	*N/A = not applicable*	*N/T = not tested*

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.
This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.
V05

TEST SUMMARY

Report Section	FCC Clause	Test Item	Result
5.1.1	15.247(b) & 15.203	Antenna Requirement	Pass
5.1.2	15.247(b)(3)	Peak Output Power	Pass
5.1.3	15.247(a)(2)	6 dB Bandwidth	Pass
5.1.3	2.1049	99% Occupied Bandwidth	Pass
5.1.4	15.247(e)	Power Spectral Density	Pass
5.1.5	15.247(d)	Conducted Spurious Emissions and Band Edges	Pass
5.1.6	15.247(d) & 15.205 & 15.209	Radiated Spurious Emissions and Band Edges	Pass
5.2.1	15.207	Mains Conducted Emission	Pass

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Contents

HISTORY OF THIS TEST REPORT **5**

1. GENERAL REMARKS **6**
1.1 COMPLEMENTARY MATERIALS **6**
1.2 DECISION RULE OF CONFORMITY **6**

2. TEST SITES **7**
2.1 TEST LABORATORY **7**
2.2 TEST FACILITY **7**
2.3 TRACEABILITY **8**
2.4 CALIBRATION **8**
2.5 MEASUREMENT UNCERTAINTY **8**

3. GENERAL PRODUCT INFORMATION **9**
3.1 PRODUCT FUNCTION AND INTENDED USE **9**
3.2 SYSTEM DETAILS AND RATINGS **9**
3.3 NOISE GENERATING AND NOISE SUPPRESSING PARTS **10**
3.4 SUBMITTED DOCUMENTS **10**

4. TEST SET-UP AND OPERATION MODES **11**
4.1 PRINCIPLE OF CONFIGURATION SELECTION **11**
4.2 CARRIER FREQUENCY AND CHANNEL **11**
4.3 TEST OPERATION AND TEST SOFTWARE **12**
4.4 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT **13**
4.5 TEST SETUP DIAGRAM **14**

5. TEST RESULTS **15**
5.1 TRANSMITTER REQUIREMENT & TEST SUITES **15**
5.1.1 Antenna Requirement *15*
5.1.2 Peak Output Power *16*
5.1.3 6 dB Bandwidth and 99% Occupied Bandwidth *18*
5.1.4 Power Spectral Density *19*
5.1.5 Conducted Spurious Emissions and Frequency Band Edges Measured in 100kHz Bandwidth *20*
5.1.6 Radiated Spurious Emissions and Band Edges *21*

5.2 MAINS EMISSION **26**
5.2.1 Mains Conducted Emission *26*

APPENDIX A - TEST RESULT OF CONDUCTED

APPENDIX B - TEST RESULT OF RADIATED EMISSIONS & MAINS CONDUCTED EMISSION

APPENDIX SP - PHOTOGRAPHS OF TEST SETUP

APPENDIX EP - PHOTOGRAPHS OF EUT

HISTORY OF THIS TEST REPORT

Report No.	Description	Date Issued
CN222PVA (P15C-BLE) 001	Original Release	2022-02-23

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:
Appendix A - Test Result of Conducted
Appendix B - Test Result of Radiated Emissions & Mains Conducted Emission
Appendix SP - Photographs of Test Setup
Appendix EP - Photographs of EUT

Applied Standard and Test Levels

Radio
FCC 47CFR Part 15: Subpart C Section 15.247 FCC 47CFR Part 2: Subpart J Section 2.1049 ANSI C63.10:2013 KDB 558074 D01 15.247 Meas Guidance v05r02

1.2 Decision Rule of Conformity

The decision rule of conformity of this test report is following the requirements of the requested standard in the quotation, and agreed among testing laboratory and manufacturer (applicant) to exclude the consideration of Measurement Uncertainty, unless it is required by the specific standard.

2. Test Sites

2.1 Test Laboratory

Taipei Testing Laboratories

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

2.2 Test Facility

Taipei Testing Laboratories

No.458-18, Sec. 2, Fenliao Rd., Linkou Dist.,
New Taipei City 244
Taiwan (R.O.C.)
FCC Registration No.: 226631
ISED Registration No.: 25563

2.3 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular basics using in house standards or comparisons.

2.5 Measurement Uncertainty

All measurement uncertainty values are shown with a coverage factor of k=2 to indicate a 95% level of confidence.

Emission Measurement Uncertainty

Parameter	Uncertainty
Radiated Emission (9 kHz ~ 30 MHz)	± 1.15 dB
Radiated Emission (30 MHz ~ 200 MHz)	± 1.32 dB
Radiated Emission (200 MHz ~ 1 GHz)	± 1.31 dB
Radiated Emission (1 GHz ~ 18 GHz)	± 1.53 dB
Radiated Emission (18 GHz ~ 40 GHz)	± 2.50 dB
Mains Conducted Emission	± 1.65 dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a Eve Flare. It contains a Bluetooth compatible module enabling the user to communicate data through a Wireless interface.
For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Basic Information of EUT

Item	EUT information
Kind of Equipment/Test Item	Eve Flare
Type Identification	20EBV9901
FCC ID	SNE-EFL-002

Technical Specification of EUT

Item	EUT information
Operating Frequency	2402 MHz ~ 2480 MHz
Channel Number	40
Data Rate	1Mbps, 2Mbps
Operation Voltage	5 Vdc
Modulation	GFSK
Maximum Output Power (mW)	4.23
Antenna Information	Refer to 5.1.1
Accessory Device	Refer to 4.4

3.3 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.4 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The test modes were adapted accordingly in reference to the instructions for use.
During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output expected by the customer and is going to be fixed on the firmware of the final end product.

Table for Parameters of Test Software Setting

Frequency (MHz)	Power Setting
2402	8
2440	8
2480	8

4.2 Carrier Frequency and Channel

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

4.3 Test Operation and Test Software

Setup for testing: Test samples are provided with an UART interface which makes it possible to control them through a test software installed on a notebook computer.
This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed as below.

Test Software	nRF_DTM.exe

The samples were used as follows:
A003195940-039
A003195940-019
Full test was applied on all test modes, but only worst case was shown.

EUT Configure Mode	Applicable To				Description
	Antenna Port Conducted Measurement	Radiated Spurious Emissions above 1 GHz	Radiated Spurious Emissions below 1 GHz	Mains Conducted Emission	
-	√	√	√	√	-

Note:
1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when position on **X-plane**.
2. "-" means no effect.

Antenna Port Conducted Measurement

☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Date Rate (Mbps)
-	2402 to 2480	2402, 2440, 2480	1
-	2402 to 2480	2402, 2440, 2480	2

Radiated Spurious Emissions (Above 1 GHz)

☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Date Rate (Mbps)
-	2402 to 2480	2402, 2440, 2480	1
-	2402 to 2480	2402, 2440, 2480	2

Radiated Spurious Emissions (Below 1 GHz)

☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Date Rate (Mbps)
-	2402 to 2480	2402	2

Mains Conducted Emission

☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Date Rate (Mbps)
-	2402 to 2480	2402	2

Test Condition

Test Item	Ambient Temperature	Relative Humidity	Tested by
Conducted Measurement	21.5 °C	65 %	Stanislas Charles
Radiated Spurious Emissions above 1 GHz	23.5-25.1 °C	55-60 %	Blake Wang
Radiated Spurious Emissions below 1 GHz	23.5-25.1 °C	55-60 %	Blake Wang
Mains Conducted Emission	20.1-20.9 °C	53-57 %	Hunter Wang

4.4 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

Accessory of EUT

No.	Product	Brand	Model	Description
A	Power Adapter	XinSPower	A122-0502000ID	I/P: 100-240 Vac, 50/60 Hz, 0.4 A O/P: 5 Vdc, 2 A Cable: 180cm non-shielded cable w/o core
-	Charging Station	eve	20EBV9901	--

Support Unit

Support Unit								
No	Description	Brand	Model	S/N	Shielded	Ferrite Core (Qty)	Length (cm)	Remark
B	UART	CP2102	N/A	N/A	NO	NO	30	--
1	Notebook	Lenovo	81BL	MP1DCD6Y	-	-	-	--

4.5 Test Setup Diagram

<Radiated Spurious Emissions mode>



<Mains Conducted Emission mode>



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

Requirement Use of approved antennas only

According to the manufacturer declaration, the EUT has an antenna with a directional gain of -0.5 dBi. The antenna is PCB antenna with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.
Refer to EUT photo for details.

5.1.2 Peak Output Power

Limit 1 watt (30 dBm)

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Power Meter	Anritsu	ML2495A	1901008	2021/3/24	2022/3/23	2022/1/18	2022/1/18
Power Sensor	Anritsu	MA2411B	1725269	2021/3/24	2022/3/23	2022/1/18	2022/1/18

Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.
Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

Test Result

Peak Output Power

<1Mbps>

Channel	Channel Frequency	Peak Output Power		Limit (dBm)
	(MHz)	(dBm)	(mW)	
Low Channel	2402	6.26	4.23	30
Middle Channel	2440	6.02	4.00	30
High Channel	2480	5.85	3.85	30

<2Mbps>

Channel	Channel Frequency	Peak Output Power		Limit (dBm)
	(MHz)	(dBm)	(mW)	
Low Channel	2402	6.25	4.22	30
Middle Channel	2440	6.01	3.99	30
High Channel	2480	5.85	3.85	30

Average Power

<1Mbps>

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2402	6.23	4.20
Middle Channel	2440	5.99	3.97
High Channel	2480	5.82	3.82

<2Mbps>

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2402	6.22	4.19
Middle Channel	2440	5.98	3.96
High Channel	2480	5.81	3.81

5.1.3 6 dB Bandwidth and 99% Occupied Bandwidth

Limit The minimum 6 dB bandwidth shall be at least 500 kHz.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV40	101512	2021/1/29	2022/1/28	2022/1/18	2022/1/18

Test Procedure

a. Set resolution bandwidth (RBW) = 100 kHz
b. Set the video bandwidth (VBW) ≥ 3 x RBW, Detector = Peak.
c. Trace mode = max hold.
d. Sweep = auto couple.
e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
f. For 99% occupied bandwidth measurement, the transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to PEAK. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean power of a given emission.

Test Results

Please refer to Appendix A.

5.1.4 Power Spectral Density

Limit

The power spectral density shall not be greater than 8 dBm in any 3 kHz band.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV40	101512	2021/1/29	2022/1/28	2022/1/18	2022/1/18

Test Procedure

a. Set analyzer center frequency to DTS channel center frequency.
b. Set the span to 1.5 times the DTS bandwidth.
c. Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
d. Set the VBW ≥ 3 × RBW.
e. Detector = peak.
f. Sweep time = auto couple.
g. Trace mode = max hold.
h. Allow trace to fully stabilize.
i. Use the peak marker function to determine the maximum amplitude level within the RBW.

Test Results

Please refer to Appendix A.

5.1.5 Conducted Spurious Emissions and Frequency Band Edges Measured in 100kHz Bandwidth

Limit

20dB (below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.)

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV40	101512	2021/1/29	2022/1/28	2022/1/18	2022/1/18

Test Procedure

Measurement procedure REF
1. Set the RBW = 100 kHz.
2. Set the VBW ≥ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

Measurement procedure OOBE
1. Set RBW = 100 kHz.
2. Set VBW ≥ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

Test Results

Please refer to Appendix A.

5.1.6 Radiated Spurious Emissions and Band Edges

Limit

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must comply with the radiated emission limits specified in §15.209(a).
Emissions radiated outside the restricted and authorized frequency bands must either comply with the radiated emission limits specified for the restricted bands or in §15.247(d).

Kind of Test Site 3m Semi-Anechoic Chamber

Test Setup

<Radiated Emissions below 30 MHz>



<Radiated Emissions 30 MHz to 1 GHz>



<Radiated Emissions above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Test Instruments

Test Period: 2022-02-03 ~ 2022-02-04

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Receiver	R&S	ESR7	102109	2021/03/16	2022/03/15
Signal Analyzer	R&S	FSV40	101508	2021/03/16	2022/03/15
Bilog Antenna	SCHWARZBECK	VULB-9168	00951	2021/02/18	2022/02/17
Horn Antenna	ETS-Lindgren	3117	00218929	2021/11/25	2022/11/24
Horn Antenna	SCHWARZBECK	BBHA 9170	00887	2021/04/08	2022/04/07
LF-AMP	Agilent	8447D	2944A10772	2021/02/18	2022/02/17
HF-AMP + AC source	EMCI	EMC051845SE	980633	2021/02/09	2022/02/08
HF-AMP + AC source	EMCI	EMC184045SE	980656	2022/1/20	2023/1/19
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104EA	800056/4EA	2021/03/17	2022/03/16
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104	804680/4	2021/03/17	2022/03/16
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104	MY37202/4	2021/03/17	2022/03/16
Microwave Cable	HUBER+SUHNER	SUCOFLEX 102EA	800898/2EA	2021/04/16	2022/04/15
Microwave Cable	HUBER+SUHNER	SUCOFLEX 102EA	800901/2EA	2021/04/16	2022/04/15
Microwave Cable	HUBER+SUHNER	SUCOFLEX 102EA	801027/2EA	2021/04/16	2022/04/15
Loop Antenna	SCHWARZBECK	FMZB1519B	00215	2021/12/08	2022/12/07

Test Procedures

For Radiated Emissions below 30 MHz

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. Parallel (OPEN), perpendicular (CLOSE), and ground-parallel (GROUND) orientations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated Emissions above 30 MHz

a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) or Peak detection (PK) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98 %) or 10 Hz (Duty cycle ≥ 98 %) for Average detection (AV) at frequency above 1 GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The Radiated Emissions testing was performed in the X(E1), Y(H) and Z(E2) axis orientation. The worst-case Axis orientation is recorded in this test report.

Test Results

Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

Please refer to Appendix B.

5.2 Mains Emission

5.2.1 Mains Conducted Emission

Limit

Mains Conducted Emission as defined in §15.207 must comply with the mains conducted emission limits.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
RF Cable	N/A	N/A	EMC-003	2021/3/16	2022/3/15
Two-Line V-Network	Rohde & Schwarz	ENV216	101938	2021/9/23	2022/9/22
EMI Test Receiver	R&S	ESCI	1816063	2021/11/15	2022/11/14

Test Procedures

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz – 30 MHz.

Test Results

Please refer to Appendix B.

Appendix A: Test Results of Conducted Test

Test Result of 6 dB Bandwidth

BLE_1M

Channel	Channel Frequency (MHz)	6 dB Bandwidth (kHz)	Limit (kHz)	Result
Low Channel	2402	710.29	> 500	Pass
Middle Channel	2440	716.28	> 500	Pass
High Channel	2480	713.29	> 500	Pass

Low Channel



Middle Channel



High Channel



BLE_2M

Channel	Channel Frequency (MHz)	6 dB Bandwidth (kHz)	Limit (kHz)	Result
Low Channel	2402	1128.87	> 500	Pass
Middle Channel	2440	1138.86	> 500	Pass
High Channel	2480	1128.87	> 500	Pass

Low Channel



Middle Channel



High Channel



Test Result of 99% Occupied Bandwidth

BLE_1M

Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Low Channel	2402	1.049
Middle Channel	2440	1.052
High Channel	2480	1.052

Low Channel



Middle Channel



High Channel



BLE_2M

Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Low Channel	2402	2.038
Middle Channel	2440	2.038
High Channel	2480	2.048

Low Channel



Middle Channel



High Channel



Test Result of Power Spectral Density

BLE_1M

Channel	Channel Frequency (MHz)	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low Channel	2402	-9.16	8	Pass
Middle Channel	2440	-9.43	8	Pass
High Channel	2480	-9.71	8	Pass

Low Channel



Middle Channel



High Channel



BLE_2M

Channel	Channel Frequency (MHz)	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low Channel	2402	-11.49	8	Pass
Middle Channel	2440	-11.80	8	Pass
High Channel	2480	-12.15	8	Pass

Low Channel



Middle Channel



High Channel



Test Result of Conducted Spurious Emissions, Tx Mode

BLE_1M

Low Channel	Middle Channel
	
High Channel	
	

BLE_2M

Low Channel



Middle Channel



High Channel



Test Result of Conducted Band Edge, Tx Mode

BLE_1M

Low Channel	High Channel
	

BLE_2M

Low Channel	High Channel
	

Appendix B: Test Results of Radiated Spurious Emissions & Mains

Conducted Emission Test

Band Edges, 2.31GHz ~ 2.9GHz

BLE_1M

Low Channel (Horizontal) Peak

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenlinu.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2340.86	52.81	14.77	38.04	74.00	-21.19	246	307	Peak	Horizontal
2 *	2402.00	94.57	56.33	38.24	74.00	20.57	246	307	Peak	Horizontal
3	2635.68	54.60	15.76	38.84	74.00	-19.40	246	307	Peak	Horizontal

Low Channel (Vertical) Peak

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenlinu.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2387.70	52.57	14.65	37.92	74.00	-21.43	116	306	Peak	Vertical
2 *	2401.80	99.99	62.05	37.94	74.00	25.99	116	306	Peak	Vertical
3	2849.85	53.63	14.71	38.92	74.00	-20.37	116	306	Peak	Vertical

BLE_1M

Low Channel (Horizontal) Average

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2373.78	39.57	1.42	38.15	54.00	-14.43	246	307	Average	Horizontal
2 *	2402.00	89.65	51.41	38.24	54.00	35.65	246	307	Average	Horizontal
3	2636.68	40.96	2.12	38.84	54.00	-13.04	246	307	Average	Horizontal

Low Channel (Vertical) Average

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2377.38	39.86	1.95	37.91	54.00	-14.14	116	306	Average	Vertical
2 *	2402.00	94.83	56.89	37.94	54.00	40.83	116	306	Average	Vertical
3	2842.77	41.11	2.20	38.91	54.00	-12.89	116	306	Average	Vertical

BLE_1M

High Channel (Horizontal) Peak

TUV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2374.07	52.48	14.33	38.15	74.00	-21.52	353	32	Peak	Horizontal
2 *	2480.00	93.24	55.02	38.22	74.00	19.24	353	32	Peak	Horizontal
3	2678.22	54.31	15.48	38.83	74.00	-19.69	353	32	Peak	Horizontal

High Channel (Vertical) Peak

TUV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2346.99	52.33	14.48	37.85	74.00	-21.67	119	303	Peak	Vertical
2 *	2480.00	99.87	61.55	38.32	74.00	25.87	119	303	Peak	Vertical
3	2483.99	55.49	17.15	38.34	74.00	-18.51	119	303	Peak	Vertical

BLE_1M

High Channel (Horizontal) Average

TUV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2371.83	39.51	1.37	38.14	54.00	-14.49	353	32	Average	Horizontal
2 *	2480.00	88.53	50.31	38.22	54.00	34.53	353	32	Average	Horizontal
3	2633.62	41.13	2.29	38.84	54.00	-12.87	353	32	Average	Horizontal

High Channel (Vertical) Average

TUV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2351.89	40.19	2.32	37.87	54.00	-13.81	119	303	Average	Vertical
2 *	2480.00	94.76	56.44	38.32	54.00	40.76	119	303	Average	Vertical
3	2483.58	41.50	3.16	38.34	54.00	-12.50	119	303	Average	Vertical

BLE_2M

Low Channel (Horizontal) Peak

TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao., Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2327.29	52.63	14.64	37.99	74.00	-21.37	106	40	Peak	Horizontal
2 *	2402.00	93.17	54.93	38.24	74.00	19.17	106	40	Peak	Horizontal
3	2848.02	54.01	15.30	38.71	74.00	-19.99	106	40	Peak	Horizontal

Low Channel (Vertical) Peak

TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao., Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2377.79	53.05	15.14	37.91	74.00	-20.95	112	305	Peak	Vertical
2 *	2402.00	99.96	62.02	37.94	74.00	25.96	112	305	Peak	Vertical
3	2843.95	53.81	14.90	38.91	74.00	-20.19	112	305	Peak	Vertical

BLE_2M

Low Channel (Horizontal) Average

TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao., Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2368.82	39.63	1.49	38.14	54.00	-14.37	106	40	Average	Horizontal
2 *	2402.00	76.66	38.42	38.24	54.00	22.66	106	40	Average	Horizontal
3	2634.85	41.04	2.20	38.84	54.00	-12.96	106	40	Average	Horizontal

Low Channel (Vertical) Average

TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao., Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2373.96	39.71	1.81	37.90	54.00	-14.29	112	305	Average	Vertical
2 *	2402.00	81.75	43.81	37.94	54.00	27.75	112	305	Average	Vertical
3	2831.09	41.08	2.19	38.89	54.00	-12.92	112	305	Average	Vertical

BLE_2M

High Channel (Horizontal) Peak

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2334.07	51.94	13.92	38.02	74.00	-22.06	349	32	Peak	Horizontal
2 *	2480.00	92.05	53.83	38.22	74.00	18.05	349	32	Peak	Horizontal
3	2671.49	53.80	14.95	38.85	74.00	-20.20	349	32	Peak	Horizontal

High Channel (Vertical) Peak

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2352.30	51.79	13.92	37.87	74.00	-22.21	258	314	Peak	Vertical
2 *	2480.00	98.26	59.94	38.32	74.00	24.26	258	314	Peak	Vertical
3	2636.92	53.57	15.00	38.57	74.00	-20.43	258	314	Peak	Vertical

BLE_2M

High Channel (Horizontal) Average

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2387.47	39.65	1.46	38.19	54.00	-14.35	349	32	Average	Horizontal
2 *	2480.00	75.86	37.64	38.22	54.00	21.86	349	32	Average	Horizontal
3	2637.21	41.06	2.22	38.84	54.00	-12.94	349	32	Average	Horizontal

High Channel (Vertical) Average

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2381.69	39.44	1.53	37.91	54.00	-14.56	258	314	Average	Vertical
2 *	2480.00	80.80	42.48	38.32	54.00	26.80	258	314	Average	Vertical
3	2483.46	41.72	3.38	38.34	54.00	-12.28	258	314	Average	Vertical

Spurious Emissions, Tx Mode, 9kHz ~ 30MHz

BLE_2M

Low Channel (Open) 9kHz~150kHz

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	0.01	56.90	39.19	17.71	127.57	-70.67	100	80	QP	Open
2	0.03	47.75	28.63	19.12	119.40	-71.65	100	195	QP	Open
3	0.05	43.72	24.42	19.30	113.52	-69.80	100	212	QP	Open
4	0.06	41.49	22.45	19.04	111.73	-70.24	100	60	QP	Open
5	0.07	40.39	21.55	18.84	110.51	-70.12	100	222	QP	Open
6	0.10	36.02	17.69	18.33	108.03	-72.01	100	222	QP	Open

Low Channel (Open) 150kHz~30MHz

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	0.15	45.37	26.97	18.40	104.08	-58.71	100	221	QP	Open
2	6.88	32.41	12.27	20.14	69.50	-37.09	100	27	QP	Open
3	15.04	34.64	12.79	21.85	69.50	-34.86	100	337	QP	Open
4	17.93	36.37	14.31	22.06	69.50	-33.13	100	11	QP	Open
5	24.89	35.48	13.06	22.42	69.50	-34.02	100	151	QP	Open
6	29.03	36.04	13.43	22.61	69.50	-33.46	100	84	QP	Open

BLE_2M

Low Channel (Close) 9kHz~150kHz

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	0.01	56.49	38.77	17.72	127.61	-71.12	100	236	QP	Close
2	0.02	48.39	29.41	18.98	119.93	-71.54	100	216	QP	Close
3	0.05	43.53	24.29	19.24	113.08	-69.55	100	222	QP	Close
4	0.06	41.31	22.27	19.04	111.73	-70.42	100	21	QP	Close
5	0.07	39.39	20.57	18.82	110.40	-71.01	100	208	QP	Close
6	0.10	35.50	17.27	18.23	107.63	-72.13	100	208	QP	Close

Low Channel (Close) 150kHz~30MHz

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	0.16	42.42	23.97	18.45	103.25	-60.83	100	241	QP	Close
2	5.63	31.91	12.29	19.62	69.50	-37.59	100	219	QP	Close
3	11.79	34.74	13.11	21.63	69.50	-34.76	100	311	QP	Close
4	18.20	35.01	12.94	22.07	69.50	-34.49	100	349	QP	Close
5	22.76	36.04	13.72	22.32	69.50	-33.46	100	330	QP	Close
6	26.09	36.21	13.74	22.47	69.50	-33.29	100	71	QP	Close

Spurious Emissions, Tx Mode, 30MHz ~ 1GHz

BLE_2M

Low Channel (Horizontal)

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	128.84	22.82	29.97	-7.15	43.50	-20.68	200	105	QP	Horizontal
2	283.07	24.28	29.32	-5.04	46.00	-21.72	100	137	QP	Horizontal
3	444.09	27.25	29.28	-2.03	46.00	-18.75	200	234	QP	Horizontal
4	686.88	30.79	29.19	1.60	46.00	-15.21	200	218	QP	Horizontal
5	844.90	35.62	31.52	4.10	46.00	-10.38	175	360	QP	Horizontal
6	958.78	34.48	28.83	5.65	46.00	-11.52	200	299	QP	Horizontal

Low Channel (Vertical)

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	49.79	23.95	29.80	-5.85	40.00	-16.05	200	52	QP	Vertical
2	156.00	22.45	28.16	-5.71	43.50	-21.05	100	49	QP	Vertical
3	273.96	23.59	29.04	-5.45	46.00	-22.41	100	204	QP	Vertical
4	384.73	26.41	29.47	-3.06	46.00	-19.59	200	63	QP	Vertical
5	624.61	29.39	28.74	0.65	46.00	-16.61	100	276	QP	Vertical
6	844.90	34.19	30.09	4.10	46.00	-11.81	169	360	QP	Vertical

Spurious Emissions, Tx Mode, 1GHz ~ 26.5GHz

BLE_1M

Low Channel (Horizontal)

TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao., Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1 !	4804.00	49.42	60.14	-10.72	54.00	-4.58	200	168	Average	Horizontal
2	4804.00	49.42	60.14	-10.72	74.00	-24.58	200	168	Peak	Horizontal

Low Channel (Vertical)

TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao., Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	4804.00	45.11	56.22	-11.11	74.00	-28.89	300	341	Peak	Vertical

BLE_1M

Middle Channel (Horizontal)

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1 !	4880.00	48.75	59.45	-10.70	54.00	-5.25	200	35	Average	Horizontal
2	4880.00	48.75	59.45	-10.70	74.00	-25.25	200	35	Peak	Horizontal
3	7320.00	47.17	56.31	-9.14	74.00	-26.83	200	147	Peak	Horizontal

Middle Channel (Vertical)

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	4880.00	45.38	56.44	-11.06	74.00	-28.62	200	350	Peak	Vertical
2	7320.00	47.36	56.62	-9.26	74.00	-26.64	200	223	Peak	Vertical

BLE_1M

High Channel (Horizontal)

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1 !	4960.00	49.72	60.31	-10.59	54.00	-4.28	200	358	Average	Horizontal
2	4960.00	49.72	60.31	-10.59	74.00	-24.28	200	358	Peak	Horizontal
3 !	7440.00	48.08	56.98	-8.90	54.00	-5.92	200	151	Average	Horizontal
4	7440.00	48.08	56.98	-8.90	74.00	-25.92	200	151	Peak	Horizontal

High Channel (Vertical)

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1 !	4960.00	49.80	60.77	-10.97	54.00	-4.20	200	97	Average	Vertical
2	4960.00	49.80	60.77	-10.97	74.00	-24.20	200	97	Peak	Vertical
3 !	7440.00	49.03	58.29	-9.26	54.00	-4.97	200	123	Average	Vertical
4	7440.00	49.03	58.29	-9.26	74.00	-24.97	200	123	Peak	Vertical

BLE_2M

Low Channel (Horizontal)

TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao., Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1 !	4804.00	48.38	59.10	-10.72	54.00	-5.62	200	170	Average	Horizontal
2	4804.00	48.38	59.10	-10.72	74.00	-25.62	200	170	Peak	Horizontal

Low Channel (Vertical)

TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao., Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	4804.00	42.55	53.66	-11.11	74.00	-31.45	200	212	Peak	Vertical

BLE_2M

Middle Channel (Horizontal)

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1 !	4880.00	48.46	59.16	-10.70	54.00	-5.54	200	168	Average	Horizontal
2	4880.00	48.46	59.16	-10.70	74.00	-25.54	200	168	Peak	Horizontal
3	7320.00	45.40	54.54	-9.14	74.00	-28.60	200	162	Peak	Horizontal

Middle Channel (Vertical)

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	4880.00	43.61	54.67	-11.06	74.00	-30.39	200	70	Peak	Vertical
2 !	7320.00	48.11	57.37	-9.26	54.00	-5.89	200	70	Average	Vertical
3	7320.00	48.11	57.37	-9.26	74.00	-25.89	200	70	Peak	Vertical

BLE_2M

High Channel (Horizontal)

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



		Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
		MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	!	4960.00	48.35	58.94	-10.59	54.00	-5.65	200	210	Average	Horizontal
2		4960.00	48.35	58.94	-10.59	74.00	-25.65	200	210	Peak	Horizontal
3		7440.00	44.95	53.85	-8.90	74.00	-29.05	200	134	Peak	Horizontal

High Channel (Vertical)

TÜV Rheinland Taiwan Ltd.
No. 458-18,Sec 2,Fenliao.,Linkou Dist.,New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



		Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase
		MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	!	4960.00	49.09	60.06	-10.97	54.00	-4.91	200	103	Average	Vertical
2		4960.00	49.09	60.06	-10.97	74.00	-24.91	200	103	Peak	Vertical
3		7440.00	47.86	57.12	-9.26	54.00	-6.14	200	129	Average	Vertical
4		7440.00	47.86	57.12	-9.26	74.00	-26.14	200	129	Peak	Vertical

Mains Conducted Emission, 150kHz ~ 30MHz

Worst Band

(Line)

TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao., Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



Trace: 1

	Freq	Level	Read Level	Factor	Limit Line	Over Limit	Remark	Pol/Phase	Note
	MHz	dBuV	dBuV	dB	dBuV	dB			
1	0.16	23.80	14.11	9.69	55.63	-31.83	Average	line1	
2	0.16	36.85	27.16	9.69	65.63	-28.78	QP	line1	
3	0.41	27.93	18.25	9.68	47.55	-19.62	Average	line1	
4	0.41	39.26	29.58	9.68	57.55	-18.29	QP	line1	
5	0.50	21.46	11.78	9.68	46.00	-24.54	Average	line1	
6	0.50	30.85	21.17	9.68	56.00	-25.15	QP	line1	
7	0.66	20.85	11.16	9.69	46.00	-25.15	Average	line1	
8	0.66	29.91	20.22	9.69	56.00	-26.09	QP	line1	
9	6.96	16.08	6.30	9.78	50.00	-33.92	Average	line1	
10	6.96	23.99	14.21	9.78	60.00	-36.01	QP	line1	
11	20.03	25.01	15.20	9.81	50.00	-24.99	Average	line1	
12	20.03	29.75	19.94	9.81	60.00	-30.25	QP	line1	

(Neutral)

TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao., Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



Trace: 1

	Freq	Level	Read Level	Factor	Limit Line	Over Limit	Remark	Pol/Phase	Note
	MHz	dBuV	dBuV	dB	dBuV	dB			
1	0.15	23.86	14.19	9.67	56.00	-32.14	Average	neutral	
2	0.15	35.84	26.17	9.67	66.00	-30.16	QP	neutral	
3	0.43	29.56	19.90	9.66	47.26	-17.70	Average	neutral	
4	0.43	39.78	30.12	9.66	57.26	-17.48	QP	neutral	
5	0.55	13.65	3.99	9.66	46.00	-32.35	Average	neutral	
6	0.55	23.31	13.65	9.66	56.00	-32.69	QP	neutral	
7	0.78	16.00	6.34	9.66	46.00	-30.00	Average	neutral	
8	0.78	26.34	16.68	9.66	56.00	-29.66	QP	neutral	
9	12.35	17.96	8.15	9.81	50.00	-32.04	Average	neutral	
10	12.35	25.13	15.32	9.81	60.00	-34.87	QP	neutral	
11	20.03	22.96	13.09	9.87	50.00	-27.04	Average	neutral	
12	20.03	28.05	18.18	9.87	60.00	-31.95	QP	neutral	