

FCC TEST REPORT (Part 24)

REPORT NO.: 060612FIA01

MODEL NO.: S198+

RECEIVED: Jun. 6, 2006

TESTED: Jun. 6, 2006

ISSUED: Jun. 6 ~ Jun. 13, 2006

APPLICANT: NINGBO BIRD CO., LTD

ADDRESS: No. 999 Dacheng East Road, Fenghua City, Zhejiang

ISSUED BY: ADT (Shanghai) Corporation

ADDRESS: 2F, Building C, No.1618, Yishan Rd., 201103,
Shanghai, China

This test report consists of 54 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by A2LA or any government agencies. The test results in the report only apply to the tested sample.

ADT (Shanghai) Corporation.



TABLE OF CONTENTS

| | | |
|-------|--|----|
| 1 | CERTIFICATION | 4 |
| 2 | SUMMARY OF TEST RESULTS | 5 |
| 2.1 | MEASUREMENT UNCERTAINTY | 6 |
| 3 | GENERAL INFORMATION..... | 7 |
| 3.1 | GENERAL DESCRIPTION OF EUT | 7 |
| 3.2 | DESCRIPTION OF TEST MODES | 8 |
| 3.3 | GENERAL DESCRIPTION OF APPLIED STANDARDS | 8 |
| 3.4 | DESCRIPTION OF SUPPORT UNITS | 9 |
| 4 | TEST TYPES AND RESULTS | 10 |
| 4.1 | MODULATION CHARACTERISTICS | 10 |
| 4.1.1 | DESCRIPTION OF MODULATION TECHNIQUE | 10 |
| 4.1.2 | THE ACTIVE TIME SLOT 8 MODULATED FRAME PLOT..... | 11 |
| 4.2 | OUTPUT POWER MEASUREMENT | 12 |
| 4.2.1 | LIMITS OF OUTPUT POWER MEASUREMENT | 12 |
| 4.2.2 | TEST INSTRUMENTS..... | 13 |
| 4.2.3 | TEST PROCEDURES | 14 |
| 4.2.4 | TEST SETUP..... | 15 |
| 4.2.5 | EUT OPERATING CONDITIONS | 16 |
| 4.2.6 | TEST RESULTS | 17 |
| 4.3 | FREQUENCY STABILITY MEASUREMENT..... | 19 |
| 4.3.1 | LIMITS OF FREQUENCY STABILITY MEASUREMENT | 19 |
| 4.3.2 | TEST INSTRUMENTS..... | 19 |
| 4.3.3 | TEST PROCEDURE..... | 20 |
| 4.3.4 | TEST SETUP..... | 21 |
| 4.3.5 | TEST RESULTS | 22 |
| 4.4 | OCCUPIED BANDWIDTH MEASUREMENT | 24 |
| 4.4.1 | LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT | 24 |
| 4.4.2 | TEST INSTRUMENTS..... | 24 |
| 4.4.3 | TEST SETUP..... | 24 |
| 4.4.4 | TEST PROCEDURES | 25 |
| 4.4.5 | EUT OPERATING CONDITION | 25 |
| 4.4.6 | TEST RESULTS | 25 |
| 4.5 | BAND EDGE MEASUREMENT..... | 28 |
| 4.5.1 | LIMITS OF BAND EDGE MEASUREMENT | 28 |
| 4.5.2 | TEST INSTRUMENTS..... | 28 |
| 4.5.3 | TEST SETUP..... | 28 |
| 4.5.4 | TEST PROCEDURES | 29 |
| 4.5.5 | EUT OPERATING CONDITION | 29 |
| 4.5.6 | TEST RESULTS | 30 |

| | | |
|-------|--|----|
| 4.6 | CONDUCTED SPURIOUS EMISSIONS | 31 |
| 4.6.1 | LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT | 31 |
| 4.6.2 | TEST INSTRUMENTS..... | 31 |
| 4.6.3 | TEST PROCEDURE..... | 32 |
| 4.6.4 | TEST SETUP..... | 32 |
| 4.6.5 | EUT OPERATING CONDITIONS | 32 |
| 4.6.6 | TEST RESULTS | 33 |
| 4.7 | RADIATED EMISSION MEASUREMENT (BELOW 1GHZ) | 41 |
| 4.7.1 | LIMITS OF RADIATED EMISSION MEASUREMENT..... | 41 |
| 4.7.2 | TEST INSTRUMENTS..... | 42 |
| 4.7.3 | TEST PROCEDURES | 43 |
| 4.7.4 | DEVIATION FROM TEST STANDARD | 43 |
| 4.7.5 | TEST SETUP..... | 44 |
| 4.7.6 | EUT OPERATING CONDITIONS | 44 |
| 4.7.7 | TEST RESULTS | 45 |
| 4.8 | EFFECTIVE RADIATED POWER MEASUREMENT (ABOVE 1 GHZ) | 47 |
| 4.8.1 | LIMITS OF RADIATED EMISSION MEASUREMENT..... | 47 |
| 4.8.2 | TEST INSTRUMENTS..... | 48 |
| 4.8.3 | TEST PROCEDURES | 49 |
| 4.8.4 | DEVIATION FROM TEST STANDARD | 49 |
| 4.8.5 | TEST SETUP..... | 50 |
| 4.8.6 | EUT OPERATING CONDITIONS | 50 |
| 4.8.7 | TEST RESULTS | 51 |
| 5 | INFORMATION ON THE TESTING LABORATORIES | 54 |



1 CERTIFICATION

PRODUCT : Dual Band GSM Mobile Phone

MODEL NO. : S198+

BRAND NAME: bird

APPLICANT : Jun. 6 ~ Jun. 13, 2006

TESTED : ENGINEERING SAMPLE

TEST SAMPLE : ENGINEERING SAMPLE

TEST STANDARDS : FCC Part 24, Subpart E

ANSI C63.4-2003

The above equipment has been tested by **ADT (Shanghai) Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

TECHNICAL

ACCEPTANCE : _____, **DATE:** JUN. 14, 2006
Steven Qian
Engineering Supervisor

APPROVED BY : _____, **DATE:** JUN. 14, 2006
Wallace Pan
Director of Operations

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC Part 24 & Part 2 / IC RSS-133 | | | |
|---|--|--------|---|
| STANDARD SECTION | TEST TYPE AND LIMIT | RESULT | REMARK |
| 2.1047(d) | Modulation Characteristics | PASS | N/A |
| 2.1046 24.232 | Maximum Peak Output Power Limit: max. 2 watts e.r.p peak power | PASS | Meet the requirement of limit. |
| 2.1055 24.235 | Frequency Stability AFC Freq. Error vs. Voltage AFC Freq. Error vs. Temperature Limit: max. ± 2.5 ppm | PASS | Meet the requirement of limit. |
| 2.1049 24.238(b) | Occupied Bandwidth | PASS | Meet the requirement of limit. |
| 24.238(b) | Band Edge Measurements | PASS | N/A |
| 2.1051 24.238 | Conducted Spurious Emissions | PASS | Meet the requirement of limit. Minimum passing margin is -31.00 dB at 15160.00MHz. |
| 2.1053 24.238 | Radiated Spurious Emissions | PASS | Meet the requirement of limit. Minimum passing margin is -3.56 dB at 19098.00MHz. |

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

| MEASUREMENT | FREQUENCY | UNCERTAINTY |
|---------------------|-----------------|-------------|
| Conducted emissions | 9kHz ~ 30MHz | 2.44 dB |
| Radiated emissions | 30MHz ~ 200MHz | 3.55 dB |
| | 200MHz ~1000MHz | 3.58 dB |
| | 1GHz ~ 18GHz | 1.10 dB |
| | 18GHz ~ 40GHz | 0.91 dB |

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

| | |
|--|--|
| PRODUCT | Dual Band GSM Mobile Phone |
| MODEL NO. | S198+ |
| POWER SUPPLY | 3.7Vdc from rechargeable lithium battery Brand: Bird Model: BD-LA 5Vdc from power adapter Brand: Bird Model: MU03-M050045-A1 I/P: 100-240Vac, 0.15A, 50/60Hz O/P: 5.0Vdc, 450mA |
| MODULATION TYPE | GMSK, QPSK for GSM |
| FREQUENCY RANGE | Tx Frequency: 1850 MHz ~ 1910 MHz (PCS band) Rx Frequency: 1930 MHz ~ 1990 MHz (PCS band) |
| NUMBER OF CHANNEL | 299 |
| MAX. CONDUCTED PEAK OUTPUT POWER | GSM Mode: 29.11dBm (0.815Watts) |
| MAX. EIRP RADITED ERP PEAK OUTPUT POWER | GSM Mode: 26.41dBm (0.438Watts) |
| E AND I OF THE FINAL OUTPUT STAGE | E: 3.7Vdc I: 0.09A |
| ANTENNA TYPE | Fixed external antenna with 0dBi gain |
| DATA CABLE | 1.26m non-shielded cable for earphone |
| I/O PORTS | Refer to user's manual |
| ASSOCIATED DEVICES | Earphone, cradle |
| EUT EXTREME VOL. RANGE | 3.3Vdc to 4.2Vdc |

NOTE:

1. The EUT is a Dual Band GSM Mobile Phone. The protocol of this system is GSM850, and PCS1900.
2. IMEI Code: 010974000000145
3. Hardware version: V1.2
4. Software version: V1.00.50-1060508CN0
5. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

299 channels are provided to this EUT in the PCS1900 band. Therefore, the low, middle and high channels are chosen for testing.

| | CHANNEL | FREQUENCY | TX MODE |
|--------|---------|------------|---------|
| LOW | 512 | 1850.2 MHz | GSM |
| MIDDLE | 661 | 1880.0 MHz | GSM, |
| HIGH | 810 | 1909.8 MHz | GSM |

NOTE:

1. Below 1 GHz, the channel 512, 661, and 810 were pre-tested in chamber. The channel 512 was chosen for final test.
2. Above 1 GHz, the channel 512, 661, and 810 were tested individually.
3. When the Power Control Level set 0, the worst case, was chosen for final test.
4. The channel space is 0.2MHz.
5. Since the EUT is considered a portable unit, it was pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.
6. For the radiated emission measurement test below 1GHz, there are two test modes. Mode A is powered by battery, and mode B is charged by power adapter

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a Dual Band GSM Mobile Phone. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 24

IC RSS-133

ANSI C63.4-2003

NOTE: All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| NO. | PRODUCT | BRAND | MODEL NO. | SERIAL NO. | CAL. DATE |
|-----|--------------------------------------|-------|-----------|------------|---------------|
| 1 | Universal Radio Communication Tester | R&S | CMU200 | 109373 | Nov. 20, 2006 |

| NO. | SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS |
|-----|---|
| A | N/A |

NOTE: All power cords of the above support units are non shielded (1.8m).

4 TEST TYPES AND RESULTS

4.1 MODULATION CHARACTERISTICS



4.1.1 DESCRIPTION OF MODULATION TECHNIQUE

According to FCC 2.1047(d), the system is used the digital modulation and accomplished with the PCS requirement as defined in the 3GGP TS 05:01, TS 05:02, TS 05:04. It uses narrowband TDMA. Eight simultaneous calls can occupy the same radio frequency.

There are 299 channels and channel space is 200kHz. The frequency band 1850 ~ 1910MHz is allocated to the uplink and 1930 ~ 1990MHz to the downlink. The uplink and downlink channel space is 80MHz and is duplex at the same time.

The modulation scheme used the GMSK (Gaussian Minimum Shift Keying) that is the special case of FSK (frequency Shift Keying). The each time slot is last about 580 μ s and data length is 156.25bits. A frame contains the eight time slots.

4.1.2 THE ACTIVE TIME SLOT 8 MODULATED FRAME PLOT FOR GSM MODE (UP-LINK WITH 1 TIME SLOT)



4.2 OUTPUT POWER MEASUREMENT

4.2.1 LIMITS OF OUTPUT POWER MEASUREMENT

The radiated peak output power shall be according to the specific rule Part 24.232(b) that “Mobile / Portable station are limited to 2 watts e.i.r.p” and 24.232(c) specific that “Peak transmit power must be measure over any interval of continuous transmission using instrumentation calibration in terms of rms-equivalent voltage.”

4.2.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED UNTIL |
|--|-------------------|------------|------------------|
| Test Receiver ROHDE & SCHWARZ | ESCS30 | E1R1001 | Apr. 19, 2007 |
| BILOG Antenna SCHWARZBECK | VULB9168 | E1A1001 | Sep. 26, 2006 |
| Preamplifier Agilent | 8447D | E1A2001 | Jan. 27, 2007 |
| Preamplifier Agilent | 8449B | E1A2002 | Jan. 27, 2007 |
| Double Ridged Broadband Horn Antenna Schwarzbeck | BBHA 9120D | E1A1002 | Feb.15, 2007 |
| *Spectrum Analyzer Agilent | E4403B | E1S1001 | Jan. 13, 2007 |
| *Spectrum Analyzer ROHDE & SCHWARZ | FSP30 | E1S1002 | May.15, 2007 |
| RF signal cable Woken | RG-402 | E1CBH01 | May. 30, 2007 |
| RF signal cable Woken | RG-402 | E1CBH02 | May. 30, 2007 |
| RF signal cable Woken | RG-402 | E1CBH03 | May. 30, 2007 |
| RF signal cable Woken | RG-412 | E1CBL02 | May. 30, 2007 |
| RF signal cable Woken | RG-412 | E1CBL03 | May. 30, 2007 |
| RF signal cable Woken | RG-412 | E1CBL04 | May. 30, 2007 |
| Software ADT | ADT_Radiated_V7.5 | N/A | N/A |
| * Power Splitter Mini-Circuits | ZAPD-4 | 400005 | NA |

NOTE:

1. The calibration interval of the above test instruments is 12 months.
2. “*” = These equipment are used for the final measurement.
3. The horn antenna and Agilent preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The Spectrum Analyzer (model: FSP30) and RF signal cable (SERIAL: E1CBH05&E1CBH07) are used only for the measurement of emission frequency above 1GHz if tested.


4.2.3 TEST PROCEDURES

- a. The EUT was set up for the maximum peak power with GSM link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels, 512, 661 and 810(low, middle and high operational frequency range.)
- b. The conducted peak output power used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer. The path loss included the splitter loss, cable loss and 20dB pad loss. The spectrum set RB/VB 3MHz, then read peak power value and record to the test. (All transmitted path loss shall be considered in the test report data.)
- c. E.I.R.P peak power measurement. In the fully anechoic chamber, EUT placed on the 1.5m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- d. The substitution horn antenna is substituted for EUT at the same position and signal generator export the CW signal to the calibration antenna. Rotated the Turn Table to find the maximum radiation power. “Raw” is the spectrum reading value, “SG” is signal generator export power, “TX Gain” is calibration antenna isotropic gain value, “TX cable” is the transmitted cable loss between the calibration antenna and signal generator. The “Factor” means that the transmission path loss is equal to “SG” - “TX cable” + “TX Gain” – “Raw”.
- e. Actually the real E.I.R.P peak power is equal to “Read Value” + “Factor”
- f. E.R.P power can be calculated from E.I.R.P power by subtracting the gain of dipole, E.R.P power= E.I.R.P power-2.15dBi.

NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection (PK)


4.2.4 TEST SETUP

EIRP POWER MEASUREMENT:



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.5 EUT OPERATING CONDITIONS

- a. The EUT makes a phone call to the GSM simulator.
- b. The GSM simulator station system controlled an EUT to export maximum output power under transmission mode and specific channel frequency.

4.2.6 TEST RESULTS

| | | | |
|---------------------------------|----------------------------|----------------------------|--------|
| EUT | Dual Band GSM Mobile Phone | MODEL | S198+ |
| MODE | TX connected | POWER CONTROL LEVEL | 0 |
| INPUT POWER (SYSTEM) | 120Vac, 60Hz | DETECTOR FUNCTION | Peak |
| ENVIRONMENTAL CONDITIONS | 27deg. C, 60%RH, 991hPa | TESTED BY | Bright |

FOR GSM MODE (UP-LINK WITH 1 TIME SLOT)

| CONDUCTED PEAK OUTPUT POWER | | | | | |
|-----------------------------|------------------------|------------------------|-------------------------------|--------------------------|-------------|
| CHANNEL NO. | FREQUENCY (MHz) | RAW VALUE (dBm) | CORRECTION FACTOR (dB) | PEAK OUTPUT POWER | |
| | | | | dBm | Watt |
| 512 | 1850.2 | 25.71 | 3.40 | 29.11 | 0.815 |
| 661 | 1880.0 | 24.54 | 3.40 | 27.94 | 0.622 |
| 810 | 1909.8 | 23.59 | 3.40 | 26.99 | 0.500 |

REMARKS: 1. Peak Output Power (dBm) = Raw Value (dBm) + Correction Factor (dB).

2. Correction Factor (dB) = Power Splitter Loss (dB) + Cable Loss (dB).

| | | | |
|---------------------------------|----------------------------|----------------------------|--------|
| EUT | Dual Band GSM Mobile Phone | MODEL | S198+ |
| MODE | TX connected | POWER CONTROL LEVEL | 0 |
| INPUT POWER (SYSTEM) | 120Vac, 60Hz | DETECTOR FUNCTION | Peak |
| ENVIRONMENTAL CONDITIONS | 27deg. C, 60%RH, 991hPa | TESTED BY | Bright |

FOR GSM MODE (UP-LINK WITH 1 TIME SLOT)

| RADIATED PEAK OUTPUT POWER | | | | | |
|----------------------------|-----------------|-----------------|------------------------|-------------------|-------|
| CHANNEL NO. | FREQUENCY (MHz) | RAW VALUE (dBm) | CORRECTION FACTOR (dB) | PEAK OUTPUT POWER | |
| | | | | dBm | Watt |
| 512 | 1850.2 | -12.23 | 38.64 | 26.41 | 0.438 |
| 661 | 1880.0 | -12.65 | 38.97 | 26.32 | 0.429 |
| 810 | 1909.8 | -14.11 | 40.23 | 26.12 | 0.409 |

REMARKS: 1. Peak Output Power (dBm) = Raw Value (dBm) + Correction Factor (dB).

2. Correction Factor (dB) = Receiver Antenna Factor (dBi) + Cable Loss (dB) + Free Space Loss (dB).

4.3 FREQUENCY STABILITY MEASUREMENT

4.3.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

According to the FCC part 2.4235 shall be tested the frequency stability. The rule is defined that "The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block." The frequency error rate is according to the JTC standard that the frequency error rate shall be accurate to within 2.5ppm of the received frequency from the base station. The test extreme voltage is according to the 2.1055(d)(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment and the extreme temperature rule is comply with the 2.1055(a)(1) $-30^{\circ}\text{C} \sim 50^{\circ}\text{C}$.

4.3.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED UNTIL |
|--------------------------------------|-----------|------------|------------------|
| UNIVERSAL RADIO COMMUNICATION TESTER | CMU 200 | 109373 | Nov. 20, 2006 |


NOTE: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

- a. Because of the measure the carrier frequency under the condition of the AFC lock, it shall be used the mobile station in the GSM link mode. This is accomplished with the use of the R&S CMU200 simulator station. The oven room could control the temperatures and humidity. The GSM link channel is the 661.
- b. Power must be removed when changing from one temperature to another or one voltage to another voltage. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- c. EUT is connected the external power supply to control the DC input power. The various Volts from the minimum 3.3 Volts to 4.2 Volts. Each step shall be record the frequency error rate.
- d. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing.
- e. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the GSM simulator.

4.3.4 TEST SETUP



4.3.5 TEST RESULTS

| | | | |
|-----------------------------|----------------------------|---------------------------------|-------------------------|
| EUT | Dual Band GSM Mobile Phone | MODEL | S198+ |
| MODE | TX channel 661 | POWER CONTROL LEVEL | 0 |
| INPUT POWER (SYSTEM) | 120Vac, 60Hz | ENVIRONMENTAL CONDITIONS | 27deg. C, 60%RH, 991hPa |
| TESTED BY | Bright | | |

FOR GSM MODE (UP-LINK WITH 1 TIME SLOT)

| AFC FREQUENCY ERROR vs. VOLTAGE | | | |
|---------------------------------|-----------------------------|------------------------------|--------------------|
| VOLTAGE (Volts) | FREQUENCY ERROR (Hz) | FREQUENCY ERROR (ppm) | LIMIT (ppm) |
| 3.3 | 57 | 0.03032 | 2.5 |
| 3.4 | 53 | 0.02819 | 2.5 |
| 3.5 | 43 | 0.02287 | 2.5 |
| 3.6 | 51 | 0.02713 | 2.5 |
| 3.7 | 34 | 0.01809 | 2.5 |
| 3.8 | 44 | 0.02340 | 2.5 |
| 3.9 | 47 | 0.02500 | 2.5 |
| 4 | 52 | 0.02766 | 2.5 |
| 4.1 | 42 | 0.02234 | 2.5 |
| 4.2 | 61 | 0.03245 | 2.5 |

| | | | |
|-----------------------------|----------------------------|---------------------------------|-------------------------|
| EUT | Dual Band GSM Mobile Phone | MODEL | S198+ |
| MODE | TX channel 661 | POWER CONTROL LEVEL | 0 |
| INPUT POWER (SYSTEM) | 120Vac, 60Hz | ENVIRONMENTAL CONDITIONS | 27deg. C, 60%RH, 991hPa |
| TESTED BY | Bright | | |

FOR GSM MODE (UP-LINK WITH 1 TIME SLOT)

| AFC FREQUENCY ERROR vs. TEMPERATURE | | | |
|-------------------------------------|----------------------|-----------------------|-------------|
| Temp. (°C) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 55 | 45 | 0.02394 | 2.5 |
| 50 | 38 | 0.02021 | 2.5 |
| 40 | 40 | 0.02128 | 2.5 |
| 30 | 41 | 0.02181 | 2.5 |
| 20 | 42 | 0.02234 | 2.5 |
| 10 | 36 | 0.01915 | 2.5 |
| 0 | 45 | 0.02394 | 2.5 |
| -10 | 43 | 0.02287 | 2.5 |

4.4 OCCUPIED BANDWIDTH MEASUREMENT

4.4.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

According to FCC 24.238(b) specified that emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

4.4.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED UNTIL |
|--------------------------------------|-----------|------------|------------------|
| * ROHDE & SCHWARZ Spectrum Analyzer | FSP30 | E1S1002 | May. 16, 2007 |
| UNIVERSAL RADIO COMMUNICATION TESTER | CMU 200 | 109373 | Nov. 20, 2006 |
| *Power Splitter Mini-Circuits | ZX10-2-20 | E2PS001 | NA |

NOTE: 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
2. “*” = These equipments are used for the final measurement.

4.4.3 TEST SETUP

Same as Item 4.2.4 (Conducted Power Setup)

4.4.4 TEST PROCEDURES

- a. The EUT was set up for the maximum peak power with GSM link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels, 512, 661 and 810(low, middle and high operational frequency range.)
- b. The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- c. FCC 24.238(b) required a measurement bandwidth is the fundamental emission below 26dB bandwidth.

4.4.5 EUT OPERATING CONDITION

- a. The EUT makes a phone call to the GSM simulator.
- b. The GSM simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.


4.4.6 TEST RESULTS

FOR GSM MODE (UP-LINK WITH 1 TIME SLOT)


| FREQUENCY (MHz) | MAX. OUTPUT POWER -26 dBc BANDWIDTH (kHz) |
|-----------------|---|
| 1850.2 | 314 |
| 1880.0 | 316 |
| 1909.8 | 316 |

FOR GSM MODE (UP-LINK WITH 1 TIME SLOT)


CH 512 MAX. POWER



CH 661 MAX. POWER



CH 810 MAX. POWER



4.5 BAND EDGE MEASUREMENT

4.5.1 LIMITS OF BAND EDGE MEASUREMENT

The PCS frequency bands refer to the FCC 24.229 rule. According to FCC 24.238(a) specified that power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. Then we measure that the bandwidth is about 300 kHz and the resolution bandwidth is 3 kHz.

4.5.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED UNTIL |
|--------------------------------------|-----------|------------|------------------|
| * ROHDE & SCHWARZ Spectrum Analyzer | FSP30 | E1S1002 | May. 16, 2007 |
| UNIVERSAL RADIO COMMUNICATION TESTER | CMU200 | 109373 | Nov. 20, 2006 |
| *Power Splitter Mini-Circuits | ZX10-2-20 | E2PS001 | NA |

NOTE: 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

2. “*” = These equipments are used for the final measurement.

4.5.3 TEST SETUP

Same as Item 4.2.4 (Conducted Power Setup)

4.5.4 TEST PROCEDURES

- a. The EUT was set up for the maximum peak power with GSM link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 2 channels, 512 and 810 (low and high operational frequency range.)
- b. The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer. This splitter loss and cable loss are the worst loss 4dB in the transmitted path track.
- c. The center frequency of spectrum is the band edge frequency and span is 2 MHz. RB of the spectrum is 3kHz and VB of the spectrum is 10 KHz.
- d. Record the max trace plot into the test report.


4.5.5 EUT OPERATING CONDITION

- a. The EUT makes a phone call to the GSM simulator.
- b. The GSM simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.


4.5.6 TEST RESULTS

FOR GSM MODE (UP-LINK WITH 1 TIME SLOT)

LOWER BAND EDGE



HIGHER BAND EDGE



4.6 CONDUCTED SPURIOUS EMISSIONS

4.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

In the FCC 24.238(a), On any frequency outside a licensee's frequency block within USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB. The limit translates in the relevant power range (1 to 0.001W). At 1W(Power Control Level 0) the specified minimum attenuation becomes 43dB and the limit of emission equal to -13dBm. At 0.001W(Power Control Level 15) the specified minimum attenuation becomes 13dB and the emission of limit equal to -13dBm. So the limit of emission is the same absolute specified line. In the FCC 24.238(c), When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges (low channel 512 and high channel 810), both upper and lower edges are compliance with FCC 24.238(b), Adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

4.6.2 TEST INSTRUMENTS


| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED UNTIL |
|--------------------------------------|-------------|------------|------------------|
| * ROHDE & SCHWARZ Spectrum Analyzer | FSP30 | E1S1002 | May. 16, 2007 |
| Universal Radio Communication Tester | CMU200 | 109373 | Nov. 20, 2006 |
| K & L Turnable Band Reject Filter | 5TNF-00083 | E1F4004 | N/A |
| * Woken High Pass Filter | EWT-57-0021 | E1F4002 | N/A |

NOTE: 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
 2. “*” = These equipments are used for the final measurement.

4.6.3 TEST PROCEDURE

- a. The EUT was set up for the maximum peak power with GSM link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels, 512, 661 and 810 (low, middle and high operational frequency range.)
- b. The conducted spurious emission used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- c. When the spectrum scanned from 9 kHz to 3GHz, it shall be connected to the band reject filter attenuated the carried frequency. The spectrum set RB/VB 1MHz.
- d. When the spectrum scanned from 3 kHz to 20GHz, it shall be connected to the high pass filter attenuated the carried frequency. The spectrum set RB/VB 1MHz.

4.6.4 TEST SETUP




4.6.5 EUT OPERATING CONDITIONS

- a. The EUT makes a phone call to the GSM simulator.
- b. The GSM simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.


4.6.6 TEST RESULTS

FOR GSM MODE (UP-LINK WITH 1 TIME SLOT)


CH 512: 9kHz ~ 3GHz




3GHz ~ 10GHz




10GHz ~ 20GHz




CH 661: 9kHz ~ 3GHz




3GHz ~ 10GHz




10GHz ~ 20GHz




CH 810: 9kHz ~ 3GHz



3GHz ~ 10GHz



10GHz ~ 20GHz



FOR GSM MODE (UP-LINK WITH 1 TIME SLOT)

| | | | |
|---------------------------------|----------------------------|----------------------------|--------|
| EUT | Dual Band GSM Mobile Phone | MODEL | S198+ |
| MODE | TX channel 512 | POWER CONTROL LEVEL | 0 |
| INPUT POWER (SYSTEM) | 120Vac, 60Hz | DETECTOR FUNCTION | Peak |
| ENVIRONMENTAL CONDITIONS | 27deg. C, 60%RH, 991hPa | TESTED BY | Bright |

| CONDUCTED SPURIOUS EMISSION | | | | | |
|-----------------------------|-------------------------------|--------------------------|------------------------------|--------------------|--------------------|
| FREQUENCY (MHz) | CORRECTION FACTOR (dB) | S.A READING (dBm) | CONDUCTED LEVEL (dBm) | LIMIT (dBm) | MARGIN (dB) |
| 5548 | 5.1 | -60.3 | -55.2 | -13 | -42.2 |
| 9258 | 7 | -60.93 | -53.93 | -13 | -40.93 |
| 12940 | 8.4 | -62.29 | -53.89 | -13 | -40.89 |
| 15160 | 9.4 | -53.4 | -44 | -13 | -31 |

REMARKS: 1. Peak Output Power (dBm) = Raw Value (dBm) + Correction Factor (dB).

2. Correction Factor (dB) = Power Splitter Loss (dB) + Cable Loss (dB).

| | | | |
|---------------------------------|----------------------------|----------------------------|--------|
| EUT | Dual Band GSM Mobile Phone | MODEL | S198+ |
| MODE | TX channel 661 | POWER CONTROL LEVEL | 0 |
| INPUT POWER (SYSTEM) | 120Vac, 60Hz | DETECTOR FUNCTION | Peak |
| ENVIRONMENTAL CONDITIONS | 27deg. C, 60%RH, 991hPa | TESTED BY | Bright |

CONDUCTED SPURIOUS EMISSION

| FREQUENCY (MHz) | CORRECTION FACTOR (dB) | S.A READING (dBm) | CONDUCTED LEVEL (dBm) | LIMIT (dBm) | MARGIN (dB) |
|------------------------|-------------------------------|--------------------------|------------------------------|--------------------|--------------------|
| 3765 | 4.1 | -62.32 | -58.22 | -13 | -45.22 |
| 5646 | 5.2 | -59.81 | -54.61 | -13 | -41.61 |
| 15200 | 9.4 | -53.47 | -44.07 | -13 | -31.07 |

REMARKS: 1. Peak Output Power (dBm) = Raw Value (dBm) + Correction Factor (dB).
 2. Correction Factor (dB) = Power Splitter Loss (dB) + Cable Loss (dB).

| | | | |
|---------------------------------|----------------------------|----------------------------|--------|
| EUT | Dual Band GSM Mobile Phone | MODEL | S198+ |
| MODE | TX channel 810 | POWER CONTROL LEVEL | 0 |
| INPUT POWER (SYSTEM) | 120Vac, 60Hz | DETECTOR FUNCTION | Peak |
| ENVIRONMENTAL CONDITIONS | 27deg. C, 60%RH, 991hPa | TESTED BY | Bright |

CONDUCTED SPURIOUS EMISSION

| FREQUENCY (MHz) | CORRECTION FACTOR (dB) | S.A READING (dBm) | CONDUCTED LEVEL (dBm) | LIMIT (dBm) | MARGIN (dB) |
|------------------------|-------------------------------|--------------------------|------------------------------|--------------------|--------------------|
| 3812 | 4.2 | -60 | -55.8 | -13 | -42.8 |
| 5730 | 5.2 | -54.86 | -49.66 | -13 | -36.66 |
| 11460 | 8.1 | -61.55 | -53.45 | -13 | -40.45 |
| 15200 | 9.4 | -53.98 | -44.58 | -13 | -31.58 |

REMARKS: 1. Peak Output Power (dBm) = Raw Value (dBm) + Correction Factor (dB).

2. Correction Factor (dB) = Power Splitter Loss (dB) + Cable Loss (dB).

4.7 RADIATED EMISSION MEASUREMENT (BELOW 1GHz)

4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

In the FCC 24.238(a), On any frequency outside a licensee's frequency block within USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB. The limit translates in the relevant power range (1 to 0.001W). At 1W(Power Control Level 0) the specified minimum attenuation becomes 43dB and the limit of emission equal to -13dBm. At 0.001W(Power Control Level 15) the specified minimum attenuation becomes 13dB and the emission of limit equal to -13dBm. So the limit of emission is the same absolute specified line.

4.7.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED UNTIL |
|--|-------------------|------------|------------------|
| Test Receiver ROHDE & SCHWARZ | ESCS30 | E1R1001 | Apr. 19, 2007 |
| BILOG Antenna SCHWARZBECK | VULB9168 | E1A1001 | Sep. 26, 2006 |
| Preamplifier Agilent | 8447D | E1A2001 | Jan. 27, 2007 |
| Preamplifier Agilent | 8449B | E1A2002 | Jan. 27, 2007 |
| Double Ridged Broadband Horn Antenna Schwarzbeck | BBHA 9120D | E1A1002 | Feb.15, 2007 |
| *Spectrum Analyzer Agilent | E4403B | E1S1001 | Jan. 13, 2007 |
| *Spectrum Analyzer ROHDE & SCHWARZ | FSP30 | E1S1002 | May.15, 2007 |
| RF signal cable Woken | RG-402 | E1CBH01 | May. 30, 2007 |
| RF signal cable Woken | RG-402 | E1CBH02 | May. 30, 2007 |
| RF signal cable Woken | RG-402 | E1CBH03 | May. 30, 2007 |
| RF signal cable Woken | RG-412 | E1CBL02 | May. 30, 2007 |
| RF signal cable Woken | RG-412 | E1CBL03 | May. 30, 2007 |
| RF signal cable Woken | RG-412 | E1CBL04 | May. 30, 2007 |
| Software ADT | ADT_Radiated_V7.5 | N/A | N/A |

NOTE:

1. The calibration interval of the above test instruments is 12 months.
2. “*” = These equipment are used for the final measurement.
3. The horn antenna and Agilent preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The Spectrum Analyzer (model: FSP30) and RF signal cable (SERIAL: E1CBH05&E1CBH07) are used only for the measurement of emission frequency above 1GHz if tested.

4.7.3 TEST PROCEDURES


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the receiving antenna, which was mounted on antenna tower and its position at 0.8 m above the ground.
- c. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading and recorded the value.
- d. Repeat step a ~ c for horizontal polarization.

NOTE: 1. The resolution bandwidth of spectrum analyzer is 10 kHz and the video bandwidth is 300 kHz for spurious emission below 1GHz.
2. The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for spurious emission above 1GHz.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation

4.7.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.7.6 EUT OPERATING CONDITIONS

- a. The notebook system makes a phone call to the GSM simulator.
- b. The GSM simulator station system controlled an EUT to export maximum output power under transmission mode and specific channel frequency.

4.7.7 TEST RESULTS

FOR GSM MODE (UP-LINK WITH 1 TIME SLOT)

| | | | |
|---------------------------------|----------------------------|--------------------------|----------------|
| EUT | Dual Band GSM Mobile Phone | MODEL | S198+ |
| MODE | TX channel 512 | FREQUENCY RANGE | Below 1000 MHz |
| INPUT POWER (SYSTEM) | 120Vac, 60Hz | DETECTOR FUNCTION | Quasi-Peak |
| ENVIRONMENTAL CONDITIONS | 24deg. C, 66%RH, 991hPa | TESTED BY | Bright |

MODE A

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M | | | | | | | | |
|--|-------------|---------------|------------------|-------------------|----------------|-------------|------------------|--------------------|
| No. | Freq. (MHz) | Factor (dB/M) | Reading (dBuV/M) | Emission (dBuV/M) | Limit (dBuV/M) | Margin (dB) | Ant. Height (cm) | Table Angle (Deg.) |
| 1 | 80.92 | 11.58 | -3.36 | 8.22 | 40 | -31.78 | 110 | 54 |
| 2 | 156.1 | 17.03 | -3.18 | 13.85 | 43.5 | -29.65 | 100 | 319 |
| 3 | 291.9 | 16.28 | -3.33 | 12.95 | 46 | -33.05 | 283 | 144 |
| 4 | 430.12 | 19.61 | -3.68 | 15.93 | 46 | -30.07 | 296 | 19 |
| 5 | 502.87 | 20.93 | -0.75 | 20.18 | 46 | -25.82 | 198 | 125 |
| 6 | 602.3 | 23.17 | -1.3 | 21.87 | 46 | -24.13 | 137 | 92 |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL 3M | | | | | | | | |
|---|-------------|---------------|------------------|-------------------|----------------|-------------|------------------|--------------------|
| No. | Freq. (MHz) | Factor (dB/M) | Reading (dBuV/M) | Emission (dBuV/M) | Limit (dBuV/M) | Margin (dB) | Ant. Height (cm) | Table Angle (Deg.) |
| 1 | 59.1 | 14.84 | -3.74 | 11.1 | 40 | -28.9 | 100 | 30 |
| 2 | 151.25 | 16.98 | -3.25 | 13.73 | 43.5 | -29.77 | 100 | 153 |
| 3 | 228.85 | 14.45 | -3.66 | 10.79 | 46 | -35.21 | 100 | 275 |
| 4 | 321 | 17.04 | -3.2 | 13.84 | 46 | -32.16 | 100 | 15 |
| 5 | 393.75 | 18.52 | -3.4 | 15.12 | 46 | -30.88 | 100 | 295 |
| 6 | 527.12 | 21.46 | -0.88 | 20.58 | 46 | -25.42 | 100 | 110 |

NOTE:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. This is valid for all 3 channels.

MODE B

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M | | | | | | | | |
|--|-------------|---------------|------------------|-------------------|----------------|-------------|------------------|--------------------|
| No. | Freq. (MHz) | Factor (dB/M) | Reading (dBuV/M) | Emission (dBuV/M) | Limit (dBuV/M) | Margin (dB) | Ant. Height (cm) | Table Angle (Deg.) |
| 1 | 122.15 | 14.9 | -3.2 | 11.7 | 43.5 | -31.8 | 100 | 19 |
| 2 | 231.28 | 14.56 | -3.62 | 10.94 | 46 | -35.06 | 201 | 213 |
| 3 | 362.23 | 17.81 | -2.89 | 14.92 | 46 | -31.08 | 356 | 82 |
| 4 | 468.93 | 20.42 | -3.13 | 17.29 | 46 | -28.71 | 212 | 31 |
| 5 | 536.83 | 21.71 | -1.05 | 20.66 | 46 | -25.34 | 280 | 193 |
| 6 | 645.95 | 23.84 | -1.31 | 22.53 | 46 | -23.47 | 363 | 262 |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL 3M | | | | | | | | |
|---|-------------|---------------|------------------|-------------------|----------------|-------------|------------------|--------------------|
| No. | Freq. (MHz) | Factor (dB/M) | Reading (dBuV/M) | Emission (dBuV/M) | Limit (dBuV/M) | Margin (dB) | Ant. Height (cm) | Table Angle (Deg.) |
| 1 | 114.87 | 14.15 | -3.5 | 10.65 | 43.5 | -32.85 | 100 | 92 |
| 2 | 187.62 | 13.73 | -3.15 | 10.58 | 43.5 | -32.92 | 100 | 214 |
| 3 | 274.93 | 15.66 | -2.67 | 12.99 | 46 | -33.01 | 100 | 338 |
| 4 | 359.8 | 17.74 | -2.8 | 14.94 | 46 | -31.06 | 100 | 235 |
| 5 | 461.65 | 20.3 | -3.61 | 16.69 | 46 | -29.31 | 100 | 169 |
| 6 | 602.3 | 23.17 | -1.24 | 21.93 | 46 | -24.07 | 100 | 49 |

NOTE:

6. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB).
7. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
8. The other emission levels were very low against the limit.
9. Margin value = Emission level – Limit value.
10. This is valid for all 3 channels.

4.8 EFFECTIVE RADIATED POWER MEASUREMENT (ABOVE 1GHz)

4.8.1 LIMITS OF RADIATED EMISSION MEASUREMENT

In the FCC 24.238(a), On any frequency outside a licensee's frequency block within USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB. The limit translates in the relevant power range (1 to 0.001W). At 1W(Power Control Level 0) the specified minimum attenuation becomes 43dB and the limit of emission equal to -13dBm. At 0.001W(Power Control Level 15) the specified minimum attenuation becomes 13dB and the emission of limit equal to -13dBm. So the limit of emission is the same absolute specified line.

4.8.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED UNTIL |
|--|-------------------|------------|------------------|
| Spectrum Agilent | E4403B | E1S1001 | Mar. 19, 2007 |
| Receiver R&S | ESCS30 | E1R1001 | Jun. 19, 2006 |
| Trilog Broadband Antenna Schwarzbeck | VULB 9168 | E1A1001 | Mar. 22, 2007 |
| Double Ridged Broadband Horn Antenna Schwarzbeck | BBHA 9120D | E1A1002 | Feb. 14, 2007 |
| Preamplifier Agilent | HP 8447D-CFG001 | E1A2001 | Jan. 27, 2007 |
| Signal Analyzer ROHDE & SCHWARZ | FSP30 | E1S1002 | May. 15, 2007 |
| RF signal cable Woken | RG-402 | E1CBH01 | May. 30, 2007 |
| RF signal cable Woken | RG-412 | E1CBL02 | May. 30, 2007 |
| RF signal cable Woken | RG-412 | E1CBL03 | May. 30, 2007 |
| RF signal cable Woken | RG-412 | E1CBL04 | May. 30, 2007 |
| Software ADT | ADT_Radiated_V7.5 | N/A | N/A |

NOTE:

- 1 The calibration interval of the above test instruments is 12 months.
- 2 The horn antenna and Agilent preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.

4.8.3 TEST PROCEDURES


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the receiving antenna, which was mounted on antenna tower and its position at 0.8 m above the ground.
- c. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading and recorded the value.
- d. The EUT is replaced by a horn antenna connected to a signal generator tuned to the frequency of emission.
- e. The signal generator level has to be adjusted to have the same emission nature.
- f. The radiated power can be calculated via the factor and antenna gain.
- g. Repeat step a ~ f for horizontal polarization.

NOTE: 1. The resolution bandwidth of spectrum analyzer is 10 kHz and the video bandwidth is 300 kHz for spurious emission below 1GHz.
2. The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for spurious emission above 1GHz.

4.8.4 DEVIATION FROM TEST STANDARD

No deviation

4.8.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.8.6 EUT OPERATING CONDITIONS

- a. The notebook system makes a phone call to the GSM simulator.
- b. The GSM simulator station system controlled an EUT to export maximum output power under transmission mode and specific channel frequency.

4.8.7 TEST RESULTS

FOR GSM MODE (UP-LINK WITH 1 TIME SLOT)

| | | | |
|-----------------------------|----------------------------|---------------------------------|-------------------------|
| EUT | Dual Band GSM Mobile Phone | MODEL | S198+ |
| MODE | TX channel 512 | FREQUENCY RANGE | Above 1000 MHz |
| INPUT POWER (SYSTEM) | 120Vac, 60Hz | ENVIRONMENTAL CONDITIONS | 24deg. C, 62%RH, 991hPa |
| TESTED BY | Bright | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | |
|---|-------------|-----------------------|-------------|-----------------------|------------------------|-------------------|
| No. | Freq. (MHz) | Emission Level (dBuV) | Limit (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Power Value (dBm) |
| 1 | 3700.4 | 53.06 | -13 | -50.33 | 9 | -41.33 |
| 2 | 5500.6 | 54 | -13 | -50.11 | 10.1 | -40.01 |
| 3 | 7400.7 | 59.88 | -13 | -44.43 | 10.2 | -34.23 |
| 4 | 9251 | 61.41 | -13 | -42.52 | 10.4 | -32.12 |
| 5 | 14850 | 68.34 | -13 | -35.66 | 11.2 | -24.46 |
| 6 | 16651 | 70.32 | -13 | -33.68 | 12.1 | -21.58 |
| 7 | 18502 | 72.84 | -13 | -31.91 | 13.2 | -18.71 |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | |
|---|-------------|-----------------------|-------------|-----------------------|------------------------|-------------------|
| No. | Freq. (MHz) | Emission Level (dBuV) | Limit (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Power Value (dBm) |
| 1 | 3700.4 | 54.43 | -13 | -49.47 | 9 | -40.47 |
| 2 | 5500.6 | 53.52 | -13 | -50.46 | 10.1 | -40.36 |
| 3 | 7400.7 | 60.3 | -13 | -43.17 | 10.2 | -32.97 |
| 4 | 9251 | 61.74 | -13 | -42.23 | 10.4 | -31.83 |
| 5 | 14850 | 68.77 | -13 | -35.23 | 11.2 | -24.03 |
| 6 | 16651 | 71.49 | -13 | -32.51 | 12.1 | -20.41 |
| 7 | 18502 | 72.99 | -13 | -31.76 | 13.2 | -18.56 |

NOTE: Power Value (dBm) = S.G Power Value (dBm) + Correction Factor (dB).

| | | | |
|-----------------------------|----------------------------|---------------------------------|-------------------------|
| EUT | Dual Band GSM Mobile Phone | MODEL | S198+ |
| MODE | TX channel 661 | FREQUENCY RANGE | Above 1000 MHz |
| INPUT POWER (SYSTEM) | 120Vac, 60Hz | ENVIRONMENTAL CONDITIONS | 24deg. C, 62%RH, 991hPa |
| TESTED BY | Bright | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | |
|---|-------------|-----------------------|-------------|-----------------------|------------------------|-------------------|
| No. | Freq. (MHz) | Emission Level (dBuV) | Limit (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Power Value (dBm) |
| 1 | 3760 | 52.33 | -13 | -49.37 | 9.1 | -40.27 |
| 2 | 5640 | 54.1 | -13 | -50.42 | 10.1 | -40.32 |
| 3 | 7520 | 61.25 | -13 | -43.17 | 10.3 | -32.87 |
| 4 | 9400 | 63.19 | -13 | -42.23 | 10.4 | -31.83 |
| 5 | 15040 | 68.98 | -13 | -35.02 | 11.2 | -23.82 |
| 6 | 16920 | 71.78 | -13 | -32.22 | 12.1 | -20.12 |
| 7 | 18800 | -72.84 | -13 | -30.88 | 13.3 | -17.58 |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | |
|---|-------------|-----------------------|-------------|-----------------------|------------------------|-------------------|
| No. | Freq. (MHz) | Emission Level (dBuV) | Limit (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Power Value (dBm) |
| 1 | 3760 | 54.86 | -13 | -49.74 | 9.1 | -40.64 |
| 2 | 5640 | 55.02 | -13 | -48.41 | 10.1 | -38.31 |
| 3 | 7520 | 60.38 | -13 | -43.31 | 10.3 | -33.01 |
| 4 | 9400 | 62.44 | -13 | -41.26 | 10.4 | -30.86 |
| 5 | 15040 | 68.77 | -13 | -35.23 | 11.2 | -24.03 |
| 6 | 16920 | 71.31 | -13 | -32.69 | 12.1 | -20.59 |
| 7 | 18800 | 73.03 | -13 | -30.67 | 13.3 | -17.37 |

NOTE: Power Value (dBm) = S.G Power Value (dBm) + Correction Factor (dB).

| | | | |
|-----------------------------|----------------------------|---------------------------------|-------------------------|
| EUT | Dual Band GSM Mobile Phone | MODEL | S198+ |
| MODE | TX channel 810 | FREQUENCY RANGE | Above 1000 MHz |
| INPUT POWER (SYSTEM) | 120Vac, 60Hz | ENVIRONMENTAL CONDITIONS | 24deg. C, 62%RH, 991hPa |
| TESTED BY | Bright | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | |
|---|--------------|-----------------------|-------------|-----------------------|------------------------|-------------------|
| No. | Freq. (MHz) | Emission Level (dBuV) | Limit (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Power Value (dBm) |
| 1 | 3819.6 | 51.75 | -13 | -52.01 | 9.1 | -42.91 |
| 2 | 5729.4 | 55.09 | -13 | -48.22 | 10.2 | -38.02 |
| 3 | 7639.2 | 60.43 | -13 | -43.34 | 10.3 | -33.04 |
| 4 | 9549 | 61.64 | -13 | -42.54 | 10.5 | -32.04 |
| 5 | 15278 | 68.99 | -13 | -35.78 | 11.3 | -24.48 |
| 6 | 17188 | 71.87 | -13 | -32.24 | 12.2 | -20.04 |
| 7 | 19098 | 73.91 | -13 | -30.06 | 13.5 | -16.56 |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | |
|---|-------------|-----------------------|-------------|-----------------------|------------------------|-------------------|
| No. | Freq. (MHz) | Emission Level (dBuV) | Limit (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Power Value (dBm) |
| 1 | 3819.6 | 55.54 | -13 | -48.33 | 9.1 | -39.23 |
| 2 | 5729.4 | 54.9 | -13 | -49.1 | 10.2 | -38.9 |
| 3 | 7639.2 | 61.7 | -13 | -42.13 | 10.3 | -31.83 |
| 4 | 9549 | 62.22 | -13 | -41.58 | 10.5 | -31.08 |
| 5 | 15278 | 69.03 | -13 | -35.46 | 11.3 | -24.16 |
| 6 | 17188 | 71.43 | -13 | -32.44 | 12.2 | -20.24 |
| 7 | 19098 | 73.88 | -13 | -30.11 | 13.5 | -16.61 |

NOTE: Power Value (dBm) = S.G Power Value (dBm) + Correction Factor (dB).

5 INFORMATION ON THE TESTING LABORATORIES

We, ADT (Shanghai) Corp., were founded in 2003 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

JAPAN

VCCI

USA

FCC, A2LA

Norway

DNV



Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.cnadt.com

If you have any comments, please feel free to contact us at the following:

ADT (Shanghai) Corporation

TEL :86-21-6465-9091

Fax : 86-21-6465-9092

Email: adtsh@vip.163.comWeb Site: www.cnadt.com