

Product Model No: IL20B-120

N0	Part No	Component	component Specification	QTY	Location	Production Factory
1	HT026	Plastics - Component	top-housing diameter: 54mm	1		XIULISHENG COMPANY
2	HT027	Plastics - Component	Bottom-housing diameter: 54mm	1		XIULISHENG COMPANY
3	MH004	cap	E26 nickel plated bronze	1		GUANGMING OR DONG SHANG
4	BS021	tube	3U 20W 5000K lamplength: 95±2mm	1		SHANG AO/YILANG COMPANY
5	PB037	Printed Wiring Boards - Component	IL25B-120-VER1 ETL-XPC-801 94-V0	1		ZHIXUAN ELECTRIC FACTORY
6	CM011	Capacitor	MEF-473-150VAC±10% P=10mm 120℃	2	C1C2	WannBao Capacitor Factory
7	CY061	Capacitor	PEI-223-100VDC±10% 120℃	1	C5	WannBao Capacitor Factory
8	CY062	Capacitor	PEI-103-1000VDC±10% 120℃	1	C7	WannBao Capacitor Factory
9	CY061	Capacitor	PEI-392-1000VDC±10% 120℃	1	C6	WannBao Capacitor Factory
10	CY056	Capacitor	PEI-473-400VDC±10% 120℃	1	C8	WannBao Capacitor Factory
11	CY107	Capacitor	CL12-511-630VDC±10% 120℃	1	C9	WannBao Capacitor Factory
12	CE038	Electrolytic capacitor	22uF/200VDC±20% 105°C RK 10m×20mm	2	C4 C3	HONGYI COMPANY
13	DO010	Diode	1N4007 V _{RMS} =700V IO=1.0A T _{STG} =-65to +175℃	4	D1~D4	YINGHECOMPANY
14	DO004	Diode	FR104 V _{RMS} =280V IO=1.0A T _{STG} =-65to +150℃	3	D6D8D9	YINGHECOMPANY
15	DO002	Triggering Diode	DB3 V _{BO} =28-36V I _{BO} =100mA T _{STG} =-40to +125℃	1	D7	YINGHECOMPANY
16	TR019	Transistor	BUL128 T _J =150℃ V _{CES} =700V I _C =4.0A TO-220	2	TR1TR2	SGS-THOMSON
17	RC125	Resistor	RT-0.5-680K Ω ±5%	1	R2	JINGTIAN RESISTOR FACTORY
18	RC126	Resistor	RT-0.5-470K Ω ±5%	1	R7	JINGTIAN RESISTOR FACTORY
19	RC127	Thermistor	WMZH-75A&SPMZA-5 (200-300R)	1	R8	XINGSHANGBAO FACTORY
20	RC128	Resistor	RT-0.25-22 Ω ±5%	3	R3R4R9	JINGTIAN RESISTOR FACTORY
21	RC129	Resistor	RT-0.25-0.5 Ω ±5%	2	R5R6	JINGTIAN RESISTOR FACTORY
22	RC130	Resistor	RT-0.25-10K Ω ±5%	1	R10	JINGTIAN RESISTOR FACTORY
23	LI053	Inductor	DR10*16 4.0mH OD:0.25mm/320T	1	L1	SHENZHEN TRANSFORMER ELECTORNICS CO.,LTD
24	LI016	Inductor	EE19 3.6mH%±5%	1	L2	SHENZHEN TRANSFORMER ELECTORNICS CO.,LTD
25	LF004	Magnetic coil	T9×5×3 3T:4T:3T	1	T	DENGYI
26	WC003	Magnetic coil wire	AWG#30 UL1423 L=140mm each red /green	2	T fittings1	YONGSHENG
27	WC003	Magnetic coil wire	AWG#30 UL1423 L=120mm white	1	T fittings2	YONGSHENG
28	WS007	Appliance Wiring Material - Component	UL1007 #22 1/0.643 5+75+15=90mm white 300V VW-1	2	LN	CHINA LONSID ELECTRIC CO LTD
29	FT013	Fuses, Supplemental	TSA, FAP+ 0.315/250VAC 3.6*10	1	F1	WALTER ELECTRONIC CO LTD
30	WS010	Sleeving, Flame Retardant - Component	GS30-2E diameter:1.0mm length:12mm	4	ABCD fittings2	WISE-KEY INSULATORS & CHEMICALS MFG CO LTD
31	WS010	Sleeving, Flame Retardant - Component	GS30-2E diameter:1.0mm length:10mm	2	C4 fittings2	WISE-KEY INSULATORS & CHEMICALS MFG CO LTD
32	WS010	Tubing, Extruded Insulating - Component	KUHS-225 diameter:10mm length:18mm	1	L1 fittings2	UNICHEM CO LTD

33	WS010	Tubing, Extruded Insulating - Component	KUHS-225 diameter:10mm length:90mm	1	F1 fittings1	UNICHEM CO LTD
----	-------	--	------------------------------------	---	-----------------	----------------

Product Model No: SL20B-120

N0	Part No	Component	component Specification	QTY	Location	Production Factory
1	HT026	Plastics - Component	top-housing diameter: 54mm	1		XIULISHENG COMPANY
2	HT027	Plastics - Component	Bottom-housing diameter: 54mm	1		XIULISHENG COMPANY
3	MH004	cap	E26 nickel plated bronze	1		GUANGMING OR DONG SHANG
4	BS021	tube	20W spiral 5000K lamplength: 73±2mm Turns:3	1		SHANG AO/YILANG COMPANY
5	PB037	Printed Wiring Boards - Component	IL25B-120-VER1 ETL-XPC-801 94-V0	1		ZHIXUAN ELECTRIC FACTORY
6	CM011	Capacitor	MEF-473-150VAC±10% 120℃	2	C1C2	WannBao Capacitor Factory
7	CY061	Capacitor	PEI-223-100VDC±10% 120℃	1	C5	WannBao Capacitor Factory
8	CY062	Capacitor	PEI-103-1000VDC±10% 120℃	1	C7	WannBao Capacitor Factory
9	CY061	Capacitor	PEI-392-1000VDC±10% 120℃	1	C6	WannBao Capacitor Factory
10	CY056	Capacitor	PEI-473-400VDC±10% 120℃	1	C8	WannBao Capacitor Factory
11	CY107	Capacitor	CL12-511-630VDC±10% 120℃	1	C9	WannBao Capacitor Factory
12	CE038	Electrolytic capacitor	22uF/200VDC±20% 105℃ RK 10m×20mm	2	C4 C3	HONGYI COMPANY
13	DO010	Diode	1N4007 V _{RMS} =700V IO=1.0A T _{STG} =-65to +175℃	4	D1~D4	YINGHECOMPANY
14	DO004	Diode	FR104 V _{RMS} =280V IO=1.0A T _{STG} =-65to +150℃	3	D6D8D9	YINGHECOMPANY
15	DO002	Triggering Diode	DB3 V _{BO} =28-36V I _{BO} =100mA T _{STG} =-40to +125℃	1	D7	YINGHECOMPANY
16	TR019	Transistor	BUL128 T _J =150℃ V _{CES} =700V I _C =4.0A TO-220	2	TR1TR2	SGS-THOMSON
17	RC125	Resistor	RT-0.5-680K Ω ±5%	1	R2	JINGTIAN RESISTOR FACTORY
18	RC126	Resistor	RT-0.5-470K Ω ±5%	1	R7	JINGTIAN RESISTOR FACTORY
19	RC127	Thermistor	WMZH-75A&SPMZA-5 (200-300R)	1	R8	XINGSHANGBAO FACTORY
20	RC128	Resistor	RT-0.25-22 Ω ±5%	3	R3R4R9	JINGTIAN RESISTOR FACTORY
21	RC129	Resistor	RT-0.25-0.5 Ω ±5%	2	R5R6	JINGTIAN RESISTOR FACTORY
22	RC130	Resistor	RT-0.25-10K Ω ±5%	1	R10	JINGTIAN RESISTOR FACTORY
23	LI053	Inductor	DR10*16 4.0mH OD:0.25mm/320T	1	L1	SHENZHEN TRANSFORMER ELECTORNICS CO.,LTD
24	LI016	Inductor	EE19 3.6mH%±5%	1	L2	SHENZHEN TRANSFORMER ELECTORNICS CO.,LTD
25	LF004	Magnetic coil	T9×5×3 3T:4T:3T	1	T	DENGYI
26	WC003	Magnetic coil wire	AWG#30 UL1423 L=140mm each red /green	2	T fittings1	YONGSHENG
27	WC003	Magnetic coil wire	AWG#30 UL1423 L=120mm white	1	T fittings2	YONGSHENG
28	WS007	Appliance Wiring Material - Component	UL1007 #22 1/0.643 5+75+15=90mm white 300V VW-1	2	LN	CHINA LONSID ELECTRIC CO LTD
29	FT013	Fuses, Supplemental	TSA, FAP+ 0.315/250VAC 3.6*10	1	F1	WALTER ELECTRONIC CO LTD
30	WS010	Sleeving, Flame Retardant - Component	GS30-2E diameter:1.0mm length:12mm	4	ABCD fittings2	WISE-KEY INSULATORS & CHEMICALS MFG CO LTD
31	WS010	Sleeving, Flame Retardant - Component	GS30-2E diameter:1.0mm length:10mm	2	C4 fittings2	WISE-KEY INSULATORS & CHEMICALS MFG CO LTD
32	WS010	Tubing, Extruded Insulating - Component	KUHS-225 diameter:10mm length:18mm	1	L1 fittings2	UNICHEM CO LTD
33	WS010	Tubing, Extruded Insulating - Component	KUHS-225 diameter:10mm length:90mm	1	F1 fittings1	UNICHEM CO LTD

Product Model No: SL25B-120

NO	Part No	Component	component Specification	QTY	Location	Production Factory
1	HT026	Plastics - Component	top-housing diameter: 58mm	1		XIULISHENG COMPANY
2	HT027	Plastics - Component	Bottom-housing diameter: 58mm	1		XIULISHENG COMPANY
3	MH004	cap	E26 nickel plated bronze	1		GUANGMING OR DONG SHANG
4	BS021	tube	25W spiral 5800K, lamplength: 93±2mm Turns:4	1		SHANG AO/YILANG COMPANY
5	PB037	Printed Wiring Boards - Component	IL25B-120-VER1 ETL-XPC-801 94-V0	1		ZHIXUAN ELECTRIC FACTORY
6	CM011	Capacitor	MEF-473-150VAC±10% 120℃	1	C1	WannBao Capacitor Factory
7	CM011	Capacitor	MEF-104-150VAC±10% 120℃	1	C2	WannBao Capacitor Factory
8	CY061	Capacitor	PEI-223-100VDC±10% 120℃	1	C5	WannBao Capacitor Factory
9	CY062	Capacitor	PEI-103-1000VDC±10% 120℃	1	C7	WannBao Capacitor Factory
10	CY061	Capacitor	PEI-392-1000VDC±10% 120℃	1	C6	WannBao Capacitor Factory
11	CY056	Capacitor	PEI-473-400VDC±10% 120℃	1	C8	WannBao Capacitor Factory
12	CY107	Capacitor	CL12-511-630VDC±10% 120℃	1	C9	WannBao Capacitor Factory
13	CE038	Electrolytic capacitor	22uF/200VDC±20% 105℃ RK 10m×20mm	2	C4 C3	HONGYI COMPANY
14	DO010	Diode	1N4007 V _{RMS} =700V IO=1.0A T _{STG} =-65to +175℃	4	D1~D4	YINGHECOMPANY
15	DO004	Diode	FR104 V _{RMS} =280V IO=1.0A T _{STG} =-65to +150℃	3	D6D8D9	YINGHECOMPANY
16	DO002	Triggering Diode	DB3 V _{BO} =28-36V I _{BO} =100mA T _{STG} =-40to +125℃	1	D7	YINGHECOMPANY
17	TR019	Transistor	BUL128 T _J =150℃ V _{CES} =700V I _C =4.0A TO-220	2	TR1TR2	SGS-THOMSON
18	RC125	Resistor	RT-0.5-680K Ω ±5%	1	R2	JINGTIAN RESISTOR FACTORY
19	RC126	Resistor	RT-0.5-470K Ω ±5%	1	R7	JINGTIAN RESISTOR FACTORY
20	RC127	Thermistor	WMZH-75A&SPMZA-5 (200-300R)	1	R8	XINGSHANGBAO FACTORY
21	RC128	Resistor	RT-0.25-22 Ω ±5%	3	R3R4R9	JINGTIAN RESISTOR FACTORY
22	RC129	Resistor	RT-0.25-0.5 Ω ±5%	2	R5R6	JINGTIAN RESISTOR FACTORY
23	RC130	Resistor	RT-0.25-10K Ω ±5%	1	R10	JINGTIAN RESISTOR FACTORY
24	LI053	Inductor	DR10*16 4.0mH OD:0.25mm/320T	1	L1	SHENZHEN TRANSFORMER ELECTORNICS CO.,LTD
25	LI016	Inductor	EE19 3.6mH%±5%	1	L2	SHENZHEN TRANSFORMER ELECTORNICS CO.,LTD
26	LF004	Magnetic coil	T9×5×3 3T:4T:3T	1	T	DENGYI
27	WC003	Magnetic coil wire	AWG#30 UL1423 L=140mm each red /green	2	T fittings1	YONGSHENG
28	WC003	Magnetic coil wire	AWG#30 UL1423 L=120mm white	1	T fittings2	YONGSHENG
29	WS007	Appliance Wiring Material - Component	UL1007 #22 1/0.643 5+75+15=90mm white 300V VW-1	2	LN	CHINA LONSID ELECTRIC CO LTD
30	FT013	Fuses, Supplemental	TSA, FAP+ 0.35/250VAC 3.6*10	1	F1	WALTER ELECTRONIC CO LTD
31	WS010	Sleeving, Flame Retardant - Component	GS30-2E diameter:1.0mm length:12mm	4	ABCD fittings2	WISE-KEY INSULATORS & CHEMICALS MFG CO LTD
32	WS010	Sleeving, Flame Retardant - Component	GS30-2E diameter:1.0mm length:10mm	2	C4 fittings2	WISE-KEY INSULATORS & CHEMICALS MFG CO LTD
33	WS010	Tubing, Extruded Insulating - Component	KUHS-225 diameter:10mm length:18mm	1	L1 fittings2	UNICHEM CO LTD
34	WS010	Tubing, Extruded Insulating - Component	KUHS-225 diameter:4mm length:80mm	2	L N fittings	UNICHEM CO LTD

Product Model No: SL28B-120

N0	Part No	Component	component Specification	QTY	Location	Production Factory
1	HT026	Plastics - Component	top-housing diameter: 54mm	1		XIULISHENG COMPANY
2	HT027	Plastics - Component	Bottom-housing diameter: 54mm	1		XIULISHENG COMPANY
3	MH004	cap	E26 nickel plated bronze	1		GUANGMING OR DONG SHANG
4	BS021	tube	28W spiral 2700K , lamplength: 95±2mm Turns:4	1		SHANG AO/YILANG COMPANY
5	PB037	Printed Wiring Boards - Component	IL25B-120-VER1 ETL-XPC-801 94-V0	1		ZHIXUAN ELECTRIC FACTORY
6	CM011	Capacitor	MEF-473-150VAC±10% 120℃	1	C1	WannBao Capacitor Factory
7	CM011	Capacitor	MEF-104-150VAC±10% 120℃	1	C2	WannBao Capacitor Factory
8	CY061	Capacitor	PEI-223-100VDC±10% 120℃	1	C5	WannBao Capacitor Factory
9	CY062	Capacitor	PEI-103-1000VDC±10% 120℃	1	C7	WannBao Capacitor Factory
10	CY061	Capacitor	PEI-392-1000VDC±10% 120℃	1	C6	WannBao Capacitor Factory
11	CY056	Capacitor	PEI-473-400VDC±10% 120℃	1	C8	WannBao Capacitor Factory
12	CY107	Capacitor	CL12-511-630VDC±10% 120℃	1	C9	WannBao Capacitor Factory
13	CE038	Electrolytic capacitor	22uF/200VDC±20% 105℃ RK 10m×20mm	2	C4 C3	HONGYI COMPANY
14	DO010	Diode	1N4007 V _{RMS} =700V IO=1.0A T _{STG} =-65to +175℃	4	D1~D4	YINGHECOMPANY
15	DO004	Diode	FR104 V _{RMS} =280V IO=1.0A T _{STG} =-65to +150℃	3	D6D8D9	YINGHECOMPANY
16	DO002	Triggering Diode	DB3 V _{BO} =28-36V I _{BO} =100mA T _{STG} =-40to +125℃	1	D7	YINGHECOMPANY
17	TR019	Transistor	BUL128 T _j =150℃ V _{CES} =700V I _C =4.0A TO-220	2	TR1TR2	SGS-THOMSON
18	RC125	Resistor	RT-0.5-680K Ω ±5%	1	R2	JINGTIAN RESISTOR FACTORY
19	RC126	Resistor	RT-0.5-470K Ω ±5%	1	R7	JINGTIAN RESISTOR FACTORY
20	RC127	Thermistor	WMZH-75A&SPMZA-5 (200-300R)	1	R8	XINGSHANGBAO FACTORY
21	RC128	Resistor	RT-0.25-22 Ω ±5%	3	R3R4R9	JINGTIAN RESISTOR FACTORY
22	RC129	Resistor	RT-0.25-0.5 Ω ±5%	2	R5R6	JINGTIAN RESISTOR FACTORY
23	RC130	Resistor	RT-0.25-10K Ω ±5%	1	R10	JINGTIAN RESISTOR FACTORY
24	LI053	Inductor	DR10*16 4.0mH OD:0.25mm/320T	1	L1	SHENZHEN TRANSFORMER ELECTORNICS CO.,LTD
25	LI016	Inductor	EE19 3.6mH%±5%	1	L2	SHENZHEN TRANSFORMER ELECTORNICS CO.,LTD
26	LF004	Magnetic coil	T9×5×3 3T:4T:3T	1	T	DENGYI
27	WC003	Magnetic coil wire	AWG#30 UL1423 L=140mm each red /green	2	T fittings1	YONGSHENG
28	WC003	Magnetic coil wire	AWG#30 UL1423 L=120mm white	1	T fittings2	YONGSHENG
29	WS007	Appliance Wiring Material - Component	UL1007 #22 1/0.643 5+75+15=90mm white 300V VW-1	2	LN	CHINA LONSID ELECTRIC CO LTD
30	FT013	Fuses, Supplemental	TSA, FAP+ 0.35/250VAC 3.6*10	1	F1	WALTER ELECTRONIC CO LTD
31	WS010	Sleeving, Flame Retardant - Component	GS30-2E diameter:1.0mm length:12mm	4	ABCD fittings2	WISE-KEY INSULATORS & CHEMICALS MFG CO LTD
32	WS010	Sleeving, Flame Retardant - Component	GS30-2E diameter:1.0mm length:10mm	2	C4 fittings2	WISE-KEY INSULATORS & CHEMICALS MFG CO LTD
33	WS010	Tubing, Extruded Insulating - Component	KUHS-225 diameter:10mm length:18mm	1	L1 fittings2	UNICHEM CO LTD
34	WS010	Tubing, Extruded Insulating - Component	KUHS-225 diameter:10mm length:90mm	1	F1 fittings1	UNICHEM CO LTD