



FCC Test Report

Test report no.: EMC_790FCC15.247_2004_B100

FCC Part 15.247 for FHSS systems / CANADA RSS-210

Model: B100

FCC ID: SOM-201458

IC ID: 4293A-201548



TTI-P-G 081/94-A0

Accredited according to ISO/IEC 17025



CTIA Authorized Test Lab
LAB CODE 20020328-00

FCC listed # 101450

IC recognized # 3925

CETECOM Inc.

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: info@ceteconusa.com • <http://www.cetecon.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2113686
Board of Directors: Dr. Harald Ansorge, Dr. Klaus Matkey, Hans Peter May

Table of Contents**1 General information****1.1 Notes****1.2 Testing laboratory****1.3 Details of applicant****1.4 Application details****1.5 Test item****1.6 Test standards****2 Technical test****2.1 Summary of test results****2.2 Test report****1 General information****1.1 Notes**

The test results of this test report relate exclusively to the test item specified in 1.5. The CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM Inc USA.

TEST REPORT PREPARED BY:**EMC Engineer: Harpreet Sidhu****1.2 Testing laboratory****CETECOM Inc.****411 Dixon Landing Road, Milpitas, CA-95035, USA****Phone: +1 408 586 6200 Fax: +1 408 586 6299****E-mail: lothar.schmidt@cetecomusa.com****Internet: www.cetecom.com**

1.3 Details of applicant

Name : **VXI Corporation**
Street : **One Front Street**
City / Zip Code : **Rollinsford, NH 03869**
Country : **USA**
Contact : **Robert Drouin**
Telephone : **800 742 8588 x263**
Fax : **603 742 5065**
e-mail : **drouin@vxicorp.com**

1.4 Application details

Date of receipt test item : 2004-10-12
Date of test : 2004-10-12/19/20

1.5 Test item

Marketing Name : Blue Parrot
Model No. : B100
Description : **Bluetooth Base for BT Headset**
FCC-ID : **SOM-201458**
IC ID : **4293A-201458**

Additional information

Frequency : 2402MHz – 2480MHz
Type of modulation : GFSK
Number of channels : 79
Antenna : Integral
Power supply : 9 VDC ±10% External power supply switching adaptor
Output power : -0.13dBm (0.97mW) max. conducted peak power
Extreme temp. Tolerance : 0°C-43°C

1.6 Test standards:**FCC Part 15 §15.247 (DA00-705) / RSS 210**

Note: All radiated measurements were made in all three orthogonal planes. The values reported are the maximum values.

2 Technical test**2.1 Summary of test results**

No deviations from the technical specification(s) were ascertained in the course of the tests
Performed

Final Verdict: (only "passed" if all single measurements are "passed")	Passed
---	---------------

Technical responsibility for area of testing:

2004-11-16	EMC & Radio	Lothar Schimdt (EMC Manager)	
Date	Section	Name	Signature

Responsible for test report and project leader:

2004-11-16	EMC & Radio	Harpreet Sidhu (EMC Engineer)	
Date	Section	Name	Signature

2.2 Test report

TEST REPORT


Test report no.: EMC_790FCC15.247_2004_B100

TEST REPORT REFERENCE


LIST OF MEASUREMENTS		PAGE
CARRIER FREQUENCY SEPERATION	§15.247(a)	7
NUMBER OF HOPPING CHANNELS	§15.247(a)	8
TIME OF OCCUPANCY (DWELL TIME)	§15.247(a)	9
SPECTRUM BANDWIDTH OF FHSS SYSTEM	§15.247(a)	12
MAXIMUM PEAK OUTPUT POWER	§15.247 (b) (1)	16
BAND EDGE COMPLIANCE	§15.247 (c)	24
EMISSION LIMITATIONS	§15.247 (c) (1)	28
CONDUCTED EMISSIONS	§15.107/207	43
RECEIVER SPURIOUS RADIATION	§15.209	44
TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS		49
BLOCK DIAGRAMS		50

CARRIER FREQUENCY SEPERATION

§15.247(a)



Date: 19.OCT.2004 17:04:16

NUMBER OF HOPPING CHANNELS**§15.247(a)****The number of hopping channels is 79**


Date: 19.OCT.2004 17:16:13

TIME OF OCCUPANCY (DWELL TIME)
DH1 – Packet
§15.247(a)

The system makes worst case 1600 hops per second or 1 time slot has a length of 625 μ s with 79 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case 800 hops per second with 79 channels. So you have each channel 10.13 times per second and so for 31.6 seconds you have 320.108 times of appearance.

Each Tx-time per appearance is 414.67 μ s.

So we have 320.108 * 414.67 μ s = 132.73ms per 31.6 seconds.




TIME OF OCCUPANCY (DWELL TIME)
DH3 – Packet**§15.247(a)**

A DH3 Packets need 3 time slots for transmit and 1 for receiving, then the system makes worst case 400 hops per second with 79 channels. So you have each channel 5.1 times per second and so for 31.6 seconds you have 161.16 times of appearance.

Each Tx-time per appearance is 1.67ms.

So we have $161.16 \times 1.67\text{ms} = 269.13\text{ms}$ per 31.6 seconds.




Date: 20.OCT.2004 13:08:52

TIME OF OCCUPANCY (DWELL TIME)
DH5 – Packet**§15.247(a)**

At DH5 Packets you need 5 time slots for transmit and 1 for receiving, then the system makes worst case 266,7 hops per second with 79 channels. So you have each channel 3.36 times per second and so for 30 seconds you have 106.176 times of appearance.

Each Tx-time per appearance is 2.91ms.

So we have $106.176 \times 2.91\text{ms} = 309.97\text{ms}$ per 31.6 seconds.




SPECTRUM BANDWIDTH OF FHSS SYSTEM **§15.247(a)**
20 dB bandwidth


TEST CONDITIONS		20 dB BANDWIDTH (kHz)		
Frequency (MHz)		2402	2441	2480
$T_{\text{nom}}(23)^\circ\text{C}$	V_{nom}	825.65	829.65	829.65

RBW / VBW as provided in the "Measurement Guidelines" (DA 00-705, March 30, 2000)


LIMIT**SUBCLAUSE §15.247(a) (1)**

The maximum 20dB bandwidth shall be at maximum 1000 KHz

SPECTRUM BANDWIDTH OF FHSS SYSTEM
20 dB bandwidth**§15.247(a)****Lowest Channel: 2402MHz**

**SPECTRUM BANDWIDTH OF FHSS SYSTEM
20 dB bandwidth****§15.247(a)****Mid Channel: 2441MHz**

Date: 19.OCT.2004 16:51:11

SPECTRUM BANDWIDTH OF FHSS SYSTEM
20 dB bandwidth**§15.247(a)****Highest Channel: 2480MHz**

Date: 19.OCT.2004 16:49:36


**MAXIMUM PEAK OUTPUT POWER
(Conducted)****§ 15.247 (b) (1)**

TEST CONDITIONS		MAXIMUM PEAK OUTPUT POWER (dBm)		
Frequency (MHz)		2402	2441	2480
$T_{\text{nom}}(23)^\circ\text{C}$	V_{nom}	-0.55	-0.23	-0.13
Measurement uncertainty		$\pm 0.5\text{dBm}$		


RBW / VBW: 3 MHz

LIMIT**SUBCLAUSE § 15.247 (b) (1)**


Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

PEAK OUTPUT POWER (CONDUCTED)**§15.247 (b)****Lowest Channel: 2402MHz**

Date: 19.OCT.2004 16:46:42

PEAK OUTPUT POWER (CONDUCTED)**§15.247 (b)****Mid Channel: 2441MHz**

Date: 19.OCT.2004 16:47:15

PEAK OUTPUT POWER (CONDUCTED)**§15.247 (b)****Highest Channel: 2480MHz**

Date: 19.OCT.2004 16:47:44

**MAXIMUM PEAK OUTPUT POWER
(RADIATED)****§ 15.247 (b) (1)****EIRP:**

TEST CONDITIONS		MAXIMUM PEAK OUTPUT POWER (dBm)		
Frequency (MHz)		2402	2441	2480
T _{nom} (23)°C	V _{nom}	-2.2	-2.85	-2.98
Measurement uncertainty		±0.5dBm		

RBW/VBW: 3 MHz


LIMIT**SUBCLAUSE § 15.247 (b) (1)**

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

PEAK OUTPUT POWER (RADIATED)**§15.247 (b) (1)****Lowest Channel: 2402MHz**

SWEEP TABLE: "EIRP BT low channel"


Start Frequency	Stop Frequency	Detector	Meas.	IF
2.397GHz	2.407GHz	MaxPeak	Coupled	3 MHz



PEAK OUTPUT POWER (RADIATED)**§15.247 (b) (1)****Mid Channel: 2441MHz**

SWEEP TABLE: "EIRP BT Mid channel"


Start Frequency	Stop Frequency	Detector	Meas.	IF
2.436GHz	2.446GHz	MaxPeak	Time Coupled	BW 3 MHz



PEAK OUTPUT POWER (RADIATED)**§15.247 (b) (1)****Highest Channel: 2480MHz**

SWEEP TABLE: "EIRP BT High channel"


Short Description:	EIRP Bluetooth channel-2480MHz			
Start Frequency	Stop Frequency	Detector	Meas.	IF
2.475GHz	2.485GHz	MaxPeak	Time Coupled	3 MHz



BAND EDGE COMPLIANCE**§15.247 (c)****Low frequency section (spurious in the restricted band 2310 – 2390 MHz)****Average Measurement****(This plot is valid for both Hopping ON & OFF)**

Operating condition : Tx at 2402MHz
SWEEP TABLE : "FCC15.247 LBE_AVG"
Short Description : FCC15.247 BT Low-band-edge
Limit Line : 54dB μ V


Start Frequency	Stop Frequency	Detector Time	Meas. Bandw.	RBW	VBW	Transducer
2.31 GHz	2.412 GHz	MaxPeak	Coupled	1 MHz	10Hz	#326 horn (dBi)



BAND EDGE COMPLIANCE**§15.247 (c)****Low frequency section (spurious in the restricted band 2310 – 2390 MHz)****Peak Measurement****(This plot is valid for both Hopping ON & OFF)**

Operating condition : Tx at 2402MHz
SWEEP TABLE : "FCC15.247 LBE_Pk"
Short Description : FCC15.247 BT Low-band-edge
Limit Line : 74dB μ V


Start Frequency	Stop Frequency	Detector Time	Meas. Bandw.	RBW	VBW	Transducer
2.31 GHz	2.412 GHz	MaxPeak	Coupled	1 MHz	1MHz	#326 horn (dBi)



BAND EDGE COMPLIANCE**§15.247 (c)****High frequency section (spurious in the restricted band 2483.5 – 2500 MHz)****Average Measurement****(This plot is valid for both Hopping ON & OFF)**

Operating condition : Tx at 2480MHz
SWEEP TABLE : "FCC15.247 HBE_AVG"
Short Description : FCC15.247 BT High-band-edge
Limit Line : 54dB μ V


Start Frequency	Stop Frequency	Detector Time	Meas. Bandw.	RBW	VBW	Transducer
2.462 GHz	2.5 GHz	MaxPeak	Coupled	1 MHz	10Hz	#326 horn (dBi)



BAND EDGE COMPLIANCE**§15.247 (c)****High frequency section (spurious in the restricted band 2483.5 – 2500 MHz)****Peak Measurement****(This plot is valid for both Hopping ON & OFF)**

Operating condition : Tx at 2480MHz
SWEEP TABLE : "FCC15.247 HBE_PK"
Short Description : FCC15.247 BT High-band-edge
Limit Line : 74dB μ V


Start Frequency	Stop Frequency	Detector Time	Meas. Bandw.	RBW	VBW	Transducer
2.462 GHz	2.5 GHz	MaxPeak	Coupled	1 MHz	1MHz	#326 horn (dBi)



**EMISSION LIMITATIONS
Transmitter (Conducted)
LIMITS****§ 15.247 (c) (1)**

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions that fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

NOTE: Frequency resolution is not fine enough to show the exact frequency of the carrier, refer to plots under EIRP.


EMISSION LIMITATIONS - Conducted (Transmitter)**§ 15.247 (c) (1)****Lowest Channel (2402MHz): 30MHz - 25GHz**

Date: 19.OCT.2004 16:54:43


EMISSION LIMITATIONS - Conducted (Transmitter)

§ 15.247 (c) (1)

Mid Channel (2441MHz): 30MHz - 25GHz



Date: 19.OCT.2004 16:55:28

EMISSION LIMITATIONS - Conducted (Transmitter)**§ 15.247 (c) (1)****Highest Channel (2480MHz): 30MHz - 25GHz**

Date: 19.OCT.2004 16:56:26

**EMISSION LIMITATIONS
Transmitter (Radiated)****§ 15.247 (c) (1)****LIMITS**

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions that fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

NOTE:

1. The radiated emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels. In the range between 3 and 26.5 GHz very short cable connections to the antenna was used to minimize the noise level.
2. Frequency resolution is not fine enough to show the exact frequency of the carrier, refer to plots under EIRP.
3. All measurements are done in peak mode unless specified with plots.

Results for the radiated measurements below 30MHz according § 15.33

Frequency	Measured values	Remarks
9KHz – 30MHz	No emissions found, caused by the EUT	This is valid for all the tested channels

EMISSION LIMITATIONS - Radiated (Transmitter)**§ 15.247 (c) (1)**

Note: All radiated measurements were made in all three orthogonal planes. The values reported are the maximum values.

Transmit at Lowest channel Frequency 2402MHz			
Frequency (MHz)	Level (dB μ V/m)		
	Peak	Quasi-Peak	Average
4781	42.03		25
7200.4	50.24		30.66


Transmit at Middle channel Frequency 2441MHz			
Frequency (MHz)	Level (dB μ V/m)		
	Peak	Quasi-Peak	Average
4884	41.77		25.27
7303	47.97		30.46

Transmit at Highest channel Frequency 2480MHz			
Frequency (MHz)	Level (dB μ V/m)		
	Peak	Quasi-Peak	Average
4951	43.78		25.66
7438	44.14		28.77

EMISSION LIMITATIONS - Radiated (Transmitter)**§ 15.247 (c) (1)****30MHz – 1GHz****Antenna: vertical****Note: This plot is valid for low, mid & high channels (worst-case plot)**

SWEEP TABLE: "BT Spuri hi 30-1G"
Short Description: Bluetooth 30MHz-1GHz


Start Frequency	Stop Frequency	Detector	Meas.	RBW	Transducer
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	3141-#1186



EMISSION LIMITATIONS - Radiated (Transmitter)**§ 15.247 (c) (1)****30MHz – 1GHz****Antenna: horizontal****Note: This plot is valid for low, mid & high channels (worst-case plot)**

SWEEP TABLE: "BT Spuri hi 30-1G"
Short Description: Bluetooth 30MHz-1GHz

Start Frequency	Stop Frequency	Detector	Meas.	RBW	Transducer
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	3141-#1186




EMISSION LIMITATIONS - Radiated (Transmitter)
Lowest Channel (2402MHz): 1GHz – 3GHz**§ 15.247 (c) (1)****NOTE: The peak above the limit is the carrier frequency.**

SWEEP TABLE: "BT Spuri hi 1-3G"

Short Description: Bluetooth Spurious 1-3GHz

Start Frequency	Stop Frequency	Detector	Meas.	RBW	Transducer
1.0 GHz	3.0 GHz	Time	Bandw.	VBW	
		MaxPeak	Coupled	1 MHz	#326 horn (dBi)



EMISSION LIMITATIONS - Radiated (Transmitter)**§ 15.247 (c) (1)****Lowest Channel (2402MHz): 3GHz – 18GHz****Average**

SWEEP TABLE:

"BT Spuri hi 3-18G"

Short Description:

Bluetooth Spurious 3-18 GHz

Start Frequency

Detector

Meas.

RBW

Transducer

Stop Frequency

Time

Bandw.

VBW

3.0 GHz


MaxPeak

Coupled

1 MHz

10Hz


#326 horn (dBi)



EMISSION LIMITATIONS - Radiated (Transmitter)
Middle Channel (2441MHz): 1GHz – 3GHz**§ 15.247 (c) (1)****NOTE: The peak above the limit is the carrier frequency.**

SWEEP TABLE: "BT Spuri hi 1-3G"
Short Description: Bluetooth Spurious 1-3GHz

Start Frequency	Stop Frequency	Detector Time	Meas. Bandw.	RBW	VBW	Transducer
1.0 GHz	3.0 GHz	MaxPeak	Coupled	1 MHz		#326 horn (dBi)




EMISSION LIMITATIONS - Radiated (Transmitter)**§ 15.247 (c) (1)****Middle Channel (2441MHz): 3GHz – 18GHz****Average**

SWEEP TABLE: "BT Spuri hi 3-18G"

Short Description: Bluetooth Spurious 3-18GHz

Start Frequency	Stop Frequency	Detector	Meas.	RBW	VBW	Transducer
3.0 GHz	18.0 GHz	Time	Bandw.			
		MaxPeak	Coupled	1 MHz	10Hz	#326 horn (dBi)




EMISSION LIMITATIONS - Radiated (Transmitter)**§ 15.247 (c) (1)****Highest Channel (2480MHz): 1GHz – 3GHz****NOTE: The peak above the limit is the carrier frequency.**

SWEEP TABLE: "BT Spuri hi 1-3G"


Short Description: Bluetooth Spurious 1-3GHz

Start Frequency	Stop Frequency	Detector	Meas.	RBW	Transducer
1.0 GHz	3.0 GHz	Time	Bandw.	VBW	
		MaxPeak	Coupled	1 MHz	#326 horn (dBi)



EMISSION LIMITATIONS - Radiated (Transmitter)**§ 15.247 (c) (1)****Highest Channel (2480MHz): 3GHz – 18GHz****Average**


SWEEP TABLE: "BT Spuri hi 3-18G"
Short Description: Bluetooth Spurious 3-18GHz
Start Stop Detector Meas. RBW Transducer
Frequency Frequency Time Bandw. VBW
3.0 GHz 18.0 GHz MaxPeak Coupled 1 MHz 10Hz #326 horn (dBi)



EMISSION LIMITATIONS - Radiated (Transmitter) **§ 15.247 (c) (1)**
18GHz – 26.5GHz**Note: This plot is valid for low, mid & high channels (worst-case plot)**

SWEEP TABLE: "BT Spuri hi 18-26.5G"
Short Description: Bluetooth Spurious 18-26.5GHz

Start Frequency	Stop Frequency	Detector	Meas.	RBW	Transducer
18 GHz	26.5 GHz	Time	Bandw.	VBW	
		MaxPeak	Coupled	1 MHz	#141 horn (dBi)



CONDUCTED EMISSIONS

§ 15.107/207

Measured with AC/DC power adapter model# Nokia ACP-7U

Technical specification: 15.107 / 15.207 (Revised as of August 20, 2002)

Limit

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50


* Decreases with logarithm of the frequency

ANALYZER SETTINGS: RBW = 10KHz

VBW = 10KHz

MEASUREMENT RESULT: "test_fin AV"

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
16.000000	43.30	0.0	50	6.7	N	GND



RECEIVER SPURIOUS RADIATION**§ 15.209****Limits**

Frequency (MHz)	Field strength (μ V/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

NOTE:


1. The radiated emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels. In the range between 3 and 26.5 GHz very short cable connections to the antenna was used to minimize the noise level.
2. All measurements are done in peak mode unless specified with the plots.

RECEIVER SPURIOUS RADIATION**§ 15.209****30MHz – 1GHz****Antenna: vertical (worst-case plot)**

SWEEP TABLE: "BT Spuri hi 30-1G"

Short Description: Bluetooth 30MHz-1GHz


Start Frequency	Stop Frequency	Detector	Meas.	RBW	Transducer
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	3141-#1186



**RECEIVER SPURIOUS RADIATION
1GHz – 3GHz****§ 15.209**

SWEEP TABLE: "BT Spuri hi 1-3G"
Short Description: Bluetooth Spurious 1-3GHz


Start Frequency	Stop Frequency	Detector	Meas.	RBW	Transducer
1.0 GHz	3.0 GHz	Time	Bandw.	VBW	#326 horn (dBi)
		MaxPeak	Coupled	1 MHz	



**RECEIVER SPURIOUS RADIATION
3GHz – 18GHz****§ 15.209**


SWEEP TABLE: "BT Spuri hi 3-18G"
Short Description: Bluetooth Spurious 3-18 GHz

Start Frequency	Stop Frequency	Detector	Meas.	RBW	Transducer
3.0 GHz	18.0 GHz	Time	Bandw.	VBW	
		MaxPeak	Coupled	1 MHz	#326 horn (dBi)




**RECEIVER SPURIOUS RADIATION
18GHz – 26.5GHz****§ 15.209**

SWEEP TABLE: "BT Spuri hi 18-26.5G"
Short Description: Bluetooth Spurious 18-26.5GHz
Start Stop Detector Meas. RBW Transducer
Frequency Frequency Time Bandw. VBW
18.0 GHz 26.5 GHz MaxPeak Coupled 1 MHz #326 horn (dBi)



TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

No	Instrument/Ancillary	Type	Manufacturer	Serial No.
01	Spectrum Analyzer	ESIB 40	Rohde & Schwarz	100107
02	Spectrum Analyzer	FSEM 30	Rohde & Schwarz	826880/010
03	Biconilog Antenna	3141	EMCO	0005-1186
04	Horn Antenna (700M-18GHz)	SAS-200/571	AH Systems	325
05	Horn Antenna (18-26.5GHz)	3160-09	EMCO	1240
06	2-3GHz Band reject filter	BRM50701	Microtronics	6
07	Pre-Amplifier	TS-ANA	Rohde & Schwarz	--
08	Pre-Amplifier	JS4-00102600	Miteq	00616

BLOCK DIAGRAMS**Conducted Testing**

Radiated Testing**ANECHOIC CHAMBER**