

North 710, Yihua Building, Shennan Road, Futian District,

Shenzhen, P. R. China

Telephone: +86-755-29413628,

Fax: +86-755-22639141

FCC ID: SOV8300 IC ID: 5511A-8300

Report No.: FCCIC10-RTE082002

Page: 1 of 68

TEST REPORT

Application No.: FCC&IC10-RTE07207RF

Applicant: ARCHOS S.A.

Address of Applicant: 12 Rue Ampere ZI 91430 Igny, France

FCC ID: SOV8300 **IC ID**: 5511A-8300

Fundamental Carrier

Frequency: 2.402GHz to 2.480GHz

Equipment Under Test (EUT):

EUT Name: A43 Internet Tablet

Item No.: 8300

Serial No.: Not supplied by client

Standards: FCC PART 15 Subpart C: 2008

RSS-210 Issue 7 July 2007 RSS-Gen Issue 2 July 2007

Date of Receipt: 20 July. 2010

Date of Test: 22 July. 2010 to 15 August. 2010

Date of Issue: 20 August. 2010

Test Result : PASS*

Authorized Signature:

Kavin Yu Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of EBO Technology Approvals or testing done by EBO Technology Approvals in connection with, distribution or use of the product described in this report must be approved by EBO Technology Approvals in writing. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: FCCIC10-RTE082002

Page: 2 of 68

1 Test Summary

Test	Test Requirement	Standard Paragraph	Result	
	FCC PART 15:2008	Section 15.207	PASS	
Conducted Emissions	RSS-Gen:2007	Section 7.2.2	PASS	
	FCC PART 15:2008	Section 15.205/15.209		
Radiated Emissions	RSS-210:2007 A 8.5		PASS	
	RSS-Gen:2007	Secion 7.2.3		
Maximum Peak Output	FCC PART 15:2008	Section 15.247 (b)	PASS	
Power	RSS-210:2007	A 8.4(2)	17.00	
20 dB Occupied	FCC PART 15:2008	Section 15.247 (a)(1)	PASS	
Bandwidth	RSS-210:2007	A 8.1(a)	1 700	
99% Occupied Bandwidth	RSS-Gen:2007	Section 4.6	PASS	
Carrier Frequency	FCC PART 15:2008	Section 15.247 (a)(1)	PASS	
Separation	RSS-210:2007	A 8.1(b)		
Number of Hopping	FCC PART 15:2008	Section 15.247 (a)(1)(iii)	PASS	
Frequencies	RSS-210:2007	A 8.4(2)	1 700	
	FCC PART 15:2008	Section 15.247 (a)(1)(iii)	PASS	
Time of Occupancy	RSS-210:2007	A 8.1(d)	FASS	
Band Edges and	FCC PART 15:2008	Section 15.247(d)	PASS	
Conducted Spurious Emissions Measurement	RSS-210:2007	A 8.5	PASS	
Antenna requirement.	FCC PART 15:2008	Section 15.247 (b)	PASS	
RF Exposure Compliance	FCC PART 15:2008	15.247(b)(4)& 1) c) D01 Mobile Portable RF Exposure v04	PASS	
Requirement	RSS-102:2010	Section 2.5.1		

FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 3 of 68

2 Contents

		Page
1	TEST SUMMARY	2
_	CONTENTS	•
2	CONTENTS	
3	GENERAL INFORMATION	5
	3.1 CLIENT INFORMATION	5
	3.2 GENERAL DESCRIPTION OF E.U.T.	
	3.3 TEST SUPPORTING SYSTEM DETAILS	
	3.4 TEST LOCATION	
	3.5 TEST FACILITY	
	3.6 MEASUREMENT UNCERTAINTY	8
	3.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
4	EQUIPMENT USED DURING TEST	9
5		
	5.1 CONDUCTED EMISSIONS	
	5.1.1 Test Setup	
	5.1.2 Test Procesure	
	5.1.3 Measurement Data	
	5.2 RADIATED EMISSIONS	
	5.2.1 Test Setup	
	5.2.2 Test Prosesure	
	5.2.3 Measurement Data	
	5.3 MAXIMUN PEAK OUTPUT POWER	
	5.3.1 Test Setup	
	• • • • • • • • • • • • • • • • • • • •	
	5.4.1 Test Setup	
	5.5 99% Occupied Bandwidth	
	5.5.1 Test Setup	
	5.5.2 Measurement Data	
	5.6 CARRIER FREQUENCY SEPARATION	
	5.6.1 Test Setup	
	5.6.2 Measurement Data	
	5.7 NUMBER OF HOPPING FREQUENCIES	
	5.7.1 Test Setup	
	5.7.2 Measurement Data	
	5.8 TIME OF OCCUPY (DWELL TIME)	
	5.8.1 Test Setup	
	5.8.2 Measurement Data	
_		
F	FCC ID: SOV 8300	
10	C ID: 55114-8300	



Report No.: FCCIC10-RTE082002

Page: 4 of 68

5.9	BAND EDGE AND CONDUTED SPURIOUS EMISSIONS MEASUREMENT	. 57
5.9.	1 Test Setup	. 57
	2 Measurement Data	
	ANTENNA REQUIREMENT	
	RF EXPOSURE COMPLIANCE	

FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 5 of 68

3 General Information

3.1 Client Information

Applicant: ARCHOS S.A.

Address of Applicant: 12 Rue Ampere ZI 91430 Igny, France

3.2 General Description of E.U.T.

Equipment Under Test: Wireless Data Transmission (Bluetooth)

Trade Name: ARCHOS

Type Designation: A43 Internet tablet

Model Number: 8300

Type of modulation: GFSK, Pi/4QPSK,8DPSK

Number of Channels: 79

Operation Frequency: 2402 ~2480MHz

Antenna Designation: PCB Antenna

Antenna Gain: 0dBi

Power Supply: Lithium polymer battery 3.7V

(The new battery be used during testing)

Date of Test: July 22,, 2010 to August 15, 2010

FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 6 of 68

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2480
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2402	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2447	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

Note:

Regards to the frequency band over 10MHz, the lowest, middle and highest frequency of channel were selected to perform the test, and then shown on this report.

So the there channel as follow:

Lowest channel: 2402MHz Middle channel: 2447MHz Highest channel: 2480 MHz

FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 7 of 68

3.3 Test Supporting System Details

Equipment Name	Modle No.	Manufacturer	FCC Status
PC	M2700	Lenovo	DOC
Monitor	TFT1780PS	AOV	DOC
Printer	LaserJet P2014	HP	DOC
Keyboard	JME7053	Lenovo	DOC
Mouse	N/A	Lenovo	DOC

3.4 Test Location

All tests were sub-contracted to:

ATC Lab Co., Ltd (Guangdong, China).

205#, Yingfeng Building, Ronggu Rd, Foshan, Guangdong, China (528305)

Phone:0757-23612690 Fax:0757-23612537

FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 8 of 68

3.5 Test Facility

IC-Registration No.: 415467

ATC Lab Co., Ltd (Guangdong, China) EMC Laboratory has been registered and fully described in a report filed with the IC (Federal Communications Commission). The acceptance letter from the IC is maintained in our files. Registration 415467. Listing date October 10, 2008.

IC-Registration No.: 7949A

The 3m Alternate Test Site of ATC Lab Co., Ltd (Guangdong, China) has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 7949A on Oct. 29th, 2008.

3.6 Measurement Uncertainty

of +/- 3×10⁻⁹ for Carrier Frequency Separation Measurement

of +/- 3×10⁻⁹ for Number of Hopping Frequencies Measurement

of +/- 3×10⁻⁹ for 20dB Bandwidth Measurement

of +/- 3×10⁻⁹ for Time of Occupancy (Dwell time) Measurement

of +/- 0.8 dB for Peak Output Power Measurement

of +/- 0.8 dB for Band Edge RF Conducted Measurement

of +/- 0.8 dB for Spurious RF Conducted Emission Measurement

of +/- 4.5 dB for Radiated Emissions

of +/- 2.3 dB for Conducted Emissions

3.7 Other Information Requested by the Customer

None

FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 9 of 68

4 Equipment Used during Test

Conducted Emi	ssion				
No.	Test Equipment	Manufacturer	Mo del No.	Serial No.	Cal. Due Date
GAL-EMC002	Shielding Room	ETS	N/A	N/A	2011-05-18
GAL-EMC003	Receiver	SCHAFFNER	SMR4503	11725	2011-07-08
GAL-EMC005	Line impedance stabilization network	EMCO	4825/2	1161	2011-07-08
GAL-EMC098	Line impedance stabilization network	EMCO	3810/2	2516	2011-07-08
RF in Chamber					
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Due Date
GAL-EMC001	Semi-anechoic Chamber	ETS	N/A	N/A	2011-05-25
GAL-EMC003	Receiver	SCHAFFNER	SMR4503	11725	2011-07-08
GAL-EMC007	Double-ridged Wave guide horn	ETS	3115	6587	2011-08-02
GAL-EMC008	Microwave system amplifier (0.5G-26.5G)	Agilent	83017A	MY3950043 8	2011-07-08
GAL-EMC017	Biconilog Antenna	ETS	3142C	00042672	2010-09-26
GAL-EMC055	Band-pass Filter	Micro-Tronic	BRM50702	S/N-030	2010-11-09
GAL-EMC056	Spectrum Analyzer 9KHz-30GHz	R&S	FSP30	100755	2010-11-02
GAL-EMC075	Double-ridged Wave guide horn	ETS	3160	00052486	2011-08-02
RF Conducted					
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Due Date
GAL-EMC056	Spectrum Analyzer 9KHz-30GHz	R&S	FSP30	100755	2010-11-02
GAL-EMC100	ATC-Lab	N/A	N/A	N/A	2010-11-02
	•	•		•	•

FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 10 of 68

5 Test Results

5.1 Conducted Emissions

Test Requirement: FCC Part15 B Section 15.207

RSS-Gen Section 7.2.2

Test Method: ANSI C63.4:2003 Frequency Range: 150KHz to 30MHz

Class/Severity: Class B

Detector: Peak for pre-scan (9 kHz resolution bandwidth)

Test Mode: Bluetooth mode (PC Active with the EUT in Bluetooth mode)

Test Voltage: 120Vac,60Hz
Test Date: 22 July. 2010

Temperature: 23° C Humidity: 54%

Limit: (a) Except as shown in paragraphs (b) and (c) of this section, for an

intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit

applies at the boundary between the frequency ranges.

Frequency of Emission (MHz)	Conducted Limit (dBuV)		
	Quasi-peak	Average	
0.15-0.5	66 to 56 *	56 to 46 *	
0.5-5	56	46	
5-30	60	50	

^{*} Decreases with the logarithm of the frequency.


FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 11 of 68

5.1.1 Test Setup



5.1.2Test Procesure

The Device was conneted to the artifical main network via PC(refer to section 3.3 for details), And test the EUT with actived in bluetooth receive mode and transmit mode.

5.1.3Measurement Data

Measure the maximised peak emissions from the EUT for both the Live and Neutral Lines. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

PC Active with the EUT in transmit mode

Frequency (MHz)	Line	Measured QP (dBuV)	QP Limit (dBuV)	Measured AV (dBuV)	AV Limit (dBuV)	Over Limit QP	Over Limit AV
0.1650	L	40.90	65.13	12.30	55.13	-24.23	-42.83
0.2650	L	29.30	61.23	13.40	51.23	-31.93	-37.83
0.3600	L	26.20	58.71	17.20	48.71	-32.51	-31.51
2.1800	L	23.10	56.00	15.90	46.00	-32.90	-30.10
7.7500	L	26.60	60.00	17.40	50.00	-33.40	-32.60
10.6100	L	28.10	60.00	21.10	50.00	-31.90	-28.90
0.1500	N	44.30	65.92	29.30	55.92	-21.62	-26.62
0.2150	N	35.00	62.95	15.80	52.95	-27.95	-37.15
2.1850	N	24.40	56.00	23.00	46.00	-31.60	-23.00
7.8650	N	28.80	60.00	23.70	50.00	-31.20	-26.30
8.2300	N	29.20	60.00	23.40	50.00	-30.80	-26.60
10.7800	N	30.50	60.00	25.20	50.00	-29.50	-24.80

Test result: The unit does meet the requirements.

Test result plot as follows:

FCC ID: SOV 8300 IC ID: 5511A-8300




Report No.: FCCIC10-RTE082002

Page: 12 of 68

Live Line

	A43	
e(s)		Range 1
		150 kHz
		30 MHz
		5 kHz
		Auto
(Pre)		AV CISPR
(Pre)		9 kHz
(Pre)		10 ms
(Final)		QP
(Final)		9 kHz
(Final)		1 6
(Final)		20
	(Pre) (Pre) (Pre) (Pinal) (Final) (Final)	(Pre) (Pre) (Pre) (Pinal) (Final) (Final)



FCC ID: SOV 8300 IC ID: 5511A-8300




Report No.: FCCIC10-RTE082002

Page: 13 of 68

Nuetral Line

Туре		A48	
Frequency Rang	(e(s)		Range 1
Start Frequency			150 kHz
Stop Frequency	,		30 MHz
Step Frequency	,		5 kHz
Attenuator			Auto
Detector	(Pre)		AV CISPR
IF Bandwidth	(Pre)		9 kHz
Measure Time	(Pre)		10 ms
Detector	(Final)		QP
IF Bandwidth	(Final)		9 kHz
Measure Time	(Final)		1 s
Sub Ranges	(Final)		20



FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 14 of 68

5.2 Radiated Emissions

Test Requirement: FCC Part15 C Section 15.247,15.209 and 15.205

RSS-210 A 8.5 and RSS-Gen Section 7.2.3

Test Method: ANSI C63.4:2003 **Frequency Range:** 30MHz to 25GHz

Receiver Setup: QP Detector (RBW=120 kHz,VBW=300kHz) for 30 to 1000 MHz RE testing

Peak Detector(RBW=1MHz,VBW=3MHz) for 1 to 25 GHz RE Peak value

testing

Peak Detector(RBW=1MHz, VBW=10Hz) for 1 to 25 GHz RE AV value testing

Test Mode: Blue tooth transmit and receiver mode

Test Date: 22 July. 2010 to 25 July. 2010

Temperature: 23° C~25°CHumidity:50%~55%

Limit: The field strength of radiated emissions from unintentional radiators at a

distance of 3 meters shall not exceed the following values:

Frequency of Emission	Field Strength	
(MHz)	(microvolts/meter)	dB (μV/m)
30 - 88	100	40(QP)
88 - 216	150	43.5(QP)
216 - 960	200	46(QP)
960-1000	500	54(QP)
Above 1000	500	54(AV)
		74(PK)

FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 15 of 68

5.2.1 Test Setup




Figure 1: 30MHz to 1GHz radiated emissions test setup




Figure 2: Above 1GHz radiated emissions test setup

FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 16 of 68

5.2.2Test Prosesure

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until all frequency measured were complete.

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain

FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 17 of 68

5.2.3Measurement Data

Radiated Emission below 1GHz

Bluetooth function with receiving modes

Frequency	Antenna	Reading	Ant./CL/	Measured	QP Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
			(dB)	(dBuV/m)			
Below 1GHz	Н	_		_	_	Less than	Pass
Below 1GHz	V	_	_	_	_	-30	Pass

Pre-scan the EUT in GFSK,Pi/4QPSK and 8DPSK with transmintting and find out the worst case is GFSK mode in transmitting.

Frequency	Antenna	Reading	Ant./CL/	Measured	QP Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
			(dB)	(dBuV/m)			
36.160	Н	-3.07	18.77	15.70	40.00	-24.30	Pass
479.600	Н	-6.60	19.20	12.60	46.00	-33.40	Pass
619.360	Н	-3.50	22.20	18.70	46.00	-27.30	Pass
808.800	Н	-5.12	24.52	19.40	46.00	-26.60	Pass
957.280	Н	-3.70	26.00	22.30	46.00	-23.70	Pass
-	-	-	ı	-	-	-	-
35.440	V	-3.30	18.70	15.40	40.00	-24.60	Pass
478.960	V	-6.70	19.20	12.50	46.00	-33.50	Pass
658.320	V	-4.10	22.20	18.10	46.00	-27.90	Pass
821.680	V	-5.12	24.72	19.60	46.00	-26.40	Pass
959.360	V	-4.20	26.00	21.80	46.00	-24.20	Pass
-	-	-	-	-	-	-	-

FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 18 of 68

Radiated Emission Above 1GHz

Bluetooth with receiving modes

Peak Measurement

Frequency	Antenna	Reading	Ant./CL/	Measured	PK Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
			(dB)	(dBuV/m)			
2402.000	Н	35.41	-0.54	34.87	74.00	-39.13	Pass
-	ı	-	ı	-	ı	-	-
-	1	-	-	-	-	-	-
-	1	-	1	-	I	-	-
-	-	-	1	-	-	-	-
-	-	-	-	-	-	-	-
2402.000	V	36.80	-0.54	36.26	74.00	-37.74	Pass
-	-	-	-	-	-	-	-
-	1	-	ı	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-

Average Measurement

verage ivicase				T			
Frequency	Antenna	Reading	Ant./CL/	Measured	AV Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
			(dB)	(dBuV/m)			
2402.000	Н	28.24	-0.54	27.70	54.00	-26.30	Pass
-	-	-	ı	-	ı	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
2402.000	V	29.67	-0.54	29.13	54.00	-24.87	Pass
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	_
-	-	-	-	-	-	-	-

FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 19 of 68

Pre-scan the EUT in GFSK,Pi/4QPSK and 8DPSK with transmintting and find out the worst case is GFSK mode in transmitting.

Transmitting mode (GFSK mode Lowest channel=2402MHz)

Peak Measurement

Frequency	Antenna	Reading	Ant./CL/	Measured	PK Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
			(dB)	(dBuV/m)			
1102.000	Н	45.78	-5.10	40.68	74.00	-33.32	Pass
4804.000	Н	43.29	6.10	49.39	74.00	-24.61	Pass
7206.000	Н	42.10	11.80	53.90	74.00	-20.10	Pass
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
1238.000	V	45.80	-4.80	41.00	74.00	-33.00	Pass
4804.000	V	42.75	6.10	48.85	74.00	-25.15	Pass
7206.000	V	41.55	11.80	53.35	74.00	-20.65	Pass
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	

Average Measurement

	crage weadarchient							
Frequency	Antenna	Reading	Ant./CL/	Measured	AV Limit	Over		
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail	
			(dB)	(dBuV/m)				
1102.000	Н	36.20	-5.10	31.10	54.00	-22.90	Pass	
4804.000	Н	28.60	6.10	34.70	54.00	-19.30	Pass	
7206.000	Н	30.10	11.80	41.90	54.00	-12.10	Pass	
-	1	-	1	-	1	-	-	
-	ı	-	ı	-	ı	-	-	
-	-	-	-	-	1	-	-	
1238.000	V	33.52	-4.80	28.72	54.00	-25.28	Pass	
4804.000	V	30.46	6.10	36.56	54.00	-17.44	Pass	
7206.000	V	28.94	11.80	40.74	54.00	-13.26	Pass	
-	1	-	1	-	1	-	-	
-	-	-	-	-	-	-	-	
-	-	-	-	-	-	-	-	

FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 20 of 68

Transmitting mode (GFSK mode Middle channel=2447MHz)

Peak Measurement

Frequency	Antenna	Reading	Ant./CL/	Measured	PK Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
			(dB)	(dBuV/m)			
1102.000	Н	45.31	-5.10	40.21	74.00	-33.79	Pass
4894.000	Н	42.39	6.10	48.49	74.00	-25.51	Pass
7341.000	Н	41.87	11.92	53.79	74.00	-20.21	Pass
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
1102.000	V	45.57	-5.10	40.47	74.00	-33.53	Pass
4894.000	V	40.36	6.10	46.46	74.00	-27.54	Pass
7341.000	V	42.00	11.92	53.92	74.00	-20.08	Pass
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-

Average Measurement

verage incast	ai CiliCili						
Frequency	Antenna	Reading	Ant./CL/	Measured	AV Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
			(dB)	(dBuV/m)			
1102.000	Н	34.25	-5.10	29.15	54.00	-24.85	Pass
4894.000	Н	30.26	6.10	36.36	54.00	-17.64	Pass
7341.000	Н	29.73	11.92	41.65	54.00	-12.35	Pass
-	-	-	•	-	•	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
1102.000	V	32.64	-5.10	27.54	54.00	-26.46	Pass
4894.000	V	29.86	6.10	35.96	54.00	-18.04	Pass
7341.000	V	29.40	11.92	41.32	54.00	-12.68	Pass
-	-	-	•	-	ı	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-

FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 21 of 68

Transmitting mode (GFSK mode Highest channel=2480MHz)

Peak Measurement

Frequency	Antenna	Reading	Ant./CL/	Measured	PK Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
			(dB)	(dBuV/m)			
1170.000	Н	44.89	-5.00	39.89	74.00	-34.11	Pass
4960.000	Н	40.53	6.10	46.63	74.00	-27.37	Pass
7440.000	Н	41.37	12.10	53.47	74.00	-20.53	Pass
-	-	-	-	-	-	-	-
-	ı	-	ı	-	I	-	-
-	-	-	-	-	-	-	-
1238.000	V	44.36	-4.80	39.56	74.00	-34.44	Pass
4960.000	V	41.05	6.10	47.15	74.00	-26.85	Pass
7440.000	V	41.26	12.10	53.36	74.00	-20.64	Pass
-	ı	-	1	-	ı	-	-
-	-	-	-	-	-	-	-
-	-	-		-	-	-	-

Average Measurement

trorage meas	verage measurement							
Frequency	Antenna	Reading	Ant./CL/	Measured	AV Limit	Over		
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail	
			(dB)	(dBuV/m)				
1170.000	Н	33.15	-5.00	28.15	54.00	-25.85	Pass	
4960.000	Η	29.86	6.10	35.96	54.00	-18.04	Pass	
7440.000	Н	28.13	12.10	40.23	54.00	-13.77	Pass	
-	-	-	1	-	1	-	-	
-	ı	-	ı	-	I	-	-	
-	-	-	1	-	1	-	-	
1238.000	V	36.70	-4.80	31.90	54.00	-22.10	Pass	
4960.000	V	30.59	6.10	36.69	54.00	-17.31	Pass	
7440.000	V	30.14	12.10	42.24	54.00	-11.76	Pass	
-	-	-	1	-	1	-	-	
-	-	-	-	-	-	-	-	
-	-	-		-		-	-	

FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002


Page: 22 of 68

Band Edge and Restriced band (Radiated measurement)


Pre-scan the EUT in GFSK,Pi/4QPSK and 8DPSK with transmintting mode and find out the worst case is 8DPSK mode in transmitting.

Transmitting with 8DPSK mode (Lowest channel=2402MHz)

Peak Measurement in Horizontal polarization



Average Measurement in Horizontal polarization



FCC ID: SOV 8300 IC ID: 5511A-8300




Report No.: FCCIC10-RTE082002


Page: 23 of 68

Transmitting with 8DPSK mode (Lowest channel=2402MHz)

Peak Measurement in Vertical polarization



Average Measurement in Vertical polarization




FCC ID: SOV 8300 IC ID: 5511A-8300




Report No.: FCCIC10-RTE082002

Page: 24 of 68

Transmitting with 8DPSK mode (Highest channel=2480MHz) Peak Measurement in Horizontal polarization



Average Measurement in Horizontal polarization




FCC ID: SOV 8300 IC ID: 5511A-8300




Report No.: FCCIC10-RTE082002

Page: 25 of 68

Peak Measurement in Vertical polarization



Average Measurement in Vertical polarization



FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 26 of 68

Remark 1:

No any other emissions level which are attenuated less than 20dB below the limit According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part. Hence there no other emissions have been reported.

Remark 2:

- 1). As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
- 2). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.
- 3) Pre-Scan has been conducted to determine the worst-case mode from all possible Combinations between available modulations, data rates and antenna ports, and found the EUT worse case mode: 8DPSK modulation mode.
- 4) For this intentional radiator operates below 25 GHz. The spectrum shall be investigated to the tenth harmonic of the highest fundamental frequency. And above the 4th harmonic of this intentional radiator, the disturbance is very low. So the test result only displays to 4th harmonic.

Remark 3: Section 15.205 Restricted bands of operation.

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	16.42 - 16.423 399.9 - 410	
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions,or comply with 15.209 limits.

FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 27 of 68

5.3 Maximun Peak Output Power

Test Requirement: FCC 15.247(b)

RSS-210 A 8.4(2)

Test Method: ANSI C63.4:2003 and KDB DA00-705.

Method of Measurement: The EUT was setup to ANSI C63.4, 2003, tested to FHSS test

procedure of KDB DA00-705 for compliance to FCC 47CFR

15.247 requirements.

Detector: RBW=1 MHz, VBW=3 MHz (Peak detector) **Test Mode:** Bluetooth in transmit mode without hopping

Power Supply: Lithium polymer battery 3.7V (The new battery be used during testing)


Test Date: 05 August. 2010

Temperature: 25° C Humidity: 54%

Limit: Regulation 15.247 (b) The Limit of Maximum Peak Output Power

Measurement is 30dBm.

5.3.1Test Setup



FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 28 of 68

5.3.2Measurement Data

For EUT communicating with GFSK Mode

Chanel Frequency (GHz)	Peak Output Power(dBm)	Cable Loss (dB)	Power level(dBm)	Limit (dBm)	Over Limit (dB)
2.402	-4.92	0.5	-4.42	30.00	-34.42
2.447	-8.22	0.5	-7.72	30.00	-37.72
2.480	-11.08	0.5	-10.58	30.00	-40.58

For EUT communicating with Pi/4QPSK Mode

~	or Let communicating with a refreshed						
Ī	Chanel	Peak Output	Cable Loss	Power	Limit	Over Limit	
	Frequency	Power(dBm)	(dB)	level(dBm)	(dBm)	(dB)	
	(GHz)						
Ī	2.402	-4.64	0.5	-4.14	30.00	-34.14	
	2.447	-7.73	0.5	-7.23	30.00	-37.23	
	2.480	-10.55	0.5	-10.05	30.00	-40.05	

For EUT communicating with 8DPSK Mode

	Chanel Frequency (GHz)	Peak Output Power(dBm)	Cable Loss (dB)	Power level(dBm)	Limit (dBm)	Over Limit (dB)
t	2.402	-4.37	0.5	-3.87	30.00	-33.87
Г	2.447	-7.21	0.5	-6.71	30.00	-36.71
	2.480	-8.25	0.5	-7.75	30.00	-37.75

Test result: The unit does meet the requirements.

Test result plot as follows:

FCC ID: SOV 8300 IC ID: 5511A-8300




Report No.: FCCIC10-RTE082002


Page: 29 of 68

The EUT communicating with GFSK Mode

Lowest channel=2402MHz



Middle channel=2447MHz



FCC ID: SOV 8300 IC ID: 5511A-8300




Center 2.48 GHz

Shenzhen EBO Technology Co., Ltd.

Span 5 MHz

Report No.: FCCIC10-RTE082002

Page: 30 of 68



FCC ID: SOV 8300 IC ID: 5511A-8300




Report No.: FCCIC10-RTE082002


Page: 31 of 68

The EUT communicating with Pi/4QPSK Mode

Lowest channel=2402MHz



Middle channel=2447MHz



FCC ID: SOV 8300 IC ID: 5511A-8300




Center 2.48 GHz

Shenzhen EBO Technology Co., Ltd.

Span 5 MHz

Report No.: FCCIC10-RTE082002

Page: 32 of 68



FCC ID: SOV 8300 IC ID: 5511A-8300




Report No.: FCCIC10-RTE082002


Page: 33 of 68

The EUT communicating with 8DPSK Mode

Lowest channel=2402MHz



Middle channel=2447MHz




FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 34 of 68

Highest channel=2480MHz



FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 35 of 68

5.4 20dB Occupied Bandwidth

Test Requirement: FCC 15.247(b)

RSS-210 A 8.1(b)

Test Method: ANSI C63.4:2003 and KDB DA00-705.

Method of Measurement: The EUT was setup to ANSI C63.4, 2003, tested to FHSS test

procedure of KDB DA00-705 for compliance to FCC 47CFR

15.247 requirements.

Detector: RBW=30kHz, VBW=100kHz (Peak detector) **Test Mode:** Bluetooth in transmit mode without hopping

Test Date: 05 August. 2010

Temperature: 24° CHumidity:55%Limit:N/A

5.4.1 Test Setup

EUT Spectrum Analyzer

5.4.2 Measurement Data

Chanel Frequency	20 dB Occupy Bandwidth(MHz)				
(GHz)	GFSK	Pi/4QPSK	8DPSK		
2.402	0.908	0.912	1.128		
2.447	0.908	0.900	1.128		
2.480	0.948	0.916	1.124		

Test result: The unit does meet the requirements.

Test result plot as follows:

FCC ID: SOV 8300 IC ID: 5511A-8300




Report No.: FCCIC10-RTE082002


Page: 36 of 68

The EUT communicating with GFSK Mode

Lowest channel=2402MHz



Middle channel=2447MHz




FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 37 of 68





Span 2 MHz

Report No.: FCCIC10-RTE082002

Page: 38 of 68


The EUT communicating with Pi/4QPSK Mode



200 kHz/

Middle channel=2447MHz

Center 2.402 GHz



FCC ID: SOV 8300 IC ID: 5511A-8300




Center 2.48 GHz

Shenzhen EBO Technology Co., Ltd.

Span 2 MHz

Report No.: FCCIC10-RTE082002

Page: 39 of 68






Report No.: FCCIC10-RTE082002


Page: 40 of 68

The EUT communicating with 8DPSK Mode





Middle channel=2447MHz



FCC ID: SOV 8300 IC ID: 5511A-8300




Highest channel=2480MHz

Shenzhen EBO Technology Co., Ltd.

Report No.: FCCIC10-RTE082002

Page: 41 of 68



-90
Center 2.48 GHz 200 kHz/ Span 2 MHz



Report No.: FCCIC10-RTE082002

Page: 42 of 68

5.5 99% Occupied Bandwidth

Test Requirement: RSS-Gen Section 4.6.1


Test Method: ANSI C63.4:2003

Detector: RBW=30kHz, VBW=100kHz (Peak detector) **Test Mode:** Bluetooth in transmit mode without hopping

Test Date: 05 August. 2010

Temperature: 24° CHumidity:56%Limit:N/A

5.5.1 Test Setup



5.5.2 Measurement Data

Chanel Frequency	99%Occupy Bandwidth(MHz)		
(GHz)	GFSK	Pi/4QPSK	8DPSK
2.402	0.888	0.984	1.080
2.447	0.980	0.948	1.088
2.480	1.108	0.996	1.076

Test result: The unit does meet the requirements.

Test result plot as follows:

FCC ID: SOV 8300 IC ID: 5511A-8300




Report No.: FCCIC10-RTE082002


Page: 43 of 68

The EUT communicating with GFSK Mode

Lowest channel=2402MHz



Middle channel=2447MHz




FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 44 of 68








Report No.: FCCIC10-RTE082002

Page: 45 of 68

The EUT communicating with Pi/4QPSK Mode



Middle channel=2447MHz





FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 46 of 68








Report No.: FCCIC10-RTE082002


Page: 47 of 68

The EUT communicating with 8DPSK Mode





Middle channel=2447MHz



FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 48 of 68







Report No.: FCCIC10-RTE082002

Page: 49 of 68

5.6 Carrier Frequency Separation

Test Requirement: FCC 15.247(a)(1)

RSS-210 A 8.1(b)

Test Method: ANSI C63.4:2003 and KDB DA00-705

Detector: RBW=30kHz,VBW=100 KHz (Peak detector)

Test Mode: Blue tooth transmit with hopping mode

Test Date: 10 August. 2010

Temperature: 24° C Humidity: 51%


Limit: ≥0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)

According to section 5.4

<u> </u>		
Mode	20dB bandwidth (MHz)	Limit(MHz)
	(worse case)	(Carrier Frequencies Separaion)
GFSK	0.948	0.632
Pi/4QPSK	0.916	0.611
8DPSK	1.128	0.752

The limit is 0.752MHz.

5.6.1Test Setup



FCC ID: SOV 8300 IC ID: 5511A-8300




Report No.: FCCIC10-RTE082002

Page: 50 of 68

5.6.2Measurement Data

Pre-scan the EUT in GFSK.Pi/4QPSK and 8DPSK modes and find out the worst case is GFSK mode.



The minimum value of Carrier Frequencies Separaion test is 0.998MHz>0.752MHz

Test result: The unit does meet the requirements.



Report No.: FCCIC10-RTE082002

Page: 51 of 68

5.7 Number of Hopping Frequencies

Test Requirement: FCC 15.247(b)

RSS-210 A 8.4 (2)

Test Method: ANSI C63.4:2003 and KDB DA00-705.

Method of Measurement: The EUT was setup to ANSI C63.4, 2003, tested to FHSS test

procedure of KDB DA00-705 for compliance to FCC 47CFR

15.247 requirements.

Detector: RBW=100kHz, VBW=300kHz (Peak detector)

Test Mode: Bluetooth in transmit with hopping mode


Test Date: 12 August. 2010

Temperature: 25° C

Humidity: 56%

Limit: At least 75 channels

5.7.1Test Setup



5.7.2Measurement Data

Pre-Scan has been conducted to determine the worst-case mode from all possible

Hopping channels numbers	Limit
79	75

Test result: The unit does meet the requirements.


Test result plot as follows:

FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 52 of 68





Report No.: FCCIC10-RTE082002

Page: 53 of 68

5.8 Time of Occupy (Dwell Time)

Test Requirement: FCC 15.247(a)(1)

RSS-210 A 8.1(d)

Test Method: ANSI C63.4:2003 and KDB DA00-705.

Method of Measurement: The EUT was setup to ANSI C63.4, 2003, tested to FHSS test

procedure of KDB DA00-705 for compliance to FCC 47CFR

15.247 requirements.

Detector: RBW=1MHz,VBW=3MHz (Peak detector); Span=0


Test Mode: Blue tooth transmit mode with hopping

Test Date: 12 August. 2010

Temperature: 24° C Humidity: 56%

Limit: ≤0.4Second

5.8.1Test Setup



5.8.2Measurement Data

Pre-Scan has been conducted to determine the worst-case mode from all possible, found that the duty cycle is same in the follow several types.

Packet	Dwell time(second)	Limti(second)
DH1,2-DH1,3-DH1	0.0510	0.4
DH3,2-DH3,3-DH3	0.0344	0.4
DH5,2-DH5,3-DH5	0.2459	0.4

The test period: T=0.4Second/channel \times 79 channel=31.6 s

DH1, 2DH1,3DH1 time slot = 0.16ms \times [$1600/(2\times79)$] $\times31.6=51.2$ ms

DH3, 2DH3,3DH3 time slot = 0.215ms \times [$1600/(4\times79)$] $\times31.6=34.4$ ms

DH5, 2DH5,3DH5 time slot = 2.305ms $\times [1600/(6\times79)] \times 31.6=245.9$ ms

Test result: The unit does meet the requirements.

Test result plots as follows:


FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 54 of 68

GFSK, Pi/4QPSK and 8DPSK mode with DH1,2-DH1, and 3-DH1 test packet.






Report No.: FCCIC10-RTE082002

Page: 55 of 68

GFSK, Pi/4QPSK and 8DPSK mode with DH3,2-DH3, and 3-DH3 test packet.






Report No.: FCCIC10-RTE082002

Page: 56 of 68

GFSK, Pi/4QPSK and 8DPSK mode with DH5,2-DH5,and 3-DH5 test packet.





Report No.: FCCIC10-RTE082002

Page: 57 of 68

5.9 Band Edge and Conduted spurious emissions Measurement

Test Requirement: FCC Part15 C Section 15.247(d)

RSS-210 A 8.5

Test Method: ANSI C63.4; FCC Part15 C Section 15.247,KDB DA00-705 for FHSS

System

Detector: RBW=100 KHz, VBW=300 KHz (Peak detector)

Test Mode: Bluetooth in transmit mode

Test Date: 15 August. 2010


Temperature:24 $^{\circ}$ CHumidity:55%

Limit: RSS-210 A 8.5 In any 100 kHz bandwidth outside the frequency band in

which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF

conducted or a radiated measurement.

5.9.1 Test Setup



5.9.2 Measurement Data

Pre-scan the EUT in hopping and without hopping modes and find out the worst case is without hopping mode

Test result: The unit does meet the requirements.

Test result plot as follows:


FCC ID: SOV 8300 IC ID: 5511A-8300




Report No.: FCCIC10-RTE082002

Page: 58 of 68

Transmitting mode in lowest channel=2402MHz (GFSK)






FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 59 of 68

Transmitting mode in middle channel=2447MHz (GFSK)







Report No.: FCCIC10-RTE082002

Page: 60 of 68

Transmitting mode in highest channel=2480MHz (GFSK)






FCC ID: SOV 8300 IC ID: 5511A-8300




Report No.: FCCIC10-RTE082002

Page: 61 of 68

Transmitting mode in lowest channel=2402MHz (Pi/4QPSK)






FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 62 of 68

Transmitting mode in middle channel=2447MHz (Pi/4QPSK)







Report No.: FCCIC10-RTE082002

Page: 63 of 68

Transmitting mode in highest channel=2480MHz (Pi/4QPSK)






FCC ID: SOV 8300 IC ID: 5511A-8300




Report No.: FCCIC10-RTE082002

Page: 64 of 68

Transmitting mode in lowest channel=2402MHz (8DPSK)






FCC ID: SOV 8300 IC ID: 5511A-8300



Report No.: FCCIC10-RTE082002

Page: 65 of 68

Transmitting mode in middle channel=2447MHz (8DPSK)






Report No.: FCCIC10-RTE082002

Page: 66 of 68

Transmitting mode in highest channel=2480MHz (8DPSK)



FCC ID: SOV 8300 IC ID: 5511A-8300

Start 30 MHz

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.ebotek.cn and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.ebotek.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

Stop 25 GHz



Report No.: FCCIC10-RTE082002

Page: 67 of 68

5.10 Antenna Requirement

Standard requirement

15.203 requirement:

For intentional device. According to 15.203. an intentional radiator shall be designed to Ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz bands that are used exclusively for fixed. Pointto-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.



Report No.: FCCIC10-RTE082002

Page: 68 of 68

5.11 RF Exposure Compliance

Standard requirement

15.247(b)(4) requirement:

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section. if transmitting antennas of directional gain greater than 6 dBi are used. the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1). (b)(2). and (b)(3) of this section. as appropriate. by the amount in dB that the directional gain of the antenna exceeds 6 dBi. RSS-102 Section 2.5.1 requirement:

above 2.2 GHz and up to 3 GHz inclusively, and with output power (i.e. the higher of the conducted or radiated (e.i.r.p.) source-based, time-averaged output power) that is less than or equal to 20 mW for general public use and 100 mW for controlled use;

EUT RF Exposure

The Max Conducted Peak Output Power is **-3.87dBm(0.410mW)** in the lowest channel (2.402GHz); The best case gain of the antenna is 0dBi.

calculate the EIRP test result:

EIRP= 0.410mW (1)

SAR requirement:

S=60 / f(GHz) = 60/2.402 = 24.98 mW ② ;

① < 20mW < ②.

So the SAR report is not required.