

Dynamic Frequency Selection (DFS) Test Report

FCC Part15 Subpart E

Applicant	:	Archos SA
Product	:	9.7inch Tablet
Model No.	:	AC97BPL
Brand Name	:	Qilive
FCC ID	:	SOVAC97BPL
		FCC CFR Title 47 Part 15 Subpart E: 2012
Standards	:	FCC OET Order 06-96A (2006)
		FCC KDB 848637
	:	☐ Master device
Operation Mode		☐ Slaver device with radar detection function
(5250~5350MHz,		
5470~5725MHz)		☒ Slaver device without radar detection function
Test Date	:	July 05, 2013 ~ July 25, 2013

Reviewed By :

Sunny Sun

(Engineer: Sunny Sun)

Approved By :

Marlinchen

(Manager: Marlin Chen)

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date
1306RSU00502	Rev. 01	Initial report	2013-07-28
1306RSU00502	Rev. 02	Updated	2013-09-03
1306RSU00502	Rev. 03	Updated report	2013-09-18
1306RSU00502	Rev. 04	Updated report	2013-09-22

CONTENTS

Description	Page
1. General Information	4
1.1. Applicant.....	4
1.2. Manufacturer	4
1.3. Feature of Product.....	4
1.4. Testing Facility	5
1.5. Standard Requirement	6
1.6. UNII Device Description	6
1.7. Test Equipment.....	7
1.8. Test Setup	7
1.9. Limits	9
1.10. Radar Waveform Calibration	13
1.11. Radar Waveform Calibration Result	14
2. Channel Move Time and Channel Closing Transmission Time	17
2.1. Test Procedure	17
2.2. Test Requirement	17
2.3. Uncertainty	17
2.4. Test Result of Channel Move Time and Channel Closing Transmission Time	18
3. Non-Occupancy Period	20
3.1. Test Procedure	20
3.2. Test Requirement	20
3.3. Uncertainty	20
3.4. Test Result of Non-Occupancy Period	21

1. General Information

1.1. Applicant

Archos SA
12 rue Ampere, 91430 Igny, France

1.2. Manufacturer

Archos SA
12 rue Ampere, 91430 Igny, France

1.3. Feature of Product

Product Name	9.7inch Tablet
Model No.	AC97BPL
Brand Name	Qilive
DFS Frequency Range	5250-5350MHz, 5470-5725MHz
Channel Number	802.11a/n-20MHz: 10
Type of Modulation	802.11a/n: OFDM
Data Rate	802.11a: 6 - 54Mbps 802.11n: up 150Mbps
Channel Control	Auto
Antenna Delivery	1Tx + 1Rx
Peak Antenna Gain	2dBi for 5.0GHz
Max Peak Power	802.11a: 5.47 dBm; 802.11n(20MHz): 5.16 dBm

802.11a/n-20MHz Center Working Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 52:	5260 MHz	Channel 56:	5280 MHz	Channel 60:	5300 MHz
Channel 64:	5320 MHz	Channel 100:	5500 MHz	Channel 104:	5520 MHz
Channel 108:	5540 MHz	Channel 112:	5560 MHz	Channel 116:	5580 MHz
Channel 132:	5660 MHz	Channel 136:	5680 MHz	Channel 140:	5700 MHz

Note : Device operating in 5150 -5250 MHz will be restricted to indoor operations only.

1.4. Testing Facility

Test Site	QuieTek Technology (Suzhou) Co., Ltd.
Test Site Location	No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech Development Zone., Suzhou, China
FCC Registration Number	800392

1.5. Standard Requirement

FCC Part 15.407:

U-NII devices operating in the 5.25-5.35 GHz band and the 5.47-5.725 GHz band shall employ a TPC mechanism. The U-NII device is required to have the capability to operate at least 6 dB below the mean EIRP value of 30dBm. A TPC mechanism is not required for systems with an E.I.R.P. of less than 500mW.

1.6. UNII Device Description

The UUT operates in the following band: 5250-5350MHz, 5470-5725 MHz

The UUT is a Client Device that does not have radar detection capability and ad-hoc function. The highest gain antenna assembly utilized with the EUT has a maximum gain of 2dBi in 5GHz frequency band. The 50-ohm Tx/Rx antenna port is connected to the test system to perform conducted tests. All test ports are proved to be 50-ohm. TPC is not required since the maximum EIRP is less than 500mW (27dBm).

The UUT utilizes 802.11a/n IP based architecture. One nominal channel bandwidth, 20 MHz is implemented.

WLAN traffic is generated by streaming the video file "TestFile.mp2" from the Master device to the Slave device in full motion video mode using the "Nero Show Time 3" with the V3.0.1.3 Codec package.

The master device is a Cisco 802.11a/b/g/n Access Point. The Cisco Access Point contains FCC ID: LDK 102061.

The UUT is a client device without radar detection therefore the interference threshold level is not required.

Statement: Information regarding the parameters of the detected Radar Waveforms is not available to the end user.

1.7. Test Equipment


Dynamic Frequency Selection (DFS)

Instrument	Manufacturer	Type No.	Serial No	Cal. Date
Spectrum Analyzer	Agilent	N9020A	MY49100159	2013.03.30
Vector Signal Generator	Agilent	E4438C	MY49070163	2013.03.30


Instrument	Manufacturer	Type No.	Serial No
Splitter/Combiner (Qty: 2)	Mini-Circuits	ZAPD-50W 4.2-6.0 GHz	NN256400424
Splitter/Combiner (Qty: 2)	MCLI	PS3-7	4463/4464
ATT (Qty: 1)	Mini-Circuits	VAT-30+	30912
Laptop PC	Asus	N80V	8BN0AS226971468
RF Cable (Qty: 6)	Mini-Circuits	N/A	DFS-1~6

Software	Manufacturer	Function
Pulse Building	Agilent	Radar Signal Generation Software
DFS Tool	Agilent	DFS Test Software

1.8. Test Setup



DFS Set-up Photo: Slave and Spectrum Analyzer



1.9. Limits

According to §15.407(h) Appendix “Compliance Measurement Procedures For Unlicensed National Information Infrastructure Devices Operating In The 5250-5350 MHz And 5470-5725MHz Bands Incorporating Dynamic Frequency Selection”.

Applicability of DFS requirements prior to use of a channel

Requirement	Operational Mode		
	Master	Client (with radar detection)	Client (without radar detection)
Non-Occupancy Period	Yes	Yes	Not Required
DFS Detection Threshold	Yes	Yes	Not Required
Channel Availability Check Time	Yes	Not Required	Not Required
Uniform Spreading	Yes	Not Required	Not Required
U-NII Detection Bandwidth	Yes	Yes	Not Required

Applicability of DFS requirements during normal operation

Requirement	Operational Mode		
	Master	Client (with radar detection)	Client (without radar detection)
DFS Detection Threshold	Yes	Yes	Not Required
Channel Closing Transmission Time	Yes	Yes	Yes
Channel Move Time	Yes	Yes	Yes
U-NII Detection Bandwidth	Yes	Yes	Not required

Interference Threshold value, Master or Client incorporating In-Service Monitoring

Maximum Transmit Power	Value (see note)
≥ 200 milliwatt	-64 dBm
< 200 milliwatt	-62 dBm
Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna. Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.	

DFS Response requirement values

Parameter	Value
Non-Occupancy Period	30 Minutes
Channel Availability Check Time	60 Seconds
Channel Move Time	10 Seconds
Channel Closing Transmission Time	200 milliseconds + approx. 60 milliseconds over remaining 10 seconds period (See Notes 1 and 2)
Note1: The instant that the Channel Move Time and the Channel Closing Transmission Time begins is as follows: For the short pulse radar test signals this instant is the end of the burst. For the frequency hopping radar test signal, this instant is the end of the last radar burst generated For the long pulse radar test signal this instant is the end of the 12 seconds period defining the radar transmission. Note 2: The channel closing transmission time is comprised of 200 milliseconds starting at the beginning of the channel move time plus any additional intermittent control signals required facilitating channel changes (an aggregate of approximately 60 milliseconds) during the remainder of the 10 seconds period. The aggregate duration of control signals will not count quiet periods in between transmissions.	

Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μsec)	PRI (μsec)	Pulses	Minimum Percentage of Successful Detection	Minimum Trials
1	1	1428	18	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (radar types 1-4)				80%	120

A minimum of 30 unique waveforms is required for each of the short pulse radar type 2 through 4. For short pulse radar type 1, then same waveform is used a minimum of 30 times. If more than 30 waveforms are used for short pulse radar type 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms. The aggregate is the average of the percentage of successful detections of short pulse radar type 1-4.

Long Pulse Radar Test Signal

Radar Waveform	Bursts	Pulses Per Burst	Pulse Width (μsec)	Chirp Width (MHz)	PRI (μsec)	Minimum Percentage of Successful Detection	Minimum Trials
5	8-20	1-3	50-100	5-20	1000-2000	80%	30

The parameters for this waveform are randomly chosen. Thirty unique waveforms are required for the long pulse radar test signal. If more than 30 waveforms are used for the long pulse radar test signal, then each additional waveform must also be unique and not repeated from the previous waveforms.

Frequency Hopping Radar Test Signal

Radar Waveform	Pulse Width (μsec)	PRI (μsec)	Hopping Sequence Length (msec)	Pulses Per Hop	Hopping Rate (kHz)	Minimum Percentage of Successful Detection	Minimum Trials
6	1	333	300	9	.333	70%	30


For the frequency hopping radar type, the same burst parameters are used for each waveform. The hopping sequence is different for each waveform and a 100-length segment is selected from the hopping sequence.

1.10. Radar Waveform Calibration

The following equipment setup was used to calibrate the conducted radar waveform. A spectrum analyzer was used to establish the test signal level for each radar type. During this process there were replace 50ohm terminal from master and client device and no transmissions by either the master or client device. The spectrum analyzer was switched to the zero span (time domain) at the frequency of the radar waveform generator. Peak detection was utilized. The spectrum analyzer resolution bandwidth (RBW) and video bandwidth (VBW) were set to 3MHz and 3 MHz.


The signal generator amplitude was set so that the power level measured at the spectrum analyzer was -61dBm due to the interference threshold level is not required.

Conducted Calibration Setup




1.11. Radar Waveform Calibration Result


Radar Type 1 Calibration Plot




Radar Type 2 Calibration Plot




Radar Type 3 Calibration Plot




Radar Type 4 Calibration Plot



Radar Type 5 Calibration Plot



Radar Type 6 Calibration Plot



2. Channel Move Time and Channel Closing Transmission Time

2.1. Test Procedure

These tests define how the following DFS parameters are verified during In-Service Monitoring; Channel Closing Transmission Time and Channel Move Time.

The steps below define the procedure to determine the above mentioned parameters when a radar burst with a level -61dBm is generated on the operating channel of the U-NII device.

A U-NII device operating as a Client device will associate with the Master device at 5500MHz.

During the in-service monitoring detection probability and channel moving tests the system was configured with a streaming video file from the master device (sourced by the PC connected to the master device via an Ethernet interface) to the client device. The streamed file was the "FCC" test file and the client device was using Media Player Classic as required by FCC Part 15 Subpart E.

Observe the transmissions of the EUT at the end of the radar burst on the operating channel for duration greater than 10 seconds. Measure and record the transmissions from the spectrum analyzer during the observation time (Channel Move Time). Compare the channel move time and channel closing transmission time results to the limits defined in the DFS Response requirement values table.

2.2. Test Requirement

Parameter	Limit
Channel Move Time	10 Seconds
Channel Closing Transmission Time	200 milliseconds + approx. 60 milliseconds over remaining 10 seconds period



2.3. Uncertainty

± 1ms.

2.4. Test Result of Channel Move Time and Channel Closing Transmission Time



Product : 9.7inch Tablet

Type 1 radar at 5300MHz



Test Item	Limit	Results
Channel Move Time	10 s	Pass
Channel Closing Transmission Time	200ms + an aggregate of 60ms over remaining 10 second period.	Pass

Type 1 radar at 5500MHz



Test Item	Limit	Results
Channel Move Time	10 s	Pass
Channel Closing Transmission Time	200ms + an aggregate of 60ms over remaining 10 second period.	Pass

3. Non-Occupancy Period

3.1. Test Procedure

Measure the EUT for more than 30 minutes following the channel close/move time to verify that the UUT does not resume any transmissions on this channel.

3.2. Test Requirement

Parameter	Limit
Non-Occupancy Period	Minimum 30 minutes


3.3. Uncertainty

$\pm 1\text{ms}$.

3.4. Test Result of Non-Occupancy Period

Product : 9.7inch Tablet

Type 1 radar at 5300MHz



Test Item	Limit	Results
Non-Occupancy Period	30 Minutes	Pass

Product : 9.7inch Tablet

Type 1 radar at 5500MHz



Test Item	Limit	Results
Non-Occupancy Period	30 Minutes	Pass

The End