



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM170100025202
Page: 1 of 91

TEST REPORT

Application No.: SZEM1701000252CR
Applicant: IMUST TECHNOLOGY LIMITED
Address of Applicant: 11/F AXA CENTRE 151 GLOUCESTER RD WANCHAI HK
Manufacturer: IMUST TECHNOLOGY LIMITED
Address of Manufacturer: 11/F AXA CENTRE 151 GLOUCESTER RD WANCHAI HK
Factory: IMUST TECHNOLOGY LIMITED
Address of Factory: 3F #2 Building Da Xing Chuangye Industrial Park, West ring Rd. & North ring Rd.
Shajin, Bao an, Shenzhen

Equipment Under Test (EUT):

EUT Name: BLUETOOTH STEREO HEADPHONE

Model No.: BH-530, AX20 ♣

♣

Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.

Trade mark: ARMANI EXCHANGE

FCC ID: SPCBH-530A

Standards: 47 CFR Part 15, Subpart C 15.247

Date of Receipt: 2017-01-11

Date of Test: 2017-01-16 to 2017-02-23

Date of Issue: 2017-02-28

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.




Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2017-02-28		Original

Authorized for issue by:				
Tested By				2017-02-23
		Bill Chen /Project Engineer		Date
Checked By				2017-02-28
		Eric Fu /Reviewer		Date

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013)	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(1)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6	47 CFR Part 15, Subpart C 15.247(d)	Pass

Declaration of EUT Family Grouping:

Model No.: BH-530, AX20

Only the model AX20 was tested, since the electrical circuit design, layout, components used, internal wiring and functions were identical for all the above models, with only difference on model No. and colour.



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION.....	6
4.1 DETAILS OF E.U.T.	6
4.2 DESCRIPTION OF SUPPORT UNITS.....	6
4.3 MEASUREMENT UNCERTAINTY.....	7
4.4 STANDARDS APPLICABLE FOR TESTING	8
4.5 TEST LOCATION	9
4.6 TEST FACILITY	9
4.7 DEVIATION FROM STANDARDS.....	9
4.8 ABNORMALITIES FROM STANDARD CONDITIONS	9
5 EQUIPMENT LIST.....	10
6 RADIO SPECTRUM TECHNICAL REQUIREMENT.....	12
6.1 ANTENNA REQUIREMENT	12
6.1.1 Test Requirement:.....	12
6.1.2 Conclusion	12
6.2 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM HOPPING SEQUENCE.....	13
6.2.1 Test Requirement:.....	13
6.2.2 Conclusion	13
7 RADIO SPECTRUM MATTER TEST RESULTS	15
7.1 20dB BANDWIDTH.....	15
7.1.1 E.U.T. Operation.....	15
7.1.2 Test Setup Diagram.....	15
7.1.3 Measurement Data	15
7.2 CONDUCTED PEAK OUTPUT POWER.....	16
7.2.1 E.U.T. Operation.....	17
7.2.2 Test Setup Diagram.....	17
7.2.3 Measurement Data	17
7.3 CARRIER FREQUENCIES SEPARATION.....	18
7.3.1 E.U.T. Operation.....	18
7.3.2 Test Setup Diagram.....	18
7.3.3 Measurement Data	18
7.4 HOPPING CHANNEL NUMBER.....	19
7.4.1 E.U.T. Operation.....	20
7.4.2 Test Setup Diagram.....	20
7.4.3 Measurement Data	20
7.5 DWELL TIME.....	21
7.5.1 E.U.T. Operation.....	22
7.5.2 Test Setup Diagram.....	22
7.5.3 Measurement Data	22
7.6 CONDUCTED SPURIOUS EMISSIONS.....	23
7.6.1 E.U.T. Operation.....	23
7.6.2 Test Setup Diagram.....	23
7.6.3 Measurement Data	23



7.7	RADIATED SPURIOUS EMISSIONS	24
7.7.1	E.U.T. Operation.....	25
7.7.2	Test Setup Diagram.....	25
7.7.3	Measurement Data	26
7.8	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....	32
7.8.1	E.U.T. Operation.....	32
7.8.2	Test Setup Diagram.....	32
7.8.3	Measurement Data	33
7.9	CONDUCTED BAND EDGES MEASUREMENT.....	38
7.9.1	E.U.T. Operation.....	38
7.9.2	Test Setup Diagram.....	38
7.9.3	Measurement Data	38
8	PHOTOGRAPHS	39
8.1	RADIATED SPURIOUS EMISSIONS TEST SETUP.....	39
8.2	EUT CONSTRUCTIONAL DETAILS	40
9	APPENDIX	41
9.1	APPENDIX 15.247.....	41-91



4 General Information

4.1 Details of E.U.T.

Product Name: BLUETOOTH STEREO HEADPHONE
Model No.: AX20
Trade Mark: ARMANI EXCHANGE
Operation Frequency: 2402MHz~2480MHz
Bluetooth Version: V3.0 with EDR
Modulation Type: GFSK; Pi/4DQPSK; 8DPSK
Number of Channel: 79
Sample Type: Portable production
Antenna Gain: 1.2dBi
Antenna Type: PIFA
Power supply: Rechargeable battery:DC 3.7V 320mAh(Charge by USB)
Test voltage: Test voltage: AC 120V 60Hz
Cable: USB cable:100cm Unshielded

4.2 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.
Laptop	Lenovo	T430u
Test board	Supply to SGS	FT232

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25 x 10 ⁻⁸
2	Timeout	2s
3	Duty cycle	0.37%
4	Occupied Bandwidth	3%
5	RF conducted power	0.75dB
6	RF power density	2.84dB
7	Conducted Spurious emissions	0.75dB
8	RF Radiated power	4.5dB (below 1GHz)
		4.8dB (above 1GHz)
9	Radiated Spurious emission test	4.5dB (30MHz-1GHz)
		4.8dB (1GHz-18GHz)
10	Temperature test	1 °C
11	Humidity test	3%
12	Supply voltages	1.5%
13	Time	3%



4.4 Standards Applicable for Testing

Table 1 : Tests Carried Out Under 47 CFR Part 15, Subpart C 15.247

Item	Status
Conducted Disturbance at AC Power Line(150kHz-30MHz)	√
20dB Bandwidth	√
Conducted Peak Output Power	√
Carrier Frequencies Separation	√
Hopping Channel Number	√
Dwell Time	√
Minimum 6dB Bandwidth	×
Power Spectrum Density	×
Conducted Spurious Emissions	√
Radiated Spurious Emissions	√
Radiated Emissions which fall in the restricted bands	√
Conducted Band Edges Measurement	√
Antenna Requirement	√
Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence	√

× Indicates that the test is not applicable
√ Indicates that the test is applicable



4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None



5 Equipment List

20dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Conducted Peak Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Carrier Frequencies Separation					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Hopping Channel Number					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Dwell Time					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09



Conducted Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2016-10-12	2017-10-12
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2016-05-18	2017-05-18

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.247


6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.



EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 1.2dBi.



6.2 Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence

6.2.1 Test Requirement:

47 CFR Part 15, Subpart C 15.247

6.2.2 Conclusion

Standard Requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1):

According to Technical Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

> Number of shift register stages: 9

> Length of pseudo-random sequence: $2^9 - 1 = 511$ bits

> Longest sequence of zeros: 8 (non-inverted signal)

Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:

Each frequency used equally on the average by each transmitter.

According to Technical Specification, the receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g):

According to Technical Specification, the system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h):



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM170100025202

Page: 14 of 91

According to Technical specification, the system incorporates with an adaptive system to detect other user within the spectrum band so that it individ

7 Radio Spectrum Matter Test Results


7.1 20dB Bandwidth

Test Requirement: 47 CFR Part 15, Subpart C 15.247
Test Method: ANSI C63.10 (2013) Section 7.8.7

7.1.1 E.U.T. Operation

Operating Environment:
Temperature: 23.0 °C Humidity: 56 % RH Atmospheric Pressure: 1020 mbar
Test mode: a:TX mode:Keep the EUT in transmitting mode

7.1.2 Test Setup Diagram



7.1.3 Measurement Data

The detailed test data see: Appendix 15.247



7.2 Conducted Peak Output Power

Test Requirement: 47 CFR Part 15, Subpart C 15.247

Test Method: ANSI C63.10 (2013) Section 7.8.5

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation


7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.0 °C Humidity: 56 % RH Atmospheric Pressure: 1020 mbar

Test mode: a:TX mode:Keep the EUT in transmitting mode

7.2.2 Test Setup Diagram



7.2.3 Measurement Data

The detailed test data see: Appendix 15.247


7.3 Carrier Frequencies Separation

Test Requirement: 47 CFR Part 15, Subpart C 15.247
Test Method: ANSI C63.10 (2013) Section 7.8.2
Limit: 2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W

7.3.1 E.U.T. Operation

Operating Environment:
Temperature: 23.0 °C Humidity: 56 % RH Atmospheric Pressure: 1020 mbar
Test mode: a:TX mode:Keep the EUT in transmitting mode

7.3.2 Test Setup Diagram



7.3.3 Measurement Data

The detailed test data see: Appendix 15.247



7.4 Hopping Channel Number

Test Requirement: 47 CFR Part 15, Subpart C 15.247

Test Method: ANSI C63.10 (2013) Section 7.8.3

Limit:

Frequency range(MHz)	Channel Number(minimum)
2400-2483.5	15


7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 23.0 °C Humidity: 56 % RH Atmospheric Pressure: 1020 mbar

Test mode: a:TX mode:Keep the EUT in transmitting mode

7.4.2 Test Setup Diagram



7.4.3 Measurement Data

The detailed test data see: Appendix 15.247



7.5 Dwell Time

Test Requirement: 47 CFR Part 15, Subpart C 15.247

Test Method: ANSI C63.10 (2013) Section 7.8.4

Limit:

Frequency(MHz)	Limit
2400-2483.5	0.4S within a period of 0.4S


7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 23.0 °C Humidity: 56 % RH Atmospheric Pressure: 1020 mbar

Test mode: a:TX mode:Keep the EUT in transmitting mode

7.5.2 Test Setup Diagram



7.5.3 Measurement Data

The detailed test data see: Appendix 15.247


7.6 Conducted Spurious Emissions

Test Requirement: 47 CFR Part 15, Subpart C 15.247
Test Method: ANSI C63.10 (2013) Section 7.8.8
Limit: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

7.6.1 E.U.T. Operation

Operating Environment:
Temperature: 23.0 °C Humidity: 56 % RH Atmospheric Pressure: 1020 mbar
Test mode: a:TX mode:Keep the EUT in transmitting mode

7.6.2 Test Setup Diagram



7.6.3 Measurement Data

The detailed test data see: Appendix 15.247



7.7 Radiated Spurious Emissions

Test Requirement: 47 CFR Part 15, Subpart C 15.247
Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6
Measurement Distance: 10m
Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Limit (dBuV/m)	Remark	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	-	-	300
0.490-1.705	24000/F(kHz)	-	-	30
1.705-30.0	30	-	-	30
30-88	29.9	40.0	Quasi-peak	3
88-216	44.7	43.5	Quasi-peak	3
216-960	60.3	46.0	Quasi-peak	3
960-1000	100	54.0	Quasi-peak	3
Above 1000	500	54.0	Average	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.




7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 24.0 °C Humidity: 54 % RH Atmospheric Pressure: 1015 mbar

Test mode: a:TX mode:Keep the EUT in transmitting mode

7.7.2 Test Setup Diagram





7.7.3 Measurement Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel (2402MHz), the middle channel (2441MHz), the Highest channel (2480MHz)
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.



Radiated Emission below 1GHz

The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L_3 : Level @ 3m distance. Unit: $\mu\text{V/m}$;

L_{10} : Level @ 10m distance. Unit: $\mu\text{V/m}$;

D_3 : 3m distance. Unit: m


D_{10} : 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m ($\mu\text{V/m}$)	Level @ 3m ($\mu\text{V/m}$)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
39.16	13.09	23.67	78.90	37.94	40.00	-2.06	V
88.65	12.75	28.45	94.83	39.54	43.50	-3.96	V
143.83	14.47	28.75	95.83	39.63	43.50	-3.87	V
381.25	17.59	27.15	90.50	39.13	46.00	-6.87	V
737.07	24.54	29.20	97.33	39.77	46.00	-6.23	V
958.79	28.07	29.65	98.83	39.90	46.00	-6.10	V
41.42	14.02	16.92	56.40	35.03	40.00	-4.97	H
52.76	12.65	18.17	60.57	35.64	40.00	-4.36	H
154.82	15.05	21.48	71.60	37.10	43.50	-6.40	H
366.82	16.63	27.86	92.87	39.36	46.00	-6.64	H
483.91	19.28	28.26	94.20	39.48	46.00	-6.52	H
766.06	25.84	27.04	90.13	39.10	46.00	-6.90	H



Mode:a; Horizontal




Condition: 10m HORIZONTAL
Job No. : 00252CR
Test Mode: TX

	Freq	Cable	Ant	Preamp	Read	Limit	Over	
	MHz	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	41.42	6.93	13.20	32.99	26.88	14.02	29.50	-15.48
2	52.76	6.25	12.55	32.98	26.83	12.65	29.50	-16.85
3	154.82	7.46	13.40	32.74	26.93	15.05	33.00	-17.95
4	366.82	8.36	14.21	32.60	26.66	16.63	35.60	-18.97
5	483.91	8.77	16.57	32.60	26.54	19.28	35.60	-16.32
6 pp	766.06	9.69	20.96	32.60	27.79	25.84	35.60	-9.76



Mode:a; Vertical



Condition: 10m VERTICAL
Job No. : 00252CR
Test Mode: TX

	Freq	Cable	Ant	Preamp	Read	Limit	Over	
	MHz	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	39.16	7.06	13.21	32.98	25.80	13.09	29.50	-16.41
2	88.65	7.47	8.67	32.83	29.44	12.75	33.00	-20.25
3	143.83	7.46	13.01	32.75	26.75	14.47	33.00	-18.53
4	381.25	8.40	14.51	32.60	27.28	17.59	35.60	-18.01
5	737.07	9.66	20.61	32.60	26.87	24.54	35.60	-11.06
6 pp	958.79	10.21	22.76	32.50	27.60	28.07	35.60	-7.53



Radiated Emission above 1GHz

Lowest

Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3626.104	32.57	7.68	37.96	43.92	46.21	74	-27.79	Vertical
4804.000	34.16	8.87	38.40	42.42	47.05	74	-26.95	Vertical
6051.874	34.74	10.49	38.25	43.92	50.90	74	-23.10	Vertical
7206.000	36.42	10.68	37.11	41.52	51.51	74	-22.49	Vertical
9608.000	37.52	12.50	35.10	37.34	52.26	74	-21.74	Vertical
12226.070	38.74	14.37	36.14	36.87	53.84	74	-20.16	Vertical
3995.234	33.59	7.81	38.00	44.65	48.05	74	-25.95	Horizontal
4804.000	34.16	8.87	38.40	44.33	48.96	74	-25.04	Horizontal
6087.002	34.77	10.45	38.21	43.70	50.71	74	-23.29	Horizontal
7206.000	36.42	10.68	37.11	41.30	51.29	74	-22.71	Horizontal
9608.000	37.52	12.50	35.10	37.55	52.47	74	-21.53	Horizontal
12050.440	38.63	14.52	35.72	35.69	53.12	74	-20.88	Horizontal

Middle

Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Reading Level (dBμV)	Level (dBμV/m)	Limit (dBμV/m)	Over limit (dB)	Polarization
3819.990	33.12	7.75	37.98	44.16	47.05	74	-26.95	Vertical
4882.000	34.30	8.98	38.44	42.56	47.40	74	-26.60	Vertical
5939.103	34.66	10.39	38.31	43.54	50.28	74	-23.72	Vertical
7323.000	36.37	10.72	37.01	41.70	51.78	74	-22.22	Vertical
9764.000	37.55	12.58	35.02	36.95	52.06	74	-21.94	Vertical
12261.500	38.76	14.34	36.23	36.51	53.38	74	-20.62	Vertical
3721.784	32.84	7.71	37.97	45.33	47.91	74	-26.09	Horizontal
4882.000	34.30	8.98	38.44	42.97	47.81	74	-26.19	Horizontal
6302.093	34.95	10.17	38.00	43.02	50.14	74	-23.86	Horizontal
7323.000	36.37	10.72	37.01	41.50	51.58	74	-22.42	Horizontal
9764.000	37.55	12.58	35.02	36.91	52.02	74	-21.98	Horizontal
12050.440	38.63	14.52	35.72	36.11	53.54	74	-20.46	Horizontal



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170100025202

Page: 31 of 91

Highest

Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Reading Level (dBμV)	Level (dBμV/m)	Limit (dBμV/m)	Over limit (dB)	Polarization
3831.060	33.15	7.75	37.98	44.21	47.13	74	-26.87	Vertical
4960.000	34.43	9.09	38.48	42.37	47.41	74	-26.59	Vertical
6184.658	34.85	10.32	38.12	43.40	50.45	74	-23.55	Vertical
7440.000	36.32	10.77	36.90	40.97	51.16	74	-22.84	Vertical
9920.000	37.58	12.67	34.94	37.23	52.54	74	-21.46	Vertical
12261.500	38.76	14.34	36.23	36.75	53.62	74	-20.38	Vertical
3792.453	33.04	7.74	37.98	45.01	47.81	74	-26.19	Horizontal
4960.000	34.43	9.09	38.48	43.20	48.24	74	-25.76	Horizontal
6025.661	34.72	10.53	38.27	43.09	50.07	74	-23.93	Horizontal
7440.000	36.32	10.77	36.90	40.82	51.01	74	-22.99	Horizontal
9920.000	37.58	12.67	34.94	37.06	52.37	74	-21.63	Horizontal
12226.070	38.74	14.37	36.14	36.72	53.69	74	-20.31	Horizontal

7.8 Radiated Emissions which fall in the restricted bands

Test Requirement: 47 CFR Part 15, Subpart C 15.247

Test Method: ANSI C63.10 (2013) Section 6.10.5




7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 24.0 °C Humidity: 54 % RH Atmospheric Pressure: 1015 mbar

Test mode: a:TX mode:Keep the EUT in transmitting mode

7.8.2 Test Setup Diagram






7.8.3 Measurement Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel (2402MHz), the middle channel (2441MHz), the Highest channel (2480MHz)
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.



Test plot as follows:

Worse case mode:	GFSK (DH5)	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	------------	---------------	--------	---------	------	----------



Condition: 3m Vertical
Job No: : 0252CR
Mode: : 2402 Bandedge
: BT


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2370.093	5.32	29.02	37.96	52.84	49.22	74.00	-24.78	
2	2390.000	5.34	29.08	37.96	46.04	42.50	74.00	-31.50	
3 pp	2402.047	5.35	29.11	37.96	95.08	91.58	74.00	17.58	



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170100025202
Page: 35 of 91

Worse case mode:	GFSK (DH5)	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	------------	---------------	--------	---------	------	------------



Condition: 3m HORIZONTAL

Job No: : 0252CR

Mode: : 2402 Bandedge
: BT


	Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark
	MHz	Loss	Factor	Factor	Level	dBuV/m	Line	Limit	
		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2369.892	5.32	29.02	37.96	57.44	53.82	74.00	-20.18	
2	2390.000	5.34	29.08	37.96	45.88	42.34	74.00	-31.66	
3 pp	2402.047	5.35	29.11	37.96	99.62	96.12	74.00	22.12	



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170100025202
Page: 36 of 91

Worse case mode:	GFSK (DH5)	Test channel:	Highest	Remark:	Peak	Vertical
------------------	------------	---------------	---------	---------	------	----------



Condition: 3m HORIZONTAL

Job No: : 0252CR


Mode: : 2480 Bandedge

: BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2480.030	5.41	29.34	37.95	99.37	96.17	74.00	22.17	
2	2483.500	5.41	29.35	37.95	47.33	44.14	74.00	-29.86	
3	2483.672	5.41	29.35	37.95	48.66	45.47	74.00	-28.53	



Worse case mode:	GFSK(DH5)	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	-----------	---------------	---------	---------	------	------------



Condition: 3m VERTICAL
Job No: : 0252CR
Mode: : 2480 Bandedge
: BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2480.279	5.41	29.34	37.95	93.05	89.85	74.00	15.85	
2	2483.500	5.41	29.35	37.95	45.40	42.21	74.00	-31.79	
3	2493.676	5.42	29.38	37.95	47.79	44.64	74.00	-29.36	

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$


7.9 Conducted Band Edges Measurement

Test Requirement: 47 CFR Part 15, Subpart C 15.247
Test Method: ANSI C63.10 (2013) Section 7.8.6

7.9.1 E.U.T. Operation

Operating Environment:
Temperature: 23.0 °C Humidity: 56 % RH Atmospheric Pressure: 1020 mbar
Test mode: a:TX mode:Keep the EUT in transmitting mode

7.9.2 Test Setup Diagram




7.9.3 Measurement Data

The detailed test data see: Appendix 15.247

8 Photographs

8.1 Radiated Spurious Emissions Test Setup





8.2 EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1701000252CR.





9 Appendix


9.1 Appendix 15.247


1. 20 dB Bandwidth

Test Mode	Test Channel	EBW[MHz]	Limit	Verdict
DH5	2402	0.730	---	PASS
DH5	2441	0.778	---	PASS
DH5	2480	0.874	---	PASS
2DH5	2402	0.706	---	PASS
2DH5	2441	0.780	---	PASS
2DH5	2480	0.776	---	PASS
3DH5	2402	0.716	---	PASS
3DH5	2441	0.738	---	PASS
3DH5	2480	0.780	---	PASS













20 dB Bandwidth_3DH5_2441




20 dB Bandwidth_3DH5_2480






2. Conducted Peak Output Power

Test Mode	Test Channel	Power[dBm]	Limit[dBm]	Verdict
DH5	2402	0.06	<30	PASS
DH5	2441	-0.48	<30	PASS
DH5	2480	-1.05	<30	PASS
2DH5	2402	-0.12	<30	PASS
2DH5	2441	-0.66	<30	PASS
2DH5	2480	-1.17	<30	PASS
3DH5	2402	-0.11	<30	PASS
3DH5	2441	-0.64	<30	PASS
3DH5	2480	-1.17	<30	PASS






Conducted Peak Output Power_DH5_2441




Conducted Peak Output Power_DH5_2480






Conducted Peak Output Power_2DH5_2402




Conducted Peak Output Power_2DH5_2441






Conducted Peak Output Power_2DH5_2480




Conducted Peak Output Power_3DH5_2402






Conducted Peak Output Power_3DH5_2441




Conducted Peak Output Power_3DH5_2480






3. Carrier Frequency Separation

Test Mode	Test Channel	Result[MHz]	Verdict
DH5	2441	0.996	PASS
2DH5	2441	1.002	PASS
3DH5	2441	1.005	PASS






Carrier Frequency Separation_2DH5_2441




Carrier Frequency Separation_3DH5_2441






4. Dwell Time

Test Mode	Test Channel	Burst Width[ms/hop/ch]	Total Hops[hop*ch]	Dwell Time[s]	Limit[s]	Verdict
DH1	2402	0.49	310	0.152	<0.4	PASS
DH3	2402	0.49	310	0.152	<0.4	PASS
DH5	2402	2.99	120	0.359	<0.4	PASS
2DH1	2402	3.01	60	0.181	<0.4	PASS
2DH3	2402	1.76	200	0.352	<0.4	PASS
2DH5	2402	3.02	70	0.211	<0.4	PASS
3DH1	2402	0.5	320	0.16	<0.4	PASS
3DH3	2402	1.76	130	0.229	<0.4	PASS
3DH5	2402	3.01	100	0.301	<0.4	PASS








Dwell Time_DH3_2402




Dwell Time_DH5_2402













5. Hopping Channel Number

Test Mode	Test Channel	Number of Hopping Channel[N]	Limit[N]	Verdict
DH5	2402	79	≥ 15	PASS
2DH5	2402	79	≥ 15	PASS
3DH5	2402	79	≥ 15	PASS









6.Band-edge for RF Conducted Emissions


Test Mode	Test Channel	Hopping	Carrier Power[dBm]	Max. Spurious Level [dBm]	Limit[dBm]	Verdict
DH5	2402	Off	-0.590	-42.802	<-20.59	PASS
DH5	2480	Off	-2.130	-63.127	<-22.13	PASS
2DH5	2402	Off	-0.190	-42.643	<-20.19	PASS
2DH5	2480	Off	-1.530	-61.870	<-21.53	PASS
3DH5	2402	Off	-0.200	-42.558	<-20.2	PASS
3DH5	2480	Off	-1.530	-62.307	<-21.53	PASS
DH5	2402	On	-0.690	-42.978	<-20.69	PASS
DH5	2480	On	-2.210	-47.710	<-22.21	PASS
2DH5	2402	On	-0.300	-42.717	<-20.3	PASS
2DH5	2480	On	-1.640	-47.650	<-21.64	PASS
3DH5	2402	On	-0.150	-42.588	<-20.15	PASS
3DH5	2480	On	-1.660	-47.691	<-21.66	PASS




Band-edge for RF Conducted Emissions_DH5_2480_Hopping Off




Band-edge for RF Conducted Emissions_2DH5_2402_Hopping Off



Band-edge for RF Conducted Emissions_2DH5_2480_Hopping Off




Band-edge for RF Conducted Emissions_3DH5_2402_Hopping Off







Band-edge for RF Conducted Emissions_3DH5_2480_Hopping Off




Band-edge for RF Conducted Emissions_DH5_2402_Hopping On




Band-edge for RF Conducted Emissions_DH5_2480_Hopping On




Band-edge for RF Conducted Emissions_2DH5_2402_Hopping On




Band-edge for RF Conducted Emissions_2DH5_2480_Hopping On



Band-edge for RF Conducted Emissions_3DH5_2402_Hopping On











7. RF Conducted Spurious Emissions


Test Mode	Test Channel	StartFre [MHz]	StopFre [MHz]	RBW [kHz]	VBW [kHz]	Pref[dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
DH5	2402	30	10000	1000	3000	-0.55	-38.850	<-20.55	PASS
DH5	2402	10000	25000	1000	3000	-0.55	-65.250	<-20.55	PASS
DH5	2441	30	10000	1000	3000	-1.1	-35.340	<-21.1	PASS
DH5	2441	10000	25000	1000	3000	-1.1	-65.030	<-21.1	PASS
DH5	2480	30	10000	1000	3000	-1.63	-38.870	<-21.63	PASS
DH5	2480	10000	25000	1000	3000	-1.63	-65.430	<-21.63	PASS
2DH5	2402	30	10000	1000	3000	-0.19	-37.480	<-20.19	PASS
2DH5	2402	10000	25000	1000	3000	-0.19	-64.890	<-20.19	PASS
2DH5	2441	30	10000	1000	3000	-0.61	-38.020	<-20.61	PASS
2DH5	2441	10000	25000	1000	3000	-0.61	-64.800	<-20.61	PASS
2DH5	2480	30	10000	1000	3000	-1.19	-39.570	<-21.19	PASS
2DH5	2480	10000	25000	1000	3000	-1.19	-65.130	<-21.19	PASS
3DH5	2402	30	10000	1000	3000	-0.13	-37.340	<-20.13	PASS
3DH5	2402	10000	25000	1000	3000	-0.13	-64.320	<-20.13	PASS
3DH5	2441	30	10000	1000	3000	-0.69	-38.140	<-20.69	PASS
3DH5	2441	10000	25000	1000	3000	-0.69	-64.990	<-20.69	PASS
3DH5	2480	30	10000	1000	3000	-1.17	-39.650	<-21.17	PASS
3DH5	2480	10000	25000	1000	3000	-1.17	-64.890	<-21.17	PASS









































Pref

