



Test Report - RF Exposure Evaluation / SAR Exclusion

Prepared For: TANDD CORPORATION

Approved for Release By:

Signature: Bruno Clavier

Name & Title: Bruno Clavier, General Manager

Date of Signature 12/16/2020

This test report shall not be reproduced except in full without the written and signed permission of Timco Engineering Inc. (IIA). This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

Table of Contents

1. CUSTOMER INFORMATION.....	3
2. LOCATION OF TESTING.....	3
2.1 TEST LABORATORY	3
2.2 TESTING WAS PERFORMED, REVIEWED BY	4
3. TEST SAMPLE(S) (EUT/DUT).....	4
3.1 DESCRIPTION OF THE EUT.....	5
4. SAR EXCLUSION CALCULATION:	6
5. HISTORY OF TEST REPORT CHANGES.....	7



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

1. Customer Information

Applicant: TANDD Corporation USA
Address: 817-1-Shimadachi, Matsumoto,
Nagano, Japan 390-0852

Contact: Akemi Oana
Telephone: 81-263-40-0131
Email address: oana@tandd.co.jp

2. Location of Testing

2.1 Test Laboratory

Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at Timco's permanent laboratory located at 849 NW State Road 45, Newberry, Florida 32669

FCC test firm # 578780
FCC Designation # US1070
FCC site registration is under A2LA certificate # 0955.01
ISED Canada test site registration # 2056A
EU Notified Body # 1177
For all designations see A2LA scope # 0955.01



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

2.2 Testing was performed, reviewed by

Dates of Testing: October 14 – December 16, 2020

Signature:

A handwritten signature of Franklin Rose in black ink.

Name & Title: Franklin Rose, EMC Specialist

Date of Signature

(YYYY-MM-DD): 2020-12-16

A handwritten signature of Tim Royer in black ink.

Sr. EMC Engineer
EMC-003838-NE

A circular logo with "CERTIFIED" at the top, "iMARIE" in the center, and "ENGINEER" at the bottom. The "i" is stylized with a small globe graphic.

Signature:

Name & Title: Tim Royer, EMC Engineer

Date of Signature

(YYYY-MM-DD): 2020-12-16



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

3. Test Sample(s) (EUT/DUT)

The test sample was received: October 14, 2020

3.1 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

Identification	
FCC ID:	SRD50100
Brief Description	Data Logger Remote Unit
Type of Modular	n/a
Model(s) #	RTR501B, RTR502B, RTR503B, RTR505B, RTR507B
Firmware version	n/a
Software version	n/a
Serial Number	n/a

Technical Characteristics	
Technology	900 MHz FSK (The host also contains 2.4 GHz BLE)
Frequency Range	902-928 MHz; 2400-2483.5 MHz
RF O/P Power (Max.)	7.2 dBm (5.25 milliwatts)
Modulation	FSK
Bandwidth & Emission Class	552.55 kHz
Number of Channels	21
Duty Cycle	10%
Antenna Gain (for each ant.)	2.15 dBi
Antenna Connector	SMA
Voltage Rating (AC or Batt.)	Battery

Antenna Characteristics			
Antenna	Frequency Range	Mode / BW	Antenna Gain
1	902-928 MHz	n/a	2.15 dBi
2	2.4 – 2.4835 GHz	n/a	0 dBi



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

4. SAR EXCLUSION CALCULATION:

900 MHz Radio

Frequency Band	Separation Distance (mm)	Max Power + Tolerance (dBm)	Max Power + Tolerance (mW)	SAR Exclusion Value
902-928 MHz	5	7.20	5.25	1.01

2.4 GHz Radio

Frequency Band	Separation Distance (mm)	Max Power + Tolerance (dBm)	Max Power + Tolerance (mW)	SAR Exclusion Value
2402-2480 MHz	5	0.50	1.12	0.35

SAR, Composite

Frequency Band	Separation Distance (mm)	SAR Exclusion Value	Limit for 1-g SAR	Limit for 10-g SAR (Extremities)	SAR Exclusion
902-2480 MHz	5	1.36	3.0	7.5	SAR EXEMPT



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

5. History of Test Report Changes

Test Report #	Revision #	Description	Date of Issue
TR_3827-20_RF Exp SAR Exclusion Rpt_1	1	Initial release	November 13, 2020
TR_3827-20_RF Exp SAR Exclusion Rpt_2	2	Clerical Updates in Section 3.1	December 2, 2020
TR_3827-20_RF Exp SAR Exclusion Rpt_3	3	Updated with 2.4 GHz Radio; clerical updates	December 16, 2020



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

END OF TEST REPORT
