

## RF Exposure / MPE Calculation

No.	15317913H
Customer	TandD Corporation
Description of EUT	Data Logger
Model Number of EUT	TR45A
FCC ID	SRD50150

TandD Corporation declares that Model: TR45A complies with FCC radiation exposure requirement specified in the FCC Rule 2.1091 (for mobile).

### **RF Exposure Calculations:**

The following information provides the minimum separation distance for the highest gain antenna provided with the "TR45A" as calculated from (B) Limits for General Population / Uncontrolled Exposure of TABLE 1- LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE) of §1.1310 Radiofrequency radiation exposure limits.

This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1mW/cm<sup>2</sup> uncontrolled exposure limit. The Friis formula used was:

$$S = \frac{P \times G}{4 \times \pi \times r^2}$$

Where

$P$  = 2.00 mW (Maximum average output power)

Time average was used for the above value in consideration of 6-minutes time-averaging  
 Burst power average was used for the above value in consideration of worst condition.

$G$  = 1.253 Numerical Antenna gain; equal to 0.98dBi

$r$  = 20 cm (Separation distance)

**Power Density Result  $S = 0.00050$  mW/cm<sup>2</sup>**