

TEST REPORT

For

Wireless Thermo Recorder

In conformity with

FCC CFR 47 Part15 (October 1, 2008) / RSS-210 Issue 7, RSS-Gen Issue 2

Model: RTR-501, RTR-502, RTR-503

FCC ID/ IC Certification No.: SRDRTR50X / 5558A-RTR50X

Test Item: Wireless Thermo Recorder

Report No: RY0907Z13R2

Issue Date: 13 July, 2009

Prepared for

T&D CORPORATION
817-1 Shimadachi, Matsumoto, Nagano, Japan 390-0852

Prepared by

RF Technologies Ltd.
472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan
Telephone: +81+(0)45- 534-0645
FAX: +81+(0)45- 534-0646

**This report shall not be reproduced, except in full, without the written permission of
RF Technologies Ltd. The test results in this report apply only to the sample tested.
RF Technologies Ltd. is managed to ISO17025 and has the necessary knowledge and test facilities for
testing according to the referenced standards.**

Table of contents

1 General information.....	3
1.1 Product description	3
1.2 Test(s) performed/ Summary of test result	3
1.3 Test facility	4
1.4 Measurement uncertainty.....	4
1.5 Summary of test results.....	5
1.5.1 Table of test summary.....	5
1.6 Setup of equipment under test (EUT)	5
1.6.1 Test configuration of EUT	5
1.6.2 Operating condition:	6
1.6.3 Setup diagram of tested system:.....	6
1.7 Equipment modifications.....	6
1.8 Deviation from the standard	6
2 Test procedure and test data	7
2.1 Occupied Bandwidth (6dB / 99%).....	7
2.2 Peak Output Power	9
2.3 Power Spectral Density.....	11
2.4 Conducted Spurious Emissions (Antenna Port).....	13
2.5 Transmitter Radiated spurious emissions	14
2.5.1 Below 30 MHz.....	16
2.5.2 Between 30 – 1000 MHz	17
2.5.3 Above 1000 MHz.....	20
2.6 Receiver Radiated spurious emissions.....	22
2.6.1 Between 30 – 1000 MHz	22
2.6.2 Above 1000 MHz.....	22
2.7 Maximum Permissible Exposure (Exposure of Humans to RF Fields)	23
3 Test setup photographs.....	24
3.1 Type of EUT	24
3.2 Definition of the EUT axis.....	24
3.3 Antenna Port Measurements	26
3.4 Radiated spurious emissions	27
4 List of utilized test equipment/ calibration	28

History

Report No.	Date	Revisions	Issued By
RY0907Z13R2	13 July, 2009	Initial Issue	K. Ohnishi

1 General information

1.1 Product description

Test item	: Wireless Thermo Recorder
Manufacturer	: T&D CORPORATION
Address	: 817-1 Shimadachi, Matsumoto, Nagano, Japan 390-0852
Model	: RTR-501, RTR-502, RTR-503
FCC ID	: SRDRTR50X
IC Certification No	: 5558A-RTR50X
Operating frequency band	: Tx/Rx Freq. (902 - 928 MHz)
Operating frequency range	: 902.9376 MHz (0ch) – 927.1296 MHz (21ch)
Oscillator frequencies	: 32.768 kHz, 9.83 MHz, 13.1072 MHz, 48 MHz
Type of Modulation	: FSK
Number of channels	: 22ch (Manufacturer declared)
RF Output Power	: 6.76 dBm (measured at the antenna terminal)
Antenna Gain	: \leq 2.14 dBi (Manufacturer declared)
Antenna Type	: Dipole antenna
Receipt date of EUT	: 20 June, 2009
Nominal power source voltages	: DC 3.3V (Battery)

1.2 Test(s) performed/ Summary of test result

Test specification(s)	: FCC CFR 47. Part 15 (October 1, 2008) / RSS-210 Issue 7, RSS-Gen Issue 2
Test method(s)	: ANSI C63.4: 2003
Test(s) started	: 5 July, 2009
Test(s) completed	: 10 July, 2009
Purpose of test(s)	: Grant for Certification of FCC / IC
Summary of test result	: Complied

Note: The above judgment is only based on the measurement data and it does not include the measurement uncertainty. Accordingly, the statement below is applied to the test result.

The EUT complies with the limit required in the standard in case that the margin is not less than the measurement uncertainty in the Laboratory.

Compliance of the EUT is more probable than non-compliance in case that the margin is less than the measurement uncertainty in the Laboratory.

Test engineer

: K. Ohnishi
K. Ohnishi
Engineer
EMC testing Department

Reviewer

: T. Ikegami
T. Ikegami
Manager
EMC testing Department

1.3 Test facility

The Federal Communications Commission has reviewed the technical characteristics of the test facilities at RF Technologies Ltd., located in 472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan, and has found these test facilities to be in compliance with the requirements of 47 CFR Part 15, section 2.948, per October 1, 2007. The description of the test facilities has been filed under registration number 319924 at the Office of the Federal Communications Commission. The facility has been added to the list of laboratories performing these test services for the public on a fee basis.

The list of all public test facilities is available on the Internet at <http://www.fcc.gov>.

Registered by Voluntary Control Council for Interference by Information Technology Equipment (VCCI)

Each registered facility number is as follows;

Test site (Semi-Anechoic chamber 3m) R-2393

Test site (Shielded room) C-2617

Registered by Industry Canada (IC): The registered facility number is as follows;

Test site No. 1 (Semi-Anechoic chamber 3m): 6974A

Accredited by **National Voluntary Laboratory Accreditation Program** (NVLAP) for the emission tests stated in the scope of the certificate under Certificate Number 200780-0

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



NVLAP LAB CODE 200780-0

1.4 Measurement uncertainty

The treatment of uncertainty is based on the general matters on the definition of uncertainty in "Guide to the expression of uncertainty in measurement (GUM)" published by ISO. The Lab's uncertainty is determined by referring UKAS Publication LAB34: 2002 "The Expression of Uncertainty in EMC Testing" and CISPR16-4-2: 2003 "Uncertainty in EMC Measurements".

The uncertainty of the measurement result in the level of confidence of approximately 95% (k=2) is as follows;

Conducted emission: ± 1.9 dB (10 kHz – 30 MHz)

Radiated emission (9 kHz - 30MHz): ± 2.8 dB

Radiated emission (30MHz - 1000MHz): ± 5.7 dB

Radiated emission (above 1000MHz): ± 5.8 dB

1.5 Summary of test results

1.5.1 Table of test summary

Requirement of;	Section in FCC15	Section in RSS210/ RSS-Gen	Sample	Result	Section in this report
1.5.1 Occupied Bandwidth (6dB/99%)	15.247(a)(2)	A8.2(a)	A2	Complied	2.1
1.5.2 Peak Output Power	15.247(b)(3)	A8.4(4)	A2	Complied	2.2
1.5.3 Power spectral density	15.247(e)	A8.2(b)	A2	Complied	2.3
1.5.4 Conducted Spurious Emissions	15.247(d)	A8.5	A2	Complied	2.4
1.5.5 Transmitter Radiated Spurious Emissions	15.205(b)/15.209	2.6	A1/A3/A4	Complied	2.5
1.5.6 Receiver Radiated Spurious Emissions	15.109	RSS-Gen 6	A1/A3/A4	Complied	2.6
1.5.7 Maximum Permissible Exposure (Exposure of Humans to RF Fields)	2.1091 1.1307(b)(1)	RSS-Gen 5.5/ RSS-102	-	Complied	2.7

1.6 Setup of equipment under test (EUT)

1.6.1 Test configuration of EUT


Equipment(s) under test:

	Item	Manufacturer	Model No.	Serial No.	Remarks
A1	Wireless Thermo Recorder	T&D CORPORATION	RTR-501*	3EB80002	For Radiated
A2	Wireless Thermo Recorder	T&D CORPORATION	RTR-501*	3EB80001	For Conducted
A3	Wireless Thermo Recorder	T&D CORPORATION	RTR-502*	3EBA0002	For Radiated
A4	Wireless Thermo Recorder	T&D CORPORATION	RTR-503*	3EBC0002	For Radiated
B	Lithium Battery	SaFT	LS 14250	08068A082	

Note: These products are data loggers designed to measure and record temperature and humidity with built-in wireless communication capability. These have the same RF circuits, but these enclosures and additional sensor are not same.


RTR-501

With Internal
Temperature Sensor




RTR-502

With External
Temperature Sensor
TR-5106 Included



RTR-503

With External
Temperature /
Humidity Sensor
TR-3310 Included




1.6.2 Operating condition:

Operating mode:

The EUT was tested under the following test mode prepared by the applicant:

- (1-1) FSK modulation, Continuous transmission (902.9376MHz)
- (1-2) FSK modulation, Continuous transmission (914.4576MHz)
- (1-3) FSK modulation, Continuous transmission (927.1296MHz)
- (2-1) Continuous receiving (902.9376MHz)
- (2-2) Continuous receiving (914.4576MHz)
- (2-3) Continuous receiving (927.1296MHz)

1.6.3 Setup diagram of tested system:



1.7 Equipment modifications

No modifications have been made to the equipment in order to achieve compliance with the applicable standards described in clause 1.2.

1.8 Deviation from the standard


No deviations from the standards described in clause 1.2.

2 Test procedure and test data

2.1 Occupied Bandwidth (6dB / 99%)

Test setup

Test setup is the following drawing. The antenna port of EUT was connected to the spectrum analyzer.



Test procedure

Measurement procedures were implemented according to the method of ANSI C63.4: 2003 clauses 13.1.7.

The EUT antenna port connected to the spectrum analyzer. The RBW is set to 100 kHz. The VBW is set to 3 times of the RBW. The sweep time is coupled appropriate.

Limitation

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test equipment used (refer to List of utilized test equipment)

SA06					
------	--	--	--	--	--

Test results



Transmission Channel	Transmission Frequency	Bandwidth [kHz]	
		6dB	99%
Low (0ch)	902.9376	568.000	460.000
Middle (10ch)	914.4576	568.000	468.000
High (21ch)	927.1296	560.000	464.000

Test Data



Tested Date: 10 July, 2009

Temperature: 23 °C
 Humidity: 51 %
 Atmos. Press: 1009 hPa



Lch (902.9376MHz)



Mch (914.4576MHz)




Hch (927.1296MHz)



2.2 Peak Output Power

Test setup

Test setup is the following drawing. The antenna port of EUT was connected to the spectrum analyzer.



Test procedure

The EUT antenna port connected to the spectrum analyzer. The RBW is set to the greater than 6dB bandwidth. The VBW is set to three times of RBW. The sweep time is coupled appropriate. The span is set to cover the carrier output spectrum. The analyzer is set to MAX HOLD.

Limitation

For systems using digital modulation in the 902–928 MHz, 2400–2483.5MHz, and 5725–5850 MHz bands: 1 Watt.

Test equipment used (refer to List of utilized test equipment)

SA06					
------	--	--	--	--	--


Test results – comply with the limitation.

Transmission Channel (Frequency: MHz)	Output power (dBm) [Result]	Output power (mW) [Result]
Low (902.9376)	6.12	4.09
Middle (914.4576)	6.44	4.41
High (927.1296)	6.76	4.74

Test Data

Tested Date: 10 July, 2009


Temperature: 23 °C
Humidity: 51 %
Atmos. Press: 1009 hPa



2.3 Power Spectral Density

Test setup

Test setup is the following drawing. The antenna port of EUT was connected to the spectrum analyzer.



Test procedure

The EUT antenna port connected to the spectrum analyzer. The RBW is set to 3 kHz. The VBW is set to 10 kHz.

The sweep time is set to (SPAN / 3 kHz) seconds. The span is set to cover the carrier output spectrum.

The correction factor is set to the spectrum analyzer in order to correct of the connected cable loss.

Limitation

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Test equipment used (refer to List of utilized test equipment)

SA06					
------	--	--	--	--	--


Test results – comply with the limitation.

Transmission Channel (MHz)	Power Spectral Density (dBm)
Low (902.9376)	5.92
Middle (914.4576)	6.23
High (927.1296)	6.57

Test Data

Tested Date: 10 July, 2009


Temperature: 23 °C
Humidity: 51 %
Atmos. Press: 1009 hPa



2.4 Conducted Spurious Emissions (Antenna Port)

Test setup

Test setup is the following drawing. The antenna port of EUT was connected to the spectrum analyzer.



Test procedure

The EUT antenna port connected to the spectrum analyzer. The RBW is set to 100 kHz. The VBW is set to 300 kHz. The sweep time is set to the coupled. The spectrum is checked from 30 MHz to 10 GHz.

Limitation

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

Test equipment used (refer to List of utilized test equipment)

SA06					
------	--	--	--	--	--

Test results – comply with the limitation.

There were no conducted spurious emissions with levels of more than 20 dB below the applicable limit.

Test Data


Tested Date: 10 July, 2009

Temperature: 23 °C

Humidity: 51 %

Atmos. Press: 1009 hPa


Worst Configuration (Hch: 927.1296MHz)



2.5 Transmitter Radiated spurious emissions

Test setup

Test setup was implemented according to the method of ANSI C63.4: 2003 clause 6 “General requirements for EUT equipment arrangements and operation”, clause 8.2 and Annex H.3 “Radiated emission measurements setup”.



Test procedure

Measurement procedures were implemented according to the method of ANSI C63.4: 2003 clauses 8.2.

The EUT is place on a non-conducted table which is 0.8m height from a ground plane and the measurement antenna to EUT distance is 3 meters. The turn table is rotated for 360 degrees to determine the maximum emission level. In the frequency range of 9 kHz to 30 MHz, a calibrated loop antenna was positioned with its plane vertical at the distance 3m from the EUT with an extrapolation of corrected distance factor and rotated about its vertical axis for maximum response at each azimuth about the EUT. For certain applications, the loop antenna also needs to be positioned horizontally. The center of the loop shall be 1 m above the ground.

In the frequency above 30 MHz, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

EUT is placed at three different orientations (X, Y and Z axis) in order to find the worst orientation.

The spectrum analyzer and receiver are set to the followings;

Below 30 MHz: RBW=10 kHz, VBW= 30 kHz
Final measurement is carried out with a receiver RBW of 9 kHz (QP)

Between 30 - 1000 MHz: RBW=100 kHz, VBW= 300 kHz
Final measurement is carried out with a receiver RBW of 120 kHz (QP)

Above 1000 MHz: Peak measurement- RBW=1 MHz, VBW= 1 MHz
Average measurement – RBW=1 MHz, VBW=10 Hz

Applicable rule and limitation

§15.205 restricted bands of operation

Except as shown in paragraph 15.205 (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.490 - 0.510	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(1)

15.205(b) except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

15.209(a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

In the emission table above, the tighter limit applies at the band edges.

The level of any unwanted emissions from an intentional radiator operating under these general provisions shall not exceed the level of the fundamental emission.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz.

Test results - Complied with requirement.

Test Data

2.5.1 Below 30 MHz

Test equipment used (refer to List of utilized test equipment)

LP01	CL11	TR06	
------	------	------	--

Tested Date: 9 July, 2009

Temperature: 20 °C
Humidity: 59 %
Atmos. Press: 1008 hPa

Operating mode: Continuous Communication

Measurement distance: 3 m

Sample: RTR-501, RTR-502, RTR-503

There is no spurious emission with levels of more than 20 dB below the applicable limit

2.5.2 Between 30 – 1000 MHz

Test equipment used (refer to List of utilized test equipment)

BA04	PR03	CL23	TR06
------	------	------	------

Tested Date: 9 July, 2009

Temperature: 20 °C
Humidity: 59 %
Atmos. Press: 1009 hPa

Operating mode: Continuous Communication (Mch: 914.4576 MHz: Worst configuration)

EUT position: X-plane (Maximum position)

Measurement distance: 3 m

Sample: RTR-501

There are no spurious emissions other than listed below;

No.	Frequency [MHz]	Reading [dBuV]	Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Antenna Polarization
1	812.855	36.3	20.1	13.7	29.3	40.8	46.0	5.2	Hori.

Calculation method

The Correction Factors and RESULT are calculated as followings.

$$\text{Correction Factor [dB/m]} = \text{FACTOR [dB/m]} + \text{LOSS [dB]} - \text{GAIN [dB]}$$


$$\text{RESULT [dBuV/m]} = \text{READING [dBuV]} + \text{Correction Factor [dB/m]}$$

Sample calculation at 812.855 MHz horizontal result as follow:

$$\text{Result [dBuV/m]} = \text{Reading} + \text{C.F} = 36.3 + 20.1 + 13.7 - 29.3 = 40.8$$

$$\text{Margin} = \text{Limit} - \text{Result} = 46.0 - 40.8 = 5.2 \text{ [dB]}$$

Graphical express of test result (30MHz-1000MHz)



Tested Date: 9 July, 2009

Temperature: 20 °C
Humidity: 59 %
Atmos. Press: 1009 hPa

Operating mode: Continuous Communication (Mch: 914.4576 MHz: Worst configuration)

EUT position: X-plane (Maximum position)

Measurement distance: 3 m

Sample: RTR-502

There are no spurious emissions other than listed below;

No.	Frequency [MHz]	Reading [dBuV]	Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Antenna Polarization
1	812.859	33.1	20.1	13.7	29.3	37.6	46.0	8.4	Hori.

Calculation method

The Correction Factors and RESULT are calculated as followings.

$$\text{Correction Factor [dB/m]} = \text{FACTOR [dB/m]} + \text{LOSS [dB]} - \text{GAIN [dB]}$$


$$\text{RESULT [dBuV/m]} = \text{READING [dBuV]} + \text{Correction Factor [dB/m]}$$

Sample calculation at 812.859 MHz horizontal result as follow:

$$\text{Result [dBuV/m]} = \text{Reading} + \text{C.F} = 33.1 + 20.1 + 13.7 - 29.3 = 37.6$$

$$\text{Margin} = \text{Limit} - \text{Result} = 46.0 - 37.6 = 8.4 \text{ [dB]}$$

Graphical express of test result (30MHz-1000MHz)



Tested Date: 9 July, 2009

 Temperature: 20 °C
 Humidity: 59 %
 Atmos. Press: 1009 hPa

Operating mode: Continuous Communication (Mch: 914.4576 MHz: Worst configuration)

EUT position: X-plane (Maximum position)

Measurement distance: 3 m

Sample: RTR-503

There are no spurious emissions other than listed below;

No.	Frequency [MHz]	Reading [dBuV]	Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Antenna Polarization
1	203.626	40.0	9.5	9.4	29.5	29.4	43.5	14.1	Hori.
2	812.857	40.0	20.1	13.7	29.3	44.5	46.0	1.5	Hori.

Calculation method

The Correction Factors and RESULT are calculated as followings.


$$\text{Correction Factor [dB/m]} = \text{FACTOR [dB/m]} + \text{LOSS [dB]} - \text{GAIN [dB]}$$

$$\text{RESULT [dBuV/m]} = \text{READING [dBuV]} + \text{Correction Factor [dB/m]}$$

Sample calculation at 812.857 MHz horizontal result as follow:

$$\text{Result [dBuV/m]} = \text{Reading} + \text{C.F} = 40.0 + 20.1 + 13.7 - 29.3 = 44.5$$

$$\text{Margin} = \text{Limit} - \text{Result} = 46.0 - 44.5 = 1.5 \text{ [dB]}$$

Graphical express of test result (30MHz-1000MHz)

2.5.3 Above 1000 MHz

Test equipment used (refer to List of utilized test equipment)

PR12 TR06 CL23 CL24 HPF2 DH02 AC01







Tested Date: 9 July, 2009

Temperature: 20 °C

Humidity: 59 %

Atmos. Press: 1008 hPa

Restricted Band Edge (Z-plane, Vertical: Worst configuration)



Harmonics and Spurious Emission above 1000 MHz

Tested Date: 5 July, 2009

 Temperature: 21 °C
 Humidity: 56 %
 Atmos. Press: 1015 hPa

Operating mode: Continuous Communication (Hch: 927.1296MHz: Worst configuration)

EUT position: Y-plane (Maximum position)

Measurement distance: 3 m

Sample: RTR-501

There are no spurious emissions with levels of more than 20 dB below the applicable limit other than listed below;

No.	Frequency [MHz]	Reading [dBuV]		C.F. [dB]	Result [dBuV/m]		Limit [dBuV/m]		Margin [dB]		Polarization
		Peak	Ave.		Peak	Ave.	Peak	Ave.	Peak	Ave.	
1	1133.246	67.1	61.8	-11.1	56.0	50.7	73.9	53.9	17.9	3.2	Hori.
2	1133.255	60.8	54.6	-11.1	49.7	43.5	73.9	53.9	24.2	10.4	Vert.

Tested Date: 5 July, 2009

 Temperature: 21 °C
 Humidity: 56 %
 Atmos. Press: 1015 hPa

Operating mode: Continuous Communication (Hch: 927.1296MHz: Worst configuration)

EUT position: Y-plane (Maximum position)

Measurement distance: 3 m

Sample: RTR-502

There are no spurious emissions with levels of more than 20 dB below the applicable limit other than listed below;

No.	Frequency [MHz]	Reading [dBuV]		C.F. [dB]	Result [dBuV/m]		Limit [dBuV/m]		Margin [dB]		Polarization
		Peak	Ave.		Peak	Ave.	Peak	Ave.	Peak	Ave.	
1	1133.277	60.8	54.8	-11.1	49.7	43.7	73.9	53.9	24.2	10.2	Vert.
2	1133.278	66.3	61.2	-11.1	55.2	50.1	73.9	53.9	18.7	3.8	Hori.

Tested Date: 5 July, 2009

 Temperature: 21 °C
 Humidity: 56 %
 Atmos. Press: 1015 hPa

Operating mode: Continuous Communication (Hch: 927.1296MHz: Worst configuration)

EUT position: Y-plane (Maximum position)

Measurement distance: 3 m

Sample: RTR-503

There are no spurious emissions with levels of more than 20 dB below the applicable limit other than listed below;

No.	Frequency [MHz]	Reading [dBuV]		C.F. [dB]	Result [dBuV/m]		Limit [dBuV/m]		Margin [dB]		Polarization
		Peak	Ave.		Peak	Ave.	Peak	Ave.	Peak	Ave.	
1	1133.200	63.9	57.9	-11.1	52.8	46.8	73.9	53.9	21.1	7.1	Hori.
2	1133.247	59.8	53.0	-11.1	48.7	41.9	73.9	53.9	25.2	12.0	Vert.

2.6 Receiver Radiated spurious emissions

Test setup - Same as clause 2.5

Test procedure - Same as clause 2.5

Applicable rule and limitation at 3m

§15.109 radiated emission limitation

Frequency (MHz)	Measurement Distance (m)	Field Strength (uV/m)	Field Strength (dBuV/m)
30 – 88	3	100	40.0
88 – 216	3	150	43.5
216 – 960	3	200	46.0
Above 960	3	500	53.9

In the emission table above, the tighter limit applies at the band edges.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector. Radiated emission limits in the above bands are based on measurements employing an average detector.

Test results - Complied with requirement.

2.6.1 Between 30 – 1000 MHz

Test equipment used (refer to List of utilized test equipment)

BA04	CL11	PR03	TR06
------	------	------	------

Test Data

Tested Date: 9 July, 2009

Temperature: 20 °C

Humidity: 59 %

Atmos. Press: 1008 hPa

Operating mode: Continuous Receiving

Measurement distance: 3 m

Sample: RTR-501, RTR-502, RTR-503

There were no spurious emissions greater than noise floor or 20dB below the limit.

2.6.2 Above 1000 MHz

Test equipment used (refer to List of utilized test equipment)

PR12	TR06	CL23	CL24	DH02		
------	------	------	------	------	--	--

Tested Date: 5 July, 2009

Temperature: 21 °C

Humidity: 56 %

Atmos. Press: 1015 hPa

Operating mode: Continuous Receiving

Measurement distance: 3 m

Sample: RTR-501, RTR-502, RTR-503

There were no spurious emissions greater than noise floor (33.5 dBuV/m, 4500 MHz) or 20dB below the limit.

2.7 Maximum Permissible Exposure (Exposure of Humans to RF Fields)

Limitation

15.247(i) systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

See 1.1307(b) (1) of this Chapter.

1.1310 The criteria of "General Population/ Uncontrolled Exposure" listed in the below table shall be used to evaluated the environmental impact of human exposure to radio-frequency radiation as specified in 1.1307(b), except in the case of portable devices which shall be evaluated according to the revisions of 2.1093 of this chapter.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz

*Plane-wave equivalent power density

NOTE 2: **General population/uncontrolled** exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The MPE distance calculations:

The Maximum Permissible Exposure (MPE) distance between the EUT's antenna and human body is calculated in accordance with FCC OET Bulletin 65 and Safety Code 6 of IC.

The MPE distance where the exposure level reaches the permitted exposure level can be calculated as bellow;

$$S = P * G / 4\pi R^2$$

Rearranging terms to calculate the MPE Distance

$$R = (P * G / 4\pi S)^{1/2}$$

Where:

R = MPE Distance in cm

P = Power in dBm (4.74 mW (927.1296MHz), Refer to page 9 in this report)

G = Antenna Gain in numeric

(1.64 = 2.14 dBi, Max. Antenna Gain)

S = Power Density Limit in mW/cm²

(0.61 mW/cm², Max. permissible exposure limit above)

Then MPE Distance is 1.007 cm.

Test results - Complied with requirement.

4 List of utilized test equipment/ calibration

RFT ID No.	Kind of Equipment and Precision	Manufacturer	Model No.	Serial Number	Calibration Date	Calibrated until
AC01	Anechoic Chamber (1st test room)	JSE	203397C	-	2008/07/04	2009/07/31
BA04	Biological Antenna	SCHAFFNER	CA2855	2903	2009/01/06	2010/01/31
CL11	Antenna Cable for RE	RFT	-	-	2009/04/13	2010/04/30
CL23	RF Cable 0.5m	SUCOFLEX	SF104PE	48773/4PE	2009/06/25	2010/06/30
CL24	RF Cable 5.0m	SUCOFLEX	SF104PE	48775/4PE	2009/06/25	2010/06/30
PR03	Pre. Amplifier	Anritsu	MH648A	M41984	2009/05/26	2010/05/31
PR12	Pre. Amplifier (1-26G)	Agilent Technologies	8449B	3008A02513	2009/01/13	2010/01/31
HPF2	High Pass Filter (1500MHz)	M-City	HPF0900-01	RF0003-01	2009/06/25	2010/06/30
TR06	Test Receiver (F/W : 3.93 SP2)	Rohde & Schwarz	ESU26	100002	2008/09/02	2009/09/01
DH02	DRG Horn Antenna	A.H. Systems	SAS-200/571	239	2009/04/13	2011/04/30

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.