

PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,

Taipei Hsien, Taiwan, R. O. C.

TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

RFI / EMI TEST REPORT

APPLICANT : **WONDE PROUD TECHNOLOGY CO., LTD.**


E U T Type : **Bluetooth GPS Receiver**

MODEL NO. : **GPS BT-77**

FCC ID : **SRKWPBT77X**

REGULATION : CFR 47 , Part 15 Subpart C , **Class B**

TEST SITE : PEP Testing Laboratory

TEST ENGINEER : 

TEST DATE : DEC. 07, 2004

ISSUED DATE : DEC. 15, 2004

REPORT NO. : E930751

PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

VERIFICATION

WE HEREBY VERIFY THAT:

The EUT listed below has completed RFI testing by PEP Testing Laboratory and it does comply with the limitation of FCC Part 15, Section 15.247 limitations .

The tested configurations and the facility complies with the radiated and AC line conducted test site criteria in ANSI C63 .4 - 2001 .

Any data in this RFI report is “ reference “ only .

APPLICANT : WONDE PROUD TECHNOLOGY CO., LTD.
PRODUCT : Bluetooth GPS Receiver
FCC ID : SRKWPBT77X
MODEL : GPS BT-77

M. Y. Tsui

M. Y. TSUI / President

PEP Testing Laboratory

12-3FL., NO. 27-1, Lane 169, Kang-Ning St.,
Hsi-Chi, Taipei Hsien, Taiwan, R. O. C.
TEL : 886-2-6922097 FAX : 886-2-6956236

TABLE OF CONTENTS

I.	GENERAL INFORMATION	5
1.1	Description of EUT	
1.2	Supporting Devices for EUT testing	
1.3	EUT Test Setup Configuration	
1.4	Channels Verification (15.205)	
II.	§15.207 POWER LINE CONDUCTED EMISSION TEST	11
2.1	Testing Description	
2.2	Software Using	
2.3	Test Result	
2.4	Conducted Emission Test Photo	
III.	§15.247(a)(1): HOPPINGCHANNEL FREQUENCY SEPARATION	15
3.1	Test Procedure	
3.2	Test result of Frequency Separation	
3.3	Spectrum Plot Data	
IV.	§15.247(a)(1) : 20dB BANDWIDTH	16
4.1	Test Procedure	
4.2	Test Result of Bandwidth	
4.3	Spectrum Plot Data	
V.	§15.247(a) (1): TIME OF OCCUPANCY(DWELL TIME)	23
5.1	Test Procedure	
5.2	Test Result of Dwell Time	
5.3	Spectrum Plot Data	
VI	§15.247(b) : THE MAXIMUM PEAK OUTPUT POWER ($\leq$ 1WATT)	25
6.1	Testing Description	
6.2	Software Using	
6.3	Test Result of Fundamental Emissions	
VII.	§15.247(b)(4) MAXIMUM PERMISSIBLE EXPOSURE (MPE)	33
7.1	MPE distance calculation	
7.2	Device operating configurations exposure conditions	
7.3	Maximum Permissible Exposure (MPE)	

PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,

Taipei Hsien, Taiwan, R. O. C.

TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

VIII. §15.247(c) : SPURIOUS RADIATED EMISSIONS	35
8.1 Out side band below 1GHz	
8.2 Out side band above 1GHz	
8.2 Spurious Radiate Emission Testing Photos	
IX. §15.247(c) : BAND-EDGES COMPLIANCE	40
X. §15.247(d) : PEAK POWER SPECTRAL DENSITY	44
10.1 Test Procedure	
10.2 Test result of Peak Power Spectral Density	
10.3 Spectrum Plot Data	
XI. LIST OF TEST INSTRUMENTS	48
XII. EUT PHOTOS	49

I . General Information

The equipment under test (EUT) is Bluetooth GPS Receiver, FCC ID: SRKWPBT77X, model GPS BT-77. The EUT can be used to work for the applications such as car navigation purpose. The working frequency is 2.402GHz-2.480GHz. DC 3.7V from battery or DC 5.3V from AC-DC adaptor is required to operate EUT. For more detail specification about EUT, please refer to the user's manual.

Test method: According to the major function designed, the EUT placement on test table was arranged alone to proceed with test. The test was carried out on EUT operational condition of Tx-On mode: continuous transmission state. The worst-case test result of each test mode was recorded and provided in this report.

At the frequencies where the peak values of the emission exceeded the quasi-peak limit, the emissions were also measured with the quasi-peak detectors. The average detector also measured the emission either (A) quasi-peak values were under quasi-peak limit but exceeded average limit, or (B) peak values were under quasi-peak limit but exceeded average limit.

1.1 Description of EUT

EUT Type	:	Bluetooth GPS Receiver
FCC ID	:	SRKWPBT77X
EUT Model No.	:	GPS BT-77
Frequency Range	:	2.402~2.480GHz
Support Channel	:	79 channels
Modulation	:	QBSK
Antenna Type	:	Comply with FCC Part 15, Section 15.203;
Build-in PCB trace type	:	can't be removed by the user
Power Supply	:	1) Manufacturer : DVE
		Model No. : DSA-0051-05C FUS 53050F
		Input : AC 100~240V, 0.2A
		Output : DC 5.3V, 0.5A
Power Cord	:	N/A

1.2 Supporting Devices for EUT testing

1. Personal Computer (PC3)

CPU : Intel P4 Socket 478 1.6GHz
FCC ID : Declaration of Conformity(DoC)
Manufacturer : LEMEL
Model Number : LMIH1A2
Power Supply : Switching
Power Cord : Non-Shielded, Detachable, 1.8m
Data Cable : N/A

2. Keyboard (KBS1 PS/2)

FCC ID : E5XKB5121WTH0110
Manufacturer : BTC
Model Number : 5121W
Power Supply : +5Vdc from PS2 of PC
Power Cord : N/A
Data Cable : **1** > Shielded , Non-detachable,1.6m
2 > Back Shell : Metal

3. Monitor (MON1 15")

FCC ID : Declaration of Conformity(DoC)
Manufacturer : SAMSUNG
Model Number : 550S
Power Supply : Switching
Power Cord : Non-Shielded, Detachable, 1.8m
Data Cable : **1** > Shielded , Non-detachable,1.2m
2 > Back Shell : Metal

4. Printer (PRN1)

FCC ID : B94C2642X
Manufacturer : Hewlett-Packard
Model Number : C2642E
Power Supply : Linear, 30Vdc O/P
Power Cable : Non-Shielded , Detachable,1.8m
Data Cable : **1** > Shielded , Detachable,1.2m
2 > Back Shell : Metal

PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

5. Modem (MOD1) × 2

FCC ID : IFAXDM1414

Manufacturer : ACEEX

Model Number : 1414

Power Supply : Linear, 9Vac O/P

Power Cable : Non-Shielded , Detachable,1.7m

Data Cable : 1 > Shielded , Detachable,1m

2 > Back Shell : Metal

6. Mouse (MOUS/1 PS/2)

FCC ID : DZL211106

Manufacturer : LOGITECH

Model Number : M-S43

Power Supply : +5Vdc from PS2 of PC

Power Cord : N/A


Data Cable : 1 > Shielded , Non-detachable,1.8m

2 > Back Shell : Metal

1.3 EUT Test Setup Configuration

- (A)Test Procedure: As required by ANSI C63.4 (2001)
- (B)Channel Verification: In order to force selection of the typical channels for testing, Dungle was connected PC through USB interface and using the driver “CSR BlueSuite”, under WinXP to force the channel selection by control PC, then set the EUT in high power and continuously transmitting mode for detecting the operating frequency, the test result for 79 channels is operating within 2.402~2.480GHz band.
- (C)Measurement Procedure: As required by FCC Part15, Section 15.31(m) measurements on intentional radiators or receiver should be performed at three frequencies for operating frequency over 10MHz, one near top, one near middle and one near bottom.
- (D)Test Channel: Due to the support channels are 79 channels, the selected three frequencies for testing would be 2.402GHz near top for CH LOW, 2.441GHz near middle for CH MID and 2.480GHz near bottom for CH HIGH.
- (E) At the frequencies where the peak values of the emission exceeded the quasi-peak limit, the emissions were also measured with the quasi-peak detectors. The average detector also measured the emission either (a) quasi-peak values were under quasi-peak limit but exceeded average limit, or (b) peak values were under quasi-peak limit but exceeded average limit.
- (F)In this RFI test report, we provided the worst case conducted emission test data and radiated emission test data. The entire testing data was recorded and provided in this report.

1.4 Channels Verification



a. EUT Type : Bluetooth GPS Receiver**b. EUT Model : GPS BT-77****c. TX Channel No. : 79**

Channel 01: 2402 MHz

Channel 02: 2403 MHz

Channel 03: 2404 MHz

Channel 04: 2405 MHz

Channel 05: 2406 MHz

Channel 06: 2407 MHz

Channel 07: 2408 MHz

Channel 08: 2409 MHz

Channel 09: 2410 MHz

Channel 10: 2411 MHz

Channel 11: 2412 MHz

Channel 12: 2413 MHz

Channel 13: 2414 MHz

Channel 14: 2415 MHz

Channel 15: 2416 MHz

Channel 16: 2417 MHz

Channel 17: 2418 MHz

Channel 18: 2419 MHz

Channel 19: 2420 MHz

Channel 20: 2421 MHz

Channel 21: 2422 MHz

Channel 22: 2423 MHz

Channel 23: 2424 MHz

Channel 24: 2425 MHz

Channel 25: 2426 MHz

Channel 26: 2427 MHz

Channel 27: 2428 MHz

Channel 28: 2429 MHz

Channel 29: 2430 MHz

Channel 30: 2431 MHz

Channel 31: 2432 MHz

Channel 32: 2433 MHz

Channel 33: 2434 MHz

Channel 34: 2435 MHz

Channel 35: 2436 MHz

Channel 36: 2437 MHz

Channel 37: 2438 MHz

Channel 38: 2439 MHz

Channel 39: 2440 MHz

Channel 40: 2441 MHz

Channel 41: 2442 MHz

Channel 42: 2443 MHz

Channel 43: 2444 MHz

Channel 44: 2445 MHz

Channel 45: 2446 MHz

Channel 46: 2447 MHz

Channel 47: 2448 MHz

Channel 48: 2449 MHz

Channel 49: 2450 MHz

Channel 50: 2451 MHz

Channel 51: 2452 MHz

Channel 52: 2453 MHz

Channel 53: 2454 MHz

Channel 54: 2455 MHz

Channel 55: 2456 MHz

Channel 56: 2457 MHz

Channel 57: 2458 MHz

Channel 58: 2459 MHz

Channel 59: 2460 MHz

Channel 60: 2461 MHz

Channel 61: 2462 MHz

Channel 62: 2463 MHz

Channel 63: 2464 MHz

Channel 64: 2465 MHz

Channel 65: 2466 MHz

Channel 66: 2467 MHz

Channel 67: 2468 MHz

Channel 68: 2469 MHz

Channel 69: 2470 MHz

Channel 70: 2471 MHz

Channel 71: 2472 MHz

Channel 72: 2473 MHz

Channel 73: 2474 MHz

Channel 74: 2475 MHz

Channel 75: 2476 MHz

Channel 76: 2477 MHz

Channel 77: 2478 MHz

Channel 78: 2479 MHz

Channel 79: 2480 MHz

Frequency Range : 2.402 GHz to 2.480 GHz

Note :

1. All channels located in the frequency range as below :


2.4 GHz --- 2.4835 GHz ☒ Yes ☐ No

Typical Channel for testing :

Channel	Channel Number	Frequency (GHz)
LOW	1	2.402
MID	40	2.441
HIGH	79	2.480

II. 15.207 Power Line Conducted Emission Test

2.1 Testing Description



2.2 Software Using

The driver of “CSR BlueSuite” is used to select the support channel as mentioned on section 1.3 (b) listed above

PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

2.3 Test Result


EUT Model No. GPS BT-77 (LINE)

Detector : Peak Value



暉鑫科技股份有限公司
PEP Testing Laboratory

Data#: 1530 File#: HNS5022-B(QP).EMI Date: 2004-11-26 Time: 17:54:10



Trace: 1579
Site : Shih-Chi : Conduction No.1(Gene)
Condition: CISPR CLASS-B(QP) LISN.L(16A) LINE
eut : E930751
power : AC 120V 60Hz
memo : Peak Value
 : Final Test

Page: 1

	Freq	Level	Over	Limit	Read	Probe	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.161	44.27	-21.16	65.43	43.97	0.20	0.10	
2	0.207	40.41	-22.91	63.32	40.10	0.20	0.11	
3	0.260	35.54	-25.88	61.42	35.16	0.20	0.18	
4	0.354	31.22	-27.65	58.87	30.92	0.20	0.10	
5	0.494	29.75	-26.35	56.10	29.36	0.20	0.19	
6	0.948	29.51	-26.49	56.00	29.11	0.20	0.20	
7	1.396	28.34	-27.66	56.00	27.94	0.20	0.20	
8	4.574	28.73	-27.27	56.00	28.22	0.21	0.30	
9	9.502	36.55	-23.45	60.00	35.96	0.29	0.30	
10	22.298	31.59	-28.41	60.00	30.49	0.70	0.40	

PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751


EUT Model No.: GPS BT-77 (NEUTRAL)

Detector : Peak Value



緯鑫科技股份有限公司
PEP Testing Laboratory

Data#: 1525 File#: EN55022-B{QP}.EMI Date: 2004-11-26 Time: 17:52:27



Trace: 1524
Site : Shih-Chi : Conduction No.1(Gene)
Condition: CISPR CLASS-B(QP) LISN.N(16A) NEUTRAL
eut : E930751
power : AC 120V 60Hz
memo : Peak Value
 : Final Test

Page: 1

	Freq	Level	Over	Limit	Read	Probe	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.154	45.40	-20.38	65.78	45.10	0.20	0.10	
2	0.197	41.83	-21.93	63.76	41.53	0.20	0.10	
3	0.474	35.32	-21.13	56.45	34.97	0.20	0.15	
4	0.958	32.83	-23.17	56.00	32.43	0.20	0.20	
5	1.560	32.06	-23.94	56.00	31.66	0.20	0.20	
6	3.190	33.24	-22.76	56.00	32.82	0.20	0.22	
7	4.574	34.73	-21.27	56.00	34.22	0.21	0.30	
8	9.966	37.76	-22.24	60.00	37.16	0.30	0.30	
9	17.661	34.57	-25.43	60.00	33.71	0.56	0.30	
10	22.655	33.53	-26.47	60.00	32.42	0.71	0.40	

2.4 Conducted Emission Test Photo

EUT Model No. GPS BT-77

< FRONT VIEW >



III. §15.247(a)(1) : Hopping Channel Frequency Separation


3.1 Test Procedure

- (1)The Hopping Channel Frequency Separation was measured in max hold analyzer mode with span wide enough to capture the peaks of two adjacent channels.
- (2)Set the Spectrum as RBW=VBW=100KHz
- (3) 3.3 Spectrum Plot Data show the Frequency Separation test results.

3.2 Test result of Frequency Separation

	Measured Separation (KHz)	Limit (KHz)	Pass/Fail
Channel Separation	1010	25	Pass
Separation at -20dB	720	25	Pass

3.3 Spectrum Plot Data



IV. §15.247(a)(1) : 20dB Bandwidth

4.1 Test Procedure

- (1)The 20dB bandwidth was measured at the EUT antenna terminal in max hold analyzer mode with span wide enough to capture the hopping channel emissions.
- (2)Set the Spectrum as RBW=VBW=10KHz
- (3) 4.2 Spectrum Plot Data show the 20dB Bandwidth test results.

4.2 Test result of Bandwidth

EUT Model No. GPS BT-77

Channel	Antenna Polarity	Bandwidth (KHz)	Limit (KHz)	Pass/Fail
LOW	H	34	1000	Pass
	V	35	1000	Pass
MID	H	36	1000	Pass
	V	35	1000	Pass
HIGH	H	36	1000	Pass
	V	36	1000	Pass

PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236


FCC ID : SRKWPBT77X

REPORT NO. : E930751

4.3 Spectrum Plot Data

Channel : CH LOW

Polarity : Horizontal



PEP Testing Laboratory


12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

Channel : CH LOW

Polarity : Vertical




PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

Channel : CH MID
Polarity : Horizontal




12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

Channel : CH MID

Polarity : Vertical



PEP Testing Laboratory


12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

Channel : CH HIGH

Polarity : Horizontal




12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

Channel : CH HIGH

Polarity : Vertical



V. §15.247(a) (1): Time of Occupancy(Dwell Time)



5.1 Test Procedure

- (1)The Time of Occupancy was measured in “max hold” analyzer mode with zero span and different sweep time to calculate the Time of Occupancy.
- (2)Set the Spectrum as RBW=VBW=1MHz
- (3)5.3 Spectrum Plot Data show the Time of Occupancy test results.

5.2 Test Result of Dwell Time


Dwell Time= $0.42 \times 80 = 33.6\text{ms} < 0.4\text{s}$

5.3 Spectrum Plot Data



VI. §15.247(b) : The maximum peak output power ($\leq 1\text{watt}$)

6.1 Testing Description



Three channels were tested : CH LOW, CH MID AND CH HIGH Measurements were taken by using both horizontal and vertical antenna polarization, and the antenna was raised and lowered from one to four meters to find the worst emission levels.

6.2 Software Using

The driver of “CSR BlueSuite” is used to select the support channel as mentioned on section 1.3 (b) listed above

6.3 Test Result of Fundamental Emissions**EUT Model No. GPS BT-77**

Channel	Frequency (MHz)	Antenna Polarity (H/V)	Spectrum Read (dBuV/m)	C.F. (dB)	Level (dBuV/m)	E.I.R.P. (W)
LOW	2401.98	H	63.91	-2.11	61.80	4.54×10^{-7}
	2401.96	V	61.55	-2.11	59.44	2.64×10^{-7}
MID	2441.06	H	69.00	-2.01	66.99	1.50×10^{-6}
	2440.98	V	65.33	-2.01	63.32	6.44×10^{-7}
HIGH	2480.04	H	70.24	-1.94	68.30	2.03×10^{-6}
	2479.90	V	65.30	-1.94	63.36	6.50×10^{-7}

Note :

1. "C.F." means corrected factor = antenna factor + cable loss – Preamplifier Gain .
2. Level means emission amplitude = S.P. + C.F. + duty cycle factor
3. Conducted output power : $P = (E d)^2 / 30G$

where $E (V) = \text{Level} (V)$ $d (m) = \text{measurement distance} = 3m$ $G = 1$ (the gain of the transmitting antenna over isotropic antenna) $P = \text{E.I.R.P.}$

4. Example :

If Level = 120 dBuV/m

$$10^{(120/20)} \times 10^{-6} = 1 \text{ V}$$

$$\text{E.I.R.P.} = (1 \times 3)^2 / 30 = 300 \text{ mW}$$

PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751


EUT Model No. GPS BT-77

Channel : CH LOW

Polarity : Horizontal



緯鑫科技股份有限公司
PEP Testing Laboratory



Site : Shih-Chi : Chamber No.3
Condition : 3m HORN ANTENNA H.3 HORIZONTAL
EUT : E930751
Power : AC 120V 60Hz
Menu : TX ON
Menu : LOW
Channel :

Freq	Level	Over	Limit	Read	Probe	Cable Preamp		Remark
		Limit	Line			Loss	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	
1 2401.980	61.80	-----	-----	63.91	28.48	4.08	34.67	

PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X


REPORT NO. : E930751

Channel : CH LOW

Polarity : Vertical



緯鑫科技股份有限公司
PEP Testing Laboratory



Site : Shih-Chi : Chamber No.3
Condition : 3m HORN ANTENNA V,3 VERTICAL
EUT : E930751
Power : AC 120V 60Hz
Memo : TX ON
Memo : 10V
Channel :

Freq	Level	Over Limit		Read Level	Probe Factor	Cable Loss	Preamplifier	Remark
		Limit	Line					
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	
1 2401.900	59.44	-----	-----	61.55	20.40	-4.00	54.67	


PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

Channel : CH MID
Polarity : Horizontal



Site : Shih-Chi : Chamber No.5
Condition : 3m HORN ANTENNA H.3 HORIZONTAL
EUT : E930751
Power : AC 120V 60Hz
Meno : TX ON
Memo : MID
Channel :

	Freq	Level	Over	Limit	Read	Probe	Cable Preamp		Remark
							Level Factor	Loss Factor	
	MHz	dBuV/m		dB dBuV/m	dBuV	dB	dB	dB	
1	2441.060	66.99	-----	-----	69.00	26.53	-4.14	34.68	

PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X


REPORT NO. : E930751

Channel : CH MID

Polarity : Vertical



暉鑫科技股份有限公司
PEP Testing Laboratory



Site : Shih-Chi : Chamber No.3
Condition : 3m HORN ANTENNA V.3 VERTICAL
EUT : E930751
Power : AC 120V 60Hz
Memo : TX ON
Memo : MID
Channel :

	Freq	Level	Over	Limit	Read	Probe	Cable Preamp		Remark
			Limit	Line			Loss Factor	Factor	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	
1	2440.900	63.32	-----	-----	65.33	20.53	4.14	34.66	

PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X


REPORT NO. : E930751

Channel : CH HIGH

Polarity : Horizontal



緯鑫科技股份有限公司
PEP Testing Laboratory



Site : Shih-Chi : Chamber No.3
Condition : 3m HORN ANTENNA H.3 HORIZONTAL
EUT : E930751
Power : AC 120V 50Hz
Memo : TX ON
Memo : HIGH
Channel :

Freq	Level	Over Limit		Read Level	Probe Factor	Cable Loss	Preamp	Remark
		Limit	Line					
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	
1 2480.040	68.30	-----	-----	70.24	20.59	-4.17	34.70	

PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X


REPORT NO. : E930751

Channel : CH HIGH

Polarity : Vertical



緯鑫科技股份有限公司
PEP Testing Laboratory



Site : Shih-Chi : Chamber No.3
Condition : 3m HORN ANTENNA V.3 VERTICAL
EUT : E930751
Power : AC 120V 60Hz
Menu : TX ON
Menu : HIGH
Channel :


	Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	Remark
1	2479.900	63.36	-----	-----	63.36	28.59	-4.17	34.70	

VII. §15.247(b)(4) Maximum Permissible Exposure (MPE)

7.1 MPE distance calculation

$$d = \frac{\sqrt{30G \text{ EIRP}}}{E}$$

7.2 Device operating configurations exposure conditions



7.3 Maximum Permissible Exposure (MPE)**EUT Model No. GPS BT-77**

Channel	Frequency	A.P.	S.P. Read	C.F.	Level	Power density at 20cm
	(MHz)	(H/V)	(dBuV/m)	(dB)	(dBuV/m)	(m W / cm ²)
LOW	2401.98	H	63.91	-2.11	61.80	2.02*10 ⁻⁶
	2401.96	V	61.55	-2.11	59.44	1.17*10 ⁻⁶
MID	2441.06	H	69.00	-2.01	66.99	6.67*10 ⁻⁶
	2440.98	V	65.33	-2.01	63.32	2.86*10 ⁻⁶
HIGH	2480.04	H	70.24	-1.94	68.30	9.01*10 ⁻⁶
	2479.90	V	65.30	-1.94	63.36	2.89*10 ⁻⁶

Note :

5. "A.P." means antenna polarity .
6. "S.P." Read means amplitude read by spectrum analyzer .
7. "C.F." means corrected factor = antenna factor + cable loss - Preamplifier Gain .
8. Level means emission amplitude = S.P. + C.F. + duty cycle factor
9. Conducted output power : $P = (E d)^2 / 30G$

where E (V) = Level (V)

d (m) = distance = 20 cm

G = 1 (the gain of the transmitting antenna over isotropic antenna)

P = E.I.R.P.

10. Example :

If Level = 120 dBuV/m

$$10^{(120/20)} \times 10^{-6} = 1 \text{ V}$$

$$\text{E.I.R.P.} = (1 \times 3)^2 / 30 = 300 \text{ mW}$$

VIII. §15.247(c) : Spurious Radiated Emissions**8.1 Out side band below 1GHz****Test Results :****Model No.** : GPS BT-77**Frequency range** : 30MHz - 1GHz**Detector** : Quasi-Peak Value**Temperature** : 26° C**Humidity** : 54 %**Antenna polarization** : HORIZONTAL ; **Test distance** : 3 m ;

Freq. (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Probe Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Remark
103.98	29.74	-13.76	43.5	28.59	10.64	1.26	10.75	
200.10	27.89	-15.61	43.5	31.95	8.81	1.93	14.80	
255.45	27.20	-18.80	46.0	28.60	12.64	2.26	16.30	
500.20	39.01	-6.99	46.0	33.45	17.30	3.01	14.75	
638.10	39.67	-6.94	46.0	35.07	19.09	3.62	18.72	
825.00	36.67	-9.33	46.0	27.39	20.33	4.08	15.13	

Antenna polarization : VERTICAL ; **Test distance** : 3 m ;

Freq. (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Probe Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Remark
83.46	37.21	-2.79	40.0	37.95	7.63	1.13	9.50	
123.69	30.13	-13.37	43.5	27.92	11.36	1.44	10.59	
207.93	31.13	-12.37	43.5	29.37	7.77	1.99	8.00	
500.20	34.39	-11.61	46.0	29.20	17.30	3.01	15.12	
533.80	35.42	-10.58	46.0	32.50	18.21	3.14	18.43	
749.40	37.42	-8.58	46.0	29.99	19.90	3.91	16.38	
825.70	36.99	-9.01	46.0	27.74	20.33	4.08	15.16	

Note :

1. Level = Read Level + Probe Factor + Cable Loss – Preamp Factor

2. Over Limit = Level – Limit Line

3. All the other frequencies are under the limits more than 20dB

PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,

Taipei Hsien, Taiwan, R. O. C.

TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

8.2 Out side band above 1GHz

Test Results :

Model No. : GPS BT-77

Frequency range : above 1GHz

Temperature : 26° C

Channel : LOW

Detector : Peak / Average Value

Humidity : 54 %

Antenna polarization : HORIZONTAL ; Test distance : 3 m ;

Freq. (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Probe Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Remark
4803	49.48	-24.52	74	44.87	32.79	5.93	34.11	PK
4803	42.14	-11.86	54	37.53	32.79	5.93	34.11	AV

Antenna polarization : VERTICAL ; Test distance : 3 m ;

Freq. (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Probe Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Remark
4803	44.72	-29.28	74	40.11	32.79	5.93	34.11	PK
4803	36.16	-17.84	54	31.55	32.79	5.93	34.11	AV

Note :

1. Level = Read Level + Probe Factor + Cable Loss – Preamp Factor
2. Over Limit = Level – Limit Line
3. All the other frequencies are under the limits more than 20dB

PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,

Taipei Hsien, Taiwan, R. O. C.

TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

Model No. : GPS BT-77

Frequency range : above 1GHz

Temperature : 26° C

Channel : MID

Detector : Peak / Average Value

Humidity : 54 %

Antenna polarization : HORIZONTAL ; Test distance : 3 m ;

		Over	Limit	Read	Probe	Cable	Preamp	
Freq.	Level	Limit	Line	Level	Factor	Loss	Factor	Remark
(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV)	(dB/m)	(dB)	(dB)	
4882	50.71	-23.29	74	45.71	33.10	5.96	34.06	PK
4882	40.97	-13.03	54	35.97	33.10	5.96	34.06	AV

Antenna polarization : VERTICAL ; Test distance : 3 m ;

		Over	Limit	Read	Probe	Cable	Preamp	
Freq.	Level	Limit	Line	Level	Factor	Loss	Factor	Remark
(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV)	(dB/m)	(dB)	(dB)	
4882	46.53	-27.47	74	41.53	33.10	5.96	34.06	PK
4882	38.43	-15.57	54	33.43	33.10	5.96	34.06	AV

Note :

1. Level = Read Level + Probe Factor + Cable Loss – Preamp Factor
2. Over Limit = Level – Limit Line
3. All the other frequencies are under the limits more than 20dB

PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,

Taipei Hsien, Taiwan, R. O. C.

TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

Model No. : GPS BT-77

Frequency range : above 1GHz

Detector : Peak / Average Value

Temperature : 26° C

Humidity : 54 %

Channel : HIGH

Antenna polarization : HORIZONTAL ; Test distance : 3 m ;

		Over	Limit	Read	Probe	Cable	Preamp	
Freq.	Level	Limit	Line	Level	Factor	Loss	Factor	Remark
(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV)	(dB/m)	(dB)	(dB)	
4962	49.92	-24.08	74	44.55	33.40	5.99	34.02	PK
4962	41.19	-12.81	54	35.82	33.40	5.99	34.02	AV

Antenna polarization : VERTICAL ; Test distance : 3 m ;

		Over	Limit	Read	Probe	Cable	Preamp	
Freq.	Level	Limit	Line	Level	Factor	Loss	Factor	Remark
(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV)	(dB/m)	(dB)	(dB)	
4962	45.89	-28.11	74	40.52	33.40	5.99	34.02	PK
4962	38.24	-15.76	54	32.87	33.40	5.99	34.02	AV

Note :

1. Level = Read Level + Probe Factor + Cable Loss – Preamp Factor
2. Over Limit = Level – Limit Line
3. All the other frequencies are under the limits more than 20dB

8.3 Spurious Radiate Emission Testing Photos

EUT Model No. GPS BT-77

< FRONT VIEW >




< REAR VIEW >



IX. §15.247(c) : Band-edges Compliance

Channel : CH LOW

Polarity : Horizontal



Test method : Public Notice DA 00-705

Detect : Peak Value

Marker-Delta method :

50.32dBuV/m-25.47 dBuV/m =24.85dBuV/m

61.80 dBuV/m-24.85 dBuV/m=36.95 dBuV/m

*36.95dBuV/m<Average Limit (54dBuV/m)

PEP Testing Laboratory


12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

Channel : CH HIGH

Polarity : Horizontal



Test method : Public Notice DA 00-705

Detect : Peak Value

Marker-Delta method :

$64.93\text{dB}\mu\text{V}/\text{m} - 26.09\text{ dB}\mu\text{V}/\text{m} = 38.84\text{dB}\mu\text{V}/\text{m}$

$68.30\text{ dB}\mu\text{V}/\text{m} - 38.84\text{ dB}\mu\text{V}/\text{m} = 29.46\text{ dB}\mu\text{V}/\text{m}$

$*29.46\text{dB}\mu\text{V}/\text{m} < \text{Average Limit } (54\text{dB}\mu\text{V}/\text{m})$

PEP Testing Laboratory


12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

Channel : CH LOW

Polarity : Vertical



PEP Testing Laboratory


12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

Channel : CH HIGH

Polarity : Vertical



X. §15.247(d) : Peak Power Spectral Density

10.1 Test Procedure

- (1) The Peak Power Spectral Density was measured at the EUT antenna terminal in max hold analyzer mode with span wide enough to capture the hopping channel emissions.
- (2) Set Spectrum as RBW=VBW=3KHz , Sweptime:auto.
- (3) 10.3 Spectrum Plot Data show the Peak Power Spectral Density test results.

10.2 Test result of Peak Power Spectral Density

Channel	Frequency (MHz)	Level (dBm)	Limit (dBm)	Pass/Fail
LOW	2401.88	-37.15	8	Pass
MID	2441.01	-31.33	8	Pass
HIGH	2479.88	-29.55	8	Pass

Note:

1. "S.P. read" means spectrum analyzer read power density.
2. "C.F." means correct factor = antenna factor + cable loss – Preamplifier Gain.
3. "Level" means power spectral density.

$$E.R.P. = (E d)^2 / 30G$$

where E (V) = S.P. read + C.F.

d (m) = measurement distance = 3m

G = 1 (the gain of the transmitting antenna over isotropic antenna)

Example :

If Level = 120 dBuV/m

$$10^{(120/20)} \times 10^{-6} = 1 \text{ V}$$

$$\begin{aligned} E.R.P. &= (1 \times 3)^2 / 30 = 300 \text{ mW} = 10 \text{ Log } (300\text{mW}/1\text{mW}) \\ &= 24.77\text{dBm} \end{aligned}$$

PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236


FCC ID : SRKWPBT77X

REPORT NO. : E930751

10.3 Spectrum Plot Data

Channel : CH LOW

Polarity : Horizontal




PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

Channel : CH MID
Polarity : Horizontal



PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X


REPORT NO. : E930751

Channel : CH HIGH

Polarity : Horizontal



緯鑫科技股份有限公司
PEP Testing Laboratory



Site : Shih-Chi : Chamber No.3
Condition : 3m HORN ANTENNA H.3 HORIZONTAL
EUT : E930751
Power : AC 120V 60Hz
Memo : Peak Power Spectral Density
Memo : TX ON
Channel : HIGH

	Freq	Level	Over	Limit	Read	Probe	Cable Preamp		Remark
			Limit	Line			Loss	Factor	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	
1	2479.600	65.60	-----	-----	67.62	26.56	4.17	34.69	

PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,

Taipei Hsien, Taiwan, R. O. C.

TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

XI. List of Test Instruments

Test Mode	Instrument	Model No.	Serial No.	Next Cal. Date	Cal. Interval
Conduction (No.1)	R & S Receiver	ESHS10	830223/008	May 22, 2005	1Year
	Rolf Heine LISN	NNB-4/63TL	98008	May 01, 2005	1Year
	R & S LISN	ESH3-Z5	844982/039	Aug. 06, 2005	1Year
	Spectrum Analyzer	R3261A	91720076	June 08, 2005	1Year
	RF Cable	Rg400	N/A	May 12, 2005	1Year
	Schaffner ISN	T411	N/A	June 29, 2005	1Year
Radiation (OP No.3)	R & S Receiver	ESBI	845658/003	July 28, 2005	1Year
	Schaffner Pre-Amp.	CPA-9232	1012	Aug. 20, 2005	1Year
	SCJWARZBECL Antenna	VULB9161	D-69250	May 19, 2005	1Year
	COM-Power Horn Ant.	AH-118 (1GHz~18GHz)	10095	May 25, 2005	1Year
	RF Cable	No.2	N/A	Feb. 19, 2005	1Year
	SCHWARZBECK Precision Dipole Ant.	VHAP (30MHz~1GHz)	970+971 953+954	June 26, 2006	3Year
	R & S Signal Generator	SMY01	829846/038	Feb. 16, 2005	2Year
Chamber (No. 3)	Spectrum Analyzer	FSP 30	100157	Aug. 30, 2005	1Year
	Pre-Amplifier	CPA-9232	1027	Feb. 24, 2005	1Year
	Antenna	VULB9160	3074	July 24, 2004	1Year
	Signal Generator	SMY02	829846/0358	Jane 29, 2005	2Year
	RF Cable	NO.3	N/A	Feb. 19, 2005	1Year
	HORN ANTENNA	AH-118	10095	May 13, 2005	1Year

XII. EUT Photos

EUT Model No. GPS BT-77




PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.

TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751




PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751



PEP Testing Laboratory

12-3Fl, No. 27-1, Lane 169, Kang-Ning St., Hsi-Chih,
Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-26922097 FAX: 886-2-26956236

FCC ID : SRKWPBT77X

REPORT NO. : E930751

