



FCC RF Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : WCDMA/LTE CPE
BRAND NAME : ZTE
MODEL NAME : MF279T
FCC ID : SRQ-MF279T
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure

The product was received on Oct. 18, 2017 and testing was completed on Nov. 10, 2017. We, Sporton International (KunShan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (KunShan) Inc., the test report shall not be reproduced except in full.

Approved by: James Huang / Manager



Sporton International (Kunshan) Inc.
No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335
China



TABLE OF CONTENTS

1	GENERAL DESCRIPTION	5
1.1	Applicant	5
1.2	Manufacturer	5
1.3	Product Feature of Equipment Under Test.....	5
1.4	Product Specification of Equipment Under Test.....	6
1.5	Modification of EUT	7
1.6	Testing Location	7
1.7	Applicable Standards.....	8
2	TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1	Carrier Frequency and Channel	9
2.2	Test Mode	10
2.3	Connection Diagram of Test System.....	12
2.4	Support Unit used in test configuration and system	13
2.5	EUT Operation Test Setup	13
2.6	Measurement Results Explanation Example.....	14
3	TEST RESULT	15
3.1	6dB and 26dB and 99% Occupied Bandwidth Measurement	15
3.2	Maximum Conducted Output Power Measurement	18
3.3	Power Spectral Density Measurement	19
3.4	Unwanted Emissions Measurement.....	22
3.5	AC Conducted Emission Measurement.....	28
3.6	Frequency Stability Measurement.....	32
3.7	Automatically Discontinue Transmission	33
3.8	Antenna Requirements	34
4	LIST OF MEASURING EQUIPMENT	35
5	UNCERTAINTY OF EVALUATION	36
APPENDIX A. CONDUCTED TEST RESULTS		
APPENDIX B. RADIATED SPURIOUS EMISSION		
APPENDIX C. DUTY CYCLE PLOTS		
APPENDIX D. SETUP PHOTOGRAPHS		



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR7O1802C	Rev. 01	Initial issue of report	Nov. 22, 2017

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB, 26dB and 99% Occupied Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 1.19 dB at 11650.000 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 10.42 dB at 3.681 MHz
3.6	15.407(g)	Frequency Stability	Within Operation Band	Pass	-
3.7	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.8	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	WCDMA/LTE CPE
Brand Name	ZTE
Model Name	MF279T
FCC ID	SRQ-MF279T
EUT supports Radios application	WCDMA/HSPA/ HSPA+ (16QAM uplink is not supported)/LTE/ WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80
IMEI Code	Conducted: 990008960001894 Conduction: N/A Radiation: N/A
HW Version	MF279THW1.0
SW Version	MF279TV1.2
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification												
Tx/Rx Channel Frequency Range		5745 MHz ~ 5825 MHz										
Maximum Output Power		<5745 MHz ~ 5825 MHz> <Ant. 1> 802.11a : 16.95 dBm / 0.0519 W 802.11n HT20 : 16.95 dBm / 0.0495 W 802.11n HT40 : 17.23 dBm / 0.0528 W 802.11ac VHT20: 17.01 dBm / 0.0502 W 802.11ac VHT40: 16.82 dBm / 0.0481 W 802.11ac VHT80: 16.98 dBm / 0.0499 W <Ant. 2> 802.11a : 16.97 dBm / 0.0459 W 802.11n HT20 : 17.06 dBm / 0.0508 W 802.11n HT40 : 16.94 dBm / 0.0494 W 802.11ac VHT20: 17.08 dBm / 0.0511 W 802.11ac VHT40: 16.90 dBm / 0.0490 W 802.11ac VHT80: 17.08 dBm / 0.0511 W MIMO <Ant. 1 + 2> 802.11n HT20 : 19.23 dBm / 0.0838 W 802.11n HT40 : 19.42 dBm / 0.0875 W 802.11ac VHT20: 19.37 dBm / 0.0865 W 802.11ac VHT40: 19.41 dBm / 0.0873 W 802.11ac VHT80: 19.10 dBm / 0.0813 W										
99% Occupied Bandwidth		<Ant. 1> 802.11n HT40 : 36.06 MHz <Ant. 2> 802.11a : 17.23 MHz 802.11ac VHT20 : 18.13 MHz 802.11ac VHT80 : 75.76 MHz MIMO <Ant. 1 + 2> 802.11n HT40 : 36.16 MHz 802.11ac VHT20 : 18.38 MHz 802.11ac VHT80 : 75.76 MHz										
Type of Modulation		802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)										
Antenna Type / Gain		<Ant. 1> : PIFA Antenna with gain 2.50 dBi <Ant. 2> : PIFA Antenna with gain 2.50 dBi										
Antenna Function Description		<table><tr><td></td><td>Ant. 1</td><td>Ant. 2</td></tr><tr><td>802.11 a/n/ac</td><td>V</td><td>V</td></tr><tr><td>802.11 n/ac MIMO</td><td>V</td><td>V</td></tr></table>			Ant. 1	Ant. 2	802.11 a/n/ac	V	V	802.11 n/ac MIMO	V	V
	Ant. 1	Ant. 2										
802.11 a/n/ac	V	V										
802.11 n/ac MIMO	V	V										

Note:

1. MIMO Ant. 1+2 is a calculated result from sum of the power MIMO Ant. 1 and MIMO Ant. 2.
2. For 802.11n HT20 / ac VHT20 and 802.11n HT40 / ac VHT40 mode, the whole testing have assessed only 802.11 ac VHT20/ HT40 by referring to their maximum conducted power.



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0) and the FCC designation No. is CN5013.

Test Site	Sporton International (Kunshan) Inc.			
Test Site Location	No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China TEL : +86-512-57900158 FAX : +86-512-57900958			
Test Site No.	Sporton Site No.			FCC Test Firm Registration No.
	TH01-KS	03CH03-KS	CO01-KS	630927

Note: The test site complies with ANSI C63.4 2014 requirement.



1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ FCC KDB 644545 D03 Guidance for IEEE 802 11ac New Rules v01
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases were recorded in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5745-5825 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "[#]" were 802.11ac VHT80.

2.2 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Single Antenna

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT80	MCS0

MIMO Antenna

Modulation	Data Rate
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT80	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : WCDMA Band V Idle + Phone Link + WLAN Link(5G) + Adapter + Lan Link




Ch. #		Band IV : 5745-5825 MHz		
		802.11a	802.11n VHT20	802.11n HT40
L	Low	149	149	151
M	Middle	157	157	-
H	High	165	165	159


Ch. #		Band IV : 5745-5825 MHz	
		802.11ac VHT80	
L	Low	-	
M	Middle	155	
H	High	-	

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8m
2.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8m DC O/P: Shielded, 1.8 m
3.	Telephone*2	BBK	HCD007(6082)TSD	N/A	N/A	N/A
4.	RJ45 Cable	N/A	N/A	N/A	Unshielded, 1.8m	N/A
5.	RJ11 Cable	N/A	N/A	N/A	Unshielded, 1.8m	N/A

2.5 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the Notebook under large package sizes transmission.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 6.9 dB.

Offset(dB) = RF cable loss(dB).

= 6.9 (dB)

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures



1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.
Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.


3.1.4 Test Setup



3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.





Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.
Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).


- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz.
- Set VBW $\geq$ 1 MHz.
- Number of points in sweep $\geq$ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (c): Measure and add $10 \log(N_{\text{ANT}})$ dB.


With this technique, spectrum measurements are performed at each output of the device, but rather than summing the spectra or the spectral peaks across the outputs, the quantity $10 \log(N_{\text{ANT}})$ dB is added to each spectrum value before comparing to the emission limit. The addition of $10 \log(N_{\text{ANT}})$ dB serves to apportion the emission limit among the N_{ANT} outputs so that each output is permitted to contribute no more than $1/N_{\text{ANT}}^{\text{th}}$ of the PSD limit.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part 15.205.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

- (2) Unwanted spurious emissions fallen in restricted bands per FCC Part 15.205 shall comply with the general field strength limits set forth in § 15.209 as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \quad \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dB μ V/m)
-17	78.3
- 27	68.3

(3) KDB789033 D02 v01r04 G)2)c)

- (i) Section 15.407(b)(1) to (b)(3) specify the unwanted emission limits for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.³
- (ii) Section 15.407(b)(4) specifies the unwanted emission limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are in terms of a Peak detector. An alternative to the band emissions mask is specified in Section 15.407(b)(4)(ii). The alternative limits are based on the highest antenna gain specified in the filing. There are also marketing and importation restrictions for the devices using the alternative limit.⁴

Note 3: An out-of-band emission that complies with both the average and peak limits of Section 15.209 is not required to satisfy the -27 dBm/MHz peak emission limit.

Note 4: Only devices with antenna gains of 10 dBi or less may be approved using the emission limits specified in Section 15.247(d) till March 2, 2018; all other devices operating in this band must use the mask specified in Section 15.407(b)(4)(i).

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.
Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW $\geq$ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz

- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


(4) Procedures for Average Unwanted Emissions Measurements Above 1000MHz

- RBW = 1 MHz
- VBW = 3 MHz
- Detector = power averaging (rms), set span/(# of points in sweep) $\geq$ RBW/2.
- Averaging type = power averaging(RMS)
- The correction factor shall be offset is 10 log (1/x), where x is the duty cycle.


2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.4.7 Duty Cycle

Please refer to Appendix C.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup






3.5.5 Test Result of AC Conducted Emission





Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WCDMA Band V Idle + Phone Link + WLAN Link(5G) + Adapter + Lan Link		



Site : CO01-KS
Condition : FCC PART 15E LISN-N-161017-060103 NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.162	47.51	-17.83	65.34	36.60	0.34	10.57	QP
2	0.162	32.21	-23.13	55.34	21.30	0.34	10.57	Average
3	0.186	44.03	-20.17	64.20	33.20	0.33	10.50	QP
4	0.186	30.03	-24.17	54.20	19.20	0.33	10.50	Average
5	3.840	40.86	-15.14	56.00	30.30	0.39	10.17	QP
6 *	3.840	33.86	-12.14	46.00	23.30	0.39	10.17	Average
7	4.180	40.86	-15.14	56.00	30.29	0.39	10.18	QP
8	4.180	32.86	-13.14	46.00	22.29	0.39	10.18	Average
9	9.654	42.52	-17.48	60.00	31.90	0.29	10.33	QP
10	9.654	34.22	-15.78	50.00	23.60	0.29	10.33	Average
11	13.915	35.28	-24.72	60.00	24.60	0.28	10.40	QP
12	13.915	28.88	-21.12	50.00	18.20	0.28	10.40	Average

3.6 Frequency Stability Measurement

3.6.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
2. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
3. The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

3.6.4 Test Setup



3.6.5 Test Result of Frequency Stability

Please refer to Appendix A.



3.7 Automatically Discontinue Transmission

3.7.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

3.8 Antenna Requirements

3.8.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2) ,if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.8.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.8.3 Antenna Gain

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(N_{ANT}/N_{SS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with G_{ANT} set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain G_{ANT} is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

			DG for Power (dBi)	DG for PSD (dBi)	Power Limit Reduction (dB)	PSD Limit Reduction (dB)
	Ant 1 (dBi)	Ant 2 (dBi)				
Band IV	2.50	2.50	2.50	5.51	0.00	0.00

Power limit reduction = Composite gain – 6dBi, (min = 0)

PSD limit reduction = Composite gain + PSD Array gain – 6dBi, (min = 0)



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 08, 2017	Oct. 27, 2017~ Oct. 30, 2017	Aug. 07, 2018	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 19, 2017	Oct. 27, 2017~ Oct. 30, 2017	Jan. 18, 2018	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 19, 2017	Oct. 27, 2017~ Oct. 30, 2017	Jan. 18, 2018	Conducted (TH01-KS)
Thermal Chamber	Hongzhan	LP-150U	HZ014011440	-40~+150°C 20%~95%RH	Apr. 18, 2017	Oct. 27, 2017~ Oct. 30, 2017	Apr. 17, 2018	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz; Max 30dBm	Oct. 19, 2017	Nov. 10, 2017	Oct. 18, 2018	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz	Apr. 18, 2017	Nov. 10, 2017	Apr. 17, 2018	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 23, 2016	Nov. 10, 2017	Nov. 22, 2017	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	35406	25MHz~2GHz	Apr. 22, 2017	Nov. 10, 2017	Apr. 21, 2018	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1356	1GHz~18GHz	Apr. 22, 2017	Nov. 10, 2017	Apr. 21, 2018	Radiation (03CH03-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Feb. 15, 2017	Nov. 10, 2017	Feb. 14, 2018	Radiation (03CH03-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1000MHz / 32 dB	Apr. 18, 2017	Nov. 10, 2017	Apr. 17, 2018	Radiation (03CH03-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18GHz~40GHz	Oct. 12, 2017	Nov. 10, 2017	Oct. 11, 2018	Radiation (03CH03-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	1GHz~18GHz	Apr. 18, 2017	Nov. 10, 2017	Apr. 17, 2018	Radiation (03CH03-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Oct. 12, 2017	Nov. 10, 2017	Oct. 11, 2018	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Nov. 10, 2017	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Nov. 10, 2017	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Nov. 10, 2017	NCR	Radiation (03CH03-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 20, 2017	Oct. 31, 2017	Apr. 19, 2018	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2017	Oct. 31, 2017	Oct. 12, 2018	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2017	Oct. 31, 2017	Oct. 12, 2018	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2017	Oct. 31, 2017	Oct. 11, 2018	Conduction (CO01-KS)

NCR: No Calibration Required

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.3dB
--	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.6dB
--	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.5dB
--	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.7dB
--	-------



Appendix A. Conducted Test Results

Report Number : FR7O1802C

Test Engineer:	Silent Hai	Temperature:	21~25	°C
Test Date:	2017/10/27 ~ 2017/10/30	Relative Humidity:	51~55	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV													
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)		Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745		17.23		20.93		16.30	0.5	0.5	Pass
11a	6Mbps	1	157	5785		17.23		21.13		16.32	0.5	0.5	Pass
11a	6Mbps	1	165	5825		17.23		21.18		16.30	0.5	0.5	Pass
HT40	MCS0	1	151	5755	35.96		40.55		35.09		0.5	0.5	Pass
HT40	MCS0	1	159	5795	36.06		41.18		35.09		0.5	0.5	Pass
VHT20	MCS0	1	149	5745		18.13		21.68		17.16	0.5	0.5	Pass
VHT20	MCS0	1	157	5785		18.13		21.68		17.16	0.5	0.5	Pass
VHT20	MCS0	1	165	5825		18.13		21.68		17.14	0.5	0.5	Pass
VHT80	MCS0	1	155	5775		75.76		83.60		75.68	0.5	0.5	Pass
HT40	MCS0	2	151	5755	36.16	36.16	40.73	40.55	35.05	31.37	0.5		Pass
HT40	MCS0	2	159	5795	36.06	35.86	40.91	40.28	35.13	35.13	0.5		Pass
VHT20	MCS0	2	149	5745	18.23	17.93	21.83	21.38	17.16	15.13	0.5		Pass
VHT20	MCS0	2	157	5785	18.28	17.98	21.93	21.38	17.16	15.45	0.5		Pass
VHT20	MCS0	2	165	5825	18.38	18.08	22.03	21.63	17.52	15.96	0.5		Pass
VHT80	MCS0	2	155	5775	75.76	75.52	84.56	82.32	75.68	75.29	0.5		Pass

TEST RESULTS DATA
Average Power Table

Band IV														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	0.11	0.10	16.95	16.97		30.00	30.00	2.50	2.50	Pass
11a	6Mbps	1	157	5785	0.11	0.10	16.67	16.62		30.00	30.00	2.50	2.50	Pass
11a	6Mbps	1	165	5825	0.11	0.10	16.36	16.19		30.00	30.00	2.50	2.50	Pass
HT20	MCS0	1	149	5745	0.04	0.04	16.95	16.42		30.00	30.00	2.50	2.50	Pass
HT20	MCS0	1	157	5785	0.04	0.04	16.78	16.65		30.00	30.00	2.50	2.50	Pass
HT20	MCS0	1	165	5825	0.04	0.04	16.42	17.06		30.00	30.00	2.50	2.50	Pass
HT40	MCS0	1	151	5755	0.11	0.09	17.23	16.61		30.00	30.00	2.50	2.50	Pass
HT40	MCS0	1	159	5795	0.11	0.09	16.76	16.94		30.00	30.00	2.50	2.50	Pass
VHT20	MCS0	1	149	5745	0.06	0.06	17.01	16.34		30.00	30.00	2.50	2.50	Pass
VHT20	MCS0	1	157	5785	0.06	0.06	16.77	16.67		30.00	30.00	2.50	2.50	Pass
VHT20	MCS0	1	165	5825	0.06	0.06	16.45	17.08		30.00	30.00	2.50	2.50	Pass
VHT80	MCS0	1	155	5775	0.24	0.24	16.98	17.08		30.00	30.00	2.50	2.50	Pass
HT40	MCS0	2	151	5755	0.12	0.12	17.18	15.49	19.42	30.00		2.50		Pass
HT40	MCS0	2	159	5795	0.12	0.12	16.74	15.94	19.36	30.00		2.50		Pass
VHT20	MCS0	2	149	5745	0.06	0.04	16.70	15.71	19.24	30.00		2.50		Pass
VHT20	MCS0	2	157	5785	0.06	0.04	16.74	15.95	19.37	30.00		2.50		Pass
VHT20	MCS0	2	165	5825	0.06	0.04	15.99	16.16	19.09	30.00		2.50		Pass
VHT80	MCS0	2	155	5775	0.24	0.24	16.75	15.31	19.10	30.00		2.50		Pass

TEST RESULTS DATA
Power Spectral Density

Band IV																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	0.11	0.10	2.22	2.22		3.03		30.00	30.00	2.50	2.50	Pass
11a	6Mbps	1	157	5785	0.11	0.10	2.22	2.22		3.45		30.00	30.00	2.50	2.50	Pass
11a	6Mbps	1	165	5825	0.11	0.10	2.22	2.22		3.76		30.00	30.00	2.50	2.50	Pass
HT40	MCS0	1	151	5755	0.11	0.09	2.22	2.22	0.55			30.00	30.00	2.50	2.50	Pass
HT40	MCS0	1	159	5795	0.11	0.09	2.22	2.22	0.22			30.00	30.00	2.50	2.50	Pass
VHT20	MCS0	1	149	5745	0.06	0.06	2.22	2.22		2.74		30.00	30.00	2.50	2.50	Pass
VHT20	MCS0	1	157	5785	0.06	0.06	2.22	2.22		2.77		30.00	30.00	2.50	2.50	Pass
VHT20	MCS0	1	165	5825	0.06	0.06	2.22	2.22		3.15		30.00	30.00	2.50	2.50	Pass
VHT80	MCS0	1	155	5775	0.24	0.24	2.22	2.22		-2.70		30.00	30.00	2.50	2.50	Pass
HT40	MCS0	2	151	5755	0.12	0.12	2.22				3.70	30.00		5.51		Pass
HT40	MCS0	2	159	5795	0.12	0.12	2.22				3.67	30.00		5.51		Pass
VHT20	MCS0	2	149	5745	0.06	0.04	2.22				6.53	30.00		5.51		Pass
VHT20	MCS0	2	157	5785	0.06	0.04	2.22				6.32	30.00		5.51		Pass
VHT20	MCS0	2	165	5825	0.06	0.04	2.22				6.52	30.00		5.51		Pass
VHT80	MCS0	2	155	5775	0.24	0.24	2.22				0.43	30.00		5.51		Pass

TEST RESULTS DATA
Frequency Stability

Band IV										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)	Note
11a	6Mbps	1	149	5745	5745.000	0.000	0.00	50	3.8	
11a	6Mbps	1	149	5745	5745.025	0.025	4.35	-30	3.8	
11a	6Mbps	1	149	5745	5745.000	0.000	0.00	20	4.35	
11a	6Mbps	1	149	5745	5744.975	-0.025	-4.35	20	3.4	
11a	6Mbps	1	149	5745	5744.975	-0.025	-4.35	20	3.8	



Appendix B. Radiated Spurious Emission

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5602.4	51.72	-16.58	68.3	44.86	30.73	12.44	36.31	347	169	P	H
		5699.99	54.22	-51.07	105.29	46.91	31.07	12.53	36.29	347	169	P	H
		5719.6	55.77	-55.02	110.79	48.16	31.32	12.57	36.28	347	169	P	H
		5724.8	65.74	-56.1	121.84	58.13	31.32	12.57	36.28	347	169	P	H
		5740	108.73	-	-	100.98	31.44	12.59	36.28	347	169	P	H
		5740	101.96	-	-	94.21	31.44	12.59	36.28	347	169	A	H
		5604.8	50.26	-18.04	68.3	43.4	30.73	12.44	36.31	323	49	P	V
		5699.99	53.42	-51.87	105.29	46.11	31.07	12.53	36.29	323	49	P	V
		5706	54.93	-52.05	106.98	47.47	31.19	12.55	36.28	323	49	P	V
		5724.8	62.44	-59.4	121.84	54.83	31.32	12.57	36.28	323	49	P	V
		5738	107.53	-	-	99.78	31.44	12.59	36.28	323	49	P	V
		5738	100.61	-	-	92.86	31.44	12.59	36.28	323	49	A	V



WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		5634.4	51.64	-16.66	68.3	44.75	30.7	12.48	36.29	100	206	P	H
		5686.8	51.54	-44.02	95.56	44.23	31.07	12.53	36.29	100	206	P	H
		5718	53.89	-56.45	110.34	46.28	31.32	12.57	36.28	100	206	P	H
		5720.01	50.86	-60.06	110.92	43.25	31.32	12.57	36.28	100	206	P	H
		5782	108.8	-	-	100.78	31.68	12.62	36.28	100	206	P	H
		5782	101.37	-	-	93.35	31.68	12.62	36.28	100	206	A	H
		5853.2	51.21	-63.79	115	42.61	32.18	12.69	36.27	100	206	P	H
		5868.8	51.4	-55.63	107.03	42.66	32.3	12.71	36.27	100	206	P	H
		5896	50.47	-39.25	89.72	41.6	32.41	12.75	36.29	100	206	P	H
		5930.8	51.82	-16.48	68.3	42.84	32.51	12.78	36.31	100	206	P	H
		5627.2	52	-16.3	68.3	45.12	30.72	12.46	36.3	374	52	P	V
		5684.4	52.2	-41.59	93.79	44.89	31.07	12.53	36.29	374	52	P	V
		5713.2	54.23	-54.77	109	46.77	31.19	12.55	36.28	374	52	P	V
		5724.4	52.19	-68.74	120.93	44.58	31.32	12.57	36.28	374	52	P	V
		5782	109.04	-	-	101.02	31.68	12.62	36.28	374	52	P	V
		5782	101.53	-	-	93.51	31.68	12.62	36.28	374	52	A	V
		5850.4	51	-70.39	121.39	42.4	32.18	12.69	36.27	374	52	P	V
		5866	51.21	-56.61	107.82	42.47	32.3	12.71	36.27	374	52	P	V
		5878	50.91	-52.16	103.07	42.11	32.35	12.73	36.28	374	52	P	V
		5948.8	51.24	-17.06	68.3	42.19	32.57	12.8	36.32	374	52	P	V



WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz		5822	108.76	-	-	100.31	32.05	12.67	36.27	100	208	P	H
		5822	101.33	-	-	92.88	32.05	12.67	36.27	100	208	A	H
		5852	53.72	-64.02	117.74	45.12	32.18	12.69	36.27	100	208	P	H
		5863.2	54.05	-54.55	108.6	45.31	32.3	12.71	36.27	100	208	P	H
		5879.2	52.5	-49.68	102.18	43.7	32.35	12.73	36.28	100	208	P	H
		5928.4	51.14	-17.16	68.3	42.16	32.51	12.78	36.31	100	208	P	H
		5820	108.64	-	-	100.19	32.05	12.67	36.27	371	57	P	V
		5820	100.85	-	-	92.4	32.05	12.67	36.27	371	57	A	V
		5851.2	52.54	-67.02	119.56	43.94	32.18	12.69	36.27	371	57	P	V
		5869.6	55.07	-51.74	106.81	46.33	32.3	12.71	36.27	371	57	P	V
		5881.6	51.58	-48.82	100.4	42.78	32.35	12.73	36.28	371	57	P	V
		5982.4	50.87	-17.43	68.3	41.7	32.67	12.84	36.34	371	57	P	V
Remark		1. No other spurious found. 2. All results are PASS against Peak and Average limit line.											



Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a		11485	50.85	-23.15	74	61.49	38.58	16.13	65.35	300	360	P	H
CH 149		11490	55.59	-18.41	74	66.23	38.58	16.13	65.35	100	248	P	V
5745MHz		11490	46.79	-7.21	54	57.43	38.58	16.13	65.35	100	248	A	V
802.11a		11565	53.02	-20.98	74	63.76	38.48	16.2	65.42	100	344	P	H
CH 157		11565	46.15	-7.85	54	56.89	38.48	16.2	65.42	100	344	A	H
5785MHz		11565	62.95	-11.05	74	73.69	38.48	16.2	65.42	311	111	P	V
		11565	52.6	-1.4	54	63.34	38.48	16.2	65.42	311	111	A	V
802.11a		11645	57.03	-16.97	74	68.01	38.27	16.29	65.54	273	349	P	H
CH 165		11645	47.87	-6.13	54	58.85	38.27	16.29	65.54	273	349	A	H
5825MHz		11650	61.95	-12.05	74	72.93	38.27	16.29	65.54	104	284	P	V
		11650	52.81	-1.19	54	63.79	38.27	16.29	65.54	104	284	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 - 5725~5850MHz
WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 165 5825MHz		5824	114.71	-	-	106.26	32.05	12.67	36.27	365	57	P	H
		5824	106.57	-	-	98.12	32.05	12.67	36.27	365	57	A	H
		5850.01	65.28	-57	122.28	56.68	32.18	12.69	36.27	365	57	P	H
		5867.6	61.81	-45.56	107.37	53.07	32.3	12.71	36.27	365	57	P	H
		5890.4	56.03	-37.84	93.87	47.16	32.41	12.75	36.29	365	57	P	H
		5940	53.9	-14.4	68.3	44.85	32.57	12.8	36.32	365	57	P	H
		5822	107.76	-	-	99.31	32.05	12.67	36.27	301	13	P	V
		5822	100.82	-	-	92.37	32.05	12.67	36.27	301	13	A	V
		5850.4	57.56	-63.83	121.39	48.96	32.18	12.69	36.27	301	13	P	V
		5857.2	57.44	-52.84	110.28	48.7	32.3	12.71	36.27	301	13	P	V
		5875.6	53.09	-51.76	104.85	44.29	32.35	12.73	36.28	301	13	P	V
		5950.8	52.92	-15.38	68.3	43.87	32.57	12.8	36.32	301	13	P	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												


Band 4 5725~5850MHz
WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz		11650	53.69	-20.31	74	64.67	38.27	16.29	65.54	300	360	P	H
		11650	46.53	-7.47	54	57.51	38.27	16.29	65.54	105	204	A	H
		11645	56.23	-17.77	74	67.21	38.27	16.29	65.54	100	129	P	V
		11645	46.23	-7.77	54	57.21	38.27	16.29	65.54	100	129	A	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



Band 4 - 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 151 5755MHz		5629.6	56.28	-12.02	68.3	49.4	30.72	12.46	36.3	317	57	P	H
		5699.9	61.59	-43.64	105.23	54.28	31.07	12.53	36.29	317	57	P	H
		5719.9	73.85	-37.02	110.87	66.24	31.32	12.57	36.28	317	57	P	H
		5723.6	76.34	-42.77	119.11	68.73	31.32	12.57	36.28	317	57	P	H
		5752	111.17	-	-	103.29	31.56	12.6	36.28	317	57	P	H
		5752	103.94	-	-	96.06	31.56	12.6	36.28	317	57	A	H
		5850.4	54.88	-66.51	121.39	46.28	32.18	12.69	36.27	317	57	P	H
		5874.8	52.99	-52.37	105.36	44.19	32.35	12.73	36.28	317	57	P	H
		5875.01	52.99	-52.3	105.29	44.19	32.35	12.73	36.28	317	57	P	H
		5928.4	51.64	-16.66	68.3	42.66	32.51	12.78	36.31	317	57	P	H
		5609.2	53.62	-14.68	68.3	46.76	30.73	12.44	36.31	297	17	P	V
		5699.9	56.01	-49.22	105.23	48.7	31.07	12.53	36.29	297	17	P	V
		5719.6	70.05	-40.74	110.79	62.44	31.32	12.57	36.28	297	17	P	V
		5724.8	73.26	-48.58	121.84	65.65	31.32	12.57	36.28	297	17	P	V
		5744	109.01	-	-	101.26	31.44	12.59	36.28	297	17	P	V
		5744	101.14	-	-	93.39	31.44	12.59	36.28	297	17	A	V
		5850.4	51.77	-69.62	121.39	43.17	32.18	12.69	36.27	297	17	P	V
		5867.2	52.36	-55.12	107.48	43.62	32.3	12.71	36.27	297	17	P	V
		5904	51.48	-32.32	83.8	42.61	32.41	12.75	36.29	297	17	P	V
		5956	51.15	-17.15	68.3	42.04	32.62	12.82	36.33	297	17	P	V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 159 5795MHz		5647.6	56.46	-11.84	68.3	49.57	30.7	12.48	36.29	302	72	P	H
		5699.6	56.6	-48.41	105.01	49.29	31.07	12.53	36.29	302	72	P	H
		5719.6	58.11	-52.68	110.79	50.5	31.32	12.57	36.28	302	72	P	H
		5724.4	61.57	-59.36	120.93	53.96	31.32	12.57	36.28	302	72	P	H
		5792	110.72	-	-	102.55	31.81	12.64	36.28	302	72	P	H
		5792	103.99	-	-	95.82	31.81	12.64	36.28	302	72	A	H
		5850.4	61.98	-59.41	121.39	53.38	32.18	12.69	36.27	302	72	P	H
		5856	60.57	-50.05	110.62	51.83	32.3	12.71	36.27	302	72	P	H
		5878.4	55.83	-46.94	102.77	47.03	32.35	12.73	36.28	302	72	P	H
		5942	52.14	-16.16	68.3	43.09	32.57	12.8	36.32	302	72	P	H
		5636	53.86	-14.44	68.3	46.97	30.7	12.48	36.29	301	8	P	V
		5688.8	53.51	-43.53	97.04	46.2	31.07	12.53	36.29	301	8	P	V
		5719.6	55.19	-55.6	110.79	47.58	31.32	12.57	36.28	301	8	P	V
		5722	55.9	-59.56	115.46	48.29	31.32	12.57	36.28	301	8	P	V
		5802	108.73	-	-	100.56	31.81	12.64	36.28	301	8	P	V
		5802	101.16	-	-	92.99	31.81	12.64	36.28	301	8	A	V
		5851.2	58.2	-61.36	119.56	49.6	32.18	12.69	36.27	301	8	P	V
		5854.8	55.67	-55.69	111.36	46.93	32.3	12.71	36.27	301	8	P	V
		5880.4	51.99	-49.3	101.29	43.19	32.35	12.73	36.28	301	8	P	V
		5977.2	50.95	-17.35	68.3	41.78	32.67	12.84	36.34	301	8	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		11510	48.04	-25.96	74	58.64	38.6	16.14	65.34	300	360	P	H
		11510	51.15	-22.85	74	61.75	38.6	16.14	65.34	300	114	P	V
		11510	44.08	-9.92	54	54.68	38.6	16.14	65.34	300	114	A	V
802.11n HT40 CH 159 5795MHz		11590	50.46	-23.54	74	61.3	38.39	16.24	65.47	100	360	P	H
		11590	57.18	-16.82	74	68.02	38.39	16.24	65.47	329	112	P	V
		11590	49.52	-4.48	54	60.36	38.39	16.24	65.47	329	111	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz
WIFI 802.11ac VHT20 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20 CH 149 5745MHz		5600.8	50.91	-17.39	68.3	44.05	30.73	12.44	36.31	301	125	P	H
		5696.4	53.22	-49.43	102.65	45.91	31.07	12.53	36.29	301	125	P	H
		5711.6	54.97	-53.58	108.55	47.51	31.19	12.55	36.28	301	125	P	H
		5722.8	62.02	-55.26	117.28	54.41	31.32	12.57	36.28	301	125	P	H
		5748	107.52	-	-	99.77	31.44	12.59	36.28	301	125	P	H
		5748	101.16	-	-	93.41	31.44	12.59	36.28	301	125	A	H
		5625.6	55.33	-12.97	68.3	48.45	30.72	12.46	36.3	306	93	P	V
		5699.2	59.73	-44.98	104.71	52.42	31.07	12.53	36.29	306	93	P	V
		5710.8	61.61	-46.72	108.33	54.15	31.19	12.55	36.28	306	93	P	V
		5724.8	63.42	-58.42	121.84	55.81	31.32	12.57	36.28	306	93	P	V
		5746	113.38	-	-	105.63	31.44	12.59	36.28	306	93	P	V
		5746	105.73	-	-	97.98	31.44	12.59	36.28	306	93	A	V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20 CH 157 5785MHz		5648.8	51.58	-16.72	68.3	44.69	30.7	12.48	36.29	100	250	P	H
		5650.4	50.92	-17.68	68.6	43.89	30.82	12.5	36.29	100	250	P	H
		5704	52.07	-54.35	106.42	44.61	31.19	12.55	36.28	100	250	P	H
		5720.8	50.76	-61.96	112.72	43.15	31.32	12.57	36.28	100	250	P	H
		5788	107.87	-	-	99.7	31.81	12.64	36.28	100	250	P	H
		5788	100.55	-	-	92.38	31.81	12.64	36.28	100	250	A	H
		5850.4	49.94	-71.45	121.39	41.34	32.18	12.69	36.27	100	250	P	H
		5862	51.98	-56.96	108.94	43.24	32.3	12.71	36.27	100	250	P	H
		5910	50.74	-28.63	79.37	41.82	32.46	12.76	36.3	100	250	P	H
		5961.2	50.78	-17.52	68.3	41.67	32.62	12.82	36.33	100	250	P	H
		5612.8	54.59	-13.71	68.3	47.73	30.73	12.44	36.31	313	170	P	V
		5664.4	54.81	-24.18	78.99	47.78	30.82	12.5	36.29	313	170	P	V
		5701.2	54.73	-50.91	105.64	47.27	31.19	12.55	36.28	313	170	P	V
		5722	54.13	-61.33	115.46	46.52	31.32	12.57	36.28	313	170	P	V
		5786	113.49	-	-	105.32	31.81	12.64	36.28	313	170	P	V
		5786	106.55	-	-	98.38	31.81	12.64	36.28	313	170	A	V
		5851.6	53.56	-65.09	118.65	44.96	32.18	12.69	36.27	313	170	P	V
		5859.6	54.25	-55.36	109.61	45.51	32.3	12.71	36.27	313	170	P	V
		5905.6	53.67	-28.95	82.62	44.75	32.46	12.76	36.3	313	170	P	V
		5947.6	52.89	-15.41	68.3	43.84	32.57	12.8	36.32	313	170	P	V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20 CH 165 5825MHz		5822	109.08	-	-	100.63	32.05	12.67	36.27	293	123	P	H
		5822	101.58	-	-	93.13	32.05	12.67	36.27	293	123	A	H
		5850.01	55.65	-66.63	122.28	47.05	32.18	12.69	36.27	293	123	P	H
		5858	54.37	-55.69	110.06	45.63	32.3	12.71	36.27	293	123	P	H
		5878.8	51.44	-51.04	102.48	42.64	32.35	12.73	36.28	293	123	P	H
		5929.6	51.23	-17.07	68.3	42.25	32.51	12.78	36.31	293	123	P	H
		5828	113.63	-	-	105.18	32.05	12.67	36.27	304	146	P	V
		5828	105.97	-	-	97.52	32.05	12.67	36.27	304	146	A	V
		5850.01	67.18	-55.1	122.28	58.58	32.18	12.69	36.27	304	146	P	V
		5862	58.82	-50.12	108.94	50.08	32.3	12.71	36.27	304	146	P	V
		5883.2	53.89	-45.32	99.21	45.09	32.35	12.73	36.28	304	146	P	V
		5934.8	52.87	-15.43	68.3	43.89	32.51	12.78	36.31	304	146	P	V
Remark		1. No other spurious found. 2. All results are PASS against Peak and Average limit line.											



Band 4 5725~5850MHz

WIFI 802.11ac VHT20 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac		11490	59.23	-14.77	74	69.87	38.58	16.13	65.35	100	237	P	H
VHT20		11490	45.16	-8.84	54	55.8	38.58	16.13	65.35	100	237	A	H
CH 149		11490	53.86	-20.14	74	64.5	38.58	16.13	65.35	100	183	P	V
5745MHz		11490	42.16	-11.84	54	52.8	38.58	16.13	65.35	100	183	A	V
802.11ac		11570	61.42	-12.58	74	72.21	38.43	16.22	65.44	100	121	P	H
VHT20		11570	49.11	-4.89	54	59.9	38.43	16.22	65.44	100	121	A	H
CH 157		11570	56.45	-17.55	74	67.24	38.43	16.22	65.44	100	0	P	V
5785MHz		11570	44.4	-9.6	54	55.19	38.43	16.22	65.44	100	184	A	V
802.11ac		11640	66.82	-7.18	74	77.8	38.27	16.29	65.54	100	234	P	H
VHT20		11640	52.08	-1.92	54	63.06	38.27	16.29	65.54	100	234	A	H
CH 165		11650	57.12	-16.88	74	68.1	38.27	16.29	65.54	100	185	P	V
5825MHz		11650	45.41	-8.59	54	56.39	38.27	16.29	65.54	100	185	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		5647.2	61.29	-7.01	68.3	54.4	30.7	12.48	36.29	318	67	P	H
		5699.2	73.68	-31.03	104.71	66.37	31.07	12.53	36.29	318	67	P	H
		5719.2	77.15	-33.53	110.68	69.54	31.32	12.57	36.28	318	67	P	H
		5723.2	78.19	-40.01	118.2	70.58	31.32	12.57	36.28	318	67	P	H
		5750	107.38	-	-	99.63	31.44	12.59	36.28	318	67	P	H
		5750	99.75	-	-	92	31.44	12.59	36.28	318	67	A	H
		5850	73.94	-48.36	122.3	65.34	32.18	12.69	36.27	318	67	P	H
		5862.8	75.89	-32.82	108.71	67.15	32.3	12.71	36.27	318	67	P	H
		5875.6	67.51	-37.34	104.85	58.71	32.35	12.73	36.28	318	67	P	H
		5924.8	55.6	-12.85	68.45	46.62	32.51	12.78	36.31	318	67	P	H
		5643.2	60.83	-7.47	68.3	53.94	30.7	12.48	36.29	274	15	P	V
		5683.2	68.32	-24.58	92.9	61.14	30.95	12.52	36.29	274	15	P	V
		5719.99	70.14	-40.76	110.9	62.53	31.32	12.57	36.28	274	15	P	V
		5722.4	73.03	-43.34	116.37	65.42	31.32	12.57	36.28	274	15	P	V
		5782	104.37	-	-	96.35	31.68	12.62	36.28	274	15	P	V
		5782	97.45	-	-	89.43	31.68	12.62	36.28	274	15	A	V
		5850	66.48	-55.82	122.3	57.88	32.18	12.69	36.27	274	15	P	V
		5863.6	67.59	-40.9	108.49	58.85	32.3	12.71	36.27	274	15	P	V
		5878.8	59.89	-42.59	102.48	51.09	32.35	12.73	36.28	274	15	P	V
		5953.6	51.95	-16.35	68.3	42.9	32.57	12.8	36.32	274	15	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												


Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac		11550	48	-26	74	58.74	38.48	16.2	65.42	300	360	P	H
VHT80		11550	55.01	-18.99	74	65.75	38.48	16.2	65.42	300	110	P	V
CH 155 5775MHz		11550	45.78	-8.22	54	56.52	38.48	16.2	65.42	300	110	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

WIFI 802.11a (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a LF		32.91	26.06	-13.94	40	31.45	26.14	0.77	32.3	-	-	P	H
		117.3	21.23	-22.27	43.5	33.46	18.48	1.56	32.27	-	-	P	H
		216.24	22.56	-23.44	46	35.54	17.07	2.16	32.21	-	-	P	H
		549.92	27.34	-18.66	46	30.68	24.9	3.52	31.76	-	-	P	H
		902.03	33.29	-12.71	46	31.17	29	4.57	31.45	150	256	P	H
		934.04	33.13	-12.87	46	30.88	29	4.64	31.39	-	-	P	H
		36.79	31.27	-8.73	40	37.94	24.7	0.89	32.26	100	58	P	V
		98.87	25.66	-17.84	43.5	37.66	18.86	1.4	32.26	-	-	P	V
		108.57	27.04	-16.46	43.5	39.09	18.74	1.48	32.27	-	-	P	V
		131.85	25.38	-18.12	43.5	37.93	18.05	1.68	32.28	-	-	P	V
		653.71	29.37	-16.63	46	31.15	25.6	4.32	31.7	-	-	P	V
		896.21	33.32	-12.68	46	31.29	28.93	4.56	31.46	-	-	P	V
Remark		1. No other spurious found. 2. All results are PASS against limit line.											



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)


= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix C. Duty Cycle Plots


Antenna	Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
1	802.11 a	97.61	2.073	0.483	1kHz
2	802.11 a	97.62	2.080	0.481	1kHz
1+2	802.11n HT20	98.99	-	-	10Hz
1+2	802.11n HT40	97.38	2.428	0.412	1kHz
1+2	802.11ac VHT80	94.64	1.152	0.868	1kHz

802.11a Ant.1






802.11a Ant.2




802.11n HT20 Ant.1+2





802.11n HT40 Ant.1+2



802.11acVHT80 Ant.1+2

