

EMC TEST REPORT

Applicant:	ZTE Corporation
Address:	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China

Manufacturer or Supplier	ZTE Corporation
Address	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China
Product	LTE Digital Mobile Phone
Brand Name	ZTE
Model Name	NX529J/nubia Z11 mini/BGH nubia Z11 mini
FCC ID	SRQ-NX529J-US
Date of tests	Jun. 15, 2016 ~ July 05, 2016 Aug. 02, 2016 ~ Aug. 11, 2016

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

- ☒ **FCC Part 15, Subpart B, Class B**
- ☒ **ANSI C63.4:2014**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Issued by Eric Shi Engineer / Mobile Department	Approved by Bill Yao Manager / Mobile Department
Eric	Bill Date: Aug. 12, 2016

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Table of Contents

RELEASE CONTROL RECORD.....	3
1 GENERAL INFORMATION.....	4
1.1 GENERAL DESCRIPTION OF EUT.....	4
1.2 SUMMARY OF TEST RESULTS.....	6
1.3 MEASUREMENT UNCERTAINTY	6
1.4 DESCRIPTION OF TEST MODES.....	7
1.5 DESCRIPTION OF SUPPORT UNITS.....	9
1.6 CONFIGURATION OF SYSTEM UNDER TEST	10
2 EMISSION TEST	11
2.1 CONDUCTED EMISSION MEASUREMENT.....	11
2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	11
2.1.2 TEST INSTRUMENTS	11
2.1.3 TEST PROCEDURES.....	12
2.1.4 DEVIATION FROM TEST STANDARD	12
2.1.5 TEST SETUP	13
2.1.6 EUT OPERATING CONDITIONS.....	13
2.1.7 TEST RESULTS.....	14
2.2 RADIATED EMISSION MEASUREMENT	16
2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	16
2.2.2 TEST INSTRUMENTS	17
2.2.3 TEST PROCEDURE	18
2.2.4 DEVIATION FROM TEST STANDARD	18
2.2.5 TEST SETUP	19
2.2.6 EUT OPERATING CONDITIONS	19
2.2.7 TEST RESULTS	20
3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	23



**BUREAU
VERITAS**

Test Report No.: FV160801W004

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FV160614W011	Original release	July 06, 2016
FV160801W004	Based on the original report FV160614W011 adding one model name & LTE Band 28.	Aug. 12, 2016



1 GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF EUT

PRODUCT	LTE Digital Mobile Phone	
MODEL NAME	NX529J/nubia Z11 mini/BGH nubia Z11 mini	
NOMINAL VOLTAGE	5.0Vdc (adapter or host equipment) 3.85Vdc (Li-ion, battery)	
BATTERY	Brand Name: LG Model Name: Li3827T44P6h726040 Power Rating: DC 3.85V, 2750mAh, Li-ion	
MODULATION TYPE	WLAN	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
	Bluetooth	GFSK, $\pi/4$ -DQPSK, 8DPSK
	GSM/EDGE	GMSK, 8PSK
	WCDMA	BPSK/QPSK
	LTE	QPSK/16QAM
OPERATING FREQUENCY	WLAN	2412 ~ 2462MHz for 11b/g/n(HT20) 5180 ~ 5240MHz, 5260 ~ 5320MHz 5500 ~ 5700MHz, 5745 ~ 5850MHz for 11a/ n(HT20)/ n(HT40)
	Bluetooth	2402MHz ~ 2480MHz
	GSM/EDGE	824.2MHz ~ 848.8MHz (FOR GSM 850) 1850.2MHz ~ 1909.8MHz (FOR PCS 1900)
	WCDMA	1852.4MHz ~ 1907.6MHz (FOR WCDMA Band2) 1712.44MHz ~ 1752.6MHz (FOR WCDMA Band4) 826.4MHz ~ 846.6MHz (FOR WCDMA Band5)
	LTE	1850MHz ~ 1910MHz (FOR LTE Band2) 1710MHz ~ 1755MHz (FOR LTE Band4) 824MHz ~ 849MHz (FOR LTE Band5) 2500MHz ~ 2570MHz (FOR LTE Band7) 699MHz ~ 716MHz (FOR LTE Band12) 704MHz ~ 716MHz (FOR LTE Band17) 703MHz ~ 748MHz (FOR LTE Band28)
HW Version	MB_C	
SW Version	NX529J_ENCommon_V1.20	
I/O PORTS	Refer to user's manual	
CABLE	USB cable: non-shielded, detachable, 1.0m	
ACCESSORY DEVICES	Refer to note as below	

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.



2. The EUT was powered by the following adapters:

ADAPTER 1	
BRAND:	RUIDE
MODEL:	STC-A515A-Z
INPUT:	AC 100-240V, 600mA
OUTPUT:	DC 5V, 1500mA

ADAPTER 2	
BRAND:	DOKOCOM
MODEL:	STC-A515A-Z
INPUT:	AC 100-240V, 600mA
OUTPUT:	DC 5V, 1500mA

ADAPTER 3	
BRAND:	Salcomp
MODEL:	STC-A515A-Z
INPUT:	AC 100-240V, 600mA
OUTPUT:	DC 5V, 1500mA

3. The EUT matched the following USB cable:

USB CABLE	
BRAND:	LIXUN
MODEL:	ZXMT1511003
SIGNAL LINE:	1.0 METER

4. The above models are identical except the model name for marketing purpose.
5. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



1.2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart B			
Standard Section	Test Item	Result	Remark
FCC Part 15, Subpart B, Class B ANSI C63.4:2014	Conducted Test	PASS	Meets limits minimum passing margin is 14.99dB at 0.544000MHz.
	Radiated Emission Test (30MHz ~ 1GHz)	PASS	Meets Class B Limit Minimum passing margin is -4.24dB at 43.58MHz
	Radiated Emission Test (Above 1GHz)	PASS	Meets Class B Limit Minimum passing margin is -13.74dB at 5913MHz

1.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz ~ 30MHz	+/-2.66dB
Radiated emissions	30MHz ~ 1GHz	+/-4.06dB
	1GHz ~ 18GHz	+/-4.58dB

1.4 DESCRIPTION OF TEST MODES

Test Mode	Test Condition
Radiated emission test	
1	GSM850 Idle +Adapter 1+ Earphone + USB cable + BT Idle + Wifi Idle(2.4G) + GPS Rx + SMI2+ Battery1
2	GSM1900 Idle +Adapter 2+ Earphone + USB cable + BT Idle + Wifi Idle(5G) + GPS Rx + SMI2+ Battery1
3	WCDMA B5 Idle +Adapter 3+ Earphone + USB cable + BT Idle + Wifi Idle(2.4G) + GPS Rx + SMI1+ Battery1
4	WCDMA B2 Idle +Adapter 1+ Earphone + USB cable + BT Idle + Wifi Idle(5G) + GPS Rx+ SMI1+ Battery1
5	WCDMA B4 Idle +Adapter 1+ Earphone + USB cable + BT Idle + Wifi Idle(5G) + GPS Rx+ SMI1+ Battery1
6	LTE B2 Idle +Adapter 2+ Earphone + USB cable + BT Idle + Wifi Idle(2.4G) + GPS Rx + SMI1+ Battery1
7	LTE B4 Idle +Adapter 3+ Earphone + USB cable + BT Idle + Wifi Idle(5G) + GPS Rx + SMI1+ Battery1
8	LTE B5 Idle +Adapter 1+ Earphone + USB cable + BT Idle + Wifi Idle(2.4G) + GPS Rx + SMI1 + Front camera on+ Battery1
9	LTE B7 Idle +Adapter 2+ Earphone + USB cable + BT Idle + Wifi Idle(5G) + GPS Rx +FM Rx+ SMI1+ Battery1
10	LTE B12 Idle +Adapter 3+ Earphone + USB cable + BT Idle + Wifi Idle(2.4G) + GPS Rx + SMI1+ Mpeg4+ Battery2
11	LTE B17 Idle + USB Link+ Earphone + USB cable + BT Idle + Wifi Idle(5G) + GPS Rx + SMI1+ Back camera on+ Battery2
12	LTE B28 Idle + Adapter 1+ Earphone + USB cable + BT Idle + Wifi Idle(5G) + GPS Rx + SMI1+ Front camera on+ Battery2
Conducted emission test	
1	GSM850 Idle +Adapter 3+ Earphone + USB cable + BT Idle + Wifi Idle(2.4G) + GPS Rx + SMI2+ Battery1
2	GSM1900 Idle +Adapter 2+ Earphone + USB cable + BT Idle + Wifi Idle(5G) + GPS Rx + SMI2+ Battery1
3	WCDMA B5 Idle +Adapter 1+ Earphone + USB cable + BT Idle + Wifi Idle(2.4G) + GPS Rx + SMI1+ Battery1
4	WCDMA B2 Idle +Adapter 3+ Earphone + USB cable + BT Idle + Wifi Idle(5G) + GPS Rx+ SMI1+ Battery1
5	WCDMA B4 Idle +Adapter 3+ Earphone + USB cable + BT Idle + Wifi Idle(5G) + GPS Rx+ SMI1+ Battery1
6	LTE B2 Idle +Adapter 2+ Earphone + USB cable + BT Idle + Wifi Idle(2.4G) + GPS Rx + SMI1+ Battery1
7	LTE B4 Idle +Adapter 1+ Earphone + USB cable + BT Idle + Wifi Idle(5G) + GPS Rx + SMI1+ Battery1
8	LTE B5 Idle +Adapter 3+ Earphone + USB cable + BT Idle + Wifi Idle(2.4G) + GPS Rx + SMI1 + Front camera on+ Battery1



9	LTE B7 Idle +Adapter 2+ Earphone + USB cable + BT Idle + Wifi Idle(5G) + GPS Rx +FM Rx+ SMI1+ Battery1
10	LTE B12 Idle + USB Link + Earphone + USB cable + BT Idle + Wifi Idle(2.4G) + GPS Rx + SMI1+ Mpeg4+ Battery2
11	LTE B17 Idle + Adapter 1+ Earphone + USB cable + BT Idle + Wifi Idle(5G) + GPS Rx + SMI1+ Back camera on+ Battery2
12	LTE B28 Idle + Adapter 1+ Earphone + USB cable + BT Idle + Wifi Idle(5G) + GPS Rx + SMI1+ Back camera on+ Battery2

NOTE:

1. For conducted emission test, test mode 11 was the worst case and only this mode was presented in this report.
2. For radiated emission test, test mode 11 was the worst case and only this mode was presented in this report.



1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

FOR EMISSION TESTS

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Universal Radio Communication Tester	R&S	CMU200	123259	N/A
2	Wireless AP	ABOCOM	WR224GR	060500749P	D43064
3	Bluetooth Earphone	FAP00	H6080	12098	N/A
4	Notebook	DELL	E6420	9H12FS1	N/A
5	Mouse	DELL	M056UOA	01688082	N/A
6	Printer	HP	hp LaserJet 1300	CNSJF75989	N/A


NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A
2	N/A
3	N/A
4	DC Line: Unshielded, Undetachable, 2.0m
5	USB Line: Unshielded, Undetachable 1.8m;
6	USB Line: Shielded, Detachable 1.5m;

NOTE:

1. All power cords of the above support units are non shielded (1.8m).
2. Items 3-4 acted as communication partners.



1.6 CONFIGURATION OF SYSTEM UNDER TEST





2 EMISSION TEST

2.1 CONDUCTED EMISSION MEASUREMENT

2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

2.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101588	Jan. 22,16	Jan. 21,17
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	Mar. 04,16	Mar. 03,17
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	Apr. 05,16	Apr. 04,17
Voltage probe	SCHWARZBECK	TK 9421	TK 9421-176	Jan. 08,16	Jan. 07,17
Test software	ADT	ADT_Cond_V7.3.7	N/A	N/A	N/A

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2. The test was performed in Dongguan Shielded Room 553.



2.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

2.1.4 DEVIATION FROM TEST STANDARD

No deviation.



2.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

2.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the use type described in the manufacturer's specifications or the user's manual.




2.1.7 TEST RESULTS

TEST VOLTAGE	DC 5V From Adapter Input 230 Vac, 50 Hz	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	24deg. C, 55RH	TESTED BY	Eric

Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	---	28.48	56.00	27.52	L1	ON	9.6
0.150000	42.90	---	66.00	23.10	L1	ON	9.6
0.556000	---	27.14	46.00	18.86	L1	ON	9.7
0.556000	37.73	---	56.00	18.27	L1	ON	9.7
1.096000	---	18.28	46.00	27.72	L1	ON	9.7
1.096000	28.80	---	56.00	27.20	L1	ON	9.7
1.760000	---	23.46	46.00	22.54	L1	ON	9.7
1.760000	31.66	---	56.00	24.34	L1	ON	9.7
17.424000	---	25.14	50.00	24.86	L1	ON	9.9
17.424000	38.67	---	60.00	21.33	L1	ON	9.9
17.972000	---	24.83	50.00	25.17	L1	ON	9.9
17.972000	39.00	---	60.00	21.00	L1	ON	9.9

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum






TEST VOLTAGE	DC 5V From Adapter Input 230 Vac, 50 Hz	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	24deg. C, 55RH	TESTED BY	Eric

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.544000	---	29.53	46.00	16.47	N	ON	10.1
0.544000	41.01	---	56.00	14.99	N	ON	10.1
1.116000	---	21.72	46.00	24.28	N	ON	9.9
1.116000	35.11	---	56.00	20.89	N	ON	9.9
1.476000	---	23.87	46.00	22.13	N	ON	9.9
1.476000	34.71	---	56.00	21.29	N	ON	9.9
2.208000	---	21.67	46.00	24.33	N	ON	9.8
2.208000	32.12	---	56.00	23.88	N	ON	9.8
4.112000	---	20.83	46.00	25.17	N	ON	9.8
4.112000	31.32	---	56.00	24.68	N	ON	9.8
14.436000	---	23.58	50.00	26.42	N	ON	9.9
14.436000	33.39	---	60.00	26.61	N	ON	9.9

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum





2.2 RADIATED EMISSION MEASUREMENT

2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.109)

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 10 meters (dBμV/m)				
Frequencies (MHz)	FCC 15B/ ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	39	29.5	40	30
88-216	43.5	33.1		
216-230	46.4	35.6		
230-960			47	37
960-1000	49.5	43.5		
1000-3000	Avg: 49.5	Avg: 43.5	Not defined	Not defined
3000+	Peak: 69.5	Peak: 63.5	Not defined	Not defined

Radiated Emissions Limits at 3 meters (dBμV/m)				
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	49.5	40	50.5	40.5
88-216	54	43.5		
216-230	56.9	46		
230-960				
960-1000	60	54	57.5	47.5
1000-3000	Avg: 60 Peak: 80	Avg: 54 Peak: 74	Avg: 56 Peak: 76	Avg: 50 Peak: 70
3000+			Avg: 60 Peak: 80	Avg: 54 Peak: 74

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. Emission level (dB μ V/m) = 20 log Emission level (uV/m).
 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
 4. QP detector shall be applied if not specified.



2.2.2 TEST INSTRUMENTS

For frequency below 1G

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Apr. 05,16	Apr. 04,17
Bilog Antenna	Teseq	CBL 6111D	30643	Jul. 14, 16	Jul. 13, 17
Amplifier	Burgeon	BPA-530	100220	Apr. 05,16	Apr. 04,17
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Mar. 12,16	Mar. 11,18
Test software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A

For frequency above 1G

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Horn Antenna	ETS-Lindgren	3117	00062558	May 30,16	May 29,18
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170242	Mar. 12,16	Mar. 11,17
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV40	101094	Apr. 05,16	Apr. 04,17
Broadband Preamplifier	SCHWARZBECK	BBV9718	305	Mar. 09,16	Mar. 08,17
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 11,15	Nov. 10,16
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A

- NOTE:**
1. The test was performed in 966m Chamber (a 3m Semi-anechoic chamber).
 2. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 3. The FCC Site Registration No. is 494399.

2.2.3 TEST PROCEDURE

The basic test procedure was in accordance with ANSI C63.4:2014 (section 12).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters Semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters (below 1GHz) and 3 meters (above 1GHz) away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. The bore sight should be used during the test above 1GHz.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test receiver/spectrum was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.

NOTE:


1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth of test receiver/spectrum analyzer is 1Hz for Average detection (AV) at frequency above 1GHz.
3. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.
4. $\text{Emission level(dBuV/m)} = \text{Raw Value(dBuV)} + \text{Correction Factor(dB/m)}$
5. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)}$ (if the raw value not contains the amplifier);
6. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)} - \text{Amplifier Gain(dB)}$ (if the raw value contains the amplifier).
7. $\text{Margin value} = \text{Emission level} - \text{Limit value}$.

2.2.4 DEVIATION FROM TEST STANDARD


No deviation.

2.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



* : depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

2.2.6 EUT OPERATING CONDITIONS

Same as item 2.1.6.




2.2.7 TEST RESULTS

TEST VOLTAGE	DC 5V From Adapter Input 120Vac, 50 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 61 %RH	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak , 120 kHz
TESTED BY	Alex Chen		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
44.55	31.71	59.62	40.00	-8.29	8.52	1.01	37.44	200	32	QP
102.75	25.71	53.23	43.50	-17.79	7.90	1.56	36.98	200	60	QP
165.8	32.46	57.11	43.50	-11.04	10.11	1.97	36.73	200	96	QP
232.73	35.24	57.81	46.00	-10.76	11.61	2.35	36.53	200	121	QP
299.66	31.24	52.02	46.00	-14.76	13.00	2.72	36.50	200	240	QP
399.57	36.89	53.28	46.00	-9.11	17.18	3.15	36.72	200	180	QP

- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 30MHz to 1000MHz.
 4. Only emissions significantly above equipment noise floor are reported.






TEST VOLTAGE	DC 5V From Adapter Input 120 Vac, 50 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 61 %RH	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak , 120 kHz
TESTED BY	Alex Chen		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
43.58	35.76	63.34	40.00	-4.24	8.88	0.99	37.45	100	42	QP
97.90	35.58	63.29	43.50	-7.92	7.77	1.52	37.00	100	56	QP
165.80	35.87	60.52	43.50	-7.63	10.11	1.97	36.73	100	96	QP
232.73	32.14	54.71	46.00	-13.86	11.61	2.35	36.53	100	123	QP
399.57	31.23	47.62	46.00	-14.77	17.18	3.15	36.72	100	180	QP
493.66	32.20	47.38	46.00	-13.80	18.32	3.44	36.94	100	240	QP

- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 30MHz to 1000MHz.
 4. Only emissions significantly above equipment noise floor are reported.





TEST VOLTAGE	DC 5V From Adapter Input 120 Vac, 50 Hz	FREQUENCY RANGE	1-6 GHz
ENVIRONMENTAL CONDITIONS	26deg. C, 61 %RH	DETECTOR FUNCTION & BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Alex Chen		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2428	36.50	44.26	54.00	-17.50	32.33	8.22	48.31	101	65	Average
2428	49.80	57.56	74.00	-24.20	32.33	8.22	48.31	101	65	Peak
3725	39.62	44.40	54.00	-14.38	33.36	10.34	48.48	101	256	Average
3725	52.34	57.12	74.00	-21.66	33.36	10.34	48.48	101	256	Peak
5913	40.26	36.62	54.00	-13.74	35.40	17.40	49.16	101	120	Average
5913	57.49	53.85	74.00	-16.51	35.40	17.40	49.16	101	100	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2445	36.23	43.94	54.00	-17.77	32.35	8.25	48.31	101	80	Average
2445	52.68	60.39	74.00	-21.32	32.35	8.25	48.31	101	80	Peak
4434	37.89	41.05	54.00	-16.11	34.23	11.35	48.74	101	150	Average
4434	52.98	56.14	74.00	-21.02	34.23	11.35	48.74	101	150	Peak
5794	38.32	35.59	54.00	-15.68	35.25	16.63	49.15	101	240	Average
5794	58.43	55.70	74.00	-15.57	35.25	16.63	49.15	101	240	Peak

- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 1GHz to 6GHz.
 4. Only emissions significantly above equipment noise floor are reported.



Test Report No.: FV160801W004

3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---