

RF EXPOSURE **EVALUATION REPORT**

APPLICANT

: SZ DJI TECHNOLOGY CO., LTD

PRODUCT NAME

Thumb Controller

MODEL NAME

RONIN TC1

TRADE NAME

DJI

BRAND NAME

DJI

FCC ID

SS3-800TC1512

47CFR 2.1093

STANDARD(S)

KDB 447498 D01 General RF Exposure

ISSUE DATE

16-01-04

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.



MORLAB GROUP

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555
Bax: 86-755-36698525
E-mail: service@morlab.cn



DIRECTORY

TEST REPORT DECLARATION	3
1. TECHNICAL INFORMATION	4
1.1. IDENTIFICATION OF APPLICANT	4
1.2. IDENTIFICATION OF MANUFACTURER·····	4
1.3. EQUIPMENT UNDER TEST (EUT)	4
1.3.1. PHOTOGRAPHS OF THE EUT	5
1.3.2. IDENTIFICATION OF ALL USED EUT····································	6
1.4. APPLIED REFERENCE DOCUMENTS	6
2.DEVICE CATEGORY AND RF EXPOSURE LIMIT	7
3.MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER	8
E CELAR HORL WO. HE ELLE HORL WO	OE IN SLAB
4. RF EXPOSURE EVALUATION	8
ANNEX A GENERAL INFORMATION	9

	Change History		
Issue	Date	Reason for change	
1.0	2016-01-04	First edition	
MORE	Will be	B SELAT MORE ME AB SELAT MORE	



TEST REPORT DECLARATION

Applicant	SZ DJI TECHNOLOGY CO., LTD
Applicant Address	14th floor, West Wing, Skyworth Semiconductor Design Building NO.18 Gaoxin South 4th Ave, Nanshan District, Shenzhen, China
Manufacturer	SZ DJI TECHNOLOGY CO., LTD
Manufacturer Address	14th floor, West Wing, Skyworth Semiconductor Design Building NO.18 Gaoxin South 4th Ave, Nanshan District, Shenzhen, China
Product Name	Thumb Controller
Model Name	RONIN TC1
Brand Name	DJI
HW Version	V1.0
SW Version	V1.0
Test Standards	47CFR 2.1093; KDB 447498 D01 General RF Exposure Guidance v06
Issue Date	2016-01-04
SAR Evaluation	Not Required

Tested by	·	Liu Jun	
40		Liu Jun	
Reviewed by	:	Zhu Zhun Zhu Zhan	
Approved by	e:	Zeng Dexin	





1. TECHNICAL INFORMATION

Note: the following data is based on the information by the applicant.

1.1. Identification of Applicant

Company Name:	SZ DJI TECHNOLOGY CO., LTD	E SELAL
Address:	14th floor, West Wing, Skyworth Semiconductor [Design Building
"IOBT MO.	NO.18 Gaoxin South 4th Ave, Nanshan District, Shenz	zhen, China

1.2. Identification of Manufacturer

Company Name:	SZ DJI TECHNOLOGY CO., LTD	
Address:	14th floor, West Wing, Skyworth Semiconductor Design Building	
B ORLAL MORE	NO.18 Gaoxin South 4th Ave, Nanshan District, Shenzhen, China	

1.3. Equipment Under Test (EUT)

Model Name:	RONIN TC1
Trade Name:	DJI 1, LE ORLE MOTO E TO ORLE
Brand Name:	DJI WOOD IN THE STATE OF THE ST
Hardware Version:	V1.0
Software Version:	V1.0
Frequency Bands:	2415-2473MHz;
Modulation Mode:	GFSK
Antenna type:	FPC Antenna



1.3.1. Photographs of the EUT

EUT front view



EUT rear view





1.3.2. Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
1#	V1.0	V1.0

1.4. Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1 OPLAS	47 CFR§2.1093	Radiofrequency Radiation Exposure Evaluation: portable devices
2	KDB 447498 D01v06	General RF Exposure Guidance



2. DEVICE CATEGORY AND RF EXPOSURE LIMIT

Per user manual, this device is a controller. Based on 47CFR 2.1093, this device belongs to portable device category with General Population/Uncontrolled exposure.

Portable Devices:

47CFR 2.1093(b)

For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

GENERAL POPULATION / UNCONTROLLED EXPOSURE

47CFR 2.1093(d) (2)

Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure. Warning labels placed on consumer devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section.





3. MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER

1. Average output power

	. V	
		Output
Channel	Frequency	Power(dBm)
	(MHz)	GFSK
alab1	2415	6.32
15	2443	5.51
30	2473	3.73

4. RF EXPOSURE EVALUATION

The device only incorporates a Bluetooth transmitter, so standalone SAR evaluation is required for Bluetooth and simultaneous SAR is not required.

Standalone transmission SAR evaluation

According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation Distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f(GHz)}$] ≤ 3.0

The maximum tune-up limit power is 4.47mW @ 2.415GHz

Controller antenna spacing 0mm from body, so use **5mm** as the most conservative minimum test separation distance,

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f(GHz)}$] =1.38 \leq 3.0

So SAR evaluation is not required for this device.



ANNEX A GENERAL INFORMATION

1. Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.	
Department:	Morlab Laboratory	
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China	
Responsible Test Lab Manager:	Mr. Su Feng	
Telephone:	+86 755 36698555	
Facsimile:	+86 755 36698525	

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory	
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang	
	Road, Block 67, BaoAn District, ShenZhen, GuangDong	
	Province, P. R. China	

***** END OF REPORT *****