



REPORT No.: SZ15120069W08

FCC RF TEST REPORT

APPLICANT : SZ DJI TECHNOLOGY CO., LTD

PRODUCT NAME : Thumb Controller

MODEL NAME : RONIN TC1

TRADE NAME : DJI

BRAND NAME : DJI

FCC ID : SS3-800TC1512

STANDARD(S) : 47 CFR Part 15 Subpart C

ISSUE DATE : 2016-01-05



SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB GROUP

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555
Http://www.morlab.com

Fax: 86-755-36698525
E-mail: service@morlab.cn



DIRECTORY

TEST REPORT DECLARATION	4
1. TECHNICAL INFORMATION	5
1.1 APPLICANT INFORMATION	5
1.2 EQUIPMENT UNDER TEST (EUT) DESCRIPTION	5
1.2.1 IDENTIFICATION OF ALL USED EUTS	5
1.3 TEST STANDARDS AND RESULTS	6
1.3.1 TEST ENVIRONMENT CONDITIONS	6
2. 47 CFR PART 15C REQUIREMENTS	7
2.1 ANTENNA REQUIREMENT	7
2.1.1 APPLICABLE STANDARD	7
2.1.2 RESULT: COMPLIANT	7
2.2 ON TIME, DUTY CYCLE AND MEASUREMENT METHODS	7
2.2.1 LIMITS	7
2.2.2 TEST DESCRIPTION	7
2.2.3 TEST RESULT	7
2.3 MAXIMUM CONDUCTED (AVERAGE) OUTPUT POWER	9
2.3.1 REQUIREMENT	9
2.3.2 TEST DESCRIPTION	9
2.3.3 TEST RESULT	9
2.4 6DB BANDWIDTH	11
2.4.1 REQUIREMENT	11
2.4.2 TEST DESCRIPTION	11
2.4.3 TESTPROCEDURE	11
2.4.4 TEST RESULT	11
2.5 CONDUCTED SPURIOUS EMISSIONS AND BAND EDGE	14
2.5.1 REQUIREMENT	14
2.5.2 TEST DESCRIPTION	14
2.5.3 TESTPROCEDURE	14
2.5.4 TEST RESULT	14
2.6 POWER SPECTRAL DENSITY (PSD)	18
2.6.1 REQUIREMENT	18



REPORT No.: SZ15120069W08

2.6.2	TEST DESCRIPTION	18
2.6.3	TEST RESULT.....	18
2.7	RESTRICTED FREQUENCY BANDS	21
2.7.1	REQUIREMENT.....	21
2.7.2	TEST DESCRIPTION	21
2.7.3	TEST PROCEDURE.....	22
2.7.4	TEST RESULT.....	22
2.8	CONDUCTED EMISSION.....	25
2.8.1	REQUIREMENT.....	25
2.8.3	TEST RESULT.....	26
2.9	RADIATED EMISSION	28
2.9.1	REQUIREMENT.....	28
2.9.2	TEST DESCRIPTION	29
2.9.3	TEST PROCEDURE.....	31
2.9.4	TEST RESULT.....	31
ANNEX A GENERAL INFORMATION.....		38

Change History		
Issue	Date	Reason for change
1.0	2016-01-05	First edition



REPORT No.: SZ15120069W08

TEST REPORT DECLARATION

Applicant	SZ DJI TECHNOLOGY CO., LTD
Applicant Address	14th floor, West Wing, Skyworth Semiconductor Design Building NO.18 Gaoxin South 4th Ave, Nanshan District, Shenzhen, China
Manufacturer	SZ DJI TECHNOLOGY CO., LTD
Manufacturer Address	14th floor, West Wing, Skyworth Semiconductor Design Building NO.18 Gaoxin South 4th Ave, Nanshan District, Shenzhen, China
Product Name	Thumb Controller
Model Name	RONIN TC1
Brand Name	DJI
HW Version	V1.0
SW Version	V1.0
Test Standards	47 CFR Part 15 Subpart C
Test Date	2015-12-15 to 2015-12-25
Test Result	PASS

Tested by : Zou Jian
Zou Jian(Test Engineer)

Reviewed by : Qiu Xiaojun
Qiu Xiaojun(RF Manager)

Approved by : Zeng Dexin
Zeng Dexin(Chief Engineer)

MORLAB GROUP

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555
Http://www.morlab.com

Fax: 86-755-36698525
E-mail: service@morlab.cn



1. TECHNICAL INFORMATION

Note: Provide by applicant.

1.1 Applicant Information

Company:	SZ DJI TECHNOLOGY CO., LTD
Address:	14th floor, West Wing, Skyworth Semiconductor Design Building NO.18 Gaoxin South 4th Ave, Nanshan District, Shenzhen, China

1.2 Equipment under Test (EUT) Description

Brand Name:	DJI
Trade Name:	DJI
Model Name:	RONIN TC1
Frequency Range:	The frequency range used is 2415MHz - 2473MHz (30 channels, at intervals of 2MHz);
Modulation Type:	GFSK
Antenna Type:	FPCAntenna
Antenna Gain:	1.69dBi

NOTE:

The EUT is a Thumb Controller, it operate at 2.4GHz ISM band; the frequencies allocated f is $F(\text{MHz})=2415+2*(n-1)$ ($1 \leq n \leq 30$). The lowest, middle, highest channel numbers of the Thumb Controller used and tested in this report are separately 1 (2415MHz), 15 (2443MHz) and 30 (2473MHz).

For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.2.1 Identification of all used EUTs

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
A01	V1.0	V1.0



1.3 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (2.4GHz ISM band radiators) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-13 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.203	Antenna Requirement	<u>PASS</u>
2	15.247(b)	Peak Output Power	<u>PASS</u>
3	15.247(a)	Bandwidth	<u>PASS</u>
4	15.247(d)	Conducted Spurious Emission and Band Edge	<u>PASS</u>
5	15.247(d)	Restricted Frequency Bands	<u>PASS</u>
6	15.207	Conducted Emission	<u>PASS</u>
7	15.209 ,15.247(d)	Radiated Emission	<u>PASS</u>
8	15.247(e)	Power spectral density (PSD)	<u>PASS</u>

The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.10-2013.

1.3.1 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106

2. 47 CFR PART 15C REQUIREMENTS

2.1 Antenna requirement

2.1.1 Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2 Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2 On time, duty cycle and measurement methods

2.2.1 Limits

None; For reporting purposes only.

2.2.2 Test description

A. Test set



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

B. Equipments List:

Please reference ANNEX A(1.4).

2.2.3 Test result


A. Test verdict:

Channel	Frequency (MHz)	On Time (msec)	Period (msec)	Duty Cycle x(linear)	Duty Cycle (%)	Refer to Plot
15	2443	1.28	13.96	0.0917	9.17	Plot B

B. Test plots



REPORT No.: SZ15120069W08



(Plot B: Channel 15: 2443 MHz)



2.3 Maximum conducted (average) Output Power


2.3.1 Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

2.3.2 Test Description

The measured output power was calculated by the reading of the Power sensor and calibration.

A. Test Setup:



The EUT (Equipment under the test) which is coupled to the Power sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in power sensor.

B. Equipments List:

Please reference ANNEX A (1.4).

2.3.3 Test Result

The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output (average) power of the EUT.

A. Test Verdict:

Average Power:

Channel	Frequency (MHz)	Maximum Conducted Output (average) Power		Limit		Verdict
				dBm	W	
1	2415	6.32	0.00429	30	1	PASS
15	2443	5.51	0.00356			PASS
30	2473	3.73	0.00236			PASS



REPORT No.: SZ15120069W08

Peak power:

Channel	Frequency (MHz)	Maximum Conducted Output (peak) Power		Limit		Verdict
				dBm	W	
		dBm	W			
1	2415	6.63	0.00460	30	1	PASS
15	2443	5.86	0.00385			PASS
30	2473	4.01	0.00252			PASS


2.4 6dB Bandwidth

2.4.1 Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

2.4.2 Test Description

A. Test Set:



The EUT which is powered by the battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

B. Equipments List:

Please reference ANNEX A(1.4).

2.4.3 TestProcedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth

RBW $\geq$ 1% of the 20 dB bandwidth

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold


2.4.4 Test Result

The lowest, middle and highest channels are selected to perform testing to record the 6 dB bandwidth of the EUT.

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Refer to Plot	Limits(kHz)	Result
1	2415	1.634	Plot A	≥500	PASS
15	2443	1.637	Plot B	≥500	PASS
30	2473	1.617	Plot C	≥500	PASS


B. Test Plots:




(Plot A: Channel 1: 2415MHz)



REPORT No.: SZ15120069W08



(Plot B: Channel 15: 2443 MHz)



(Plot C: Channel 30: 2473MHz)


2.5 Conducted Spurious Emissions and Band Edge

2.5.1 Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.5.2 Test Description

A. Test Set:



The EUT which is powered by the battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

B. Equipments List:

Please reference ANNEX A (1.4).

2.5.3 TestProcedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

2.5.4 Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.




REPORT No.: SZ15120069W08

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
1	2415	-51.92	Plot A.1	1.26	-18.74	PASS
15	2443	-52.01	Plot B.1	0.63	-19.37	PASS
30	2473	-53.36	Plot C.1	0.65	-19.35	PASS

B. Test Plots:


Note: the power of the EUT transmitting frequency should be ignored.




(Plot A.1: Channel = 0, 30MHz to 25GHz)



REPORT No.: SZ15120069W08




(Band Edge@ Channel = 0)




(Plot B.1: Channel = 19, 30MHz to 25GHz)



REPORT No.: SZ15120069W08



(Plot C.1: Channel = 39, 30MHz to 25GHz)



(Band Edge@ Channel = 39)


2.6 Power spectral density (PSD)

2.6.1 Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

2.6.2 Test Description

A. Test Set:



The EUT which is powered by the battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

B. Equipments List:

Please reference ANNEX A (1.4).

2.6.3 Test Result

The lowest, middle and highest channels are tested.

A. Test Verdict:

Spectral power density (dBm/3kHz)							
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	10log(1/x)	Average PSD (dBm/3kHz)	Refer to Plot	Limit (dBm/3kHz)	Verdict
1	2415	-4.34	10.38	6.04	Plot A	8	PASS
15	2443	-4.96	10.38	5.42	Plot B	8	PASS
30	2473	-6.87	10.38	3.51	Plot C	8	PASS
Measurement uncertainty: $\pm 1.3\text{dB}$							
Note: x refers to duty cycle.							

B. Test Plots:



REPORT No.: SZ15120069W08



(Plot A: Channel = 1)



(Plot B: Channel = 15)



REPORT No.: SZ15120069W08



(Plot C: Channel = 30)


2.7 Restricted Frequency Bands

2.7.1 Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.7.2 Test Description

A. Test Setup



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

B. Equipments List:

Please reference ANNEX A(1.4).



2.7.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured.

RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 KHz for $f < 1\text{GHz}$

VBW = 3 MHz for peak and 10Hz for average

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

2.7.4 Test Result

The lowest and highest channels are tested to verify the Restricted Frequency Bands.

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

Note: 1. Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

2. All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2373.66	PK	46.21	-33.63	32.56	45.14	74	Pass
1	2388.86	AV	33.62	-33.63	32.56	32.55	54	Pass
30	2484.96	PK	45.70	-33.18	32.5	45.02	74	Pass
30	2483.98	AV	33.62	-33.18	32.5	32.94	54	Pass


B. Test Plots:



REPORT No.: SZ15120069W08




(Plot A1: Channel = 0 PEAK)



(Plot A2: Channel = 0 AVG)



(Plot B1: Channel = 30 PEAK)



(Plot B2: Channel = 30 AVG)

2.8 Conducted Emission

2.8.1 Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5- 30	60	50

NOTE:

- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.8.2 Test Description

A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 1.5m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10:2013.

B. Equipments List:



Please reference ANNEX A(1.4).


2.8.3 Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.


A. Test setup:

The EUT configuration of the emission tests is EUT + PC (charging + transmitting).

B. Test Plots:



(Plot A: L Phase)



(Plot B: N Phase)



2.9 Radiated Emission

2.9.1 Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:


1. For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)


2.9.2 Test Description

A. Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.10 (2013). For radiated emissions below or equal to 1GHz, The EUT was set-up on insulator 80cm above the Ground Plane, For radiated emissions above 1GHz, The EUT was set-up on insulator 150cm above the Ground Plane. The set-up and test methods were according to ANSI C63.10.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

- (a) In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna.



The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.

(b) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

B. Equipments List:

Please reference ANNEX A(1.4).

2.9.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

2.9.4 Test Result

According to ANSI C63.10 ,because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.


The low frequency, which started from 9KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

2.9.4.1 GFSK Test Mode

**A. Test Plots for the Whole Measurement Frequency Range:**

TX mode:

Plots for Channel = 1




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
32.428	22.09	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
65.207	13.54	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
110.125	12.81	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
3655.028	45.10	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
10372.177	48.63	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
19199.382	49.89	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz @2415MHz)



REPORT No.: SZ15120069W08




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
32.428	28.55	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
42.140	19.04	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
62.778	19.66	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
2921.804	44.83	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
7948.463	48.46	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
12197.090	49.28	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz @2415MHz)



REPORT No.: SZ15120069W08

Plot for Channel = 15




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
32.428	21.70	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
65.207	13.61	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
112.553	13.52	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
2303.561	44.25	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
9133.843	48.59	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
18755.374	50.60	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz @2443MHz)



REPORT No.: SZ15120069W08




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
32.428	28.43	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
42.140	17.80	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
65.207	19.90	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
2803.673	45.66	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
7056.374	47.63	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
11736.789	49.26	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz @2443MHz)



REPORT No.: SZ15120069W08

Plot for Channel = 30




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
32.428	21.99	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
65.207	14.33	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
129.549	15.77	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
4530.824	46.80	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
10425.132	48.59	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
18836.843	49.90	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz@2473MHz)



REPORT No.: SZ15120069W08



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
32.428	29.49	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
62.778	21.89	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
79.775	14.86	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
4522.677	46.73	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
7989.198	47.56	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
18906.092	50.51	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz @2473MHz)



ANNEX A GENERAL INFORMATION

1.1 Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

1.2 Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

1.3 Facilities and Accreditations

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at FL.1, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC registration number is 695796.

1.4 Maximum measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Measurements	Frequency	Uncertainty
Conducted emissions	9KHz~30MHz	2.44dB
Radiated emissions	30MHz~200MHz	2.93
	200MHz~1000MHz	2.95
	1GHz~18GHz	2.26
	18GHz~40GHz	1.94

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2



REPORT No.: SZ15120069W08

1.5 Test Equipments Utilized

1.5.1 Conducted Test Equipments

Conducted Test Equipment						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
1	Spectrum Analyzer	MY45101810	E4407B	Agilent	2015.03.28	2016.03.27
2	USB Wideband Power Sensor	MY54210011	U2021XA	Agilent	2015.03.28	2016.03.27
3	EXA Signal Analyzer	MY53470838	N9010A	Agilent	2015.08.26	2016.08.25
4	RF cable	CB01	RF01	Morlab	N/A	N/A
5	Attenuator	(n.a.)	10dB	Resnet	N/A	N/A
6	SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.5.2 Conducted Emission Test Equipments

Conducted Emission Test Equipments						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
1	Receiver	595WX11007	PMM9010	Narda S.T.S/PMM	2015.05.07	2016.05.06
2	LISN	812744	NSLK 8127	Schwarzbeck	2015.06.18	2016.06.17
3	Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2015.05.07	2016.05.06
4	Coaxial cable(BNC)	CB01	EMC01	Morlab	N/A	N/A

1.5.3 Radiated Test Equipments

Radiated Test Equipments						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal.Due Date
1	System Simulator	GB45360846	8960-E5515C	Agilent	2015.05.07	2016.05.06
2	Receiver	MY54130016	N9038A	Agilent	2015.05.07	2016.05.06
3	Test Antenna - Bi-Log	N/A	VULB9163	Schwarzbeck	2015.05.14	2016.05.13
4	Test Antenna - Horn	9170C-531	BBHA9170	Schwarzbeck	2015.03.31	2016.03.30
5	Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2015.02.26	2016.02.25
6	Test Antenna - Horn	71688	BBHA 9120D	Schwarzbeck	2015.02.26	2016.02.25
7	Coaxial cable(N male)	CB02	EMC02	Morlab	N/A	N/A
8	Coaxial cable(N male)	CB03	EMC03	Morlab	N/A	N/A



REPORT No.: SZ15120069W08

1.5.4 Climate Chamber

Climate Chamber						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Climate Chamber	2004012	HL4003T	Yinhe	2015.02.26	2016.02.25

1.5.5 Vibration Table

Vibration Table						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Vibration Table	N/A	ACT2000-S015L	CMI-COM	2015.02.26	2016.02.25

1.5.6 Auxiliary Test Equipment

Auxiliary Test Equipment						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Computer	N.A	N.A	Asus	N.A	N.A

1.5.7 Anechoic Chamber

Anechoic Chamber						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Anechoic Chamber	N/A	9m*6m*6m	Changning	2015.05.14	2016.05.13

***** END OF REPORT *****