

**SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch**

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230400101303

Page: 1 of 139

# TEST REPORT

**Application No.:** SZCR2304001013AT  
**Applicant:** SZ DJI TECHNOLOGY CO., LTD.  
**Address of Applicant:** Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili Community, Xili Street, Nanshan District, Shenzhen, China.  
**Manufacturer:** SZ DJI TECHNOLOGY CO., LTD.  
**Address of Manufacturer:** Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili Community, Xili Street, Nanshan District, Shenzhen, China.

**Equipment Under Test (EUT):**

**EUT Name:** DJI Air 3  
**Model No.:** EB3WBC  
**Trade Mark:** DJI  
**FCC ID:** SS3-EB3WBC2303  
**Standard(s) :** 47 CFR Part 15, Subpart C 15.247  
**Date of Receipt:** 2023-04-10  
**Date of Test:** 2023-04-23 to 2023-05-28  
**Date of Issue:** 2023-06-05

<b>Test Result:</b>	<b>Pass*</b>
---------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu  
EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2023-06-05		Original

<b>Authorized for issue by:</b>			
		Darren Yuan	
		_____	
		Darren Yuan/Project Engineer	
		Eric Fu	
		_____	
		Eric Fu/Reviewer	



## 2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Conducted Peak Output Power		ANSI C63.10 (2013) Section 11.9.2	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2013) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2013) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass



### 3 Contents

	Page
<b>1 Cover Page .....</b>	<b>1</b>
<b>2 Test Summary.....</b>	<b>3</b>
<b>3 Contents .....</b>	<b>4</b>
<b>4 General Information.....</b>	<b>6</b>
4.1 Details of E.U.T.....	6
4.2 Description of Support Units.....	6
4.3 Measurement Uncertainty .....	6
4.4 Test Location .....	7
4.5 Test Facility.....	7
4.6 Deviation from Standards.....	7
4.7 Abnormalities from Standard Conditions.....	7
<b>5 Equipment List .....</b>	<b>8</b>
<b>6 Radio Spectrum Technical Requirement.....</b>	<b>12</b>
6.1 Antenna Requirement .....	12
6.1.1 Test Requirement: .....	12
6.1.2 Conclusion.....	12
<b>7 Radio Spectrum Matter Test Results.....</b>	<b>13</b>
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz) .....	13
7.1.1 E.U.T. Operation .....	13
7.1.2 Test Mode Description .....	13
7.1.3 Test Setup Diagram .....	14
7.1.4 Measurement Procedure and Data.....	14
7.2 Conducted Peak Output Power .....	17
7.2.1 E.U.T. Operation .....	17
7.2.2 Test Mode Description .....	17
7.2.3 Test Setup Diagram .....	18
7.2.4 Measurement Procedure and Data.....	18
7.3 Minimum 6dB Bandwidth.....	19
7.3.1 E.U.T. Operation .....	19
7.3.2 Test Mode Description .....	19
7.3.3 Test Setup Diagram .....	19
7.3.4 Measurement Procedure and Data.....	19
7.4 Power Spectrum Density .....	20
7.4.1 E.U.T. Operation .....	20
7.4.2 Test Mode Description .....	20
7.4.3 Test Setup Diagram .....	20
7.4.4 Measurement Procedure and Data.....	20
7.5 Conducted Band Edges Measurement .....	21
7.5.1 E.U.T. Operation .....	21



# SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230400101303

Page: 5 of 139

7.5.2	Test Mode Description .....	21
7.5.3	Test Setup Diagram .....	22
7.5.4	Measurement Procedure and Data.....	22
7.6	Conducted Spurious Emissions .....	23
7.6.1	E.U.T. Operation .....	23
7.6.2	Test Mode Description .....	23
7.6.3	Test Setup Diagram .....	24
7.6.4	Measurement Procedure and Data.....	24
7.7	Radiated Emissions which fall in the restricted bands .....	25
7.7.1	E.U.T. Operation .....	25
7.7.2	Test Mode Description .....	26
7.7.3	Test Setup Diagram .....	26
7.7.4	Measurement Procedure and Data.....	27
7.8	Radiated Spurious Emissions Below 1GHz.....	60
7.8.1	E.U.T. Operation .....	60
7.8.2	Test Mode Description .....	60
7.8.3	Test Setup Diagram .....	61
7.8.4	Measurement Procedure and Data.....	61
7.9	Radiated Spurious Emissions Above 1GHz .....	65
7.9.1	E.U.T. Operation .....	65
7.9.2	Test Mode Description .....	65
7.9.3	Test Setup Diagram .....	66
7.9.4	Measurement Procedure and Data.....	67
<b>8</b>	<b>Test Setup Photo .....</b>	<b>92</b>
<b>9</b>	<b>EUT Constructional Details (EUT Photos).....</b>	<b>92</b>
<b>10</b>	<b>Appendix.....</b>	<b>93</b>



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**

## 4 General Information

### 4.1 Details of E.U.T.

Power supply:	Powered by Lithium-ion Polymer rechargeable battery Battery information Model: BWX233-4241-14.76 Nominal Voltage: 14.76V Rated Capacity: 4241mAh, 62.6Wh
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz, 802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Channel Spacing:	5MHz
Number of Channels:	802.11g/n(HT20): 11 802.11n(HT40): 7
Antenna Type:	PCB Antenna
Antenna Gain:	1.5dBi

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

### 4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Power Adapter	DJI	PD-65US	N/A

### 4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	± 3.0dB (150kHz to 30MHz)
Conducted Peak Output Power	± 0.75dB
Minimum 6dB Bandwidth	± 3%
Power Spectrum Density	± 2.84dB
Conducted Band Edges Measurement	± 0.75dB
Conducted Spurious Emissions	± 0.75dB
Radiated Emissions which fall in the restricted bands	± 4.5dB (Below 1GHz); ± 4.8dB (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	± 4.5dB
Radiated Spurious Emissions Above 1GHz	± 4.8dB

Remark:

The  $U_{lab}$  (lab Uncertainty) is less than  $U_{CISPR/ETSI}$  (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

#### • VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

#### • FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

#### • Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

### 4.6 Deviation from Standards

None

### 4.7 Abnormalities from Standard Conditions

None



## 5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2022-05-14	2025-05-13
EMI Test Receiver	Rohde&Schwarz	ESCI	SEM004-02	2023-03-20	2024-03-19
Measurement Software	AUDIX	e3 V8.2014-6-27a	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2022-07-08	2023-07-07
LISN	Rohde&Schwarz	ENV216	SEM007-01	2022-09-20	2023-09-19
LISN	ETS-LINDGREN	3816/2	SEM007-02	2023-03-20	2024-03-19

Conducted Peak Output Power					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2023-04-01	2024-03-31
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2023-03-21	2024-03-20
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2022-10-20	2023-10-19
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2023-03-21	2024-03-20
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2022-07-08	2023-07-07
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2023-03-31	2024-03-30

Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2022-10-20	2023-10-19
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2023-03-21	2024-03-20
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2022-07-08	2023-07-07
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2023-03-31	2024-03-30



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Power Spectrum Density					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2022-10-20	2023-10-19
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2023-03-21	2024-03-20
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2022-07-08	2023-07-07
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2023-03-31	2024-03-30

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2022-10-20	2023-10-19
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2023-03-21	2024-03-20
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2022-07-08	2023-07-07
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2023-03-31	2024-03-30

Conducted Spurious Emissions					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2022-10-20	2023-10-19
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2023-03-21	2024-03-20
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2022-07-08	2023-07-07
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2023-03-31	2024-03-30



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

<b>Radiated Emissions which fall in the restricted bands</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Inventory No.</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2022-04-02	2025-04-01
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2023-03-20	2024-03-19
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2022-07-24	2024-07-23
Microwave system amplifier	Agilent	83017A	SEM005-25	2022-09-21	2023-09-20
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2022-07-08	2023-07-07
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2022-08-10	2024-08-09
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2023-03-20	2024-03-19

<b>Radiated Spurious Emissions Below 1GHz</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Inventory No.</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2021-03-27	2024-03-26
MXE EMI receiver	KEYSIGHT	N9038A	SEM004-16	2022-10-20	2023-10-19
Trilog-Broadband Antenna	Schwarzbeck	VULB9168	SEM003-18	2021-10-28	2023-10-27
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-04	2023-03-31	2024-03-30
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2021-11-30	2023-11-29
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM029-01	2022-07-08	2023-07-07



# SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230400101303

Page: 11 of 139

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2022-04-02	2025-04-01
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2023-03-20	2024-03-19
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2022-07-24	2024-07-23
Microwave system amplifier	Agilent	83017A	SEM005-25	2022-09-21	2023-09-20
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2022-07-08	2023-07-07

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2022-09-04	2023-09-03
Humidity/ Temperature Indicator	Anymetre	TH101B	SEM002-09	2022-09-04	2023-09-03
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2023-03-23	2024-03-22



SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch Technical Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

#### 6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 1.5dBi.

Antenna location: Refer to internal photo.



## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz

#### 7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23.2 °C

Humidity: 50.5 % RH

Atmospheric Pressure: 1015 mbar

#### 7.1.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Final test	08	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); Only the data of worst case is recorded in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

### 7.1.3 Test Setup Diagram




### 7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: Level=Read Level+ Cable Loss+ LISN Factor



Test Mode: 08; Line: Live line




Site : Shielding Room  
 Condition: Line  
 Job No. : 01013AT  
 Test mode: 08

	Freq	Cable Loss	LISN Factor	Read Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dB	
1	0.1524	0.03	9.63	29.45	39.11	65.87	QP
2	0.1524	0.03	9.63	0.55	10.21	55.87	Average
3	0.2268	0.04	9.62	33.79	43.45	62.57	QP
4	0.2268	0.04	9.62	23.72	33.38	52.57	Average
5 *	0.3596	0.05	9.62	34.16	43.83	58.74	QP
6	0.3596	0.05	9.62	25.13	34.80	48.74	Average
7	0.5671	0.06	9.62	31.38	41.06	56.00	QP
8 *	0.5671	0.06	9.62	23.79	33.47	46.00	Average
9	2.2726	0.11	9.64	23.64	33.39	56.00	QP
10	2.2726	0.11	9.64	13.72	23.47	46.00	Average
11	29.5269	0.38	10.18	15.71	26.27	60.00	QP
12	29.5269	0.38	10.18	10.19	20.75	50.00	Average



Test Mode: 08; Line: Neutral Line



Site : Shielding Room  
 Condition: Neutral  
 Job No. : 01013AT  
 Test mode: 08

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1668	0.03	9.62	25.27	34.92	65.12	-30.20	QP
2	0.1668	0.03	9.62	-2.37	7.28	55.12	-47.84	Average
3	0.2404	0.04	9.62	31.42	41.08	62.08	-21.00	QP
4	0.2404	0.04	9.62	20.88	30.54	52.08	-21.54	Average
5	0.3374	0.05	9.62	32.00	41.67	59.27	-17.60	QP
6 *	0.3374	0.05	9.62	23.16	32.83	49.27	-16.44	Average
7 *	0.5611	0.06	9.62	29.77	39.45	56.00	-16.55	QP
8	0.5611	0.06	9.62	19.03	28.71	46.00	-17.29	Average
9	2.1326	0.11	9.64	22.31	32.06	56.00	-23.94	QP
10	2.1326	0.11	9.64	11.06	20.81	46.00	-25.19	Average
11	9.0113	0.20	9.77	18.29	28.26	60.00	-31.74	QP
12	9.0113	0.20	9.77	12.97	22.94	50.00	-27.06	Average



**7.2 Conducted Peak Output Power**

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.2

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq$ hopping channels $< 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

**7.2.1 E.U.T. Operation**

Operating Environment:

Temperature: 28.0 °C Humidity: 41.7 % RH Atmospheric Pressure: 1010 mbar

**7.2.2 Test Mode Description**


Pre-scan / Final test	Mode Code	Description
Final test	07	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); Only the data of worst case is recorded in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

### 7.2.3 Test Setup Diagram



### 7.2.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



### 7.3 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)  
 Test Method: ANSI C63.10 (2013) Section 11.8.1

Limit:

≥500 kHz

#### 7.3.1 E.U.T. Operation


Operating Environment:

Temperature: 28.0 °C Humidity: 41.7 % RH Atmospheric Pressure: 1010 mbar

#### 7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	07	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); Only the data of worst case is recorded in the report.

#### 7.3.3 Test Setup Diagram



#### 7.3.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com  
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

### 7.4 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

#### 7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 28.0 °C Humidity: 41.7 % RH Atmospheric Pressure: 1010 mbar

#### 7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	07	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); Only the data of worst case is recorded in the report.

#### 7.4.3 Test Setup Diagram



#### 7.4.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com  
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

**7.5 Conducted Band Edges Measurement**

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)  
 Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

**7.5.1 E.U.T. Operation**

Operating Environment:

Temperature: 28.0 °C Humidity: 41.7 % RH Atmospheric Pressure: 1010 mbar

**7.5.2 Test Mode Description**


Pre-scan / Final test	Mode Code	Description
Final test	07	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); Only the data of worst case is recorded in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

### 7.5.3 Test Setup Diagram



### 7.5.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

**7.6 Conducted Spurious Emissions**

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)  
 Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

**7.6.1 E.U.T. Operation**

Operating Environment:

Temperature: 28.0 °C Humidity: 41.7 % RH Atmospheric Pressure: 1010 mbar

**7.6.2 Test Mode Description**


Pre-scan / Final test	Mode Code	Description
Final test	07	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); Only the data of worst case is recorded in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

### 7.6.3 Test Setup Diagram



### 7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

**7.7 Radiated Emissions which fall in the restricted bands**

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

**7.7.1 E.U.T. Operation**

Operating Environment:

Temperature: 21.6 °C Humidity: 59.0 % RH Atmospheric Pressure: 1005 mbar




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

**7.7.2 Test Mode Description**

Pre-scan / Final test	Mode Code	Description
Pre-scan	07	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); Only the data of worst case is recorded in the report.
Final test	08	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); Only the data of worst case is recorded in the report.

**7.7.3 Test Setup Diagram**



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

### 7.7.4 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Test Mode: 08; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 Band edge  
 Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2360.02	4.22	28.64	35.65	58.02	55.23	74.00	-18.77 peak
2	2390.00	4.25	28.76	35.64	57.77	55.14	74.00	-18.86 peak
3 q	2412.00	4.27	28.87	35.63	109.61	107.12	74.00	33.12 peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 Band edge  
 Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.97	4.25	28.76	35.64	46.99	44.36	54.00	-9.64	Average
2	2390.00	4.25	28.76	35.64	46.99	44.36	54.00	-9.64	Average
3 q	2412.00	4.27	28.87	35.63	106.28	103.79	54.00	49.79	Average



Test Mode: 08; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 Band edge  
 Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2314.10	4.17	28.46	35.67	56.36	53.32	74.00	-20.68	Peak
2	2390.00	4.25	28.76	35.64	54.29	51.66	74.00	-22.34	Peak
3 q	2412.00	4.27	28.87	35.63	97.09	94.60	74.00	20.60	Peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 Band edge  
 Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.00	4.25	28.76	35.64	43.29	40.66	54.00	-13.34	Average
2	2390.00	4.25	28.76	35.64	43.26	40.63	54.00	-13.37	Average
3 q	2412.00	4.27	28.87	35.63	94.23	91.74	54.00	37.74	Average



Test Mode: 08; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 Band edge  
 Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 2462.00	4.32	29.17	35.62	108.87	106.74	74.00	32.74 peak
2	2483.50	4.34	29.30	35.61	57.94	55.97	74.00	-18.03 peak
3	2483.79	4.34	29.30	35.61	58.27	56.30	74.00	-17.70 peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 Band edge  
 Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	q 2462.00	4.32	29.17	35.62	105.37	103.24	54.00	49.24	Average
2	2483.50	4.34	29.30	35.61	49.65	47.68	54.00	-6.32	Average
3	2483.79	4.34	29.30	35.61	48.36	46.39	54.00	-7.61	Average



Test Mode: 08; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 Band edge  
 Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.00	4.32	29.17	35.62	95.20	93.07	74.00	19.07 Peak
2	2483.50	4.34	29.30	35.61	54.78	52.81	74.00	-21.19 Peak
3	2492.84	4.35	29.36	35.61	56.13	54.23	74.00	-19.77 Peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 Band edge  
 Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	q 2462.00	4.32	29.17	35.62	92.56	90.43	54.00	36.43	Average
2	2483.50	4.34	29.30	35.61	43.51	41.54	54.00	-12.46	Average
3	2483.99	4.34	29.30	35.61	43.37	41.40	54.00	-12.60	Average



Test Mode: 08; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 Band edge  
 Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.61	4.25	28.76	35.64	74.80	72.17	74.00	-1.83	peak
2	2390.00	4.25	28.76	35.64	74.38	71.75	74.00	-2.25	peak
3 q	2412.00	4.27	28.87	35.63	112.86	110.37	74.00	36.37	peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 Band edge  
 Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.85	4.25	28.76	35.64	53.97	51.34	54.00	-2.66	Average
2	2390.00	4.25	28.76	35.64	53.86	51.23	54.00	-2.77	Average
3 q	2412.00	4.27	28.87	35.63	103.86	101.37	54.00	47.37	Average



Test Mode: 08; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 Band edge  
 Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2384.41	4.24	28.74	35.64	63.16	60.50	74.00	-13.50	Peak
2	2390.00	4.25	28.76	35.64	61.29	58.66	74.00	-15.34	Peak
3 q	2412.00	4.27	28.87	35.63	100.25	97.76	74.00	23.76	Peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 Band edge  
 Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.97	4.25	28.76	35.64	46.58	43.95	54.00	-10.05	Average
2	2390.00	4.25	28.76	35.64	46.58	43.95	54.00	-10.05	Average
3 q	2412.00	4.27	28.87	35.63	91.89	89.40	54.00	35.40	Average



Test Mode: 08; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 Band edge  
 Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.00	4.32	29.17	35.62	112.08	109.95	74.00	35.95 peak
2	2483.50	4.34	29.30	35.61	72.13	70.16	74.00	-3.84 peak
3	2483.79	4.34	29.30	35.61	71.64	69.67	74.00	-4.33 peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 Band edge  
 Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	q 2462.00	4.32	29.17	35.62	102.81	100.68	54.00	46.68	Average
2	2483.50	4.34	29.30	35.61	51.99	50.02	54.00	-3.98	Average
3	2483.79	4.34	29.30	35.61	51.58	49.61	54.00	-4.39	Average



Test Mode: 08; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 Band edge  
 Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 2462.00	4.32	29.17	35.62	98.75	96.62	74.00	22.62 Peak
2	2483.50	4.34	29.30	35.61	59.51	57.54	74.00	-16.46 Peak
3	2483.84	4.34	29.30	35.61	58.95	56.98	74.00	-17.02 Peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 Band edge  
 Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.00	4.32	29.17	35.62	90.05	87.92	54.00	33.92 Average
2	2483.50	4.34	29.30	35.61	44.43	42.46	54.00	-11.54 Average
3	2484.09	4.34	29.31	35.61	44.56	42.60	54.00	-11.40 Average



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 Band edge  
 Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.85	4.25	28.76	35.64	75.36	72.73	74.00	-1.27	peak
2	2390.00	4.25	28.76	35.64	73.90	71.27	74.00	-2.73	peak
3 q	2412.00	4.27	28.87	35.63	112.30	109.81	74.00	35.81	peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 Band edge  
 Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.85	4.25	28.76	35.64	53.68	51.05	54.00	-2.95	Average
2	2390.00	4.25	28.76	35.64	53.67	51.04	54.00	-2.96	Average
3 q	2412.00	4.27	28.87	35.63	103.11	100.62	54.00	46.62	Average



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 Band edge  
 Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.73	4.25	28.76	35.64	64.80	62.17	74.00	-11.83	Peak
2	2390.00	4.25	28.76	35.64	63.66	61.03	74.00	-12.97	Peak
3 q	2412.00	4.27	28.87	35.63	100.66	98.17	74.00	24.17	Peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 Band edge  
 Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2337.66	4.19	28.55	35.66	43.56	40.64	54.00	-13.36	Average
2	2390.00	4.25	28.76	35.64	46.38	43.75	54.00	-10.25	Average
3 q	2412.00	4.27	28.87	35.63	90.65	88.16	54.00	34.16	Average



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 Band edge  
 Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.00	4.32	29.17	35.62	112.70	110.57	74.00	36.57 peak
2	2483.50	4.34	29.30	35.61	72.99	71.02	74.00	-2.98 peak
3	2484.49	4.34	29.31	35.61	74.61	72.65	74.00	-1.35 peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 Band edge  
 Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 2462.00	4.32	29.17	35.62	102.11	99.98	54.00	45.98 Average
2	2483.50	4.34	29.30	35.61	52.08	50.11	54.00	-3.89 Average
3	2483.79	4.34	29.30	35.61	51.96	49.99	54.00	-4.01 Average



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 Band edge  
 Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 2462.00	4.32	29.17	35.62	98.16	96.03	74.00	22.03 Peak
2	2483.50	4.34	29.30	35.61	58.35	56.38	74.00	-17.62 Peak
3	2483.89	4.34	29.30	35.61	62.15	60.18	74.00	-13.82 Peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 Band edge  
 Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.00	4.32	29.17	35.62	89.35	87.22	54.00	33.22 Average
2	2483.50	4.34	29.30	35.61	44.84	42.87	54.00	-11.13 Average
3	2483.79	4.34	29.30	35.61	44.58	42.61	54.00	-11.39 Average



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2422 Band edge  
 Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2387.12	4.25	28.75	35.64	73.18	70.54	74.00	-3.46 peak
2	2390.00	4.25	28.76	35.64	70.27	67.64	74.00	-6.36 peak
3 q	2422.00	4.28	28.93	35.63	106.24	103.82	74.00	29.82 peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2422 Band edge  
 Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.83	4.25	28.76	35.64	53.41	50.78	54.00	-3.22	Average
2	2390.00	4.25	28.76	35.64	53.24	50.61	54.00	-3.39	Average
3 q	2422.00	4.28	28.93	35.63	96.54	94.12	54.00	40.12	Average



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2422 Band edge  
 Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2387.42	4.25	28.75	35.64	64.61	61.97	74.00	-12.03	Peak
2	2390.00	4.25	28.76	35.64	60.52	57.89	74.00	-16.11	Peak
3 q	2422.00	4.28	28.93	35.63	95.07	92.65	74.00	18.65	Peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2422 Band edge  
 Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.53	4.25	28.76	35.64	46.61	43.98	54.00	-10.02	Average
2	2390.00	4.25	28.76	35.64	46.74	44.11	54.00	-9.89	Average
3 q	2422.00	4.28	28.93	35.63	85.99	83.57	54.00	29.57	Average



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2452 Band edge  
 Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 2452.00	4.31	29.11	35.62	105.08	102.88	74.00	28.88 peak
2	2483.50	4.34	29.30	35.61	68.60	66.63	74.00	-7.37 peak
3	2488.10	4.35	29.33	35.61	72.15	70.22	74.00	-3.78 peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2452 Band edge  
 Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	q 2452.00	4.31	29.11	35.62	94.98	92.78	54.00	38.78	Average
2	2483.50	4.34	29.30	35.61	52.00	50.03	54.00	-3.97	Average
3	2484.64	4.35	29.31	35.61	51.65	49.70	54.00	-4.30	Average



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2452 Band edge  
 Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2452.00	4.31	29.11	35.62	92.91	90.71	74.00	16.71 Peak
2	2483.50	4.34	29.30	35.61	56.64	54.67	74.00	-19.33 Peak
3	2484.22	4.34	29.31	35.61	60.62	58.66	74.00	-15.34 Peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2452 Band edge  
 Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2452.00	4.31	29.11	35.62	83.99	81.79	54.00	27.79 Average
2	2483.50	4.34	29.30	35.61	45.08	43.11	54.00	-10.89 Average
3	2483.87	4.34	29.30	35.61	45.11	43.14	54.00	-10.86 Average



**7.8 Radiated Spurious Emissions Below 1GHz**

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

**7.8.1 E.U.T. Operation**

Operating Environment:

Temperature: 23.2 °C Humidity: 50.5 % RH Atmospheric Pressure: 1015 mbar

**7.8.2 Test Mode Description**


Pre-scan / Final test	Mode Code	Description
Pre-scan	07	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); Only the data of worst case is recorded in the report.
Final test	08	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); Only the data of worst case is recorded in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

### 7.8.3 Test Setup Diagram



### 7.8.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.



Test Mode: 08; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel: Middle



Condition: 10m HORIZONTAL


Job No. : 01013AT

Test Mode: 08

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	32.293	29.05	16.26	0.66	32.46	13.51	29.50	-15.99	QP
2	107.888	29.21	14.37	0.86	32.40	12.04	33.00	-20.96	QP
3 pp	243.377	44.33	15.97	1.30	32.40	29.20	35.60	-6.40	QP
4	297.224	38.01	17.60	1.43	32.40	24.64	35.60	-10.96	QP
5	492.469	29.90	21.76	1.84	32.49	21.01	35.60	-14.59	QP
6	696.857	27.15	25.10	2.21	32.50	21.96	35.60	-13.64	QP



Test Mode: 08; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel: Middle



Condition: 10m VERTICAL

Job No. : 01013AT

Test Mode: 08

	Read	Ant	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 pp	42.154	36.12	17.22	0.60	32.43	21.51	29.50	-7.99 QP
2	107.888	39.38	14.37	0.86	32.40	22.21	33.00	-10.79 QP
3	176.888	35.48	16.06	1.11	32.40	20.25	33.00	-12.75 QP
4	243.377	36.83	15.97	1.30	32.40	21.70	35.60	-13.90 QP
5	359.186	34.25	18.98	1.53	32.40	22.36	35.60	-13.24 QP
6	502.940	31.81	22.01	1.86	32.50	23.18	35.60	-12.42 QP



# SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230400101303

Page: 64 of 139

The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L<sub>3</sub>: Level @ 3m distance. Unit: uV/m;

L<sub>10</sub>: Level @ 10m distance. Unit: uV/m;

D<sub>3</sub>: 3m distance. Unit: m

D<sub>10</sub>: 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 3m (uV/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
32.293	13.51	4.74	15.79	23.97	40	-16.03	H
107.888	12.04	4.00	13.33	22.50	43.5	-21.00	H
243.377	29.20	28.84	96.13	39.66	46	-6.34	H
297.224	24.64	17.06	56.87	35.10	46	-10.90	H
492.469	21.01	11.23	37.44	31.47	46	-14.53	H
696.857	21.96	12.53	41.77	32.42	46	-13.58	H
42.154	21.51	11.90	39.66	31.97	40	-8.03	V
107.888	22.21	12.90	42.99	32.67	43.5	-10.83	V
176.888	20.25	10.29	34.31	30.71	43.5	-12.79	V
243.377	21.70	12.16	40.54	32.16	46	-13.84	V
359.186	22.36	13.12	43.74	32.82	46	-13.18	V
502.940	23.18	14.42	48.07	33.64	46	-12.36	V



SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch Technical Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

**7.9 Radiated Spurious Emissions Above 1GHz**

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

**7.9.1 E.U.T. Operation**

Operating Environment:

Temperature: 22.9 °C Humidity: 51.2 % RH Atmospheric Pressure: 1010 mbar

**7.9.2 Test Mode Description**


Pre-scan / Final test	Mode Code	Description
Pre-scan	07	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); Only the data of worst case is recorded in the report.
Final test	08	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); Only the data of worst case is recorded in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

### 7.9.3 Test Setup Diagram



Above 1GHz



### 7.9.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Test Mode: 08; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 TX RSE  
 : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1199.73	2.80	24.40	37.71	50.99	40.48	74.00	-33.52	peak
2	4495.13	6.77	33.50	34.67	46.10	51.70	74.00	-22.30	peak
3	4824.00	7.06	33.90	34.88	45.41	51.49	74.00	-22.51	peak
4	6974.98	8.32	35.75	35.89	44.81	52.99	74.00	-21.01	peak
5	7236.00	8.54	35.80	35.95	44.86	53.25	74.00	-20.75	peak
6 q	9648.00	10.41	37.10	35.55	41.54	53.50	74.00	-20.50	peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 TX RSE  
 : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1682.48	3.47	26.77	36.44	46.55	40.35	74.00	-33.65	peak
2	4392.38	6.67	33.52	34.60	45.57	51.16	74.00	-22.84	peak
3	4824.00	7.06	33.90	34.88	44.86	50.94	74.00	-23.06	peak
4	6894.81	8.30	35.60	35.82	44.59	52.67	74.00	-21.33	peak
5	7236.00	8.54	35.80	35.95	45.08	53.47	74.00	-20.53	peak
6 q	9648.00	10.41	37.10	35.55	41.53	53.49	74.00	-20.51	peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2437 TX RSE  
 : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Factor	Level	Line	Limit	Remark	
MHz	dB	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1611.09	3.38	26.54	36.60	47.35	40.67	74.00	-33.33	peak
2	4279.59	6.56	33.60	34.53	46.06	51.69	74.00	-22.31	peak
3	4874.00	7.10	34.05	34.91	44.08	50.32	74.00	-23.68	peak
4	6377.20	8.22	35.25	35.38	45.11	53.20	74.00	-20.80	peak
5	7311.00	8.61	35.90	35.97	44.76	53.30	74.00	-20.70	peak
6 q	9748.00	10.45	37.20	35.56	41.54	53.63	74.00	-20.37	peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2437 TX RSE  
 : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1	1331.29	3.01	24.83	37.32	51.37	41.89	74.00	-32.11 peak
2	4367.06	6.65	33.57	34.59	46.10	51.73	74.00	-22.27 peak
3	4874.00	7.10	34.05	34.91	44.24	50.48	74.00	-23.52 peak
4	6526.37	8.25	35.55	35.51	44.38	52.67	74.00	-21.33 peak
5	7311.00	8.61	35.90	35.97	44.64	53.18	74.00	-20.82 peak
6 q	9748.00	10.45	37.20	35.56	41.85	53.94	74.00	-20.06 peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 TX RSE  
 : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1331.29	3.01	24.83	37.32	51.06	41.58	74.00	-32.42	peak
2	4181.77	6.47	33.29	34.46	45.68	50.98	74.00	-23.02	peak
3	4924.00	7.15	34.15	34.94	43.57	49.93	74.00	-24.07	peak
4	6507.54	8.24	35.52	35.50	44.33	52.59	74.00	-21.41	peak
5	7386.00	8.68	35.90	35.98	44.19	52.79	74.00	-21.21	peak
6 q	9848.00	10.49	37.30	35.57	40.87	53.09	74.00	-20.91	peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 TX RSE  
 : 2.4G WIFI 11B

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1702.04	3.49	26.80	36.40	46.37	40.26	74.00	-33.74 peak
2	4367.06	6.65	33.57	34.59	46.28	51.91	74.00	-22.09 peak
3	4924.00	7.15	34.15	34.94	44.07	50.43	74.00	-23.57 peak
4	6377.20	8.22	35.25	35.38	44.75	52.84	74.00	-21.16 peak
5	7386.00	8.68	35.90	35.98	44.19	52.79	74.00	-21.21 peak
6 q	9848.00	10.49	37.30	35.57	41.22	53.44	74.00	-20.56 peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 TX RSE  
 : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1468.76	3.20	25.28	36.95	49.25	40.78	74.00	-33.22	peak
2	4469.21	6.74	33.50	34.65	45.97	51.56	74.00	-22.44	peak
3	4824.00	7.06	33.90	34.88	45.52	51.60	74.00	-22.40	peak
4	6488.75	8.24	35.48	35.48	44.86	53.10	74.00	-20.90	peak
5	7236.00	8.54	35.80	35.95	44.60	52.99	74.00	-21.01	peak
6 q	9648.00	10.41	37.10	35.55	41.31	53.27	74.00	-20.73	peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 TX RSE  
 : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1331.29	3.01	24.83	37.32	50.51	41.03	74.00	-32.97	peak
2	4379.70	6.66	33.54	34.59	45.71	51.32	74.00	-22.68	peak
3	4824.00	7.06	33.90	34.88	44.28	50.36	74.00	-23.64	peak
4	6679.04	8.27	35.60	35.65	44.47	52.69	74.00	-21.31	peak
5	7236.00	8.54	35.80	35.95	44.86	53.25	74.00	-20.75	peak
6 q	9648.00	10.41	37.10	35.55	41.92	53.88	74.00	-20.12	peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:middle




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2437 TX RSE  
 : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1331.29	3.01	24.83	37.32	49.98	40.50	74.00	-33.50	peak
2	4469.21	6.74	33.50	34.65	46.54	52.13	74.00	-21.87	peak
3	4874.00	7.10	34.05	34.91	44.68	50.92	74.00	-23.08	peak
4	5763.62	7.95	34.53	35.03	44.93	52.38	74.00	-21.62	peak
5 q	7311.00	8.61	35.90	35.97	45.32	53.86	74.00	-20.14	peak
6	9748.00	10.45	37.20	35.56	41.65	53.74	74.00	-20.26	peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:middle




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2437 TX RSE  
 : 2.4G WIFI 11G

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1672.78	3.46	26.75	36.46	46.46	40.21	74.00	-33.79 peak
2	4379.70	6.66	33.54	34.59	45.49	51.10	74.00	-22.90 peak
3	4874.00	7.10	34.05	34.91	44.70	50.94	74.00	-23.06 peak
4	6995.17	8.32	35.79	35.91	44.88	53.08	74.00	-20.92 peak
5	7311.00	8.61	35.90	35.97	44.90	53.44	74.00	-20.56 peak
6 q	9748.00	10.45	37.20	35.56	41.76	53.85	74.00	-20.15 peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 TX RSE  
 : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1653.55	3.43	26.71	36.51	46.40	40.03	74.00	-33.97	peak
2	4291.98	6.57	33.60	34.54	45.78	51.41	74.00	-22.59	peak
3	4924.00	7.15	34.15	34.94	44.34	50.70	74.00	-23.30	peak
4 q	6874.91	8.30	35.60	35.81	45.02	53.11	74.00	-20.89	peak
5	7386.00	8.68	35.90	35.98	44.11	52.71	74.00	-21.29	peak
6	9848.00	10.49	37.30	35.57	40.60	52.82	74.00	-21.18	peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 TX RSE  
 : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1601.80	3.37	26.51	36.63	47.75	41.00	74.00	-33.00	peak
2	4230.40	6.51	33.52	34.49	45.72	51.26	74.00	-22.74	peak
3	4924.00	7.15	34.15	34.94	44.55	50.91	74.00	-23.09	peak
4	6914.76	8.31	35.63	35.84	44.24	52.34	74.00	-21.66	peak
5 q	7386.00	8.68	35.90	35.98	45.25	53.85	74.00	-20.15	peak
6	9848.00	10.49	37.30	35.57	41.30	53.52	74.00	-20.48	peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 TX RSE  
 : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1	1597.18	3.37	26.47	36.64	48.76	41.96	74.00	-32.04 peak
2	4443.45	6.72	33.50	34.64	45.88	51.46	74.00	-22.54 peak
3	4824.00	7.06	33.90	34.88	45.44	51.52	74.00	-22.48 peak
4	5797.03	7.98	34.59	35.03	45.05	52.59	74.00	-21.41 peak
5	7236.00	8.54	35.80	35.95	44.29	52.68	74.00	-21.32 peak
6 q	9648.00	10.41	37.10	35.55	41.56	53.52	74.00	-20.48 peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2412 TX RSE  
 : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1601.80	3.37	26.51	36.63	48.58	41.83	74.00	-32.17 peak
2	4329.35	6.61	33.60	34.56	45.97	51.62	74.00	-22.38 peak
3	4824.00	7.06	33.90	34.88	44.29	50.37	74.00	-23.63 peak
4	6934.78	8.31	35.67	35.86	45.04	53.16	74.00	-20.84 peak
5	7236.00	8.54	35.80	35.95	44.98	53.37	74.00	-20.63 peak
6 q	9648.00	10.41	37.10	35.55	41.70	53.66	74.00	-20.34 peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2437 TX RSE  
 : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	3.47	26.77	36.43	46.37	40.18	74.00	-33.82	peak
2	6.71	33.50	34.63	45.87	51.45	74.00	-22.55	peak
3	7.10	34.05	34.91	45.95	52.19	74.00	-21.81	peak
4	8.22	35.20	35.35	45.17	53.24	74.00	-20.76	peak
5 q	8.61	35.90	35.97	45.20	53.74	74.00	-20.26	peak
6	10.45	37.20	35.56	41.44	53.53	74.00	-20.47	peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2437 TX RSE  
 : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1327.45	3.00	24.81	37.33	51.05	41.53	74.00	-32.47	peak
2	4230.40	6.51	33.52	34.49	45.80	51.34	74.00	-22.66	peak
3	4874.00	7.10	34.05	34.91	44.43	50.67	74.00	-23.33	peak
4	6974.98	8.32	35.75	35.89	44.55	52.73	74.00	-21.27	peak
5 q	7311.00	8.61	35.90	35.97	45.00	53.54	74.00	-20.46	peak
6	9748.00	10.45	37.20	35.56	41.14	53.23	74.00	-20.77	peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 TX RSE  
 : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1601.80	3.37	26.51	36.63	47.60	40.85	74.00	-33.15	peak
2	4181.77	6.47	33.29	34.46	45.62	50.92	74.00	-23.08	peak
3	4924.00	7.15	34.15	34.94	43.60	49.96	74.00	-24.04	peak
4	6717.76	8.28	35.56	35.68	45.26	53.42	74.00	-20.58	peak
5 q	7386.00	8.68	35.90	35.98	45.01	53.61	74.00	-20.39	peak
6	9848.00	10.49	37.30	35.57	41.28	53.50	74.00	-20.50	peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2462 TX RSE  
 : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	3.46	26.75	36.46	46.89	40.64	74.00	-33.36	peak
2	6.34	32.93	34.38	46.33	51.22	74.00	-22.78	peak
3	7.15	34.15	34.94	44.43	50.79	74.00	-23.21	peak
4	8.30	35.60	35.82	44.81	52.89	74.00	-21.11	peak
5 q	8.68	35.90	35.98	44.79	53.39	74.00	-20.61	peak
6	10.49	37.30	35.57	41.08	53.30	74.00	-20.70	peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2422 TX RSE  
 : 2.4G WIFI 11N40

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1648.78	3.43	26.70	36.52	46.51	40.12	74.00	-33.88 peak
2	4329.35	6.61	33.60	34.56	45.28	50.93	74.00	-23.07 peak
3	4844.00	7.08	33.98	34.89	45.38	51.55	74.00	-22.45 peak
4	6934.78	8.31	35.67	35.86	44.40	52.52	74.00	-21.48 peak
5 q	7266.00	8.57	35.83	35.96	44.91	53.35	74.00	-20.65 peak
6	9688.00	10.42	37.10	35.56	41.33	53.29	74.00	-20.71 peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2422 TX RSE  
 : 2.4G WIFI 11N40

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1672.78	3.46	26.75	36.46	47.53	41.28	74.00	-32.72 peak
2	4443.45	6.72	33.50	34.64	45.62	51.20	74.00	-22.80 peak
3	4844.00	7.08	33.98	34.89	44.76	50.93	74.00	-23.07 peak
4	6954.85	8.31	35.71	35.87	44.73	52.88	74.00	-21.12 peak
5	7266.00	8.57	35.83	35.96	44.67	53.11	74.00	-20.89 peak
6 q	9688.00	10.42	37.10	35.56	41.99	53.95	74.00	-20.05 peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:middle




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2437 TX RSE  
 : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1	1331.29	3.01	24.83	37.32	50.00	40.52	74.00	-33.48 peak
2	4417.84	6.69	33.50	34.62	45.57	51.14	74.00	-22.86 peak
3	4874.00	7.10	34.05	34.91	44.74	50.98	74.00	-23.02 peak
4	5813.81	8.00	34.63	35.03	45.28	52.88	74.00	-21.12 peak
5	7311.00	8.61	35.90	35.97	44.50	53.04	74.00	-20.96 peak
6 q	9748.00	10.45	37.20	35.56	41.31	53.40	74.00	-20.60 peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:middle




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2437 TX RSE  
 : 2.4G WIFI 11N40

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1702.04	3.49	26.80	36.40	46.51	40.40	74.00	-33.60 peak
2	4417.84	6.69	33.50	34.62	45.75	51.32	74.00	-22.68 peak
3	4874.00	7.10	34.05	34.91	44.04	50.28	74.00	-23.72 peak
4	6358.79	8.22	35.22	35.37	44.46	52.53	74.00	-21.47 peak
5 q	7311.00	8.61	35.90	35.97	44.77	53.31	74.00	-20.69 peak
6	9748.00	10.45	37.20	35.56	40.96	53.05	74.00	-20.95 peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01013AT/01014AT  
 Mode : 2452 TX RSE  
 : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Factor	Level	Line	Limit	Remark	
MHz	dB	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.62	3.46	26.76	36.45	46.83	40.60	74.00	-33.40	peak
2	4193.87	6.48	33.36	34.47	46.31	51.68	74.00	-22.32	peak
3	4904.00	7.13	34.11	34.92	44.47	50.79	74.00	-23.21	peak
4 q	6303.89	8.21	35.20	35.32	44.86	52.95	74.00	-21.05	peak
5	7356.00	8.65	35.90	35.98	44.36	52.93	74.00	-21.07	peak
6	9808.00	10.47	37.22	35.57	40.75	52.87	74.00	-21.13	peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01013AT/01014AT  
 Mode : 2452 TX RSE  
 : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1252.89	2.89	24.51	37.55	51.51	41.36	74.00	-32.64	peak
2	4254.92	6.54	33.60	34.51	45.90	51.53	74.00	-22.47	peak
3	4904.00	7.13	34.11	34.92	43.94	50.26	74.00	-23.74	peak
4	6894.81	8.30	35.60	35.82	44.38	52.46	74.00	-21.54	peak
5	7356.00	8.65	35.90	35.98	44.88	53.45	74.00	-20.55	peak
6 q	9808.00	10.47	37.22	35.57	41.49	53.61	74.00	-20.39	peak



## 8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2304001013AT

## 9 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for SZCR2304001013AT



## 10 Appendix

### 1. Duty Cycle

#### 1.1 Ant1

##### 1.1.1 Test Result


Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11b	SISO	2412	8.616	8.626	99.88	0.01	0.04
		2437	8.616	8.626	99.88	0.01	0.04
		2462	8.616	8.626	99.88	0.01	0.04
802.11g	SISO	2412	1.427	1.445	98.75	0.05	0.03
		2437	1.428	1.445	98.82	0.05	0.03
		2462	1.429	1.446	98.82	0.05	0.03
802.11n (HT20)	SISO	2412	1.337	1.354	98.74	0.05	0.03
		2437	1.337	1.354	98.74	0.05	0.03
		2462	1.336	1.355	98.60	0.06	0.03
802.11n (HT40)	SISO	2422	0.664	0.682	97.36	0.12	0.03
		2437	0.666	0.682	97.65	0.10	0.03
		2452	0.665	0.682	97.51	0.11	0.03





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


### 1.1.2 Test Graph









802.11n(HT20)\_LCH\_2412MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20)\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20)\_HCH\_2462MHz\_Ant1 (SISO)\_NTNV




802.11n(HT40)\_LCH\_2422MHz\_Ant1 (SISO)\_NTNV



802.11n(HT40)\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV



802.11n(HT40)\_HCH\_2452MHz\_Ant1 (SISO)\_NTNV



2. Bandwidth


2.1 OBW

2.1.1 Test Result

Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)	Verdict
				Result	
802.11b	SISO	2412	1	11.703	Pass
		2437	1	11.940	Pass
		2462	1	11.966	Pass
802.11g	SISO	2412	1	17.856	Pass
		2437	1	17.997	Pass
		2462	1	17.657	Pass
802.11n (HT20)	SISO	2412	1	18.741	Pass
		2437	1	18.994	Pass
		2462	1	18.681	Pass
802.11n (HT40)	SISO	2422	1	36.966	Pass
		2437	1	37.056	Pass
		2452	1	36.966	Pass





### 2.1.2 Test Graph




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**







### 802.11n(HT20)\_LCH\_2412MHz\_Ant1 (SISO)\_NTNV




### 802.11n(HT20)\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV






802.11n(HT40)\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV



802.11n(HT40)\_HCH\_2452MHz\_Ant1 (SISO)\_NTNV



2.2 6dB BW

2.2.1 Test Result


Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
802.11b	SISO	2412	1	8.126	>=0.5	Pass
		2437	1	8.130	>=0.5	Pass
		2462	1	8.131	>=0.5	Pass
802.11g	SISO	2412	1	15.243	>=0.5	Pass
		2437	1	16.312	>=0.5	Pass
		2462	1	15.213	>=0.5	Pass
802.11n (HT20)	SISO	2412	1	15.223	>=0.5	Pass
		2437	1	17.055	>=0.5	Pass
		2462	1	15.487	>=0.5	Pass
802.11n (HT40)	SISO	2422	1	35.662	>=0.5	Pass
		2437	1	35.798	>=0.5	Pass
		2452	1	35.682	>=0.5	Pass





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


### 2.2.2 Test Graph









802.11n(HT20)\_LCH\_2412MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20)\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV






802.11n(HT40)\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV



802.11n(HT40)\_HCH\_2452MHz\_Ant1 (SISO)\_NTNV



### 3. Maximum Conducted Output Power

#### 3.1 Power

##### 3.1.1 Test Result

Mode	TX Type	Frequency (MHz)	Maximum Average Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
802.11b	SISO	2412	17.58	<=30	Pass
		2437	17.63	<=30	Pass
		2462	17.59	<=30	Pass
802.11g	SISO	2412	17.02	<=30	Pass
		2437	16.90	<=30	Pass
		2462	17.03	<=30	Pass
802.11n (HT20)	SISO	2412	16.64	<=30	Pass
		2437	16.71	<=30	Pass
		2462	16.74	<=30	Pass
802.11n (HT40)	SISO	2422	15.81	<=30	Pass
		2437	16.01	<=30	Pass
		2452	15.92	<=30	Pass



## 4. Maximum Power Spectral Density


### 4.1 PSD


#### 4.1.1 Test Result

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm/3kHz)		Verdict
			ANT1	Limit	
802.11b	SISO	2412	-5.43	<=8	Pass
		2437	-5.32	<=8	Pass
		2462	-5.60	<=8	Pass
802.11g	SISO	2412	-5.44	<=8	Pass
		2437	-7.92	<=8	Pass
		2462	-6.23	<=8	Pass
802.11n (HT20)	SISO	2412	-7.21	<=8	Pass
		2437	-7.83	<=8	Pass
		2462	-6.40	<=8	Pass
802.11n (HT40)	SISO	2422	-12.12	<=8	Pass
		2437	-11.41	<=8	Pass
		2452	-10.32	<=8	Pass




### 4.1.2 Test Graph






Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com



802.11n(HT20)\_LCH\_2412MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20)\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**

802.11n(HT20)\_HCH\_2462MHz\_Ant1 (SISO)\_NTNV




802.11n(HT40)\_LCH\_2422MHz\_Ant1 (SISO)\_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

802.11n(HT40)\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV



802.11n(HT40)\_HCH\_2452MHz\_Ant1 (SISO)\_NTNV



## 5. Unwanted Emissions In Non-restricted Frequency Bands


### 5.1 Ref


#### 5.1.1 Test Result

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
802.11b	SISO	2412	1	9.38
		2437	1	9.45
		2462	1	9.00
802.11g	SISO	2412	1	5.76
		2437	1	5.35
		2462	1	5.94
802.11n (HT20)	SISO	2412	1	5.81
		2437	1	5.84
		2462	1	5.96
802.11n (HT40)	SISO	2422	1	1.86
		2437	1	1.99
		2452	1	1.98



### 5.1.2 Test Graph





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**

