

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230400101305


Page: 1 of 354

TEST REPORT

Application No.: SZCR2304001013AT
Applicant: SZ DJI TECHNOLOGY CO., LTD.
Address of Applicant: Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili Community, Xili Street, Nanshan District, Shenzhen, China.
Manufacturer: SZ DJI TECHNOLOGY CO., LTD.
Address of Manufacturer: Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili Community, Xili Street, Nanshan District, Shenzhen, China.
Equipment Under Test (EUT):
EUT Name: DJI Air 3
Model No.: EB3WBC
Trade Mark: DJI
FCC ID: SS3-EB3WBC2303
Standard(s) : 47 CFR Part 15, Subpart E 15.407
Date of Receipt: 2023-04-10
Date of Test: 2023-04-24 to 2023-05-28
Date of Issue: 2023-06-06

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2023-06-06		Original

Authorized for issue by:			
		Darren Yuan	
		_____ Darren Yuan/Project Engineer	
		Eric Fu	
		_____ Eric Fu/Reviewer	



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart E 15.407	N/A	47 CFR Part 15, Subpart C 15.203	Pass
Transmission in the Absence of Data		N/A	47 CFR Part 15, Subpart E 15.407 (c)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart E 15.407	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)	Pass
Duty Cycle		KDB 789033 II B 1	KDB 789033 D02 II B 1	Pass
99% Bandwidth		KDB 789033 II D	N/A	Pass
26dB Emission bandwidth		KDB 789033 D02 II C 1	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Minimum 6 dB bandwidth (5.725-5.85 GHz band)		KDB 789033 D02 II C 2	47 CFR Part 15, Subpart E 15.407 (e)	Pass
Maximum Conducted output power		KDB 789033 D02 II E	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Peak Power spectrum density		KDB 789033 D02 II F	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Radiated Emissions (Below 1GHz)		KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions which fall in the restricted bands		KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions (Above 1GHz)		KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Frequency Stability		ANSI C63.10 (2013) Section 6.8	47 CFR Part 15, Subpart E 15.407 (g)	Pass

Remark: KDB 789033 D02 is not accredited by A2LA



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	6
4.1 Details of E.U.T.....	6
4.2 Description of Support Units.....	7
4.3 Measurement Uncertainty	7
4.4 Test Location	8
4.5 Test Facility.....	8
4.6 Deviation from Standards.....	8
4.7 Abnormalities from Standard Conditions.....	8
5 Equipment List	9
6 Radio Spectrum Technical Requirement	14
6.1 Antenna Requirement	14
6.1.1 Test Requirement:	14
6.1.2 Conclusion.....	14
6.2 Transmission in the Absence of Data	15
6.2.1 Test Requirement:	15
6.2.2 Conclusion.....	15
7 Radio Spectrum Matter Test Results	16
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	16
7.1.1 E.U.T. Operation	16
7.1.2 Test Mode Description	16
7.1.3 Test Setup Diagram	17
7.1.4 Measurement Procedure and Data.....	17
7.2 Duty Cycle	20
7.2.1 E.U.T. Operation	20
7.2.2 Test Mode Description	20
7.2.3 Test Setup Diagram	20
7.2.4 Measurement Procedure and Data.....	20
7.3 99% Bandwidth	21
7.3.1 E.U.T. Operation	21
7.3.2 Test Mode Description	21
7.3.3 Test Setup Diagram	21
7.3.4 Measurement Procedure and Data.....	21
7.4 26dB Emission bandwidth	22
7.4.1 E.U.T. Operation	22
7.4.2 Test Mode Description	22



7.4.3	Test Setup Diagram	22
7.4.4	Measurement Procedure and Data.....	22
7.5	Minimum 6 dB bandwidth (5.725-5.85 GHz band).....	23
7.5.1	E.U.T. Operation	23
7.5.2	Test Mode Description	23
7.5.3	Test Setup Diagram	24
7.5.4	Measurement Procedure and Data.....	24
7.6	Maximum Conducted output power	25
7.6.1	E.U.T. Operation	25
7.6.2	Test Mode Description	25
7.6.3	Test Setup Diagram	26
7.6.4	Measurement Procedure and Data.....	26
7.7	Peak Power spectrum density	27
7.7.1	E.U.T. Operation	27
7.7.2	Test Mode Description	27
7.7.3	Test Setup Diagram	28
7.7.4	Measurement Procedure and Data.....	28
7.8	Radiated Emissions (Below 1GHz).....	29
7.8.1	E.U.T. Operation	29
7.8.2	Test Mode Description	29
7.8.3	Test Setup Diagram	30
7.8.4	Measurement Procedure and Data.....	31
7.9	Radiated Emissions which fall in the restricted bands	35
7.9.1	E.U.T. Operation	35
7.9.2	Test Mode Description	36
7.9.3	Test Setup Diagram	37
7.9.4	Measurement Procedure and Data.....	37
7.10	Radiated Emissions (Above 1GHz).....	86
7.10.1	E.U.T. Operation.....	87
7.10.2	Test Mode Description	87
7.10.3	Test Setup Diagram	88
7.10.4	Measurement Procedure and Data.....	89
7.11	Frequency Stability.....	108
7.11.1	E.U.T. Operation.....	108
7.11.2	Test Mode Description	108
7.11.3	Test Setup Diagram	108
7.11.4	Measurement Procedure and Data.....	108
8	Test Setup Photo	109
9	EUT Constructional Details (EUT Photos).....	109
10	Appendix.....	110



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	Powered by Lithium-ion Polymer rechargeable battery Battery information Model: BWX233-4241-14.76 Nominal Voltage: 14.76V Rated Capacity: 4241mAh, 62.6Wh
Operation Frequency:	5.1G SDR 10MHz: 5157MHz-5245MHz 20MHz: 5161MHz-5240MHz 40MHz: 5170MHz-5230MHz 5.8G SDR 1.4MHz mode: 5728.5MHz-5844.5MHz 1.4MHz CA mode: 5730.12MHz-5846.12MHz 3MHz mode: 5727.5MHz-5844.5MHz 3MHz CA mode: 5730.2MHz-5847.2MHz 5MHz mode: 5732.5MHz-5842.5MHz 10MHz mode: 5730.5MHz-5844.5MHz 20MHz: 5735.5MHz-5839.5MHz 40MHz: 5745.5MHz-5829.5MHz
Modulation Type:	OFDM
Channel Spacing:	5.1G SDR 10MHz: 1MHz 20MHz: 1MHz 40MHz: 1MHz 5.8G SDR 1.4MHz mode: 2MHz 1.4MHz CA mode: 2MHz 3MHz mode: 3MHz 3MHz CA mode: 3MHz 5MHz mode: 5MHz 10MHz mode: 1MHz 20MHz: 1MHz 40MHz: 1MHz
Number of Channels:	5.1G SDR 10MHz: 89 20MHz: 80 40MHz: 61



	5.8G SDR 1.4MHz mode: 59 1.4MHz CA mode: 59 3MHz mode: 40 3MHz CA mode: 40 5MHz mode: 23 10MHz mode: 115 20MHz mode: 105 40MHz mode: 85
Antenna Type:	PCB Antenna
Antenna Gain:	5.1G SDR: Antenna 0&1: 2.5dBi, Antenna 2&3: 1.5dBi, Antenna 4&5: 1dBi 5.8G SDR: Antenna 0&1: 2dBi, Antenna 2&3: 3dBi, Antenna 4&5: 2.5dBi

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Power Adapter	DJI	PD-65US	N/A

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	± 3.1dB
Duty Cycle	± 0.37%
99% Bandwidth	± 3%
26dB Emission bandwidth	± 3%
Minimum 6 dB bandwidth (5.725-5.85 GHz band)	± 3%
Maximum Conducted output power	± 0.75dB
Peak Power spectrum density	± 2.84dB
Radiated Emissions (Below 1GHz)	± 6.0dB for 3m; ± 5.0dB for 10m
Radiated Emissions which fall in the restricted bands	± 6.0dB (below 1GHz); ± 4.6dB (above 1GHz);
Radiated Emissions (Above 1GHz)	± 4.6dB (1-18GHz); ± 4.8dB (18-40GHz)
Frequency Stability	± 7.25 x 10-8

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{CISPR/ETSI}$ (CISPR/ETSI Uncertainty), so the test results
 – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
 – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.11 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2022-05-14	2025-05-13
EMI Test Receiver	Rohde&Schwarz	ESCI	SEM004-02	2023-03-20	2024-03-19
Matching Pad	N/A	N/A	SEM021-23	2023-03-22	2024-03-21
Matching Pad	N/A	N/A	SEM021-24	2023-03-22	2024-03-21
Measurement Software	AUDIX	e3 V8.2014-6-27a	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2022-07-08	2023-07-07
LISN	Rohde&Schwarz	ENV216	SEM007-01	2022-09-20	2023-09-19
LISN	ETS-LINDGREN	3816/2	SEM007-02	2023-03-20	2024-03-19

Duty Cycle					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2022-10-20	2023-10-19
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2023-03-21	2024-03-20
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2022-09-29	2023-09-28
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2022-07-08	2023-07-07
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2023-03-31	2024-03-30
Programmable Temperature & Humidity Chamber	Votsch Industrietechnik GmbH	VT 4002	SEM002-15	2023-03-21	2024-03-20

99% Bandwidth					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2022-10-20	2023-10-19
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2023-03-21	2024-03-20
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2022-09-29	2023-09-28
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2022-07-08	2023-07-07
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2023-03-31	2024-03-30
Programmable Temperature & Humidity Chamber	Votsch Industrietechnik GmbH	VT 4002	SEM002-15	2023-03-21	2024-03-20



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230400101305

Page: 10 of 354

26dB Emission bandwidth					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2022-10-20	2023-10-19
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2023-03-21	2024-03-20
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2022-09-29	2023-09-28
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2022-07-08	2023-07-07
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2023-03-31	2024-03-30
Programmable Temperature & Humidity Chamber	Votsch Industrietechnik GmbH	VT 4002	SEM002-15	2023-03-21	2024-03-20

Minimum 6 dB bandwidth (5.725-5.85 GHz band)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2022-10-20	2023-10-19
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2023-03-21	2024-03-20
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2022-09-29	2023-09-28
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2022-07-08	2023-07-07
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2023-03-31	2024-03-30
Programmable Temperature & Humidity Chamber	Votsch Industrietechnik GmbH	VT 4002	SEM002-15	2023-03-21	2024-03-20



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Center EEC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Maximum Conducted output power					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2023-04-01	2024-03-31
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2023-03-21	2024-03-20
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2022-10-20	2023-10-19
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2023-03-21	2024-03-20
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2022-09-29	2023-09-28
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2022-07-08	2023-07-07
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2023-03-31	2024-03-30
Programmable Temperature & Humidity Chamber	Votsch Industrietechnik GmbH	VT 4002	SEM002-15	2023-03-21	2024-03-20

Peak Power spectrum density					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2022-10-20	2023-10-19
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2023-03-21	2024-03-20
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2022-09-29	2023-09-28
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2022-07-08	2023-07-07
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2023-03-31	2024-03-30
Programmable Temperature & Humidity Chamber	Votsch Industrietechnik GmbH	VT 4002	SEM002-15	2023-03-21	2024-03-20



Radiated Emissions (Below 1GHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2021-03-27	2024-03-26
MXE EMI receiver	KEYSIGHT	N9038A	SEM004-16	2022-10-20	2023-10-19
Trilog-Broadband Antenna	Schwarzbeck	VULB9168	SEM003-18	2021-10-28	2023-10-27
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-04	2023-03-31	2024-03-30
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2021-11-30	2023-11-29
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM029-01	2022-07-08	2023-07-07

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2022-04-02	2025-04-01
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2023-03-20	2024-03-19
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2022-07-24	2024-07-23
Microwave system amplifier	Agilent	83017A	SEM005-25	2022-09-21	2023-09-20
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2022-07-08	2023-07-07

Radiated Emissions (Above 1GHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2022-04-02	2025-04-01
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2023-03-20	2024-03-19
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2022-07-24	2024-07-23
Microwave system amplifier	Agilent	83017A	SEM005-25	2022-09-21	2023-09-20
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2022-07-08	2023-07-07



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230400101305

Page: 13 of 354

Frequency Stability					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2022-10-20	2023-10-19
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2023-03-21	2024-03-20
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2022-09-29	2023-09-28
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2022-07-08	2023-07-07
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2023-03-31	2024-03-30
Programmable Temperature & Humidity Chamber	Votsch Industrietechnik GmbH	VT 4002	SEM002-15	2023-03-21	2024-03-20

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2022-09-04	2023-09-03
Humidity/ Temperature Indicator	Anymetre	TH101B	SEM002-09	2022-09-04	2023-09-03
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2023-03-23	2024-03-22



6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the Antenna are follows:

5.1G SDR: ANT0&1: 2.5dBi, ANT2&3: 1.5dBi, ANT4&5: 1dBi, the directional gain is 5.51dBi

5.8G SDR: ANT0&1: 2dBi, ANT2&3: 3dBi, ANT4&5: 2.5dBi, the directional gain is 6.01dBi

Antenna location: Refer to internal photo.



6.2 Transmission in the Absence of Data

6.2.1 Test Requirement:

47 CFR Part 15, Subpart E 15.407 (c)

6.2.2 Conclusion

Standard Requirement:

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Applicants shall include in their application for equipment authorization a description of how this requirement is met.

EUT Details:

SDR chip support automatically discontinue transmission in case of either absence of information to transmit or operational failure, if the chip detect absence of information to transmit or operational failure, it will be automatically shut off.



7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

7.1.1 E.U.T. Operation

Operating Environment:


Temperature: 23.2 °C Humidity: 50.5 % RH Atmospheric Pressure: 1015 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	26	TX mode (5.8G SDR_1.4MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	28	TX mode (5.8G SDR_3MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	30	TX mode (5.8G SDR_5MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	32	TX mode (5.8G SDR_10MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	34	TX mode (5.8G SDR_20MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	36	TX mode (5.8G SDR_40MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	38	TX mode (5.1G SDR_10MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	40	TX mode (5.1G SDR_20MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Final test	42	TX mode (5.1G SDR_40MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter



7.1.3 Test Setup Diagram




7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: Level=Read Level+ Cable Loss+ LISN Factor



Test Mode: 42; Line: Live line




Site : Shielding Room
 Condition: Line
 Job No. : 01013AT
 Test mode: 42

	Freq	Cable Loss	LISN Factor	Read Level	Limit Level	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB
1	0.1659	0.03	9.62	25.68	35.33	65.16	-29.83 QP
2	0.1659	0.03	9.62	-2.59	7.06	55.16	-48.10 Average
3	0.2378	0.04	9.62	34.40	44.06	62.17	-18.11 QP
4	0.2378	0.04	9.62	25.10	34.76	52.17	-17.41 Average
5	0.3596	0.05	9.62	34.48	44.15	58.74	-14.59 QP
6	0.3596	0.05	9.62	25.55	35.22	48.74	-13.52 Average
7 *	0.5641	0.06	9.62	32.01	41.69	56.00	-14.31 QP
8 *	0.5641	0.06	9.62	23.83	33.51	46.00	-12.49 Average
9	2.7068	0.12	9.64	21.63	31.39	56.00	-24.61 QP
10	2.7068	0.12	9.64	12.24	22.00	46.00	-24.00 Average
11	5.4763	0.16	9.68	15.90	25.74	60.00	-34.26 QP
12	5.4763	0.16	9.68	9.04	18.88	50.00	-31.12 Average



Test Mode: 42; Line: Neutral Line



Site : Shielding Room
 Condition: Neutral
 Job No. : 01013AT
 Test mode: 42

	Freq	Cable Loss	LISN Factor	Read Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dB	
1	0.1806	0.03	9.62	23.72	64.46	-31.09	QP
2	0.1806	0.03	9.62	-3.95	54.46	-48.76	Average
3	0.2256	0.04	9.62	31.07	62.61	-21.88	QP
4	0.2256	0.04	9.62	20.70	52.61	-22.25	Average
5 *	0.3577	0.05	9.62	32.86	58.78	-16.25	QP
6 *	0.3577	0.05	9.62	25.07	48.78	-14.04	Average
7	0.5979	0.06	9.62	29.42	56.00	-16.90	QP
8	0.5979	0.06	9.62	19.68	46.00	-16.64	Average
9	2.4476	0.11	9.64	22.63	56.00	-23.62	QP
10	2.4476	0.11	9.64	11.89	46.00	-24.36	Average
11	29.2157	0.38	10.45	17.87	60.00	-31.30	QP
12	29.2157	0.38	10.45	12.12	50.00	-27.05	Average



7.2 Duty Cycle

Test Requirement KDB 789033 D02 II B 1
 Test Method: KDB 789033 II B 1


7.2.1 E.U.T. Operation

Operating Environment:
 Temperature: 28.0 °C Humidity: 41.7 % RH Atmospheric Pressure: 1010 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	25	TX mode (5.8G SDR_1.4MHz)_Keep the EUT in transmitting mode
Final test	27	TX mode (5.8G SDR_3MHz)_Keep the EUT in transmitting mode
Final test	29	TX mode (5.8G SDR_5MHz)_Keep the EUT in transmitting mode
Final test	31	TX mode (5.8G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	33	TX mode (5.8G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	35	TX mode (5.8G SDR_40MHz)_Keep the EUT in transmitting mode
Final test	37	TX mode (5.1G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	39	TX mode (5.1G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	41	TX mode (5.1G SDR_40MHz)_Keep the EUT in transmitting mode

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.3 99% Bandwidth

Test Requirement N/A
 Test Method: KDB 789033 II D


7.3.1 E.U.T. Operation

Operating Environment:
 Temperature: 28.0 °C Humidity: 41.7 % RH Atmospheric Pressure: 1010 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	25	TX mode (5.8G SDR_1.4MHz)_Keep the EUT in transmitting mode
Final test	27	TX mode (5.8G SDR_3MHz)_Keep the EUT in transmitting mode
Final test	29	TX mode (5.8G SDR_5MHz)_Keep the EUT in transmitting mode
Final test	31	TX mode (5.8G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	33	TX mode (5.8G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	35	TX mode (5.8G SDR_40MHz)_Keep the EUT in transmitting mode
Final test	37	TX mode (5.1G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	39	TX mode (5.1G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	41	TX mode (5.1G SDR_40MHz)_Keep the EUT in transmitting mode

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.4 26dB Emission bandwidth

Test Requirement 47 CFR Part 15, Subpart E 15.407 (a)

Test Method: KDB 789033 D02 II C 1

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 28.0 °C Humidity: 41.7 % RH Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	37	TX mode (5.1G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	39	TX mode (5.1G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	41	TX mode (5.1G SDR_40MHz)_Keep the EUT in transmitting mode

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Center EEC Laboratory.

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.5 Minimum 6 dB bandwidth (5.725-5.85 GHz band)

Test Requirement 47 CFR Part 15, Subpart E 15.407 (e)

Test Method: KDB 789033 D02 II C 2

Limit:

Frequency band(MHz)	Limit
5725-5850	≥500 kHz

7.5.1 E.U.T. Operation

Operating Environment:


Temperature: 28.0 °C Humidity: 41.7 % RH Atmospheric Pressure: 1010 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	25	TX mode (5.8G SDR_1.4MHz)_Keep the EUT in transmitting mode
Final test	27	TX mode (5.8G SDR_3MHz)_Keep the EUT in transmitting mode
Final test	29	TX mode (5.8G SDR_5MHz)_Keep the EUT in transmitting mode
Final test	31	TX mode (5.8G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	33	TX mode (5.8G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	35	TX mode (5.8G SDR_40MHz)_Keep the EUT in transmitting mode



7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.6 Maximum Conducted output power

Test Requirement 47 CFR Part 15, Subpart E 15.407 (a)

Test Method: KDB 789033 D02 II E

Limit:

Frequency band(MHz)	Limit
5150-5250	≤1W(30dBm) for master device
	≤250mW(24dBm) for client device
5150-5250 (EIRP)	≤125mW(21dBm) for outdoor access point device
5250-5350	≤250mW(24dBm) for client device or 11dBm+10logB*
5470-5725	≤250mW(24dBm) for client device or 11dBm+10logB*
5725-5850	≤1W(30dBm)
Remark:	* Where B is the 26dB emission bandwidth in MHz. The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 28.0 °C Humidity: 41.7 % RH Atmospheric Pressure: 1010 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	25	TX mode (5.8G SDR_1.4MHz)_Keep the EUT in transmitting mode
Final test	27	TX mode (5.8G SDR_3MHz)_Keep the EUT in transmitting mode
Final test	29	TX mode (5.8G SDR_5MHz)_Keep the EUT in transmitting mode
Final test	31	TX mode (5.8G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	33	TX mode (5.8G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	35	TX mode (5.8G SDR_40MHz)_Keep the EUT in transmitting mode
Final test	37	TX mode (5.1G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	39	TX mode (5.1G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	41	TX mode (5.1G SDR_40MHz)_Keep the EUT in transmitting mode




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编:518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



7.7 Peak Power spectrum density

Test Requirement 47 CFR Part 15, Subpart E 15.407 (a)

Test Method: KDB 789033 D02 II F

Limit:

Frequency band(MHz)	Limit
5150-5250	≤17dBm in 1MHz for master device
	≤11dBm in 1MHz for client device
5250-5350	≤11dBm in 1MHz for client device
5470-5725	≤11dBm in 1MHz for client device
5725-5850	≤30dBm in 500 kHz
Remark:	The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 28.0 °C Humidity: 41.7 % RH Atmospheric Pressure: 1010 mbar

7.7.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Final test	25	TX mode (5.8G SDR_1.4MHz)_Keep the EUT in transmitting mode
Final test	27	TX mode (5.8G SDR_3MHz)_Keep the EUT in transmitting mode
Final test	29	TX mode (5.8G SDR_5MHz)_Keep the EUT in transmitting mode
Final test	31	TX mode (5.8G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	33	TX mode (5.8G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	35	TX mode (5.8G SDR_40MHz)_Keep the EUT in transmitting mode
Final test	37	TX mode (5.1G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	39	TX mode (5.1G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	41	TX mode (5.1G SDR_40MHz)_Keep the EUT in transmitting mode



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.8 Radiated Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: KDB 789033 D02 II G

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 23.2 °C Humidity: 50.5 % RH Atmospheric Pressure: 1015 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	25	TX mode (5.8G SDR_1.4MHz)_Keep the EUT in transmitting mode
Pre-scan	26	TX mode (5.8G SDR_1.4MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	27	TX mode (5.8G SDR_3MHz)_Keep the EUT in transmitting mode
Pre-scan	28	TX mode (5.8G SDR_3MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	29	TX mode (5.8G SDR_5MHz)_Keep the EUT in transmitting mode
Pre-scan	30	TX mode (5.8G SDR_5MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	31	TX mode (5.8G SDR_10MHz)_Keep the EUT in transmitting mode
Pre-scan	32	TX mode (5.8G SDR_10MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	33	TX mode (5.8G SDR_20MHz)_Keep the EUT in transmitting mode
Pre-scan	34	TX mode (5.8G SDR_20MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	35	TX mode (5.8G SDR_40MHz)_Keep the EUT in transmitting mode




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Pre-scan	36	TX mode (5.8G SDR_40MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	37	TX mode (5.1G SDR_10MHz)_Keep the EUT in transmitting mode
Pre-scan	38	TX mode (5.1G SDR_10MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	39	TX mode (5.1G SDR_20MHz)_Keep the EUT in transmitting mode
Pre-scan	40	TX mode (5.1G SDR_20MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	41	TX mode (5.1G SDR_40MHz)_Keep the EUT in transmitting mode
Final test	42	TX mode (5.1G SDR_40MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter

7.8.3 Test Setup Diagram



Below 30MHz

30MHz-1GHz



7.8.4 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- 2. For emission below 1GHz, through the pre-scan found the worst case is the lowest channel of 802.11a. Only the worst case is recorded in the report.
- 3. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.



Test Mode: 42; Polarity: Horizontal; Modulation: OFDM; Channel: Middle



Condition: 10m HORIZONTAL


Job No. : 01013AT

Test Mode: 42

	Read Freq	Ant Level	Ant Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	31.843	29.34	16.26	0.67	32.46	13.81	29.50	-15.69	QP
2	72.084	29.69	14.77	0.76	32.40	12.82	29.50	-16.68	QP
3	199.286	33.39	14.93	1.19	32.40	17.11	33.00	-15.89	QP
4 pp	243.377	43.23	15.97	1.30	32.40	28.10	35.60	-7.50	QP
5	297.224	38.57	17.60	1.43	32.40	25.20	35.60	-10.40	QP
6	501.179	29.97	21.97	1.86	32.50	21.30	35.60	-14.30	QP



Test Mode: 42; Polarity: Vertical; Modulation: OFDM; Channel: Middle



Condition: 10m VERTICAL

Job No. : 01013AT

Test Mode: 42

	Read Freq	Ant Level	Ant Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 pp	41.567	35.54	17.19	0.60	32.43	20.90	29.50	-8.60	QP
2	108.267	39.47	14.39	0.86	32.40	22.32	33.00	-10.68	QP
3	177.509	34.78	16.02	1.11	32.40	19.51	33.00	-13.49	QP
4	243.377	36.48	15.97	1.30	32.40	21.35	35.60	-14.25	QP
5	359.186	34.36	18.98	1.53	32.40	22.47	35.60	-13.13	QP
6	497.677	32.12	21.91	1.85	32.50	23.38	35.60	-12.22	QP



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230400101305

Page: 34 of 354

The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L₃: Level @ 3m distance. Unit: uV/m;

L₁₀: Level @ 10m distance. Unit: uV/m;

D₃: 3m distance. Unit: m

D₁₀: 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 3m (uV/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
31.843	13.81	4.90	16.34	24.27	40	-15.73	H
72.084	12.82	4.38	14.58	23.28	40	-16.72	H
199.286	17.11	7.17	23.90	27.57	43.5	-15.93	H
243.377	28.10	25.41	84.70	38.56	46	-7.44	H
297.224	25.20	18.20	60.66	35.66	46	-10.34	H
501.179	21.30	11.61	38.71	31.76	46	-14.24	H
41.567	20.90	11.09	36.97	31.36	40	-8.64	V
108.267	22.32	13.06	43.54	32.78	43.5	-10.72	V
177.509	19.51	9.45	31.50	29.97	43.5	-13.53	V
243.377	21.35	11.68	38.94	31.81	46	-14.19	V
359.186	22.47	13.29	44.30	32.93	46	-13.07	V
497.677	23.38	14.76	49.19	33.84	46	-12.16	V



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.9 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: KDB 789033 D02 II G

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.9.1 E.U.T. Operation

Operating Environment:



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


Temperature: 23.9 °C Humidity: 59.5 % RH Atmospheric Pressure: 1010 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	25	TX mode (5.8G SDR_1.4MHz)_Keep the EUT in transmitting mode
Final test	26	TX mode (5.8G SDR_1.4MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	27	TX mode (5.8G SDR_3MHz)_Keep the EUT in transmitting mode
Final test	28	TX mode (5.8G SDR_3MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	29	TX mode (5.8G SDR_5MHz)_Keep the EUT in transmitting mode
Final test	30	TX mode (5.8G SDR_5MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	31	TX mode (5.8G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	32	TX mode (5.8G SDR_10MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	33	TX mode (5.8G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	34	TX mode (5.8G SDR_20MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	35	TX mode (5.8G SDR_40MHz)_Keep the EUT in transmitting mode
Final test	36	TX mode (5.8G SDR_40MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	37	TX mode (5.1G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	38	TX mode (5.1G SDR_10MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	39	TX mode (5.1G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	40	TX mode (5.1G SDR_20MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	41	TX mode (5.1G SDR_40MHz)_Keep the EUT in transmitting mode
Final test	42	TX mode (5.1G SDR_40MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter



7.9.3 Test Setup Diagram




7.9.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor



Test Mode: 26; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5728.5 Band edge
 : SDR 1.4M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 5646.37	7.84	34.50	35.02	56.56	63.88	68.20	-4.32 Peak
2	5715.00	7.91	34.50	35.02	64.61	72.00	109.40	-37.40 peak
3	5725.00	7.92	34.50	35.02	74.43	81.83	122.20	-40.37 peak
4	5728.50	7.92	34.50	35.02	113.94	121.34	-----	----- peak



Test Mode: 26; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5728.5 Band edge
 : SDR 1.4M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 5647.89	7.84	34.50	35.02	55.95	63.27	68.20	-4.93 Peak
2	5715.00	7.91	34.50	35.02	55.48	62.87	109.40	-46.53 peak
3	5725.00	7.92	34.50	35.02	61.00	68.40	122.20	-53.80 peak
4	5728.50	7.92	34.50	35.02	102.32	109.72	-----	----- peak



Test Mode: 26; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5846.12 Band edge
 : SDR 1.4M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5846.12	8.02	34.69	35.03	112.15	119.83	-----	-----
2	5850.00	8.03	34.70	35.03	66.29	73.99	122.20	-48.21
3	5860.00	8.04	34.72	35.03	61.49	69.22	109.40	-40.18
4 q	5940.29	8.11	34.88	35.04	56.79	64.74	68.20	-3.46



Test Mode: 26; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5846.12 Band edge
 : SDR 1.4M

		Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5846.12	8.02	34.69	35.03	102.76	110.44	-----	-----	peak
2	5850.00	8.03	34.70	35.03	57.99	65.69	122.20	-56.51	peak
3	5860.00	8.04	34.72	35.03	55.71	63.44	109.40	-45.96	peak
4 q	5944.47	8.11	34.89	35.04	56.57	64.53	68.20	-3.67	peak



Test Mode: 28; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5727.5 Band edge
 : SDR 3M

		Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	q 5645.81	7.84	34.50	35.02	56.93	64.25	68.20	-3.95	peak
2	5715.00	7.91	34.50	35.02	62.15	69.54	109.40	-39.86	peak
3	5725.00	7.92	34.50	35.02	90.71	98.11	122.20	-24.09	peak
4	5727.50	7.92	34.50	35.02	112.95	120.35	-----	-----	peak



Test Mode: 28; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5727.5 Band edge
 : SDR 3M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 5643.18	7.84	34.50	35.02	55.56	62.88	68.20	-5.32 peak
2	5715.00	7.91	34.50	35.02	55.54	62.93	109.40	-46.47 peak
3	5725.00	7.92	34.50	35.02	77.49	84.89	122.20	-37.31 peak
4	5727.50	7.92	34.50	35.02	101.16	108.56	-----	----- peak



Test Mode: 28; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5847.2 Band edge
 : SDR 3M

		Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5847.20	8.03	34.69	35.03	112.91	120.60	-----	-----	peak
2	5850.00	8.03	34.70	35.03	76.97	84.67	122.20	-37.53	peak
3	5860.00	8.04	34.72	35.03	62.39	70.12	109.40	-39.28	peak
4 q	5946.47	8.11	34.89	35.04	56.43	64.39	68.20	-3.81	peak



Test Mode: 28; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5847.2 Band edge
 : SDR 3M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5847.20	8.03	34.69	35.03	102.94	110.63	-----	----- peak
2	5850.00	8.03	34.70	35.03	68.27	75.97	122.20	-46.23 peak
3	5860.00	8.04	34.72	35.03	56.81	64.54	109.40	-44.86 peak
4 q	5925.29	8.09	34.85	35.04	57.12	65.02	68.20	-3.18 peak



Test Mode: 30; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5732.5 Band edge
 : SDR 5M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 5649.69	7.85	34.50	35.02	56.83	64.16	68.20	-4.04 Peak
2	5715.00	7.91	34.50	35.02	71.23	78.62	109.40	-30.78 peak
3	5725.00	7.92	34.50	35.02	90.58	97.98	122.20	-24.22 peak
4	5732.50	7.92	34.50	35.02	115.32	122.72	-----	----- peak



Test Mode: 30; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5732.5 Band edge
 : SDR 5M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 5642.91	7.84	34.50	35.02	56.05	63.37	68.20	-4.83
2	5715.00	7.91	34.50	35.02	61.54	68.93	109.40	-40.47
3	5725.00	7.92	34.50	35.02	79.89	87.29	122.20	-34.91
4	5732.50	7.92	34.50	35.02	104.46	111.86	-----	-----



Test Mode: 30; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5842.5 Band edge
 : SDR 5M

		Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5842.50	8.02	34.69	35.03	117.01	124.69	-----	-----	peak
2	5850.00	8.03	34.70	35.03	88.83	96.53	122.20	-25.67	peak
3	5860.00	8.04	34.72	35.03	73.24	80.97	109.40	-28.43	peak
4 q	5937.29	8.11	34.87	35.04	56.63	64.57	68.20	-3.63	peak



Test Mode: 30; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5842.5 Band edge
 : SDR 5M

		Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5842.50	8.02	34.69	35.03	105.64	113.32	-----	-----	peak
2	5850.00	8.03	34.70	35.03	79.34	87.04	122.20	-35.16	peak
3	5860.00	8.04	34.72	35.03	62.71	70.44	109.40	-38.96	peak
4 q	5954.67	8.12	34.91	35.04	57.18	65.17	68.20	-3.03	peak



Test Mode: 32; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5730.5 Band edge
 : SDR 10M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	5649.69	7.85	34.50	35.02	57.34	64.67	68.20	-3.53 Peak
2	5715.00	7.91	34.50	35.02	87.77	95.16	109.40	-14.24 peak
3	5725.00	7.92	34.50	35.02	103.07	110.47	122.20	-11.73 peak
4	5730.50	7.92	34.50	35.02	113.42	120.82	-----	----- peak



Test Mode: 32; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5730.5 Band edge
 : SDR 10M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	5640.83	7.84	34.50	35.02	56.41	63.73	68.20	-4.47 Peak
2	5715.00	7.91	34.50	35.02	78.25	85.64	109.40	-23.76 peak
3	5725.00	7.92	34.50	35.02	92.14	99.54	122.20	-22.66 peak
4	5730.50	7.92	34.50	35.02	102.26	109.66	-----	----- peak



Test Mode: 32; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5844.5 Band edge
 : SDR 10M

		Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5844.50	8.02	34.69	35.03	115.02	122.70	-----	-----	peak
2	5850.00	8.03	34.70	35.03	102.02	109.72	122.20	-12.48	peak
3	5860.00	8.04	34.72	35.03	83.64	91.37	109.40	-18.03	peak
4 q	5932.79	8.10	34.87	35.04	56.82	64.75	68.20	-3.45	peak



Test Mode: 32; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5844.5 Band edge
 : SDR 10M

		Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5844.50	8.02	34.69	35.03	104.12	111.80	-----	-----	peak
2	5850.00	8.03	34.70	35.03	91.04	98.74	122.20	-23.46	peak
3	5860.00	8.04	34.72	35.03	74.61	82.34	109.40	-27.06	peak
4 q	5950.48	8.12	34.90	35.04	56.39	64.37	68.20	-3.83	peak



Test Mode: 34; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5735.5 Band edge
 : SDR 20M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 5646.50	7.84	34.50	35.02	59.49	66.81	68.20	-1.39
2	5715.00	7.91	34.50	35.02	92.56	99.95	109.40	-9.45
3	5725.00	7.92	34.50	35.02	97.08	104.48	122.20	-17.72
4	5735.50	7.93	34.50	35.03	111.40	118.80	-----	-----



Test Mode: 34; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5735.5 Band edge
 : SDR 20M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 5645.53	7.84	34.50	35.02	55.95	63.27	68.20	-4.93
2	5715.00	7.91	34.50	35.02	81.13	88.52	109.40	-20.88
3	5725.00	7.92	34.50	35.02	85.64	93.04	122.20	-29.16
4	5735.50	7.93	34.50	35.03	100.35	107.75	-----	-----



Test Mode: 34; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5839.5 Band edge
 : SDR 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5839.50	8.02	34.68	35.03	112.20	119.87	-----	-----	peak
2	5850.00	8.03	34.70	35.03	93.67	101.37	122.20	-20.83	peak
3	5860.00	8.04	34.72	35.03	87.68	95.41	109.40	-13.99	peak
4 q	5928.29	8.10	34.86	35.04	58.50	66.42	68.20	-1.78	Peak



Test Mode: 34; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5839.5 Band edge
 : SDR 20M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5839.50	8.02	34.68	35.03	100.51	108.18	-----	-----
2	5850.00	8.03	34.70	35.03	85.59	93.29	122.20	-28.91
3	5860.00	8.04	34.72	35.03	77.68	85.41	109.40	-23.99
4 q	5925.79	8.10	34.85	35.04	57.53	65.44	68.20	-2.76



Test Mode: 36; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5745.5 Band edge
 : SDR 40M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 5648.30	7.85	34.50	35.02	59.70	67.03	68.20	-1.17 peak
2	5715.00	7.91	34.50	35.02	83.43	90.82	109.40	-18.58 peak
3	5725.00	7.92	34.50	35.02	88.73	96.13	122.20	-26.07 peak
4	5745.50	7.93	34.50	35.03	106.62	114.02	-----	----- peak



Test Mode: 36; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5745.5 Band edge
 : SDR 40M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	5648.44	7.85	34.50	35.02	56.32	63.65	68.20	-4.55 peak
2	5715.00	7.91	34.50	35.02	70.68	78.07	109.40	-31.33 peak
3	5725.00	7.92	34.50	35.02	75.12	82.52	122.20	-39.68 peak
4	5745.50	7.93	34.50	35.03	95.96	103.36	-----	----- peak



Test Mode: 36; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5829.5 Band edge
 : SDR 40M

		Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5829.50	8.01	34.66	35.03	105.22	112.86	-----	-----	peak
2	5850.00	8.03	34.70	35.03	82.87	90.57	122.20	-31.63	peak
3	5860.00	8.04	34.72	35.03	81.73	89.46	109.40	-19.94	peak
4 q	5926.96	8.10	34.85	35.04	59.33	67.24	68.20	-0.96	peak



Test Mode: 36; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5829.5 Band edge
 : SDR 40M

		Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5829.50	8.01	34.66	35.03	94.77	102.41	-----	-----	peak
2	5850.00	8.03	34.70	35.03	70.74	78.44	122.20	-43.76	peak
3	5860.00	8.04	34.72	35.03	71.13	78.86	109.40	-30.54	peak
4 q	5932.62	8.10	34.87	35.04	57.78	65.71	68.20	-2.49	peak



Test Mode: 38; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5157 Band edge
 : SDR 10M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5125.32	7.34	34.05	34.99	55.75	62.15	74.00	-11.85 peak
2	5149.98	7.36	34.00	34.99	54.71	61.08	74.00	-12.92 peak
3 q	5157.00	7.37	34.00	34.99	83.93	90.31	68.20	22.11 peak



Test Mode: 38; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5157 Band edge
 : SDR 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5115.77	7.33	34.07	34.99	43.81	50.22	54.00	-3.78	Average
2 q	5149.98	7.36	34.00	34.99	43.98	50.35	54.00	-3.65	Average
3	5157.00	7.37	34.00	34.99	74.52	80.90	-----	-----	Average



Test Mode: 38; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5157 Band edge
 : SDR 10M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5147.96	7.36	34.00	34.99	57.44	63.81	74.00	-10.19 Peak
2	5149.98	7.36	34.00	34.99	58.19	64.56	74.00	-9.44 Peak
3 q	5157.00	7.37	34.00	34.99	92.86	99.24	68.20	31.04 Peak



Test Mode: 38; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5157 Band edge
 : SDR 10M

		Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5149.36	7.36	34.00	34.99	46.08	52.45	54.00	-1.55	Average
2 q	5149.98	7.36	34.00	34.99	46.30	52.67	54.00	-1.33	Average
3	5157.00	7.37	34.00	34.99	82.85	89.23	-----	-----	Average



Test Mode: 38; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5245 Band edge
 : SDR 10M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 5245.00	7.46	34.00	35.00	94.30	100.76	68.20	32.56 peak
2	5350.02	7.56	34.30	35.00	54.33	61.19	74.00	-12.81 peak
3	5359.57	7.57	34.34	35.00	54.77	61.68	74.00	-12.32 peak



Test Mode: 38; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5245 Band edge
 : SDR 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5245.00	7.46	34.00	35.00	84.99	91.45	-----	-----	Average
2	5350.02	7.56	34.30	35.00	43.27	50.13	54.00	-3.87	Average
3 q	5355.04	7.57	34.32	35.00	43.52	50.41	54.00	-3.59	Average



Test Mode: 38; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5245 Band edge
 : SDR 10M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 5245.00	7.46	34.00	35.00	105.08	111.54	68.20	43.34 Peak
2	5350.02	7.56	34.30	35.00	55.44	62.30	74.00	-11.70 Peak
3	5356.88	7.57	34.33	35.00	55.60	62.50	74.00	-11.50 Peak



Test Mode: 38; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5245 Band edge
 : SDR 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5245.00	7.46	34.00	35.00	95.10	101.56	-----	-----	Average
2	5350.02	7.56	34.30	35.00	43.75	50.61	54.00	-3.39	Average
3 q	5355.04	7.57	34.32	35.00	43.90	50.79	54.00	-3.21	Average



Test Mode: 40; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5161 Band edge
 : SDR 20M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5111.80	7.33	34.08	34.99	55.73	62.15	74.00	-11.85 peak
2	5149.98	7.36	34.00	34.99	55.30	61.67	74.00	-12.33 peak
3 q	5161.00	7.38	34.00	34.99	84.61	91.00	68.20	22.80 peak



Test Mode: 40; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5161 Band edge
 : SDR 20M

		Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	q 5111.60	7.33	34.08	34.99	43.60	50.02	54.00	-3.98	Average
2	5149.98	7.36	34.00	34.99	43.55	49.92	54.00	-4.08	Average
3	5161.00	7.38	34.00	34.99	73.27	79.66	-----	-----	Average



Test Mode: 40; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5161 Band edge
 : SDR 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5148.96	7.36	34.00	34.99	56.32	62.69	74.00	-11.31	Peak
2	5149.98	7.36	34.00	34.99	56.03	62.40	74.00	-11.60	Peak
3 q	5161.00	7.38	34.00	34.99	88.38	94.77	68.20	26.57	Peak



Test Mode: 40; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5161 Band edge
 : SDR 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5149.16	7.36	34.00	34.99	44.35	50.72	54.00	-3.28	Average
2 q	5149.98	7.36	34.00	34.99	44.84	51.21	54.00	-2.79	Average
3	5161.00	7.38	34.00	34.99	77.39	83.78	-----	-----	Average



Test Mode: 40; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5240 Band edge
 : SDR 20M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 5240.00	7.45	34.00	35.00	93.00	99.45	68.20	31.25 peak
2	5350.02	7.56	34.30	35.00	53.74	60.60	74.00	-13.40 peak
3	5356.88	7.57	34.33	35.00	55.12	62.02	74.00	-11.98 peak



Test Mode: 40; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5240 Band edge
 : SDR 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5240.00	7.45	34.00	35.00	82.23	88.68	-----	-----	Average
2	5350.02	7.56	34.30	35.00	43.07	49.93	54.00	-4.07	Average
3 q	5351.21	7.56	34.30	35.00	43.40	50.26	54.00	-3.74	Average



Test Mode: 40; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5240 Band edge
 : SDR 20M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 5240.00	7.45	34.00	35.00	102.69	109.14	68.20	40.94 Peak
2	5350.02	7.56	34.30	35.00	55.51	62.37	74.00	-11.63 Peak
3	5357.45	7.57	34.33	35.00	55.65	62.55	74.00	-11.45 Peak



Test Mode: 40; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5240 Band edge
 : SDR 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5240.00	7.45	34.00	35.00	91.42	97.87	-----	-----	Average
2	5350.02	7.56	34.30	35.00	43.37	50.23	54.00	-3.77	Average
3 q	5355.46	7.57	34.32	35.00	44.07	50.96	54.00	-3.04	Average



Test Mode: 42; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5170 Band edge
 : SDR 40M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5105.65	7.32	34.09	34.99	56.07	62.49	74.00	-11.51 peak
2	5149.98	7.36	34.00	34.99	55.41	61.78	74.00	-12.22 peak
3 q	5170.00	7.38	34.00	34.99	82.66	89.05	68.20	20.85 peak



Test Mode: 42; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5170 Band edge
 : SDR 40M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 5100.10	7.31	34.10	34.99	43.58	50.00	54.00	-4.00 Average
2	5149.98	7.36	34.00	34.99	43.48	49.85	54.00	-4.15 Average
3	5170.00	7.38	34.00	34.99	71.46	77.85	-----	----- Average



Test Mode: 42; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5170 Band edge
 : SDR 40M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5148.46	7.36	34.00	34.99	57.10	63.47	74.00	-10.53 Peak
2	5149.98	7.36	34.00	34.99	60.91	67.28	74.00	-6.72 Peak
3 q	5170.00	7.38	34.00	34.99	91.43	97.82	68.20	29.62 Peak



Test Mode: 42; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5170 Band edge
 : SDR 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5148.76	7.36	34.00	34.99	45.93	52.30	54.00	-1.70	Average
2 q	5149.98	7.36	34.00	34.99	46.72	53.09	54.00	-0.91	Average
3	5170.00	7.38	34.00	34.99	79.72	86.11	-----	-----	Average



Test Mode: 42; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5230 Band edge
 : SDR 40M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 5230.00	7.44	34.00	34.99	91.24	97.69	68.20	29.49 peak
2	5350.02	7.56	34.30	35.00	55.16	62.02	74.00	-11.98 peak
3	5353.99	7.57	34.32	35.00	54.94	61.83	74.00	-12.17 peak



Test Mode: 42; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5230 Band edge
 : SDR 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5230.00	7.44	34.00	34.99	79.43	85.88	-----	-----	Average
2	5350.02	7.56	34.30	35.00	43.21	50.07	54.00	-3.93	Average
3 q	5360.00	7.57	34.34	35.00	43.41	50.32	54.00	-3.68	Average



Test Mode: 42; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5230 Band edge
 : SDR 40M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 5230.00	7.44	34.00	34.99	100.07	106.52	68.20	38.32 Peak
2	5350.02	7.56	34.30	35.00	54.82	61.68	74.00	-12.32 Peak
3	5354.64	7.57	34.32	35.00	55.93	62.82	74.00	-11.18 Peak



Test Mode: 42; Polarity: Vertical; Modulation: OFDM; Channel: High



Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5230 Band edge
 : SDR 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5230.00	7.44	34.00	34.99	88.57	95.02	-----	-----	Average
2	5350.02	7.56	34.30	35.00	43.57	50.43	54.00	-3.57	Average
3 q	5359.51	7.57	34.34	35.00	43.96	50.87	54.00	-3.13	Average



7.10 Radiated Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)
 Test Method: KDB 789033 D02 II G
 Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1GHz	500	3

*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.10.1 E.U.T. Operation

Operating Environment:

Temperature: 21.6 °C Humidity: 51.3 % RH Atmospheric Pressure: 1010 mbar

7.10.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Pre-scan	25	TX mode (5.8G SDR_1.4MHz)_Keep the EUT in transmitting mode
Final test	26	TX mode (5.8G SDR_1.4MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	27	TX mode (5.8G SDR_3MHz)_Keep the EUT in transmitting mode
Pre-scan	28	TX mode (5.8G SDR_3MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	29	TX mode (5.8G SDR_5MHz)_Keep the EUT in transmitting mode
Pre-scan	30	TX mode (5.8G SDR_5MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	31	TX mode (5.8G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	32	TX mode (5.8G SDR_10MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	33	TX mode (5.8G SDR_20MHz)_Keep the EUT in transmitting mode
Pre-scan	34	TX mode (5.8G SDR_20MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	35	TX mode (5.8G SDR_40MHz)_Keep the EUT in transmitting mode
Pre-scan	36	TX mode (5.8G SDR_40MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	37	TX mode (5.1G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	38	TX mode (5.1G SDR_10MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	39	TX mode (5.1G SDR_20MHz)_Keep the EUT in transmitting mode
Pre-scan	40	TX mode (5.1G SDR_20MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter
Pre-scan	41	TX mode (5.1G SDR_40MHz)_Keep the EUT in transmitting mode
Pre-scan	42	TX mode (5.1G SDR_40MHz) + Charging_Keep the EUT in transmitting mode and charged by adapter



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.10.3 Test Setup Diagram



7.10.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- 2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
- 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
- 5. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.



Test Mode: 26; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5728.5 TX RSE
 Note : SDR 1.4M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1242.068	2.87	24.48	37.58	47.61	37.38	68.20	-30.82	peak
2	1687.347	3.47	26.77	36.43	46.56	40.37	74.00	-33.63	peak
3	4495.125	6.77	33.50	34.67	43.74	49.34	68.20	-18.86	peak
4	8638.399	9.81	36.60	35.71	40.43	51.13	68.20	-17.07	peak
5	11457.000	11.55	37.96	36.27	39.06	52.30	74.00	-21.70	peak
6	q17485.500	14.20	43.59	37.44	32.48	52.83	68.20	-15.37	peak



Test Mode: 26; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5728.5 TX RSE
 Note : SDR 1.4M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1217.190	2.83	24.43	37.66	48.95	38.55	74.00	-35.45	peak
2	1597.181	3.37	26.47	36.64	47.22	40.42	74.00	-33.58	peak
3	4230.396	6.51	33.52	34.49	44.19	49.73	74.00	-24.27	peak
4	8866.062	10.01	36.70	35.58	39.65	50.78	68.20	-17.42	peak
5	11457.000	11.55	37.96	36.27	37.97	51.21	74.00	-22.79	peak
6	q17485.500	14.20	43.59	37.44	32.79	53.14	68.20	-15.06	peak



Test Mode: 26; Polarity: Horizontal; Modulation: OFDM; Channel: Middle




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5786.5 TX RSE
 Note : SDR 1.4M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1203.199	2.81	24.41	37.70	47.73	37.25	74.00	-36.75	peak
2	1653.550	3.43	26.71	36.51	46.07	39.70	68.20	-28.50	peak
3	4430.628	6.71	33.50	34.63	43.66	49.24	68.20	-18.96	peak
4	8840.473	9.99	36.70	35.59	39.10	50.20	68.20	-18.00	peak
5	11573.000	11.63	38.00	36.34	38.01	51.30	74.00	-22.70	peak
6	q17359.500	14.19	43.46	37.45	32.87	53.07	68.20	-15.13	peak



Test Mode: 26; Polarity: Vertical; Modulation: OFDM; Channel: Middle




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5786.5 TX RSE
 Note : SDR 1.4M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1260.149	2.90	24.54	37.53	49.00	38.91	68.20	-29.29	peak
2	1687.347	3.47	26.77	36.43	46.63	40.44	74.00	-33.56	peak
3	4230.396	6.51	33.52	34.49	43.64	49.18	74.00	-24.82	peak
4	8814.957	9.97	36.70	35.60	40.44	51.51	68.20	-16.69	peak
5	11575.000	11.63	38.00	36.34	38.31	51.60	74.00	-22.40	peak
6	q17362.500	14.19	43.46	37.45	32.89	53.09	68.20	-15.11	peak



Test Mode: 26; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5846.12 TX RSE
 Note : SDR 1.4M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1199.726	2.80	24.40	37.71	48.52	38.01	74.00	-35.99	peak
2	1587.975	3.35	26.36	36.66	46.26	39.31	74.00	-34.69	peak
3	4098.010	6.38	33.00	34.40	44.07	49.05	74.00	-24.95	peak
4	8764.146	9.92	36.70	35.63	40.41	51.40	68.20	-16.80	peak
5	11692.240	11.70	38.00	36.41	39.15	52.44	74.00	-21.56	peak
6	q17538.360	14.21	43.64	37.43	32.57	52.99	68.20	-15.21	peak



Test Mode: 26; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5846.12 TX RSE
 Note : SDR 1.4M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1199.726	2.80	24.40	37.71	47.65	37.14	74.00	-36.86	peak
2	1601.804	3.37	26.51	36.63	46.76	40.01	74.00	-33.99	peak
3	4050.904	6.33	32.90	34.37	44.25	49.11	74.00	-24.89	peak
4	8738.852	9.90	36.70	35.65	39.87	50.82	68.20	-17.38	peak
5	11692.240	11.70	38.00	36.41	39.26	52.55	74.00	-21.45	peak
6	q17538.360	14.21	43.64	37.43	32.07	52.49	68.20	-15.71	peak



Test Mode: 32; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5730.5 TX RSE
 Note : SDR 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1206.682	2.81	24.41	37.69	47.36	36.89	74.00	-37.11	peak
2	1687.347	3.47	26.77	36.43	45.60	39.41	74.00	-34.59	peak
3	4354.454	6.63	33.59	34.58	43.99	49.63	74.00	-24.37	peak
4	8638.399	9.81	36.60	35.71	40.14	50.84	68.20	-17.36	peak
5	11461.000	11.56	37.96	36.27	38.81	52.06	74.00	-21.94	peak
6	17191.500	14.18	43.28	37.46	33.00	53.00	68.20	-15.20	peak



Test Mode: 32; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5730.5 TX RSE
 Note : SDR 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1199.726	2.80	24.40	37.71	47.97	37.46	74.00	-36.54	peak
2	1597.181	3.37	26.47	36.64	47.30	40.50	74.00	-33.50	peak
3	4430.628	6.71	33.50	34.63	43.99	49.57	68.20	-18.63	peak
4	8688.480	9.86	36.68	35.68	40.30	51.16	68.20	-17.04	peak
5	11461.000	11.56	37.96	36.27	39.05	52.30	74.00	-21.70	peak
6	q17191.500	14.18	43.28	37.46	32.98	52.98	68.20	-15.22	peak



Test Mode: 32; Polarity: Horizontal; Modulation: OFDM; Channel: Middle




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5787.5 TX RSE
 Note : SDR 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1199.726	2.80	24.40	37.71	49.39	38.88	74.00	-35.12	peak
2	1692.231	3.48	26.78	36.42	45.88	39.72	74.00	-34.28	peak
3	4304.400	6.59	33.60	34.54	43.46	49.11	74.00	-24.89	peak
4	8891.725	10.04	36.70	35.56	40.21	51.39	68.20	-16.81	peak
5	11575.000	11.63	38.00	36.34	38.54	51.83	74.00	-22.17	peak
6	q17362.500	14.19	43.46	37.45	32.23	52.43	68.20	-15.77	peak



Test Mode: 32; Polarity: Vertical; Modulation: OFDM; Channel: Middle




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5787.5 TX RSE
 Note : SDR 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1199.726	2.80	24.40	37.71	51.40	40.89	74.00	-33.11	peak
2	1601.804	3.37	26.51	36.63	51.61	44.86	74.00	-29.14	peak
3	4316.859	6.60	33.60	34.55	43.11	48.76	74.00	-25.24	peak
4	8840.473	9.99	36.70	35.59	39.68	50.78	68.20	-17.42	peak
5	11575.000	11.63	38.00	36.34	38.20	51.49	74.00	-22.51	peak
6	q17362.500	14.19	43.46	37.45	32.86	53.06	68.20	-15.14	peak



Test Mode: 32; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT/01014AT
 Mode : 5844.5 TX RSE
 Note : SDR 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1199.726	2.80	24.40	37.71	48.36	37.85	74.00	-36.15	peak
2	1587.975	3.35	26.36	36.66	47.48	40.53	74.00	-33.47	peak
3	4329.354	6.61	33.60	34.56	43.18	48.83	74.00	-25.17	peak
4	7898.049	9.13	36.20	36.07	41.64	50.90	68.20	-17.30	peak
5	11689.000	11.70	38.00	36.40	39.04	52.34	74.00	-21.66	peak
6	q17533.500	14.21	43.63	37.43	32.50	52.91	68.20	-15.29	peak



Test Mode: 32; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT/01014AT
 Mode : 5844.5 TX RSE
 Note : SDR 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1199.726	2.80	24.40	37.71	51.67	41.16	74.00	-32.84	peak
2	1620.431	3.39	26.58	36.58	46.85	40.24	74.00	-33.76	peak
3	4405.090	6.68	33.50	34.61	44.01	49.58	68.20	-18.62	peak
4	8789.516	9.95	36.70	35.62	39.89	50.92	68.20	-17.28	peak
5	11689.000	11.70	38.00	36.40	38.69	51.99	74.00	-22.01	peak
6	q17533.500	14.21	43.63	37.43	32.52	52.93	68.20	-15.27	peak



Test Mode: 38; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT
 Mode : 5157 TX RSE
 Note : SDR 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1199.726	2.80	24.40	37.71	48.27	37.76	74.00	-36.24	peak
2	1677.621	3.46	26.76	36.45	45.53	39.30	74.00	-34.70	peak
3	4304.400	6.59	33.60	34.54	43.25	48.90	74.00	-25.10	peak
4	8613.468	9.79	36.60	35.72	40.85	51.52	68.20	-16.68	peak
5	10314.000	10.78	37.41	35.72	39.31	51.78	68.20	-16.42	peak
6	15471.000	13.52	40.87	37.44	36.57	53.52	74.00	-20.48	peak



Test Mode: 38; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT
 Mode : 5157 TX RSE
 Note : SDR 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1245.663	2.87	24.49	37.57	46.87	36.66	68.20	-31.54	peak
2	1677.621	3.46	26.76	36.45	44.89	38.66	74.00	-35.34	peak
3	4417.841	6.69	33.50	34.62	43.08	48.65	68.20	-19.55	peak
4	8789.516	9.95	36.70	35.62	40.08	51.11	68.20	-17.09	peak
5	10314.000	10.78	37.41	35.72	39.31	51.78	68.20	-16.42	peak
6	15471.000	13.52	40.87	37.44	35.30	52.25	74.00	-21.75	peak



Test Mode: 38; Polarity: Horizontal; Modulation: OFDM; Channel: Middle




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT
 Mode : 5201 TX RSE
 Note : SDR 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1231.345	2.85	24.46	37.62	47.46	37.15	74.00	-36.85	peak
2	1583.392	3.35	26.30	36.67	47.00	39.98	74.00	-34.02	peak
3	4230.396	6.51	33.52	34.49	43.63	49.17	74.00	-24.83	peak
4	8764.146	9.92	36.70	35.63	39.48	50.47	68.20	-17.73	peak
5	10402.000	10.84	37.50	35.75	38.50	51.09	68.20	-17.11	peak
6	15603.000	13.69	41.00	37.49	36.32	53.52	74.00	-20.48	peak



Test Mode: 38; Polarity: Vertical; Modulation: OFDM; Channel: Middle




Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT
 Mode : 5201 TX RSE
 Note : SDR 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1196.264	2.79	24.39	37.73	49.04	38.49	74.00	-35.51	peak
2	1692.231	3.48	26.78	36.42	46.19	40.03	74.00	-33.97	peak
3	4329.354	6.61	33.60	34.56	43.09	48.74	74.00	-25.26	peak
4	8638.399	9.81	36.60	35.71	39.17	49.87	68.20	-18.33	peak
5	10400.000	10.84	37.50	35.75	38.95	51.54	68.20	-16.66	peak
6	15600.000	13.68	41.00	37.49	35.43	52.62	74.00	-21.38	peak



Test Mode: 38; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 01013AT
 Mode : 5245 TX RSE
 Note : SDR 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1199.726	2.80	24.40	37.71	47.96	37.45	74.00	-36.55	peak
2	1692.231	3.48	26.78	36.42	46.01	39.85	74.00	-34.15	peak
3	4405.090	6.68	33.50	34.61	44.13	49.70	68.20	-18.50	peak
4	8814.957	9.97	36.70	35.60	39.97	51.04	68.20	-17.16	peak
5	10490.000	10.91	37.50	35.79	39.42	52.04	68.20	-16.16	peak
6	15735.000	13.84	41.17	37.55	35.70	53.16	74.00	-20.84	peak



Test Mode: 38; Polarity: Vertical; Modulation: OFDM; Channel: High



Site : chamber
 Condition: 3m VERTICAL
 Job No : 01013AT
 Mode : 5245 TX RSE
 Note : SDR 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1297.103	2.95	24.69	37.42	47.21	37.43	68.20	-30.77	peak
2	1601.804	3.37	26.51	36.63	49.38	42.63	74.00	-31.37	peak
3	4495.125	6.77	33.50	34.67	43.55	49.15	68.20	-19.05	peak
4	q 8738.852	9.90	36.70	35.65	39.97	50.92	68.20	-17.28	peak
5	10490.000	10.91	37.50	35.79	38.30	50.92	68.20	-17.28	peak
6	15735.000	13.84	41.17	37.55	36.08	53.54	74.00	-20.46	peak



7.11 Frequency Stability

Test Requirement 47 CFR Part 15, Subpart E 15.407 (g)

Test Method: ANSI C63.10 (2013) Section 6.8

7.11.1 E.U.T. Operation


Operating Environment:

Temperature: 28.0 °C Humidity: 41.7 % RH Atmospheric Pressure: 1010 mbar

7.11.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	25	TX mode (5.8G SDR_1.4MHz)_Keep the EUT in transmitting mode
Final test	27	TX mode (5.8G SDR_3MHz)_Keep the EUT in transmitting mode
Final test	29	TX mode (5.8G SDR_5MHz)_Keep the EUT in transmitting mode
Final test	31	TX mode (5.8G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	33	TX mode (5.8G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	35	TX mode (5.8G SDR_40MHz)_Keep the EUT in transmitting mode
Final test	37	TX mode (5.1G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	39	TX mode (5.1G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	41	TX mode (5.1G SDR_40MHz)_Keep the EUT in transmitting mode

7.11.3 Test Setup Diagram



7.11.4 Measurement Procedure and Data

Please Refer to Appendix for Details



8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2304001013AT

9 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for SZCR2304001013AT



10 Appendix

5.1G SDR SISO Mode: ANT0&ANT1&ANT2&ANT3

1. Duty Cycle


1.1 Ant0


1.1.1 Test Result


Ant0							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
10M	SISO	5157	100.000	100.000	100.00	0.00	0.00
		5201	100.000	100.000	100.00	0.00	0.00
		5245	100.000	100.000	100.00	0.00	0.00
20M	SISO	5161	100.000	100.000	100.00	0.00	0.00
		5201	100.000	100.000	100.00	0.00	0.00
		5240	100.000	100.000	100.00	0.00	0.00
40M	SISO	5170	100.000	100.000	100.00	0.00	0.00
		5200	100.000	100.000	100.00	0.00	0.00
		5230	100.000	100.000	100.00	0.00	0.00





1.1.2 Test Graph











2. Bandwidth


2.1 OBW


2.1.1 Test Result


Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)	Verdict
				Result	
10M	SISO	5157	0	9.105	Pass
		5201	0	9.131	Pass
		5245	0	9.119	Pass
20M	SISO	5161	0	17.977	Pass
		5201	0	18.018	Pass
		5240	0	18.026	Pass
40M	SISO	5170	0	35.943	Pass
		5200	0	35.963	Pass
		5230	0	35.947	Pass





2.1.2 Test Graph












2.2 26dB BW


2.2.1 Test Result


Mode	TX Type	Frequency (MHz)	ANT	26dB Bandwidth (MHz)	Verdict
				Result	
10M	SISO	5157	0	10.339	Pass
		5201	0	10.814	Pass
		5245	0	10.496	Pass
20M	SISO	5161	0	19.196	Pass
		5201	0	19.346	Pass
		5240	0	19.066	Pass
40M	SISO	5170	0	38.053	Pass
		5200	0	37.779	Pass
		5230	0	37.841	Pass





2.2.2 Test Graph











3. Maximum Conducted Output Power

3.1 Power

3.1.1 Test Result

Mode	TX Type	Frequency (MHz)	EIRP (dBm)					Verdict
			ANT0	ANT1	ANT2	ANT3	Limit	
10M	SISO	5157	10.78	10.39	10.16	9.88	<=21	Pass
		5201	20.77	20.52	20.49	20.16	<=21	Pass
		5245	20.17	20.29	20.25	20.80	<=21	Pass
20M	SISO	5161	10.61	10.36	10.59	9.39	<=21	Pass
		5201	20.69	20.43	20.39	20.07	<=21	Pass
		5240	20.95	20.64	20.6	20.65	<=21	Pass
40M	SISO	5170	11.51	11.67	10.99	10.23	<=21	Pass
		5200	20.74	20.42	20.39	20.05	<=21	Pass
		5230	20.81	20.47	20.42	20.48	<=21	Pass

4. Maximum Power Spectral Density

4.1 PSD

4.1.1 Test Result

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm/MHz)					Verdict
			ANT0	ANT1	ANT2	ANT3	Limit	
10M	SISO	5157	-0.42	-0.80	-0.04	-0.37	<=17	Pass
		5201	9.59	9.32	10.33	10.03	<=17	Pass
		5245	9.06	9.17	10.30	10.69	<=17	Pass
20M	SISO	5161	-3.49	-3.65	-2.38	-3.72	<=17	Pass
		5201	6.73	6.30	7.28	6.88	<=17	Pass
		5240	6.83	6.51	7.52	7.55	<=17	Pass
40M	SISO	5170	-5.48	-5.45	-5.05	-5.85	<=17	Pass
		5200	3.80	3.41	4.43	3.99	<=17	Pass
		5230	3.89	3.44	4.34	4.33	<=17	Pass





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


4.1.2 Test Graph











Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

