

**CFR 47 FCC PART 15 SUBPART C**

**TEST REPORT**

*For*

**DJI Mini 5 Pro**

**MODEL NUMBER: MT5MFND**

**REPORT NUMBER: 4791691684-1-RF-3**

**ISSUE DATE: December 31, 2024**

**FCC ID: SS3-MT5MFND25**

*Prepared for*

**SZ DJI TECHNOLOGY CO., LTD.**

**Lobby of T2, DJI Sky City, No 53 Xianyuan Road, Xili Community, Xili Street,  
Nanshan District, Shenzhen, China**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch**

**Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan,  
Guangdong, China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.

## Revision History

| Rev. | Issue Date           | Revisions     | Revised By |
|------|----------------------|---------------|------------|
| V0   | December 31,<br>2024 | Initial Issue |            |

### Summary of Test Results

| Test Item                                 | Clause  | Limit/Requirement                             | Result |
|---|---|---|--------|
| Antenna Requirement                       | N/A   | FCC Part 15.203/15.247 (c)                    | Pass   |
| AC Power Line Conducted Emission          | ANSI C63.10-2013, Clause 6.2                  | FCC Part 15.207                               | Pass   |
| Conducted Output Power                    | ANSI C63.10-2013, Clause 11.9.2.3.1           | FCC Part 15.247 (b)(3)                        | Pass   |
| 6dB Bandwidth and 99% Occupied Bandwidth  | ANSI C63.10-2013, Clause 11.8.1               | FCC Part 15.247 (a)(2)                        | Pass   |
| Power Spectral Density                    | ANSI C63.10-2013, Clause 11.10.5              | FCC Part 15.247 (e)                           | Pass   |
| Conducted Band edge and spurious emission | ANSI C63.10-2013, Clause 11.11                | FCC Part 15.247(d)                            | Pass   |
| Radiated Band edge and Spurious Emission  | ANSI C63.10-2013, Clause 11.12 & Clause 11.13 | FCC Part 15.247 (d)<br>FCC Part 15.205/15.209 | Pass   |
| Duty Cycle                                | ANSI C63.10-2013, Clause 11.6                 | None; for reporting purposes only.            | Pass   |

\*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

\*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C> when <Simple Acceptance> decision rule is applied.

## CONTENTS

|  |            |
|--|------------|
| <b>1. ATTESTATION OF TEST RESULTS.....</b>                 | <b>6</b>   |
| <b>2. TEST METHODOLOGY.....</b>                            | <b>7</b>   |
| <b>3. FACILITIES AND ACCREDITATION.....</b>                | <b>7</b>   |
| <b>4. CALIBRATION AND UNCERTAINTY .....</b>                | <b>8</b>   |
| 4.1. <i>MEASURING INSTRUMENT CALIBRATION .....</i>         | <i>8</i>   |
| 4.2. <i>MEASUREMENT UNCERTAINTY.....</i>                   | <i>8</i>   |
| <b>5. EQUIPMENT UNDER TEST .....</b>                       | <b>9</b>   |
| 5.1. <i>DESCRIPTION OF EUT .....</i>                       | <i>9</i>   |
| 5.2. <i>MAXIMUM POWER.....</i>                             | <i>9</i>   |
| 5.3. <i>CHANNEL LIST .....</i>                             | <i>10</i>  |
| 5.4. <i>TEST CHANNEL CONFIGURATION.....</i>                | <i>12</i>  |
| 5.5. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>    | <i>12</i>  |
| 5.6. <i>WORST-CASE CONFIGURATIONS.....</i>                 | <i>13</i>  |
| 5.7. <i>DESCRIPTION OF AVAILABLE ANTENNAS .....</i>        | <i>14</i>  |
| 5.8. <i>SUPPORT UNITS FOR SYSTEM TEST .....</i>            | <i>15</i>  |
| <b>6. MEASURING EQUIPMENT AND SOFTWARE USED.....</b>       | <b>16</b>  |
| <b>7. ANTENNA PORT TEST RESULTS .....</b>                  | <b>19</b>  |
| 7.1. <i>CONDUCTED OUTPUT POWER .....</i>                   | <i>19</i>  |
| 7.2. <i>6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....</i>  | <i>20</i>  |
| 7.3. <i>POWER SPECTRAL DENSITY .....</i>                   | <i>22</i>  |
| 7.4. <i>CONDUCTED BAND EDGE AND SPURIOUS EMISSION.....</i> | <i>23</i>  |
| 7.5. <i>DUTY CYCLE .....</i>                               | <i>25</i>  |
| <b>8. RADIATED TEST RESULTS.....</b>                       | <b>26</b>  |
| 8.1. <i>RESTRICTED BANDEDGE .....</i>                      | <i>34</i>  |
| 8.2. <i>SPURIOUS EMISSIONS(1 GHZ~3 GHZ) .....</i>          | <i>65</i>  |
| 8.3. <i>SPURIOUS EMISSIONS(3 GHZ~18 GHZ) .....</i>         | <i>71</i>  |
| 8.4. <i>SPURIOUS EMISSIONS(9 KHZ~30 MHZ) .....</i>         | <i>95</i>  |
| 8.5. <i>SPURIOUS EMISSIONS(18 GHZ~26 GHZ) .....</i>        | <i>98</i>  |
| 8.6. <i>SPURIOUS EMISSIONS(30 MHZ~1 GHZ).....</i>          | <i>100</i> |
| <b>9. ANTENNA REQUIREMENT .....</b>                        | <b>102</b> |
| <b>10. AC POWER LINE CONDUCTED EMISSION .....</b>          | <b>103</b> |

|            |  |            |
|------------|--|------------|
| <b>11.</b> | <b>TEST DATA.....</b>                                  | <b>106</b> |
| 11.1.      | <i>APPENDIX A: DTS BANDWIDTH.....</i>                  | <i>106</i> |
| 11.1.1.    | Test Result.....                                       | 106        |
| 11.1.2.    | Test Graphs .....                                      | 107        |
| 11.2.      | <i>APPENDIX B: OCCUPIED CHANNEL BANDWIDTH.....</i>     | <i>120</i> |
| 11.2.1.    | Test Result.....                                       | 120        |
| 11.2.2.    | Test Graphs .....                                      | 121        |
| 11.3.      | <i>APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER.....</i> | <i>134</i> |
| 11.3.1.    | Test Result.....                                       | 134        |
| 11.4.      | <i>APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY.....</i> | <i>137</i> |
| 11.4.1.    | Test Result.....                                       | 137        |
| 11.4.2.    | Test Graphs .....                                      | 139        |
| 11.5.      | <i>APPENDIX E: BAND EDGE MEASUREMENTS.....</i>         | <i>152</i> |
| 11.5.1.    | Test Result.....                                       | 152        |
| 11.5.2.    | Test Graphs .....                                      | 153        |
| 11.6.      | <i>APPENDIX F: CONDUCTED SPURIOUS EMISSION .....</i>   | <i>163</i> |
| 11.6.1.    | Test Result.....                                       | 163        |
| 11.6.2.    | Test Graphs .....                                      | 165        |
| 11.7.      | <i>APPENDIX G: DUTY CYCLE.....</i>                     | <i>203</i> |
| 11.7.1.    | Test Result.....                                       | 203        |
| 11.7.2.    | Test Graphs .....                                      | 204        |

## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

Company Name: SZ DJI TECHNOLOGY CO., LTD.  
Address: Lobby of T2, DJI Sky City, No 53 Xianyuan Road, Xili Community, Xili Street, Nanshan District, Shenzhen, China

### Manufacturer Information

Company Name: SZ DJI TECHNOLOGY CO., LTD.  
Address: Lobby of T2, DJI Sky City, No 53 Xianyuan Road, Xili Community, Xili Street, Nanshan District, Shenzhen, China

### EUT Information

EUT Name: DJI Mini 5 Pro  
Model: MT5MFND  
Brand: DJI  
Sample Received Date: September 21, 2024  
Sample Status: Nromal  
Sample ID: 7771135  
Date of Tested: October 11, 2024 to December 31, 2024

| APPLICABLE STANDARDS         |              |
|------------------------------|--------------|
| STANDARD                     | TEST RESULTS |
| CFR 47 FCC PART 15 SUBPART C | Pass         |

Prepared By:



Fanny Huang  
Engineer Project Associate

Checked By:



Kebo Zhang  
Senior Project Engineer

Approved By:



Stephen Guo  
Operations Manager

## 2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C, KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, KDB 662911 D01 Multiple Transmitter Output v02r01, CFR 47 FCC Part 2, ANSI C63.10-2013.

## 3. FACILITIES AND ACCREDITATION

|                           |   |
|---------------------------|---|
| Accreditation Certificate | <p><b>A2LA (Certificate No.: 4102.01)</b><br/>         UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b><br/>         UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>ISED (Company No.: 21320)</b><br/>         UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p><b>VCCI (Registration No.: G-20192, C-20153, T-20155 and R-20202)</b><br/>         UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793.<br/>         Facility Name:<br/>         Chamber D, the VCCI registration No. is G-20192 and R-20202<br/>         Shielding Room B, the VCCI registration No. is C-20153 and T-20155</p> |
|---------------------------|---|

**Note 1:**

All tests measurement facilities use to collect the original measurement data of this report are located at Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China. And the new lab address after relocation is Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China.

**Note 2:**

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

**Note 3:**

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Test Item   | Uncertainty               |
|---|---------------------------|
| Conduction emission   | 3.62 dB                   |
| Radiated Emission<br>(Included Fundamental Emission) (9 kHz ~ 30 MHz)   | 2.2 dB                    |
| Radiated Emission<br>(Included Fundamental Emission) (30 MHz ~ 1 GHz)   | 4.00 dB                   |
| Radiated Emission<br>(Included Fundamental Emission) (1 GHz to 26 GHz)  | 5.78 dB (1 GHz ~ 18 GHz)  |
|   | 5.23 dB (18 GHz ~ 26 GHz) |
| Duty Cycle  | ±0.028%                   |
| DTS and 99% Occupied Bandwidth  | ±0.0196%                  |
| Maximum Conducted Output Power  | ±0.686 dB                 |
| Maximum Power Spectral Density Level  | ±0.743 dB                 |
| Conducted Band-edge Compliance  | ±1.328 dB                 |
| Conducted Unwanted Emissions In Non-restricted<br>Frequency Bands   | ±0.746 dB (9 kHz ~ 1 GHz) |
|   | ±1.328dB (1 GHz ~ 26 GHz) |
| Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. |                           |

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

|          |                |
|----------|----------------|
| EUT Name | DJI Mini 5 Pro |
| Model    | MT5MFND        |

|                     |  |
|---------------------|--|
| Radio Technology    | SRD 2.4G   |
| Operation Frequency | 2.4G 10 MHz Bandwidth (2407.5 MHz ~ 2467.5 MHz)<br>2.4G 20 MHz Bandwidth (2412.5 MHz ~ 2462.5 MHz)<br>2.4G 40 MHz Bandwidth (2422.5 MHz ~ 2452.5 MHz)<br>2.4G 60 MHz Bandwidth (2432.5 MHz ~ 2442.5 MHz) |
| Modulation          | OFDM (QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)  |
| Battery             | DC 7V/7.16V  |
| Power Supply        | DC 5V/9V/12V   |

Note: All power supply modes have been pre-scanned, only the worst data was recorded in the report.

### 5.2. MAXIMUM POWER

| SRD 2.4G    | Frequency (MHz)         | Channel Number | Maximum Conducted Average Output Power (dBm) |
|-------------|-------------------------|----------------|--|
| 10 MHz Mode | 2407.5 MHz ~ 2467.5 MHz | 1-61[61]       | 29.03  |
| 20 MHz Mode | 2412.5 MHz ~ 2462.5 MHz | 1-51[51]       | 29.07  |
| 40 MHz Mode | 2422.5 MHz ~ 2452.5 MHz | 1-31[31]       | 27.54  |
| 60 MHz Mode | 2432.5 MHz ~ 2442.5 MHz | 1-11[11]       | 27.51  |

### 5.3. CHANNEL LIST

| 2.4G 10 MHz Bandwidth (2407.5 MHz ~ 2467.5 MHz) |                 |         |                 |         |                 |         |                 |
|---|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel   | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 1   | 2407.5          | 17      | 2423.5          | 33      | 2439.5          | 49      | 2455.5          |
| 2   | 2408.5          | 18      | 2424.5          | 34      | 2440.5          | 50      | 2456.5          |
| 3   | 2409.5          | 19      | 2425.5          | 35      | 2441.5          | 51      | 2457.5          |
| 4   | 2410.5          | 20      | 2426.5          | 36      | 2442.5          | 52      | 2458.5          |
| 5   | 2411.5          | 21      | 2427.5          | 37      | 2443.5          | 53      | 2459.5          |
| 6   | 2412.5          | 22      | 2428.5          | 38      | 2444.5          | 54      | 2460.5          |
| 7   | 2413.5          | 23      | 2429.5          | 39      | 2445.5          | 55      | 2461.5          |
| 8   | 2414.5          | 24      | 2430.5          | 40      | 2446.5          | 56      | 2462.5          |
| 9   | 2415.5          | 25      | 2431.5          | 41      | 2447.5          | 57      | 2463.5          |
| 10  | 2416.5          | 26      | 2432.5          | 42      | 2448.5          | 58      | 2464.5          |
| 11  | 2417.5          | 27      | 2433.5          | 43      | 2449.5          | 59      | 2465.5          |
| 12  | 2418.5          | 28      | 2434.5          | 44      | 2450.5          | 60      | 2466.5          |
| 13  | 2419.5          | 29      | 2435.5          | 45      | 2451.5          | 61      | 2467.5          |
| 14  | 2420.5          | 30      | 2436.5          | 46      | 2452.5          | /       | /               |
| 15  | 2421.5          | 31      | 2437.5          | 47      | 2453.5          | /       | /               |
| 16  | 2422.5          | 32      | 2438.5          | 48      | 2454.5          | /       | /               |

| 2.4G 20 MHz Bandwidth (2412.5 MHz ~ 2462.5 MHz) |                 |         |                 |         |                 |         |                 |
|---|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel   | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 1   | 2412.5          | 14      | 2425.5          | 27      | 2438.5          | 40      | 2451.5          |
| 2   | 2413.5          | 15      | 2426.5          | 28      | 2439.5          | 41      | 2452.5          |
| 3   | 2414.5          | 16      | 2427.5          | 29      | 2440.5          | 42      | 2453.5          |
| 4   | 2415.5          | 17      | 2428.5          | 30      | 2441.5          | 43      | 2454.5          |
| 5   | 2416.5          | 18      | 2429.5          | 31      | 2442.5          | 44      | 2455.5          |
| 6   | 2417.5          | 19      | 2430.5          | 32      | 2443.5          | 45      | 2456.5          |
| 7   | 2418.5          | 20      | 2431.5          | 33      | 2444.5          | 46      | 2457.5          |
| 8   | 2419.5          | 21      | 2432.5          | 34      | 2445.5          | 47      | 2458.5          |
| 9   | 2420.5          | 22      | 2433.5          | 35      | 2446.5          | 48      | 2459.5          |
| 10  | 2421.5          | 23      | 2434.5          | 36      | 2447.5          | 49      | 2460.5          |
| 11  | 2422.5          | 24      | 2435.5          | 37      | 2448.5          | 50      | 2461.5          |
| 12  | 2423.5          | 25      | 2436.5          | 38      | 2449.5          | 51      | 2462.5          |
| 13  | 2424.5          | 26      | 2437.5          | 39      | 2450.5          | /       | /               |

| 2.4G 40 MHz Bandwidth (2422.5 MHz ~ 2452.5 MHz) |                 |         |                 |         |                 |         |                 |
|---|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel   | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 1   | 2422.5          | 9       | 2430.5          | 17      | 2438.5          | 25      | 2446.5          |
| 2   | 2423.5          | 10      | 2431.5          | 18      | 2439.5          | 26      | 2447.5          |
| 3   | 2424.5          | 11      | 2432.5          | 19      | 2440.5          | 27      | 2448.5          |
| 4   | 2425.5          | 12      | 2433.5          | 20      | 2441.5          | 28      | 2449.5          |
| 5   | 2426.5          | 13      | 2434.5          | 21      | 2442.5          | 29      | 2450.5          |
| 6   | 2427.5          | 14      | 2435.5          | 22      | 2443.5          | 30      | 2451.5          |
| 7   | 2428.5          | 15      | 2436.5          | 23      | 2444.5          | 31      | 2452.5          |
| 8   | 2429.5          | 16      | 2437.5          | 24      | 2445.5          | /       | /               |

| 2.4 GHz 60 MHz Bandwidth (2432.5 MHz ~ 2442.5 MHz) |                 |         |                 |         |                 |         |                 |
|--|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel  | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 1  | 2432.5          | 4       | 2435.5          | 7       | 2438.5          | 10      | 2441.5          |
| 2  | 2433.5          | 5       | 2436.5          | 8       | 2439.5          | 11      | 2442.5          |
| 3  | 2434.5          | 6       | 2437.5          | 9       | 2440.5          | /       | /               |

#### 5.4. TEST CHANNEL CONFIGURATION

| SRD 2.4G    | Test Channel Number   | Frequency  |
|-------------|---|--|
| 10 MHz Mode | CH 1(Low Channel),<br>CH 3,<br>CH 4<br>CH 31(MID Channel),<br>CH 61(High Channel)   | 2407.5 MHz,<br>2409.5 MHz,<br>2410.5 MHz,<br>2437.5 MHz,<br>2467.5 MHz |
| 20 MHz Mode | CH 1(Low Channel),<br>CH3,<br>CH 26(MID Channel),<br>CH 51(High Channel)            | 2412.5 MHz,<br>2414.5 MHz,<br>2437.5 MHz,<br>2462.5 MHz                |
| 40 MHz Mode | CH 1(Low Channel),<br>CH 11,<br>CH 14<br>CH 16(MID Channel),<br>CH 31(High Channel) | 2422.5 MHz,<br>2432.5 MHz,<br>2435.5 MHz,<br>2437.5 MHz,<br>2452.5 MHz |
| 60 MHz Mode | CH 1(Low Channel),<br>CH 2,<br>CH 4,<br>CH 6(MID Channel),<br>CH 11(High Channel)   | 2432.5 MHz,<br>2433.5 MHz,<br>2435.5 MHz,<br>2437.5 MHz,<br>2442.5 MHz |

#### 5.5. THE WORSE CASE POWER SETTING PARAMETER

| The Worse Case Power Setting Parameter under 2400 ~ 2483.5 MHz Band |                         |                                  |
|---|-------------------------|----------------------------------|
| Test Software   |                         | DjiSdrConsole-v2.2.8             |
| Modulation Mode   | Transmit Antenna Number | Test Software setting value      |
|   |                         | NCB: 10 MHz/20 MHz/40 MHz/60 MHz |
|   |                         | All Channels                     |
| All   | All                     | Default                          |

## 5.6. WORST-CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst case Data Rates declared by the customer:

- SRD 2.4G-10 MHz Mode/QPSK
- SRD 2.4G-20 MHz Mode/QPSK
- SRD 2.4G-40 MHz Mode/QPSK
- SRD 2.4G-60 MHz Mode/QPSK

The EUT has 4 separate antennas which correspond to 4 separate antenna ports, core ANT 0, core ANT 1, core ANT 2, core ANT 3 correspond to antenna 0, antenna 1, antenna 2, antenna 3 respectively. Only Antenna 1 & Antenna 3 support WIFI. Only Antenna 3 support BLE. Antenna 0,1,2,3 support SRD. For SRD, the EUT support 1TX4RX and 2TX4RX mode. 1TX4RX and 2TX4RX have the same power setting, so only the worst data for 2TX4RX mode were recorded in the report. For 2T4R mode, antenna 0 and antenna 1/ antenna 0 and antenna 3/ antenna 1 and antenna 2/ antenna 2 and antenna 3 used as transmit antennas and all the 4 antennas can use as receive antennas, all the transmit combination(ANT0 and ANT1 / ANT0 and ANT3 / ANT1 and ANT2 / ANT2 and ANT3) had been tested, but only the worst data for ANT0 and ANT1 were recorded in the report.

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

Radiated emissions tests were performed with the MIMO modes. These were found to be the worst modulation scheme with regards to emissions after preliminary investigations and, as this mode emits the highest conducted output power level, it was deemed to be the worst case.

## 5.7. DESCRIPTION OF AVAILABLE ANTENNAS

| Antenna | Frequency (MHz) | Antenna Type   | Maximum Antenna Gain (dBi) |
|---------|-----------------|----------------|----------------------------|
| 0       | 2400 ~ 2483.5   | Dipole Antenna | 1                          |
| 1       | 2400 ~ 2483.5   | Dipole Antenna | 1                          |
| 2       | 2400 ~ 2483.5   | Dipole Antenna | 1                          |
| 3       | 2400 ~ 2483.5   | Dipole Antenna | 1                          |

MIMO output power port and MIMO PSD port summing were performed in accordance with KDB 662911 D01. For the STBC mode results the Directional Gain was calculated in accordance with the following method.

For output power measurements:

Directional gain =  $G_{ANT} + \text{Array Gain} = 1 \text{ dBi}$

$G_{ANT}$ : equal to the gain of the antenna having the highest gain

Array Gain = 0 dB (i.e., no array gain) for  $N_{ANT} \leq 4$

For power spectral density (PSD) measurements:

Directional gain =  $G_{ANT} + \text{Array Gain} = 1 \text{ dBi}$

$G_{ANT}$ : equal to the gain of the antenna having the highest gain

Array Gain = 0 dB (i.e., no array gain) for  $N_{ANT} \leq 4$

| Test Mode   | Transmit and Receive Mode                    | Description   |
|-------------|--|---|
| 10 MHz Mode | <input checked="" type="checkbox"/> 2TX, 4RX | ANT 0,1 / 0,3 / 1,2 / 2,3 can be used as transmitting antenna.<br>ANT 0,1, 2, 3 can be used as receiving antenna. |
| 20 MHz Mode | <input checked="" type="checkbox"/> 2TX, 4RX | ANT 0,1 / 0,3 / 1,2 / 2,3 can be used as transmitting antenna.<br>ANT 0,1, 2, 3 can be used as receiving antenna. |
| 40 MHz Mode | <input checked="" type="checkbox"/> 2TX, 4RX | ANT 0,1 / 0,3 / 1,2 / 2,3 can be used as transmitting antenna.<br>ANT 0,1, 2, 3 can be used as receiving antenna. |
| 60 MHz Mode | <input checked="" type="checkbox"/> 2TX, 4RX | ANT 0,1 / 0,3 / 1,2 / 2,3 can be used as transmitting antenna.<br>ANT 0,1, 2, 3 can be used as receiving antenna. |

Note: 1. The value of the antenna gain was declared by customer.

2. Only WIFI 2.4G & SRD 5G, BLE & SRD 5G, WIFI 5G & SRD 2.4G can transmit simultaneously.

## 5.8. SUPPORT UNITS FOR SYSTEM TEST

### SUPPORT EQUIPMENT

| Item | Equipment   | Brand Name | Model Name | Remarks   |
|------|-------------|------------|------------|---|
| 1    | Laptop      | Lenovo     | E42-80     | /   |
| 2    | USB Adapter | MI         | MDY-08-EH  | Input: AC 100 ~ 240 V, 50/60 Hz, 0.5 A<br>Output: DC 5 V, 2.5 A/9 V, 2 A/12V, 1.5 A |

### I/O CABLES

| Cable No | Port | Connector Type | Cable Type | Cable Length(m) | Remarks |
|----------|------|----------------|------------|-----------------|---------|
| 1        | USB  | Type C         | Unshielded | 1.0             | /       |

### ACCESSORIES


| Item | Accessory                        | Brand Name | Model Name       | Description  |
|------|----------------------------------|------------|------------------|--|
| 1    | Lithium-ion Rechargeable Battery | DJI        | BWXNN5-4680-7.16 | Max Charge Voltage: 8.6V<br>Normal Voltage: 7.16V  |
| 2    | Lithium-ion Rechargeable Battery | DJI        | BWXNN5-2788-7.0  | Max Charge Voltage: 8.6V<br>Normal Voltage: 7V   |
| 3    | Adapter Power                    | DJI        | PD-65CN          | Input: AC 100 ~ 240 V, 50/60 Hz, 2.0 A<br>Output: DC 5 V, 5 A/9 V, 5 A/12V, 5 A/15V, 4.3A/20V, 3.25A |

### TEST SETUP

The EUT can work in engineering mode with a software through a laptop.

### SETUP DIAGRAM FOR TESTS

For AC Power Line Conducted Emission Test:



For Others Test:



## 6. MEASURING EQUIPMENT AND SOFTWARE USED

| R&S TS 8997 Test System             |                 |            |                         |              |              |              |
|-------------------------------------|-----------------|------------|-------------------------|--------------|--------------|--------------|
| Equipment                           | Manufacturer    | Model No.  | Serial No.              | Upper Cal.   | Last Cal.    | Due. Date    |
| Power sensor, Power Meter           | R&S             | OSP120     | 100921                  | /            | Mar.25,2024  | Mar.24,2025  |
| Vector Signal Generator             | R&S             | SMBV100A   | 261637                  | Oct.12, 2023 | Sep 28, 2024 | Sep 27, 2025 |
| Signal Generator                    | R&S             | SMB100A    | 178553                  | Oct.12, 2023 | Sep 28, 2024 | Sep 27, 2025 |
| Signal Analyzer                     | R&S             | FSV40      | 101118                  | Oct.12, 2023 | Sep 28, 2024 | Sep 27, 2025 |
| Software                            |                 |            |                         |              |              |              |
| Description                         | Manufacturer    |            | Name                    |              | Version      |              |
| For R&S TS 8997 Test System         | Rohde & Schwarz |            | EMC 32                  |              | 10.60.10     |              |
| Tonsend RF Test System              |                 |            |                         |              |              |              |
| Equipment                           | Manufacturer    | Model No.  | Serial No.              | Upper Cal.   | Last Cal.    | Due. Date    |
| Wideband Radio Communication Tester | R&S             | CMW500     | 1201.0002K50-161167-ij  | /            | Sep 28, 2024 | Sep 27, 2025 |
| Wireless Connectivity Tester        | R&S             | CMW270     | 1201.0002K75-1025       | Sep.25, 2023 | Sep 13, 2024 | Sep 12, 2025 |
| PXA Signal Analyzer                 | Keysight        | N9030A     | MY55410512              | Oct.12, 2023 | Sep 28, 2024 | Sep 27, 2025 |
| MXG Vector Signal Generator         | Keysight        | N5182B     | MY56200284              | Oct.12, 2023 | Sep 28, 2024 | Sep 27, 2025 |
| MXG Vector Signal Generator         | Keysight        | N5172B     | MY56200301              | Oct.12, 2023 | Sep 28, 2024 | Sep 27, 2025 |
| DC power supply                     | Keysight        | E3642A     | MY55159130              | Oct.12, 2023 | Sep 28, 2024 | Sep 27, 2025 |
| Temperature & Humidity Chamber      | SANMOOD         | SG-80-CC-2 | 2088                    | Oct.12, 2023 | Sep 28, 2024 | Sep 27, 2025 |
| Attenuator                          | Aglient         | 8495B      | 2814a12853              | Oct.12, 2023 | Sep 28, 2024 | Sep 27, 2025 |
| RF Control Unit                     | Tonscend        | JS0806-2   | 23B80620666             | /            | Mar.25,2024  | Mar.24,2025  |
| Software                            |                 |            |                         |              |              |              |
| Description                         | Manufacturer    |            | Name                    |              | Version      |              |
| Tonsend SRD Test System             | Tonsend         |            | JS1120-3 RF Test System |              | V3.2.22      |              |

| Conducted Emissions                   |              |           |              |              |              |              |
|---------------------------------------|--------------|-----------|--------------|--------------|--------------|--------------|
| Equipment                             | Manufacturer | Model No. | Serial No.   | Upper Cal.   | Last Cal.    | Due Date     |
| EMI Test Receiver                     | R&S          | ESR3      | 101961       | Oct.13, 2023 | Sep 28, 2024 | Sep 27, 2025 |
| Two-Line V-Network                    | R&S          | ENV216    | 101983       | Oct.13, 2023 | Sep 28, 2024 | Sep 27, 2025 |
| Artificial Mains Networks             | Schwarzbeck  | NSLK 8126 | 8126465      | Oct.13, 2023 | Sep 28, 2024 | Sep 27, 2025 |
| Software                              |              |           |              |              |              |              |
| Description                           |              |           | Manufacturer |              | Name         | Version      |
| Test Software for Conducted Emissions |              |           | Farad        |              | EZ-EMC       | Ver. UL-3A1  |

| Radiated Emissions          |              |                             |               |              |               |               |
|-----------------------------|--------------|-----------------------------|---------------|--------------|---------------|---------------|
| Equipment                   | Manufacturer | Model No.                   | Serial No.    | Upper Cal.   | Last Cal.     | Due Date      |
| MXE EMI Receiver            | KESIGHT      | N9038A                      | MY56400036    | Oct.12, 2023 | Sep 28, 2024  | Sep 27, 2025  |
| Hybrid Log Periodic Antenna | TDK          | HLP-3003C                   | 130960        | Aug.02, 2021 | June 28, 2024 | June 27, 2027 |
| Preamplifier                | HP           | 8447D                       | 2944A09099    | Oct.12, 2023 | Sep 28, 2024  | Sep 27, 2025  |
| EMI Measurement Receiver    | R&S          | ESR26                       | 101377        | Oct.12, 2023 | Sep 28, 2024  | Sep 27, 2025  |
| Horn Antenna                | TDK          | HRN-0118                    | 130939        | /            | Apr.29, 2022  | Apr.28, 2025  |
| Preamplifier                | TDK          | PA-02-0118                  | TRS-305-00067 | Oct.12, 2023 | Sep 28, 2024  | Sep 27, 2025  |
| Horn Antenna                | Schwarzbeck  | BBHA9170                    | 697           | /            | June 30, 2024 | June 29, 2027 |
| Preamplifier                | TDK          | PA-02-2                     | TRS-307-00003 | Oct.12, 2023 | Sep 28, 2024  | Sep 27, 2025  |
| Preamplifier                | TDK          | PA-02-3                     | TRS-308-00002 | Oct.12, 2023 | Sep 28, 2024  | Sep 27, 2025  |
| Loop antenna                | Schwarzbeck  | 1519B                       | 00008         | /            | Dec.14, 2021  | Dec.13, 2024  |
| Preamplifier                | TDK          | PA-02-001-3000              | TRS-302-00050 | Oct.12, 2023 | Sep 28, 2024  | Sep 27, 2025  |
| High Pass Filter            | Wi           | WHKX10-2700-3000-18000-40SS | 23            | Oct.12, 2023 | Sep 28, 2024  | Sep 27, 2025  |
| Band Reject Filter          | Wainwright   | WRCJV8-2350-2400-2483.5-    | 4             | Oct.12, 2023 | Sep 28, 2024  | Sep 27, 2025  |

|                                      |  |              |  |        |             |  |
|--------------------------------------|--|--------------|--|--------|-------------|--|
|                                      |  | 2533.5-40SS  |  |        |             |  |
| <b>Software</b>                      |  |              |  |        |             |  |
| Description                          |  | Manufacturer |  | Name   | Version     |  |
| Test Software for Radiated Emissions |  | Farad        |  | EZ-EMC | Ver. UL-3A1 |  |

| <b>Other Instrument</b>    |              |           |            |              |              |              |
|----------------------------|--------------|-----------|------------|--------------|--------------|--------------|
| Equipment                  | Manufacturer | Model No. | Serial No. | Upper Cal.   | Last Cal.    | Due Date     |
| Temperature humidity probe | OMEGA        | ITHX-SD-5 | 18470007   | Oct.21, 2023 | Oct.8, 2024  | Oct.7, 2025  |
| Barometer                  | Yiyi         | Baro      | N/A        | Oct.19, 2023 | Oct.10, 2024 | Oct.9, 2025  |
| Attenuator                 | Agilent      | 8495B     | 2814a12853 | Oct.12, 2023 | Sep 28, 2024 | Sep 27, 2025 |

## 7. ANTENNA PORT TEST RESULTS

### 7.1. CONDUCTED OUTPUT POWER

#### LIMITS

| CFR 47 FCC Part15 (15.247) Subpart C |                  |                  |                       |
|--------------------------------------|------------------|------------------|-----------------------|
| Section                              | Test Item        | Limit            | Frequency Range (MHz) |
| CFR 47 FCC 15.247(b)(3)              | AVG Output Power | 1 watt or 30 dBm | 2400-2483.5           |

#### TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.9.2.3.1.

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the average output power, after any corrections for external attenuators and cables.

The test result in dBm by adding  $[10 \log (1 / D)]$ , where D is the duty cycle.

#### TEST SETUP



#### TEST ENVIRONMENT

|                     |        |                   |          |
|---------------------|--------|-------------------|----------|
| Temperature         | 25.6°C | Relative Humidity | 63.5%    |
| Atmosphere Pressure | 101kPa | Test Voltage      | DC 7.16V |

#### TEST DATE / ENGINEER

|           |                  |         |             |
|-----------|------------------|---------|-------------|
| Test Date | October 13, 2024 | Test By | Johnson Liu |
|-----------|------------------|---------|-------------|

#### TEST RESULTS

Please refer to section "Test Data" - Appendix C

## 7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

### LIMITS

| CFR 47 FCC Part15 (15.247) Subpart C |                |           |                       |
|--------------------------------------|----------------|-----------|-----------------------|
| Section                              | Test Item      | Limit     | Frequency Range (MHz) |
| CFR 47 FCC 15.247(a)(2)              | 6 dB Bandwidth | ≥ 500 kHz | 2400-2483.5           |

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.


Connect the EUT to the spectrum analyzer and use the following settings:

|                  |   |
|------------------|---|
| Center Frequency | The center frequency of the channel under test  |
| Frequency Span   | For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission<br>For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW |
| Detector         | Peak  |
| RBW              | For 6 dB Bandwidth: 100 kHz<br>For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth  |
| VBW              | For 6 dB Bandwidth: ≥3 × RBW<br>For 99 % Occupied Bandwidth: ≥3 × RBW   |
| Trace            | Max hold  |
| Sweep            | Auto couple   |

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### TEST SETUP



**TEST ENVIRONMENT**

|                     |        |                   |          |
|---------------------|--------|-------------------|----------|
| Temperature         | 25.6°C | Relative Humidity | 63.5%    |
| Atmosphere Pressure | 101kPa | Test Voltage      | DC 7.16V |

**TEST DATE / ENGINEER**

|           |                  |         |             |
|-----------|------------------|---------|-------------|
| Test Date | October 13, 2024 | Test By | Johnson Liu |
|-----------|------------------|---------|-------------|

**TEST RESULTS**

Please refer to section "Test Data" - Appendix A&B

### 7.3. POWER SPECTRAL DENSITY

#### LIMITS

| CFR 47 FCC Part15 (15.247) Subpart C |                        |                         |                       |
|--------------------------------------|------------------------|-------------------------|-----------------------|
| Section                              | Test Item              | Limit                   | Frequency Range (MHz) |
| CFR 47 FCC §15.247 (e)               | Power Spectral Density | 8 dBm in any 3 kHz band | 2400-2483.5           |

#### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.5.


Connect the EUT to the spectrum analyzer and use the following settings:

|                  |  |
|------------------|--|
| Center Frequency | The center frequency of the channel under test               |
| Detector         | power averaging (rms)  |
| RBW              | $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$         |
| VBW              | $\geq 3 \times \text{RBW}$                                   |
| Span             | $1.5 \times \text{OBW bandwidth}$                            |
| Trace            | Employ trace averaging(rms)mode over a minimum of 100 traces |
| Sweep time       | Auto couple  |

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

#### TEST SETUP



#### TEST ENVIRONMENT

|                     |        |                   |          |
|---------------------|--------|-------------------|----------|
| Temperature         | 25.6°C | Relative Humidity | 63.5%    |
| Atmosphere Pressure | 101kPa | Test Voltage      | DC 7.16V |

#### TEST DATE / ENGINEER

|           |                  |         |             |
|-----------|------------------|---------|-------------|
| Test Date | October 13, 2024 | Test By | Johnson Liu |
|-----------|------------------|---------|-------------|

#### TEST RESULTS

Please refer to section "Test Data" - Appendix D

## 7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyzer and use the following settings for reference level measurement:

|                  |  |
|------------------|--|
| Center Frequency | The center frequency of the channel under test |
| Detector         | Peak   |
| RBW              | 100 kHz  |
| VBW              | $\geq 3 \times \text{RBW}$                     |
| Span             | 1.5 x DTS bandwidth                            |
| Trace            | Max hold                                       |
| Sweep time       | Auto couple.                                   |


Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

|                    |   |
|--------------------|---|
| Span               | Set the center frequency and span to encompass frequency range to be measured |
| Detector           | Peak  |
| RBW                | 100 kHz   |
| VBW                | $\geq 3 \times \text{RBW}$  |
| measurement points | $\geq \text{span}/\text{RBW}$   |
| Trace              | Max hold  |
| Sweep time         | Auto couple.  |

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

### TEST SETUP



### TEST ENVIRONMENT

|                     |        |                   |          |
|---------------------|--------|-------------------|----------|
| Temperature         | 25.6°C | Relative Humidity | 63.5%    |
| Atmosphere Pressure | 101kPa | Test Voltage      | DC 7.16V |

**TEST DATE / ENGINEER**

|           |                  |         |             |
|-----------|------------------|---------|-------------|
| Test Date | October 13, 2024 | Test By | Johnson Liu |
|-----------|------------------|---------|-------------|

**TEST RESULTS**

Please refer to section "Test Data" - Appendix E&F

## 7.5. DUTY CYCLE


### LIMITS

None; for reporting purposes only.

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

### TEST SETUP



### TEST ENVIRONMENT

|                     |        |                   |          |
|---------------------|--------|-------------------|----------|
| Temperature         | 25.6°C | Relative Humidity | 63.5%    |
| Atmosphere Pressure | 101kPa | Test Voltage      | DC 7.16V |

### TEST DATE / ENGINEER

|           |                  |         |             |
|-----------|------------------|---------|-------------|
| Test Date | October 13, 2024 | Test By | Johnson Liu |
|-----------|------------------|---------|-------------|

### TEST RESULTS

Please refer to section "Test Data" - Appendix G

## 8. RADIATED TEST RESULTS

### LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

| Emissions radiated outside of the specified frequency bands above 30 MHz |                                    |                                      |         |
|--|------------------------------------|--------------------------------------|---------|
| Frequency Range (MHz)  | Field Strength Limit (uV/m) at 3 m | Field Strength Limit (dBuV/m) at 3 m |         |
|  |                                    | Quasi-Peak                           |         |
| 30 - 88  | 100                                | 40                                   |         |
| 88 - 216   | 150                                | 43.5                                 |         |
| 216 - 960  | 200                                | 46                                   |         |
| Above 960  | 500                                | 54                                   |         |
| Above 1000   | 500                                | Peak                                 | Average |
|  |                                    | 74                                   | 54      |

| FCC Emissions radiated outside of the specified frequency bands below 30 MHz |                                   |                               |
|--|-----------------------------------|-------------------------------|
| Frequency (MHz)  | Field strength (microvolts/meter) | Measurement distance (meters) |
| 0.009-0.490  | 2400/F(kHz)                       | 300                           |
| 0.490-1.705  | 24000/F(kHz)                      | 30                            |
| 1.705-30.0   | 30                                | 30                            |

FCC Restricted bands of operation refer to FCC §15.205 (a):

| MHz                      | MHz                 | MHz           | GHz              |
|--------------------------|---------------------|---------------|------------------|
| 0.090-0.110              | 16.42-16.423        | 399.9-410     | 4.5-5.15         |
| <sup>1</sup> 0.495-0.505 | 16.69475-16.69525   | 608-614       | 5.35-5.46        |
| 2.1735-2.1905            | 16.80425-16.80475   | 960-1240      | 7.25-7.75        |
| 4.125-4.128              | 25.5-25.67          | 1300-1427     | 8.025-8.5        |
| 4.17725-4.17775          | 37.5-38.25          | 1435-1626.5   | 9.0-9.2          |
| 4.20725-4.20775          | 73-74.6             | 1645.5-1646.5 | 9.3-9.5          |
| 6.215-6.218              | 74.8-75.2           | 1660-1710     | 10.6-12.7        |
| 6.26775-6.26825          | 108-121.94          | 1718.8-1722.2 | 13.25-13.4       |
| 6.31175-6.31225          | 123-138             | 2200-2300     | 14.47-14.5       |
| 8.291-8.294              | 149.9-150.05        | 2310-2390     | 15.35-16.2       |
| 8.362-8.366              | 156.52475-156.52525 | 2483.5-2500   | 17.7-21.4        |
| 8.37625-8.38675          | 156.7-156.9         | 2690-2900     | 22.01-23.12      |
| 8.41425-8.41475          | 162.0125-167.17     | 3260-3267     | 23.6-24.0        |
| 12.29-12.293             | 167.72-173.2        | 3332-3339     | 31.2-31.8        |
| 12.51975-12.52025        | 240-285             | 3345.8-3358   | 36.43-36.5       |
| 12.57675-12.57725        | 322-335.4           | 3600-4400     | ( <sup>2</sup> ) |
| 13.36-13.41              |                     |               |                  |

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup>Above 38.6c

## TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

|       |  |
|-------|--|
| RBW   | 200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz) |
| VBW   | 200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz) |
| Sweep | Auto   |

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made

to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of  $377\Omega$ . For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to  $Y-51.5 = Z$  dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

|          |          |
|----------|----------|
| RBW      | 120 kHz  |
| VBW      | 300 kHz  |
| Sweep    | Auto     |
| Detector | Peak/QP  |
| Trace    | Max hold |

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

|          |                                |
|----------|--------------------------------|
| RBW      | 1 MHz                          |
| VBW      | PEAK: 3 MHz<br>AVG: see note 6 |
| Sweep    | Auto                           |
| Detector | Peak                           |
| Trace    | Max hold                       |

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes have been tested, but only the worst data was recorded in the report.
5. dBuA/m= dBuV/m- 20Log10[120π] = dBuV/m- 51.5

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 3 GHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (3 GHz ~ 18 GHz):

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG:  $VBW=1/T_{on}$ , where:  $T_{on}$  is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):


Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.


### TEST SETUP



Below 1 GHz and above 30 MHz



Above 1 GHz



**TEST ENVIRONMENT**

|                     |        |                   |       |
|---------------------|--------|-------------------|-------|
| Temperature         | 22.8°C | Relative Humidity | 53.1% |
| Atmosphere Pressure | 101kPa | Test Voltage      |       |


**TEST DATE / ENGINEER**

|           |                  |         |           |
|-----------|------------------|---------|-----------|
| Test Date | October 30, 2024 | Test By | Rex Huang |
|-----------|------------------|---------|-----------|

**TEST RESULTS**


**8.1. RESTRICTED BANDEDGE**

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M PK | Frequency(MHz): | 2407.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2355.840        | 19.75          | 31.60          | 51.35           | 74.00          | -22.65      | peak   |
| 2   | 2390.000        | 14.86          | 31.73          | 46.59           | 74.00          | -27.41      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M PK | Frequency(MHz): | 2407.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2387.400        | 30.97          | 32.55          | 63.52           | 74.00          | -10.48      | peak   |
| 2   | 2390.000        | 29.93          | 32.55          | 62.48           | 74.00          | -11.52      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M AV | Frequency(MHz): | 2407.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2387.400        | 15.76          | 32.55          | 48.31           | 54.00          | -5.69       | AVG    |
| 2   | 2390.000        | 16.62          | 32.55          | 49.17           | 54.00          | -4.83       | AVG    |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M PK | Frequency(MHz): | 2409.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2365.920        | 31.07          | 32.47          | 63.54           | 74.00          | -10.46      | peak   |
| 2   | 2390.000        | 30.13          | 32.55          | 62.68           | 74.00          | -11.32      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M AV | Frequency(MHz): | 2409.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2365.920        | 15.87          | 32.47          | 48.34           | 54.00          | -5.66       | AVG    |
| 2   | 2390.000        | 16.36          | 32.55          | 48.91           | 54.00          | -5.09       | AVG    |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M PK | Frequency(MHz): | 2410.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2348.180        | 31.15          | 32.40          | 63.55           | 74.00          | -10.45      | peak   |
| 2   | 2390.000        | 30.21          | 32.55          | 62.76           | 74.00          | -11.24      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M AV | Frequency(MHz): | 2410.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2348.180        | 15.64          | 32.40          | 48.04           | 54.00          | -5.96       | AVG    |
| 2   | 2390.000        | 15.92          | 32.55          | 48.47           | 54.00          | -5.53       | AVG    |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M PK | Frequency(MHz): | 2467.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2483.500        | 30.34          | 32.80          | 63.14           | 74.00          | -10.86      | peak   |
| 2   | 2493.290        | 32.58          | 32.83          | 65.41           | 74.00          | -8.59       | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M AV | Frequency(MHz): | 2467.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2483.500        | 16.12          | 32.80          | 48.92           | 54.00          | -5.08       | AVG    |
| 2   | 2493.290        | 16.08          | 32.83          | 48.91           | 54.00          | -5.09       | AVG    |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 20M PK | Frequency(MHz): | 2412.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2390.000        | 35.77          | 32.55          | 68.32           | 74.00          | -5.68       | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 20M AV | Frequency(MHz): | 2412.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2390.000        | 19.98          | 32.55          | 52.53           | 54.00          | -1.47       | AVG    |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 20M PK | Frequency(MHz): | 2414.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2388.545        | 31.09          | 32.55          | 63.64           | 74.00          | -10.36      | peak   |
| 2   | 2390.000        | 29.78          | 32.55          | 62.33           | 74.00          | -11.67      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 20M AV | Frequency(MHz): | 2414.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2388.545        | 15.97          | 32.55          | 48.52           | 54.00          | -5.48       | AVG    |
| 2   | 2390.000        | 16.11          | 32.55          | 48.66           | 54.00          | -5.34       | AVG    |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 20M PK | Frequency(MHz): | 2462.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2483.500        | 30.48          | 32.80          | 63.28           | 74.00          | -10.72      | peak   |
| 2   | 2487.240        | 31.51          | 32.81          | 64.32           | 74.00          | -9.68       | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 20M AV | Frequency(MHz): | 2462.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2483.500        | 16.56          | 32.80          | 49.36           | 54.00          | -4.64       | AVG    |
| 2   | 2487.240        | 16.15          | 32.81          | 48.96           | 54.00          | -5.04       | AVG    |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 40M PK | Frequency(MHz): | 2422.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2390.000        | 32.17          | 32.55          | 64.72           | 74.00          | -9.28       | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 40M AV | Frequency(MHz): | 2422.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2390.000        | 18.85          | 32.55          | 51.40           | 54.00          | -2.60       | AVG    |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 40M PK | Frequency(MHz): | 2432.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2356.400        | 31.02          | 32.43          | 63.45           | 74.00          | -10.55      | peak   |
| 2   | 2390.000        | 29.89          | 32.55          | 62.44           | 74.00          | -11.56      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 40M AV | Frequency(MHz): | 2432.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2356.400        | 15.69          | 32.43          | 48.12           | 54.00          | -5.88       | AVG    |
| 2   | 2390.000        | 15.91          | 32.55          | 48.46           | 54.00          | -5.54       | AVG    |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 40M PK | Frequency(MHz): | 2435.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2388.000        | 30.84          | 32.55          | 63.39           | 74.00          | -10.61      | peak   |
| 2   | 2390.000        | 29.39          | 32.55          | 61.94           | 74.00          | -12.06      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 40M AV | Frequency(MHz): | 2435.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2388.000        | 15.84          | 32.55          | 48.39           | 54.00          | -5.61       | AVG    |
| 2   | 2390.000        | 15.90          | 32.55          | 48.45           | 54.00          | -5.55       | AVG    |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 40M PK | Frequency(MHz): | 2452.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2483.500        | 30.67          | 32.80          | 63.47           | 74.00          | -10.53      | peak   |
| 2   | 2493.140        | 30.81          | 32.83          | 63.64           | 74.00          | -10.36      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 40M AV | Frequency(MHz): | 2452.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2483.500        | 16.45          | 32.80          | 49.25           | 54.00          | -4.75       | AVG    |
| 2   | 2493.140        | 16.06          | 32.83          | 48.89           | 54.00          | -5.11       | AVG    |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 60M PK | Frequency(MHz): | 2432.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2379.905        | 31.74          | 32.51          | 64.25           | 74.00          | -9.75       | peak   |
| 2   | 2390.000        | 31.61          | 32.55          | 64.16           | 74.00          | -9.84       | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 60M AV | Frequency(MHz): | 2432.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2379.905        | 15.74          | 32.51          | 48.25           | 54.00          | -5.75       | AVG    |
| 2   | 2390.000        | 18.90          | 32.55          | 51.45           | 54.00          | -2.55       | AVG    |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 60M PK | Frequency(MHz): | 2433.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2366.575        | 31.19          | 32.47          | 63.66           | 74.00          | -10.34      | peak   |
| 2   | 2390.000        | 30.04          | 32.55          | 62.59           | 74.00          | -11.41      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 60M AV | Frequency(MHz): | 2433.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2366.575        | 15.66          | 32.47          | 48.13           | 54.00          | -5.87       | AVG    |
| 2   | 2390.000        | 16.28          | 32.55          | 48.83           | 54.00          | -5.17       | AVG    |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 60M PK | Frequency(MHz): | 2435.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2353.360        | 30.88          | 32.42          | 63.30           | 74.00          | -10.70      | peak   |
| 2   | 2390.000        | 29.71          | 32.55          | 62.26           | 74.00          | -11.74      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 60M AV | Frequency(MHz): | 2435.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2353.360        | 15.62          | 32.42          | 48.04           | 54.00          | -5.96       | AVG    |
| 2   | 2390.000        | 16.43          | 32.55          | 48.98           | 54.00          | -5.02       | AVG    |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 60M PK | Frequency(MHz): | 2442.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2483.500        | 30.24          | 32.80          | 63.04           | 74.00          | -10.96      | peak   |
| 2   | 2489.650        | 31.05          | 32.81          | 63.86           | 74.00          | -10.14      | peak   |


|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 60M AV | Frequency(MHz): | 2442.5   |
| Polarity:  | Vertical   | Test Voltage:   | DC 7.16V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 2483.500        | 16.26          | 32.80          | 49.06           | 54.00          | -4.94       | AVG    |
| 2   | 2489.650        | 16.15          | 32.81          | 48.96           | 54.00          | -5.04       | AVG    |


### 8.2. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M    | Frequency(MHz): | 2407.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark      |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|-------------|
| 1   | 1362.000        | 47.31          | -12.52         | 34.79           | 74.00          | -39.21      | peak        |
| 2   | 1836.000        | 46.15          | -9.95          | 36.20           | 74.00          | -37.80      | peak        |
| 3   | 2088.000        | 45.66          | -9.75          | 35.91           | 74.00          | -38.09      | peak        |
| 4   | 2407.500        | 60.63          | -8.54          | 52.09           | /              | /           | Fundamental |
| 5   | 2642.000        | 45.15          | -7.52          | 37.63           | 74.00          | -36.37      | peak        |
| 6   | 2846.000        | 44.05          | -6.63          | 37.42           | 74.00          | -36.58      | peak        |

|            |          |                 |          |
|------------|----------|-----------------|----------|
| Test Mode: | SRD 10M  | Frequency(MHz): | 2407.5   |
| Polarity:  | Vertical | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark      |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|-------------|
| 1   | 1854.000        | 46.38          | -9.30          | 37.08           | 74.00          | -36.92      | peak        |
| 2   | 2080.000        | 45.54          | -8.90          | 36.64           | 74.00          | -37.36      | peak        |
| 3   | 2407.500        | 71.04          | -7.72          | 63.32           | /              | /           | Fundamental |
| 4   | 2582.000        | 45.17          | -6.89          | 38.28           | 74.00          | -35.72      | peak        |
| 5   | 2686.000        | 44.90          | -6.34          | 38.56           | 74.00          | -35.44      | peak        |
| 6   | 2914.000        | 44.68          | -5.10          | 39.58           | 74.00          | -34.42      | peak        |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M    | Frequency(MHz): | 2437.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark      |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|-------------|
| 1   | 1590.000        | 46.50          | -11.35         | 35.15           | 74.00          | -38.85      | peak        |
| 2   | 2080.000        | 45.89          | -9.78          | 36.11           | 74.00          | -37.89      | peak        |
| 3   | 2328.000        | 49.49          | -8.82          | 40.67           | 74.00          | -33.33      | peak        |
| 4   | 2437.500        | 67.27          | -8.39          | 58.88           | /              | /           | Fundamental |
| 5   | 2684.000        | 45.79          | -7.34          | 38.45           | 74.00          | -35.55      | peak        |
| 6   | 2906.000        | 43.92          | -6.35          | 37.57           | 74.00          | -36.43      | peak        |

|            |          |                 |          |
|------------|----------|-----------------|----------|
| Test Mode: | SRD 10M  | Frequency(MHz): | 2437.5   |
| Polarity:  | Vertical | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark      |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|-------------|
| 1   | 1416.000        | 46.41          | -12.05         | 34.36           | 74.00          | -39.64      | peak        |
| 2   | 1910.000        | 46.09          | -9.26          | 36.83           | 74.00          | -37.17      | peak        |
| 3   | 2088.000        | 45.78          | -8.87          | 36.91           | 74.00          | -37.09      | peak        |
| 4   | 2330.000        | 47.28          | -7.99          | 39.29           | 74.00          | -34.71      | peak        |
| 5   | 2437.500        | 74.51          | -7.57          | 66.94           | /              | /           | Fundamental |
| 6   | 2792.000        | 44.86          | -5.79          | 39.07           | 74.00          | -34.93      | peak        |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M    | Frequency(MHz): | 2467.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark      |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|-------------|
| 1   | 1358.000        | 46.53          | -12.55         | 33.98           | 74.00          | -40.02      | peak        |
| 2   | 1850.000        | 46.79          | -9.97          | 36.82           | 74.00          | -37.18      | peak        |
| 3   | 2026.000        | 45.75          | -10.00         | 35.75           | 74.00          | -38.25      | peak        |
| 4   | 2322.000        | 48.56          | -8.85          | 39.71           | 74.00          | -34.29      | peak        |
| 5   | 2467.500        | 59.52          | -8.28          | 51.24           | /              | /           | Fundamental |
| 6   | 2852.000        | 44.29          | -6.59          | 37.70           | 74.00          | -36.30      | peak        |


|            |          |                 |          |
|------------|----------|-----------------|----------|
| Test Mode: | SRD 10M  | Frequency(MHz): | 2467.5   |
| Polarity:  | Vertical | Test Voltage:   | DC 7.16V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark      |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|-------------|
| 1   | 1328.000        | 46.65          | -12.38         | 34.27           | 74.00          | -39.73      | peak        |
| 2   | 1730.000        | 46.97          | -9.94          | 37.03           | 74.00          | -36.97      | peak        |
| 3   | 1910.000        | 46.85          | -9.26          | 37.59           | 74.00          | -36.41      | peak        |
| 4   | 2338.000        | 46.31          | -7.95          | 38.36           | 74.00          | -35.64      | peak        |
| 5   | 2467.500        | 69.18          | -7.48          | 61.70           | /              | /           | Fundamental |
| 6   | 2842.000        | 45.07          | -5.50          | 39.57           | 74.00          | -34.43      | peak        |


### 8.3. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M    | Frequency(MHz): | 2407.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 5790.000        | 42.99          | 2.84           | 45.83           | 74.00          | -28.17      | peak   |
| 2   | 7995.000        | 42.13          | 8.03           | 50.16           | 74.00          | -23.84      | peak   |
| 3   | 9855.000        | 36.43          | 13.29          | 49.72           | 74.00          | -24.28      | peak   |
| 4   | 11445.000       | 32.40          | 17.81          | 50.21           | 74.00          | -23.79      | peak   |
| 5   | 13080.000       | 29.58          | 20.46          | 50.04           | 74.00          | -23.96      | peak   |
| 6   | 17955.000       | 21.92          | 28.98          | 50.90           | 74.00          | -23.10      | peak   |

|            |          |                 |          |
|------------|----------|-----------------|----------|
| Test Mode: | SRD 10M  | Frequency(MHz): | 2407.5   |
| Polarity:  | Vertical | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 4650.000        | 42.89          | 1.07           | 43.96           | 74.00          | -30.04      | peak   |
| 2   | 7785.000        | 40.09          | 8.20           | 48.29           | 74.00          | -25.71      | peak   |
| 3   | 9285.000        | 38.10          | 11.55          | 49.65           | 74.00          | -24.35      | peak   |
| 4   | 10845.000       | 35.50          | 14.42          | 49.92           | 74.00          | -24.08      | peak   |
| 5   | 13395.000       | 29.73          | 20.29          | 50.02           | 74.00          | -23.98      | peak   |
| 6   | 17775.000       | 24.60          | 26.01          | 50.61           | 74.00          | -23.39      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M    | Frequency(MHz): | 2437.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 4875.000        | 45.92          | 0.80           | 46.72           | 74.00          | -27.28      | peak   |
| 2   | 9210.000        | 37.70          | 11.05          | 48.75           | 74.00          | -25.25      | peak   |
| 3   | 10380.000       | 36.50          | 13.42          | 49.92           | 74.00          | -24.08      | peak   |
| 4   | 10680.000       | 35.60          | 14.31          | 49.91           | 74.00          | -24.09      | peak   |
| 5   | 12540.000       | 30.74          | 18.97          | 49.71           | 74.00          | -24.29      | peak   |
| 6   | 17745.000       | 22.96          | 27.00          | 49.96           | 74.00          | -24.04      | peak   |

|            |          |                 |          |
|------------|----------|-----------------|----------|
| Test Mode: | SRD 10M  | Frequency(MHz): | 2437.5   |
| Polarity:  | Vertical | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 5715.000        | 40.57          | 3.80           | 44.37           | 74.00          | -29.63      | peak   |
| 2   | 9735.000        | 35.84          | 12.79          | 48.63           | 74.00          | -25.37      | peak   |
| 3   | 11610.000       | 32.07          | 16.84          | 48.91           | 74.00          | -25.09      | peak   |
| 4   | 12630.000       | 31.31          | 18.08          | 49.39           | 74.00          | -24.61      | peak   |
| 5   | 14085.000       | 27.96          | 22.03          | 49.99           | 74.00          | -24.01      | peak   |
| 6   | 16935.000       | 24.64          | 24.91          | 49.55           | 74.00          | -24.45      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M    | Frequency(MHz): | 2467.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 4920.000        | 43.54          | 0.93           | 44.47           | 74.00          | -29.53      | peak   |
| 2   | 8325.000        | 38.99          | 8.73           | 47.72           | 74.00          | -26.28      | peak   |
| 3   | 9870.000        | 38.40          | 13.30          | 51.70           | 74.00          | -22.30      | peak   |
| 4   | 11520.000       | 31.43          | 18.07          | 49.50           | 74.00          | -24.50      | peak   |
| 5   | 13530.000       | 26.99          | 22.34          | 49.33           | 74.00          | -24.67      | peak   |
| 6   | 18000.000       | 19.59          | 29.44          | 49.03           | 74.00          | -24.97      | peak   |

|            |          |                 |          |
|------------|----------|-----------------|----------|
| Test Mode: | SRD 10M  | Frequency(MHz): | 2467.5   |
| Polarity:  | Vertical | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 4920.000        | 43.18          | 2.08           | 45.26           | 74.00          | -28.74      | peak   |
| 2   | 8820.000        | 39.89          | 10.02          | 49.91           | 74.00          | -24.09      | peak   |
| 3   | 9855.000        | 38.98          | 12.80          | 51.78           | 74.00          | -22.22      | peak   |
| 4   | 12345.000       | 31.63          | 18.04          | 49.67           | 74.00          | -24.33      | peak   |
| 5   | 14010.000       | 27.30          | 22.00          | 49.30           | 74.00          | -24.70      | peak   |
| 6   | 16995.000       | 24.08          | 24.98          | 49.06           | 74.00          | -24.94      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 20M    | Frequency(MHz): | 2412.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 4650.000        | 43.26          | 0.08           | 43.34           | 74.00          | -30.66      | peak   |
| 2   | 9945.000        | 35.50          | 13.32          | 48.82           | 74.00          | -25.18      | peak   |
| 3   | 11850.000       | 31.17          | 18.70          | 49.87           | 74.00          | -24.13      | peak   |
| 4   | 12570.000       | 31.10          | 18.97          | 50.07           | 74.00          | -23.93      | peak   |
| 5   | 14205.000       | 26.64          | 23.12          | 49.76           | 74.00          | -24.24      | peak   |
| 6   | 17925.000       | 20.83          | 28.67          | 49.50           | 74.00          | -24.50      | peak   |

|            |          |                 |          |
|------------|----------|-----------------|----------|
| Test Mode: | SRD 20M  | Frequency(MHz): | 2412.5   |
| Polarity:  | Vertical | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 4530.000        | 44.41          | 0.59           | 45.00           | 74.00          | -29.00      | peak   |
| 2   | 9585.000        | 37.13          | 12.61          | 49.74           | 74.00          | -24.26      | peak   |
| 3   | 10695.000       | 35.60          | 13.95          | 49.55           | 74.00          | -24.45      | peak   |
| 4   | 12780.000       | 31.10          | 18.34          | 49.44           | 74.00          | -24.56      | peak   |
| 5   | 14295.000       | 27.49          | 21.81          | 49.30           | 74.00          | -24.70      | peak   |
| 6   | 17070.000       | 24.51          | 25.03          | 49.54           | 74.00          | -24.46      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 20M    | Frequency(MHz): | 2437.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 5865.000        | 40.26          | 2.98           | 43.24           | 74.00          | -30.76      | peak   |
| 2   | 8115.000        | 39.86          | 8.32           | 48.18           | 74.00          | -25.82      | peak   |
| 3   | 9765.000        | 36.44          | 13.19          | 49.63           | 74.00          | -24.37      | peak   |
| 4   | 11520.000       | 31.20          | 18.07          | 49.27           | 74.00          | -24.73      | peak   |
| 5   | 12255.000       | 31.05          | 18.92          | 49.97           | 74.00          | -24.03      | peak   |
| 6   | 18000.000       | 20.87          | 29.44          | 50.31           | 74.00          | -23.69      | peak   |

|            |          |                 |          |
|------------|----------|-----------------|----------|
| Test Mode: | SRD 20M  | Frequency(MHz): | 2437.5   |
| Polarity:  | Vertical | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 5880.000        | 39.46          | 4.06           | 43.52           | 74.00          | -30.48      | peak   |
| 2   | 9390.000        | 37.12          | 11.93          | 49.05           | 74.00          | -24.95      | peak   |
| 3   | 10980.000       | 34.05          | 14.97          | 49.02           | 74.00          | -24.98      | peak   |
| 4   | 13125.000       | 29.82          | 19.37          | 49.19           | 74.00          | -24.81      | peak   |
| 5   | 14010.000       | 27.96          | 22.00          | 49.96           | 74.00          | -24.04      | peak   |
| 6   | 17250.000       | 24.86          | 25.14          | 50.00           | 74.00          | -24.00      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 20M    | Frequency(MHz): | 2462.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 5865.000        | 40.56          | 2.98           | 43.54           | 74.00          | -30.46      | peak   |
| 2   | 7785.000        | 40.17          | 7.70           | 47.87           | 74.00          | -26.13      | peak   |
| 3   | 9585.000        | 36.77          | 12.73          | 49.50           | 74.00          | -24.50      | peak   |
| 4   | 12000.000       | 30.13          | 18.92          | 49.05           | 74.00          | -24.95      | peak   |
| 5   | 14025.000       | 25.94          | 23.54          | 49.48           | 74.00          | -24.52      | peak   |
| 6   | 17910.000       | 21.45          | 28.53          | 49.98           | 74.00          | -24.02      | peak   |

|            |          |                 |          |
|------------|----------|-----------------|----------|
| Test Mode: | SRD 20M  | Frequency(MHz): | 2462.5   |
| Polarity:  | Vertical | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 5970.000        | 39.24          | 4.19           | 43.43           | 74.00          | -30.57      | peak   |
| 2   | 7335.000        | 37.82          | 7.77           | 45.59           | 74.00          | -28.41      | peak   |
| 3   | 9870.000        | 36.53          | 12.78          | 49.31           | 74.00          | -24.69      | peak   |
| 4   | 11520.000       | 33.13          | 16.59          | 49.72           | 74.00          | -24.28      | peak   |
| 5   | 13425.000       | 29.32          | 20.38          | 49.70           | 74.00          | -24.30      | peak   |
| 6   | 17850.000       | 23.03          | 26.37          | 49.40           | 74.00          | -24.60      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 40M    | Frequency(MHz): | 2422.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 5955.000        | 40.67          | 3.15           | 43.82           | 74.00          | -30.18      | peak   |
| 2   | 9735.000        | 35.93          | 13.12          | 49.05           | 74.00          | -24.95      | peak   |
| 3   | 10725.000       | 34.92          | 14.49          | 49.41           | 74.00          | -24.59      | peak   |
| 4   | 12420.000       | 30.95          | 19.03          | 49.98           | 74.00          | -24.02      | peak   |
| 5   | 13125.000       | 28.94          | 20.69          | 49.63           | 74.00          | -24.37      | peak   |
| 6   | 17775.000       | 22.32          | 27.22          | 49.54           | 74.00          | -24.46      | peak   |

|            |          |                 |          |
|------------|----------|-----------------|----------|
| Test Mode: | SRD 40M  | Frequency(MHz): | 2422.5   |
| Polarity:  | Vertical | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 3060.000        | 49.56          | -3.09          | 46.47           | 74.00          | -27.53      | peak   |
| 2   | 7920.000        | 40.32          | 8.42           | 48.74           | 74.00          | -25.26      | peak   |
| 3   | 9555.000        | 37.22          | 12.53          | 49.75           | 74.00          | -24.25      | peak   |
| 4   | 11055.000       | 34.64          | 15.31          | 49.95           | 74.00          | -24.05      | peak   |
| 5   | 13980.000       | 28.62          | 21.91          | 50.53           | 74.00          | -23.47      | peak   |
| 6   | 17040.000       | 25.87          | 25.01          | 50.88           | 74.00          | -23.12      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 40M    | Frequency(MHz): | 2437.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 4875.000        | 42.83          | 0.80           | 43.63           | 74.00          | -30.37      | peak   |
| 2   | 8055.000        | 39.56          | 8.18           | 47.74           | 74.00          | -26.26      | peak   |
| 3   | 9780.000        | 36.34          | 13.22          | 49.56           | 74.00          | -24.44      | peak   |
| 4   | 11610.000       | 31.38          | 18.25          | 49.63           | 74.00          | -24.37      | peak   |
| 5   | 12690.000       | 30.67          | 19.20          | 49.87           | 74.00          | -24.13      | peak   |
| 6   | 17985.000       | 21.08          | 29.29          | 50.37           | 74.00          | -23.63      | peak   |

|            |          |                 |          |
|------------|----------|-----------------|----------|
| Test Mode: | SRD 40M  | Frequency(MHz): | 2437.5   |
| Polarity:  | Vertical | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 5115.000        | 42.07          | 2.45           | 44.52           | 74.00          | -29.48      | peak   |
| 2   | 8955.000        | 38.28          | 10.36          | 48.64           | 74.00          | -25.36      | peak   |
| 3   | 9720.000        | 39.45          | 12.77          | 52.22           | 74.00          | -21.78      | peak   |
| 4   | 12690.000       | 30.94          | 18.18          | 49.12           | 74.00          | -24.88      | peak   |
| 5   | 13440.000       | 29.32          | 20.43          | 49.75           | 74.00          | -24.25      | peak   |
| 6   | 17295.000       | 24.63          | 25.16          | 49.79           | 74.00          | -24.21      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 40M    | Frequency(MHz): | 2452.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 5640.000        | 41.17          | 2.53           | 43.70           | 74.00          | -30.30      | peak   |
| 2   | 9345.000        | 37.71          | 11.64          | 49.35           | 74.00          | -24.65      | peak   |
| 3   | 10125.000       | 36.19          | 13.29          | 49.48           | 74.00          | -24.52      | peak   |
| 4   | 11850.000       | 31.67          | 18.70          | 50.37           | 74.00          | -23.63      | peak   |
| 5   | 13140.000       | 29.94          | 20.78          | 50.72           | 74.00          | -23.28      | peak   |
| 6   | 18000.000       | 21.46          | 29.44          | 50.90           | 74.00          | -23.10      | peak   |

|            |          |                 |          |
|------------|----------|-----------------|----------|
| Test Mode: | SRD 40M  | Frequency(MHz): | 2452.5   |
| Polarity:  | Vertical | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 5715.000        | 40.95          | 3.80           | 44.75           | 74.00          | -29.25      | peak   |
| 2   | 8250.000        | 40.38          | 9.15           | 49.53           | 74.00          | -24.47      | peak   |
| 3   | 9810.000        | 40.81          | 12.84          | 53.65           | 74.00          | -20.35      | peak   |
| 4   | 11490.000       | 33.86          | 16.50          | 50.36           | 74.00          | -23.64      | peak   |
| 5   | 14220.000       | 28.47          | 22.02          | 50.49           | 74.00          | -23.51      | peak   |
| 6   | 16425.000       | 26.42          | 23.72          | 50.14           | 74.00          | -23.86      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 60M    | Frequency(MHz): | 2432.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 5955.000        | 41.49          | 3.15           | 44.64           | 74.00          | -29.36      | peak   |
| 2   | 8415.000        | 39.00          | 8.87           | 47.87           | 74.00          | -26.13      | peak   |
| 3   | 10290.000       | 35.82          | 13.34          | 49.16           | 74.00          | -24.84      | peak   |
| 4   | 11520.000       | 31.33          | 18.07          | 49.40           | 74.00          | -24.60      | peak   |
| 5   | 12420.000       | 30.57          | 19.03          | 49.60           | 74.00          | -24.40      | peak   |
| 6   | 18000.000       | 20.73          | 29.44          | 50.17           | 74.00          | -23.83      | peak   |

|            |          |                 |          |
|------------|----------|-----------------|----------|
| Test Mode: | SRD 60M  | Frequency(MHz): | 2432.5   |
| Polarity:  | Vertical | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 4965.000        | 42.01          | 2.23           | 44.24           | 74.00          | -29.76      | peak   |
| 2   | 6855.000        | 38.57          | 6.98           | 45.55           | 74.00          | -28.45      | peak   |
| 3   | 9285.000        | 37.82          | 11.55          | 49.37           | 74.00          | -24.63      | peak   |
| 4   | 10290.000       | 36.52          | 12.93          | 49.45           | 74.00          | -24.55      | peak   |
| 5   | 12750.000       | 31.32          | 18.30          | 49.62           | 74.00          | -24.38      | peak   |
| 6   | 16620.000       | 25.43          | 24.29          | 49.72           | 74.00          | -24.28      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 60M    | Frequency(MHz): | 2437.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 5640.000        | 40.65          | 2.53           | 43.18           | 74.00          | -30.82      | peak   |
| 2   | 9240.000        | 38.69          | 11.18          | 49.87           | 74.00          | -24.13      | peak   |
| 3   | 9990.000        | 37.23          | 13.34          | 50.57           | 74.00          | -23.43      | peak   |
| 4   | 11835.000       | 31.20          | 18.69          | 49.89           | 74.00          | -24.11      | peak   |
| 5   | 13830.000       | 26.48          | 22.88          | 49.36           | 74.00          | -24.64      | peak   |
| 6   | 18000.000       | 21.23          | 29.44          | 50.67           | 74.00          | -23.33      | peak   |

|            |          |                 |          |
|------------|----------|-----------------|----------|
| Test Mode: | SRD 60M  | Frequency(MHz): | 2437.5   |
| Polarity:  | Vertical | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 5880.000        | 40.18          | 4.06           | 44.24           | 74.00          | -29.76      | peak   |
| 2   | 7905.000        | 40.23          | 8.39           | 48.62           | 74.00          | -25.38      | peak   |
| 3   | 9750.000        | 41.15          | 12.80          | 53.95           | 74.00          | -20.05      | peak   |
| 4   | 10815.000       | 35.09          | 14.30          | 49.39           | 74.00          | -24.61      | peak   |
| 5   | 12255.000       | 31.93          | 17.92          | 49.85           | 74.00          | -24.15      | peak   |
| 6   | 16920.000       | 25.35          | 24.89          | 50.24           | 74.00          | -23.76      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 60M    | Frequency(MHz): | 2442.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 6855.000        | 37.92          | 6.11           | 44.03           | 74.00          | -29.97      | peak   |
| 2   | 10005.000       | 35.77          | 13.33          | 49.10           | 74.00          | -24.90      | peak   |
| 3   | 11250.000       | 32.49          | 17.24          | 49.73           | 74.00          | -24.27      | peak   |
| 4   | 11955.000       | 30.80          | 18.85          | 49.65           | 74.00          | -24.35      | peak   |
| 5   | 13920.000       | 25.80          | 23.26          | 49.06           | 74.00          | -24.94      | peak   |
| 6   | 17985.000       | 20.70          | 29.29          | 49.99           | 74.00          | -24.01      | peak   |


|            |          |                 |          |
|------------|----------|-----------------|----------|
| Test Mode: | SRD 60M  | Frequency(MHz): | 2442.5   |
| Polarity:  | Vertical | Test Voltage:   | DC 7.16V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 4800.000        | 43.04          | 1.67           | 44.71           | 74.00          | -29.29      | peak   |
| 2   | 8640.000        | 38.77          | 9.84           | 48.61           | 74.00          | -25.39      | peak   |
| 3   | 9765.000        | 42.54          | 12.81          | 55.35           | 74.00          | -18.65      | peak   |
| 4   | 11040.000       | 34.68          | 15.24          | 49.92           | 74.00          | -24.08      | peak   |
| 5   | 12555.000       | 32.42          | 18.03          | 50.45           | 74.00          | -23.55      | peak   |
| 6   | 16770.000       | 25.69          | 24.69          | 50.38           | 74.00          | -23.62      | peak   |


### 8.4. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M    | Frequency(MHz): | 2407.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | FCC Result (dBuV/m) | FCC Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|---------------------|--------------------|-------------|--------|
| 1   | 0.0100          | 79.22          | -101.40        | -22.18              | 47.6               | -69.78      | peak   |
| 2   | 0.0114          | 78.38          | -101.40        | -23.02              | 46.46              | -69.48      | peak   |
| 3   | 0.0188          | 74.64          | -101.35        | -26.71              | 42.12              | -68.83      | peak   |
| 4   | 0.0269          | 70.46          | -101.38        | -30.92              | 39.01              | -69.93      | peak   |
| 5   | 0.0446          | 65.16          | -101.45        | -36.29              | 34.61              | -70.90      | peak   |
| 6   | 0.0656          | 63.86          | -101.55        | -37.69              | 31.26              | -68.95      | peak   |

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M    | Frequency(MHz): | 2407.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | FCC Result (dBuV/m) | FCC Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|---------------------|--------------------|-------------|--------|
| 1   | 0.1554          | 80.27          | -101.65        | -21.38              | 23.77              | -45.15      | peak   |
| 2   | 0.1794          | 77.27          | -101.68        | -24.41              | 22.53              | -46.94      | peak   |
| 3   | 0.2013          | 74.56          | -101.72        | -27.16              | 21.52              | -48.68      | peak   |
| 4   | 0.2530          | 69.14          | -101.80        | -32.66              | 19.54              | -52.20      | peak   |
| 5   | 0.3084          | 65.95          | -101.86        | -35.91              | 17.82              | -53.73      | peak   |
| 6   | 0.3684          | 61.98          | -101.93        | -39.95              | 16.27              | -56.22      | peak   |


|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M    | Frequency(MHz): | 2407.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | FCC Result (dBuV/m) | FCC Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|---------------------|--------------------|-------------|--------|
| 1   | 0.5298          | 65.03          | -62.08         | 2.95                | 33.12              | -30.17      | peak   |
| 2   | 0.8898          | 63.45          | -62.20         | 1.25                | 28.62              | -27.37      | peak   |
| 3   | 2.0539          | 59.20          | -61.81         | -2.61               | 29.54              | -32.15      | peak   |
| 4   | 6.2445          | 55.13          | -61.32         | -6.19               | 29.54              | -35.73      | peak   |
| 5   | 10.5234         | 53.81          | -60.82         | -7.01               | 29.54              | -36.55      | peak   |
| 6   | 16.3959         | 53.67          | -60.96         | -7.29               | 29.54              | -36.83      | peak   |


### 8.5. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M    | Frequency(MHz): | 2407.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 18416.000       | 50.23          | -5.35          | 44.88           | 74.00          | -29.12      | peak   |
| 2   | 20640.000       | 49.12          | -5.22          | 43.90           | 74.00          | -30.10      | peak   |
| 3   | 21552.000       | 48.73          | -4.61          | 44.12           | 74.00          | -29.88      | peak   |
| 4   | 23064.000       | 46.99          | -3.42          | 43.57           | 74.00          | -30.43      | peak   |
| 5   | 23744.000       | 47.15          | -3.20          | 43.95           | 74.00          | -30.05      | peak   |
| 6   | 25000.000       | 45.86          | -2.10          | 43.76           | 74.00          | -30.24      | peak   |


|            |          |                 |          |
|------------|----------|-----------------|----------|
| Test Mode: | SRD 10M  | Frequency(MHz): | 2407.5   |
| Polarity:  | Vertical | Test Voltage:   | DC 7.16V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 18856.000       | 49.23          | -5.34          | 43.89           | 74.00          | -30.11      | peak   |
| 2   | 20240.000       | 49.82          | -5.61          | 44.21           | 74.00          | -29.79      | peak   |
| 3   | 21560.000       | 48.99          | -4.60          | 44.39           | 74.00          | -29.61      | peak   |
| 4   | 23264.000       | 48.76          | -3.36          | 45.40           | 74.00          | -28.60      | peak   |
| 5   | 23640.000       | 47.97          | -3.17          | 44.80           | 74.00          | -29.20      | peak   |
| 6   | 24968.000       | 45.76          | -2.14          | 43.62           | 74.00          | -30.38      | peak   |


### 8.6. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)

|            |            |                 |          |
|------------|------------|-----------------|----------|
| Test Mode: | SRD 10M    | Frequency(MHz): | 2407.5   |
| Polarity:  | Horizontal | Test Voltage:   | DC 7.16V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 68.8000         | 40.36          | -16.05         | 24.31           | 40.00          | -15.69      | QP     |
| 2   | 199.7500        | 41.23          | -11.60         | 29.63           | 43.50          | -13.87      | QP     |
| 3   | 237.5800        | 48.66          | -13.65         | 35.01           | 46.00          | -10.99      | QP     |
| 4   | 263.7700        | 44.96          | -13.59         | 31.37           | 46.00          | -14.63      | QP     |
| 5   | 372.4100        | 39.76          | -9.27          | 30.49           | 46.00          | -15.51      | QP     |
| 6   | 450.9800        | 39.21          | -8.12          | 31.09           | 46.00          | -14.91      | QP     |

|            |          |                 |          |
|------------|----------|-----------------|----------|
| Test Mode: | SRD 10M  | Frequency(MHz): | 2407.5   |
| Polarity:  | Vertical | Test Voltage:   | DC 7.16V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1   | 68.8000         | 35.96          | -16.05         | 19.91           | 40.00          | -20.09      | QP     |
| 2   | 237.5800        | 42.74          | -13.65         | 29.09           | 46.00          | -16.91      | QP     |
| 3   | 262.8000        | 39.85          | -13.64         | 26.21           | 46.00          | -19.79      | QP     |
| 4   | 374.3500        | 37.36          | -9.28          | 28.08           | 46.00          | -17.92      | QP     |
| 5   | 451.9500        | 39.99          | -8.10          | 31.89           | 46.00          | -14.11      | QP     |
| 6   | 504.3300        | 38.51          | -7.14          | 31.37           | 46.00          | -14.63      | QP     |

## 9. ANTENNA REQUIREMENT

### REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### DESCRIPTION

Pass

## 10. AC POWER LINE CONDUCTED EMISSION

### LIMITS

Please refer to CFR 47 FCC §15.207 (a)


| FREQUENCY (MHz) | Quasi-peak | Average   |
|-----------------|------------|-----------|
| 0.15 -0.5       | 66 - 56 *  | 56 - 46 * |
| 0.50 -5.0       | 56.00      | 46.00     |
| 5.0 -30.0       | 60.00      | 50.00     |

### TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

### TEST SETUP



### TEST ENVIRONMENT


|                     |        |                   |              |
|---------------------|--------|-------------------|--------------|
| Temperature         | 25.0°C | Relative Humidity | 61.0%        |
| Atmosphere Pressure | 101kPa | Test Voltage      | AC 120V 60Hz |

**TEST DATE / ENGINEER**

|           |                  |         |             |
|-----------|------------------|---------|-------------|
| Test Date | October 22, 2024 | Test By | Johnson Liu |
|-----------|------------------|---------|-------------|

**TEST RESULTS**

|            |         |                 |        |
|------------|---------|-----------------|--------|
| Test Mode: | SRD 10M | Frequency(MHz): | 2437.5 |
| Line:      | Line    |                 |        |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Remark |
|-----|-----------------|----------------|--------------|---------------|--------------|-------------|--------|
| 1   | 0.1572          | 38.52          | 10.33        | 48.85         | 65.61        | -16.76      | QP     |
| 2   | 0.1572          | 11.77          | 10.33        | 22.10         | 55.61        | -33.51      | AVG    |
| 3   | 0.1818          | 37.14          | 10.28        | 47.42         | 64.40        | -16.98      | QP     |
| 4   | 0.1818          | 11.74          | 10.28        | 22.02         | 54.40        | -32.38      | AVG    |
| 5   | 0.2195          | 30.68          | 10.24        | 40.92         | 62.84        | -21.92      | QP     |
| 6   | 0.2195          | 12.71          | 10.24        | 22.95         | 52.84        | -29.89      | AVG    |
| 7   | 0.2540          | 29.59          | 10.24        | 39.83         | 61.63        | -21.80      | QP     |
| 8   | 0.2540          | 11.56          | 10.24        | 21.80         | 51.63        | -29.83      | AVG    |
| 9   | 0.4333          | 17.58          | 10.24        | 27.82         | 57.19        | -29.37      | QP     |
| 10  | 0.4333          | 7.72           | 10.24        | 17.96         | 47.19        | -29.23      | AVG    |
| 11  | 0.5633          | 29.67          | 10.24        | 39.91         | 56.00        | -16.09      | QP     |
| 12  | 0.5633          | 22.83          | 10.24        | 33.07         | 46.00        | -12.93      | AVG    |

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

|            |         |                 |        |
|------------|---------|-----------------|--------|
| Test Mode: | SRD 10M | Frequency(MHz): | 2437.5 |
| Line:      | Neutral |                 |        |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Remark |
|-----|-----------------|----------------|--------------|---------------|--------------|-------------|--------|
| 1   | 0.1513          | 37.97          | 10.34        | 48.31         | 65.93        | -17.62      | QP     |
| 2   | 0.1513          | 12.24          | 10.34        | 22.58         | 55.93        | -33.35      | AVG    |
| 3   | 0.1671          | 37.59          | 10.31        | 47.90         | 65.10        | -17.20      | QP     |
| 4   | 0.1671          | 11.66          | 10.31        | 21.97         | 55.10        | -33.13      | AVG    |
| 5   | 0.2057          | 30.68          | 10.24        | 40.92         | 63.38        | -22.46      | QP     |
| 6   | 0.2057          | 10.78          | 10.24        | 21.02         | 53.38        | -32.36      | AVG    |
| 7   | 0.2213          | 30.48          | 10.24        | 40.72         | 62.77        | -22.05      | QP     |
| 8   | 0.2213          | 11.77          | 10.24        | 22.01         | 52.77        | -30.76      | AVG    |
| 9   | 0.5602          | 32.25          | 10.24        | 42.49         | 56.00        | -13.51      | QP     |
| 10  | 0.5602          | 22.71          | 10.24        | 32.95         | 46.00        | -13.05      | AVG    |
| 11  | 1.6585          | 21.14          | 9.97         | 31.11         | 56.00        | -24.89      | QP     |
| 12  | 1.6585          | 12.31          | 9.97         | 22.28         | 46.00        | -23.72      | AVG    |

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.


## 11. TEST DATA


### 11.1. APPENDIX A: DTS BANDWIDTH

#### 11.1.1. Test Result


| Test Mode | Antenna | Frequency[MHz] | DTS BW [MHz] | FL[MHz] | FH[MHz] | Limit[MHz] | Verdict |
|-----------|---------|----------------|--------------|---------|---------|------------|---------|
| SRD 10M   | Ant0    | 2407.5         | 9.04         | 2402.98 | 2412.02 | ≥0.5       | PASS    |
|           | Ant1    | 2407.5         | 9.04         | 2402.98 | 2412.02 | ≥0.5       | PASS    |
|           | Ant0    | 2409.5         | 9.04         | 2404.98 | 2414.02 | ≥0.5       | PASS    |
|           | Ant1    | 2409.5         | 9.04         | 2404.98 | 2414.02 | ≥0.5       | PASS    |
|           | Ant0    | 2410.5         | 9.04         | 2405.98 | 2415.02 | ≥0.5       | PASS    |
|           | Ant1    | 2410.5         | 9.04         | 2405.98 | 2415.02 | ≥0.5       | PASS    |
|           | Ant0    | 2437.5         | 9.04         | 2432.98 | 2442.02 | ≥0.5       | PASS    |
|           | Ant1    | 2437.5         | 9.04         | 2432.98 | 2442.02 | ≥0.5       | PASS    |
| SRD 20M   | Ant0    | 2467.5         | 9.00         | 2462.98 | 2471.98 | ≥0.5       | PASS    |
|           | Ant1    | 2467.5         | 9.04         | 2462.94 | 2471.98 | ≥0.5       | PASS    |
|           | Ant0    | 2412.5         | 17.84        | 2403.62 | 2421.46 | ≥0.5       | PASS    |
|           | Ant1    | 2412.5         | 17.64        | 2403.86 | 2421.50 | ≥0.5       | PASS    |
|           | Ant0    | 2414.5         | 17.88        | 2405.58 | 2423.46 | ≥0.5       | PASS    |
|           | Ant1    | 2414.5         | 17.60        | 2405.86 | 2423.46 | ≥0.5       | PASS    |
|           | Ant0    | 2437.5         | 17.88        | 2428.58 | 2446.46 | ≥0.5       | PASS    |
|           | Ant1    | 2437.5         | 17.88        | 2428.58 | 2446.46 | ≥0.5       | PASS    |
| SRD 40M   | Ant0    | 2462.5         | 17.72        | 2453.50 | 2471.22 | ≥0.5       | PASS    |
|           | Ant1    | 2462.5         | 17.60        | 2453.54 | 2471.14 | ≥0.5       | PASS    |
|           | Ant0    | 2422.5         | 23.12        | 2412.18 | 2435.30 | ≥0.5       | PASS    |
|           | Ant1    | 2422.5         | 22.56        | 2412.50 | 2435.06 | ≥0.5       | PASS    |
|           | Ant0    | 2432.5         | 23.52        | 2421.78 | 2445.30 | ≥0.5       | PASS    |
|           | Ant1    | 2432.5         | 21.36        | 2422.50 | 2443.86 | ≥0.5       | PASS    |
|           | Ant0    | 2435.5         | 23.60        | 2424.70 | 2448.30 | ≥0.5       | PASS    |
|           | Ant1    | 2435.5         | 21.52        | 2425.34 | 2446.86 | ≥0.5       | PASS    |
| SRD 60M   | Ant0    | 2437.5         | 23.60        | 2426.70 | 2450.30 | ≥0.5       | PASS    |
|           | Ant1    | 2437.5         | 23.12        | 2426.94 | 2450.06 | ≥0.5       | PASS    |
|           | Ant0    | 2452.5         | 23.44        | 2441.86 | 2465.30 | ≥0.5       | PASS    |
|           | Ant1    | 2452.5         | 21.92        | 2441.94 | 2463.86 | ≥0.5       | PASS    |
|           | Ant0    | 2432.5         | 42.12        | 2411.86 | 2453.98 | ≥0.5       | PASS    |
|           | Ant1    | 2432.5         | 41.16        | 2412.22 | 2453.38 | ≥0.5       | PASS    |
|           | Ant0    | 2433.5         | 43.20        | 2412.38 | 2455.58 | ≥0.5       | PASS    |
|           | Ant1    | 2433.5         | 42.36        | 2412.50 | 2454.86 | ≥0.5       | PASS    |
| SRD 60M   | Ant0    | 2435.5         | 43.08        | 2413.78 | 2456.86 | ≥0.5       | PASS    |
|           | Ant1    | 2435.5         | 41.52        | 2414.86 | 2456.38 | ≥0.5       | PASS    |
|           | Ant0    | 2437.5         | 42.24        | 2416.62 | 2458.86 | ≥0.5       | PASS    |
|           | Ant1    | 2437.5         | 41.64        | 2416.50 | 2458.14 | ≥0.5       | PASS    |
|           | Ant0    | 2442.5         | 39.96        | 2422.10 | 2462.06 | ≥0.5       | PASS    |
|           | Ant1    | 2442.5         | 41.76        | 2421.38 | 2463.14 | ≥0.5       | PASS    |

### 11.1.2. Test Graphs






SRD 10M\_Ant1\_2409.5




SRD 10M\_Ant0\_2410.5



SRD 10M\_Ant1\_2410.5






SRD 10M\_Ant0\_2437.5




SRD 10M\_Ant1\_2437.5




SRD 10M\_Ant0\_2467.5







SRD 20M\_Ant0\_2414.5




SRD 20M\_Ant1\_2414.5




SRD 20M\_Ant0\_2437.5




SRD 20M\_Ant1\_2437.5




SRD 20M\_Ant0\_2462.5



SRD 20M\_Ant1\_2462.5




SRD 40M\_Ant0\_2422.5




SRD 40M\_Ant1\_2422.5




SRD 40M\_Ant0\_2432.5




SRD 40M\_Ant1\_2432.5



SRD 40M\_Ant0\_2435.5



SRD 40M\_Ant1\_2435.5




SRD 40M\_Ant0\_2437.5




SRD 40M\_Ant1\_2437.5




SRD 40M\_Ant0\_2452.5




SRD 40M\_Ant1\_2452.5




SRD 60M\_Ant0\_2432.5




SRD 60M\_Ant1\_2432.5




SRD 60M\_Ant0\_2433.5




SRD 60M\_Ant1\_2433.5




SRD 60M\_Ant0\_2435.5




SRD 60M\_Ant1\_2435.5




SRD 60M\_Ant0\_2437.5



SRD 60M\_Ant1\_2437.5



SRD 60M\_Ant0\_2442.5




SRD 60M\_Ant1\_2442.5

## 11.2. APPENDIX B: OCCUPIED CHANNEL BANDWIDTH


### 11.2.1. Test Result

| Test Mode | Antenna | Frequency[MHz] | OCB [MHz] | FL[MHz]   | FH[MHz]   |
|-----------|---------|----------------|-----------|-----------|-----------|
| SRD 10M   | Ant0    | 2407.5         | 8.991     | 2403.0245 | 2412.0155 |
|           | Ant1    | 2407.5         | 9.031     | 2402.9845 | 2412.0155 |
|           | Ant0    | 2409.5         | 9.071     | 2404.9845 | 2414.0554 |
|           | Ant1    | 2409.5         | 9.111     | 2404.9446 | 2414.0554 |
|           | Ant0    | 2410.5         | 9.191     | 2405.9845 | 2415.1753 |
|           | Ant1    | 2410.5         | 9.351     | 2405.9046 | 2415.2552 |
|           | Ant0    | 2437.5         | 9.071     | 2432.9845 | 2442.0554 |
|           | Ant1    | 2437.5         | 9.111     | 2432.9446 | 2442.0554 |
|           | Ant0    | 2467.5         | 9.75      | 2462.2652 | 2472.0155 |
| Ant1      | 2467.5  | 9.191          | 2462.8247 | 2472.0155 |           |
| SRD 20M   | Ant0    | 2412.5         | 17.982    | 2403.5490 | 2421.5310 |
|           | Ant1    | 2412.5         | 17.862    | 2403.6289 | 2421.4910 |
|           | Ant0    | 2414.5         | 18.182    | 2405.4690 | 2423.6508 |
|           | Ant1    | 2414.5         | 18.102    | 2405.5490 | 2423.6508 |
|           | Ant0    | 2437.5         | 18.462    | 2428.3092 | 2446.7707 |
|           | Ant1    | 2437.5         | 18.182    | 2428.4690 | 2446.6508 |
|           | Ant0    | 2462.5         | 18.501    | 2452.9895 | 2471.4910 |
|           | Ant1    | 2462.5         | 18.142    | 2453.2692 | 2471.4111 |
| SRD 40M   | Ant0    | 2422.5         | 32.527    | 2406.5160 | 2439.0435 |
|           | Ant1    | 2422.5         | 32.687    | 2406.4361 | 2439.1234 |
|           | Ant0    | 2432.5         | 32.687    | 2416.2762 | 2448.9635 |
|           | Ant1    | 2432.5         | 32.607    | 2416.3561 | 2448.9635 |
|           | Ant0    | 2435.5         | 33.007    | 2419.1164 | 2452.1234 |
|           | Ant1    | 2435.5         | 32.767    | 2419.2762 | 2452.0435 |
|           | Ant0    | 2437.5         | 33.407    | 2420.8766 | 2454.2832 |
|           | Ant1    | 2437.5         | 33.566    | 2420.8766 | 2454.4431 |
|           | Ant0    | 2452.5         | 32.927    | 2435.5569 | 2468.4840 |
|           | Ant1    | 2452.5         | 32.767    | 2435.7967 | 2468.5639 |
| SRD 60M   | Ant0    | 2432.5         | 52.627    | 2406.4860 | 2459.1134 |
|           | Ant1    | 2432.5         | 52.627    | 2406.4860 | 2459.1134 |
|           | Ant0    | 2433.5         | 52.627    | 2407.4860 | 2460.1134 |
|           | Ant1    | 2433.5         | 52.627    | 2407.3661 | 2459.9935 |
|           | Ant0    | 2435.5         | 52.747    | 2409.3661 | 2462.1134 |
|           | Ant1    | 2435.5         | 52.627    | 2409.3661 | 2461.9935 |
|           | Ant0    | 2437.5         | 53.227    | 2411.0065 | 2464.2333 |
|           | Ant1    | 2437.5         | 53.347    | 2411.0065 | 2464.3531 |
|           | Ant0    | 2442.5         | 53.227    | 2415.5270 | 2468.7537 |
|           | Ant1    | 2442.5         | 52.987    | 2415.7667 | 2468.7537 |


### 11.2.2. Test Graphs




SRD 10M\_Ant0\_2407.5




SRD 10M\_Ant1\_2407.5



SRD 10M\_Ant0\_2409.5




SRD 10M\_Ant1\_2409.5




SRD 10M\_Ant0\_2410.5



SRD 10M\_Ant1\_2410.5




SRD 10M\_Ant0\_2437.5




SRD 10M\_Ant1\_2437.5




SRD 10M\_Ant0\_2467.5




SRD 10M\_Ant1\_2467.5




SRD 20M\_Ant0\_2412.5




SRD 20M\_Ant1\_2412.5






SRD 20M\_Ant0\_2414.5




SRD 20M\_Ant1\_2414.5




SRD 20M\_Ant0\_2437.5






SRD 40M\_Ant0\_2422.5



SRD 40M\_Ant1\_2422.5



SRD 40M\_Ant0\_2432.5