



**SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park,  
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
Email: ee.shenzhen@sgs.com

Report No.: SZEM180500417703  
Page: 1 of 88

## TEST REPORT

**Application No.:** SZEM1805004177CR  
**Applicant:** SZ DJI TECHNOLOGY CO., LTD  
**Address of Applicant:** 14th floor, West Wing, Skyworth Semiconductor Design Building NO.18  
Gaoxin South 4th Ave, Nanshan District, Shenzhen, China  
**Manufacturer:** SZ DJI TECHNOLOGY CO., LTD  
**Address of Manufacturer:** 14th floor, West Wing, Skyworth Semiconductor Design Building NO.18  
Gaoxin South 4th Ave, Nanshan District, Shenzhen, China  
**Factory:** SZ DJI TECHNOLOGY CO., LTD  
**Address of Factory:** 14th floor, West Wing, Skyworth Semiconductor Design Building NO.18  
Gaoxin South 4th Ave, Nanshan District, Shenzhen, China  
**Equipment Under Test (EUT):**  
**EUT Name:** C2  
**Model No.:** RC1A  
**Trade mark:** DJI  
**FCC ID:** SS3-RC1A1805  
**IC:** 11805A-RC1A1805  
**Standard(s) :** 47 CFR Part 15, Subpart E 15.407  
RSS-Gen Issue 5, April 2018  
RSS-247 Issue 2, February 2017  
**Date of Receipt:** 2018-05-18  
**Date of Test:** 2018-05-25 to 2018-05-28  
**Date of Issue:** 2018-06-15

<b>Test Result:</b>	<b>Pass*</b>
---------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu  
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



<i>Revision Record</i>				
<i>Version</i>	<i>Chapter</i>	<i>Date</i>	<i>Modifier</i>	<i>Remark</i>
01		2018-06-15		Original

Authorized for issue by:			
			
	<hr/>		
	Hank Yan /Project Engineer		
			
	<hr/>		
	Eric Fu /Reviewer		

## 2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart E 15.407; RSS-Gen	N/A	47 CFR Part 15, Subpart C 15.203; RSS-Gen Section 6.8	Pass
Transmission in the Absence of Data	47 CFR Part 15, Subpart E 15.407; RSS-247	N/A	47 CFR Part 15, Subpart E 15.407 (c); RSS-247 Section 6.4(a)	Pass

N/A: Not applicable

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart E 15.407; RSS-Gen	ANSI C63.10 Section 6.2	47 CFR Part 15, 15.207 & 15.407 b(6); RSS-Gen Section 8.8	Pass
99% Bandwidth	47 CFR Part 15, Subpart E 15.407; RSS-Gen	ANSI C63.10 Section 6.9.3	RSS-Gen Section 6.7	Pass
Minimum 6 dB bandwidth (5.725-5.85 GHz band )	47 CFR Part 15, Subpart E 15.407; RSS-247	KDB 789033 D02 Section C.2	47 CFR Part 15, Subpart E 15.407 (e); RSS-247 Section 6.2.4	Pass
Maximum Conducted output power	47 CFR Part 15, Subpart E 15.407; RSS-247	ANSI C63.10 Section 12.3	47 CFR Part 15, Subpart E 15.407 (a); RSS-247 Section 6.2	Pass
Peak Power spectrum density	47 CFR Part 15, Subpart E 15.407; RSS-247	ANSI C63.10 Section 12.5	47 CFR Part 15, Subpart E 15.407 (a); RSS-247 Section 6.2	Pass
Radiated Emissions	47 CFR Part 15, Subpart E 15.407; RSS-247	ANSI C63.10 Section 12.7.3	47 CFR Part 15, Subpart E 15.209 & 15.407(b) ; RSS-247 Section 3.3 & 6.2 & RSS-Gen Section 8.9	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart E 15.407; RSS-247	ANSI C63.10 Section 12.7.2	47 CFR Part 15, Subpart E 15.209 & 15.407(b); RSS-247 Section 3.3 & RSS-Gen Section 8.9	Pass
Frequency Stability	47 CFR Part 15, Subpart E 15.407	ANSI C63.10 (2013) Section 6.8	47 CFR Part 15, Subpart C 15.407 (g)	Pass

N/A: Not applicable



### 3 Contents

	Page
<b>1 COVER PAGE</b> .....	<b>1</b>
<b>2 TEST SUMMARY</b> .....	<b>3</b>
<b>3 CONTENTS</b> .....	<b>4</b>
<b>4 GENERAL INFORMATION</b> .....	<b>6</b>
4.1 DETAILS OF E.U.T. ....	6
4.2 DESCRIPTION OF SUPPORT UNITS .....	8
4.3 MEASUREMENT UNCERTAINTY .....	9
4.4 TEST LOCATION.....	10
4.5 TEST FACILITY.....	10
4.6 DEVIATION FROM STANDARDS.....	10
4.7 ABNORMALITIES FROM STANDARD CONDITIONS .....	10
<b>5 EQUIPMENT LIST</b> .....	<b>11</b>
<b>6 RADIO SPECTRUM TECHNICAL REQUIREMENT</b> .....	<b>14</b>
6.1 ANTENNA REQUIREMENT .....	14
6.1.1 <i>Test Requirement:</i> .....	14
6.1.2 <i>Conclusion</i> .....	14
6.2 TRANSMISSION IN THE ABSENCE OF DATA.....	15
6.2.1 <i>Test Requirement:</i> .....	15
6.2.2 <i>Conclusion</i> .....	15
<b>7 RADIO SPECTRUM MATTER TEST RESULTS</b> .....	<b>16</b>
7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ).....	16
7.1.1 <i>E.U.T. Operation</i> .....	16
7.1.2 <i>Test Setup Diagram</i> .....	16
7.1.3 <i>Measurement Procedure and Data</i> .....	17
7.2 99% BANDWIDTH .....	20
7.2.1 <i>E.U.T. Operation</i> .....	20
7.2.2 <i>Test Setup Diagram</i> .....	20
7.2.3 <i>Measurement Procedure and Data</i> .....	20
7.3 MINIMUM 6 DB BANDWIDTH (5.725-5.85 GHZ BAND ) .....	21
7.3.1 <i>E.U.T. Operation</i> .....	21
7.3.2 <i>Test Setup Diagram</i> .....	21
7.3.3 <i>Measurement Procedure and Data</i> .....	21
7.4 MAXIMUM CONDUCTED OUTPUT POWER.....	22
7.4.1 <i>E.U.T. Operation</i> .....	22
7.4.2 <i>Test Setup Diagram</i> .....	23
7.4.3 <i>Measurement Procedure and Data</i> .....	23
7.5 PEAK POWER SPECTRUM DENSITY.....	24
7.5.1 <i>E.U.T. Operation</i> .....	24
7.5.2 <i>Test Setup Diagram</i> .....	24
7.5.3 <i>Measurement Procedure and Data</i> .....	24
7.6 RADIATED EMISSIONS .....	25
7.6.1 <i>E.U.T. Operation</i> .....	25
7.6.2 <i>Test Setup Diagram</i> .....	26
7.6.3 <i>Measurement Procedure and Data</i> .....	27



7.7	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS .....	48
7.7.1	<i>E.U.T. Operation</i> .....	49
7.7.2	<i>Test Setup Diagram</i> .....	49
7.7.3	<i>Measurement Procedure and Data</i> .....	50
7.8	FREQUENCY STABILITY .....	63
<b>8</b>	<b>APPENDIX</b> .....	<b>64</b>
8.1	APPENDIX 15.407 .....	64



## 4 General Information

### 4.1 Details of E.U.T.

Power supply:	DC 3.83V Li-ion Battery
Operation Frequency:	1.4M BW: 5728.5MHz ~ 5846.5MHz; 10M BW: 5730.5MHz ~ 5844.5MHz; 20M BW: 5735.5MHz ~ 5839.5MHz
Number of Channels:	1.4M BW: 60; 10M BW: 115; 20M BW: 105
Modulation Type:	OFDM
Channel Spacing:	1.4M BW: 2MHz; 10M BW: 1MHz; 20M BW: 1MHz
Antenna Type:	PCB Antenna
Antenna Gain:	4dBi

Channel List for 1.4MHz BW							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5728.5	16	5758.5	31	5788.5	46	5818.5
2	5730.5	17	5760.5	32	5790.5	47	5820.5
3	5732.5	18	5762.5	33	5792.5	48	5822.5
4	5734.5	19	5764.5	34	5794.5	49	5824.5
5	5736.5	20	5766.5	35	5796.5	50	5826.5
6	5738.5	21	5768.5	36	5798.5	51	5828.5
7	5740.5	22	5770.5	37	5800.5	52	5830.5
8	5742.5	23	5772.5	38	5802.5	53	5832.5
9	5744.5	24	5774.5	39	5804.5	54	5834.5
10	5746.5	25	5776.5	40	5806.5	55	5836.5
11	5748.5	26	5778.5	41	5808.5	56	5838.5
12	5750.5	27	5780.5	42	5810.5	57	5840.5
13	5752.5	28	5782.5	43	5812.5	58	5842.5
14	5754.5	29	5784.5	44	5814.5	59	5844.5
15	5756.5	30	5786.5	45	5816.5	60	5846.5

Note: The highlight frequencies are chosen to do all of the test.



Channel List for 10MHz BW							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5730.5	30	5759.5	59	5788.5	88	5817.5
2	5731.5	31	5760.5	60	5789.5	89	5818.5
3	5732.5	32	5761.5	61	5790.5	90	5819.5
4	5733.5	33	5762.5	62	5791.5	91	5820.5
5	5734.5	34	5763.5	63	5792.5	92	5821.5
6	5735.5	35	5764.5	64	5793.5	93	5822.5
7	5736.5	36	5765.5	65	5794.5	94	5823.5
8	5737.5	37	5766.5	66	5795.5	95	5824.5
9	5738.5	38	5767.5	67	5796.5	96	5825.5
10	5739.5	39	5768.5	68	5797.5	97	5826.5
11	5740.5	40	5769.5	69	5798.5	98	5827.5
12	5741.5	41	5770.5	70	5799.5	99	5828.5
13	5742.5	42	5771.5	71	5800.5	100	5829.5
14	5743.5	43	5772.5	72	5801.5	101	5830.5
15	5744.5	44	5773.5	73	5802.5	102	5831.5
16	5745.5	45	5774.5	74	5803.5	103	5832.5
17	5746.5	46	5775.5	75	5804.5	104	5833.5
18	5747.5	47	5776.5	76	5805.5	105	5834.5
19	5748.5	48	5777.5	77	5806.5	106	5835.5
20	5749.5	49	5778.5	78	5807.5	107	5836.5
21	5750.5	50	5779.5	79	5808.5	108	5837.5
22	5751.5	51	5780.5	80	5809.5	109	5838.5
23	5752.5	52	5781.5	81	5810.5	110	5839.5
24	5753.5	53	5782.5	82	5811.5	111	5840.5
25	5754.5	54	5783.5	83	5812.5	112	5841.5
26	5755.5	55	5784.5	84	5813.5	113	5842.5
27	5756.5	56	5785.5	85	5814.5	114	5843.5
28	5757.5	57	5786.5	86	5815.5	115	5844.5
29	5758.5	58	5787.5	87	5816.5		

Note: The highlight frequencies are chosen to do all of the test.



Channel List for 20MHz BW							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5735.5	28	5762.5	55	5789.5	82	5816.5
2	5736.5	29	5763.5	56	5790.5	83	5817.5
3	5737.5	30	5764.5	57	5791.5	84	5818.5
4	5738.5	31	5765.5	58	5792.5	85	5819.5
5	5739.5	32	5766.5	59	5793.5	86	5820.5
6	5740.5	33	5767.5	60	5794.5	87	5821.5
7	5741.5	34	5768.5	61	5795.5	88	5822.5
8	5742.5	35	5769.5	62	5796.5	89	5823.5
9	5743.5	36	5770.5	63	5797.5	90	5824.5
10	5744.5	37	5771.5	64	5798.5	91	5825.5
11	5745.5	38	5772.5	65	5799.5	92	5826.5
12	5746.5	39	5773.5	66	5800.5	93	5827.5
13	5747.5	40	5774.5	67	5801.5	94	5828.5
14	5748.5	41	5775.5	68	5802.5	95	5829.5
15	5749.5	42	5776.5	69	5803.5	96	5830.5
16	5750.5	43	5777.5	70	5804.5	97	5831.5
17	5751.5	44	5778.5	71	5805.5	98	5832.5
18	5752.5	45	5779.5	72	5806.5	99	5833.5
19	5753.5	46	5780.5	73	5807.5	100	5834.5
20	5754.5	47	5781.5	74	5808.5	101	5835.5
21	5755.5	48	5782.5	75	5809.5	102	5836.5
22	5756.5	49	5783.5	76	5810.5	103	5837.5
23	5757.5	50	5784.5	77	5811.5	104	5838.5
24	5758.5	51	5785.5	78	5812.5	105	5839.5
25	5759.5	52	5786.5	79	5813.5		
26	5760.5	53	5787.5	80	5814.5		
27	5761.5	54	5788.5	81	5815.5		

Note: The highlight frequencies are chosen to do all of the test.

## 4.2 Description of Support Units

The EUT has been tested as an independent unit.

### 4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 2.84\text{dB}$
6	Conducted Spurious emissions	$\pm 0.75\text{dB}$
7	RF Radiated power	$\pm 4.5\text{dB}$ (below 1GHz)
		$\pm 4.8\text{dB}$ (above 1GHz)
8	Radiated Spurious emission test	$\pm 4.5\text{dB}$ (Below 1GHz)
		$\pm 4.8\text{dB}$ (Above 1GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Supply voltages	$\pm 1.5\%$
12	Time	$\pm 3\%$



#### **4.4 Test Location**

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

#### **4.5 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

#### **4.6 Deviation from Standards**

None

#### **4.7 Abnormalities from Standard Conditions**

None

## 5 Equipment List

<b>Conducted Emissions at AC Power Line (150kHz-30MHz)</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2017-05-10	2020-05-09
Measurement Software	AUDIX	e3 V5.4.1221d	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2017-07-13	2018-07-12
LISN	Rohde & Schwarz	ENV216	SEM007-01	2017-09-27	2018-09-26
LISN	ETS-LINDGREN	3816/2	SEM007-02	2018-04-02	2019-04-01
EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2018-04-02	2019-04-01

<b>99% Bandwidth</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-27	2018-09-26
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2017-07-13	2018-07-12
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26

<b>Minimum 6 dB bandwidth (5.725-5.85 GHz band )</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-27	2018-09-26
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2017-07-13	2018-07-12
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26

<b>Maximum Conducted output power</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-27	2018-09-26
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2017-07-13	2018-07-12
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26



<b>Peak Power spectrum density</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-27	2018-09-26
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2017-07-13	2018-07-12
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26

<b>RE in Chamber</b>						
<b>Item</b>	<b>Test Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Inventory No.</b>	<b>Cal. Date (yyyy-mm-dd)</b>	<b>Cal. Due date (yyyy-mm-dd)</b>
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2017-08-05	2020-08-04
2	MXE EMI Receiver (20Hz-8.4GHz)	Agilent Technologies	N9038A	SEM004-05	2017-09-27	2018-09-26
3	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-01	2017-06-27	2020-06-26
4	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEM005-01	2018-04-02	2019-04-01
5	Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
6	Coaxial Cable	SGS	N/A	SEM025-01	2017-07-13	2018-07-12

<b>Radiated Emissions which fall in the restricted bands</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2017-07-13	2018-07-12
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2018-04-02	2019-04-01
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017-06-27	2020-06-26
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Horn Antenna(15GHz-40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2017-09-27	2018-09-26
Low Noise Amplifier(100MHz-18GHz)	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2017-09-27	2018-09-27
Pre-amplifier(18-26GHz)	Rohde & Schwarz	CH14-H052	SEM005-17	2018-04-02	2019-04-01



# SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM180500417703

Page: 13 of 88

Pre-amplifier(26GHz-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2018-04-02	2019-04-01
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21
Band filter	N/A	N/A	SEM023-01	N/A	N/A

Frequency Stability					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-27	2018-09-26
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2017-07-13	2018-07-12
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2017-09-29	2018-09-28
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2018-04-08	2019-04-07

## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203; RSS-Gen Section 6.8

#### 6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

Refer to the EUT photos.

The antenna is integrated on the main PCB and no consideration of replacement. The best-case gain of the antenna is 4dBi. The product has two antennas, but only one antenna is used to transmit signal at any time. Pre-test was used to find out the worst case, and only the data of worst case is recorded in the report.



## **6.2 Transmission in the Absence of Data**

### **6.2.1 Test Requirement:**

47 CFR Part 15, Subpart E 15.407 (c); RSS-247 Section 6.4(a)

### **6.2.2 Conclusion**

Standard Requirement:

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Applicants shall include in their application for equipment authorization a description of how this requirement is met.

EUT Details:

RF chip (ACPD4GD31D3) support automatically discontinue transmission in case of either absence of information to transmit or operational failure, if the chip detects absence of information to transmit or operational failure, it will be automatically shut off.

## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, 15.207 & 15.407 b(6); RSS-Gen Section 8.8  
Test Method: ANSI C63.10 Section 6.2  
Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

#### 7.1.1 E.U.T. Operation


Operating Environment:

Temperature: 24.3 °C Humidity: 45.1 % RH Atmospheric Pressure: 1015 mbar

Pretest these modes to find the worst case:  
c:TX mode\_Keep the EUT in continuously transmitting mode with modulation.  
d: Charge + TX mode\_Keep the EUT in charging and continuously transmitting mode with modulation.

The worst case for final test: d: Charge + TX mode\_Keep the EUT in charging and continuously transmitting mode with modulation.

#### 7.1.2 Test Setup Diagram




### 7.1.3 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor

Pre-test was performed on each mode at the lowest, middle and highest channel, and found 1.4MHz BW mode at the middle channel is the worst case. So, only the data of that case is recorded in the report.


Mode:d; Line:Live Line



Site : Shielding Room  
 Condition: Line  
 Job No. : 04177CR  
 Test mode: d

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.15	0.02	9.51	20.45	29.98	55.96	-25.98	Average
2	0.15	0.02	9.51	39.87	49.40	65.96	-16.56	QP
3	0.17	0.02	9.52	19.51	29.05	54.81	-25.76	Average
4	0.17	0.02	9.52	38.51	48.05	64.81	-16.76	QP
5	0.20	0.03	9.50	17.50	27.03	53.71	-26.68	Average
6	0.20	0.03	9.50	35.57	45.10	63.71	-18.61	QP
7	0.21	0.03	9.50	13.08	22.61	53.23	-30.62	Average
8	0.21	0.03	9.50	32.14	41.67	63.23	-21.56	QP
9	0.24	0.03	9.51	14.08	23.62	52.26	-28.64	Average
10	0.24	0.03	9.51	31.57	41.11	62.26	-21.15	QP
11	0.27	0.03	9.51	12.03	21.57	51.12	-29.55	Average
12	0.27	0.03	9.51	28.03	37.57	61.12	-23.55	QP

Mode:d; Line:Neutral Line



Site : Shielding Room  
 Condition: Neutral  
 Job No. : 04177CR  
 Test mode: d

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.15	0.02	9.58	19.23	28.83	55.94	-27.11	Average
2	0.15	0.02	9.58	39.71	49.31	65.94	-16.63	QP
3	0.18	0.03	9.58	15.61	25.22	54.42	-29.20	Average
4	0.18	0.03	9.58	35.03	44.64	64.42	-19.78	QP
5	0.22	0.03	9.57	13.27	22.87	52.88	-30.01	Average
6	0.22	0.03	9.57	30.97	40.57	62.88	-22.31	QP
7	0.23	0.03	9.58	13.17	22.78	52.35	-29.57	Average
8	0.23	0.03	9.58	29.83	39.44	62.35	-22.91	QP
9	0.26	0.03	9.58	13.38	22.99	51.51	-28.52	Average
10	0.26	0.03	9.58	28.00	37.61	61.51	-23.90	QP
11	0.62	0.06	9.62	9.42	19.10	46.00	-26.90	Average
12	0.62	0.06	9.62	16.03	25.71	56.00	-30.29	QP


## 7.2 99% Bandwidth

Test Requirement RSS-Gen Section 6.7  
 Test Method: ANSI C63.10 Section 6.9.3

### 7.2.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.1 °C Humidity: 58.4 % RH Atmospheric Pressure: 1010 mbar  
 Test mode c:TX mode\_Keep the EUT in continuously transmitting mode with modulation.

### 7.2.2 Test Setup Diagram



### 7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.407


**7.3 Minimum 6 dB bandwidth (5.725-5.85 GHz band )**

Test Requirement 47 CFR Part 15, Subpart E 15.407 (e); RSS-247 Section 6.2.4  
 Test Method: KDB 789033 D02 II C 2  
 Limit:  $\geq 500$  kHz

**7.3.1 E.U.T. Operation**

Operating Environment:  
 Temperature: 25.1 °C Humidity: 58.2 % RH Atmospheric Pressure: 1010 mbar  
 Test mode c:TX mode\_Keep the EUT in continuously transmitting mode with modulation.

**7.3.2 Test Setup Diagram**



**7.3.3 Measurement Procedure and Data**

The detailed test data see: Appendix 15.407



## 7.4 Maximum Conducted output power

Test Requirement 47 CFR Part 15, Subpart E 15.407 (a); RSS-247 Section 6.2

Test Method: ANSI C63.10 Section 12.3

Limit:

### Frequency band(MHz) Limit (FCC)

5150-5250 Conducted power  $\leq 1W(30dBm)$  for master device  
Conducted power  $\leq 250mW(24dBm)$  for client device

5250-5350 Conducted power  $\leq 250mW(24dBm)$  or  $11dBm+10\log B^*$

5470-5725 Conducted power  $\leq 250mW(24dBm)$  or  $11dBm+10\log B^*$

5725-5850 Conducted power  $\leq 1W(30dBm)$

Remark: \* Where B is the 26dB emission bandwidth in MHz.

### Frequency band(MHz) Limit (Canada IC)

5150-5250 e.i.r.p.  $\leq 200mW(23dBm)$  or  $10 + 10\log B^*$

5250-5350 Conducted power  $\leq 250mW(24dBm)$  or  $11dBm+10\log B^*$   
e.i.r.p.  $\leq 1W(30dBm)$  or  $17 + 10\log B^*$

5470-5725 Conducted power  $\leq 250mW(24dBm)$  or  $11dBm+10\log B^*$   
e.i.r.p.  $\leq 1W(30dBm)$  or  $17 + 10\log B^*$

5725-5850 Conducted power  $\leq 1W(30dBm)$

Remark: \* Where B is the 99% emission bandwidth in MHz.


### 7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 25.1 °C Humidity: 58.2 % RH Atmospheric Pressure: 1010 mbar

Test mode c:TX mode\_Keep the EUT in continuously transmitting mode with modulation.

### 7.4.2 Test Setup Diagram



### 7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.407

### 7.5 Peak Power spectrum density

Test Requirement 47 CFR Part 15, Subpart E 15.407 (a); RSS-247 Section 6.2  
 Test Method: ANSI C63.10 Section 12.5  
 Limit:


Frequency band(MHz)	Limit
5150-5250	≤ 17dBm/MHz for master device (FCC) ≤ 11dBm/MHz for client device (FCC) e.i.r.p. spectral density ≤ 10dBm/MHz (IC)
5250-5350	≤ 11dBm/MHz
5470-5725	≤ 11dBm/MHz
5725-5850	≤ 30dBm/500kHz

#### 7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 25.1 °C Humidity: 58.3 % RH Atmospheric Pressure: 1010 mbar  
 Test mode c:TX mode\_Keep the EUT in continuously transmitting mode with modulation.

#### 7.5.2 Test Setup Diagram



#### 7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.407




## 7.6 Radiated Emissions

Test Requirement	47 CFR Part 15, Subpart E 15.209 & 15.407(b) ; RSS-247 Section 3.3 & 6.2 & RSS-Gen Section 8.9
Test Method:	ANSI C63.10 Section 12.7.3
Measurement Distance:	3m
Limit:	
For transmitters operating in the 5.15-5.25 GHz band:	All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
For transmitters operating in the 5.25-5.35 GHz band:	All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
For transmitters operating in the 5.47-5.725 GHz band:	All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
For transmitters operating in the 5.725-5.85 GHz band:	(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

### 7.6.1 E.U.T. Operation

Operating Environment:	
Temperature:	24.8 °C
Humidity:	47.4 % RH
Atmospheric Pressure:	1015 mbar
Pretest these modes to find the worst case:	c:TX mode_Keep the EUT in continuously transmitting mode with modulation. d: Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with modulation.
The worst case for final test:	d: Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with modulation.

**7.6.2 Test Setup Diagram**



### 7.6.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

1.  $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamp Factor}$
2. For emission below 1GHz, pre-test was performed on each mode at the lowest, middle and highest channel, and found 1.4MHz BW mode at the middle channel is the worst case. So, only the data of that case is recorded in the report.
3. Scan from 9kHz to 40GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
4. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

**30MHz~1GHz**

QP value:

Mode:d; Polarization:Horizontal




Condition: 3m HORIZONTAL

Job No. : 04177CR

Test mode: d

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	145.35	1.31	14.21	27.52	41.92	29.92	43.50	-13.58
2	pp 203.52	1.42	16.63	27.53	42.42	32.94	43.50	-10.56
3	249.43	1.67	18.94	27.53	33.16	26.24	46.00	-19.76
4	483.91	2.54	24.28	27.86	26.36	25.32	46.00	-20.68
5	701.76	2.91	27.91	27.55	27.33	30.60	46.00	-15.40
6	935.55	3.64	29.98	26.96	24.32	30.98	46.00	-15.02

Mode:d; Polarization:Vertical




Condition: 3m VERTICAL  
 Job No. : 04177CR  
 Test mode: d

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	53.32	0.80	13.85	27.59	34.13	21.19	40.00	-18.81
2	124.13	1.26	13.23	27.52	34.20	21.17	43.50	-22.33
3	146.37	1.31	14.30	27.52	33.70	21.79	43.50	-21.71
4	196.51	1.39	16.40	27.53	34.69	24.95	43.50	-18.55
5	654.23	2.81	27.33	27.62	25.76	28.28	46.00	-17.72
6 pp	906.48	3.61	29.83	27.06	24.74	31.12	46.00	-14.88



Above 1GHz

Mode:d; Polarization:Horizontal; Bandwidth:1.4MHz; Channel:5728.5MHz




Condition: 3m HORIZONTAL  
Job No : 04177CR  
Mode : 5728.5 TX RSE  
Note : 1.4M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1227.791	4.53	24.71	41.21	46.90	34.93	74.00	-39.07	peak
2	1597.181	5.35	26.24	41.47	48.77	38.89	74.00	-35.11	peak
3	4482.150	7.54	33.57	42.41	48.05	46.75	74.00	-27.25	peak
4	8917.462	10.38	37.17	38.74	42.42	51.23	74.00	-22.77	peak
5	11457.000	12.10	37.89	38.17	38.58	50.40	74.00	-23.60	peak
6	pp17185.500	16.29	42.71	40.44	34.14	52.70	74.00	-21.30	peak



Mode:d; Polarization:Vertical; Bandwidth:1.4MHz; Channel:5728.5MHz




Condition: 3m VERTICAL  
Job No : 04177CR  
Mode : 5728.5 TX RSE  
Note : 1.4M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Line	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1199.726	4.42	24.59	41.18	49.18	37.01	74.00	-36.99 peak
2	1597.181	5.35	26.24	41.47	47.72	37.84	74.00	-36.16 peak
3	4329.354	7.37	33.30	42.39	48.25	46.53	74.00	-27.47 peak
4	8840.473	10.36	37.14	38.86	43.32	51.96	74.00	-22.04 peak
5	11457.000	12.10	37.89	38.17	38.71	50.53	74.00	-23.47 peak
6	pp17185.500	16.29	42.71	40.44	34.38	52.94	74.00	-21.06 peak



Mode:d; Polarization:Horizontal; Bandwidth:1.4MHz; Channel:5788.5MHz




Condition: 3m HORIZONTAL  
Job No : 04177CR  
Mode : 5788.5 TX RSE  
Note : 1.4M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	
1	1242.068	4.58	24.78	41.22	44.10	32.24	74.00	-41.76 peak
2	1542.733	5.42	26.00	41.43	44.94	34.93	74.00	-39.07 peak
3	4316.859	7.36	33.28	42.38	46.92	45.18	74.00	-28.82 peak
4	7898.049	9.96	36.62	40.26	44.23	50.55	74.00	-23.45 peak
5	11575.000	12.17	37.87	38.24	37.86	49.66	74.00	-24.34 peak
6	pp17362.500	15.90	42.82	40.59	34.38	52.51	74.00	-21.49 peak



Mode:d; Polarization:Vertical; Bandwidth:1.4MHz; Channel:5788.5MHz




Condition: 3m VERTICAL  
Job No : 04177CR  
Mode : 5788.5 TX RSE  
Note : 1.4M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	
1	1278.492	4.72	24.93	41.25	44.94	33.34	74.00	-40.66 peak
2	1692.231	5.24	26.64	41.53	46.78	37.13	74.00	-36.87 peak
3	4443.453	7.50	33.50	42.41	47.48	46.07	74.00	-27.93 peak
4	8969.161	10.39	37.19	38.66	41.50	50.42	74.00	-23.58 peak
5	11575.000	12.17	37.87	38.24	36.65	48.45	74.00	-25.55 peak
6	pp17362.500	15.90	42.82	40.59	34.28	52.41	74.00	-21.59 peak



Mode:d; Polarization:Horizontal; Bandwidth:1.4MHz; Channel:5846.5MHz




Condition: 3m HORIZONTAL  
Job No : 04177CR  
Mode : 5846.5 TX RSE  
Note : 1.4M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1206.682	4.44	24.62	41.19	45.40	33.27	74.00	-40.73	peak
2	1639.274	5.30	26.42	41.49	47.15	37.38	74.00	-36.62	peak
3	4430.628	7.48	33.48	42.41	47.18	45.73	74.00	-28.27	peak
4	8738.852	10.33	37.10	39.01	42.56	50.98	74.00	-23.02	peak
5	11693.000	12.21	37.82	38.32	38.32	50.03	74.00	-23.97	peak
6	pp17539.500	15.64	42.95	40.73	35.44	53.30	74.00	-20.70	peak



Mode:d; Polarization:Vertical; Bandwidth:1.4MHz; Channel:5846.5MHz




Condition: 3m VERTICAL  
Job No : 04177CR  
Mode : 5846.5 TX RSE  
Note : 1.4M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1278.492	4.72	24.93	41.25	44.94	33.34	74.00	-40.66	peak
2	1692.231	5.24	26.64	41.53	46.78	37.13	74.00	-36.87	peak
3	4367.058	7.41	33.37	42.39	47.92	46.31	74.00	-27.69	peak
4	8563.818	10.29	37.03	39.28	42.68	50.72	74.00	-23.28	peak
5	11693.000	12.21	37.82	38.32	38.83	50.54	74.00	-23.46	peak
6	pp17539.500	15.64	42.95	40.73	34.25	52.11	74.00	-21.89	peak



Mode:d; Polarization:Horizontal; Bandwidth:10MHz; Channel:5730.5MHz




Condition: 3m HORIZONTAL  
Job No : 04177CR  
Mode : 5730.5 TX RSE  
Note : 10M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1231.345	4.54	24.63	38.07	44.81	35.91	74.00	-38.09	peak
2	1692.231	5.24	26.64	38.02	44.35	38.21	74.00	-35.79	peak
3	4242.641	7.27	33.60	38.13	47.50	50.24	74.00	-23.76	peak
4	7035.727	10.12	36.49	37.27	41.95	51.29	74.00	-22.71	peak
5	11461.000	12.10	38.07	35.97	34.73	48.93	74.00	-25.07	peak
6	pp17191.500	16.28	43.03	36.20	30.19	53.30	74.00	-20.70	peak



Mode:d; Polarization:Vertical; Bandwidth:10MHz; Channel:5730.5MHz




Condition: 3m VERTICAL  
Job No : 04177CR  
Mode : 5730.5 TX RSE  
Note : 10M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1168.920	4.29	24.32	38.08	44.95	35.48	74.00	-38.52	peak
2	1629.825	5.31	26.38	38.03	46.14	39.80	74.00	-34.20	peak
3	4316.859	7.36	33.60	38.17	47.54	50.33	74.00	-23.67	peak
4	7829.860	9.97	36.50	36.54	41.22	51.15	74.00	-22.85	peak
5	11461.000	12.10	38.07	35.97	35.88	50.08	74.00	-23.92	peak
6	pp17191.500	16.28	43.03	36.20	30.43	53.54	74.00	-20.46	peak



Mode:d; Polarization:Horizontal; Bandwidth:10MHz; Channel:5787.5MHz




Condition: 3m HORIZONTAL  
Job No : 04177CR  
Mode : 5787.5 TX RSE  
Note : 10M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1242.068	4.58	24.68	38.07	44.75	35.94	74.00	-38.06	peak
2	1687.347	5.24	26.62	38.02	45.36	39.20	74.00	-34.80	peak
3	4316.859	7.36	33.60	38.17	47.21	50.00	74.00	-24.00	peak
4	7898.049	9.96	36.54	36.49	41.41	51.42	74.00	-22.58	peak
5	11575.000	12.17	38.18	36.10	35.93	50.18	74.00	-23.82	peak
6	pp17362.500	15.90	43.24	36.12	29.56	52.58	74.00	-21.42	peak



Mode:d; Polarization:Vertical; Bandwidth:10MHz; Channel:5787.5MHz




Condition: 3m VERTICAL  
Job No : 04177CR  
Mode : 5787.5 TX RSE  
Note : 10M ANT0

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1217.190	4.49	24.56	38.07	46.44	37.42	74.00	-36.58 peak
2	1687.347	5.24	26.62	38.02	45.05	38.89	74.00	-35.11 peak
3	3958.309	6.94	33.49	38.00	47.42	49.85	74.00	-24.15 peak
4	8969.161	10.39	36.56	35.43	39.77	51.29	74.00	-22.71 peak
5	11575.000	12.17	38.18	36.10	34.54	48.79	74.00	-25.21 peak
6	pp17362.500	15.90	43.24	36.12	29.54	52.56	74.00	-21.44 peak



Mode:d; Polarization:Horizontal; Bandwidth:10MHz; Channel:5844.5MHz




Condition: 3m HORIZONTAL  
Job No : 04177CR  
Mode : 5844.5 TX RSE  
Note : 10M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1227.791	4.53	24.61	38.07	44.49	35.56	74.00	-38.44	peak
2	1611.091	5.34	26.30	38.03	44.97	38.58	74.00	-35.42	peak
3	4495.125	7.55	33.60	38.26	46.93	49.82	74.00	-24.18	peak
4	7943.838	9.96	36.57	36.45	41.17	51.25	74.00	-22.75	peak
5	11689.000	12.21	38.29	36.24	35.96	50.22	74.00	-23.78	peak
6	pp17533.500	15.64	43.46	36.03	29.40	52.47	74.00	-21.53	peak



Mode:d; Polarization:Vertical; Bandwidth:10MHz; Channel:5844.5MHz




Condition: 3m VERTICAL  
Job No : 04177CR  
Mode : 5844.5 TX RSE  
Note : 10M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1227.791	4.53	24.61	38.07	44.91	35.98	74.00	-38.02	peak
2	1677.621	5.25	26.58	38.03	44.95	38.75	74.00	-35.25	peak
3	4443.453	7.50	33.60	38.24	47.41	50.27	74.00	-23.73	peak
4	7015.420	10.13	36.49	37.29	41.58	50.91	74.00	-23.09	peak
5	11689.000	12.21	38.29	36.24	36.68	50.94	74.00	-23.06	peak
6	pp17533.500	15.64	43.46	36.03	28.95	52.02	74.00	-21.98	peak



Mode:d; Polarization:Horizontal; Bandwidth:20MHz; Channel:5735.5MHz




Condition: 3m HORIZONTAL  
Job No : 04177CR  
Mode : 5735.5 TX RSE  
Note : 20M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Line	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1192.811	4.39	24.44	38.07	45.99	36.75	74.00	-37.25 peak
2	1697.129	5.23	26.66	38.02	44.50	38.37	74.00	-35.63 peak
3	4430.628	7.48	33.60	38.23	46.42	49.27	74.00	-24.73 peak
4	8713.630	10.33	36.26	35.67	40.20	51.12	74.00	-22.88 peak
5	11471.000	12.11	38.08	35.98	35.69	49.90	74.00	-24.10 peak
6	pp17206.500	16.25	43.05	36.19	29.83	52.94	74.00	-21.06 peak



Mode:d; Polarization:Vertical; Bandwidth:20MHz; Channel:5735.5MHz




Condition: 3m VERTICAL  
Job No : 04177CR  
Mode : 5735.5 TX RSE  
Note : 20M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1282.193	4.73	24.87	38.06	45.06	36.60	74.00	-37.40	peak
2	1687.347	5.24	26.62	38.02	45.38	39.22	74.00	-34.78	peak
3	4392.376	7.44	33.60	38.21	47.32	50.15	74.00	-23.85	peak
4	8840.473	10.36	36.41	35.55	39.39	50.61	74.00	-23.39	peak
5	11471.000	12.11	38.08	35.98	35.39	49.60	74.00	-24.40	peak
6	pp17206.500	16.25	43.05	36.19	29.49	52.60	74.00	-21.40	peak



Mode:d; Polarization:Horizontal; Bandwidth:20MHz; Channel:5787.5MHz




Condition: 3m HORIZONTAL  
Job No : 04177CR  
Mode : 5787.5 TX RSE  
Note : 20M ANT0

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1234.909	4.55	24.65	38.07	44.30	35.43	74.00	-38.57 peak
2	1511.833	5.46	25.85	38.04	45.29	38.56	74.00	-35.44 peak
3	3946.885	6.93	33.46	38.00	47.51	49.90	74.00	-24.10 peak
4	7263.015	10.06	36.39	37.05	41.68	51.08	74.00	-22.92 peak
5	11575.000	12.17	38.18	36.10	34.64	48.89	74.00	-25.11 peak
6	pp17362.500	15.90	43.24	36.12	29.47	52.49	74.00	-21.51 peak



Mode:d; Polarization:Vertical; Bandwidth:20MHz; Channel:5787.5MHz




Condition: 3m VERTICAL  
Job No : 04177CR  
Mode : 5787.5 TX RSE  
Note : 20M ANT0

	Freq	Cable Loss	Ant Factor	Preamplifier	Read Level	Limit Level	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1300.858	4.80	24.96	38.06	44.88	36.58	74.00	-37.42 peak
2	1653.550	5.28	26.48	38.03	45.07	38.80	74.00	-35.20 peak
3	4169.698	7.18	33.60	38.09	47.25	49.94	74.00	-24.06 peak
4	7829.860	9.97	36.50	36.54	42.20	52.13	74.00	-21.87 peak
5	11575.000	12.17	38.18	36.10	35.40	49.65	74.00	-24.35 peak
6	pp17362.500	15.90	43.24	36.12	29.92	52.94	74.00	-21.06 peak



Mode:d; Polarization:Horizontal; Bandwidth:20MHz; Channel:5839.5MHz




Condition: 3m HORIZONTAL  
Job No : 04177CR  
Mode : 5839.5 TX RSE  
Note : 20M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1206.682	4.44	24.51	38.07	45.32	36.20	74.00	-37.80	peak
2	1644.019	5.30	26.44	38.03	45.39	39.10	74.00	-34.90	peak
3	4430.628	7.48	33.60	38.23	48.39	51.24	74.00	-22.76	peak
4	7650.888	9.98	36.39	36.70	41.66	51.33	74.00	-22.67	peak
5	11679.000	12.21	38.28	36.23	36.25	50.51	74.00	-23.49	peak
6	pp17518.500	15.62	43.43	36.04	29.64	52.65	74.00	-21.35	peak



Mode:d; Polarization:Vertical; Bandwidth:20MHz; Channel:5839.5MHz



Condition: 3m VERTICAL  
Job No : 04177CR  
Mode : 5839.5 TX RSE  
Note : 20M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1300.858	4.80	24.96	38.06	44.87	36.57	74.00	-37.43	peak
2	1597.181	5.35	26.24	38.03	45.16	38.72	74.00	-35.28	peak
3	4443.453	7.50	33.60	38.24	48.48	51.34	74.00	-22.66	peak
4	7966.832	9.95	36.58	36.43	41.17	51.27	74.00	-22.73	peak
5	pp11679.000	12.21	38.28	36.23	38.63	52.89	74.00	-21.11	peak
6	17518.500	15.62	43.43	36.04	29.61	52.62	74.00	-21.38	peak



## 7.7 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart E 15.209 & 15.407(b); RSS-247 Section 3.3 & RSS-Gen Section 8.9  
Test Method: ANSI C63.10 Section 12.7.2  
Measurement Distance: 3m  
Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

### 7.7.1 E.U.T. Operation


Operating Environment:

Temperature: 25.6 °C      Humidity: 56.3 % RH      Atmospheric Pressure: 1010 mbar

Pretest these modes to find the worst case:  
 c:TX mode\_Keep the EUT in continuously transmitting mode with modulation.  
 d: Charge + TX mode\_Keep the EUT in charging and continuously transmitting mode with modulation.

The worst case for final test:  
 c:TX mode\_Keep the EUT in continuously transmitting mode with modulation.

### 7.7.2 Test Setup Diagram




### **7.7.3 Measurement Procedure and Data**

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor



Mode:c; Polarization:Horizontal; Bandwidth:1.4MHz; Channel:5728.5MHz




Condition: 3m HORIZONTAL  
Job No : 04177CR  
Mode : 5728.5 Band edge  
Note : 1.4M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5715.000	9.61	34.82	41.85	58.77	61.35	109.40	-48.05	peak
2	5725.000	9.64	34.83	41.84	59.73	62.36	122.20	-59.84	peak
3 pp	5728.500	9.65	34.83	41.83	110.19	112.84	125.20	-12.36	peak



Mode:c; Polarization:Vertical; Bandwidth:1.4MHz; Channel:5728.5MHz




Condition: 3m VERTICAL  
Job No : 04177CR  
Mode : 5728.5 Band edge  
Note : 1.4M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5715.000	9.61	34.82	41.85	59.74	62.32	109.40	-47.08	peak
2	5725.000	9.64	34.83	41.84	70.03	72.66	122.20	-49.54	peak
3 pp	5728.500	9.65	34.83	41.83	121.65	124.30	125.20	-0.90	peak



Mode:c; Polarization:Horizontal; Bandwidth:1.4MHz; Channel:5846.5MHz




Condition: 3m HORIZONTAL  
Job No : 04177CR  
Mode : 5846.5 Band edge  
Note : 1.4M ANT0

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 5846.500	10.06	34.95	41.73	108.65	111.93	125.20	-13.27	peak
2	5850.000	10.07	34.95	41.73	59.65	62.94	122.20	-59.26	peak
3	5860.000	10.10	34.96	41.72	58.52	61.86	109.40	-47.54	peak



Mode:c; Polarization:Vertical; Bandwidth:1.4MHz; Channel:5846.5MHz




Condition: 3m VERTICAL  
Job No : 04177CR  
Mode : 5846.5 Band edge  
Note : 1.4M ANT0

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp 5846.500	10.06	34.95	41.73	121.10	124.38	125.20	-0.82 peak
2	5850.000	10.07	34.95	41.73	69.25	72.54	122.20	-49.66 peak
3	5860.000	10.10	34.96	41.72	61.71	65.05	109.40	-44.35 peak




Mode:c; Polarization:Horizontal; Bandwidth:10MHz; Channel:5730.5MHz



Condition: 3m HORIZONTAL  
Job No : 04177CR  
Mode : 5730.5 Band edge  
Note : 10M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5715.000	9.61	34.82	41.85	57.34	59.92	109.40	-49.48	peak
2	5725.000	9.64	34.83	41.84	84.39	87.02	122.20	-35.18	peak
3 pp	5730.500	9.66	34.84	41.83	102.24	104.91	125.20	-20.29	peak

Mode:c; Polarization:Vertical; Bandwidth:10MHz; Channel:5730.5MHz




Condition: 3m VERTICAL  
 Job No : 04177CR  
 Mode : 5730.5 Band edge  
 Note : 10M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5715.000	9.61	34.82	41.85	61.76	64.34	109.40	-45.06	peak
2	5725.000	9.64	34.83	41.84	100.08	102.71	122.20	-19.49	peak
3 pp	5730.500	9.66	34.84	41.83	117.16	119.83	125.20	-5.37	peak



Mode:c; Polarization:Horizontal; Bandwidth:10MHz; Channel:5844.5MHz




Condition: 3m HORIZONTAL  
Job No : 04177CR  
Mode : 5844.5 Band edge  
Note : 10M ANT0

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 5844.500	10.05	34.95	41.74	103.16	106.42	125.20	-18.78	peak
2	5850.000	10.07	34.95	41.73	81.19	84.48	122.20	-37.72	peak
3	5860.000	10.10	34.96	41.72	60.30	63.64	109.40	-45.76	peak



Mode:c; Polarization:Vertical; Bandwidth:10MHz; Channel:5844.5MHz




Condition: 3m VERTICAL  
Job No : 04177CR  
Mode : 5844.5 Band edge  
Note : 10M ANT0

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 5844.500	10.05	34.95	41.74	116.83	120.09	125.20	-5.11	peak
2	5850.000	10.07	34.95	41.73	94.67	97.96	122.20	-24.24	peak
3	5860.000	10.10	34.96	41.72	71.23	74.57	109.40	-34.83	peak



Mode:c; Polarization:Horizontal; Bandwidth:20MHz; Channel:5735.5MHz




Condition: 3m HORIZONTAL  
Job No : 04177CR  
Mode : 5735.5 Band edge  
Note : 20M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5715.000	9.61	34.82	41.85	61.58	64.16	109.40	-45.24	peak
2	5725.000	9.64	34.83	41.84	70.51	73.14	122.20	-49.06	peak
3 pp	5735.500	9.68	34.84	41.83	100.73	103.42	125.20	-21.78	peak



Mode:c; Polarization:Vertical; Bandwidth:20MHz; Channel:5735.5MHz




Condition: 3m VERTICAL  
Job No : 04177CR  
Mode : 5735.5 Band edge  
Note : 20M ANT0

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5715.000	9.61	34.82	41.85	71.98	74.56	109.40	-34.84	peak
2	5725.000	9.64	34.83	41.84	83.15	85.78	122.20	-36.42	peak
3 pp	5735.500	9.68	34.84	41.83	116.69	119.38	125.20	-5.82	peak



Mode:c; Polarization:Horizontal; Bandwidth:20MHz; Channel:5839.5MHz




Condition: 3m HORIZONTAL  
Job No : 04177CR  
Mode : 5839.5 Band edge  
Note : 20M ANT0

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 5839.500	10.37	35.04	41.66	101.53	105.28	68.20	37.08	peak
2	5850.000	10.07	34.95	41.73	71.39	74.68	122.20	-47.52	peak
3	5860.000	10.10	34.96	41.72	63.62	66.96	109.40	-42.44	peak



Mode:c; Polarization:Vertical; Bandwidth:20MHz; Channel:5839.5MHz



Condition: 3m VERTICAL  
Job No : 04177CR  
Mode : 5839.5 Band edge  
Note : 20M ANT0

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 5839.500	10.03	34.94	41.74	114.67	117.90	125.20	-7.30	peak
2	5850.000	10.07	34.95	41.73	88.12	91.41	122.20	-30.79	peak
3	5860.000	10.10	34.96	41.72	83.24	86.58	109.40	-22.82	peak



## **7.8 Frequency Stability**

Test Requirement	47 CFR Part 15, Subpart C 15.407 (g)
Test Method:	ANSI C63.10 (2013) Section 6.8
Limit:	The frequency tolerance shall be maintained within the band of operation frequency over a temperature variation of 0 degrees to 35 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.
Conclusion:	Pass. The applicant declares that the emissions are maintained within the band of operation under all conditions of normal operation as specified in the user's manual.





## 8 Appendix


### 8.1 Appendix 15.407

#### 1.Emission Bandwidth Measurement


Test Mode	Test Channel	Ant	EBW[MHz]	Limit[MHz]	Verdict
1.4MHz BW	5728.5	Ant1	1.110	$\geq 0.5$	PASS
1.4MHz BW	5788.5	Ant1	1.122	$\geq 0.5$	PASS
1.4MHz BW	5846.5	Ant1	1.101	$\geq 0.5$	PASS
20MHz BW	5735.5	Ant1	18.090	$\geq 0.5$	PASS
20MHz BW	5787.5	Ant1	18.060	$\geq 0.5$	PASS
20MHz BW	5839.5	Ant1	18.060	$\geq 0.5$	PASS
10MHz BW	5730.5	Ant1	9.030	$\geq 0.5$	PASS
10MHz BW	5787.5	Ant1	9.015	$\geq 0.5$	PASS
10MHz BW	5844.5	Ant1	9.030	$\geq 0.5$	PASS




**Emission Bandwidth Measurement\_1.4MHz BW\_5846.5\_Ant1**




**Emission Bandwidth Measurement\_20MHz BW\_5735.5\_Ant1**




**Emission Bandwidth Measurement\_20MHz BW\_5787.5\_Ant1**




**Emission Bandwidth Measurement\_20MHz BW\_5839.5\_Ant1**




**Emission Bandwidth Measurement\_10MHz BW\_5730.5\_Ant1**



**Emission Bandwidth Measurement\_10MHz BW\_5787.5\_Ant1**









## 2.Occupied Bandwidth Measurement


Test Mode	Test Channel	Ant	OBW[MHz]	Limit[MHz]	Verdict
1.4MHz BW	5728.5	Ant1	1.155	---	PASS
1.4MHz BW	5788.5	Ant1	1.161	---	PASS
1.4MHz BW	5846.5	Ant1	1.152	---	PASS
20MHz BW	5735.5	Ant1	17.730	---	PASS
20MHz BW	5787.5	Ant1	17.760	---	PASS
20MHz BW	5839.5	Ant1	17.730	---	PASS
10MHz BW	5730.5	Ant1	9.045	---	PASS
10MHz BW	5787.5	Ant1	9.045	---	PASS
10MHz BW	5844.5	Ant1	9.060	---	PASS









**Occupied Bandwidth Measurement\_10MHz BW\_5730.5\_Ant1**



**Occupied Bandwidth Measurement\_10MHz BW\_5787.5\_Ant1**





**3.Maximum Conduct Output Power**


Test Mode	Test Channel	Ant	Power [dBm]	Limit [dBm]	Verdict
1.4MHz BW	5728.5	Ant1	21.52	<30.00	PASS
1.4MHz BW	5788.5	Ant1	21.60	<30.00	PASS
1.4MHz BW	5846.5	Ant1	20.83	<30.00	PASS
10MHz BW	5730.5	Ant1	21.49	<30.00	PASS
10MHz BW	5787.5	Ant1	21.09	<30.00	PASS
10MHz BW	5844.5	Ant1	21.76	<30.00	PASS
20MHz BW	5735.5	Ant1	21.42	<30.00	PASS
20MHz BW	5787.5	Ant1	21.18	<30.00	PASS
20MHz BW	5839.5	Ant1	21.11	<30.00	PASS




#### 4. Maximum Power Spectral Density

Test Mode	Test Channel	Ant	Level [dBm/500 kHz]	10log(1/x) Factor[dB]	10log(500k Hz/RBW) Factor [dB]	PSD [dBm/500 kHz]	Limit [dBm/500 kHz]	Verdict
1.4MHz BW	5728.5	Ant1	16.67	0	0	16.67	<30.00	PASS
1.4MHz BW	5788.5	Ant1	15.73	0	0	15.73	<30.00	PASS
1.4MHz BW	5846.5	Ant1	15.61	0	0	15.61	<30.00	PASS
20MHz BW	5735.5	Ant1	6.17	0	0	6.17	<30.00	PASS
20MHz BW	5787.5	Ant1	5.27	0	0	5.27	<30.00	PASS
20MHz BW	5839.5	Ant1	6.03	0	0	6.03	<30.00	PASS
10MHz BW	5730.5	Ant1	9.86	0	0	9.86	<30.00	PASS
10MHz BW	5787.5	Ant1	9.16	0	0	9.16	<30.00	PASS
10MHz BW	5844.5	Ant1	9.13	0	0	9.13	<30.00	PASS


Maximum Power Spectral Density\_TNVN\_1.4MHz BW\_5728.5\_Ant1




Maximum Power Spectral Density\_TNVN\_1.4MHz BW\_5788.5\_Ant1




**Maximum Power Spectral Density\_TNVN\_1.4MHz BW\_5846.5\_Ant1**




**Maximum Power Spectral Density\_TNVN\_20MHz BW\_5735.5\_Ant1**




Maximum Power Spectral Density\_TNVN\_20MHz BW\_5787.5\_Ant1




Maximum Power Spectral Density\_TNVN\_20MHz BW\_5839.5\_Ant1



Maximum Power Spectral Density\_TNVN\_10MHz BW\_5730.5\_Ant1



Maximum Power Spectral Density\_TNVN\_10MHz BW\_5787.5\_Ant1










5.Duty Cycle (x)


Test Mode	Test Channel	Ant	Duty Cycle[%]	10log(1/x) Factor[dB]
1.4MHz BW	5728.5	Ant1	100	0
1.4MHz BW	5788.5	Ant1	100	0
1.4MHz BW	5846.5	Ant1	100	0
20MHz BW	5735.5	Ant1	100	0
20MHz BW	5787.5	Ant1	100	0
20MHz BW	5839.5	Ant1	100	0
10MHz BW	5730.5	Ant1	100	0
10MHz BW	5787.5	Ant1	100	0
10MHz BW	5844.5	Ant1	100	0





Duty Cycle\_1.4MHz BW\_5846.5\_Ant1




Duty Cycle\_20MHz BW\_5735.5\_Ant1







Duty Cycle\_10MHz BW\_5730.5\_Ant1



Duty Cycle\_10MHz BW\_5787.5\_Ant1





- End of the Report -