



## FCC RF EXPOSURE REPORT

*For*

**Rear Phased Array Radar**

**MODEL NUMBER: RD241608RBV2**

**REPORT NUMBER: 4791309052-5-2**

**ISSUE DATE: August 9, 2024**

**FCC ID: SS3-RD241608RB2**

*Prepared for*

**SZ DJI TECHNOLOGY CO.,LTD.**

**Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili Community, Xili Street,  
Nanshan District, Shenzhen**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch**

**Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**

## Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
<u>V0</u>	<u>August 9, 2024</u>	<u>Initial Issue</u>	<u></u>

---

## TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS .....	4
2. TEST METHODOLOGY .....	5
3. FACILITIES AND ACCREDITATION .....	5
4. DESCRIPTION OF EUT .....	6
5. REQUIREMENT .....	7

# 1. ATTESTATION OF TEST RESULTS

## Applicant Information

Company Name: SZ DJI TECHNOLOGY CO.,LTD.  
Address: Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili Community, Xili Street, Nanshan District, Shenzhen

## Manufacturer Information

Company Name: SZ DJI TECHNOLOGY CO.,LTD.  
Address: Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili Community, Xili Street, Nanshan District, Shenzhen

## EUT Information

EUT Name: Rear Phased Array Radar  
Model: RD241608RBV2  
Brand Name: DJI  
Sample Status: normal  
Sample ID: 7201002-1  
Sample Received Date: May 10, 2024  
Date of Tested: May 10, 2024 ~ July 10, 2024

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47CFR§2.1091	PASS
KDB-447498 D01 V06	PASS

Prepared By:



Fanny Huang  
Engineer Project Associate

Checked By:



Kebo Zhang  
Senior Project Engineer

Approved By:



Stephen Guo  
Operations Manager

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 and KDB 447498 D01 General RF Exposure Guidance v06.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>ISED (Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p><b>VCCI (Registration No.: G-20192, C-20153, T-20155 and R-20202)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20192 and R-20202 Shielding Room B, the VCCI registration No. is C-20153 and T-20155</p>
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.

#### 4. DESCRIPTION OF EUT

EUT Name	Rear Phased Array Radar
Model	RD241608RBV2

Frequency Range:	24.05 ~ 24.25 GHz
Channel Number:	1
Type of Modulation:	FMCW
Antenna Type:	Linear Antenna
Antenna Gain:	10 dBi
Normal Test Voltage:	DC 52.22 V

## 5. REQUIREMENT

### LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

### RF EXPOSURE LIMIT

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (Minutes)
0.3 -- 1.34	614	1.63	(100)*	30
1.34 -- 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 -- 300	27.5	0.073	0.2	30
300 -- 1500	--	--	f/1500	30
1500 -- 100,000	--	--	1.0	30

### CALCULATION METHOD

$$S = PG / 4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

**CALCULATED RESULTS**

## Radio Frequency Radiation Exposure Evaluation

(Worst case)			
Operating Mode	Max. EIRP	Power density	Limit
	(dBm)	(mW/ cm <sup>2</sup> )	
FMCW	2.91	0.00039	1

Note:

1. The calculated distance is 20 cm.

2. The power comes from operation description.

Max. EIRP = 107.68 dBuV/m in 1m = (107.68-104.77) dBm=2.91 dBm

Therefore the maximum calculations of above situations are less than the "1" limit.

---

**END OF REPORT**