



FCC PART 15C TEST REPORT

Issued to

SZ DJI TECHNOLOGY CO.,LTD

For

Range Extender

Model Name: RE500
 Trade Name: DJI
 Brand Name: DJI
 FCC ID: SS3-RE5001307
 Standard: 47 CFR Part 15 Subpart C
 Test date: 2013-7-3 to 2013-11-1
 Issue date: 2013-11-1

By

Shenzhen MORLAB Communication Technology Co., Ltd.

Tested by Nie Quan
 Nie Quan
 (Test Engineer)

Approved by Zeng Dexin
 Zeng Dexin
 (Chief Engineer)

Review by Peng Huarui
 Peng Huarui
 (Project Manager)

Date 2013.11.1

Date 2013.11.1

Date 2013.11.1



The report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen MORLAB Communication Technology Co., Ltd. It may not be reproduced in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it, or a certified copy thereof prepared by the Shenzhen MORLAB Telecommunication Co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen MORLAB Telecommunication Co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. In the event of the improper use of the report, Shenzhen MORLAB Telecommunication Co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

DIRECTORY

1. GENERAL INFORMATION	3
1.1. EUT Description	3
1.2. Test Standards and Results.....	4
1.3. Facilities and Accreditations	5
2. 47 CFR PART 15C REQUIREMENTS.....	6
2.1. Antenna requirement.....	6
2.2. Peak Output Power.....	6
2.3. Bandwidth	9
2.4. Conducted Spurious Emissions and Band Edge	22
2.5. Power spectral density (PSD)	41
2.6. Restricted Frequency Bands.....	54
2.7. Conducted Emission	73
2.8. Radiated Emission.....	76
2.9. RF exposure evaluation.....	111

Change History		
Issue	Date	Reason for change
1.0	November 1, 2013	First edition
1.1	November 5, 2013	Update 802.11n-20 test results.

1. General Information

1.1. EUT Description

EUT Type: Range Extender
Serial No.....: (n.a, marked #1 by test site)
Hardware Version.....: V2.0
Software Version: V1.05
Applicant: SZ DJI TECHNOLOGY CO.,LTD
Room 613、 614, 6/F, HKUST SZ IER Bldg, No.9 Yuexing 1st Rd
Hi-Tech Park(south), Nanshan District, Shenzhen, Guangdong,
China
Manufacturer: SZ DJI TECHNOLOGY CO., LTD
Room 613、 614, 6/F, HKUST SZ IER Bldg, No.9 Yuexing, 1st Rd
Hi-Tech Park(south), Nanshan District, Shenzhen, Guangdong,
China
Frequency Range.....: 802.11b/g/n-20MHz: 2.412GHz - 2.462GHz
Channel Number.....: 802.11b/g/n-20MHz: 11
Modulation Type: DSSS (802.11b), OFDM (802.11g/n)
Antenna Type.....: Integral Antenna
Antenna Gain.....: 1.0dBi

Note 1: The EUT is Range Extender, it contains WIFI Module operating at 2.4GHz ISM band; it supports 802.11b, 802.11g, 802.11n and they are all tested in this report.

Note 2: The frequencies allocated is $F \text{ (MHz)} = 2412 + 5 * (n - 1)$ ($1 \leq n \leq 11$). The lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 1 (2412MHz), 6 (2437MHz) and 11 (2462MHz).

Note 3: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

Note 4: The antenna connector of EUT is designed with permanent attachment and no consideration of replacement.

Note 5: The repeater is work with a certified transmitter-the DJI Camera, is incapable of being used with open source transmitters, the FCC ID of the DJI camera is: SS3-FC2001307.

Note 6: The repeater and the camera are connected by a RF cable. The camera is transmittin at its maximum level (about 12dBm), through a 12dB attenuator, the Repeater works at its maximum input level (about 0dBm).

1.2. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Wi-Fi, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-12 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.203	Antenna Requirement	PASS
2	15.247(b)	Peak Output Power	PASS
3	15.247(a)	Bandwidth	PASS
4	15.247(d)	Conducted Spurious Emission and Band Edge	PASS
5	15.247(d)	Restricted Frequency Bands	PASS
6	15.207	Conducted Emission	PASS
7	15.209 ,15.247(d)	Radiated Emission	PASS
8	15.247(e)	Power spectral density (PSD)	PASS
9	15.247(i), 1.1307&2.1093	RF exposure evaluation	PASS

The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.4 2009.

These RF tests were performed according to the method of measurements prescribed in KDB558074 D01 V03 (04/09/2013).

1.3. Facilities and Accreditations

1.3.1. Facilities

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at FL.1, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10 2009, ANSI C63.4 2009 and CISPR Publication 22; the FCC registration number is 695796.

1.3.2. Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106

2. 47 CFR Part 15C Requirements

2.1. Antenna requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Peak Output Power

2.2.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

2.2.2. Test Description

The measured output power was calculated by the reading of the Power Meter and calibration.

A. Test Setup:

The EUT (Equipment under the test) is coupled to the Power Meter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in power meter.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
EPM Series Power Meter	Agilent	E4418B	GB43318055	2013.05.12	2014.05.11
Power Sensor	Agilent	8482A	MY41091706	2013.05.12	2014.05.11

2.2.3. Test Result

The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

2.2.3.1. 802.11b Test mode

For antenna A

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	15.33	0.034119	30	1	PASS
6	2437	15.39	0.034594			PASS
11	2462	15.44	0.034995			PASS

For antenna B

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	14.76	0.029923	30	1	PASS
6	2437	14.55	0.028510			PASS
11	2462	14.67	0.029309			PASS

2.2.3.2. 802.11g Test mode

For antenna A

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	12.40	0.017378	30	1	PASS
6	2437	12.43	0.017498			PASS
11	2462	12.42	0.017458			PASS

For antenna B

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	11.74	0.014928	30	1	PASS
6	2437	11.64	0.014588			PASS
11	2462	11.58	0.014388			PASS

2.2.3.3. 802.11n-20MHz Test mode

For antenna A

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	12.36	0.017219	30	1	PASS
6	2437	12.34	0.017140			PASS
11	2462	12.35	0.017179			PASS

For antenna B

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	11.53	0.014223	30	1	PASS
6	2437	11.64	0.014588			PASS
11	2462	11.31	0.013521			PASS

For antenna A+B

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	14.98	0.031442	30	1	PASS
6	2437	15.01	0.031728			PASS
11	2462	14.87	0.030700			PASS

Note: Each antenna port was measured individually, and the aggregated power was summed mathematically.

Remark:

- 1) The MIMO test requirement, RF conducted output power shall measure each transmitter chain by using channel power method. And after obtain each individual transmitter chain power, then sum the output power by using the following formula;

$$((\text{dBm}/\text{Chain } 1)/10^{\text{Log}}) + (\text{dBm}/\text{Chain } 2)/10^{\text{Log}} + (\text{dBm}/\text{Chain } N)/10^{\text{Log}} =$$
 Combined peak output power in mW.


2.3. Bandwidth

2.3.1. Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

2.3.2. Test Description

A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2013.05.12	2014.05.11

2.3.3. Test Result

The lowest, middle and highest channels are selected to perform testing to record the 6 dB bandwidth of the Module.


2.3.3.1. 802.11b Test mode

For antenna A


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Refer to Plot	Limits(kHz)	Result
1	2412	10.128	Plot A	≥ 500	PASS
6	2437	10.112	Plot B	≥ 500	PASS
11	2462	10.069	Plot C	≥ 500	PASS


B. Test Plots:



(Plot A: Channel 1: 2412MHz @ 802.11b)



(Plot B: Channel 6: 2437 MHz @ 802.11b)




(Plot C: Channel 11: 2462MHz @ 802.11b)

For antenna B


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Refer to Plot	Limits(kHz)	Result
1	2412	10.128	Plot A	≥ 500	PASS
6	2437	10.111	Plot B	≥ 500	PASS
11	2462	10.121	Plot C	≥ 500	PASS


B. Test Plots:



(Plot A: Channel 1: 2412MHz @ 802.11b)



(Plot B: Channel 6: 2437 MHz @ 802.11b)



(Plot C: Channel 11: 2462MHz @ 802.11b)


2.3.3.2. 802.11g Test mode

For antenna A


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Refer to Plot	Limits (kHz)	Result
1	2412	16.453	Plot D	≥ 500	PASS
6	2437	16.465	Plot E	≥ 500	PASS
11	2462	16.425	Plot F	≥ 500	PASS


B. Test Plots:



(Plot D: Channel 1: 2412MHz @ 802.11g)



(Plot E: Channel 6: 2437MHz @ 802.11g)




(Plot F: Channel 11: 2462MHz @ 802.11g)

For antenna B


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Refer to Plot	Limits (kHz)	Result
1	2412	16.512	Plot D	≥ 500	PASS
6	2437	16.441	Plot E	≥ 500	PASS
11	2462	16.512	Plot F	≥ 500	PASS


B. Test Plots:



(Plot D: Channel 1: 2412MHz @ 802.11g)



(Plot E: Channel 6: 2437MHz @ 802.11g)



(Plot F: Channel 11: 2462MHz @ 802.11g)

2.3.3.3. 802.11n-20 Test mode


For antenna A

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Refer to Plot	Limits (kHz)	Result
1	2412	17.590	Plot G	≥ 500	PASS
6	2437	17.575	Plot H	≥ 500	PASS
11	2462	17.588	Plot I	≥ 500	PASS

B. Test Plots:

Agilent 14:53:42 Oct 28, 2013 R T



Center 2.412 GHz Span 25 MHz
 #Res BW 100 kHz #VBW 300 kHz #Sweep 4 ms (401 pts)


Occupied Bandwidth
 17.6334 MHz

Occ BW % Pwr 99.00 %
 x dB -6.00 dB

Transmit Freq Error -90.775 kHz
 x dB Bandwidth 17.590 MHz

(Plot G: Channel 1: 2412MHz @ 802.11n-20)

Agilent 14:51:16 Oct 28, 2013 R T




Center 2.437 GHz Span 25 MHz
 #Res BW 100 kHz #VBW 300 kHz #Sweep 4 ms (401 pts)

Occupied Bandwidth
 17.6424 MHz

Occ BW % Pwr 99.00 %
 x dB -6.00 dB

Transmit Freq Error -95.929 kHz
 x dB Bandwidth 17.575 MHz

(Plot H: Channel 6: 2437MHz @ 802.11n-20)




(Plot I: Channel 11: 2462MHz @ 802.11n-20)

For antenna B


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Refer to Plot	Limits (kHz)	Result
1	2412	17.438	Plot G	≥ 500	PASS
6	2437	17.702	Plot H	≥ 500	PASS
11	2462	17.796	Plot I	≥ 500	PASS


B. Test Plots:



(Plot G: Channel 1: 2412MHz @ 802.11n-20)



(Plot H: Channel 6: 2437MHz @ 802.11n-20)



(Plot I: Channel 11: 2462MHz @ 802.11n-20)


2.4. Conducted Spurious Emissions and Band Edge

2.4.1. Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.4.2. Test Description

A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2013.05.12	2014.05.11

2.4.3. Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.

2.4.3.1. 802.11b Test mode


For antenna A

A. Test Verdict:


Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
1	2412	-34.17	Plot A.1	1.006	-19.00	PASS
6	2437	-35.64	Plot B.1	0.662	-19.30	PASS
11	2462	-36.79	Plot C.1	0.507	-19.50	PASS

B. Test Plots:


Note: the power of the Module transmitting frequency should be ignored.




(Plot A.1: Channel = 1, 30MHz to 25GHz)




(Band Edge @Channel = 1)



(Plot B.1: Channel = 6, 30MHz to 25GHz)



(Plot C.1: Channel = 11, 30MHz to 25GHz)



(Band Edge @Channel = 11)


For antenna B

A. Test Verdict:


Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
1	2412	-35.25	Plot A.1	-0.004	-20.0	PASS
6	2437	-36.28	Plot B.1	0.469	-19.5	PASS
11	2462	-37.81	Plot C.1	-0.545	-20.5	PASS

B. Test Plots:


Note: the power of the Module transmitting frequency should be ignored.




(Plot A.1: Channel = 1, 30MHz to 25GHz)




(Band Edge @Channel = 1)



(Plot B.1: Channel = 6, 30MHz to 25GHz)



(Plot C.1: Channel = 11, 30MHz to 25GHz)



(Band Edge @Channel = 11)

2.4.3.2. 802.11g Test mode


For Antenna A

A. Test Verdict:


Channel	Frequency (MHz)	Measured Out of Band Emission (dBm)	Max. of Band Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
1	2412	-45.26	Plot D.1	-3.714	-23.7	PASS
6	2437	-45.12	Plot E.1	-3.233	-23.2	PASS
11	2462	-46.47	Plot F.1	-3.819	-23.8	PASS

B. Test Plots:


Note: the power of the Module transmitting frequency should be ignored.




(Plot D.1: Channel = 1, 30MHz to 25GHz)




(Band Edge @Channel = 1)



(Plot E.1: Channel = 6, 30MHz to 25GHz)



(Plot F.1: Channel = 11, 30MHz to 25GHz)



(Band Edge @Channel = 11)


For Antenna B

A. Test Verdict:


Channel	Frequency (MHz)	Measured Out of Band Emission (dBm)	Max. Band Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
1	2412	-45.78	Plot D.1	-4.404	-24.4	PASS
6	2437	-45.73	Plot E.1	-4.281	-24.3	PASS
11	2462	-48.84	Plot F.1	-4.487	-24.5	PASS

B. Test Plots:


Note: the power of the Module transmitting frequency should be ignored.




(Plot D.1: Channel = 1, 30MHz to 25GHz)




(Band Edge @Channel = 1)



(Plot E.1: Channel = 6, 30MHz to 25GHz)



(Plot F.1: Channel = 11, 30MHz to 25GHz)



(Band Edge @Channel = 11)

2.4.3.3. 802.11n -20MHz Test mode


For Antenna A

A. Test Verdict:


Channel	Frequency (MHz)	Measured Out of Band Emission (dBm)	Max. Band Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
1	2412	-45.80	Plot G.1	-3.462	-23.5	PASS
6	2437	-48.12	Plot H.1	-3.688	-23.7	PASS
11	2462	-47.71	Plot I.1	-4.532	-24.5	PASS

B. Test Plots:


Note: the power of the Module transmitting frequency should be ignored.




(Plot G.1: Channel = 1, 30MHz to 25GHz)




(Band Edge @Channel = 1)



(Plot H.1: Channel = 6, 30MHz to 25GHz)



(Plot I.1: Channel = 11, 30MHz to 25GHz)



(Band Edge @Channel = 11)


For Antenna B

A. Test Verdict:


Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
1	2412	-44.97	Plot G.1	-4.296	-24.3	PASS
6	2437	-47.84	Plot H.1	-3.784	-23.8	PASS
11	2462	-46.42	Plot I.1	-3.887	-23.9	PASS

B. Test Plots:


Note: the power of the Module transmitting frequency should be ignored.




(Plot G.1: Channel = 1, 30MHz to 25GHz)




(Band Edge @Channel = 1)



(Plot H.1: Channel = 6, 30MHz to 25GHz)



(Plot I.1: Channel = 11, 30MHz to 25GHz)



(Band Edge @Channel = 11)


2.5. Power spectral density (PSD)

2.5.1. Requirement

According to FCC section 15.247(e), the same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

2.5.2. Test Description

A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2013.05.12	2014.05.11

2.5.3. Test Result


2.5.3.1. 802.11b Test mode

For antenna A


A. Test Verdict:

Spectral power density (dBm/3kHz)					
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Refer to Plot	Limit (dBm/3kHz)	Verdict
1	2412	-10.43	Plot A	8	PASS
6	2437	-9.433	Plot B	8	PASS
11	2462	-12.15	Plot C	8	PASS
Measurement uncertainty: ± 1.3 dB					


B. Test Plots:



(Plot A: Channel = 1 @ 802.11b)



(Plot B: Channel = 6 @ 802.11b)




(Plot C: Channel = 11 @ 802.11b)

For antenna B


A. Test Verdict:

Spectral power density (dBm/3kHz)					
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Refer to Plot	Limit (dBm/3kHz)	Verdict
1	2412	-12.78	Plot A	8	PASS
6	2437	-13.62	Plot B	8	PASS
11	2462	-13.97	Plot C	8	PASS
Measurement uncertainty: ± 1.3 dB					


B. Test Plots:



(Plot A: Channel = 1 @ 802.11b)



(Plot B: Channel = 6 @ 802.11b)



(Plot C: Channel = 11 @ 802.11b)


2.5.3.2. 802.11g Test mode

For antenna A


A. Test Verdict:

Spectral power density (dBm/3kHz)					
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Refer to Plot	Limit (dBm/3kHz)	Verdict
1	2412	-17.49	Plot A	8	PASS
6	2437	-17.69	Plot B	8	PASS
11	2462	-16.56	Plot C	8	PASS
Measurement uncertainty: ± 1.3 dB					


B. Test Plots:



(Plot D: Channel = 1 @ 802.11g)



(Plot E: Channel = 6 @ 802.11g)



(Plot F: Channel = 11 @ 802.11g)


For antenna B

A. Test Verdict:


Spectral power density (dBm/3kHz)					
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Refer to Plot	Limit (dBm/3kHz)	Verdict
1	2412		Plot A	8	PASS
6	2437		Plot B	8	PASS
11	2462		Plot C	8	PASS

Measurement uncertainty: ± 1.3 dB


B. Test Plots:



(Plot D: Channel = 1 @ 802.11g)



(Plot E: Channel = 6 @ 802.11g)



(Plot F: Channel = 11 @ 802.11g)


2.5.3.3. 802.11n-20MHz Test mode

For antenna A


A. Test Verdict:

Spectral power density (dBm/3kHz)					
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Refer to Plot	Limit (dBm/3kHz)	Verdict
1	2412	-18.10	Plot A	8	PASS
6	2437	-17.21	Plot B	8	PASS
11	2462	-18.92	Plot C	8	PASS
Measurement uncertainty: ± 1.3 dB					


B. Test Plots:



(Plot G: Channel = 1 @ 802.11n-20MHz)



(Plot H: Channel = 6 @ 802.11n-20MHz)




(Plot I: Channel = 11 @ 802.11n-20MHz)

For antenna B


A. Test Verdict:

Spectral power density (dBm/3kHz)					
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Refer to Plot	Limit (dBm/3kHz)	Verdict
1	2412	-18.03	Plot A	8	PASS
6	2437	-19.28	Plot B	8	PASS
11	2462	-18.59	Plot C	8	PASS
Measurement uncertainty: ± 1.3 dB					


B. Test Plots:



(Plot G: Channel = 1 @ 802.11n-20MHz)



(Plot H: Channel = 6 @ 802.11n-20MHz)



(Plot I: Channel = 11 @ 802.11n-20MHz)

For antenna A+B

Spectral power density (dBm/3kHz)					
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Refer to Plot	Limit (dBm/3kHz)	Verdict
1	2412	-15.05	Plot A	8	PASS
6	2437	-15.11	Plot B	8	PASS
11	2462	-15.74	Plot C	8	PASS
Measurement uncertainty: ± 1.3 dB					


2.6. Restricted Frequency Bands

2.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.6.2. Test Description

A. Test Setup



The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2013.05.12	2014.05.11
Full-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2013.05.12	2014.05.11
Test Antenna	Schwarzbeck	BBHA 9120C	9120C-384	2013.05.12	2014.05.11

2.6.3. Test Result

The lowest and highest channels are tested to verify the band edge emissions.

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

Note: Band edge tests were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.


2.6.3.1. 802.11b Test mode
For antenna A

The lowest and highest channels are tested to verify the band edge emissions.


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading UR (dBuV)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2398.56	PK	54.31	-30.93	32.56	55.94	74	Pass
1	2398.28	AV	44.90	-30.93	32.56	46.53	54	Pass
11	2494.21	PK	51.35	-29.05	32.50	54.80	74	Pass
11	2499.05	AV	43.27	-29.05	32.50	46.72	54	Pass


B. Test Plots:




(Plot A1: Channel = 1 PEAK @ 802.11b)



(Plot A2: Channel = 1 AVG @ 802.11b)



(Plot B1: Channel = 11 PEAK @ 802.11b)




(Plot B2: Channel = 11 AVG @ 802.11b)

For antenna B


The lowest and highest channels are tested to verify the band edge emissions.

A. Test Verdict:


Channel	Frequency (MHz)	Detector	Receiver Reading UR (dBuV)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2373.64	PK	47.19	-30.93	32.56	48.82	74	Pass
1	2397.72	AV	35.96	-30.93	32.56	37.59	54	Pass
11	2487.94	PK	47.78	-29.05	32.50	51.23	74	Pass
11	2492.97	AV	35.67	-29.05	32.50	39.12	54	Pass

B. Test Plots:



(Plot A1: Channel = 1 PEAK @ 802.11b)



(Plot A2: Channel = 1 AVG @ 802.11b)



(Plot B1: Channel = 11 PEAK @ 802.11b)



(Plot B2: Channel = 11 AVG @ 802.11b)

2.6.3.2. 802.11g Test mode


For antenna A

The lowest and highest channels are tested to verify the band edge emissions.


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading UR (dB μ V)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2398.56	PK	65.74	-30.93	32.56	67.37	74	Pass
1	2398.84	AV	41.71	-30.93	32.56	43.34	54	Pass
11	2484.33	PK	49.33	-29.05	32.50	52.78	74	Pass
11	2494.40	AV	37.21	-29.05	32.50	40.66	54	Pass


B. Test Plots:




(Plot C1: Channel = 1 PEAK @ 802.11g)



(Plot C2: Channel = 1 AVG @ 802.11g)



(Plot D1: Channel = 11 PEAK @ 802.11g)




(Plot D2: Channel = 11 AVG @ 802.11g)


For antenna B

A. Test Verdict:


Channel	Frequency (MHz)	Detector	Receiver Reading UR (dBuV)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2396.04	PK	51.94	-30.93	32.56	53.57	74	Pass
1	2398.28	AV	39.39	-30.93	32.56	41.02	54	Pass
11	2484.99	PK	46.73	-29.05	32.50	50.18	74	Pass
11	2483.50	AV	35.84	-29.05	32.50	39.29	54	Pass

B. Test Plots:



(Plot C1: Channel = 1 PEAK @ 802.11g)



(Plot C2: Channel = 1 AVG @ 802.11g)



(Plot D1: Channel = 11 PEAK @ 802.11g)



(Plot D2: Channel = 11 AVG @ 802.11g)

2.6.3.3. 802.11n-20MHz Test mode


For antenna A

The lowest and highest channels are tested to verify the band edge emissions.


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading UR (dB μ V)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2398.84	PK	65.99	-30.93	32.56	67.62	74	Pass
1	2398.84	AV	43.23	-30.93	32.56	44.86	54	Pass
11	2485.75	PK	51.87	-29.05	32.50	55.32	74	Pass
11	2495.54	AV	38.06	-29.05	32.50	41.51	54	Pass


B. Test Plots:




(Plot E1: Channel = 1 PEAK @ 802.11n-20)



(Plot E2: Channel = 1 AVG @ 802.11n-20)



(Plot F1: Channel = 11 PEAK @ 802.11n-20)




(Plot F2: Channel = 11 AVG @ 802.11n-20)

For antenna B


The lowest and highest channels are tested to verify the band edge emissions.

A. Test Verdict:


Channel	Frequency (MHz)	Detector	Receiver Reading UR (dBuV)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2398.28	PK	52.84	-30.93	32.56	54.47	74	Pass
1	2398.28	AV	38.29	-30.93	32.56	39.92	54	Pass
11	2484.71	PK	48.12	-29.05	32.50	51.57	74	Pass
11	2484.23	AV	36.89	-29.05	32.50	40.34	54	Pass

B. Test Plots:



(Plot E1: Channel = 1 PEAK @ 802.11n-20)



(Plot E2: Channel = 1 AVG @ 802.11n-20)



(Plot F1: Channel = 11 PEAK @ 802.11n-20)



(Plot F2: Channel = 11 AVG @ 802.11n-20)


For antenna A+B

The lowest and highest channels are tested to verify the band edge emissions.


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading UR (dB μ V)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2398.56	PK	51.16	-30.93	32.56	52.79	74	Pass
1	2398.00	AV	38.03	-30.93	32.56	39.66	54	Pass
11	2484.90	PK	54.80	-29.05	32.50	58.25	74	Pass
11	2484.14	AV	38.24	-29.05	32.50	41.69	54	Pass


B. Test Plots:




(Plot E1: Channel = 1 PEAK @ 802.11n-20)



(Plot E2: Channel = 1 AVG @ 802.11n-20)



(Plot F1: Channel = 11 PEAK @ 802.11n-20)



(Plot F2: Channel = 11 AVG @ 802.11n-20)

2.7. Conducted Emission

2.7.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.7.2. Test Description

A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSIC63.4:2009

The factors of the site are calibrated to correct the reading. During the measurement, the EUT is activated and controlled by the Wi-Fi Service Supplier (SS) via a Common Antenna.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2013.05.12	2014.05.11
LISN	Schwarzbeck	NSLK 8127	812744	2013.05.12	2014.05.11
Service Supplier	R&S	CMU200	100448	2013.05.12	2014.05.11
Pulse Limiter (20dB)	Schwarzbeck	VTSD 9561-D	9391	(n.a.)	(n.a.)


2.7.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.


A. Test setup:

The EUT configuration of the emission tests is EUT + Link.

B. Test Plots:



(Plot A: L Phase)



(Plot B: N Phase)

2.8. Radiated Emission

2.8.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:


1. For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)


2.8.2. Test Description

A. Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4 (2009). The EUT was set-up on insulator 80cm above the Ground Plane. The set-up and test methods were according to ANSI C63.4.

The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the EUT is activated and controlled by the Wireless Router via a Common Antenna, and is set to operate under hopping-on test mode.

For the Test Antenna:

- (a) In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- (b) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 2GHz) and Horn Test Antenna (above 2GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	R&S	CMU200	100448	2013.05.12	2014.05.11
Receiver	Agilent	E7405A	US44210471	2013.05.12	2014.05.11
Full-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2013.05.12	2014.05.11
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	2013.05.12	2014.05.11
Test Antenna - Horn	Schwarzbeck	BBHA 9120D	9120C-963	2013.05.12	2014.05.11

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Test Antenna - Horn	R&S	HL050S7	71688	2013.05.12	2014.05.11
Test Antenna -Loop	Schwarzbeck	FMZB 1519	1519-022	2013.05.12	2014.05.11

2.8.3. Test Result

According to ANSI C63.4 selection 4.2.2, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.


Note: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

2.8.3.1. 802.11b Test mode


A. Test Plots for the Whole Measurement Frequency Range:

For antenna A

Plots for Channel = 1




(Plot A.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
250.125	28.68	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2412.000	55.28	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
15728.180	41.85	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot A.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
598.454	38.45	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2412.000	50.87	N.A	N.A	N.A	N.A	N.A	Vertical	PASS
15783.042	41.27	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot A.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6




(Plot B.1: 9kHz to 30MHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
250.125	28.48	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2437.000	47.93	N.A	N.A	N.A	N.A	N.A	Horizontal	PASS
15783.042	41.10	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot B.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
598.454	38.95	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2437.000	50.46	N.A	N.A	N.A	N.A	N.A	Vertical	PASS
4865.337	46.94	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot B.3: Antenna Vertical, 30MHz to 25GHz)


Plot for Channel = 11


(Plot C.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
250.125	28.81	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2462.000	50.09	N.A	N.A	N.A	N.A	N.A	Horizontal	PASS
15728.180	40.98	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot C.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
598.454	38.62	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2462.000	49.97	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
15728.180	41.34	N.A	N.A	74.0	N.A	54.0	Vertical	PASS


(Plot C.3: Antenna Vertical, 30MHz to 25GHz)

For antenna B

Plots for Channel = 1




(Plot A.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
240.449	29.05	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
683.117	27.52	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2412.000	43.88	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
15783.042	41.35	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot A.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
112.244	15.31	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
487.182	33.72	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2412.000	42.67	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
15783.042	40.97	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot A.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6




(Plot B.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
240.449	29.04	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
663.766	25.57	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2437.000	44.79	N.A	N.A	N.A	N.A	N.A	Horizontal	PASS
15783.042	41.53	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot B.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
240.449	21.60	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
666.185	28.74	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2437.000	45.34	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
15783.042	40.83	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot B.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11




(Plot C.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
288.828	29.14	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
666.185	28.16	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2462.000	46.35	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
15728.180	41.79	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot C.2: Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
240.449	21.34	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
666.185	27.56	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2462.000	45.83	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
15783.042	40.98	N.A	N.A	74.0	N.A	54.0	Vertical	PASS


(Plot C.3: Antenna Vertical, 30MHz to 25GHz)

2.8.3.2. 802.11g Test mode


For antenna A

A. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 1




(Plot D.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
250.125	27.85	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2412.000	49.62	N.A	N.A	N.A	N.A	N.A	Horizontal	PASS
15783.042	41.22	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot D.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
598.454	38.52	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2412.000	54.01	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
15783.042	41.43	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot D.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6




(Plot E.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
250.125	29.53	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2437.000	51.74	N.A	N.A	N.A	N.A	N.A	Horizontal	PASS
15399.002	40.84	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot E.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
250.125	35.50	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2437.000	52.06	N.A	N.A	N.A	N.A	N.A	Vertical	PASS
15728.180	41.41	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot E.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11




(Plot F.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
598.454	35.71	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2462.000	50.70	N.A	N.A	N.A	N.A	N.A	Horizontal	PASS
4920.200	42.54	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot F.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
598.454	39.45	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2462.000	56.28	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
7389.027	47.98	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot F.3: Antenna Vertical, 30MHz to 25GHz)


For antenna B

B. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 1




(Plot D.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
240.449	34.74	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
697.631	31.80	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2412.000	44.21	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
15728.180	41.28	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot D.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
112.244	15.86	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
489.601	28.91	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2412.000	42.95	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
15783.042	40.74	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot D.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6




(Plot E.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
240.449	30.54	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
700.050	26.85	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2437.000	44.16	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
15783.042	41.60	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot E.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
167.880	17.59	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
663.766	26.97	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2437.000	44.50	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
15783.042	41.05	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot E.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11




(Plot F.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
240.449	33.99	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
288.828	35.00	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2462.000	45.54	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
15783.042	41.54	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot F.2: Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
288.828	21.99	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
663.766	26.62	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2462.000	46.15	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
15728.180	41.01	N.A	N.A	74.0	N.A	54.0	Vertical	PASS


(Plot F.3: Antenna Vertical, 30MHz to 25GHz)

2.8.3.3. 802.11n-20MHz Test mode


For antenna A

A. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 1




(Plot G.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
102.569	23.14	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
245.287	27.98	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
400.100	28.52	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
598.454	31.12	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2412.000	59.02	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
4810.474	47.56	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot G.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
598.454	38.45	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2412.000	51.09	N.A	N.A	54.0	N.A	54.0	Vertical	PASS
14192.020	40.76	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot G.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6




(Plot H.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
250.125	27.97	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2437.000	48.97	N.A	N.A	N.A	N.A	N.A	Horizontal	PASS
4865.337	38.45	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot H.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
250.125	33.77	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2437.0000	55.31	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
4865.337	46.58	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot H.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11




(Plot I.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
250.125	30.79	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2462.000	51.67	N.A	N.A	N.A	N.A	N.A	Horizontal	PASS
15783.042	41.70	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot I.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
598.454	39.37	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2462.000	50.39	N.A	N.A	N.A	N.A	N.A	Vertical	PASS
7389.027	48.09	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot I.3: Antenna Vertical, 30MHz to 25GHz)


For antenna B

B. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 1




(Plot G.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
167.880	30.04	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
288.828	33.84	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2412.000	42.07	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
15783.042	40.92	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot G.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
167.880	19.18	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
342.045	25.81	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2412.000	43.62	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
15783.042	41.18	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot G.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6




(Plot H.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
240.449	28.64	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
700.050	25.84	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2437.0000	44.19	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
15728.180	41.08	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot H.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
170.299	19.74	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
663.766	29.39	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2437.000	43.14	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
15728.180	40.63	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot H.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11




(Plot I.1: 9kHz to 30MHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
150.948	30.54	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
288.828	35.87	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2462.000	44.60	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
14192.020	40.37	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot I.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
288.828	29.63	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
666.185	29.78	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2462.000	44.84	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
15728.180	41.49	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot I.3: Antenna Vertical, 30MHz to 25GHz)


For antenna A+B
A. Test Plots for the Whole Measurement Frequency Range:
Plots for Channel = 1


(Plot G.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
673.44	37.40	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2406.484	66.98	N.A	N.A	74.0	N.A	54.0	Horizontal	N/A
15783.042	40.68	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot G.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
673.441	36.46	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2406.484	74.90	N.A	N.A	74.0	N.A	54.0	Vertical	N/A
12381.546	39.73	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot G.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6




(Plot H.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
199.327	34.14	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
2431.421	66.37	N.A	N.A	74.0	N.A	54.0	Horizontal	N/A
15783.042	39.70	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot H.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
199.327	34.73	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
2431.421	72.59	N.A	N.A	74.0	N.A	54.0	Vertical	N/A
12600.998	40.13	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot H.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11




(Plot I.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
199.327	34.21	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
2456.359	63.99	N.A	N.A	74.0	N.A	54.0	Horizontal	N/A
4920.200	53.94	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot I.2: Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
199.327	33.31	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
2456.359	72.76	N.A	N.A	74.0	N.A	54.0	Vertical	N/A
15728.180	39.86	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot I.3: Antenna Vertical, 30MHz to 25GHz)

2.9. RF exposure evaluation

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4 \pi R^2}$$

Where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

2.9.1. Limits for Maximum Permissible Exposure

According to FCC Part 1.1307, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidelines.

According to FCC Part 1.1310 RF exposure is calculated.

Limits for General Population/ Uncontrolled Exposure			
Frequency Range (MHz)	Electric Field Strength(E)(V/m)	Magnetic Field Strength (H)(A/m)	Power Density (S)(mW/cm ²)
0.3-1.34	614	1.63	(100)*
1.34-30	824/f	2.19/f	(180/f ²)*
30-300	27.5	0.073	0.2
300-1500			f/1500
1500-100,000			1.0

Test result

Maximum peak output power at antenna input terminal(dBm):	15.44
Maximum peak output power at antenna input terminal(mW):	34.995
Source-based time-averaged output power:	--
Prediction distance(cm):	20
Predication frequency(MHz):	2462
Antenna Gain (typical) (dBi):	1.0
Power density at predication frequency at <u>20</u> cm(mW/cm^2):	0.008765
MPE limit for RF exposure at prediction frequency(mW/cm^2):	1.0

2.9.2. Conclusion

Since the test result is passed, the SAR measurement is not required.

**** END OF REPORT ****