

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000402803

Page: 1 of 217

TEST REPORT

Application No.: SZCR2410004028AT
Applicant: SZ DJI TECHNOLOGY CO., LTD.
Address of Applicant: Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili Community, Xili Street, Nanshan District, 518055 Shenzhen, China
Manufacturer: SZ DJI TECHNOLOGY CO., LTD.
Address of Manufacturer: Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili Community, Xili Street, Nanshan District, 518055 Shenzhen, China

Equipment Under Test (EUT):**EUT Name:** AGRAS T70/AGRAS T70P**Model No.:** 3WWDZ-U50B, 3WWDZ-U70A ♣

♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.

Trade Mark: DJI**FCC ID:** SS3-T702412**Standard(s) :** 47 CFR Part 15, Subpart C 15.247**Date of Receipt:** 2024-12-27**Date of Test:** 2025-03-04 to 2025-03-13**Date of Issue:** 2025-03-16**Test Result:****Pass***

* In the configuration tested, the EUT complied with the standards specified above.

Kenx Xu

Keny Xu
EMC Laboratory ManagerSGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000402803

Page: 2 of 217

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2025-03-16		Original

Authorized for issue by:				
		Darren Yuan		
		Darren Yuan/Project Engineer		
		Eric Fu		
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2013) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2013) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Peak Output Power		ANSI C63.10 (2013) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass

Declaration of EUT Family Grouping:

Model No.: 3WWDZ-U50B, 3WWDZ-U70A

Only the model 3WWDZ-U50B was tested, since according to the declaration from the applicant, the electrical circuit design, PCB layout, components used and internal wiring and functions were identical for the above models, with only difference on the two models are equipped with water tanks of different capacities and are paired with batteries of different capacities ,3WWDZ-U50B equipped with 50L water tanks and BAX811- 30000mAh-52.5V battery, 3WWDZ-U70A equipped with 70L water tanks and BAX901- 41000mAh-52.78V battery.

Note: Both BAX811- 30000mAh-52.5V and BAX901- 41000mAh-52.78V battery are pre-scans, only the worst data recorded in this report.



3 Contents

	Page
1 Cover Page	1
2 Test Summary.....	3
3 Contents	4
4 General Information.....	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units.....	6
4.3 Measurement Uncertainty	7
4.4 Test Location	8
4.5 Test Facility.....	8
4.6 Deviation from Standards.....	8
4.7 Abnormalities from Standard Conditions	8
5 Equipment List	9
6 Radio Spectrum Technical Requirement.....	11
6.1 Antenna Requirement	11
6.1.1 Test Requirement:	11
6.1.2 Conclusion	11
7 Radio Spectrum Matter Test Results.....	12
7.1 Radiated Emissions which fall in the restricted bands	12
7.1.1 E.U.T. Operation	12
7.1.2 Test Mode Description	12
7.1.3 Test Setup Diagram	13
7.1.4 Measurement Procedure and Data.....	14
7.2 Radiated Spurious Emissions Below 1GHz.....	47
7.2.1 E.U.T. Operation	47
7.2.2 Test Mode Description	47
7.2.3 Test Setup Diagram	48
7.2.4 Measurement Procedure and Data.....	48
7.3 Radiated Spurious Emissions Above 1GHz	52
7.3.1 E.U.T. Operation	52
7.3.2 Test Mode Description	52
7.3.3 Test Setup Diagram	52
7.3.4 Measurement Procedure and Data.....	53
7.4 Conducted Peak Output Power	60
7.4.1 E.U.T. Operation	60
7.4.2 Test Mode Description	60
7.4.3 Test Setup Diagram	61
7.4.4 Measurement Procedure and Data.....	61
7.5 Minimum 6dB Bandwidth.....	62
7.5.1 E.U.T. Operation	62



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000402803

Page: 5 of 217

7.5.2	Test Mode Description	62
7.5.3	Test Setup Diagram	62
7.5.4	Measurement Procedure and Data	62
7.6	Power Spectrum Density	63
7.6.1	E.U.T. Operation	63
7.6.2	Test Mode Description	63
7.6.3	Test Setup Diagram	63
7.6.4	Measurement Procedure and Data	63
7.7	Conducted Band Edges Measurement	64
7.7.1	E.U.T. Operation	64
7.7.2	Test Mode Description	64
7.7.3	Test Setup Diagram	64
7.7.4	Measurement Procedure and Data	65
7.8	Conducted Spurious Emissions	66
7.8.1	E.U.T. Operation	66
7.8.2	Test Mode Description	66
7.8.3	Test Setup Diagram	66
7.8.4	Measurement Procedure and Data	67
8	Test Setup Photo	68
9	EUT Constructional Details (EUT Photos)	68
10	Appendix	69



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	Powered by Lithium-Ion Polymer Rechargeable Battery Battery information Battery 1 Model: BAX901-41000mAh-52.78V Nominal Voltage: 52.78V Rated Capacity: 41000mAh, 2164Wh Battery 2 Model: BAX811-30000mAh-52.5V Nominal Voltage: 52.5V Rated Capacity: 30000mAh, 1575Wh
Operation Frequency:	10MHz mode: 2407.5MHz-2467.5MHz 20MHz mode: 2412.5MHz-2462.5MHz 40MHz mode: 2422.5MHz-2452.5MHz 60MHz mode: 2432.5MHz-2442.5MHz
Modulation Type:	OFDM
Channel Spacing:	10MHz mode: 1MHz 20MHz mode: 1MHz 40MHz mode: 1MHz 60MHz mode: 1MHz
Number of Channels:	10MHz mode: 61 20MHz mode: 51 40MHz mode: 31 60MHz mode: 11
Antenna Type:	Dipole Antenna
Antenna Gain:	ANT0: 3.5dBi, ANT1: 3.5dBi, ANT2: 3.5dBi, ANT3: 3.5dBi
Cable Loss (for RF conducted test):	0.9dB

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--
The EUT has been tested as an independent unit.			



4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (Below 1GHz); $\pm 4.6\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Spurious Emissions Above 1GHz	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)
Conducted Peak Output Power	$\pm 0.75\text{dB}$
Minimum 6dB Bandwidth	$\pm 3\%$
Power Spectrum Density	$\pm 2.84\text{dB}$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000402803

Page: 8 of 217

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2024-05-11	2027-05-10
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2025-03-04	2026-03-03
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2023-07-23	2025-07-22
Microwave system amplifier	Agilent	83017A	SEM005-25	2024-09-14	2025-09-13
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2024-07-06	2025-07-05
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2024-08-10	2025-08-09
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2024-03-15	2025-03-14

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2024-03-26	2025-03-25
MXE EMI receiver	KEYSIGHT	N9038A	SEM004-16	2024-08-14	2025-08-13
Trilog-Broadband Antenna	Schwarzbeck	VULB9168	SEM003-18	2023-09-23	2025-09-22
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-04	2025-03-04	2026-03-03
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2023-11-20	2025-11-19
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM029-01	2024-07-06	2025-07-05

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000402803

Page: 10 of 217

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2024-05-11	2027-05-10
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2025-03-04	2026-03-03
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2023-07-23	2025-07-22
Microwave system amplifier	Agilent	83017A	SEM005-25	2024-09-14	2025-09-13
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2024-07-06	2025-07-05
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2024-08-10	2025-08-09
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2024-03-15	2025-03-14

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2025-03-04	2026-03-03
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2025-03-04	2026-03-03
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2024-08-14	2025-08-13
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2025-03-04	2026-03-03
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2024-07-06	2025-07-05
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2025-03-03	2026-03-02

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2024-07-24	2025-07-23
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2024-07-24	2025-07-23
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2024-03-18	2025-03-17



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 3.5dBi; the directional gain is 6.51dBi.

Antenna location: Refer to internal photo.



7 Radio Spectrum Matter Test Results

7.1 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C

Humidity: 56.3 % RH


Atmospheric Pressure: 1020 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode (2.4G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	05	TX mode (2.4G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	06	TX mode (2.4G SDR_40MHz)_Keep the EUT in transmitting mode
Final test	07	TX mode (2.4G SDR_60MHz)_Keep the EUT in transmitting mode



7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Remark 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.

Remark 4: For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.



Test Mode: 04; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2407.5 Band edge
: 2.4G SDR 10M

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2340.618	3.62	28.97	0.00	29.58	62.17	74.00	-11.83	peak
2	2390.000	3.66	29.10	0.00	26.95	59.71	74.00	-14.29	peak
3 p	2407.500	3.67	29.07	0.00	83.64	116.38	74.00	42.38	peak



Test Mode: 04; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2407.5 Band edge
: 2.4G SDR 10M

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2357.153	3.64	29.10	0.00	16.60	49.34	54.00	-4.66	Average
2	2390.000	3.66	29.10	0.00	16.25	49.01	54.00	-4.99	Average
3 q	2407.500	3.67	29.07	0.00	73.43	106.17	54.00	52.17	Average



Test Mode: 04; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 04028AT\04029AT
 Mode : 2407.5 Band edge
 : 2.4G SDR 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2378.136	3.65	29.10	0.00	29.60	62.35	74.00	-11.65	Peak
2	2390.000	3.66	29.10	0.00	27.35	60.11	74.00	-13.89	Peak
3 p	2407.500	3.67	29.07	0.00	90.66	123.40	74.00	49.40	Peak



Test Mode: 04; Polarity: Vertical; Modulation: OFDM; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 04028AT\04029AT
Mode : 2407.5 Band edge
: 2.4G SDR 10M


		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2368.161	3.65	29.10	0.00	16.73	49.48	54.00	-4.52	Average
2	2390.000	3.66	29.10	0.00	16.05	48.81	54.00	-5.19	Average
3 q	2407.500	3.67	29.07	0.00	80.32	113.06	54.00	59.06	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 04; Polarity: Horizontal; Modulation: OFDM; Channel: High



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 04028AT\04029AT
 Mode : 2467.5 Band edge
 : 2.4G SDR 10M

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2467.500	3.72	28.90	0.00	87.56	120.18	74.00	46.18	peak
2	2483.500	3.73	28.90	0.00	27.87	60.50	74.00	-13.50	peak
3	2494.803	3.74	28.90	0.00	29.59	62.23	74.00	-11.77	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000402803

Page: 20 of 217

Test Mode: 04; Polarity: Horizontal; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2467.5 Band edge
: 2.4G SDR 10M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 2467.500	3.72	28.90	0.00	76.22	108.84	54.00	54.84	Average
2 2483.500	3.73	28.90	0.00	16.19	48.82	54.00	-5.18	Average
3 2493.493	3.74	28.90	0.00	16.87	49.51	54.00	-4.49	Average




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 04; Polarity: Vertical; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 04028AT\04029AT
Mode : 2467.5 Band edge
: 2.4G SDR 10M

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2467.500	3.72	28.90	0.00	87.75	120.37	74.00	46.37	Peak
2	2483.500	3.73	28.90	0.00	27.29	59.92	74.00	-14.08	Peak
3	2492.436	3.73	28.90	0.00	29.32	61.95	74.00	-12.05	Peak

Test Mode: 04; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
Condition: 3m VERTICAL
Job No : 04028AT\04029AT
Mode : 2467.5 Band edge
: 2.4G SDR 10M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2467.500	3.72	28.90	0.00	82.14	114.76	54.00	60.76 Average
2	2483.500	3.73	28.90	0.00	16.41	49.04	54.00	-4.96 Average
3	2498.586	3.74	28.90	0.00	16.69	49.33	54.00	-4.67 Average



Test Mode: 05; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2412.5 Band edge
: 2.4G SDR 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2365.849	3.64	29.10	0.00	29.35	62.09	74.00	-11.91	peak
2	2390.000	3.66	29.10	0.00	27.68	60.44	74.00	-13.56	peak
3 p	2412.500	3.68	29.05	0.00	82.94	115.67	74.00	41.67	peak



Test Mode: 05; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2412.5 Band edge
: 2.4G SDR 20M

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2354.600	3.64	29.10	0.00	16.55	49.29	54.00	-4.71	Average
2	2390.000	3.66	29.10	0.00	16.16	48.92	54.00	-5.08	Average
3 q	2412.500	3.68	29.05	0.00	72.47	105.20	54.00	51.20	Average



Test Mode: 05; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
Condition: 3m VERTICAL
Job No : 04028AT\04029AT
Mode : 2412.5 Band edge
: 2.4G SDR 20M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2384.997	3.66	29.10	0.00	29.27	62.03	74.00	-11.97 Peak
2	2390.000	3.66	29.10	0.00	28.00	60.76	74.00	-13.24 Peak
3 p	2412.500	3.68	29.05	0.00	89.19	121.92	74.00	47.92 Peak



Test Mode: 05; Polarity: Vertical; Modulation: OFDM; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 04028AT\04029AT
Mode : 2412.5 Band edge
: 2.4G SDR 20M


		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2354.184	3.63	29.10	0.00	16.66	49.39	54.00	-4.61 Average
2	2390.000	3.66	29.10	0.00	16.20	48.96	54.00	-5.04 Average
3 q	2412.500	3.68	29.05	0.00	78.81	111.54	54.00	57.54 Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 05; Polarity: Horizontal; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2462.5 Band edge
: 2.4G SDR 20M


		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2462.500	3.71	28.90	0.00	83.78	116.39	74.00	42.39	peak
2	2483.500	3.73	28.90	0.00	27.37	60.00	74.00	-14.00	peak
3	2493.389	3.74	28.90	0.00	30.15	62.79	74.00	-11.21	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 05; Polarity: Horizontal; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2462.5 Band edge
: 2.4G SDR 20M


		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q	2462.500	3.71	28.90	0.00	73.22	105.83	54.00	51.83	Average
2	2483.500	3.73	28.90	0.00	16.55	49.18	54.00	-4.82	Average
3	2492.905	3.74	28.90	0.00	16.65	49.29	54.00	-4.71	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 05; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
Condition: 3m VERTICAL
Job No : 04028AT\04029AT
Mode : 2462.5 Band edge
: 2.4G SDR 20M

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2462.500	3.71	28.90	0.00	90.69	123.30	74.00	49.30	Peak
2	2483.500	3.73	28.90	0.00	28.30	60.93	74.00	-13.07	Peak
3	2492.299	3.73	28.90	0.00	29.05	61.68	74.00	-12.32	Peak



Test Mode: 05; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
Condition: 3m VERTICAL
Job No : 04028AT\04029AT
Mode : 2462.5 Band edge
: 2.4G SDR 20M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 2462.500	3.71	28.90	0.00	79.57	112.18	54.00	58.18	Average
2 2483.500	3.73	28.90	0.00	16.57	49.20	54.00	-4.80	Average
3 2489.878	3.73	28.90	0.00	17.04	49.67	54.00	-4.33	Average



Test Mode: 06; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2422.5 Band edge
: 2.4G SDR 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2369.971	3.65	29.10	0.00	29.12	61.87	74.00	-12.13	peak
2	2390.000	3.66	29.10	0.00	28.96	61.72	74.00	-12.28	peak
3 p	2422.500	3.68	29.01	0.00	81.27	113.96	74.00	39.96	peak



Test Mode: 06; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2422.5 Band edge
: 2.4G SDR 40M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2371.703	3.65	29.10	0.00	16.69	49.44	54.00	-4.56 Average
2	2390.000	3.66	29.10	0.00	16.28	49.04	54.00	-4.96 Average
3 q	2422.500	3.68	29.01	0.00	70.56	103.25	54.00	49.25 Average



Test Mode: 06; Polarity: Vertical; Modulation: OFDM; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 04028AT\04029AT
Mode : 2422.5 Band edge
: 2.4G SDR 40M

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2323.540	3.61	28.73	0.00	30.44	62.78	74.00	-11.22	Peak
2	2390.000	3.66	29.10	0.00	27.71	60.47	74.00	-13.53	Peak
3 p	2422.500	3.68	29.01	0.00	81.47	114.16	74.00	40.16	Peak




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000402803

Page: 34 of 217

Test Mode: 06; Polarity: Vertical; Modulation: OFDM; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 04028AT\04029AT
Mode : 2422.5 Band edge
: 2.4G SDR 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.238	3.66	29.10	0.00	16.68	49.44	54.00	-4.56	Average
2	2390.000	3.66	29.10	0.00	16.23	48.99	54.00	-5.01	Average
3 q	2422.500	3.68	29.01	0.00	77.57	110.26	54.00	56.26	Average




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 06; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2452.5 Band edge
: 2.4G SDR 40M

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2452.500	3.71	28.90	0.00	82.18	114.79	74.00	40.79	peak
2	2483.500	3.73	28.90	0.00	27.54	60.17	74.00	-13.83	peak
3	2491.707	3.73	28.90	0.00	28.86	61.49	74.00	-12.51	peak



Test Mode: 06; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2452.5 Band edge
: 2.4G SDR 40M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 2452.500	3.71	28.90	0.00	71.27	103.88	54.00	49.88	Average
2 2483.500	3.73	28.90	0.00	16.20	48.83	54.00	-5.17	Average
3 2498.793	3.74	28.90	0.00	16.70	49.34	54.00	-4.66	Average



Test Mode: 06; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
Condition: 3m VERTICAL
Job No : 04028AT\04029AT
Mode : 2452.5 Band edge
: 2.4G SDR 40M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	2452.500	3.71	28.90	0.00	88.63	121.24	74.00	47.24 Peak
2	2483.500	3.73	28.90	0.00	27.37	60.00	74.00	-14.00 Peak
3	2492.698	3.73	28.90	0.00	30.26	62.89	74.00	-11.11 Peak



Test Mode: 06; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
Condition: 3m VERTICAL
Job No : 04028AT\04029AT
Mode : 2452.5 Band edge
: 2.4G SDR 40M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 2452.500	3.71	28.90	0.00	77.55	110.16	54.00	56.16	Average
2 2483.500	3.73	28.90	0.00	16.55	49.18	54.00	-4.82	Average
3 2493.123	3.74	28.90	0.00	16.75	49.39	54.00	-4.61	Average



Test Mode: 07; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2432.5 Band edge
: 2.4G SDR 60M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2353.682	3.63	29.10	0.00	29.11	61.84	74.00	-12.16 peak
2	2390.000	3.66	29.10	0.00	29.07	61.83	74.00	-12.17 peak
3 p	2432.500	3.69	28.97	0.00	78.05	110.71	74.00	36.71 peak
4	2483.500	3.73	28.90	0.00	27.70	60.33	74.00	-13.67 peak
5	2489.549	3.73	28.90	0.00	29.02	61.65	74.00	-12.35 peak



Test Mode: 07; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2432.5 Band edge
: 2.4G SDR 60M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2346.252	3.63	29.05	0.00	16.68	49.36	54.00	-4.64	Average
2	2390.000	3.66	29.10	0.00	16.18	48.94	54.00	-5.06	Average
3 q	2432.500	3.69	28.97	0.00	66.46	99.12	54.00	45.12	Average
4	2483.500	3.73	28.90	0.00	16.25	48.88	54.00	-5.12	Average
5	2492.108	3.73	28.90	0.00	16.73	49.36	54.00	-4.64	Average



Test Mode: 07; Polarity: Vertical; Modulation: OFDM; Channel: Low



Site : chamber
 Condition: 3m VERTICAL
 Job No : 04028AT\04029AT
 Mode : 2432.5 Band edge
 : 2.4G SDR 60M


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2354.054	3.63	29.10	0.00	28.89	61.62	74.00	-12.38	peak
2	2390.000	3.66	29.10	0.00	26.28	59.04	74.00	-14.96	peak
3 p	2432.500	3.69	28.97	0.00	78.09	110.75	74.00	36.75	Peak
4	2483.500	3.73	28.90	0.00	26.89	59.52	74.00	-14.48	Peak
5	2491.911	3.73	28.90	0.00	28.84	61.47	74.00	-12.53	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 07; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
Condition: 3m VERTICAL
Job No : 04028AT\04029AT
Mode : 2432.5 Band edge
: 2.4G SDR 60M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2376.489	3.65	29.10	0.00	16.61	49.36	54.00	-4.64	Average
2	2390.000	3.66	29.10	0.00	16.20	48.96	54.00	-5.04	Average
3 q	2432.500	3.69	28.97	0.00	72.59	105.25	54.00	51.25	Average
4	2483.500	3.73	28.90	0.00	16.32	48.95	54.00	-5.05	Average
5	2484.241	3.73	28.90	0.00	16.87	49.50	54.00	-4.50	Average



Test Mode: 07; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2442.5 Band edge
: 2.4G SDR 60M

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2442.500	3.70	28.93	0.00	78.41	111.04	74.00	37.04	peak
2	2483.500	3.73	28.90	0.00	27.68	60.31	74.00	-13.69	peak
3	2495.065	3.74	28.90	0.00	29.37	62.01	74.00	-11.99	peak



Test Mode: 07; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2442.5 Band edge
: 2.4G SDR 60M

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q	2442.500	3.70	28.93	0.00	66.79	99.42	54.00	45.42	Average
2	2483.500	3.73	28.90	0.00	16.41	49.04	54.00	-4.96	Average
3	2496.226	3.74	28.90	0.00	16.96	49.60	54.00	-4.40	Average



Test Mode: 07; Polarity: Vertical; Modulation: OFDM; Channel: High




Site : chamber
Condition: 3m VERTICAL
Job No : 04028AT\04029AT
Mode : 2442.5 Band edge
: 2.4G SDR 60M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p 2442.500		3.70	28.93	0.00	84.46	117.09	74.00	43.09 Peak
2 2483.500		3.73	28.90	0.00	27.84	60.47	74.00	-13.53 Peak
3 2494.292		3.74	28.90	0.00	30.11	62.75	74.00	-11.25 Peak



Test Mode: 07; Polarity: Vertical; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 04028AT\04029AT
Mode : 2442.5 Band edge
: 2.4G SDR 60M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2442.500	3.70	28.93	0.00	72.81	105.44	54.00	51.44 Average
2	2483.500	3.73	28.90	0.00	16.27	48.90	54.00	-5.10 Average
3	2490.527	3.73	28.90	0.00	16.74	49.37	54.00	-4.63 Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.2 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5

Measurement Distance: 10m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.6 °C

Humidity: 50.5 % RH


Atmospheric Pressure: 1020 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	04	TX mode (2.4G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	05	TX mode (2.4G SDR_20MHz)_Keep the EUT in transmitting mode
Pre-scan	06	TX mode (2.4G SDR_40MHz)_Keep the EUT in transmitting mode
Pre-scan	07	TX mode (2.4G SDR_60MHz)_Keep the EUT in transmitting mode



7.2.3 Test Setup Diagram




7.2.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

Test Mode: 05; Polarity: Horizontal




Condition: 10m HORIZONTAL
Job No. : 04028AT/04029AT
Test Mode: 05

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	44.431	40.59	17.50	0.51	32.50	26.10	29.50	-3.40	QP
2	52.575	37.51	18.21	0.55	32.49	23.78	29.50	-5.72	QP
3 pp	149.486	44.90	17.72	0.95	32.50	31.07	33.00	-1.93	QP
4	157.559	41.85	17.84	0.98	32.50	28.17	33.00	-4.83	QP
5	176.888	42.04	16.33	1.06	32.50	26.93	33.00	-6.07	QP
6	857.025	34.18	26.99	2.58	31.97	31.78	35.60	-3.82	QP



Test Mode: 05; Polarity: Vertical



Condition: 10m VERTICAL
Job No. : 04028AT/04029AT
Test Mode: 05

	Read	Ant	Cable	Preamp		Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	37.416	39.05	16.69	0.46	32.50	23.70	29.50	-5.80 QP
2	52.575	37.32	18.21	0.55	32.49	23.59	29.50	-5.91 QP
3	104.170	45.62	13.78	0.77	32.50	27.67	33.00	-5.33 QP
4 pp	117.360	45.26	15.21	0.82	32.50	28.79	33.00	-4.21 QP
5	173.205	40.45	16.74	1.04	32.50	25.73	33.00	-7.27 QP
6	845.088	31.92	26.80	2.56	32.02	29.26	35.60	-6.34 QP



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000402803

Page: 51 of 217

The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L₃: Level @ 3m distance. Unit: uV/m;

L₁₀: Level @ 10m distance. Unit: uV/m;

D₃: 3m distance. Unit: m

D₁₀: 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 3m (uV/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
44.431	26.10	20.18	67.28	36.56	40	-3.44	H
52.575	23.78	15.45	51.51	34.24	40	-5.76	H
149.486	31.07	35.77	119.23	41.53	43.5	-1.97	H
157.559	28.17	25.62	85.38	38.63	43.5	-4.87	H
176.888	26.93	22.21	74.03	37.39	43.5	-6.11	H
857.025	31.78	38.82	129.38	42.24	46	-3.76	H
37.416	23.70	15.31	51.04	34.16	40	-5.84	V
52.575	23.59	15.12	50.39	34.05	40	-5.95	V
104.170	27.67	24.18	80.61	38.13	43.5	-5.37	V
117.360	28.79	27.51	91.70	39.25	43.5	-4.25	V
173.205	25.73	19.34	64.47	36.19	43.5	-7.31	V
845.088	29.26	29.04	96.80	39.72	46	-6.28	V



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.3 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 56.3 % RH

Atmospheric Pressure: 1020 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	04	TX mode (2.4G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	05	TX mode (2.4G SDR_20MHz)_Keep the EUT in transmitting mode
Pre-scan	06	TX mode (2.4G SDR_40MHz)_Keep the EUT in transmitting mode
Pre-scan	07	TX mode (2.4G SDR_60MHz)_Keep the EUT in transmitting mode

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:


1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
- 5:For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle<98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 05; Polarity: Horizontal; Modulation: OFDM; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2412.5 RSE TX
: 2.4G SDR

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1574.265	4.73	26.90	54.80	57.19	34.02	74.00	-39.98	peak
2	4354.454	8.06	34.44	54.26	53.67	41.91	74.00	-32.09	peak
3	4825.000	8.01	34.40	54.22	51.86	40.05	74.00	-33.95	peak
4	6564.209	9.19	35.44	53.16	52.94	44.41	74.00	-29.59	peak
5	7237.500	9.29	35.70	53.18	51.75	43.56	74.00	-30.44	peak
6 p	9650.000	11.38	37.50	53.34	51.16	46.70	74.00	-27.30	peak



Test Mode: 05; Polarity: Vertical; Modulation: OFDM; Channel: Low




Site : chamber
Condition: 3m VERTICAL
Job No : 04028AT\04029AT
Mode : 2412.5 RSE TX
: 2.4G SDR

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1597.181	4.78	26.81	54.80	56.65	33.44	74.00	-40.56	peak
2	4367.058	8.04	34.54	54.26	54.79	43.11	74.00	-30.89	peak
3	4825.000	8.01	34.40	54.22	53.74	41.93	74.00	-32.07	peak
4	5847.517	9.45	34.40	53.26	54.36	44.95	74.00	-29.05	peak
5	7237.500	9.29	35.70	53.18	52.46	44.27	74.00	-29.73	peak
6 p	9650.000	11.38	37.50	53.34	53.61	49.15	74.00	-24.85	peak



Test Mode: 05; Polarity: Horizontal; Modulation: OFDM; Channel: middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2437.5 RSE TX
: 2.4G SDR

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1606.441	4.80	26.74	54.81	56.63	33.36	74.00	-40.64	peak
2	4367.058	8.04	34.54	54.26	53.78	42.10	74.00	-31.90	peak
3	4875.000	8.03	34.60	54.21	51.83	40.25	74.00	-33.75	peak
4	6470.026	9.16	35.54	53.15	52.14	43.69	74.00	-30.31	peak
5	7312.500	9.21	35.70	53.17	52.47	44.21	74.00	-29.79	peak
6 p	9750.000	11.32	37.40	53.30	52.46	47.88	74.00	-26.12	peak



Test Mode: 05; Polarity: Vertical; Modulation: OFDM; Channel: middle




Site : chamber
Condition: 3m VERTICAL
Job No : 04028AT\04029AT
Mode : 2437.5 RSE TX
: 2.4G SDR

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1597.181	4.78	26.81	54.80	56.07	32.86	74.00	-41.14	peak
2	4181.768	8.30	33.80	54.28	54.95	42.77	74.00	-31.23	peak
3	4875.000	8.03	34.60	54.21	52.74	41.16	74.00	-32.84	peak
4	6934.778	9.48	35.74	53.19	53.77	45.80	74.00	-28.20	peak
5	7312.500	9.21	35.70	53.17	52.55	44.29	74.00	-29.71	peak
6 p	9750.000	11.32	37.40	53.30	51.68	47.10	74.00	-26.90	peak



Test Mode: 05; Polarity: Horizontal; Modulation: OFDM; Channel: High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04028AT\04029AT
Mode : 2462.5 RSE TX
: 2.4G SDR

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1490.142	4.57	26.52	54.77	57.04	33.36	74.00	-40.64	peak
2	4392.376	8.00	34.74	54.26	53.54	42.02	74.00	-31.98	peak
3	4925.000	8.05	34.65	54.21	52.89	41.38	74.00	-32.62	peak
4	6995.172	9.53	35.71	53.20	52.98	45.02	74.00	-28.98	peak
5	7387.500	9.14	35.78	53.16	51.92	43.68	74.00	-30.32	peak
6 p	9850.000	11.27	37.20	53.26	51.26	46.47	74.00	-27.53	peak



Test Mode: 05; Polarity: Vertical; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 04028AT\04029AT
Mode : 2462.5 RSE TX
: 2.4G SDR

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1503.119	4.58	26.81	54.78	56.73	33.34	74.00	-40.66	peak
2	4015.929	8.54	32.84	54.30	55.64	42.72	74.00	-31.28	peak
3	4925.000	8.05	34.65	54.21	52.72	41.21	74.00	-32.79	peak
4	5439.885	9.16	34.68	53.69	54.10	44.25	74.00	-29.75	peak
5	7387.500	9.14	35.78	53.16	52.42	44.18	74.00	-29.82	peak
6 p	9850.000	11.27	37.20	53.26	51.00	46.21	74.00	-27.79	peak



7.4 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 50.2 % RH

Atmospheric Pressure: 1020 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode (2.4G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	05	TX mode (2.4G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	06	TX mode (2.4G SDR_40MHz)_Keep the EUT in transmitting mode
Final test	07	TX mode (2.4G SDR_60MHz)_Keep the EUT in transmitting mode

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



7.5 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)

Test Method: ANSI C63.10 (2013) Section 11.8.1

Limit:

≥500 kHz

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 50.2 % RH

Atmospheric Pressure: 1020 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode (2.4G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	05	TX mode (2.4G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	06	TX mode (2.4G SDR_40MHz)_Keep the EUT in transmitting mode
Final test	07	TX mode (2.4G SDR_60MHz)_Keep the EUT in transmitting mode

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.6 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 50.2 % RH

Atmospheric Pressure: 1020 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode (2.4G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	05	TX mode (2.4G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	06	TX mode (2.4G SDR_40MHz)_Keep the EUT in transmitting mode
Final test	07	TX mode (2.4G SDR_60MHz)_Keep the EUT in transmitting mode

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.7 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 50.2 % RH

Atmospheric Pressure: 1020 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode (2.4G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	05	TX mode (2.4G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	06	TX mode (2.4G SDR_40MHz)_Keep the EUT in transmitting mode
Final test	07	TX mode (2.4G SDR_60MHz)_Keep the EUT in transmitting mode

7.7.3 Test Setup Diagram



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000402803

Page: 65 of 217

7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.8 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 50.2 % RH

Atmospheric Pressure: 1020 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode (2.4G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	05	TX mode (2.4G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	06	TX mode (2.4G SDR_40MHz)_Keep the EUT in transmitting mode
Final test	07	TX mode (2.4G SDR_60MHz)_Keep the EUT in transmitting mode

7.8.3 Test Setup Diagram



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen) EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000402803

Page: 67 of 217

7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

8 Test Setup Photo

Refer to Setup Photo for SZCR2410004028AT

9 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for SZCR2410004028AT

10 Appendix

For ANT0&1:

1. Duty Cycle


1.1 Test Result

1.1.1 Ant0


Ant0							
Mode	Tx Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
10M	MIMO	2407.5	100.000	100.000	100.00	0.00	0.00
		2437.5	100.000	100.000	100.00	0.00	0.00
		2467.5	100.000	100.000	100.00	0.00	0.00
20M	MIMO	2412.5	100.000	100.000	100.00	0.00	0.00
		2437.5	100.000	100.000	100.00	0.00	0.00
		2462.5	100.000	100.000	100.00	0.00	0.00
40M	MIMO	2422.5	100.000	100.000	100.00	0.00	0.00
		2437.5	100.000	100.000	100.00	0.00	0.00
		2452.5	100.000	100.000	100.00	0.00	0.00
60M	MIMO	2432.5	100.000	100.000	100.00	0.00	0.00
		2437.5	100.000	100.000	100.00	0.00	0.00
		2442.5	100.000	100.000	100.00	0.00	0.00

1.2 Test Graph


1.2.1 Ant0




10M_HCH_2467.5MHz_Ant0_NTNV




20M_LCH_2412.5MHz_Ant0_NTNV




20M_MCH_2437.5MHz_Ant0_NTNV




20M_HCH_2462.5MHz_Ant0_NTNV




40M_LCH_2422.5MHz_Ant0_NTNV




40M_MCH_2437.5MHz_Ant0_NTNV




40M_HCH_2452.5MHz_Ant0_NTNV




60M_LCH_2432.5MHz_Ant0_NTNV



60M_MCH_2437.5MHz_Ant0_NTNV



60M_HCH_2442.5MHz_Ant0_NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW


Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
10M	MIMO	2407.5	0	9.129	/	Pass
		2437.5	0	9.105	/	Pass
		2467.5	0	9.076	/	Pass
20M	MIMO	2412.5	0	17.923	/	Pass
		2437.5	0	17.876	/	Pass
		2462.5	0	17.833	/	Pass
40M	MIMO	2422.5	0	31.488	/	Pass
		2437.5	0	31.181	/	Pass
		2452.5	0	32.353	/	Pass
60M	MIMO	2432.5	0	51.475	/	Pass
		2437.5	0	51.332	/	Pass
		2442.5	0	51.498	/	Pass

2.1.2 6dB BW


Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
10M	MIMO	2407.5	0	8.987	≥ 0.5	Pass
		2437.5	0	8.983	≥ 0.5	Pass
		2467.5	0	9.001	≥ 0.5	Pass
20M	MIMO	2412.5	0	17.899	≥ 0.5	Pass
		2437.5	0	17.748	≥ 0.5	Pass
		2462.5	0	17.753	≥ 0.5	Pass
40M	MIMO	2422.5	0	22.723	≥ 0.5	Pass
		2437.5	0	22.715	≥ 0.5	Pass
		2452.5	0	24.324	≥ 0.5	Pass
60M	MIMO	2432.5	0	39.216	≥ 0.5	Pass
		2437.5	0	39.832	≥ 0.5	Pass
		2442.5	0	39.948	≥ 0.5	Pass

2.2 Test Graph


2.2.1 OBW




10M_HCH_2467.5MHz_Ant0_NTNV




20M_LCH_2412.5MHz_Ant0_NTNV



20M_MCH_2437.5MHz_Ant0_NTNV



20M_HCH_2462.5MHz_Ant0_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


40M_LCH_2422.5MHz_Ant0_NTNV




40M_MCH_2437.5MHz_Ant0_NTNV




40M_HCH_2452.5MHz_Ant0_NTNV




60M_LCH_2432.5MHz_Ant0_NTNV



60M_MCH_2437.5MHz_Ant0_NTNV



60M_HCH_2442.5MHz_Ant0_NTNV





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000402803

Page: 83 of 217

2.2.2 6dB BW


10M_LCH_2407.5MHz_Ant0_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com




10M_MCH_2437.5MHz_Ant0_NTNV




10M_HCH_2467.5MHz_Ant0_NTNV




20M_LCH_2412.5MHz_Ant0_NTNV




20M_MCH_2437.5MHz_Ant0_NTNV




20M_HCH_2462.5MHz_Ant0_NTNV



40M_LCH_2422.5MHz_Ant0_NTNV



40M_MCH_2437.5MHz_Ant0_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

40M_HCH_2452.5MHz_Ant0_NTNV



60M_LCH_2432.5MHz_Ant0_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen) Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

60M_MCH_2437.5MHz_Ant0_NTNV



60M_HCH_2442.5MHz_Ant0_NTNV



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Average Conducted Output Power (dBm)				Verdict
			ANT0	ANT1	MIMO	Limit	
10M	MIMO	2407.5	23.64	22.99	26.34	<=30	Pass
		2437.5	23.91	24.44	27.19	<=30	Pass
		2467.5	24.14	23.81	26.99	<=30	Pass
20M	MIMO	2412.5	23.50	22.50	26.04	<=30	Pass
		2437.5	23.77	24.31	27.06	<=30	Pass
		2462.5	24.55	23.38	27.01	<=30	Pass
40M	MIMO	2422.5	23.66	22.90	26.31	<=30	Pass
		2437.5	23.61	24.18	26.91	<=30	Pass
		2452.5	25.08	22.80	27.10	<=30	Pass
60M	MIMO	2432.5	21.48	21.66	24.58	<=30	Pass
		2437.5	21.45	21.78	24.63	<=30	Pass
		2442.5	21.54	21.49	24.53	<=30	Pass

4. Maximum Power Spectral Density


4.1 Test Result

4.1.1 PSD


Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm/3kHz)				Verdict
			ANT0	ANT1	MIMO	Limit	
10M	MIMO	2407.5	6.55	-1.77	6.85	<=8	Pass
		2437.5	7.53	-0.38	7.77	<=8	Pass
		2467.5	2.16	0.16	4.29	<=8	Pass
20M	MIMO	2412.5	-3.37	-1.86	0.46	<=8	Pass
		2437.5	-3.42	0.47	1.12	<=8	Pass
		2462.5	-2.54	0.28	0.93	<=8	Pass
40M	MIMO	2422.5	-2.64	0.41	2.16	<=8	Pass
		2437.5	-3.32	-3.12	-0.21	<=8	Pass
		2452.5	-3.52	-4.99	-1.49	<=8	Pass
60M	MIMO	2432.5	-8.48	-3.86	-3.03	<=8	Pass
		2437.5	-3.64	-8.67	-2.67	<=8	Pass
		2442.5	-5.17	-2.60	-0.69	<=8	Pass

4.2 Test Graph


4.2.1 PSD




10M_LCH_2407.5MHz_MIMO_NTNV




10M_MCH_2437.5MHz_Ant0_NTNV




10M_MCH_2437.5MHz_Ant1_NTNV




10M_MCH_2437.5MHz_MIMO_NTNV



10M_HCH_2467.5MHz_Ant0_NTNV



10M_HCH_2467.5MHz_Ant1_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen EMC Laboratory)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

10M_HCH_2467.5MHz_MIMO_NTNV



20M_LCH_2412.5MHz_Ant0_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen) EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

20M_LCH_2412.5MHz_Ant1_NTNV



20M_LCH_2412.5MHz_MIMO_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


20M_MCH_2437.5MHz_Ant0_NTNV



20M_MCH_2437.5MHz_Ant1_NTNV



20M_MCH_2437.5MHz_MIMO_NTNV



20M_HCH_2462.5MHz_Ant0_NTNV

