

Report File No.: STROR-07-075 Page : 1 of 50

TEST REPORT

OF

FCC Part 15 Subpart B&C §15.247

FCC ID : SS4BM150R

Equipment Under Test : PDA

Model Name : BM-150R

Serial No. : N/A

Applicant : Bluebird Soft, Inc.

Manufacturer : Bluebird Soft, Inc.

Date of Test(s) : $2007-08-10 \sim 2007-09-27$

Date of Issue : 2007-10-19

In the configuration tested, the EUT complied with the standards specified above.

Tested By:	2	Date	2007-10-19	
	Geoffrey Do	_		
Approved By	man	Date	2007-10-19	
	Denny Ham	<u> </u>		



Report File No.: STROR-07-075 Page : 2 of 50

INDEX

TABLE OF CONTENTS	Page
1. General Information	3
2. Conducted Power Line Test	7
3. Spurious Emission, Band Edge and Restricted Band Test	12
4. 20dB Bandwidth	21
5. Maximum Peak Output Power	24
6. Hopping Channel Separation	27
7. Number of Hopping Frequency	29
8. Time of Occupancy(Dwell Time)	32
9. Power Spectral Density	39
10. Antenna Requirement	42
Appendix A-1. Photo of Spurious Emission Test	
Appendix A -2. Photos of Conducted Power Line Test	
Appendix B. Photos of the EUT	



Report File No.: STROR-07-075 Page : 3 of 50

1. General Information

1.1. Testing Laboratory

SGS Testing Korea Co., Ltd.

Wireless Div. 2FL, 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea 435-040

www.electrolab.kr.sgs.com

Telephone : 82-31-428-5700 FAX : 82-31-427-2371

1.2. Details of Applicant

Applicant : Bluebird Soft, Inc.

Address : 558-5, Sinsa-dong, Kangnam-gu, Seoul, Korea

Contact Person : In-Gu Kim
Phone No. : 82-2-541-4002
Fax No. : 82-2-548-0870

1.3. Description of EUT

Kind of Product	PDA
Model Name	BM-150R
Serial Number	N/A
Power Supply	DC 3.7 V
Frequency Range	824.2 MHz ~ 848.8 MHz(GSM 850), 1850.2 MHz ~ 1909.8 MHz(GSM 1900) 2412 MHz ~ 2462 MHz(11b/g), 2402 MHz ~ 2480 MHz(Bluetooth) 88.1 MHz ~ 107.9 MHz(FM Transmitter)
Modulation Technique	DSSS(11b), OFDM(11g), FHSS(Bluetooth), GMSK, 8-PSK, FM
Frequency Generation	11 CH(11b/g), 79 CH(Bluetooth), 125(GSM 850), 300(GSM 1900) 199 CH(FM Transmitter)
Number of Channels	-20 °C ~ 55 °C
Operating Conditions	Fixed Type(11b/g, Bluetooth), Inverted F Type(GSM), Pannel ANT(FM Transmitter)
Antenna Type	-3.93 dBi(WLAN), -1.93 dBi(Bluetooth), -6.07 dBi(GSM 900), 1.02 dBi(GSM 1900)

1.4. Details of modification

-N/A



Report File No.: STROR-07-075 Page : 4 of 50

1.5. Information about the FHSS characteristics:

1.5.1. Pseudorandom Frequency Hopping Sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency.

Consecutive hops correspond to different RF hop frequencies. The nominal hop rate is 1600 hops/s.

1.5.2. Equal Hopping Frequency Use

All Bluetooth units participating in the piconet are time and hop-synchronized to the channel.

1.5.3. System Receiver Input Bandwidth

Each channel bandwidth is 1MHz



Report File No.: STROR-07-075 Page : 5 of 50

1.6. Test Equipment List

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Signal Generator	Agilent	E4438C	May 2008
Spectrum Analyzer	Agilent	E4440A	May 2008
Spectrum Analyzer	H.P.	8565E	Dec. 2007
Amplifier	H.P.	OPT H64	July 2008
Preamplifier	Agilent	8449B	May 2008
Attenuator	Agilent	8494B	May 2008
Two-Line V-Network	Rohde & Schwarz	NNB 41	Sep. 2008
Test Receiver	Rohde & Schwarz	ESVS10	April 2008
Ultra-Broadband Antenna	Rohde & Schwarz		Sep. 2008
Horn Antenna	Electro-Metrics	RGA-60	Dec. 2007
Anechoic Chamber	SY Corporation	L x W x H 6.5 x 3.6 x 3.6	Aug. 2008



Report File No.: STROR-07-075 Page : 6 of 50

1.6. Summary of Test Results

The EUT has been tested according to the following specifications:


APPLIED STANDARD:FCC Part15, Subpart B & Subpart C							
Standard Section	Test Item	Result					
15.107(a)	AC Power Conducted Emission	Complied					
15.205(a) 15.209(a) 15.247(d)	Spurious Emission, Band Edge and Restricted Bands	Complied					
15.247(a)(1)	20 dB Bandwidth	Complied					
15.247(b)(1)	Maximum Peak Output Power	Complied					
15.247(a)(1)	Frequency Separation	Complied					
15.247(a)(1)(iii)	Number of Hopping Frequency	Complied					
15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Complied					
15.247(e)	Power Spectral Density	Complied					



Report File No.: STROR-07-075 Page : 7 of 50

2. Conducted Power Line Test

2.1. Test Setup



2.2. Limit

According to §15.107(a) for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network(LISN).

Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

Enaguanay of Emissian (MHz)	Conducted limit (dBµV)				
Frequency of Emission (MHz)	Qausi-peak	Average			
0.15 – 0.50	66-56*	56-46*			
0.50 - 5.00	56	46			
5.00 – 30.0	60	50			

^{*} Decreases with the logarithm of the frequency.



Report File No.: STROR-07-075 Page : 8 of 50

2.3. Test Procedures

The test procedure is performed in a $6.5m \times 3.6m \times 3.6m$ (L×W×H) shielded room. The EUT along with its peripherals were placed on a $1.0m(W) \times 1.5m(L)$ and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.

The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.



Report File No.: STROR-07-075 Page : 9 of 50

2.4. Test Results

The following table shows the highest levels of conducted emissions on both phase of Hot and Neutral line.

Ambient temperature : 23 $^{\circ}$ C Relative humidity : 42 $^{\circ}$

Frequency range : 0.15 MHz - 30 MHz

Measured Bandwidth : 9 kHz

FREQ.	LEVEL	(dBuV)	LINE	LIMIT(dBuV)	MARG	IN(dB)
(MHz)	Q-Peak	Average	LINE	Q-Peak	Average	Q-Peak	Average
0.28	16.50	13.20	N	60.82	50.82	44.32	37.62
6.65	34.70	22.30	N	60.00	50.00	25.30	27.70
6.95	40.00	30.30	N	60.00	50.00	20.00	19.70
7.53	38.00	24.80	N	60.00	50.00	22.00	25.20
13.03	35.90	24.30	N	60.00	50.00	24.10	25.740
27.13	24.20	18.30	N	60.00	50.00	35.80	31.70
0.15	32.70	14.70	Н	66.00	56.00	33.30	41.30
0.27	21.90	13.00	Н	61.12	51.12	39.22	38.12
0.45	24.70	14.50	Н	56.93	46.93	32.23	32.43
6.66	44.80	33.10	Н	60.00	50.00	15.20	16.90
7.00	37.00	27.10	Н	60.00	50.00	23.00	22.90
7.26	39.60	26.40	Н	60.00	50.00	20.40	23.60

Note;


Line (H) : Hot Line (N) : Neutral



Report File No.: STROR-07-075 Page : 10 of 50

Plot of Conducted Power line


Test mode: (Hot)





Report File No.: STROR-07-075 Page : 11 of 50

Test mode: (Neutral)






Report File No.: STROR-07-075 Page : 12 of 50

3. Spurious Emission, Band Edge, and Restricted Band Test


3.1. Test Setup

3.1.1. Spurious Radiated Emissions

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to 24 GHz Emissions.





Report File No.: STROR-07-075 Page: 13 of 50

3.1.2. Spurious RF Conducted Emissions



3.2. Limit

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section §15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section §15.205(a), must also comply the radiated emission limits specified in section §15.205(c))

According to § 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance (Meters)	Field Strength (dBµV/m)	Field Strength (μV/m)
30 - 88	3	40.0	100
88 – 216	3	43.5	150
216 – 960	3	46.0	200
Above 960	3	54.0	500

According to §15.109(a), for an unintentional device, except for Class A digital devices, the field strength of radiated emission from unintentional radiators at a distance of 3 meters shall not exceed the above table.



Report File No.: STROR-07-075 Page: 14 of 50

3.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.4:2003

3.3.1. Test Procedures for Spurious Radiated Emissions

- 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
- 3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- 6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE;

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1 GHz.
- 2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz for Peak detection and frequency above 1 GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1 GHz.

3.3.2. Test Procedures for Spurious RF Conducted Emissions

- 1. The transmitter output was connected to the spectrum analyzer through an attenuator.
- 2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using RBW=100 kHz, VBW=100 kHz.



Report File No.: STROR-07-075 Page : 15 of 50

3.4. Test Results

Ambient temperature : 23 °C Relative humidity : 41%

3.4.1. Spurious Radiated Emission (30 MHz ~ 1000 MHz)

The frequency spectrum from 30 MHz to 1000 MHz was investigated. All emissions are not reported much lower than the prescribed limits.

Radiated Emissions		Ant	Correctio	Correction Factors		FCC Limit		
Frequency (MHz)	Reading (dBuV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+CL (dB)	Actual (dBuV/m)	Limit (dBuV/m)	Margin (dB)
54.25	58.00	P	V	6.02	-26.92	37.10	40.00	2.90
104.37	40.70	Р	Н	9.07	-26.31	23.46	43.50	20.04
144.78	45.50	P	V	7.86	-25.89	27.46	43.50	16.04
183.58	46.20	P	V	7.61	-25.60	28.21	43.50	15.29
235.32	39.70	Р	V	8.87	-25.11	23.47	46.00	22.53
Above 300								

Remark:

- 1. All spurious emission at channels are almost the same below 1 GHz, so that the channel was chosen at representative in final test.
- 2. "*" means the restricted band.
- 3. Actual = Reading + AF + (Amp Gain + CL)



Report File No.: STROR-07-075 Page: 16 of 50

3.4.2. Spurious Radiated Emission (Above 1000 MHz)

The frequency spectrum above 1000 MHz was investigated. All emissions are not reported much lower than the prescribed limits.

A. Low Channel (2402 MHz)

Radiated Emissions		Ant	Correction Factors		Total FCC Limi		imit	
Frequency (MHz)	Reading (dBuV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+CL (dB)	Actual (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2390.00*	43.17	P	Н	28.06	-28.19	43.04	54.00	10.96
4804.00	41.11	P	Н	32.90	-24.78	49.23	54.00	4.77
Above 5000	Not Detected							

B. Middle Channel (2441 MHz)

Radiated Emissions		Ant	Correction Factors		Total	FCC Limit		
Frequency (MHz)	Reading (dBuV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+CL (dB)	Actual (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4882.00	40.27	P	Н	32.93	-25.07	48.13	54.00	5.87
Above 5000	Not Detected							



Report File No.: STROR-07-075 Page: 17 of 50

C. High Channel (2480 MHz)

Radiated Emissions		Ant	Correction Factors		Total Limit		it	
Frequency (MHz)	Reading (dBuV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+CL (dB)	Actual (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.50*	38.35	P	Н	28.34	-28.14	38.55	54.00	15.45
4944.30	38.07	P	Н	32.96	-25.00	46.04	54.00	7.96
Above 5000	Not Detected							

Remarks;


- 1. "*" means the restricted band.
- 2. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental Frequency.
- 3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using peak/average detector mode.
- 4. Average test would be performed if the peak result were greater than the average limit.
- 5. Actual = Reading + AF + (Amp Gain + CL




Report File No.: STROR-07-075 Page: 18 of 50

3.4.3. Spurious RF Conducted Emissions: Plot of Spurious RF Conducted Emission

Low Channel









Report File No.: STROR-07-075 Page: 19 of 50

Middle Channel









Report File No.: STROR-07-075 Page : 20 of 50

High Channel








Report File No.: STROR-07-075 Page : 21 of 50

4. 20 dB Bandwidth Measurement

4.1. Test Setup



4.2. Limit

Limit: Not Applicable

4.3. Test Procedure

- 1. The 20dB band width was measured with a spectrum analyzer connected to RF antenna connector(conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency. The analyzer center frequency was set to the EUT carrier frequency, using the analyzer. Display Line and Marker Delta functions, the 20dB band width of the emission was determined.
- 2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using RBW=10 kHz, VBW=10 kHz, Span=2 MHz.



Report File No.: STROR-07-075 Page : 22 of 50

4.4. Test Results

Ambient temperature : 22 °C Relative humidity : 43 %

Channel	Channel Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2402	0.927
Middle	2441	0.827
High	2480	0.833

Low Channel





Report File No.: STROR-07-075 Page : 23 of 50

Middle Channel



High Channel






Report File No.: STROR-07-075 Page : 24 of 50

5. Maximum Peak Output Power Measurement

5.1. Test Setup



5.2. Limit

\$15.247(b)(3) For systems using digital modulation in the $902\sim928$ MHz, $2400\sim2483.5$ MHz, and $5725\sim5850$ MHz band: 1 Watt.

5.3. Test Procedure

- 1. The RF power output was measured with a Spectrum analyzer connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency, A spectrum analyzer was used to record the shape of the transmit signal.
- 2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using; Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = 1 MHz

 $VBW \ge RBW$

Sweep = auto

Detector function = peak

Trace = max hold



Report File No.: STROR-07-075 Page : 25 of 50

5.4. Test Results


Ambient temperature : 22 °C Relative humidity : 43 %

Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Margin (dB)
Low	2402	-3.86	30	33.86
Middle	2441	-2.83	30	32.83
High	2480	-2.07	30	32.07

NOTE:

- 1. Cable loss = 0.4 dB, Attenuator = 16 dB.
- 2. The results are calculated as the following equation :
 Peak Power Output = Peak Power Reading + Cable loss + Attenuator


Low Channel






Report File No.: STROR-07-075 Page : 26 of 50

Middle Channel



High Channel






Report File No.: STROR-07-075 Page : 27 of 50

6. Hopping Channel Separation

6.1. Test Setup



6.2. Limit

§15.247(a)(1) Frequency hopping system operating in 2400-2483.5MHz. Band may have hopping channel carrier frequencies that are separated by 25kHz or two-third of 20dB bandwidth of the hopping channel, whichever is is greater, provided the systems operate with an output power no greater than 125mW.

6.3. Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
- 3. By using the MaxHold function record the separation of adjacent channels.
- 4. Measure the frequency difference of these two adjacent channels by spectrum analyzer MARK function. And then plot the result on spectrum analyzer screen.
- 5. Repeat above procedures until all frequencies measured were complete.
- 6. Set center frequency of spectrum analyzer = middle of hopping channel.
- 7. Set the spectrum analyzer as RBW=100 kHz, VBW=100 kHz, Span=5 MHz and Sweep = auto.



Report File No.: STROR-07-075 Page : 28 of 50


6.4. Test Results

Ambient temperature : 22 °C Relative humidity : 43 %

Channel (Middle)	Adjacent Hopping Channel Separation (kHz)	Two-third of 20 dB Bandwidth (kHz)	Minimum Bandwidth
2441 MHz	1000	750	25 kHz

Note;

20 dB bandwidth measurement, the measured channel separation should be greater than two-third of 20dB bandwidth or Minimum bandwidth.






Report File No.: STROR-07-075 Page : 29 of 50

7. Number of Hopping Frequency

7.1. Test Setup



7.2. Limit

§15.247(a)(1)(iii) For frequency hopping system operating in the 2400-2483.5MHz bands shall use at least 15 hopping frequencies.

7.3. Test Procedure

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna the port to the Spectrum analyzer
- 3. Set spectrum analyzer Start=2400 MHz, Stop=2441.5 MHz, Sweep=auto and Start=2441.5 MHz, Stop= 2483.5 MHz, Sweep=auto.
- 4. Set the spectrum analyzer as RBW, VBW=510 kHz.
- 5. Max hold, view and count how many channel in the band.



Report File No.: STROR-07-075 Page : 30 of 50


7.4. Test Results


Ambient temperature : 22 °C Relative humidity : 43 %

Number of Hopping Frequency	Limit	Remark
79	>= 15	Refer to the attached plot.



Report File No.: STROR-07-075 Page : 31 of 50








Report File No.: STROR-07-075 Page : 32 of 50

8. TIME OF OCCUPANCY (DWELL TIME)

8.1. Test Set up



8.2. Limit

§15.247(a)(1)(iii) For frequency hopping system operating in the 2400-2483.5MHz band, the average time of occupancy on any frequency shall not be greater than 0.4 second within a 31.6 second period.

A period time=0.4(s)*79=31.6(s)

8.3. Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable.
- 3. Adjust the center frequency of spectrum analyzer on any frequency be measured and set spectrum analyzer to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- 4. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- 5. Repeat above procedures until all frequencies measured were complete.
- 6. The Bluetooth has 3 type of payload, DH1, DH3, DH5. The hopping rate is 1600 per second.



Report File No.: STROR-07-075 Page : 33 of 50

8.4. Test Results

Ambient temperature : 22 °C Relative humidity : 43 %

Time of occupancy on the TX channel in 31.6sec


= time domain slot length \times (hop rate \div number of hop per channel) \times 31.6

8.4.1. Packet Type: DH1

Frequency	Dwell Time (ms)	Time of occupancy on the Tx Channel in 31.6 sec (ms)	Limit for time of occupancy on the Tx Channel in 31.6 sec (ms)
2402 MHz	0.420	134.40	400
2441 MHz	0.419	134.08	400
2480 MHz	0.409	130.88	400

2402 MHz: 0.420(ms) × [$(1600 \div 2) \div 79$] ×31.6(s) = 134.40 (ms) 2441 MHz: 0.419(ms) × [$(1600 \div 2) \div 79$] ×31.6(s) = 134.08 (ms) 2480 MHz: 0.409(ms) × [$(1600 \div 2) \div 79$] ×31.6(s) = 130.88 (ms)


2402 MHz






Report File No.: STROR-07-075 Page : 34 of 50

2441 MHz



2480 MHz






Report File No.: STROR-07-075 Page : 35 of 50

8.4.2. Packet Type: DH3

Frequency	Dwell Time (ms)	Time of occupancy on the Tx Channel in 31.6 sec (ms)	Limit for time of occupancy on the Tx Channel in 31.6 sec (ms)
2402 MHz	1.677	268.32	400
2441 MHz	1.128	180.48	400
2480 MHz	1.134	181.44	400

2402 MHz: 1.677(ms) × [$(1600 \div 4) \div 79$] ×31.6(s) = 268.32 (ms) 2441 MHz: 1.128(ms) × [$(1600 \div 4) \div 79$] ×31.6(s) = 180.48 (ms) 2480 MHz: 1.134(ms) × [$(1600 \div 4) \div 79$] ×31.6(s) = 181.44 (ms)


2402 MHz






Report File No.: STROR-07-075 Page : 36 of 50

2441 MHz



2480 MHz






Report File No.: STROR-07-075 Page : 37 of 50

8.4.3. Packet Type: DH5

Frequency	Dwell Time (ms)	Time of occupancy on the Tx Channel in 31.6 sec (ms)	Limit for time of occupancy on the Tx Channel in 31.6 sec (ms)
2402 MHz	2.899	309.23	400
2441 MHz	2.881	307.31	400
2480 MHz	2.923	311.79	400

2402 MHz: $2.899 \text{ (ms)} \times [(1600 \div 6) \div 79] \times 31.6 \text{(s)} = 309.23 \text{ (ms)}$ 2441 MHz: $2.881 \text{ (ms)} \times [(1600 \div 6) \div 79] \times 31.6 \text{(s)} = 306.31 \text{ (ms)}$ 2480 MHz: $2.923 \text{ (ms)} \times [(1600 \div 6) \div 79] \times 31.6 \text{(s)} = 311.79 \text{ (ms)}$


2402 MHz






Report File No.: STROR-07-075 Page : 38 of 50

2441 MHz



2480 MHz






Report File No.: STROR-07-075 Page : 39 of 50

9. POWER SPECTRAL DENSITY MEASUREMENT

9.1. Test Setup



9.2. Limit

§15.247(e) For digitally modulated system, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

9.3. Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
- 3. By using the MaxHold function record the separation of adjacent channels.
- 4. Repeat above procedures until all frequencies measured were complete.
- 5. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using; RBW=3 kHz, VBW=10 kHz, Span=300 kHz and Sweep=100 s.




Report File No.: STROR-07-075 Page : 40 of 50

9.4. Test Results

Ambient temperature : 22 °C Relative humidity : 43 %

Frequency	Final RF Power Level in 3 kHz BW (dBm)	Maximum Limit (dBm)	Margin (dB)
2402 MHz	-14.77	8	22.77
2441 MHz	-13.16	8	21.16
2480 MHz	-12.76	8	20.76


2402 MHz






Report File No.: STROR-07-075 Page : 41 of 50

2441 MHz



2480 MHz





Report File No.: STROR-07-075 Page : 42 of 50

10. ANTENNA REQUIREMENT

10.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section §15.247 (b) if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the gain of the antenna exceeds 6dBi.


10.2. Antenna Connected Construction

Antenna used in this product is Fixed type (Chip antenna) gain of -1.93 dBi



Report File No.: STROR-07-075 Page : 43 of 50

Appendix A-1. Photo of Field Strength & Radiated Emission Test





Report File No.: STROR-07-075 Page : 44 of 50

Appendix A -2. Photos of Conducted Power Line Test







Report File No.: STROR-07-075 Page : 45 of 50

Appendix B. Photos of the EUT

Front View of EUT



Rear View of EUT





Report File No.: STROR-07-075 Page : 46 of 50

Right View of EUT



Left View of EUT






Report File No.: STROR-07-075 Page : 47 of 50

Inner of EUT




Top View of Main-board






Report File No.: STROR-07-075 Page : 48 of 50

Bottom View of Main-board




Top View of Keyboard






Report File No.: STROR-07-075 Page : 49 of 50

Bottom View of Keyboard



Top View of LCD





Report File No.: STROR-07-075 Page : 50 of 50

Bottom View of LCD

